



# RF EXPOSURE REPORT

**REPORT NO.:** SA970825L06

**MODEL NO.:** BHS-808

**ACCORDING:** FCC Guidelines for Human Exposure  
IEEE C95.1

**APPLICANT:** Iqua Ltd

**ADDRESS:** Kivenlahdentie 7, 02360 Espoo, Finland

**ISSUED BY:** Advance Data Technology Corporation

**LAB ADDRESS:** No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou Hsiang,  
Taipei Hsien 244, Taiwan, R.O.C.

**TEST LOCATION:** No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei  
Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.



No Evaluation required if power is below this threshold:

F(GHz)		mW
Low	2.402	24.58
High	2.480	

Maximum measured transmitter power:

Pout (dBm)	Pout (mW)	
Conducted Power	4.74	2.98
EIRP Power	2.59	1.82

**\*Note:** The antenna is chip antenna with -2.15dBi gain.

Threshold for no SAR evaluation is 24.58mW

Transmitter power is 1.82mW

Conclusion: No SAR evaluation required since Transmitter Pout is below FCC threshold