

FCC CERTIFICATION
On Behalf of
Eastern Times Technology Co., Ltd.

2.4G Wireless Optical Mouse
Model No.: DS-2116(2216-A)

FCC ID: TUV2116-A

Prepared for : Eastern Times Technology Co., Ltd.
Address : Building 5, Penghua Industry Park, Heping Rd.(W),
Longhua, Shenzhen, Guangdong, China

Prepared by : ACCURATE TECHNOLOGY CO. LTD
Address : F1, Bldg. A, Changyuan New Material Port, Keyuan Rd.
Science & Industry Park, Nanshan, Shenzhen, Guangdong
P.R. China

Tel: (0755) 26503290
Fax: (0755) 26503396

Report Number : ATE20081864
Date of Test : October 9-27, 2008
Date of Report : October 30, 2008

TABLE OF CONTENTS

Description	Page
Test Report Certification	
1. GENERAL INFORMATION	4
1.1. Description of Device (EUT).....	4
1.2. Description of Test Facility	4
1.3. Measurement Uncertainty	5
2. MEASURING DEVICE AND TEST EQUIPMENT	6
3. SUMMARY OF TEST RESULTS.....	7
4. FUNDAMENTAL AND HARMONICS RADIATED EMISSION MEASUREMENT	8
4.1. Block Diagram of Test Setup.....	8
4.2. The Emission Limit	9
4.3. Configuration of EUT on Measurement	9
4.4. Operating Condition of EUT	9
4.5. Test Procedure	10
4.6. The Field Strength of Radiation Emission Measurement Results	11
5. RADIATED EMISSION FOR FCC PART 15 SECTION 15.249(D).....	14
5.1. Block Diagram of Test Setup.....	14
5.2. The Emission Limit For Section 15.249(d)	15
5.3. EUT Configuration on Measurement	15
5.4. Operating Condition of EUT	15
5.5. Test Procedure	16
5.6. The Emission Measurement Result	17
6. BAND EDGES	20
6.1. The Requirement	20
6.2. EUT Configuration on Measurement	20
6.3. Operating Condition of EUT	20
6.4. Test Procedure	20
6.5. The Measurement Result	21
7. ANTENNA REQUIREMENT.....	23
7.1. The Requirement	23
7.2. Antenna Construction	23

APPENDIX I (TEST CURVES) (22 pages)

Test Report Certification

Applicant : Eastern Times Technology Co., Ltd.
Manufacturer : Eastern Times Technology Co., Ltd.
EUT Description : 2.4G Wireless Optical Mouse
(A) MODEL NO.: DS-2116(2216-A)
(B) SERIAL NO.: N/A
(C) POWER SUPPLY: 3.0V DC (“AAA” batteries 2×)

Measurement Procedure Used:

FCC Rules and Regulations Part 15 Subpart C Section 15.249: 2008 & ANSI C63.4: 2003

The device described above is tested by ACCURATE TECHNOLOGY CO. LTD to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C Section 15.249 limits. The measurement results are contained in this test report and ACCURATE TECHNOLOGY CO. LTD is assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC requirements.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of ACCURATE TECHNOLOGY CO. LTD.

Date of Test : October 9-27, 2008

Prepared by : 
(Engineer)

Approved & Authorized Signer : 
(Manager)

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

EUT	:	2.4G Wireless Optical Mouse
Model Number	:	DS-2116(2216-A)
Power Supply	:	3.0V DC (“AAA” batteries 2×)
Operate Frequency	:	2402.9-2478.1MHz
Channel Number	:	48
Applicant Address	:	Eastern Times Technology Co., Ltd. Building 5, Penghua Industry Park, Heping Rd.(W), Longhua, Shenzhen, Guangdong, China
Manufacturer Address	:	Eastern Times Technology Co., Ltd. Building 5, Penghua Industry Park, Heping Rd.(W), Longhua, Shenzhen, Guangdong, China
Date of sample received	:	October 7, 2008
Date of Test	:	October 9-27, 2008

1.2. Description of Test Facility

EMC Lab	:	Accredited by TUV Rheinland Shenzhen Listed by FCC The Registration Number is 752051 Listed by Industry Canada The Registration Number is 5077A-2 Accredited by China National Accreditation Committee for Laboratories The Certificate Registration Number is L3193
Name of Firm	:	ACCURATE TECHNOLOGY CO. LTD
Site Location	:	F1, Bldg. A, Changyuan New Material Port, Keyuan Rd. Science & Industry Park, Nanshan, Shenzhen, Guangdong P.R. China

1.3.Measurement Uncertainty

Conducted Emission Expanded Uncertainty = 2.23dB, k=2

Radiated emission expanded uncertainty
(9kHz-30MHz) = 3.08dB, k=2

Radiated emission expanded uncertainty
(30MHz-1000MHz) = 4.42dB, k=2

Radiated emission expanded uncertainty
(Above 1GHz) = 4.06dB, k=2

2. MEASURING DEVICE AND TEST EQUIPMENT

Table 1: List of Test and Measurement Equipment

Kind of equipment	Manufacturer	Type	S/N	Calibrated until
EMI Test Receiver	Rohde&Schwarz	ESCS30	100307	03.29.2009
EMI Test Receiver	Rohde&Schwarz	ESPI3	101526/003	03.29.2009
Spectrum Analyzer	Agilent	E7405A	MY45115511	03.29.2009
Pre-Amplifier	Rohde&Schwarz	CBLU118354 0-01	3791	03.31.2009
Loop Antenna	Schwarzbeck	FMZB1516	1516131	03.28.2009
Bilog Antenna	Schwarzbeck	VULB9163	9163-323	03.29.2009
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-655	12.20.2008
Horn Antenna	Schwarzbeck	BBHA9170	9170-359	10.09.2009
LISN	Rohde&Schwarz	ESH3-Z5	100305	03.29.2009
LISN	Schwarzbeck	NSLK8126	8126431	03.29.2009

3. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
Section 15.207	Conducted Emission	N/A
Section 15.249(d)	Radiated Emission	Compliant
Section 15.249(a)	The fundamental field strength and the harmonics	Compliant
Section 15.249(d)	Band Edge	Compliant

4. FUNDAMENTAL AND HARMONICS RADIATED EMISSION MEASUREMENT


4.1. Block Diagram of Test Setup

4.1.1. Block diagram of connection between the EUT and simulators



(EUT: 2.4G Wireless Optical Mouse)

4.1.2. Anechoic Chamber Test Setup Diagram



(EUT: 2.4G Wireless Optical Mouse)

4.2.The Emission Limit

4.2.1.For intentional radiators, According to section 15.249(a), Operation within the frequency band of 2.4 to 2.4835GHz, The fundamental field strength shall not exceed 94 dB μ V/m and the harmonics shall not exceed 54 dB μ V/m.

Fundamental Frequency	Field Strength of Fundamental (millivolts/meter)	Field Strength of harmonics (microvolts/meter)
902-928MHz	50	500
2400-2483.5MHz	50	500
5725-5875MHz	50	500
24.0-24.25GHz	250	2500

4.2.2.According to section 15.249(e), as shown in section 15.35(b), the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

4.3.Configuration of EUT on Measurement

The following equipment are installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

4.3.1. 2.4G Wireless Optical Mouse (EUT)

Model Number : DS-2116(2216-A)
 Serial Number : N/A
 Manufacturer : Eastern Times Technology Co., Ltd.

4.4.Operating Condition of EUT

4.4.1.Setup the EUT and simulator as shown as Section 4.1.

4.4.2.Turn on the power of all equipment.

4.4.3. Let the EUT work in TX modes measure it. The transmit frequency are 2402.9-2478.1MHz. We are select 2402.9MHz, 2439.7MHz, 2478.1MHz TX frequency to transmit.

4.5. Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.4: 2003 on radiated emission measurement.

The bandwidth of test receiver (R&S ESI26) is set at 1MHz.

4.6. The Field Strength of Radiation Emission Measurement Results

PASS.

Date of Test:	<u>October 9-27, 2008</u>	Temperature:	<u>25°C</u>
EUT:	<u>2.4G Wireless Optical Mouse</u>	Humidity:	<u>52%</u>
Model No.:	<u>DS-2116(2216-A)</u>	Power Supply:	<u>3.0V DC (“AAA” batteries 2×)</u>
Test Mode:	<u>TX 2402.9MHz</u>	Test Engineer:	<u>Joe</u>

Fundamental Radiated Emissions

Frequency (MHz)	Reading(dBμV/m)		Factor(dB) Corr.	Result(dBμV/m)		Limit(dBμV/m)		Margin(dB)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
2402.901	85.38	91.51	-7.45	77.93	84.06	94	114	-16.07	-29.94	Vertical
2402.901	89.26	95.60	-7.45	81.81	88.15	94	114	-12.19	-25.85	Horizontal

Harmonics Radiated Emissions

Frequency (MHz)	Reading(dBμV/m)		Factor(dB) Corr.	Result(dBμV/m)		Limit(dBμV/m)		Margin(dB)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
4805.804	48.61	55.21	-0.28	48.33	54.93	54	74	-5.67	-19.07	Vertical
4805.804	50.85	57.51	-0.28	50.57	57.23	54	74	-3.43	-16.77	Horizontal

The spectral diagrams in appendix I display the measurement of peak values.

Note:

1. The emission emitted by the EUT is too low to be measured except the emission listed above.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:

$$\text{Result} = \text{Reading} + \text{Corrected Factor}$$

$$\text{Where Corrected Factor} = \text{Antenna Factor} + \text{Cable Loss} + \text{High Pass Filter Loss} - \text{Amplifier Gain}$$

Date of Test:	<u>October 9-27, 2008</u>	Temperature:	<u>25°C</u>
EUT:	<u>2.4G Wireless Optical Mouse</u>	Humidity:	<u>52%</u>
Model No.:	<u>DS-2116(2216-A)</u>	Power Supply:	<u>3.0V DC (“AAA” batteries 2×)</u>
Test Mode:	<u>TX 2439.7MHz</u>	Test Engineer:	<u>Joe</u>

Fundamental Radiated Emissions

Frequency (MHz)	Reading(dBμV/m)		Factor(dB) Corr.	Result(dBμV/m)		Limit(dBμV/m)		Margin(dB)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
2439.702	84.44	90.75	-7.36	77.08	83.39	94	114	-16.92	-30.61	Vertical
2439.702	87.33	93.67	-7.36	79.97	86.31	94	114	-14.03	-27.69	Horizontal

Harmonics Radiated Emissions

Frequency (MHz)	Reading(dBμV/m)		Factor(dB) Corr.	Result(dBμV/m)		Limit(dBμV/m)		Margin(dB)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
4879.408	49.81	56.33	0.13	49.94	56.46	54	74	-4.06	-17.54	Vertical
4879.408	47.96	54.46	0.13	48.09	54.59	54	74	-5.91	-19.41	Horizontal

The spectral diagrams in appendix I display the measurement of peak values.

Note:

1. The emission emitted by the EUT is too low to be measured except the emission listed above.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:

$$\text{Result} = \text{Reading} + \text{Corrected Factor}$$

$$\text{Where Corrected Factor} = \text{Antenna Factor} + \text{Cable Loss} + \text{High Pass Filter Loss} - \text{Amplifier Gain}$$

Date of Test:	<u>October 9-27, 2008</u>	Temperature:	<u>25°C</u>
EUT:	<u>2.4G Wireless Optical Mouse</u>	Humidity:	<u>52%</u>
Model No.:	<u>DS-2116(2216-A)</u>	Power Supply:	<u>3.0V DC (“AAA” batteries 2×)</u>
Test Mode:	<u>TX 2478.1MHz</u>	Test Engineer:	<u>Joe</u>

Fundamental Radiated Emissions

Frequency (MHz)	Reading(dBμV/m)		Factor(dB) Corr.	Result(dBμV/m)		Limit(dBμV/m)		Margin(dB)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
2478.103	85.91	92.44	-7.37	78.54	85.07	94	114	-15.46	-28.93	Vertical
2478.103	87.97	94.46	-7.37	80.60	87.09	94	114	-13.40	-26.91	Horizontal

Harmonics Radiated Emissions

Frequency (MHz)	Reading(dBμV/m)		Factor(dB) Corr.	Result(dBμV/m)		Limit(dBμV/m)		Margin(dB)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
4956.209	49.03	55.44	0.51	49.54	55.95	54	74	-4.46	-18.05	Vertical
4956.209	49.62	55.59	0.51	50.13	56.10	54	74	-3.87	-17.90	Horizontal

The spectral diagrams in appendix I display the measurement of peak values.

Note:

1. The emission emitted by the EUT is too low to be measured except the emission listed above.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:

$$\text{Result} = \text{Reading} + \text{Corrected Factor}$$

$$\text{Where Corrected Factor} = \text{Antenna Factor} + \text{Cable Loss} + \text{High Pass Filter Loss} - \text{Amplifier Gain}$$

5. RADIATED EMISSION FOR FCC PART 15 SECTION 15.249(D)


5.1. Block Diagram of Test Setup

5.1.1. Block diagram of connection between the EUT and simulators



(EUT: 2.4G Wireless Optical Mouse)

5.1.2. Anechoic Chamber Test Setup Diagram



(EUT: 2.4G Wireless Optical Mouse)

5.2.The Emission Limit For Section 15.249(d)

5.2.1.Emission radiated outside of the specified frequency bands, except for harmonics, shall be comply with the general radiated emission limits in Section 15.209.

Radiation Emission Measurement Limits According to Section 15.209

Frequency (MHz)	Limit		The final measurement in band 9-90kHz, 110-490kHz and above 1000MHz is performed with Average detector. Except those frequency bands mention above, the final measurement for frequencies below 1000MHz is performed with Quasi Peak detector.
	Field Strength of Quasi-peak Value (microvolts/m)	Field Strength of Quasi-peak Value (dB μ V/m)	
30 - 88	100	40	
88 - 216	150	43.5	
216 - 960	200	46	
Above 960	500	54	

5.3.EUT Configuration on Measurement

The following equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

5.3.1. 2.4G Wireless Optical Mouse (EUT)

Model Number : DS-2116(2216-A)
 Serial Number : N/A
 Manufacturer : Eastern Times Technology Co., Ltd.

5.4.Operating Condition of EUT

5.4.1.Setup the EUT and simulator as shown as Section 5.1.

5.4.2.Turn on the power of all equipment.

5.4.3. Let the EUT work in TX modes measure it. The transmit frequency are 2402.9-2478.1MHz. We are select 2402.9MHz, 2439.7MHz, 2478.1MHz TX frequency to transmit.

5.5. Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.4: 2003 on radiated emission measurement.

The bandwidth of test receiver (R&S ESI26) is set at 120KHz in 30-1000MHz. and set at 1MHz in above 1000MHz.

The frequency range from 30MHz to 25000MHz is checked.

The final measurement in band 9-90kHz, 110-490kHz and above 1000MHz is performed with Average detector. Except those frequency bands mention above, the final measurement for frequencies below 1000MHz is performed with Quasi Peak detector.

5.6.The Emission Measurement Result

PASS.

Date of Test:	<u>October 9-27, 2008</u>	Temperature:	<u>25°C</u>
EUT:	<u>2.4G Wireless Optical Mouse</u>	Humidity:	<u>52%</u>
Model No.:	<u>DS-2116(2216-A)</u>	Power Supply:	<u>3.0V DC (“AAA” batteries 2×)</u>
Test Mode:	<u>TX 2402.9MHz</u>	Test Engineer:	<u>Joe</u>

Frequency (MHz)	Reading (dBμV/m)	Factor(dB) Corr.	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
	QP		QP	QP	QP	
-	-	-	-	-	-	Vertical
-	-	-	-	-	-	Horizontal

The spectral diagrams in appendix I display the measurement of peak values.

Note:

1. Remark “- “ means that the emission level is too low to be measured.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:

$$\text{Result} = \text{Reading} + \text{Corrected Factor}$$

$$\text{Where Corrected Factor} = \text{Antenna Factor} + \text{Cable Loss} + \text{High Pass Filter Loss} - \text{Amplifier Gain}$$

Date of Test: October 9-27, 2008
 EUT: 2.4G Wireless Optical Mouse
 Model No.: DS-2116(2216-A)
 Test Mode: TX 2439.7MHz

Temperature: 25°C
 Humidity: 52%
 Power Supply: 3.0V DC (“AAA” batteries 2×)
 Test Engineer: Joe

Frequency (MHz)	Reading (dBμV/m)	Factor(dB) Corr.	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
	QP		QP	QP	QP	
-	-	-	-	-	-	Vertical
-	-	-	-	-	-	Horizontal

The spectral diagrams in appendix I display the measurement of peak values.

Note:

1. Remark “-” means that the emission level is too low to be measured.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:

$$\text{Result} = \text{Reading} + \text{Corrected Factor}$$

$$\text{Where Corrected Factor} = \text{Antenna Factor} + \text{Cable Loss} + \text{High Pass Filter Loss} - \text{Amplifier Gain}$$

Date of Test:	<u>October 9-27, 2008</u>	Temperature:	<u>25°C</u>
EUT:	<u>2.4G Wireless Optical Mouse</u>	Humidity:	<u>52%</u>
Model No.:	<u>DS-2116(2216-A)</u>	Power Supply:	<u>3.0V DC (“AAA” batteries 2×)</u>
Test Mode:	<u>TX 2478.1MHz</u>	Test Engineer:	<u>Joe</u>

Frequency (MHz)	Reading (dBμV/m)	Factor(dB) Corr.	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Polarization
	QP		QP	QP	QP	
-	-	-	-	-	-	Vertical
-	-	-	-	-	-	Horizontal

The spectral diagrams in appendix I display the measurement of peak values.

Note:

1. Remark “-” means that the emission level is too low to be measured.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:

$$\text{Result} = \text{Reading} + \text{Corrected Factor}$$

$$\text{Where Corrected Factor} = \text{Antenna Factor} + \text{Cable Loss} + \text{High Pass Filter Loss} - \text{Amplifier Gain}$$

6. BAND EDGES

6.1. The Requirement

6.1.1. Band Edge from 2400MHz to 2483.5MHz. Emission radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.

6.2. EUT Configuration on Measurement

The following equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

6.2.1. 2.4G Wireless Optical Mouse (EUT)

Model Number : DS-2116(2216-A)
Serial Number : N/A
Manufacturer : Eastern Times Technology Co., Ltd.

6.3. Operating Condition of EUT

6.3.1. Setup the EUT and simulator as shown as Section 4.1.

6.3.2. Turn on the power of all equipment.

6.3.3. Let the EUT work in TX modes measure it. The transmit frequency are 2402.9-2478.1MHz. We are select 2402.9MHz, 2478.1MHz TX frequency to transmit.

6.4. Test Procedure

1. The EUT is placed on a turntable, which is 0.8m above the ground plane and worked at highest radiated power.
2. The turntable was rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
RBW=1MHz, VBW=1MHz

6.5.The Measurement Result

Pass.

Date of Test:	<u>October 27, 2008</u>	Temperature:	<u>25°C</u>
EUT:	<u>2.4G Wireless Laser Mouse</u>	Humidity:	<u>52%</u>
Model No.:	<u>DS-2116(2216-A)</u>	Power Supply:	<u>3.0V DC (“AAA” batteries 2×)</u>
Test Mode:	<u>TX 2402.9MHz</u>	Test Engineer:	<u>Joe</u>

Frequency (MHz)	Reading(dBμV/m)		Factor(dB) Corr.	Result(dBμV/m)		Limit(dBμV/m)		Margin(dB)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
2400.000	46.78	53.33	-7.46	39.32	45.87	54	74	-14.68	-28.13	Vertical
2400.000	50.69	57.20	-7.46	43.23	49.74	54	74	-10.77	-24.26	Horizontal

The spectral diagrams in appendix I display the measurement of peak values.

Note:

1. The emission emitted by the EUT is too low to be measured except the emission listed above.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:

Result = Reading + Corrected Factor

Where Corrected Factor = Antenna Factor + Cable Loss + High Pass Filter Loss – Amplifier Gain

Date of Test:	<u>October 27, 2008</u>	Temperature:	<u>25°C</u>
EUT:	<u>2.4G Wireless Laser Mouse</u>	Humidity:	<u>52%</u>
Model No.:	<u>DS-2116(2216-A)</u>	Power Supply:	<u>3.0V DC (“AAA” batteries 2×)</u>
Test Mode:	<u>TX 2478.1MHz</u>	Test Engineer:	<u>Joe</u>

Frequency (MHz)	Reading(dBμV/m)		Factor(dB) Corr.	Result(dBμV/m)		Limit(dBμV/m)		Margin(dB)		Polarization
	AV	PEAK		AV	PEAK	AV	PEAK	AV	PEAK	
2483.500	46.78	52.92	-7.37	39.41	45.55	54	74	-14.59	-28.45	Vertical
2483.500	45.26	51.98	-7.37	37.89	44.61	54	74	-16.11	-29.39	Horizontal

The spectral diagrams in appendix I display the measurement of peak values.

Note:

1. The emission emitted by the EUT is too low to be measured except the emission listed above.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:

$$\text{Result} = \text{Reading} + \text{Corrected Factor}$$

$$\text{Where Corrected Factor} = \text{Antenna Factor} + \text{Cable Loss} + \text{High Pass Filter Loss} - \text{Amplifier Gain}$$


7. ANTENNA REQUIREMENT

7.1.The Requirement

7.1.1. According to Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

7.2.Antenna Construction

The antenna is PCB Layout antenna, no consideration of replacement.



Antenna

APPENDIX I (Test Curves)




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: RTTE #547	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: DC 3V
Test item: Radiation Test	Date: 08/10/13/
Temp.(C)/Hum.(%) 25 C / 52 %	Time: 9/22/05
EUT: 2.4G Wireless Optical Mouse	Engineer Signature: Joe
Mode: TX 2402.9MHz	Distance: 3m
Model: DS-2116(2216-A)	
Manufacturer: Eastern Times	

Note: Sample No.:3083624 Report No.:ATE20081864



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: RTTE #548	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: DC 3V
Test item: Radiation Test	Date: 08/10/13/
Temp.(C)/Hum.(%) 25 C / 52 %	Time: 9/26/04
EUT: 2.4G Wireless Optical Mouse	Engineer Signature: Joe
Mode: TX 2402.9MHz	Distance: 3m
Model: DS-2116(2216-A)	
Manufacturer: Eastern Times	

Note: Sample No.:3083624 Report No.:ATE20081864



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: RTTE #575	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: DC 3V
Test item: Radiation Test	Date: 08/10/15/
Temp.(C)/Hum.(%) 25 C / 52 %	Time: 11/35/42
EUT: 2.4G Wireless Optical Mouse	Engineer Signature: Joe
Mode: TX 2402.9MHz	Distance: 3m
Model: DS-2116(2216-A)	
Manufacturer: Eastern Times	

Note: Sample No.:3083624 Report No.:ATE20081864



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2402.901	95.60	-7.45	88.15	114.00	-25.85	peak	
2	2402.901	89.26	-7.45	81.81	94.00	-12.19	AVG	
3	4805.804	57.51	-0.28	57.23	74.00	-16.77	peak	
4	4805.804	50.85	-0.28	50.57	54.00	-3.43	AVG	




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: RTTE #574	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: DC 3V
Test item: Radiation Test	Date: 08/10/15/
Temp.(C)/Hum.(%) 25 C / 52 %	Time: 11/25/47
EUT: 2.4G Wireless Optical Mouse	Engineer Signature: Joe
Mode: TX 2402.9MHz	Distance: 3m
Model: DS-2116(2216-A)	
Manufacturer: Eastern Times	

Note: Sample No.:3083624 Report No.:ATE20081864



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2402.901	91.51	-7.45	84.06	114.00	-29.94	peak	
2	2402.901	85.38	-7.45	77.93	94.00	-16.07	AVG	
3	4805.804	55.21	-0.28	54.93	74.00	-19.07	peak	
4	4805.804	48.61	-0.28	48.33	54.00	-5.67	AVG	




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: RTTE #566	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: DC 3V
Test item: Radiation Test	Date: 2008/10/13
Temp.(C)/Hum.(%) 25 C / 52 %	Time: 14:06:51
EUT: 2.4G Wireless Optical Mouse	Engineer Signature: Joe
Mode: TX 2402.9MHz	Distance: 3m
Model: DS-2116(2216-A)	
Manufacturer: Eastern Times	

Note: Sample No.:3083624 Report No.:ATE20081864



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
-----	-------------	------------------	-------------	-----------------	----------------	-------------	----------	--------




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: RTTE #567	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: DC 3V
Test item: Radiation Test	Date: 2008/10/13
Temp.(C)/Hum.(%) 25 C / 52 %	Time: 14:10:46
EUT: 2.4G Wireless Optical Mouse	Engineer Signature: Joe
Mode: TX 2402.9MHz	Distance: 3m
Model: DS-2116(2216-A)	
Manufacturer: Eastern Times	

Note: Sample No.:3083624 Report No.:ATE20081864



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
-----	-------------	------------------	-------------	-----------------	----------------	-------------	----------	--------




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: RTTE #550	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: DC 3V
Test item: Radiation Test	Date: 08/10/13/
Temp.(C)/Hum.(%) 25 C / 52 %	Time: 9/30/41
EUT: 2.4G Wireless Optical Mouse	Engineer Signature: Joe
Mode: TX 2439.7MHz	Distance: 3m
Model: DS-2116(2216-A)	
Manufacturer: Eastern Times	

Note: Sample No.:3083624 Report No.:ATE20081864



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
-----	-------------	------------------	-------------	-----------------	----------------	-------------	----------	--------




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: RTTE #549	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: DC 3V
Test item: Radiation Test	Date: 08/10/13/
Temp.(C)/Hum.(%) 25 C / 52 %	Time: 9/28/56
EUT: 2.4G Wireless Optical Mouse	Engineer Signature: Joe
Mode: TX 2439.7MHz	Distance: 3m
Model: DS-2116(2216-A)	
Manufacturer: Eastern Times	

Note: Sample No.:3083624 Report No.:ATE20081864



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: RTTE #576	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: DC 3V
Test item: Radiation Test	Date: 08/10/15/
Temp.(C)/Hum.(%) 25 C / 52 %	Time: 11/39/22
EUT: 2.4G Wireless Optical Mouse	Engineer Signature: Joe
Mode: TX 2439.7MHz	Distance: 3m
Model: DS-2116(2216-A)	
Manufacturer: Eastern Times	

Note: Sample No.:3083624 Report No.:ATE20081864



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2439.702	93.67	-7.36	86.31	114.00	-27.69	peak	
2	2439.702	87.33	-7.36	79.97	94.00	-14.03	AVG	
3	4879.408	54.46	0.13	54.59	74.00	-19.41	peak	
4	4879.408	47.96	0.13	48.09	54.00	-5.91	AVG	




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: RTTE #577	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: DC 3V
Test item: Radiation Test	Date: 08/10/15/
Temp.(C)/Hum.(%) 25 C / 52 %	Time: 11/42/44
EUT: 2.4G Wireless Optical Mouse	Engineer Signature: Joe
Mode: TX 2439.7MHz	Distance: 3m
Model: DS-2116(2216-A)	
Manufacturer: Eastern Times	

Note: Sample No.:3083624 Report No.:ATE20081864



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2439.702	90.75	-7.36	83.39	114.00	-30.61	peak	
2	2439.702	84.44	-7.36	77.08	94.00	-16.92	AVG	
3	4879.408	56.33	0.13	56.46	74.00	-17.54	peak	
4	4879.408	49.81	0.13	49.94	54.00	-4.06	AVG	




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: RTTE #569	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: DC 3V
Test item: Radiation Test	Date: 2008/10/13
Temp.(C)/Hum.(%) 25 C / 52 %	Time: 14:19:47
EUT: 2.4G Wireless Optical Mouse	Engineer Signature: Joe
Mode: TX 2439.7MHz	Distance: 3m
Model: DS-2116(2216-A)	
Manufacturer: Eastern Times	

Note: Sample No.:3083624 Report No.:ATE20081864



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
-----	-------------	------------------	-------------	-----------------	----------------	-------------	----------	--------




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: RTTE #568	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: DC 3V
Test item: Radiation Test	Date: 2008/10/13
Temp.(C)/Hum.(%) 25 C / 52 %	Time: 14:15:41
EUT: 2.4G Wireless Optical Mouse	Engineer Signature: Joe
Mode: TX 2439.7MHz	Distance: 3m
Model: DS-2116(2216-A)	
Manufacturer: Eastern Times	

Note: Sample No.:3083624 Report No.:ATE20081864



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
-----	-------------	------------------	-------------	-----------------	----------------	-------------	----------	--------




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: RTTE #551	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: DC 3V
Test item: Radiation Test	Date: 08/10/13/
Temp.(C)/Hum.(%) 25 C / 52 %	Time: 9/33/20
EUT: 2.4G Wireless Optical Mouse	Engineer Signature: Joe
Mode: TX 2478.1MHz	Distance: 3m
Model: DS-2116(2216-A)	
Manufacturer: Eastern Times	

Note: Sample No.:3083624 Report No.:ATE20081864



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
-----	-------------	------------------	-------------	-----------------	----------------	-------------	----------	--------




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: RTTE #552	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: DC 3V
Test item: Radiation Test	Date: 08/10/13/
Temp.(C)/Hum.(%) 25 C / 52 %	Time: 9/34/49
EUT: 2.4G Wireless Optical Mouse	Engineer Signature: Joe
Mode: TX 2478.1MHz	Distance: 3m
Model: DS-2116(2216-A)	
Manufacturer: Eastern Times	

Note: Sample No.:3083624 Report No.:ATE20081864



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
-----	-------------	------------------	-------------	-----------------	----------------	-------------	----------	--------




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: RTTE #579	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: DC 3V
Test item: Radiation Test	Date: 08/10/15/
Temp.(C)/Hum.(%) 25 C / 52 %	Time: 11/46/27
EUT: 2.4G Wireless Optical Mouse	Engineer Signature: Joe
Mode: TX 2478.1MHz	Distance: 3m
Model: DS-2116(2216-A)	
Manufacturer: Eastern Times	

Note: Sample No.:3083624 Report No.:ATE20081864



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2478.103	94.46	-7.37	87.09	114.00	-26.91	peak	
2	2478.103	87.97	-7.37	80.60	94.00	-13.40	AVG	
3	4956.209	55.59	0.51	56.10	74.00	-17.90	peak	
4	4956.209	49.62	0.51	50.13	54.00	-3.87	AVG	




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: RTTE #578	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: DC 3V
Test item: Radiation Test	Date: 08/10/15/
Temp.(C)/Hum.(%) 25 C / 52 %	Time: 11/44/22
EUT: 2.4G Wireless Optical Mouse	Engineer Signature: Joe
Mode: TX 2478.1MHz	Distance: 3m
Model: DS-2116(2216-A)	
Manufacturer: Eastern Times	

Note: Sample No.:3083624 Report No.:ATE20081864



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2478.103	92.44	-7.37	85.07	114.00	-28.93	peak	
2	2478.103	85.91	-7.37	78.54	94.00	-15.46	AVG	
3	4956.209	55.44	0.51	55.95	74.00	-18.05	peak	
4	4956.209	49.03	0.51	49.54	54.00	-4.46	AVG	




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: RTTE #570	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: DC 3V
Test item: Radiation Test	Date: 2008/10/13
Temp.(C)/Hum.(%) 25 C / 52 %	Time: 14:26:34
EUT: 2.4G Wireless Optical Mouse	Engineer Signature: Joe
Mode: TX 2478.1MHz	Distance: 3m
Model: DS-2116(2216-A)	
Manufacturer: Eastern Times	

Note: Sample No.:3083624 Report No.:ATE20081864



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
-----	-------------	------------------	-------------	-----------------	----------------	-------------	----------	--------




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: RTTE #571	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: DC 3V
Test item: Radiation Test	Date: 2008/10/13
Temp.(C)/Hum.(%) 25 C / 52 %	Time: 14:30:57
EUT: 2.4G Wireless Optical Mouse	Engineer Signature: Joe
Mode: TX 2478.1MHz	Distance: 3m
Model: DS-2116(2216-A)	
Manufacturer: Eastern Times	

Note: Sample No.:3083624 Report No.:ATE20081864



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
-----	-------------	------------------	-------------	-----------------	----------------	-------------	----------	--------




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: RTTE #697	Polarization: Horizontal
Standard: FCC Part 15 PEAK 2.4G	Power Source: DC 3V
Test item: Radiation Test	Date: 08/10/27/
Temp.(C)/Hum.(%) 25 C / 52 %	Time: 11/11/34
EUT: 2.4G Wireless Optical Mouse	Engineer Signature: Joe
Mode: TX 2402.9MHz	Distance: 3m
Model: DS-2116(2216-A)	
Manufacturer: Eastern Times	

Note: Sample No.:3083624 Report No.:ATE20081864



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2400.000	57.20	-7.46	49.74	74.00	-24.26	peak	
2	2400.000	50.69	-7.46	43.23	54.00	-10.77	AVG	




ACCURATE TECHNOLOGY CO., LTD.
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: RTTE #698	Polarization: Vertical
Standard: FCC Part 15 PEAK 2.4G	Power Source: DC 3V
Test item: Radiation Test	Date: 08/10/27/
Temp.(C)/Hum.(%) 25 C / 52 %	Time: 11/14/47
EUT: 2.4G Wireless Optical Mouse	Engineer Signature: Joe
Mode: TX 2402.9MHz	Distance: 3m
Model: DS-2116(2216-A)	
Manufacturer: Eastern Times	

Note: Sample No.:3083624 Report No.:ATE20081864



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2400.000	53.33	-7.46	45.87	74.00	-28.13	peak	
2	2400.000	46.78	-7.46	39.32	54.00	-14.68	AVG	




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: RTTE #696	Polarization: Horizontal
Standard: FCC Part 15 PEAK 2.4G	Power Source: DC 3V
Test item: Radiation Test	Date: 08/10/27/
Temp.(C)/Hum.(%) 25 C / 52 %	Time: 11/05/48
EUT: 2.4G Wireless Optical Mouse	Engineer Signature: Joe
Mode: TX 2478.1MHz	Distance: 3m
Model: DS-2116(2216-A)	
Manufacturer: Eastern Times	

Note: Sample No.:3083624 Report No.:ATE20081864



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2483.530	51.98	-7.37	44.61	74.00	-29.39	peak	
2	2483.530	45.26	-7.37	37.89	54.00	-16.11	AVG	




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: RTTE #695	Polarization: Vertical
Standard: FCC Part 15 PEAK 2.4G	Power Source: DC 3V
Test item: Radiation Test	Date: 08/10/27/
Temp.(C)/Hum.(%) 25 C / 52 %	Time: 10/59/00
EUT: 2.4G Wireless Optical Mouse	Engineer Signature: Joe
Mode: TX 2478.1MHz	Distance: 3m
Model: DS-2116(2216-A)	
Manufacturer: Eastern Times	

Note: Sample No.:3083624 Report No.:ATE20081864



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2483.500	52.92	-7.37	45.55	74.00	-28.45	peak	
2	2483.500	46.78	-7.37	39.41	54.00	-14.59	AVG	