WARRANTY

1. Warranty Period: 12 months from purchase.
2. If the products have any qualified problems, Please Contact Us.
   We Will Solve the Problem for you ASAP.

PACKAGE CONTENT

Mechanical Keyboard x1
User Manual x1

FCC Warning Statement

Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment. This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications.However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:
--Reorient or relocate the receiving antenna.
--Increase the separation between the equipment and receiver.
--Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
• Consult the dealer or an experienced radio/TV technician for help.This device complies with part 15 of the FCC rules. Operation is subject to the following two conditions (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Made in China

USER MANUAL

E-YOOSO®

Z-99

Wired+2.4G+BT three-modes RGB Mechanical Keyboard

PRODUCTS FEATURE

Ergonomic design.
High quality button switches.

LED LIGHTING MODES

Support 15 backlit modes switching.

Adjust the backlight brightness. When it is adjusted to the extreme position, 1、A indicators will flash 3 times and are adjustable in 5 levels.

Adjust the backlight streamer speed. When it is adjusted to the extreme position, 1、A indicators will flash 3 times and are adjustable in 5 levels.

Light switching: Red, Green, Blue, Yellow, Pink, Cyan, White, RGB (supporting for 11 types).

LIGHT EFFECT ADJUSTMENT ON BOTH SIDES

Cycle switching of side lamp effect: Flow, Neon, Static, Pulse, Off.

Switch side lamp speed.

Switch the color of side lamp (Available for Pulse and Static).

WHITE LIGHT TEST FUNCTION

Use + to test full-key white light and press again to restore the original light effect. It is for testing purposes only.

CUSTOM KEY SETTINGS OF LIGHTING MODES

+ = Light recording

Press FN+Backspace to enter light self-defining mode. Light off、Press FN+Backspace again to enter recording state、1、A indicators will flicker continuously (and it will be off after recording is over). Press the same key continuously to the designated color, and go on setting other keys to form the needed backlight pattern. After the setting is completed, press FN+Backspace again to save it. When a light macro is played, press FN+Backspace, the light of the defined key will be normally on for indication (FN key cannot self define the light).

WIRED /2.4 G/ BLUETOOTH SWITCHING

1. Switch through the keyboard front power switch and FN key composite function. When the power switch is OFF, it is in Wired mode (the M indicator light is green). When the power switch is ON, press the FN key along with the 1/ 2/@/3# key to switch to Bluetooth mode (the M indicator light is blue/cyan/pink). Or press the FN key along with the +@ key to switch to 2.4G mode (the M indicator light is yellow).

BLUETOOTH2.4G PAIRING MODE

1、Bluetooth: Press and hold FN + (1/@/2/@/3#) for 3 seconds to enter the corresponding channel pairing mode of Bluetooth, the M indicator light will flash in blue/cyan/pink, prompting to enter pairing status; the indicator light is always on after the pairing is successful.
2、2.4G: Press and hold FN + (4$) for 3 seconds to enter 2.4G pairing mode, the M indicator light will flash yellow, then connect the receiver to the computer, and the M indicator light will be solid yellow after the pairing is successful.

MODE STATUS BT/2.4G SELECTION

Press FN + (1/@/2/@/3#/4$) to switch the BT1/BT2/BT3/2.4G state of the keyboard respectively.

SUPPORT WIN LOCK FUNCTION

+ to lock the WIN key, repeak to unlock.

MAC/WIN FUNCTION KEY SWITCH

Switching to the Win system: Press the FN key along with the W key, 1、A indicator lights flash 3 times. Switching to the MAC system: Press the FN key along with the A key, 1、A indicator lights flash 3 times.

MAC multimedia functions are as follows:

- Reduce screen brightness /FN+F1=F1
- Increase screen brightness /FN+F2=F2
- Multitask window (mission control)/FN+F3=F3
- Activate Siri, Release Delay Time: 200MS/FN+F4=F4
- App exposé function (Ctrl + Down Arrow)/FN+F5=F5
- Search(Command+space) /FN+F6=F6
- Prev Track/FN+F7=F7
- Stop/FN+F8=F8
- Next Track/FN+F9=F9
- Mute/FN+F10=F10
- Volume –/FN+F11=F11
- Volume +/FN+F12=F12

WIN multimedia functions are as follows:

- + Computer
- + Home
- + Calculator
- + Media Play
- + Prev Track
- + Next Track
- + Play/Pause
- + Stop
- + Mute
- + Volume –
- + Volume +
- + E-mail

FN COMPOSITE FUNCTION

+ = HOME + = END + = Scr.Lk

LOW VOLTAGE INDICATOR

1. When the battery voltage is lower than 3.3V, the light effect will be turned off, and the red light of the battery indicator will flash slowly when a button is pressed.
2. When the battery voltage is equal to or lower than 3.0V, the keyboard function is turned off.

AUTOMATIC POWER SAVING

The backlight turns off and enters the standby state if the keyboard is not operated for 3 minute, and enters the sleep state if there is no operation in 30 minutes.

CHARGING INDICATOR

If you connect the TYPE-C USB cable to the computer or the charging adaptor, the keyboard will be in the charging state, the battery indicator light will be solid red when charging, and will be green when fully charged.

BATTERY LEVEL INDICATOR

Use RGB indicator lines flashing when the battery is lower than 20%, purple when the battery is lower than 40%, blue when the battery is lower than 60%, cyan when the battery is lower than 80%, green when fully charged. The red light is always on when the battery is being charged, and turns green when it is fully charged.

POWER DISPLAY FUNCTION

+ To turn off the entire backlight, and the letter area 1~0 displays the power level. When the battery is low, the button 1~3# will display in red, the button 11~0 will display green when the battery is above 3#, and the default light effect will be restored after releasing it.

RECOVER TO THE DEFAULT SETTING

+ Long press for 3 seconds to recover to the default setting.

SYSTEM SUPPORT

Windows/Mac.

BATTERY SAFETY GUIDELINES

DO NOT replace the battery with a different model
DO NOT use this product if the battery shows signs of damage including, but not limited to burning, deformation, leakage, or the smell of electrolytic material.
DO NOT touch the battery if material is leaking and seek immediate medical attention if any material comes into contact with your skin or eyes
DO NOT expose the battery to liquid, heat sources, electricity (outside of the product itself), or other non-standard operating condition.
DO NOT remove the battery except for proper disposal and recycling as required by local laws and regulations.
DO NOT impact, bend, alter, dissemble, or otherwise damage the battery as the contents are volatile, hazardous, and can be harmful

CAUTION:
Failing to follow all safety guidelines may result product damage, explosion, fire, and/or electric shock

为满足中国电子电气产品有害物质限制相关的法律和其它要求，对本产品中有害物质、按部件分类，声明如下。

部件名称	有害物质					
	铅（Pb）	汞（Hg）	镉（Cd）	六价铬（Cr(VI)）	多溴联苯（PBB）	多溴二苯醚（PBDE）
印刷电路板组件	X	O	O	O	O	O
外壳及部件	O	O	O	O	O	O

本表格依据SJ/T 11364的规定编制。

O：表示该有害物质在该部件的某一均质材料中的含量均在GB/T 26572规定的限量要求以下。

X：表示该有害物质至少在该部件的某一均质材料中的含量超出GB/T 26572规定的限量要求。

表中标记"X"的部件，皆因全球技术发展水平限制而无法实现有害物质的替代。

印刷电路板组件：包括印刷电路板及其零部件，电子元器件等根据产品型号不同，应折衷设定的产品可能不含有可以上所有部件。

在中华人民共和国境内销售的电子电气产品必须标识此标志，标志内的数字代表在正常使用环境下对产品所存储使用寿命。

《废弃电器电子产品回收处理管理条例》

倡导环保和低碳的消费体验，建议拥有该产品的客户在不需要此产品时，应按中国家庭废弃电器电子产品回收处理相关法律法规，将其交给当地具有回收处理资质的厂商进行回收处理，降低资源消费，保护地球自然环境。

使用手册

元素®

Z-99

有线+2.4G+蓝牙三模RGB机械键盘

产品特色

人体工程学原理的外形设计理念。
高品质按键开关，手感舒适。

LED灯光模式

+ 对15种灯光模式进行切换。

+ 调节背光亮度,键盘数据线拔下,1、A指示灯熄灭,5级可调。

+ 调节背光流光速度，调整后指示灯闪烁3次，5级可调。

+ 背光颜色调节 红 绿 蓝 黄 粉 青 白 RGB (支持11种灯光模式进行切换)。

两边侧灯光效调节

+ 循环切换侧灯灯效:流光、霓虹、常亮、呼吸、灭。

+ 切换侧灯速度。

+ 切换侧灯颜色(呼吸、常亮有效)。

白光测试功能

使用 + 键出全键白光，再按一次恢复原有灯效，仅供测试功能用。

灯光录制

+ = 灯光录制

按FN+宏按键(BACKSPACE)进入灯光自定义模式，键位灯全亮。再按一次FN+宏按键退入录制状态。
1、A指示灯呼吸灯亮（录制调整指示）。在按按把一按键来指定宏。再键盘设置其他按键，键位将调整为两光系统，光效保留后，再按FN+宏按键进行存储即可，按键灯灭后即，按FN+宏按键，已定义按键灯会常亮指示灯N键不熄灭灯光。

有线/2.4G蓝牙切换

1、按以键盘右键单独开关及FN键复合功能进行切换。电源开关在OFF时为有线模式 M指示灯为绿色。电源开关在ON状态，FN+ 1/ 2@/ 3# 为蓝牙模式M指示灯为蓝色模式为蓝色闪灯1次。FN+ 4$ 为2.4G模式 M指示灯为黄色。

星球2.4G配对

1、蓝牙 FN+ 1/ 2@/ 3# 长按3秒进入蓝牙的相应通道配对模式，M指示灯相应的蓝色/青色/紫红色会闪烁，表示进入配对状态，配对成功后指示灯常亮。
2.2.4G FN+ 4$ 长按3秒进入2.4G对码模式，M指示灯黄色闪烁，然后将接收器连接到电脑，对码成功后M指示灯黄色常亮。

BT/2.4G选择

1、按按 FN+ 1/ 2@/ 3# / 4$ 分别切换键盘到BT1 / BT2 / BT3 / 2.4G状态。

支持锁WIN功能

+ 锁可以锁定WIN键的功能，重复解锁 (注意MAC系统下面无锁Win键功能)。

系统支持

支持Windows/Mac系。

MAC/WIN功能按键对照

默认 WIN 系统,按 FN+W 键按一下切换到 WIN 系统，1、A 指示灯闪烁 3 下,FN+A 切换到 MAC，1、A 指示灯闪烁 3 下。

MAC 多媒体功能键下：

- 屏幕亮度调高/FN+F1=F1
- 屏幕亮度加/FN+F2=F2
- 多任务窗口(mission control)/FN+F3=F3
- 呼出Siri, 延时200MS/FN+F4=F4
- app exposé功能 (control+下箭头)/FN+F5=F5
- 搜索(Command+space) /FN+F6=F6
- 上一曲/FN+F7=F7
- 暂停/FN+F8=F8
- 下一曲/FN+F9=F9
- 静音/FN+F10=F10
- 音量减/FN+F11=F11
- 音量加/FN+F12=F12

WIN 多媒体功能键下：

- + 我的电脑
- + 主页
- + 计算器
- + 播放器
- + 上一曲
- + 下一曲
- + 播放/暂停
- + 停止播放
- + 静音
- + 音量减
- + 音量加
- + 邮件

FN复合键

+ = HOME + = END + = Scr.Lk

低电压指示

1. 电池电压低于3.3V，亮终灯效，在有按键动作时灯红灯慢闪。
2. 电池电压等于或低于3.0V，键盘功能失效，在有按键动作时灯红灯慢闪。

自动省电

键盘未操作3分钟后背光灯熄灭进入待机状态，键盘未操作30分钟键盘进入休眠状态。

充电指示

插上TYPE-C USB线后连到电脑或外电源适配器，键盘将处于充电状态，充电时电池指示灯红色常亮，充满时显示绿色。

电池指示灯指示电量功能

使用RGB指示 电量低于20%为红色闪烁，电量低于40%为紫色，电量低于60%为蓝色，电量低于80%为青色，满电绿色。充电状态下指示红灯常亮，满电绿色。

电量显示功能

+ 整个背光灯熄 字母区 1!~0) 显示电量。电量低时按键 1!~3# 显示红色，3# 以上的电量，1!~0) 都显示绿色，松开指示恢复默认灯效。

恢复出厂设置

+ 长按三秒恢复出厂设置并清除所有宏设定。

△ 注意

如果电池更换不当会有爆炸危险,只能用同样类型或等效类型的电池来更换

--可能满足特别电池型号，可能会缩短它的寿命或使用。对某些类型的锂电池也如此。

--将电池留给人火中或加热炉中，或对电池组进行机械挤压或切割也会造成可能导致爆炸；

--将电池组放置在极高温度环境中，可能导致爆炸或泄漏或燃烧或产生气体；和

--电池组承受极低气压，可能导致爆炸或泄漏或燃烧或产生气体；

--零专业人员调节拆解或维修该产品，否则有可能造成产品进一步的损坏或人身伤害

型号	7188	备注：尺寸：L100*W100mm 材质：100g 双胶纸 印刷：单黑双面印刷			拼版
名称	说明书				
日期	2024 -4-19				
页码	1 OF 5	文件编号	(BYK916+BK3632)		
绘图	何周平 审核		核准	版本	A.0