



Report No.: FCC 1912054 File Reference No.: 2019-12-16

Applicant: Eastern Times Technology Co., Ltd.

Product: GAMING KEYBOARD

Model No.: REDRAGON

Trademark: K530RGB, ET-8452, ET-8453, K530W-RGB

Test Standards: FCC Part 15.247

Test Result:

It is herewith confirmed and found to comply with the

requirements set up by ANSI C63.10, FCC Part 15.247 for

the evaluation of electromagnetic compatibility

Approved By

Jack Chung

Jack Chung

Manager

Dated: December 16, 2019

Results appearing herein relate only to the sample tested The technical reports is issued errors and omissions exempt and is subject to withdrawal at

SHENZHEN TIMEWAY TESTING LABORATORIES

Zone C, 1st Floor, Block B, Jun Xiang Da Building, Zhongshan Park Road West, Tong Le Village, Nanshan District, Shenzhen, China

Tel (755) 83448688, Fax (755) 83442996, E-Mail:info@timeway-lab.com

Report No.: FCC1912054 Page 2 of 52

Date: 2019-12-16



Special Statement:

The testing quality ability of our laboratory meet with "Quality Law of People's Republic of China" Clause 19.

The testing quality system of our laboratory meet with ISO/IEC-17025 requirements, which is approved by CNAL. This approval result is accepted by MRA of APLAC.

Our test facility is recognized, certified, or accredited by the following organizations:

CNAS-LAB Code: L2292

The EMC Laboratory has been assessed and in compliance with CNAS-CL01 accreditation criteria for testing Laboratories (identical to ISO/IEC 17025:2005 General Requirements) for the Competence of testing Laboratories.

FCC-Registration No.: 744189

The EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 744189.

Industry Canada (IC) — Registration No.:5205A

The EMC Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 5205A.

A2LA (Certification Number:5013.01)

The EMC Laboratory has been accredited by the American Association for Laboratory Accreditation (A2LA). Certification Number:5013.01

Page 3 of 52

Report No.: FCC1912054

Date: 2019-12-16



Test Report Conclusion

Content

1.0	General Details	4
1.1	Test Lab Details.	4
1.2	Applicant Details	4
1.3	Description of EUT	4
1.4	Submitted Sample	4
1.5	Test Duration.	4
1.6	Test Uncertainty.	4
1.7	Test By	5
2.0	List of Measurement Equipment	6
3.0	Technical Details	7
3.1	Summary of Test Results.	7
3.2	Test Standards.	7
4.0	EUT Modification.	7
5.0	Power Line Conducted Emission Test.	8
5.1	Schematics of the Test.	8
5.2	Test Method and Test Procedure.	8
5.3	Configuration of the EUT	8
5.4	EUT Operating Condition.	9
5.5	Conducted Emission Limit.	9
5.6	Test Result.	9
6.0	Radiated Emission test.	12
6.1	Test Method and Test Procedure.	12
6.2	Configuration of the EUT	12
5.3	EUT Operation Condition.	12
5.4	Radiated Emission Limit.	13
7.0	6dB Bandwidth Measurement Bandwidth.	22
8.0	Maximum Peak Output Power.	27
9.0	Power Spectral Density Measurement.	29
10.0	Out of Band Measurement.	34
11.0	Antenna Requirement.	41
12.0	FCC ID Label.	42
13.0	Photo of Test Setup and EUT View.	43

Date: 2019-12-16



1.0 General Details

1.1 Test Lab Details

Name: SHENZHEN TIMEWAY TESTING LABORATORIES.

Address: Zone C, 1st Floor, Block B, Jun Xiang Da Building, Zhongshan Park Road West, Tong Le

Village, Nanshan District, Shenzhen, China

Telephone: (755) 83448688 Fax: (755) 83442996

1.2 Applicant Details

Applicant: Eastern Times Technology Co., Ltd.

Address: Building D, Nan An Industrial Area, Youganpu Village, Fenggang Town, Dongguan City,

Guangdong, China

Telephone: 13077806581/0769-86800511

Fax: --

1.3 Description of EUT

Product: GAMING KEYBOARD

Manufacturer: Eastern Times Technology Co., Ltd.

Address: Building D, Nan An Industrial Area, Youganpu Village, Fenggang Town,

Dongguan City, Guangdong, China

Brand Name: REDRAGON

Additional Brand Name: N/A

Model Number: K530RGB

Additional Model Number: ET-8452, ET-8453, K530W-RGB

Type of Modulation GFSK (Bluetooth BLE)

Frequency range 2402-2480MHz Frequency Selection By software

Channel Number 40

Rating: DC5V or Built-in DC 3.7V, 3000mAh Li-ion battery

1.4 Submitted Sample: 1 Samples

1.5 Test Duration

2019-12-06 to 2019-12-16

1.6 Test Uncertainty

Conducted Emissions Uncertainty = 3.6dB

Radiated Emissions below 1GHz Uncertainty =4.7dB Radiated Emissions above 1GHz Uncertainty =6.0dB

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No.: FCC1912054 Page 5 of 52

Date: 2019-12-16



Conducted Power Uncertainty =6.0dB Occupied Channel Bandwidth Uncertainty =5%

1.7 Test Engineer

The sample tested by

Print Name: Terry Tang

Terry Tang

Page 6 of 52 Report No.: FCC1912054

Date: 2019-12-16



2.0 Test Equipment					
Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
ESPI Test Receiver	R&S	ESPI 3	100379	2019-06-21	2020-06-20
TWO Line-V-NETW	R&S	EZH3-Z5	100294	2019-06-21	2020-06-20
TWO Line-V-NETW	R&S	EZH3-Z5	100253	2019-06-21	2020-06-20
Impuls-Begrenzer	R&S	ESH3-Z2	100281	2019-06-21	2020-06-20
Loop Antenna	EMCO	6507	00078608	2020-06-20	2020-06-20
Spectrum	R&S	FSIQ26	100292	2019-06-21	2020-06-20
Horn Antenna	A-INFO	LB-180400-KF	J211060660	2019-06-21	2020-06-20
Horn Antenna	R&S	BBHA 9120D	9120D-631	2018-07-09	2021-07-08
Power meter	Anritsu	ML2487A	6K00003613	2019-08-22	2020-08-21
Power sensor	Anritsu	MA2491A	32263	2019-08-22	2020-08-21
Bilog Antenna	Schwarebeck	VULB9163	9163/340	2018-07-04	2021-07-03
9*6*6 Anechoic			N/A	2018-02-07	2021-02-06
EMI Test Receiver	RS	ESVB	826156/011	2019-06-21	2020-06-20
EMI Test Receiver	RS	ESH3	860904/006	2019-06-21	2020-06-20
Spectrum	HP/Agilent	ESA-L1500A	US37451154	2019-06-21	2020-06-20
Spectrum	HP/Agilent	E4407B	MY50441392	2019-06-21	2020-06-20
Spectrum	RS	FSP	1164.4391.38	2019-01-20	2020-01-19
RF Cable	Zhengdi	ZT26-NJ-NJ-8 M/FA		2019-06-21	2020-06-20
RF Cable	Zhengdi	7m		2019-06-21	2020-06-20
RF Switch	EM	EMSW18	060391	2019-06-21	2020-06-20
Pre-Amplifier	Schwarebeck	BBV9743	#218	2019-06-21	2020-06-20
Pre-Amplifier	HP/Agilent	8449B	3008A00160	2019-06-21	2020-06-20
LISN	SCHAFFNER	NNB42	00012	2019-01-08	2020-01-07

Report No.: FCC1912054

Date: 2019-12-16



3.0 **Technical Details**

3.1 **Summary of test results**

Standard	Test Type	Result	Notes
ECC Part 15, Paragraph 15.107 & 15.207	Conducted Emission Test	PASS	Complies
FCC Part 15 Subpart C Paragraph 15.247(a)(2) Limit	Spectrum bandwidth of a Orthogonal Frequency Division Multiplex System Limit: 6dB bandwidth>500kHz	PASS	Complies
FCC Part 15, Paragraph 15.247(b)	Maximum peak output power Limit: max. 30dBm	PASS	Complies
FCC Part 15, Paragraph 15.109,15.205 & 15.209	Transmitter Radiated Emission Limit: Table 15.209	PASS	Complies
FCC Part 15, Paragraph 15.247(e)	Power Spectral Density Limit: max. 8dBm	PASS	Complies
FCC Part 15, Paragraph 15.247(d)	Out of Band Emission and Restricted Band Radiation Limit: 20dB less than peak value of fundamental frequency Restricted band limit: Table 15.209	PASS	Complies

3.2 **Test Standards**

FCC Part 15 Subpart & Subpart C, Paragraph 15.247

EUT Modification 4.0

No modification by SHENZHEN TIMEWAY TESTING LABORATORIES.


Report No.: FCC1912054

Date: 2019-12-16



5.Power Line Conducted Emission Test

5.1 Schematics of the test




EUT: Equipment Under Test

5.2 Test Method and test Procedure

The EUT was tested according to ANSI C63.10-2013. The Frequency spectrum From 0.15MHz to 30MHz was investigated. The LISN used was 50ohm/50uH as specified by section 5.1 of ANSI C63.10 –2013.

Test Voltage: 120V~, 60Hz Block diagram of Test setup



5.3 Configuration of The EUT

The EUT was configured according to ANSI C63.10-2013. All interface ports were connected to the appropriate peripherals. All peripherals and cables are listed below.

A. EUT

Device		Manufacturer	Model	FCC ID
			K530RGB,	
GAMING KEYBOARD		RD Eastern Times Technology Co., Ltd.	ET-8452,ET-8453,	TUVET-8452
			K530W-RGB	

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No.: FCC1912054 Page 9 of 52

Date: 2019-12-16



B. Internal Device

Device	Manufacturer	Model	Rating

C. Peripherals

Device	Manufacturer	Model	Rating
Power Supply	h.TV	S012BB80500200	Input: 100-240V~, 50/60Hz, 500mA;
			Output: DC5V, 2A

5.4 EUT Operating Condition

Operating condition is according to ANSI C63.10-2013.

- A Setup the EUT and simulators as shown on follow
- B Enable AF signal and confirm EUT active to normal condition

5.5 Power line conducted Emission Limit according to Paragraph 15.207 and 15.107

Frequency	Class A Lim	its (dB µ V)	Class B Limits (dB µ V)			
(MHz) Quasi-peak Leve		Quasi-peak Level Average Level		Average Level		
$0.15 \sim 0.50$	79.0	66.0	66.0~56.0*	56.0~46.0*		
0.50 ~5.00	73.0	60.0	56.0	46.0		
5.00 ~ 30.00	73.0	60.0	60.0	50.0		

Notes:

- 1. *Decreasing linearly with logarithm of frequency.
- 2. The tighter limit shall apply at the transition frequencies

5.6 Test Results

The frequency spectrum from 0.15MHz to 30MHz was investigated. All reading are quasi-peak values with a resolution bandwidth of 9kHz.

Date: 2019-12-16



A: Conducted Emission on Live Terminal (150kHz to 30MHz)

EUT Operating Environment


Temperature: 26°C Humidity: 65%RH Atmospheric Pressure: 101 kPa

EUT set Condition: Keep Bluetooth Transmitting

Equipment Level: Class B

Results: PASS

Please refer to following diagram for individual



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.5010	31.01	9.77	40.78	56.00	-15.22	QP	Р	
2	0.5010	22.00	9.77	31.77	46.00	-14.23	AVG	Р	
3	1.1055	24.56	9.79	34.35	56.00	-21.65	QP	Р	
4	1.1055	15.14	9.79	24.93	46.00	-21.07	AVG	Р	
5	1.6515	23.79	9.80	33.59	56.00	-22.41	QP	Р	
6	1.6515	12.17	9.80	21.97	46.00	-24.03	AVG	Р	
7	4.6731	22.54	9.92	32.46	56.00	-23.54	QP	Р	
8	4.6731	12.12	9.92	22.04	46.00	-23.96	AVG	Р	

Report No.: FCC1912054

Date: 2019-12-16



B: Conducted Emission on Neutral Terminal (150kHz to 30MHz)

EUT Operating Environment


Temperature: 26°C Humidity: 65%RH Atmospheric Pressure: 101 kPa

EUT set Condition: Keep Bluetooth Transmitting

Equipment Level: Class B

Results: Pass

Please refer to following diagram for individual



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.5010	24.39	9.77	34.16	56.00	-21.84	QP	Р	
2	0.5010	13.83	9.77	23.60	46.00	-22.40	AVG	Р	
3	0.5205	23.00	9.77	32.77	56.00	-23.23	QP	Р	
4	0.5205	9.62	9.77	19.39	46.00	-26.61	AVG	Р	
5	1.1484	18.23	9.79	28.02	56.00	-27.98	QP	Р	
6	1.1484	6.44	9.79	16.23	46.00	-29.77	AVG	Р	
7	4.7082	18.61	9.92	28.53	56.00	-27.47	QP	Р	
8	4.7082	9.54	9.92	19.46	46.00	-26.54	AVG	Р	
9	7.9101	18.33	10.06	28.39	60.00	-31.61	QP	Р	
10	7.9101	7.22	10.06	17.28	50.00	-32.72	AVG	Р	


Date: 2019-12-16



6 Radiated Emission Test

- 6.1 Test Method and test Procedure:
- (1) The EUT was tested according to ANSI C63.10-2013. The radiated test was performed at Timeway EMC Laboratory. This site is on file with the FCC laboratory division, Registration No.744189
- (2) The EUT, peripherals were put on the turntable which table size is 1m x 1.5 m, table high 0.8 m. All set up is according to ANSI C63.10-2013.
- (3) The frequency spectrum from 30 MHz to 25 GHz was investigated. All readings from 30 MHz to 1 GHz are Quasi-peak values with a resolution bandwidth of 120 kHz. For measurement above 1GHz, peak values with RBW=1MHz VBW=3MHz and PK detector. AV value with RBW=1MHz, VBW=3MHz and RMS detector. Measurements were made at 3 meters.
- (4) The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency.
- (5) Maximizing procedure was performed on the six (6) highest emissions to ensure EUT compliance is with all installation combinations. All data was recorded in the peak detection mode. Quasi-peak readings was performed only when an emission was found to be marginal (within -4 dB of specification limit), and are distinguished with a "QP" in the data table.
- (6) The antenna polarization: Vertical polarization and Horizontal polarization.

Block diagram of Test setup



- 6.2 Configuration of The EUT
 Same as section 5.3 of this report
- 6.3 EUT Operating Condition
 Same as section 5.4 of this report.

Report No.: FCC1912054 Page 13 of 52

Date: 2019-12-16



6.4 Radiated Emission Limit

All emission from a digital device, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strength specified below:

Frequencies in restricted band are complied to limit on Paragraph 15.209 and 15.109

	-	
Frequency Range (MHz)	Distance (m)	Field strength (dB μ V/m)
30-88	3	40.0
88-216	3	43.5
216-960	3	46.0
Abov 960	3	54.0

Note:

- 1. RF Voltage $(dBuV) = 20 \log RF \text{ Voltage } (uV)$
- 2. In the Above Table, the higher limit applies at the band edges.
- 3. Distance refers to the distance in meters between the measuring instrument antenna and the EUT
- 4. Battery was fully charged during the radiated emissions test.

Page 14 of 52

Report No.: FCC1912054

Date: 2019-12-16



Test result

General Radiated Emission Data and Harmonics Radiated Emission Data

Radiated Emission In Horizontal (30MHz----1000MHz)

EUT set Condition: Keep Bluetooth Transmitting

Results: Pass

Test Figure:

FCC_FCC Part 15B Class B 30MHz-1GHz

70

40

40

40

40

40

40

40

50

50

10

Frequency (MHz)

No.	Frequency	Results	Factor	Limit	Over	Detector	Table (o)	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	Limit (dB)			(cm)		
1	205.041	22.92	-13.59	43.5	-20.58	Peak	68.00	200	Н	Pass
2	236.801	24.70	-12.34	46.0	-21.30	Peak	105.00	100	Н	Pass
3	398.265	28.92	-8.67	46.0	-17.08	Peak	360.00	200	Н	Pass

Report No.: FCC1912054

Date: 2019-12-16



Test result

General Radiated Emission Data and Harmonics Radiated Emission Data


Radiated Emission In Vertical (30MHz----1000MHz)

EUT set Condition: **Keep Transmitting**

Results: Pass

Test Figure:

FCC_FCC Part 15B Class B 30MHz-1GHz



No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table (o)	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)			(cm)		
1	215.951	19.38	-13.60	43.5	-24.12	Peak	187.00	200	V	Pass
2	398.508	26.08	-8.65	46.0	-19.92	Peak	266.00	200	٧	Pass
3	599.733	29.84	-4.98	46.0	-16.16	Peak	360.00	200	V	Pass

Page 16 of 52

Report No.: FCC1912054

Date: 2019-12-16




Test Figures above 1GHz:

Please refer to the following test plots for details:

Low Channel: Vertical

FCC_FCC Part 15B Class B 1GHz-18GHz - 2



No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table (o)	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)			(cm)		
2	4802.799	49.28	3.12	54.0	-4.72	Peak	272.00	100	٧	Pass


Page 17 of 52 Report No.: FCC1912054

Date: 2019-12-16



Low Channel: Horizontal






No.	Frequency	Results	Factor	Limit	Over	Detector	Table (o)	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	Limit (dB)			(cm)		
2	4802.799	49.60	3.12	54.0	-24.40	Peak	238.00	100	Н	Pass

Report No.: FCC1912054 Page 18 of 52

Date: 2019-12-16



Middle Channel: Vertical




No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table (o)	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)			(cm)		
2	4879.280	49.48	3.20	74.0	-4.52	Peak	267.00	100	V	Pass

Report No.: FCC1912054 Page 19 of 52

Date: 2019-12-16



Middle Channel: Horizontal




No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table (o)	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)			(cm)		
2	4879.280	50.45	3.20	54.0	-3.55	Peak	259.00	100	Н	Pass

Report No.: FCC1912054 Page 20 of 52

Date: 2019-12-16



High Channel: Vertical



No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table (o)	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)			(cm)		
2	4960.010	47.45	3.36	54.0	-6.55	Peak	212.00	100	V	Pass


Frequency (MHz)

Report No.: FCC1912054 Page 21 of 52

Date: 2019-12-16



High Channel: Horizontal



Note: 1. Level = Reading + AF + Cable - Preamp

- 2. For the radiated emissions above 18G, it is the floor noise.
- 3. The measured PK value less than the AV limit, no necessary to take down the AV measurement result.

Page 22 of 52


Report No.: FCC1912054

Date: 2019-12-16



7.0 6dB Bandwidth Measurement

7.1 Test Setup



7.2 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is >500 kHz

7.3 Test Procedure

- 1. Set resolution bandwidth (RBW) = 100 kHz
- 2. Set the video bandwidth (VBW) \geq 3 x RBW.
- 3. Detector = Peak.
- 4. Trace mode = \max hold.
- 5. Sweep = auto couple.
- 6. Allow the trace to stabilize.
- 7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

7.4 Test Result

Page 23 of 52 Report No.: FCC1912054

Date: 2019-12-16



6dB BW

EUT	EUT GAMING KE		YBOARD	Model		k	K530RGB
Mode		Keep Trans	smitting	Input Voltag	Input Voltage		DC3.7V
Temperat	Temperature 24 deg		g. C, Humidity		56% RH		
Channel	hannel			andwidth Min		inimum Limit (kHz)	Pass/ Fail
Low	2402 73		37		500	Pass	
Middle	le 2440		7	754		500	Pass
High	High 2480		737			500	Pass


Report No.: FCC1912054 Page 24 of 52

Date: 2019-12-16



Test Figure:

1. Condition: Low Channel




Date: 12.DEC.2019 16:02:06

Report No.: FCC1912054 Page 25 of 52

Date: 2019-12-16



2. Condition: Middle Channel




Date: 12.DEC.2019 16:00:13

Report No.: FCC1912054 Page 26 of 52

Date: 2019-12-16



3. High Channel



Date: 12.DEC.2019 15:57:55


Report No.: FCC1912054 Page 27 of 52

Date: 2019-12-16



8. Maximum Output Power

8.1 Test Setup



8.2 Limits of Maximum Output Power

The Maximum Output Power Measurement is 30dBm.

8.3 Test Procedure

The RF power output was measured with a Power meter connected to the RF Antenna connector (conducted measurement) while EUT was operating in transmit mode at the appropriate centre frequency.

Note: the Peak power were measured.

Report No.: FCC1912054 Page 28 of 52

Date: 2019-12-16



8.4Test Results

EUT	EUT GAMING KEY		BOARD Model			K530RGB		
Mode		Keep Transmitting		Input Voltage	DC3.7V			
Temperatu	Temperature 24 deg.		Ξ,	Humidity		56% RH		
Channel	Cł	nannel Frequency	Max	Max. Power Output (dBm)			Pass/ Fail	
Chamer		(MHz)	Peak			Limit (dBm)		
Low		2402		-5.07		30	Pass	
Middle		2440		-5.33		30	Pass	
High		2480		-5.60		30	Pass	

Note: 1. the result basic equation calculation as follow:

Max. Power Output = Power Reading + Cable loss + Attenuator


Report No.: FCC1912054 Page 29 of 52

Date: 2019-12-16



9. Power Spectral Density Measurement

9.1 Test Setup



9.2 Limits of Power Spectral Density Measurement

The Maximum Power Spectral Density Measurement is 8dBm.

9.3 Test Procedure

- 1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
- 2. Set the RBW = 10 kHz.
- 3. Set the VBW \geq 30 kHz.
- 4. Set the span to 1.5 times the DTS channel bandwidth.
- 5. Detector = peak.
- 6. Sweep time = auto couple.
- 7. Trace mode = max hold.
- 8. Allow trace to fully stabilize.
- 9. Use the peak marker function to determine the maximum amplitude level.
- 10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.
- 11. The resulting peak PSD level must be ≤ 8 dBm.

Report No.: FCC1912054 Page 30 of 52

Date: 2019-12-16



9.4Test Result

EUT		GAM	ING KEYBO	OARD	Model	K530RGB		
Mode		Keep Transmitting			Input	DC3.7V		
			Voltage					
Temperat	Temperature				Humidity	56% RH		
Channel	Re	Power ading (Bm)	Cable Loss (dB)	Final Po	wer Spectral ty (dBm)	Maximum Limit (dBm)	Pass/ Fail	
Low	-1	-17.33 0.2 -		17.13	8	Pass		
Middle	-1	16.37 0.2 -1		16.17	8	Pass		
High	-1	5.55	0.2	-	15.35	8	Pass	

Note: The result basic equation calculation as follow:

Peak Power Output = Peak Power Reading + Cable loss

Page 31 of 52


Report No.: FCC1912054

Date: 2019-12-16



Test Figure:

1. Condition: Low Channel




Report No.: FCC1912054 Page 32 of 52

Date: 2019-12-16



2. Condition: Middle Channel




Report No.: FCC1912054 Page 33 of 52

Date: 2019-12-16



3. High Channel



12.DEC.2019 13:48:32 Date:


Page 34 of 52

Report No.: FCC1912054

Date: 2019-12-16



10 Out of Band Measurement 10.1 Test Setup for band edge



The restricted band requirement based on radiated emission test; please see the clause 6 for the test setup

10.2 Limits of Out of Band Emissions Measurement

- 1. Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).
- 2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.

10.3 Test Procedure

For signals in the restricted bands above and below the 2.4-2.483GHz allocated band a measurement was made of Radiated emission test. (Peak values with RBW=1MHz, VBW=3MHz and PK detector. AV value with RBW=1MHz, VBW=3MHz and RMS detector)

For bandage test, the spectrum set as follows: RBW=100 kHz, VBW=300 kHz. A conducted measurement used

10.4 Test Result

Please see next pages

Note: 1. For band-edge measurement, the frequency from 30MHz-25GHz was tested. And It met the FCC rule.

Report No.: FCC1912054 Page 35 of 52


Date: 2019-12-16



10.4 Band-edge Measurement

EUT	GAMING KEYBOARD	Model	K530RGB
Mode	Keep Transmitting	Input Voltage	DC3.7V
Temperature	24 deg. C,	Humidity	56% RH
Test Result:	Pass	Detector	PK

Test Figure:



Report No.: FCC1912054 Page 36 of 52


Date: 2019-12-16



10.4 Band-edge Measurement

EUT	GAMING KEYBOARD	Model	K530RGB
Mode	Keeping Transmitting	Input Voltage	DC3.7V
Temperature	24 deg. C,	Humidity	56% RH
Test Result:	Pass	Detector	PK

Test Figure:



Report No.: FCC1912054 Page 37 of 52

Date: 2019-12-16



10.4 Restrict Band Measurement

	EUT	GAMIN	G KEYE	BOARD	Mod	lel		K53	0RGB	
	Mode	Keep	Transmi	tting	Input Vo	oltage		DC	23.7V	
To	emperature	2	4 deg. C	,	Humio	dity		569	% RH	
T	est Result:		Pass					CI	I L	
CC_FCC 90-r	Part 15B Class B 1GHz-18G	Hz - 2				·				
80 - 70 - 60 - 50 - 50 - 50 - 50 - 50 - 50 - 5										
40-	hadista photos de la companya de la			i ya fa ka						Marin
23	60				Frequency (MHz	z)				2410
No.	Frequency	Results	Factor	Limit	Over	Detector	Table (o)	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	Limit (dB)			(cm)		
	2390	45.60	-3.53	54.0	-8.40	Peak	266.00	100	Н	Pass

Page 38 of 52

Report No.: FCC1912054

Date: 2019-12-16



10.4 Restrict Band Measurement

	UT	GAM	ING KEY	BOARD		Model		k	K530RGI	В
M	lode	Ke	ep Transn	nitting	Inp	ut Voltage			DC3.7V	7
Temp	erature		24 deg. (C,	I	Iumidity			56% RH	[
Test	Result:		Pass						CHL	
CC_FCC Part 1	5B Class B 1GHz-18GF	Hz - 2								
70- E 60-									~~	
>										
(m/\ngp) as 50-										V. Market
					Frequency (MHz			dh kara		2410
40-	Frequency	Results	Factor	Limit	Frequency (MH:	Detector	Table (o)	Height	ANT	2410 Verdict
30- 2360	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)			Table (o)	Height (cm)	ANT	

Note: The measured PK value less than the AV limit, no necessary to take down the AV measurement result.

Report No.: FCC1912054 Page 39 of 52

Date: 2019-12-16



10.4 Restrict Band Measurement

E	UT	GAMIN	IG KEYI	BOARD	Mo	odel		K5	30RGB		
Me	ode	Keep Transmitting			Input Voltage Humidity		DC3.7V				
Temp	erature	24 deg. C,		56% RH							
Test I	st Result: Pass							(СНН		
	B Class B 1GHz-18GH	lz - 2									
1.0E+2-											
90-											
			/								
80-	80										
70-	70										
level (dBuV/m)			-	**	N.						
50-											
	O- MATTER TO THE PROPERTY OF T				The second second					Maleria .	
40-						radio di adia di diferi	data andat bedian	1			
										T. Indian	
30- 2470					2483.5 Frequency (M	H ₇)				250	
		Danulta	Fa atau	Lineia		Г	Table (a)	l laimht	ANIT	\/a.adi.at	
No	Frequency	Results	Factor	Limit	Over	Detector	Table (o)	Height	ANT	Verdict	
No.		(-ID1//)		(dBuV/m)	Limit (dB)			(cm)			
-	(MHz)	(dBuV/m)	(dB)						1	l _	
No.		(dBuV/m) 56.49 35.76	-3.57 -3.57	74.0	-10.51 -18.24	Peak AV	257.00 257.00	100	Н	Pass Pass	

Page 40 of 52

Report No.: FCC1912054

Date: 2019-12-16



10.4 Restrict Band Measurement

L	UT	GAMIN	G KEYE	SOARD	Model			K530)RGB		
Mo	Mode Keep Transmitting					ige	DC3.7V				
Tempe	erature	2	4 deg. C.	,	Humidity	y		56% RH			
Test R	Result:		Pass					CH	ΗH		
CC_FCC Part 15E	B Class B 1GHz-18GF	Hz - 2									
70-				- No.							
level (dBu//m) 20 - 20 - 20 - 20 - 20 - 20 - 20 - 20 -	/										
			7	N.							
9 50-			/	Y	Пт						
40-	YATINA MARAJANIANA	A HAR AN ALLANDA MARKANIA	<i>/</i>		W. Land Hall Hall Hall Hall Hall Hall Hall Hal						
40- 40- 30- 2470	With the party of the second	Market Market Market	/		2483.5 Frequency (MHz)			okalan para da katalan ja		2500	
40-	Frequency	Results	Factor	Limit		Detector	Table	Height	ANT	2500	
30- 2470	Frequency (MHz)	Results (dBuV/m)	Factor (dB)		Frequency (MHz)		Table (o)	Height (cm)	ANT		

Note: The measured PK value less than the AV limit, no necessary to take down the AV measurement result.

Date: 2019-12-16



Page 41 of 52

11.0 Antenna Requirement

11.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitter antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the mount in dB that the directional gain of the antenna exceeds 6 dBi.

11.2 Antenna Connected construction

PCB antenna used. The maximum gain of the antennas is 2.0dBi.

Report No.: FCC1912054 Page 42 of 52

Date: 2019-12-16




12.0 FCC ID Label

FCC ID: TUVET-8452

This device complies with part 15 of the FCC rules. Operation is subject to the following two conditions (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

The label must not be a stick-on paper label. The label on these products must be permanently affixed to the product and readily visible at the time of purchase and must last the expected lifetime of the equipment not be readily detachable.

Mark Location:



Page 43 of 52


Report No.: FCC1912054

Date: 2019-12-16



13.0 Photo of testing


Conducted Emission Test Setup:




Date: 2019-12-16



Radiated Emission Test Setup:





Date: 2019-12-16



Photographs - EUT





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to


adopt any other remedies which may be appropriate.

Date: 2019-12-16



Photographs - EUT





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Date: 2019-12-16



Photographs - EUT





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to


adopt any other remedies which may be appropriate.

Date: 2019-12-16



Photographs - EUT






The report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Date: 2019-12-16



Photographs - EUT






The report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any

Date: 2019-12-16



Photographs - EUT






The report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Date: 2019-12-16



Photographs - EUT






The report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any

Date: 2019-12-16



Photographs - EUT





End of the report

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.