

File reference No.: 2022-06-21

Applicant: Eastern Times Technology Co.,Ltd

Product: 3 MODES PORTABLE MECHANICAL KEYBOARD

Model No.: K625P-KBS, ET-8568, K625P-KNS, K625P-KRS,

K625P-WNS, K625P-WRS, K625P-WBS

Trademark: REDRAGON

Test Standards: FCC Part 15.249

Test result:

It is herewith confirmed and found to comply with the

requirements set up by ANSI C63.10 &FCC Part 15 Subpart C,

Paragraph 15.249 regulations for the evaluation of

electromagnetic compatibility

Approved By

Terry long

Terry Tang

Manager

Dated: June 21, 2022

Results appearing herein relate only to the sample tested The technical reports is issued errors and omissions exempt and is subject to withdrawal at

SHENZHEN TIMEWAY TESTING LABORATORIES

Zone C, 1st Floor, Block B, Jun Xiang Da Building, Zhongshan Park Road West, Tong Le Village, Nanshan District, Shenzhen, China

Tel (755) 83448688, Fax (755) 83442996, E-Mail:info@timeway-lab.com

Report No.: TW2206141-02E Page 2 of 34

Date: 2022-06-21



Special Statement:

The testing quality ability of our laboratory meet with "Quality Law of People's Republic of China" Clause 19.

The testing quality system of our laboratory meet with ISO/IEC-17025 requirements, which is approved by CNAS. This approval result is accepted by MRA of APLAC.

Our test facility is recognized, certified, or accredited by the following organizations:

CNAS-LAB Code: L2292

The EMC Laboratory has been assessed and in compliance with CNAS-CL01 accreditation criteria for testing Laboratories (identical to ISO/IEC 17025:2017 General Requirements) for the Competence of testing Laboratories.

FCC-Registration No.: 744189

The EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 744189.

Industry Canada (IC) — Registration No.:5205A

The EMC Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 5205A.

A2LA (Certification Number:5013.01)

The EMC Laboratory has been accredited by the American Association for Laboratory Accreditation (A2LA). Certification Number:5013.01

Date: 2022-06-21



Test Report Conclusion

		4	- 4
Co	۱n	TA	nt

1.0	General Details	4
1.1	Test Lab Details	4
1.2	Applicant Details	4
1.3	Description of EUT	4
1.4	Submitted Sample	4
1.5	Test Duration.	5
1.6	Test Uncertainty	5
1.7	Test By	5
2.0	List of Measurement Equipment	6
3.0	Technical Details	7
3.1	Summary of Test Results	7
3.2	Test Standards	7
4.0	EUT Modification	7
5.0	Power Line Conducted Emission Test	8
5.1	Schematics of the Test	8
5.2	Test Method and Test Procedure	8
5.3	Configuration of the EUT	8
5.4	EUT Operating Condition.	9
5.5	Conducted Emission Limit.	9
5.6	Test Result.	9
6.0	Radiated Emission test	12
6.1	Test Method and Test Procedure	12
6.2	Configuration of the EUT	13
6.3	EUT Operation Condition.	13
6.4	Radiated Emission Limit.	14
6.5	Test Result.	15
7.0	Band Edge	23
7.1	Test Method and Test Procedure.	23
7.2	Radiated Test Setup	23
7.3	Configuration of the EUT	23
7.4	EUT Operating Condition.	23
7.5	Band Edge Limit.	23
7.6	Band Edge Test Result.	24
8.0	Antenna Requirement	28
9.0	20dB bandwidth measurement	29
10.0	FCC ID Label	32
11.0	Photo of Test Setup and EUT View	33

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Date: 2022-06-21



1.0 General Details

1.1 Test Lab Details

Name: SHENZHEN TIMEWAY TESTING LABORATORIES.

Address: Zone C, 1st Floor, Block B, Jun Xiang Da Building, Zhongshan Park Road West, Tong Le

Village, Nanshan District, Shenzhen, China

Telephone: (755) 83448688 Fax: (755) 83442996

Site on File with the Federal Communications Commission – United Sates

Registration Number: 744189 For 3m Anechoic Chamber

1.2 Applicant Details

Applicant: Eastern Times Technology Co.,Ltd

Address: Building D, Nan An Industrial Area, Youganpu Village, Fenggang Town, Dongguan City,

Guangdong, China.

Telephone: -Fax: --

1.3 Description of EUT

Product: 3 MODES PORTABLE MECHANICAL KEYBOARD

Manufacturer: Eastern Times Technology Co.,Ltd

Address: Building D, Nan An Industrial Area, Youganpu Village, Fenggang Town,

Dongguan City, Guangdong, China.

Trademark: REDRAGON

Additional Trademark: N/A

Model Number: K625P-KBS

Additional Model Name ET-8568, K625P-KNS, K625P-KRS, K625P-WNS, K625P-WRS, K625P-WBS

Serial No.: RDK625P-KBS22052501007

Rating: DC5.0V, 790mA or DC3.7V, 330mA Battery: DC3.7V, 1900mAh Li-ion battery

Modulation Type: GFSK

Operation Frequency: 2402-2480MHz

Channel Separate: 1MHz Channel Number: 79

Antenna Designation PCB antenna with gain -1.85dBi maximum (Declared by the Manufacturer)

1.4 Submitted Sample: 1 pc

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No.: TW2206141-02E Page 5 of 34

Date: 2022-06-21



1.5 Test Duration

2022-06-11 to 2022-06-21

1.6 Test Uncertainty

Conducted Emissions Uncertainty =3.6dB

Radiated Emissions below 1GHz Uncertainty =4.7dB

Radiated Emissions above 1GHz Uncertainty =6.0dB

Conducted Power Uncertainty = 6.0dB

Occupied Channel Bandwidth Uncertainty = 5%

Conducted Emissions Uncertainty = 3.6dB

Note: The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

1.7 Test Engineer

The sample tested by

Print Name: Terry Tang

Page 6 of 34

Report No.: TW2206141-02E

Date: 2022-06-21



2.0 Test Equipment					
Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
ESPI Test Receiver	R&S	ESPI 3	100379	2022-06-17	2023-06-16
LISN	R&S	EZH3-Z5	100294	2022-06-17	2023-06-16
LISN	R&S	EZH3-Z5	100253	2022-06-17	2023-06-16
Impuls-Begrenzer	R&S	ESH3-Z2	100281	2022-06-17	2023-06-16
Loop Antenna	EMCO	6507	00078608	2021-06-18	2024-06-17
Spectrum	R&S	FSIQ26	100292	2022-06-17	2023-06-16
Horn Antenna	A-INFO	LB-180400-KF	J211060660	2021-07-02	2024-07-01
Horn Antenna	R&S	BBHA 9120D	9120D-631	2021-07-02	2024-07-01
Power meter	Anritsu	ML2487A	6K00003613	2022-06-17	2023-06-16
Power sensor	Anritsu	MA2491A	32263	2022-06-17	2023-06-16
Bilog Antenna	Schwarebeck	VULB9163	9163/340	2021-07-02	2024-07-01
9*6*6 Anechoic			N/A	2021-07-02	2022-07-01
EMI Test Receiver	RS	ESVB	826156/011	2022-06-17	2023-06-16
EMI Test Receiver	RS	ESH3	860904/006	2022-06-17	2023-06-16
Spectrum	HP/Agilent	ESA-L1500A	US37451154	2022-06-17	2023-06-16
Spectrum	HP/Agilent	E4407B	MY50441392	2022-06-17	2023-06-16
Spectrum	RS	FSP	1164.4391.38	2022-01-15	2023-01-14
RF Cable	Zhengdi	ZT26-NJ-NJ-8M/FA		2022-06-17	2023-06-16
RF Cable	Zhengdi	7m		2022-06-17	2023-06-16
RF Switch	EM	EMSW18	060391	2022-06-17	2023-06-16
Pre-Amplifier	Schwarebeck	BBV9743	#218	2022-06-17	2023-06-16
Pre-Amplifier	HP/Agilent	8449B	3008A00160	2022-06-17	2023-06-16
LISN	SCHAFFNER	NNB42	00012	2022-01-05	2023-01-04

2.2 Automation Test Software

For Conducted Emission Test

Name	Version
EZ-EMC	Ver.EMC-CON 3A1.1

For Radiated Emissions

Name	Version
EMI Test Software BL410-EV18.91	V18.905
EMI Test Software BL410-EV18.806 High Frequency	V18.06

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Page 7 of 34

Report No.: TW2206141-02E

Date: 2022-06-21



3.0 Technical Details

3.1 Summary of test results

The EUT has	been tested	l according to	o the foll	owing s	specifications:

Standard	Test Type	Result	Notes
FCC Part 15, Paragraph 15.203	Antenna Requirement	Pass	Complies
FCC Part 15, Paragraph 15.207	Conducted Emission Test	Pass	Complies
FCC Part 15 Subpart C Paragraph 15.249(a) & 15.249(b) Limit	Field Strength of Fundamental	Pass	Complies
FCC Part 15, Paragraph 15.209	Radiated Emission Test	Pass	Complies
FCC Part 15 Subpart C Paragraph 15.249(d) Limit	Band Edge Test	Pass	Complies

3.2 Test Standards

FCC Part 15 Subpart C, Paragraph 15.249, ANSI C63.4:2014 and ANSI C63.10:2013

4.0 EUT Modification


No modification by SHENZHEN TIMEWAY TESTING LABORATORIES

Date: 2022-06-21



5. Power Line Conducted Emission Test

5.1 Schematics of the test




EUT: Equipment Under Test

5.2 Test Method and test Procedure

The EUT was tested according to ANSI C63.10-2013. The Frequency spectrum from 0.15MHz to 30MHz was investigated. The LISN used was 50ohm/50uH as specified by section 5.1 of ANSI C63.10 –2013.

Test Voltage: 120V~, 60Hz Block diagram of Test setup



5.3 Configuration of the EUT

The EUT was configured according to ANSI C63.10-2013. All interface ports were connected to the appropriate peripherals. All peripherals and cables are listed below.

79 channels are provided to the EUT

A. EUT

Device	Manufacturer Model		FCC ID
3 MODES PORTABLE	Fastam Timas	K625P-KBS, ET-8568, K625P-KNS,	
MECHANICAL	Eastern Times	K625P-KRS, K625P-WNS,	TUVET-8568
KEYBOARD	Technology Co.,Ltd	K625P-WRS, K625P-WBS	

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Report No.: TW2206141-02E Page 9 of 34

Date: 2022-06-21



B. Internal Device

Device	Manufacturer	Model	FCC ID/DOC
N/A			

C. Peripherals

Device	Manufacturer	Model	Rating
Power Supply	KEYU	KA23-0502000DEU	Input: 100-240V~, 50/60Hz, 0.35A;
			Output: DC5V, 2A

5.4 EUT Operating Condition

Operating condition is according to ANSI C63.10-2013

- A Setup the EUT and simulators as shown on follow
- B Enable AF signal and confirm EUT active to normal condition

5.5 Power line conducted Emission Limit according to Paragraph 15.207

Frequency	Limits (dB µ V)			
(MHz)	Quasi-peak Level	Average Level		
$0.15 \sim 0.50$	66.0~56.0*	56.0~46.0*		
$0.50 \sim 5.00$	56.0	46.0		
$5.00 \sim 30.00$	60.0	50.0		

Notes:

- 1. *Decreasing linearly with logarithm of frequency.
- 2. The tighter limit shall apply at the transition frequencies

5.6 Test Results:

Pass

Date: 2022-06-21



A: Conducted Emission on Live Terminal (150kHz to 30MHz)


EUT Operating Environment

Temperature: 25°C Humidity: 65%RH Atmospheric Pressure: 101 kPa

EUT set Condition: Communication by BT

Results: Pass

Please refer to following diagram for individual



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.2748	30.47	9.75	40.22	60.97	-20.75	QP	Р
2	0.2748	16.47	9.75	26.22	50.97	-24.75	AVG	Р
3	0.6063	33.20	9.78	42.98	56.00	-13.02	QP	Р
4	0.6063	25.05	9.78	34.83	46.00	-11.17	AVG	Р
5	0.8832	30.66	9.79	40.45	56.00	-15.55	QP	Р
6	0.8832	19.55	9.79	29.34	46.00	-16.66	AVG	Ъ
7	1.7256	25.38	9.80	35.18	56.00	-20.82	QP	Р
8	1.7256	15.72	9.80	25.52	46.00	-20.48	AVG	J
9	13.4247	22.47	10.31	32.78	60.00	-27.22	QP	Р
10	13.4247	11.53	10.31	21.84	50.00	-28.16	AVG	Р
11	25.0194	18.08	10.99	29.07	60.00	-30.93	QP	Р
12	25.0194	8.85	10.99	19.84	50.00	-30.16	AVG	Р

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Date: 2022-06-21



B: Conducted Emission on Neutral Terminal (150kHz to 30MHz)


EUT Operating Environment

Temperature: 25°C Humidity: 65%RH Atmospheric Pressure: 101 kPa

EUT set Condition: Communication by BT

Results: Pass

Please refer to following diagram for individual



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1500	31.34	9.79	41.13	66.00	-24.87	QP	Р
2	0.1500	13.50	9.79	23.29	56.00	-32.71	AVG	Р
3	0.3255	28.89	9.76	38.65	59.57	-20.92	QP	Р
4	0.3255	12.53	9.76	22.29	49.57	-27.28	AVG	Р
5	0.6453	34.86	9.78	44.64	56.00	-11.36	QP	Р
6	0.6453	25.47	9.78	35.25	46.00	-10.75	AVG	Р
7	0.9924	29.97	9.79	39.76	56.00	-16.24	QP	Р
8	0.9924	16.96	9.79	26.75	46.00	-19.25	AVG	Р
9	3.2457	22.68	9.85	32.53	56.00	-23.47	QP	Р
10	3.2457	9.57	9.85	19.42	46.00	-26.58	AVG	Р
11	17.6016	28.91	10.54	39.45	60.00	-20.55	QP	Р
12	17.6016	17.29	10.54	27.83	50.00	-22.17	AVG	Р

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No.: TW2206141-02E Page 12 of 34

Date: 2022-06-21




6 Radiated Emission Test

- 6.1 Test Method and test Procedure:
- (1) The EUT was tested according to ANSI C63.10-2013. The radiated test was performed at Timeway EMC Laboratory. This site is on file with the FCC laboratory division, Registration No. 744189
- (2) The EUT, peripherals were put on the turntable which table size is 1m x 1.5 m, table high 0.8 m. All set up is according to ANSI C63.10-2013.
- (3) The frequency spectrum from 30 MHz to 25 GHz was investigated. All readings from 30 MHz to 1 GHz are quasi-peak values with a resolution bandwidth of 120 kHz. All readings are above 1 GHz, peak values with a resolution bandwidth of 1 MHz (Note: for Fundamental frequency radiated emission measurement, RBW=3MHz, VBW=10MHz). Measurements were made at 3 meters.
- (4) The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency.
- (5) The antenna polarization: Vertical polarization and Horizontal polarization.

Block diagram of Test setup


For radiated emissions from 9kHz to 30MHz




Date: 2022-06-21



For radiated emissions from 30MHz to1GHz



For radiated emissions above 1GHz



- 6.2 Configuration of The EUT
 Same as section 5.3 of this report
- 6.3 EUT Operating Condition

 Same as section 5.4 of this report.

Report No.: TW2206141-02E Page 14 of 34

Date: 2022-06-21



6.4 Radiated Emission Limit

All emission from a digital device, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strength specified below:

A FCC Part 15 Subpart C Paragraph 15.249(a) Limit

Fundamental Frequency	Field Stre	ength of Fundame	ntal (3m)	Field Strength of Harmonics (3m)			
(MHz)	mV/m	dBu	V/m	uV/m	dBu	V/m	
2400-2483.5	50	94 (Average)	114 (Peak)	500	54 (Average)	74 (Peak)	

Note:

- 1. RF Field Strength (dBuV) = 20 log RF Voltage (uV)
- 2.Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.
- 3. The emission limit in this paragraph is based on measurement instrumentation employing an average detector.

B. Frequencies in restricted band are complied to limit on Paragraph 15.209.

Frequency Range (MHz)	Distance (m)	Field strength (dB μ V/m)				
0.009-0.490	3	20log(2400/F(kHz)) +40log (300/3)				
0.490-1.705	3	20log(24000/F(kHz)) +40log (30/3)				
1.705-30	3	69.5				
30-88	3	40.0				
88-216	3	43.5				
216-960	3	46.0				
Above 960	3	54.0				

Note:

- 1. RF Voltage (dBuV) = 20 log RF Voltage (uV)
- 2. In the Above Table, the tighter limit applies at the band edges.
- 3. Distance refers to the distance in meters between the measuring instrument antenna and the EUT
- 4. All scanning using PK detector. And the final emission level was get using QP detector for frequency range from 30-1000MHz.As to 1G-25G, the final emission level got using PK. For fundamental measurement, PK detector used.
- 5. For radiated emissions from 9kHz to 30MHz, the emission level is much less than the limit for more than 20dB. No necessary to take down the record.
- 6. Battery full charged during tests.

Report No.: TW2206141-02E Page 15 of 34

Date: 2022-06-21




6.5 Test result

A Fundamental & Harmonics Radiated Emission Data

Please refer to the following test plots for details: Low Channel-2402MHz

Horizontal




No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table (o)	Height	ANT	Verdict	
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)			(cm)			
1	2402	85.90	-3.57	114.0	-28.10	Peak	93.00	100	Horizontal	Pass	
2	4802.799	54.33	3.12	74.0	-19.67	Peak	73.00	100	Horizontal	Pass	
2**	4802.799	48.49	3.12	54.0	-5.51	AV	73.00	100	Horizontal	Pass	

Report No.: TW2206141-02E Page 16 of 34

Date: 2022-06-21



Vertical



No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)		(o)	(cm)		
1	2402	75.89	-3.57	114.0	-38.11	Peak	165.00	100	Vertical	Pass
2	4802.799	49.38	3.12	74.0	-24.62	Peak	337.00	100	Vertical	Pass


Report No.: TW2206141-02E Page 17 of 34

Date: 2022-06-21



Please refer to the following test plots for details: Middle Channel-2441MHz

Horizontal




No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)		(o)	(cm)		
1	2441	85.48	-3.57	114.0	-28.52	Peak	96.00	100	Horizontal	Pass
2	4883.529	52.40	3.20	74.0	-21.60	Peak	60.00	100	Horizontal	Pass

Report No.: TW2206141-02E Page 18 of 34

Date: 2022-06-21



Vertical



Ī	No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table (o)	Height	ANT	Verdict
		(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)			(cm)		
	1	2441	75.43	-3.57	114.0	-38.57	Peak	169.00	100	Vertical	Pass


Report No.: TW2206141-02E Page 19 of 34

Date: 2022-06-21



Please refer to the following test plots for details: High Channel-2480MHz

Horizontal




No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)		(o)	(cm)		
1	2480	85.29	-3.57	114.0	-28.71	Peak	97.00	100	Horizontal	Pass
2	4960.010	52.86	3.36	74.0	-21.14	Peak	314.00	100	Horizontal	Pass

Report No.: TW2206141-02E Page 20 of 34

Date: 2022-06-21



Vertical



152.00 Pass 2480 76.53 -3.57 114.0 -37.47 Peak 100 Vertical

Note: (2) Emission Level = Reading Level + Antenna Factor + Cable Loss-Amplifier

- (3) Margin=Emission-Limits
- (4) According to section 15.35(b), the peak limit is 20dB higher than the average limit
- (5) For test purpose, keep EUT continuous transmitting
- (5) For emission above 18GHz and Below 30MHz, It is only the floor noise. No necessary to take down.
- (6) the measured PK value less than the AV limit.

Date: 2022-06-21




B. General Radiated Emission Data Radiated Emission In Horizontal (30MHz----1000MHz)

EUT set Condition: Keep Tx transmitting

Results: Pass

Please refer to following diagram for individual



No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table (o)	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)			(cm)		
1	238.983	28.19	-12.41	46.0	-17.81	Peak	255.00	100	Horizontal	Pass
2	279.228	28.47	-11.53	46.0	-17.53	Peak	279.00	100	Horizontal	Pass
3	426.631	29.34	-8.21	46.0	-16.66	Peak	96.00	100	Horizontal	Pass
4	475.361	31.03	-7.43	46.0	-14.97	Peak	74.00	100	Horizontal	Pass
5	500.090	32.02	-6.91	46.0	-13.98	Peak	104.00	100	Horizontal	Pass
6	962.179	31.90	-1.59	54.0	-22.10	Peak	139.00	100	Horizontal	Pass

Report No.: TW2206141-02E Page 22 of 34

Date: 2022-06-21




Radiated Emission In Vertical (30MHz----1000MHz)

EUT set Condition: Keep Tx transmitting

Results: Pass

Please refer to following diagram for individual



No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)		(o)	(cm)		
1	41.152	21.57	-12.01	40.0	-18.43	Peak	261.00	100	Vertical	Pass
2	254.984	27.42	-11.94	46.0	-18.58	Peak	360.00	100	Vertical	Pass
3	276.803	23.77	-11.56	46.0	-22.23	Peak	288.00	100	Vertical	Pass
4	482.149	31.93	-7.35	46.0	-14.07	Peak	183.00	100	Vertical	Pass
5	510.030	33.29	-6.83	46.0	-12.71	Peak	150.00	100	Vertical	Pass
6	960.240	32.63	-1.63	54.0	-21.37	Peak	329.00	100	Vertical	Pass

Date: 2022-06-21




7. Band Edge

7.1 Test Method and test Procedure:

- (1) The EUT was tested according to ANSI C63.10–2013. The radiated test was performed at Timeway EMC Laboratory. This site is on file with the FCC laboratory division, Registration No. 744189
- (2) Set Spectrum as RBW=1MHz, VBW=3MHz and Peak detector used for PK value. RBW=1MHz, VBW=10Hz and Peak detector used for AV value.
- (3) The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency.
- (4) The antenna polarization: Vertical polarization and Horizontal polarization.

7. 2 Radiated Test Setup



For the actual test configuration, please refer to the related items – Photos of Testing

7.3 Configuration of The EUT

Same as section 5.3 of this report

7.4 EUT Operating Condition

Same as section 5.4 of this report.

7.5 Band Edge Limit


Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Report No.: TW2206141-02E Page 24 of 34






Report No.: TW2206141-02E Page 25 of 34



Product:	3 MODES PORTABLE MECHANICAL	Detector	Vertical
	KEYBOARD		
Mode	Keeping Transmitting	Test Voltage	DC3.7V
Temperature	24 deg. C,	Humidity	56% RH
Test Result:	Pass		




		1	1	1						
No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)		(o)	(cm)		
1	2401.917	75.77	-3.57	74.0	1.77	Peak	172.00	100	Vertical	Pass
2	2400.012	53.49	-3.57	74.0	-20.51	Peak	166.00	100	Vertical	Pass
2**	2400.012	37.07	-3.57	54.0	-16.93	AV	166.00	100	Vertical	Pass
3	2390.070	43.41	-3.53	74.0	-30.59	Peak	286.00	100	Vertical	Pass

Report No.: TW2206141-02E Page 26 of 34



Product:	3 MODES PORTABLE MECHANICAL KEYBOARD	Polarity	Horizontal
Mode	Keeping Transmitting	Test Voltage	DC3.7V
Temperature	24 deg. C,	Humidity	56% RH
Test Result:	Pass		



No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table (o)	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)			(cm)		
1	2480.055	85.28	-3.57	74.0	11.28	Peak	91.00	100	Horizontal	N/A
2	2483.587	54.45	-3.57	74.0	-19.55	Peak	91.00	100	Horizontal	Pass
2**	2483.587	38.70	-3.57	54.0	-15.30	AV	91.00	100	Horizontal	Pass

Report No.: TW2206141-02E Page 27 of 34

Date: 2022-06-21



	Product:	Product:			MECHANICA D	L	Detector			ıl	
	Mode		Keeping Transmitting Test Volt						DC3.7	C3.7V	
,	Temperature			24 deg. C.	,	Humidity 56%			56% R	6 RH	
	Test Result:			Pass							
Part 1:	LSC Class B 1GHz-18GHz	-2									
90 80 70	0-										
60 50 40 30 20	0-	Level Aladian in Aliji							الله المالية المرابط ا	de de constitue de la constitu	
50 40 30 20 10					2483.5 Frequency (MHz)		de de le			2500	
50 40 30 20 10	0-	Results	Factor	Limit	Frequency (MHz)	Detector	Table (o)	Height	ANT	2500 Verdie	
50 40 30 20 10	0-	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Frequency (MHz)	Detector	Table (o)	Height (cm)	ANT		
50 40 30 20 10	0- 0- 0- 0- 0- 0- 2470				Over Limit (dB)	Detector	Table (o)	_	ANT		

Note: The PK emission level less than the AV limit. No necessary to record the AV emission level.

Date: 2022-06-21



Page 28 of 34

8.0 Antenna Requirement

Applicable Standard

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

This product has a PCB antenna with gain -1.85dBi maximum. It fulfills the requirement of this section.

Test Result: Pass

Page 29 of 34

Report No.: TW2206141-02E



FSK Modulation	ì										
Product:	3 MODES PORTABLE MECHANICAL KEYBOARD					Test Mode:		Keep transmitting		transmitting	
Mode	Keeping Transmitting Test Voltage DC3.						C3.7V				
Temperature		24 d	eg. C,			Humid	ity 56% RH				
Test Result:		Pa	ass			Detect	or	PK			
0dB Bandwidth		912.0	00kHz								
Ref 10 dB	m 	*Att 20	O dB	*RBW 3 *VBW 1 SWT 5	00 kHz		2.401			1	
-0 -0 -0 AXH			\sim				1 (T1		2 dBm	A	
20		I	<i></i>	N	\	Temp		nds) -24.1: 456)0	ı		
-30						4					
40							M			3DB	
160 m									MM ~		
-70											
80 90											
Center 2.4 ate: 15.JUN.2	02 GHz		300	kHz/				Span	3 MHz		


Page 30 of 34

Report No.: TW2206141-02E

Date: 2022-06-21



GFSK Modulation							
Product:	3 MODES PORTABLE MECHANICAL	Test Mode:	V and tunnamitting				
Product:	KEYBOARD	rest wrode:	Keep transmitting				
Mode	Keeping Transmitting	Test Voltage	DC3.7V				
Temperature	24 deg. C,	Humidity	56% RH				
Test Result:	Pass	Detector	PK				
20dB Bandwidth	912.00kHz	-					



Date: 15.JUN.2022 18:16:12


Page 31 of 34

Report No.: TW2206141-02E

Date: 2022-06-21



GFSK Modulation							
Product:	3 MODES PORTABLE MECHANICAL	Test Mode:	Voor trongmitting				
Product.	KEYBOARD	rest wrode.	Keep transmitting				
Mode	Keeping Transmitting	Test Voltage	DC3.7V				
Temperature	24 deg. C,	Humidity	56% RH				
Test Result:	Pass	Detector	PK				
20dB Bandwidth	906.00kMHz	-	-				



Date: 15.JUN.2022 18:17:47

Report No.: TW2206141-02E Page 32 of 34

Date: 2022-06-21



10.0 FCC ID Label

FCC ID: TUVET-8568

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation

The label must not be a stick-on paper label. The label on these products must be permanently affixed to the product and readily visible at the time of purchase and must last the expected lifetime of the equipment not be readily detachable.

Mark Location:



Page 33 of 34

Report No.: TW2206141-02E

Date: 2022-06-21



11.0 Photo of testing


11.1 Conducted test View--



Date: 2022-06-21



Radiated emission test view



Photographs – EUT

Please refer test report TW2206141-01E

-- End of the report--

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.