

# RF Exposure Evaluation Report

Product Name : TG-BT5-IN

Model No. : TG-BT5-IN

FCC ID : TV7-TB5I

Applicant : Mikrotikls SIA

Address : Brīvības gatve 214i,Rīga LV-1039 Latvia

Date of Receipt : Apr. 09, 2021

Date of Declaration : May 12, 2021

Report No. : 2140201R-E3082100013

Report Version : V1.0



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration report of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF or any agency of the government.

The test report shall not be reproduced without the written approval of DEKRA Testing and Certification Co., Ltd.

Measurement uncertainties evaluated for each testing system and associated connections are given here to provide the system information for reference. Compliance determinations do not take into account measurement uncertainties for each testing system, but are based on the results of the compliance measurement.

Issued Date: May 12, 2021

Report No.: 2140201R-E3082100013



Product Name	TG-BT5-IN	
Applicant	Mikrotikls SIA	
Address	Brīvības gatve 214i, Rīga LV-1039 Latvia	
Manufacturer	Mikrotikls SIA	
Model No.	TG-BT5-IN	
FCC ID.	TV7-TB5I	
Trade Name	MikroTik	
Applicable Standard	KDB 447498 D01 v06	<input type="checkbox"/> Minimum test separation distance $\geq 20$ cm <input checked="" type="checkbox"/> For low power devices
Test Result	Complied	

Documented By :



( Senior Adm. Specialist / Joanne Lin )

Tested By :



( Senior Engineer / Wen Lee )

Approved By :



( Director / Vincent Lin )

---

## Revision History

Report No.	Version	Description	Issued Date
2140201R-E3082100013	V1.0	Initial issue of report.	2021-05-12

## 1. GENERAL INFORMATION

### 1.1. EUT Description

Product Name	TG-BT5-IN
Trade Name	MikroTik
Model No.	TG-BT5-IN
FCC ID.	TV7-TB5I
Frequency Range	2402-2480MHz
Channel Separation	2MHz
Channel Number	V5.0: 40CH
Type of Modulation	V5.0: GFSK (1Mbps, 2Mbps)
Antenna Type	PCB trace Antenna
Antenna Gain	Refer to the table "Antenna List"

#### Antenna List

No.	Manufacturer	Part No.	Antenna Type	Peak Gain
1	MikroTik	TG-IN-Trace	PCB trace Antenna	1.5dBi in 2.4 GHz

## 2. RF Exposure Evaluation

### 2.1. Standard Applicable

According to 1.1307 (b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

### 2.2. Measurement Result:

According to KDB Publication 447498 D01, section 4.3.1, per the calculations of item 1 ( $\text{Power(mW)}/\text{separation (mm)} \cdot \sqrt{f(\text{GHz})} \leq 3.0$ ), SAR is required as shown in the table below where calculated values are greater than 3.0:

Operation frequency = 2450MHz and antenna separation distance = 5mm

Body SAR Test Exclusion Threshold = 10mW

Frequency Band (MHz)	Maximum peak output power Peak Gain: 1.5dBi			SAR Test Exclusion Threshold	Calculated Threshold Value ( $\leq 3.0$ SAR is not required)
	conducted (dBm)	EIRP (dBm)	EIRP (mW)	(mW)	
2402	3.24	4.74	2.98	10	0.923

Note1: The SAR/MPE measurement is not necessary.

Note2: The maximum peak output power is refer to report No.: 2140201R-E3032110108 from the DEKRA.