

Mikrotik	Model:RB931-2nD	Test Number:	160414C			
MPE Calculator	MPE uses EIRP for calculation. EIRP is based on TX power added to the antenna gain in dBi. dBi = dB gain compared to an isotropic radiator. S = power density in mW/cm <sup>2</sup>					
		Output Power	dBd + 2.17 = dBi	Antenna Gain (dBi)	2.7	
Tx Frequency (MHz)	2437	Maximum (Watts)	0.097778	dBi to dBd	2.2	
				Antenna Gain (dBd)	0.53	
Cable Loss (dB)	0.0	(dBm)	19.9	Antenna minus cable (dBd)	2.70	
	Calculated ERP (mw)	110.470	EIRP = Po(dBm) + Gain (dB)			
	Calculated EIRP (mw)	182.072		Radiated (EIRP) dBm	22.602	
		Power density (S)	EIRP = EIRP - 2.17 dB	Radiated (ERP) dBm	20.432	
		EIRP ----- = mW/cm <sup>2</sup> 4 π r <sup>2</sup>				
		EIRP (mW), r (cm)				
	<b>Occupational Limit</b>	FCC radio frequency radiation exposure limits per 1.1310				
	5	mW/cm <sup>2</sup>	Frequency (MHz)	Occupational Limit (mW/cm <sup>2</sup> )	Public Limit (mW/cm <sup>2</sup> )	
	50	W/m <sup>2</sup>	300-1,500	ƒ300	ƒ1500	
		<b>General Public Limit</b>	1,500-10,000	5	1	
	1	mW/cm <sup>2</sup>				
	10	W/m <sup>2</sup>				
		<b>Occupational Limit</b>	IC radio frequency radiation exposure limits per RSS-102			
	0.6455 <sup>0.5</sup>	W/m <sup>2</sup>	Frequency (MHz)	Occupational Limit (W/m <sup>2</sup> )	Public Limit (W/m <sup>2</sup> )	
	0.95332	W/m <sup>2</sup>	100-6,000	0.6455 <sup>0.5</sup>		
		<b>General Public Limit</b>	6,000-15,000	50		
	0.02619 <sup>0.6834</sup>	W/m <sup>2</sup>	48-300		1.291	
	5.40397	W/m <sup>2</sup>	300-6,000		0.02619 <sup>0.6834</sup>	
			6,000-15,000	50	10	
EIRP	S	S	Distance	Distance	Distance	Distance
milliwatts	mW/cm <sup>2</sup>	W/m <sup>2</sup>	cm	meter	inches	Feet
182.072	0.00179	0.01789	90.00	0.90	35.43	2.95
182.072	0.00226	0.02264	80.00	0.80	31.50	2.62
182.072	0.00296	0.02957	70.00	0.70	27.56	2.30
182.072	0.00402	0.04025	60.00	0.60	23.62	1.97
182.072	0.00580	0.05796	50.00	0.50	19.69	1.64
182.072	0.00906	0.09056	40.00	0.40	15.75	1.31
182.072	0.01610	0.16099	30.00	0.30	11.81	0.98
182.072	0.03622	0.36222	20.00	0.20	7.87	0.66
182.072	0.09273	0.92728	12.50	0.13	4.92	0.41
182.072	0.22639	2.26388	8.00	0.08	3.15	0.26
182.072	0.40247	4.02467	6.00	0.060	2.36	0.20
182.072	0.49687	4.96873	5.40	0.054	2.13	0.18
182.072	0.57955	5.79553	5.00	0.050	1.97	0.16
182.072	0.95259	9.52586	3.90	0.039	1.54	0.13
182.072	1.60987	16.09870	3.00	0.030	1.18	0.10
182.072	4.47186	44.71860	1.80	0.018	0.71	0.06
182.072	14.48883	144.88826	1.00	0.010	0.39	0.03
			Frequency (MHz)	Occupational Limit minimum Distance (meters)	Public Limit minimum distance (meters)	
			47CFR 1.1310	0.20	0.20	
			RSS-102	0.20	0.20	

Rogers Labs, Inc.  
4405 W. 259th Terrace  
Louisburg, KS 66053  
Phone/Fax: (913) 837-3214  
Revision 1

Mikrotik SIA  
Model: RB931-2nD  
Test #: 160414C  
Test to: 47CFR 15.247, RSS-247  
File: RB931-2nD RFExp

S/N: 678E01DC4C3F/612  
FCC ID#: TV7931-2ND  
IC: 7442A-9312ND  
Date: October 31, 2016  
Page 1 of 1