

Mikrotik	RBmAPL-2nD	Test Number:	150730A-151104			
MPE Calculator	MPE uses EIRP for calculation. EIRP is based on TX power added to the antenna gain in dBi. dBi = dB gain compared to an isotropic radiator. S = power density in mW/cm ²					
				Antenna Gain (dBi)	1.2	
		Output Power		dBd + 2.17 = dBi	2.2	
Tx Frequency (MHz)	2437	Maximum (Watts)	0.16111	Antenna Gain (dBd)	-0.97	
Cable Loss (dB)	0.0	(dBm)	22.1	Antenna minus cable (dB)	1.20	
Calculated ERP (mw)	128.861			EIRP = Po(dBm) + Gain (dB)		
Calculated EIRP (mw)	212.384			Radiated (EIRP) dBm	23.271	
				ERP = EIRP - 2.17 dB		
Occupational Limit	5 W/m ²	<div style="border: 1px solid black; padding: 5px;"> Power density (S) EIRP ----- = mW/cm² $4 \pi r^2$ r (cm) EIRP (mW) </div>		Radiated (ERP) dBm	21.101	
General Public Limit	1 W/m ²					
FCC radio frequency radiation exposure limits per 1.1310						
	Frequency (MHz)	Occupational Limit (W/m ²)	Public Limit (W/m ²)			
	300-1,500	f/300	f/1500			
	1,500-10,000	5	1			
IC radio frequency radiation exposure limits per RSS-102						
	Frequency (MHz)	Occupational Limit (W/m ²)	Public Limit (W/m ²)			
Occupational Limit	0.6455f ^{0.5} W/m ²					
	31.86574 W/m ²	0.6455f ^{0.5}				
General Public Limit	0.02619f ^{0.6834} W/m ²	6,000-15,000	50			
	5.40397 W/m ²	48-300		1.291		
		300-6,000		0.02619f ^{0.6834}		
		6,000-15,000	50	10		
EIRP	S	S	Distance	Distance	Distance	Distance
milliwatts	mW/cm ²	W/m ²	cm	meter	inches	Feet
212.384	0.00209	0.02087	90.00	0.90	35.43	2.95
212.384	0.00264	0.02641	80.00	0.80	31.50	2.62
212.384	0.00345	0.03449	70.00	0.70	27.56	2.30
212.384	0.00469	0.04695	60.00	0.60	23.62	1.97
212.384	0.00676	0.06760	50.00	0.50	19.69	1.64
212.384	0.01056	0.10563	40.00	0.40	15.75	1.31
212.384	0.01878	0.18779	30.00	0.30	11.81	0.98
212.384	0.04225	0.42252	20.00	0.20	7.87	0.66
212.384	0.10001	1.00006	13.00	0.13	5.12	0.43
212.384	0.20865	2.08654	9.00	0.09	3.54	0.30
212.384	0.26408	2.64078	8.00	0.080	3.15	0.26
212.384	0.34492	3.44918	7.00	0.070	2.76	0.23
212.384	0.46947	4.69471	6.00	0.060	2.36	0.20
212.384	0.53893	5.38934	5.60	0.056	2.20	0.18
212.384	1.05631	10.56310	4.00	0.040	1.57	0.13
212.384	1.87788	18.77885	3.00	0.030	1.18	0.10
212.384	2.93419	29.34195	2.40	0.024	0.94	0.08
		Frequency (MHz)	Occupational Limit minimum Distance (meters) FCC Limits	Occupational Limit minimum Distance (Meters) IC Limits	Public Limit minimum distance (meters) FCC Limits	Public Limit minimum distance (Meters) IC Limits
		300-1,500	N/A	N/A	N/A	N/A
		1,500-10,000	0.06	0.02	0.13	0.06

Rogers Labs, Inc.
 4405 W. 259th Terrace
 Louisburg, KS 66053
 Phone/Fax: (913) 837-3214
 Revision 1

Mikrotiks SIA
 Model: RBmAP L-2nD
 Test #: 150730A-151104
 Test to: 47CFR 15.247, RSS-247
 File: RBmAPL2ND RFExp

S/N: 642A01DDE062
 FCC ID#: TV7MAPL2ND
 IC: 7442A-MAPL2ND
 Date: December 20, 2015
 Page 1 of 1