

# Submittal Application Report

FOR  
GRANT OF CERTIFICATION

FOR


Model: RouterBOARD Metal 9HPn  
912-917 MHz  
Single Input Single Output  
Broadband Digital Transmission System  
FCC ID: TV7METAL9HPN


FOR

**MIKROTIKLS SIA**

Pernavas 46  
Riga, Latvia LV-1009

Test Report Number: 140407

Authorized Signatory:   
Scot D. Rogers



**ROGERS LABS, INC.**

4405 West 259<sup>th</sup> Terrace  
 Louisburg, KS 66053  
 Phone / Fax (913) 837-3214

**Engineering Test Report for  
 Grant of Certification Application**

FOR  
 CFR 47, PART 15C - Intentional Radiators  
 CFR 47 Paragraph 15.247  
 License Exempt Intentional Radiator

For

**MIKROTIKLS SIA**

Pernavas 46  
 Riga, Latvia LV-1009

SISO Broadband Digital Transmission System

Model: RouterBOARD Metal 9HPn  
 Frequency Range 912-917 MHz  
 FCC ID#: TV7METAL9HPN

Test Date: April 7, 2014

Certifying Engineer: *Scot D. Rogers*  
 Scot D. Rogers  
 Rogers Labs, Inc.  
 4405 West 259<sup>th</sup> Terrace  
 Louisburg, KS 66053  
 Telephone/Facsimile: (913) 837-3214

This report shall not be reproduced except in full, without the written approval of the laboratory.  
 This report must not be used by the client to claim product endorsement by NVLAP, NIST, or  
 any agency of the U.S. Government.



# Table Of Contents

**TABLE OF CONTENTS..... 3**

**REVISIONS..... 4**

**FORWARD ..... 5**

**OPINION / INTERPRETATION OF RESULTS ..... 5**

**EQUIPMENT TESTED..... 5**

**Equipment Function .....6**

**Equipment Configuration.....6**

**APPLICATION FOR CERTIFICATION..... 7**

**APPLICABLE STANDARDS & TEST PROCEDURES ..... 8**

**EQUIPMENT TESTING PROCEDURES ..... 8**

**AC Line Conducted Emission Test Procedure .....8**

**Radiated Emission Test Procedure.....8**

        Diagram 1 Test arrangement for Conducted emissions .....9

        Diagram 2 Test arrangement for radiated emissions of tabletop equipment.....10

        Diagram 3 Test arrangement for radiated emissions tested on Open Area Test Site (OATS).....11

**TEST SITE LOCATIONS ..... 11**

**LIST OF TEST EQUIPMENT ..... 12**

**UNITS OF MEASUREMENTS ..... 13**

**ENVIRONMENTAL CONDITIONS..... 13**

**STATEMENT OF MODIFICATIONS AND DEVIATIONS ..... 13**

**INTENTIONAL RADIATORS..... 13**

**Antenna Requirements .....13**

**Restricted Bands of Operation.....14**

        Table 1 General Radiated Emissions in Restricted Bands Data .....14

        Table 2 Harmonic Radiated Emissions in Restricted Bands Data (TG-Y915-17).....15

**Summary of Results for Radiated Emissions in Restricted Bands .....15**

**AC Line Conducted Emissions Procedure .....16**

        Figure 1 AC Line Conducted Emissions Line 1 .....17

        Figure 2 AC Line Conducted Emissions Line 2 .....17

        Table 3 AC Line Conducted Emissions Data (Highest Emissions) Line L1 .....18

        Table 4 AC Line Conducted Emissions Data (Highest Emissions) Line L2 .....18

**Summary of Results for AC Line Conducted Emissions .....18**

**General Radiated Emissions Procedure.....19**



Table 5 General Radiated Emissions from EUT Data (Highest Emissions) .....20

**Summary of Results for General Radiated Emissions .....20**

**Operation in the Band 2400 – 2483.5 MHz .....21**

Table 6 Transmitter Antenna port Conducted Emissions Data (Total Highest) .....21

Table 7 Transmitter Antenna Conducted Emissions Data .....21

Figure 3 Plot of Transmitter Emissions (Across Operational Band, b/g/n Mode) .....22

Figure 4 Plot of Transmitter Emissions (Across Operational Band, g Mode) .....22

Figure 5 Plot of Low Band Edge (b/g/n Mode) .....23

Figure 6 Plot of High Band Edge (b/g/n Mode) .....23

Figure 7 Plot of Occupied Bandwidth (b/g/n Mode) .....24

Figure 8 Plot of Occupied Bandwidth (g Mode) .....24

**Transmitter Emissions Data.....25**

Table 8 Transmitter Radiated Emission (TG-Y915-17) .....25

**Summary of Results for Transmitter Radiated Emissions of Intentional Radiator .....25**

**ANNEX..... 26**

**Annex A Measurement Uncertainty Calculations .....27**

**Annex B Rogers Labs Test Equipment List.....28**

**Annex C Rogers Qualifications .....29**

**Annex D FCC Site Registration Letter.....30**

**Annex E Industry Canada Site Registration Letter .....31**

## Revisions

Revision 1, Issued April 15, 2014



## Forward

The following information is submitted for consideration in obtaining Grant of Certification for License Exempt Digital Transmission System Intentional Radiator operating under CFR 47 Paragraph 15.247.

Name of Applicant: Mikrotiks SIA  
 Pernavas 46  
 Riga, Latvia LV-1009

Model: RouterBOARD Metal 9HPn FCC ID: TV7METAL9HPN FRN: 0014 43 1100

Frequency Range: 912-917 MHz (802.11b/g/n mode operation)

Total Operating Power: 0.5 watt

## Opinion / Interpretation of Results

Tests Performed	Margin (dB)	Results
Emissions as per CFR 47 paragraphs 2 and 15.205	-21.7	Complies
Emissions as per CFR 47 paragraphs 2 and 15.207	-7.7	Complies
Emissions as per CFR 47 paragraphs 2 and 15.209	-2.7	Complies
Harmonic Emissions per CFR 47 15.247	-21.0	Complies
Peak Power Spectral Density per CFR 47 15.247	-4.8	Complies

## Equipment Tested


<u>Equipment</u>	<u>Model</u>	<u>SN</u>	<u>FCC I.D.</u>
EUT	RouterBOARD Metal 9HPn	4D2B0251F36E/405	TV7METAL9HPN
AC Adapter	FLD181-240075-U	N/A	N/A
Laptop Computer	Dell Latitude	6CD35Q1	N/A

<u>Antenna/Type</u>	<u>Model</u>	<u>Gain</u>
Yagi	TG-Y915-17	17 dBi

### **Equipment Function**

The EUT is a 912-917 MHz 1x1 SISO Digital Transmission System used to transmit data in applications offering broadband wireless connectivity for point-to-point communications. The design provides N-style antenna connection port for use with authorized antenna systems. For testing purposes, the EUT was connected to the manufacturer supplied Power Over Ethernet (POE) adapter and AC/DC power supply and communicating to the laptop computer through the Ethernet network interface. This configuration offered operational control of the transmitter and communications over the network interface between the EUT and supporting computer system. The RouterBOARD Metal 9HPn offers single Ethernet port for connection with the POE network interface. No other interfacing options are provided. For testing purposes, the RouterBOARD Metal 9HPn received powered from the AC/DC adapter and POE interface and was configured to transmit in available modes. The antenna system complies with requirements for unique antenna connection when installed by professional installer.

### **Equipment Configuration**



## Application for Certification

- (1) Manufacturer: Mikrotikls SIA  
Pernavas 46  
Riga, Latvia LV-1009
- (2) Identification: Model: RouterBOARD Metal 9HPn  
FCC I.D.: TV7METAL9HPN
- (3) Instruction Book:  
Refer to Exhibit for Instruction Manual.
- (4) Description of Circuit Functions:  
Refer to Exhibit of Operational Description.
- (5) Block Diagram with Frequencies:  
Refer to Exhibit of Operational Description.
- (6) Report of Measurements:  
Report of measurements follows in this Report.
- (7) Photographs: Construction, Component Placement, etc.:  
Refer to Exhibit for photographs of equipment.
- (8) List of Peripheral Equipment Necessary for operation. The equipment operates from power received from the supporting Power Over Ether (POE) and AC/DC adapter. The EUT provides single connection point for the POE network interface and incorporates single N-style antenna connector. The EUT is produced with n-style antenna port connector for use with authorized antenna systems. During testing, the EUT was powered through the POE adapter and AC/DC adapter.
- (9) Transition Provisions of CFR47 15.37 are not requested
- (10) Not Applicable. The unit is not a scanning receiver.
- (11) Not Applicable. The EUT does not operate in the 59 – 64 GHz frequency band.
- (12) The equipment is not software defined and this section is not applicable.

## **Applicable Standards & Test Procedures**

In accordance with the Federal Communications Code of Federal Regulations, dated October 1, 2013, Part 2, Subpart J, Paragraphs 2.907, 2.911, 2.913, 2.925, 2.926, 2.1031 through 2.1057, and applicable parts of paragraph 15, Part 15C Paragraph 15.212 and 15.247 the following information is submitted. Test procedures used are the established Methods of Measurement of Radio-Noise Emissions as described in ANSI C63.4-2009, ANSI C63.10-2009, KDB 558074 D01 v03r1, and KDB 913591. Testing for the AC line-conducted and radiated emissions were performed as defined in section 6 of ANSI C63.10-2009.

## **Equipment Testing Procedures**


### ***AC Line Conducted Emission Test Procedure***

Testing for the AC line-conducted emissions was performed as defined in ANSI C63.10-2009. The test setup, including the EUT, was arranged in the test configurations as presented during testing. The test configuration was placed on a 1 x 1.5-meter wooden bench, 0.8 meters high located in a screen room. The power lines of the system were isolated from the power source using a standard LISN with a 50- $\mu$ Hy choke. EMI was coupled to the spectrum analyzer through a 0.1  $\mu$ F capacitor internal to the LISN. The LISN was positioned on the floor beneath the wooden bench supporting the EUT. The power lines and cables were draped over the back edge of the table. Refer to diagram 1 showing typical test arrangement and photographs in exhibits for EUT placement used during testing.

### ***Radiated Emission Test Procedure***


The EUT was placed on a rotating 1 x 1.5-meter wooden platform, 0.8 meters above the ground plane at a distance of 3 meters from the FSM antenna. Radiated emissions testing was performed as required in CFR47 15, RSS-210 and specified in sections 6 and 7 of ANSI C63.10-2009. EMI energy was maximized by equipment placement, raising and lowering the FSM antenna, changing the antenna polarization, and by rotating the turntable. Each emission was maximized before data was taken using a spectrum analyzer. The frequency spectrum from 9 kHz to 25,000 MHz was searched for during preliminary investigation. Refer to diagrams 2 and 3 showing typical test arrangement and photographs in the test setup exhibits for specific EUT placement during testing.






1. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 cm to 40 cm long see (see 6.2.3.1).
2. I/O cables that are not connected to an accessory shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m (see 6.2.2).
3. EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50  $\Omega$  loads. LISN can be placed on top of, or immediately beneath, reference ground plane (see 6.2.2 and 6.2.3).
  - 3.1 All other equipment powered from additional LISN(s).
  - 3.2 Multiple-outlet strip can be used for multiple power cords of non-EUT equipment.
  - 3.3 LISN at least 80 cm from nearest part of EUT chassis.
4. Non-EUT components of EUT system being tested.
5. Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop (see 6.2.3.1).
6. Edge of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane (see 6.2.2 for options).
7. Antenna may be integral or detachable. If detachable, the antenna shall be attached for this test.

**Diagram 1 Test arrangement for Conducted emissions**



1. A LISN is optional for radiated measurements between 30 MHz to 1000 MHz, but not allowed for measurements below 30 MHz and above 1000 MHz. (See 6.4.3, 6.5.1, and 6.6.3.). If used, connect EUT to one LISN. Unused LISN measuring port connectors shall be terminated in 50Ω. LISN can be placed on top of, or immediately beneath, reference ground plane (see 6.2.2 and 6.2.3.1).
  - 1.1 LISN spaced at least 80 cm from nearest part of EUT chassis.
2. The EUT shall be placed in the center of the table to the extent possible. (See 6.2.3.1 and 6.3.4).
3. A vertical conducting plane, if used for conducted tests per 6.2.2, shall be removed for radiated emission tests.
4. Antenna may be integral or detachable, depending on the EUT.
5. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 cm to 40 cm long.

**Diagram 2 Test arrangement for radiated emissions of tabletop equipment**



Frequency: 9 kHz-30 MHz	Frequency: 30 MHz- 1 GHz	Frequency: Above 1 GHz
RBW = 9 kHz	RBW = 120 kHz	RBW = 1 MHz
VBW = 30 kHz	VBW = 120 kHz	VBW = 1 MHz
Sweep time = Auto	Sweep time = Auto	Sweep time = Auto
Detector = PK, QP	Detector = PK, QP	Detector = PK, AV

**Diagram 3 Test arrangement for radiated emissions tested on Open Area Test Site (OATS)**

### Test Site Locations

Conducted EMI	The AC power line conducted emissions testing performed in a shielded screen room located at Rogers Labs, Inc., 4405 W. 259 <sup>th</sup> Terrace, Louisburg, KS
Radiated EMI	The radiated emissions tests were performed at the 3 meters, Open Area Test Site (OATS) located at Rogers Labs, Inc., 4405 W. 259 <sup>th</sup> Terrace, Louisburg, KS
Site Registration	Refer to Annex for Site Registration Letters
NVLAP Accreditation	Lab code 200087-0

## List of Test Equipment

A Rohde and Schwarz ESU40 and/or Hewlett Packard 8591EM was used as the measuring device for the emissions testing of frequencies below 1 GHz. A Rohde and Schwarz ESU40 and/or Hewlett Packard 8562A Spectrum Analyzer was used as the measuring device for testing the emissions at frequencies above 1 GHz. The analyzer settings used are described in the following table. Refer to the appendix for a complete list of test equipment.

AC Line Conducted Emissions (0.150 -30 MHz)		
RBW	AVG. BW	Detector Function
9 kHz	30 kHz	Peak / Quasi Peak
Emissions (30-1000 MHz)		
RBW	AVG. BW	Detector Function
120 kHz	300 kHz	Peak / Quasi Peak
Emissions (Above 1000 MHz)		
RBW	Video BW	Detector Function
100 kHz	100 kHz	Peak
1 MHz	1 MHz	Peak / Average

<u>Equipment</u>	<u>Manufacturer</u>	<u>Model (SN)</u>	<u>Band</u>	<u>Cal Date</u>	<u>Due</u>
<input checked="" type="checkbox"/> LISN	Comp. Design	FCC-LISN-2-MOD.CD (126)	.15-30MHz	10/13	10/14
<input checked="" type="checkbox"/> Cable	Time Microwave	750HF290-750 (L10M)	9kHz-40 GHz	10/13	10/14
<input checked="" type="checkbox"/> Cable	Belden	RG-58 (L1-CAT3-11509)	9kHz-30 MHz	10/13	10/14
<input checked="" type="checkbox"/> Cable	Belden	RG-58 (L2-CAT3-11509)	9kHz-30 MHz	10/13	10/14
<input type="checkbox"/> Antenna	ARA	BCD-235-B (169)	20-350MHz	10/13	10/14
<input type="checkbox"/> Antenna	EMCO	3147 (40582)	200-1000MHz	10/13	10/14
<input checked="" type="checkbox"/> Antenna	Com Power	AH-118 (10110)	1-18 GHz	10/13	10/14
<input checked="" type="checkbox"/> Antenna	Com Power	AH-840 (101046)	18-40 GHz	5/13	5/14
<input checked="" type="checkbox"/> Antenna	EMCO	6509 (9502-1374)	.001-30 MHz	10/13	10/14
<input checked="" type="checkbox"/> Antenna	Sunol	JB-6 (A100709)	30-1000 MHz	10/13	10/14
<input checked="" type="checkbox"/> Antenna	Standard	FXRY638A (621786)	10-18 GHz	5/13	5/14
<input type="checkbox"/> Antenna	EMCO	3143 (9607-1277)	20-1200 MHz	5/13	5/14
<input type="checkbox"/> Analyzer	HP	8591EM (3628A00871)	9kHz-1.8GHz	5/13	5/14
<input type="checkbox"/> Analyzer	HP	8562A (3051A05950)	9kHz-110GHz	5/13	5/14
<input checked="" type="checkbox"/> Analyzer	Rohde & Schwarz	ESU40 (100108)	20Hz-40GHz	5/13	5/14
<input checked="" type="checkbox"/> Amplifier	Com-Power	PA-010 (171003)	100Hz-30MHz	10/13	10/14
<input checked="" type="checkbox"/> Amplifier	Com-Power	CPPA-102 (01254)	1-1000 MHz	10/13	10/14
<input checked="" type="checkbox"/> Amplifier	Com-Power	PAM-118A (551014)	0.5-18 GHz	10/13	10/14



## Units of Measurements

Conducted EMI      Data is in dB $\mu$ V; dB referenced to one microvolt

Radiated EMI      Data is in dB $\mu$ V/m; dB/m referenced to one microvolt per meter

Sample Calculation:

RFS = Radiated Field Strength, FSM = Field Strength Measured

A.F. = Receive antenna factor, Gain = amplification gains and/or cable losses

RFS (dB $\mu$ V/m @ 3m) = FSM (dB $\mu$ V) + A.F. (dB) - Gain (dB)

## Environmental Conditions

Ambient Temperature	22.4° C
Relative Humidity	33%
Atmospheric Pressure	1006.6 mb

## Statement of Modifications and Deviations

No modifications to the EUT were required for the unit to demonstrate compliance with the CFR47 Part 15C emissions standards. There were no deviations to the specifications.

## Intentional Radiators

As per CFR47, Subpart C, paragraph 15.247 the following information is submitted.

### ***Antenna Requirements***

The EUT utilizes N-style connector for use with authorized antenna systems. The antenna connection point requires professional installation to comply with the unique antenna connection requirements. As such, the EUT is limited to professional installations only. The requirements of 15.203 are fulfilled; there are no deviations or exceptions to the specification.

### **Restricted Bands of Operation**

Spurious emissions falling in the restricted frequency bands of operation were measured at the OATS. The EUT utilizes frequency, determining circuitry, which generates harmonics falling in the restricted bands. Emissions were investigated at the OATS, using appropriate antennas or pyramidal horns, amplification stages, and a spectrum analyzer. Peak and average amplitudes of frequencies above 1000 MHz were compared to the required limits with worst-case data presented below. Test procedures of ANSI C63.4-2009 paragraphs 13.1 and 8.3.1.2 and KDB 558074 paragraph 10.2 were used during testing. No other significant emission was observed which fell into the restricted bands of operation. Computed emission values take into account the received radiated field strength, receive antenna correction factor, amplifier gain stage, and test system cable losses.

**Table 1 General Radiated Emissions in Restricted Bands Data**

Frequency in MHz	Horizontal Peak (dBμV/m)	Horizontal Quasi-Peak (dBμV/m)	Horizontal Average (dBμV/m)	Vertical Peak (dBμV/m)	Vertical Quasi-Peak (dBμV/m)	Vertical Average (dBμV/m)	Limit @ 3m (dBμV/m)
108.8	40.7	38.2	N/A	43.5	40.2	N/A	43.5
112.8	41.5	38.8	N/A	40.4	37.8	N/A	43.5
114.2	39.2	36.2	N/A	37.6	34.2	N/A	43.5
115.6	38.8	34.9	N/A	34.8	33.1	N/A	43.5
117.1	36.6	32.8	N/A	33.8	30.1	N/A	43.5

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded above for frequency range of 30-1000 MHz. Peak and Average amplitude emissions are recorded above for frequency range above 1000 MHz.

**Table 2 Harmonic Radiated Emissions in Restricted Bands Data (TG-Y915-17)**

Frequency in MHz	Horizontal Peak (dB $\mu$ V/m)	Horizontal Quasi-Peak (dB $\mu$ V/m)	Horizontal Average (dB $\mu$ V/m)	Vertical Peak (dB $\mu$ V/m)	Vertical Quasi-Peak (dB $\mu$ V/m)	Vertical Average (dB $\mu$ V/m)	Limit @ 3m (dB $\mu$ V/m)
2736.0	59.4	N/A	28.8	42.2	N/A	28.8	54.0
2751.0	58.3	N/A	29.0	42.1	N/A	29.0	54.0
3648.0	54.0	N/A	31.1	43.7	N/A	31.0	54.0
3668.0	58.9	N/A	31.2	43.1	N/A	31.2	54.0
4560.0	59.9	N/A	32.3	44.6	N/A	32.3	54.0
4585.0	60.1	N/A	31.9	44.2	N/A	31.9	54.0
5472.0	57.6	N/A	31.7	44.3	N/A	31.7	54.0

Other emissions present had amplitudes at least 20 dB below the limit.

Peak and Quasi-Peak amplitude emissions are recorded above for frequency range of 30-1000 MHz. Peak and Average amplitude emissions are recorded in tables above for frequency range above 1000 MHz.

**Summary of Results for Radiated Emissions in Restricted Bands**

The EUT demonstrated compliance with the radiated emissions requirements of 47CFR Part 15C Intentional Radiators. The EUT demonstrated a worst-case minimum margin of -3.3 dB below the radiated emissions requirements in restricted frequency bands. Peak, Quasi-peak, and average amplitudes were checked for compliance with the regulations. Worst-case emissions are reported with other emissions found in the restricted frequency bands at least 20 dB below the requirements.



### ***AC Line Conducted Emissions Procedure***

The EUT was arranged in a typical equipment configuration and placed on a 1 x 1.5-meter wooden bench 80 cm above the conducting ground plane, floor of a screen room. The bench was positioned 40 cm away from the wall of the screen room. The LISN was positioned on the floor of the screen room 80-cm from the rear of the EUT. The manufacturer supplied AC power cord for the POE supporting the EUT was connected to the LISN. A second LISN was positioned on the floor of the screen room 80-cm from the rear of the supporting equipment of the EUT. All power cords except the EUT were then powered from the second LISN. EMI was coupled to the spectrum analyzer through a 0.1  $\mu$ F capacitor, internal to the LISN. Power line conducted emissions testing were carried out individually for each current carrying conductor of the EUT. The excess length of lead between the system and the LISN receptacle was folded back and forth to form a bundle not exceeding 40 cm in length. The screen room, conducting ground plane, analyzer, and LISN were bonded together to the protective earth ground. Preliminary testing was performed to identify the frequency of each radio frequency emission displaying the highest amplitude. The cables were repositioned to obtain maximum amplitude of measured EMI level. Once the worst-case configuration was identified, plots were made of the EMI from 0.15 MHz to 30 MHz then the data was recorded with maximum conducted emissions levels. Refer to figures one and two for plots of the AC Power Line conducted emissions of the computer systems supporting the EUT.






Figure 1 AC Line Conducted Emissions Line 1




Figure 2 AC Line Conducted Emissions Line 2

**Table 3 AC Line Conducted Emissions Data (Highest Emissions) Line L1**

Trace	Frequency	Level (dBµV)	Detector	Delta Limit/dB
2	266.000000000 kHz	35.22	Average	-16.02
1	390.000000000 kHz	48.82	Quasi Peak	-9.24
2	394.000000000 kHz	40.20	Average	-7.78
2	470.000000000 kHz	36.32	Average	-10.20
1	478.000000000 kHz	46.45	Quasi Peak	-9.92
2	654.000000000 kHz	36.78	Average	-9.22
1	658.000000000 kHz	46.21	Quasi Peak	-9.79
1	742.000000000 kHz	45.13	Quasi Peak	-10.87
1	1.230000000 MHz	45.33	Quasi Peak	-10.67
2	1.410000000 MHz	25.63	Average	-20.37
2	1.566000000 MHz	31.22	Average	-14.78
1	1.566000000 MHz	45.42	Quasi Peak	-10.58
1	2.070000000 MHz	44.41	Quasi Peak	-11.59

Other emissions present had amplitudes at least 20 dB below the limit.

**Table 4 AC Line Conducted Emissions Data (Highest Emissions) Line L2**

Trace	Frequency	Level (dBµV)	Detector	Delta Limit/dB
2	202.000000000 kHz	33.92	Average	-19.61
2	266.000000000 kHz	35.89	Average	-15.35
1	390.000000000 kHz	49.03	Quasi Peak	-9.04
2	394.000000000 kHz	39.50	Average	-8.47
2	470.000000000 kHz	35.28	Average	-11.24
1	478.000000000 kHz	45.86	Quasi Peak	-10.52
2	654.000000000 kHz	35.08	Average	-10.92
1	654.000000000 kHz	45.76	Quasi Peak	-10.24
1	754.000000000 kHz	43.68	Quasi Peak	-12.32
1	1.198000000 MHz	43.10	Quasi Peak	-12.90
1	1.546000000 MHz	43.74	Quasi Peak	-12.26
2	1.574000000 MHz	28.20	Average	-17.80
1	2.126000000 MHz	42.15	Quasi Peak	-13.85

Other emissions present had amplitudes at least 20 dB below the limit.

**Summary of Results for AC Line Conducted Emissions**

The EUT demonstrated compliance to the conducted emissions requirements of CFR47 Part 15C equipment. The EUT system demonstrated minimum margin of -7.7 dB below the limit.

Measurements were taken using the peak, quasi peak, and average, measurement function for each emissions amplitude and were below the limits stated in the specification. Other emissions were present with recorded data representing worst-case amplitudes.



### **General Radiated Emissions Procedure**

The EUT was arranged in a typical equipment configuration and operated through all available modes with worst-case data recorded. Preliminary testing was performed in a screen room with the EUT positioned 1 meter from the FSM. Radiated emissions measurements were performed to identify the frequencies, which produced the highest emissions. Each radiated emission was then maximized at the OATS location before final radiated emissions measurements were performed. Final data was taken with the EUT located at the OATS at a distance of 3 meters between the EUT and the receiving antenna. The frequency spectrum from 9 kHz to 25,000 MHz was searched for general radiated emissions. Measured emission levels were maximized by EUT placement on the table, rotating the turntable through 360 degrees, varying the antenna height between 1 and 4 meters above the ground plane and changing antenna position between horizontal and vertical polarization. Antennas used were Loop from 9 kHz to 30 MHz, Broadband Biconical from 30 to 200 MHz, Biconilog from 30 to 1000 MHz, Log Periodic from 200 MHz to 1 GHz and or double Ridge or pyramidal horns and mixers from 1 GHz to 40 GHz, notch filters and appropriate amplifiers and external mixers were utilized.

**Table 5 General Radiated Emissions from EUT Data (Highest Emissions)**

Frequency in MHz	Horizontal Peak (dBµV/m)	Horizontal Quasi-Peak (dBµV/m)	Horizontal Average (dBµV/m)	Vertical Peak (dBµV/m)	Vertical Quasi-Peak (dBµV/m)	Vertical Average (dBµV/m)	Limit @ 3m (dBµV/m)
77.2	38.7	37.3	N/A	37.0	35.6	N/A	40.0
79.3	36.5	32.9	N/A	35.2	32.5	N/A	40.0
104.7	42.5	39.8	N/A	43.1	40.8	N/A	43.5
106.7	40.5	37.4	N/A	44.0	40.8	N/A	43.5
108.8	40.7	38.2	N/A	43.5	40.2	N/A	43.5
112.8	41.5	38.8	N/A	40.4	37.8	N/A	43.5
114.2	39.2	36.2	N/A	37.6	34.2	N/A	43.5
115.6	38.8	34.9	N/A	34.8	33.1	N/A	43.5
117.1	36.6	32.8	N/A	33.8	30.1	N/A	43.5
233.8	35.2	31.5	N/A	32.6	28.6	N/A	46.0

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded above for frequency range of 30-1000 MHz. Peak and Average amplitude emissions are recorded above for frequency range above 1000 MHz.

**Summary of Results for General Radiated Emissions**

The EUT demonstrated compliance with the radiated emissions requirements of CFR47 Part 15C paragraph 15.209 Intentional Radiators. The EUT computer support system demonstrated a minimum margin of -2.7 dB below the requirements. Other emissions were present with amplitudes at least 20 dB below the Limits.

**Operation in the Band 2400 – 2483.5 MHz**

The power output was measured at the antenna port and the open area test site at a three-meter distance. The EUT was placed on a wooden turntable 0.8 meters above the ground plane at a distance of 3 meters from the FSM antenna. The peak and quasi-peak amplitude of the frequencies below 1000 MHz were measured using a spectrum analyzer. The peak and average amplitude of emissions above 1000 MHz including were measured using a spectrum analyzer. Emissions data was recorded from the measurement results. Plots were made of transmitter performance for reference purposes. Refer to figures three through fourteen showing plots of the EUT performance displaying compliance with the specifications.

**Table 6 Transmitter Antenna port Conducted Emissions Data (Total Highest)**

Channel Mode	Total Output Power (dBm / Watts)	Total Power Spectral Density (dBm)
20 MHz	27.00 dBm / 0.5 Watts	3.17

**Table 7 Transmitter Antenna Conducted Emissions Data**

Frequency MHz	Antenna Conducted Output Power dBm	6-dB Occupied Bandwidth kHz	Power Spectral Density dBm
912.0	27.00	16,725	2.15
917.0	26.98	16,680	3.17




Figure 3 Plot of Transmitter Emissions (Across Operational Band, b/g/n Mode)




Figure 4 Plot of Transmitter Emissions (Across Operational Band, g Mode)




Figure 5 Plot of Low Band Edge (b/g/n Mode)




Figure 6 Plot of High Band Edge (b/g/n Mode)




Figure 7 Plot of Occupied Bandwidth (b/g/n Mode)




Figure 8 Plot of Occupied Bandwidth (g Mode)



**Transmitter Emissions Data**

**Table 8 Transmitter Radiated Emission (TG-Y915-17)**

Frequency in MHz	Horizontal Peak (dBµV/m)	Horizontal Average (dBµV/m)	Vertical Peak (dBµV/m)	Vertical Average (dBµV/m)	Limit @ 3m (dBµV/m)
912.0	--	--	--	--	--
1824.0	37.2	25.0	38.1	24.9	54.0
2736.0	41.3	28.8	42.2	28.8	54.0
3648.0	43.7	31.1	43.7	31.0	54.0
4560.0	44.8	32.3	44.6	32.3	54.0
5472.0	44.8	31.7	44.3	31.7	54.0
6384.0	43.9	31.1	43.7	31.1	54.0
917.0	--	--	--	--	--
1834.0	38.1	25.0	39.4	26.3	54.0
2751.0	41.9	29.0	42.1	29.0	54.0
3668.0	43.8	31.2	43.1	31.2	54.0
4585.0	44.4	31.9	44.2	31.9	54.0
5502.0	43.9	31.1	43.3	31.2	54.0
6419.0	45.9	32.9	46.1	33.0	54.0

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded above for frequency range of 30-1000 MHz. Peak and Average amplitude emissions are recorded above for frequency range above 1000 MHz.

**Summary of Results for Transmitter Radiated Emissions of Intentional Radiator**

The EUT demonstrated compliance with the radiated emissions requirements of CFR47 Part 15.247. Peak antenna port conducted power of 0.5 watt (27.0 dBm). The peak power spectral density presented a minimum margin of -4.8 dB below the requirements. The EUT demonstrated a minimum margin of -21.0 dB below the harmonic emissions requirements. There were no other significantly measurable emissions in the restricted bands other than those recorded in this report. Other emissions were present with amplitudes at least 20 dB below the requirements.

There were no other deviations or exceptions to the requirements.



NVLAP Lab Code 200087-0

## **Annex**

- Annex A Measurement Uncertainty Calculations
- Annex B Rogers Labs Test Equipment List
- Annex C Rogers Qualifications
- Annex D FCC Site Registration Letter
- Annex E Industry Canada Site Registration Letter

**Annex A Measurement Uncertainty Calculations**

Measurement uncertainty calculations were made for the laboratory. Result of measurement uncertainty calculations are recorded below for AC line conducted and radiated emission measurements.

Measurement Uncertainty	$U_{(E)}$	$U_{(lab)}$
3 Meter Horizontal 30-200 MHz Measurements	2.08	4.16
3 Meter Vertical 30-200 MHz Measurements	2.16	4.33
3 Meter Vertical Measurements 200-1000 MHz	2.99	5.97
10 Meter Horizontal Measurements 30-200 MHz	2.07	4.15
10 Meter Vertical Measurements 30-200 MHz	2.06	4.13
10 Meter Horizontal Measurements 200-1000 MHz	2.32	4.64
10 Meter Vertical Measurements 200-1000 MHz	2.33	4.66
3 Meter Measurements 1-6 GHz	2.57	5.14
3 Meter Measurements 6-18 GHz	2.58	5.16
AC Line Conducted	1.72	3.43



**Annex B Rogers Labs Test Equipment List**

List of Test Equipment	Calibration Date
Spectrum Analyzer: Rohde & Schwarz ESU40	5/13
Spectrum Analyzer: HP 8562A, HP Adapters: 11518, 11519, and 11520 Mixers: 11517A, 11970A, 11970K, 11970U, 11970V, 11970W	5/13
Spectrum Analyzer: HP 8591EM	5/13
Antenna: EMCO Biconilog Model: 3143	5/13
Antenna: Sunol Biconilog Model: JB6	10/13
Antenna: EMCO Log Periodic Model: 3147	10/13
Antenna: Com Power Model: AH-118	10/13
Antenna: Com Power Model: AH-840	10/13
Antenna: Antenna Research Biconical Model: BCD 235	10/13
Antenna: EMCO 6509	10/13
LISN: Compliance Design Model: FCC-LISN-2.Mod.cd, 50 µHy/50 ohm/0.1 µf	10/13
R.F. Preamp CPPA-102	10/13
Attenuator: HP Model: HP11509A	10/13
Attenuator: Mini Circuits Model: CAT-3	10/13
Attenuator: Mini Circuits Model: CAT-3	10/13
Cable: Belden RG-58 (L1)	10/13
Cable: Belden RG-58 (L2)	10/13
Cable: Belden 8268 (L3)	10/13
Cable: Time Microwave: 4M-750HF290-750	10/13
Cable: Time Microwave: 10M-750HF290-750	10/13
Frequency Counter: Leader LDC825	2/14
Oscilloscope Scope: Tektronix 2230	2/14
Wattmeter: Bird 43 with Load Bird 8085	2/14
Power Supplies: Sorensen SRL 20-25, SRL 40-25, DCR 150, DCR 140	2/14
R.F. Generators: HP 606A, HP 8614A, HP 8640B	2/14
R.F. Power Amp 65W Model: 470-A-1010	2/14
R.F. Power Amp 50W M185- 10-501	2/14
R.F. Power Amp A.R. Model: 10W 1010M7	2/14
R.F. Power Amp EIN Model: A301	2/14
LISN: Compliance Eng. Model 240/20	2/14
LISN: Fischer Custom Communications Model: FCC-LISN-50-16-2-08	2/14
Antenna: EMCO Dipole Set 3121C	2/14
Antenna: C.D. B-101	2/14
Antenna: Solar 9229-1 & 9230-1	2/14
Audio Oscillator: H.P. 201CD	2/14
ELGAR Model: 1751	2/14
ELGAR Model: TG 704A-3D	2/14
ESD Test Set 2010i	2/14
Fast Transient Burst Generator Model: EFT/B-101	2/14
Field Intensity Meter: EFM-018	2/14
KEYTEK Ecat Surge Generator	2/14
Shielded Room 5 M x 3 M x 3.0 M	



## **Annex C Rogers Qualifications**

***Scot D. Rogers, Engineer***

### **Rogers Labs, Inc.**

Mr. Rogers has approximately 17 years experience in the field of electronics. Engineering experience includes six years in the automated controls industry and remaining years working with the design, development and testing of radio communications and electronic equipment.

#### Positions Held

Systems Engineer: A/C Controls Mfg. Co., Inc. 6 Years

Electrical Engineer: Rogers Consulting Labs, Inc. 5 Years

Electrical Engineer: Rogers Labs, Inc. Current

#### Educational Background

- 1) Bachelor of Science Degree in Electrical Engineering from Kansas State University.
- 2) Bachelor of Science Degree in Business Administration Kansas State University.
- 3) Several Specialized Training courses and seminars pertaining to Microprocessors and Software programming.

Scot D. Rogers



NVLAP Lab Code 200087-0

**Annex D FCC Site Registration Letter**

**FEDERAL COMMUNICATIONS COMMISSION**

**Laboratory Division  
7435 Oakland Mills Road  
Columbia, MD 21046**

June 28, 2013

Registration Number: 90910

Rogers Labs, Inc.  
4405 West 259th Terrace,  
Louisburg, KS 66053

Attention: Scot Rogers,


Re: Measurement facility located at Louisburg  
3 & 10 meter site  
Date of Renewal: June 28, 2013

Dear Sir or Madam:

Your request for renewal of the registration of the subject measurement facility has been received. The information submitted has been placed in your file and the registration has been renewed. The name of your organization will remain on the list of facilities whose measurement data will be accepted in conjunction with applications for Certification under Parts 15 or 18 of the Commission's Rules. Please note that the file must be updated for any changes made to the facility and the registration must be renewed at least every three years.

Measurement facilities that have indicated that they are available to the public to perform measurement services on a fee basis may be found on the FCC website [www.fcc.gov](http://www.fcc.gov) under E-Filing, OET Equipment Authorization Electronic Filing, Test Firms.

Sincerely,



Phyllis Parrish  
Industry Analyst

Rogers Labs, Inc.  
4405 W. 259th Terrace  
Louisburg, KS 66053  
Phone/Fax: (913) 837-3214  
Revision 1


Mikrotikls SIA  
Model: RouterBOARD Metal 9HPn  
Test #: 140407  
Test to: CFR47 (15.247)  
File: Mikrotikls RBMetal9HPn TstRpt 140407

SN: 4D2B0251F36E/405  
FCC ID#: TV7METAL9HPN  
Date: April 15, 2014  
Page 30 of 31



NVLAP Lab Code 200087-0

## Annex E Industry Canada Site Registration Letter



June 19, 2013

OUR FILE: 46405-3041

Submission No: 168037

Rogers Labs Inc.  
4405 West 259th Terrace  
Louisburg  
KS, USA  
66053

**Attention:** Mr. Scot D. Rogers

Dear Sir:

The Bureau has received your application for the renewal of 3/10m OATS. Be advised that the information received was satisfactory to Industry Canada. The following number(s) is now associated to the site(s) for which registration / renewal was sought (**Site# 3041A-1**). Please reference the appropriate site number in the body of test reports containing measurements performed on the site. In addition, please keep for your records the following information;

- The company address code associated to the site(s) located at the above address is: **3041A**

Furthermore, to obtain or renew a unique site number, the applicant shall demonstrate that the site has been accredited to ANSI C63.4-2003 or later. A scope of accreditation indicating the accreditation by a recognized accreditation body to ANSI C63.4-2003 or later shall be accepted. Please indicate in a letter the previous assigned site number if applicable and the type of site (example: 3 metre OATS or 3 metre chamber). If the test facility is not accredited to ANSI C63.4-2003 or later, the test facility shall submit test data demonstrating full compliance with the ANSI standard. The Bureau will evaluate the filing to determine if recognition shall be granted.

The frequency for re-validation of the test site and the information that is required to be filed or retained by the testing party shall comply with the requirements established by the accrediting organization. However, in all cases, test site re-validation shall occur on an interval not to **exceed three years**. There is no fee or form associated with an OATS filing. OATS submissions are encouraged to be submitted electronically to the Bureau using the following URL;

[http://strategis.ic.gc.ca/epic/internet/inceb-bhst.nsf/en/h\\_tt00052e.html](http://strategis.ic.gc.ca/epic/internet/inceb-bhst.nsf/en/h_tt00052e.html).

If you have any questions, you may contact the Bureau by e-mail at [certification.bureau@ic.gc.ca](mailto:certification.bureau@ic.gc.ca) Please reference our file and submission number above for all correspondence.

Yours sincerely,

Bill Payn  
For: Wireless Laboratory Manager  
**Certification and Engineering Bureau**  
3701 Carling Ave., Building 94  
P.O. Box 11490, Station "H"  
Ottawa, Ontario K2H 8S2  
Email: [Bill.Payn@ic.gc.ca](mailto:Bill.Payn@ic.gc.ca)  
Tel. No. (613) 990-3639  
Fax. No. (613) 990-4752

Rogers Labs, Inc.  
4405 W. 259th Terrace  
Louisburg, KS 66053  
Phone/Fax: (913) 837-3214  
Revision 1

Mikrotikls SIA  
Model: RouterBOARD Metal 9HPn  
Test #: 140407  
Test to: CFR47 (15.247)  
File: Mikrotikls RBMetal9HPn TstRpt 140407

SN: 4D2B0251F36E/405  
FCC ID#: TV7METAL9HPN  
Date: April 15, 2014  
Page 31 of 31