

**SUBMITTAL
APPLICATION
REPORT**

**FOR
GRANT OF CERTIFICATION**

FOR

**Model: SXT-5HPnD
5745-5825 MHz**


**MIMO Broadband Digital Transmission System
FCC ID: TV7SXT-5HPND**

FOR

MIKROTIKLS SIA
Pernavas 46
Riga, Latvia LV-1009

Test Report Number: 110914B

Authorized Signatory: *Scot D Rogers*
Scot D. Rogers



ROGERS LABS, INC.

4405 West 259th Terrace
 Louisburg, KS 66053
 Phone / Fax (913) 837-3214

**Engineering Test Report
 For
 Grant of Certification Application**

FOR
 CFR 47, PART 15C - Intentional Radiators
 CFR 47 Paragraph 15.247
 License Exempt Intentional Radiator

For

MIKROTIKLS SIA

Pernavas 46
 Riga, Latvia LV-1009

MIMO Broadband Digital Transmission System
 Model: SXT-5HPnD
 Frequency Range 5745-5825 MHz
 FCC ID#: TV7SXT-5HPND

Test Date: September 14, 2011

Certifying Engineer: *Scot D. Rogers*
 Scot D. Rogers
 Rogers Labs, Inc.
 4405 West 259th Terrace
 Louisburg, KS 66053
 Telephone/Facsimile: (913) 837-3214

This report shall not be reproduced except in full, without the written approval of the laboratory. This report must not be used by the client to claim product endorsement by NVLAP, NIST, or any agency of the U.S. Government.



Table Of Contents

TABLE OF CONTENTS..... 3

FORWARD 5

OPINION / INTERPRETATION OF RESULTS 5

ENVIRONMENTAL CONDITIONS..... 5

EQUIPMENT TESTED..... 5

APPLICATION FOR CERTIFICATION..... 6

APPLICABLE STANDARDS & TEST PROCEDURES 7

EQUIPMENT FUNCTION AND CONFIGURATION..... 7

 Equipment Configuration.....8

TEST SITE LOCATIONS 8

UNITS OF MEASUREMENTS 8

TEST PROCEDURES..... 9

 AC Line Conducted Emission Test Procedure9

 Radiated Emission Test Procedure.....9

LIST OF TEST EQUIPMENT 10

INTENTIONAL RADIATORS..... 11

 Antenna Requirements11

 Restricted Bands of Operation.....11

 General Radiated Emissions in Restricted Bands Data12

 Harmonic Radiated Emissions in Restricted Bands Data12

Summary of Results for Radiated Emissions in Restricted Bands12

AC Line Conducted Emissions Procedure.....13

 Figure One AC Line Conducted Emissions Line 1.....14

 Figure Two AC Line Conducted Emissions Line 2.....14

 AC Line Conducted Emissions Data (Highest Emissions).....15

Summary of Results for AC Line Conducted Emissions16

General Radiated Emissions Procedure.....16

 Figure Three General Radiated Emissions taken at 1 meter in screen room17

 Figure Four General Radiated Emissions taken at 1 meter in screen room17

 Figure Five General Radiated Emissions taken at 1 meter in screen room.....18

 Figure Six General Radiated Emissions taken at 1 meter in screen room18

 Figure Seven General Radiated Emissions taken at 1 meter in screen room.....19

 Figure Eight General Radiated Emissions taken at 1 meter in screen room19



Figure Nine General Radiated Emissions taken at 1 meter in screen room.....20

Figure Ten General Radiated Emissions taken at 1 meter in screen room20

Figure Eleven General Radiated Emissions taken at 1 meter in screen room.....21

General Radiated Emissions from EUT Data (Highest Emissions all antenna options).....22

Summary of Results for General Radiated Emissions.....22

Operation in the Band 5725 – 5850 MHz.....23

Figure Twelve Plot of Transmitter Emissions (Across Operational Band, 20MHz Mode).....24

Figure Thirteen Plot of Transmitter Emissions (Across Operational Band, 40MHz Mode).....24

Figure Fourteen Plot of 6dB Band width (20 MHz Mode, 5745 MHz).....25

Figure Fifteen Plot of 6dB Band width (20 MHz Mode, 5785 MHz).....25

Figure Sixteen Plot of 6dB Band width (20 MHz Mode, 5825 MHz).....26

Figure Seventeen Plot of 6dB Band width (40 MHz Mode, 5755 MHz).....26

Figure Eighteen Plot of 6dB Band width (40 MHz Mode, 5795 MHz).....27

Figure Nineteen Plot of 6dB Band width (40 MHz Mode, 5815 MHz).....27

Figure Twenty Plot of Power Spectral Density (20 MHz Mode, 5745 MHz)28

Figure Twenty-one Plot of Power Spectral Density (20 MHz Mode, 5785 MHz)28

Figure Twenty-two Plot of Power Spectral Density (20 MHz Mode, 5825 MHz).....29

Figure Twenty-three Plot of Power Spectral Density (40 MHz Mode, 5755 MHz).....29

Figure Twenty-four Plot of Power Spectral Density (40 MHz Mode, 5795 MHz)30

Figure Twenty-five Plot of Power Spectral Density (40 MHz Mode, 5815 MHz).....30

Figure Twenty-six Plot of Lower Band Edge (20 MHz Mode).....31

Figure Twenty-seven Plot of Upper Band Edge (20 MHz Mode).....31

Figure Twenty-eight Plot of Lower Band Edge (40 MHz Mode).....32

Figure Twenty-nine Plot of Upper Band Edge (40 MHz Mode)32

Transmitter Emissions Data.....33

Calculated Transmitter Antenna Port Power33

Transmitter Radiated Emission (worst-case).....33

Summary of Results for Transmitter Radiated Emissions of Intentional Radiator.....34

STATEMENT OF MODIFICATIONS AND DEVIATIONS 34

ANNEX..... 35

Annex A Measurement Uncertainty Calculations.....36

Annex B Rogers Labs Test Equipment List.....38

Annex C Rogers Qualifications.....39

Annex D FCC Site Registration Letter.....40

Annex E Industry Canada Site Registration Letter41



Forward

The following information is submitted for consideration in obtaining Grant of Certification for License Exempt Digital Transmission System Intentional Radiator operating under CFR 47 Paragraph 15.247.

Name of Applicant: Mikrotiks SIA
Pernavas 46
Riga, Latvia LV-1009

Model: SXT-5HPnD

FCC I.D.: TV7SXT-5HPND FRN: 0014 43 1100

Frequency Range: 5745-5825 MHz (20 MHz channel operation), 5755-5815 MHz (40 MHz channel operation)

Operating Power: 0.4-Watts output power, 26.3 dBm

Opinion / Interpretation of Results

Tests Performed	Margin (dB)	Results
Emissions as per CFR 47 paragraphs 2 and 15.205	-3.4	Complies
Emissions as per CFR 47 paragraphs 2 and 15.207	-4.1	Complies
Emissions as per CFR 47 paragraphs 2 and 15.209	-2.5	Complies
Harmonic Emissions per CFR 47 15.247	-12.7	Complies
Peak Power Spectral Density per CFR 47 15.247	-2.9	Complies

Environmental Conditions

Ambient Temperature 21.6° C
Relative Humidity 38%
Atmospheric Pressure 1026.8 mb

Equipment Tested

<u>Equipment</u>	<u>Model</u>	<u>FCC I.D.</u>
EUT	SXT-5HPnD	TV7SXT-5HPND
AC Adapter	KSAS015240003	11556
Dell Studio XPS	921LBN1	N/A

<u>Antenna/Type</u>	<u>Model</u>
Integral	SXT-5HPnD

Rogers Labs, Inc.
4405 W. 259th Terrace
Louisburg, KS 66053
Phone/Fax: (913) 837-3214
Revision 1

Mikrotiks SIA
Model: SXT-5HPnD
Test #: 110914B
Test to: CFR47 (15.247)
File: Mikrotikls SXT5HPnD 110914B TstRpt

SN: 34A101DD0BF3
FCC ID#: TV7SXT-5HPND
Date: October 30, 2011
Page 5 of 41

Application for Certification

- (1) Manufacturer: Mikrotikls SIA
Pernavas 46
Riga, Latvia LV-1009
- (2) Identification: Model: SXT-5HPnD

FCC I.D.: TV7SXT-5HPND
- (3) Instruction Book:

Refer to Exhibit for Instruction Manual.
- (4) Description of Circuit Functions:

Refer to Exhibit of Operational Description.
- (5) Block Diagram with Frequencies:

Refer to Exhibit of Operational Description.
- (6) Report of Measurements:

Report of measurements follows in this Report.
- (7) Photographs: Construction, Component Placement, etc.:

Refer to Exhibit for photographs of equipment.
- (8) List of Peripheral Equipment Necessary for operation. The equipment operates from power received from authorized POE (Power Over Ethernet) AC power adapter. The EUT offers connection ports for USB flash drive (offering additional memory storage) and network cable only. During testing, the EUT was connected to CPU through network cable and POE adapter. A USB memory stick was connected to the USB port during testing. The EUT received power supplied from external POE AC adapter.
- (9) Transition Provisions of CFR47 15.37 are not requested.
- (10) Not Applicable. The unit is not a scanning receiver.
- (11) Not Applicable. The EUT does not operate in the 59 – 64 GHz frequency band.
- (12) The equipment is not software defined and this section is not applicable.



Applicable Standards & Test Procedures


In accordance with the Federal Communications Code of Federal Regulations, dated October 1, 2010, Part 2, Subpart J, Paragraphs 2.907, 2.911, 2.913, 2.925, 2.926, 2.1031 through 2.1057, and applicable parts of paragraph 15, Part 15C Paragraph 15.247 the following information is submitted.

Test procedures used are the established Methods of Measurement of Radio-Noise Emissions as described in the ANSI C63.4-2009 Document, FCC documents KDB 558074, DA00-1407 and DA00-705 and/or TIA/EIA 603-1. Testing for the AC line-conducted emissions were performed as defined in sections 7 and 13.1.3, testing of the radiated emissions was performed as defined in sections 8 and 13.1.4 of ANSI C63.4-2009. Testing of the intentional radiated emissions was performed as defined in section 13 of ANSI C63.4-2009.

Equipment Function and Configuration

The EUT is a 5745-5825 MHz Digital Transmission System transmitters used to transmit data in applications offering broadband wireless connectivity. The equipment is marketed for use to incorporate a wireless link to exchange data information from one point to another. For testing purposes, the SXT-5HPnD transceiver was connected to the manufacturer supplied POE AC power adapter and communicating to the laptop computer through network interface allowing for operational control of the transmitter and communications over the network interface between the EUT and supporting computer system. A USB memory stick was connected to the USB port during testing. The SXT-5HPnD receives power from the supplied POE AC power adapter connected to utility power systems. The EUT offers connection port for network only and requires power supplied from external source POE AC adapter, no provides no other interfacing options. For testing purposes, the SXT-5HPnD received powered from the POE AC adapter and configured to transmit in available data modes. The device is marketed for professional installation. Antenna connection and options comply with the unique antenna connection requirements.

Equipment Configuration



Test Site Locations

- Conducted EMI** The AC power line conducted emissions testing performed in a shielded screen room located at Rogers Labs, Inc., 4405 W. 259th Terrace, Louisburg, KS
- Radiated EMI** The radiated emissions tests were performed at the 3 meters, Open Area Test Site (OATS) located at Rogers Labs, Inc., 4405 W. 259th Terrace, Louisburg, KS
- Site Registration** Refer to Annex for Site Registration Letters
- NVLAP Accreditation** Lab code 200087-0

Units of Measurements

- Conducted EMI** Data is in dB μ V; dB referenced to one microvolt
- Radiated EMI** Data is in dB μ V/m; dB/m referenced to one microvolt per meter

Sample Calculation:

RFS = Radiated Field Strength, FSM = Field Strength Measured
 A.F. = Receive antenna factor, Gain = amplification gains and/or cable losses

$$RFS \text{ (dB}\mu\text{V/m @ 3m)} = FSM \text{ (dB}\mu\text{V)} + A.F. \text{ (dB)} - \text{Gain (dB)}$$

Test Procedures

AC Line Conducted Emission Test Procedure

The EUT operates from DC power only and must be connected to an approved POE AC adapter for operation. For testing purposes, the manufacturer supplied POE AC power adapter was used to power the EUT and system. Testing for the AC line-conducted emissions testing was performed as defined in sections 7 and 13.1.3 of ANSI C63.4-2009. The test setup including the EUT was arranged in typical equipment configurations and placed on a 1 x 1.5-meter wooden bench, 0.8 meters high located in a screen room. The power lines of the system were isolated from the power source using a standard LISN with a 50- μ Hy choke. EMI was coupled to the spectrum analyzer through a 0.1 μ F capacitor internal to the LISN. The LISN was positioned on the floor beneath the wooden bench supporting the EUT. The power lines and cables were draped over the back edge of the table.

Radiated Emission Test Procedure

The EUT was placed on a rotating 1 x 1.5-meter wooden platform, 0.8 meters above the ground plane at a distance of 3 meters from the FSM antenna. Testing for the radiated emissions was performed as required by CFR47 15 and specified in sections 8 and 13.1.4 of ANSI C63.4-2009. EMI energy was maximized by equipment placement, raising and lowering the FSM antenna, changing the antenna polarization, and by rotating the turntable. Each emission was maximized before data was taken using a spectrum analyzer. Refer to photographs in the test setup exhibits for EUT placement during testing.

List of Test Equipment

A Rohde and Schwarz ESU40 and/or Hewlett Packard 8591EM was used as the measuring device for the emissions testing of frequencies below 1 GHz. A Rohde and Schwarz ESU40 and/or Hewlett Packard 8562A Spectrum Analyzer was used as the measuring device for testing the emissions at frequencies above 1 GHz. The analyzer settings used are described in the following table. Refer to the appendix for a complete list of test equipment.

AC Line Conducted Emissions (0.150 -30 MHz)		
RBW	AVG. BW	Detector Function
9 kHz	30 kHz	Peak / Quasi Peak
Emissions (30-1000 MHz)		
RBW	AVG. BW	Detector Function
120 kHz	300 kHz	Peak / Quasi Peak
Emissions (Above 1000 MHz)		
RBW	Video BW	Detector Function
100 kHz	100 kHz	Peak
1 MHz	1 MHz	Peak / Average

<u>Equipment</u>	<u>Manufacturer</u>	<u>Model</u>	<u>Calibration Date</u>	<u>Due</u>
LISN	Comp. Design	FCC-LISN-2-MOD.CD	10/10	10/11
Antenna	ARA	BCD-235-B	10/10	10/11
Antenna	EMCO	3147	10/10	10/11
Antenna	EMCO	3147	10/10	10/11
Antenna	Com Power	AH-118	10/10	10/11
Analyzer	HP	8591EM	5/11	5/12
Analyzer	HP	8562A	5/11	5/12
Analyzer	Rohde & Schwarz	ESU40	5/11	5/12



Intentional Radiators

As per CFR47, Subpart C, paragraph 15.247 the following information is submitted.

Antenna Requirements

The EUT utilizes integral antenna system and offers no provision for alternate antenna system. The design is marketed for professional installation and use as described in accompanying documentation. The antenna connection point complies with the unique antenna connection requirements. The requirements of 15.203 are fulfilled; there are no deviations or exceptions to the specification.

Restricted Bands of Operation

Spurious emissions falling in the restricted frequency bands of operation were measured at a distance of three meters on the OATS. Measurements were made for each antenna option. Emissions other than transmitter harmonics measured similar for all configurations and are presented below. Harmonic emissions, in restricted bands, were measured for each antenna style offered and recorded. The EUT utilizes frequency, determining circuitry, which generates harmonics falling in the restricted bands. Emissions were measured at the OATS, using appropriate antennas or pyramidal horns, amplification stages, and a spectrum analyzer. No other significant emission was observed which fell into the restricted bands of operation.

General Radiated Emissions in Restricted Bands Data

Frequency in MHz	Horizontal Peak (dBµV/m)	Horizontal Quasi-Peak (dBµV/m)	Horizontal Average (dBµV/m)	Vertical Peak (dBµV/m)	Vertical Quasi-Peak (dBµV/m)	Vertical Average (dBµV/m)	Limit @ 3m (dBµV/m)
108.2	37.6	32.7	N/A	43.8	39.8	N/A	43.5
108.8	43.3	37.7	N/A	44.9	40.1	N/A	43.5
114.2	37.1	33.3	N/A	41.0	38.9	N/A	43.5
250.0	40.7	39.4	N/A	41.2	39.5	N/A	46.0
400.0	43.5	42.1	N/A	42.0	38.3	N/A	46.0
1200.0	50.9	N/A	43.4	54.7	N/A	43.6	54.0
1600.0	50.8	N/A	46.5	49.8	N/A	44.5	54.0

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded above for frequency range of 30-1000 MHz. Peak and Average amplitude emissions are recorded above for frequency range above 1000 MHz.

Harmonic Radiated Emissions in Restricted Bands Data

Frequency in MHz	Horizontal Peak (dBµV/m)	Horizontal Quasi-Peak (dBµV/m)	Horizontal Average (dBµV/m)	Vertical Peak (dBµV/m)	Vertical Quasi-Peak (dBµV/m)	Vertical Average (dBµV/m)	Limit @ 3m (dBµV/m)
11490.0	48.2	N/A	35.7	48.0	N/A	35.5	54.0
11570.0	48.1	N/A	35.7	47.5	N/A	35.0	54.0
11650.0	54.0	N/A	16.6	16.1	N/A	35.4	54.0
22980.0	37.5	N/A	24.7	37.3	N/A	24.7	54.0

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded above for frequency range of 30-1000 MHz. Peak and Average amplitude emissions are recorded above for frequency range above 1000 MHz.

Summary of Results for Radiated Emissions in Restricted Bands

The EUT demonstrated compliance with the radiated emissions requirements of CFR 47 Part 15C Intentional Radiators. The EUT demonstrated a minimum margin of -3.4 dB below the radiated emissions requirements in restricted frequency bands. Peak, Quasi-peak, and average amplitudes were checked for compliance with the regulations. Worst-case emissions are reported with other emissions found in the restricted frequency bands at least 20 dB below the requirements.

AC Line Conducted Emissions Procedure

The EUT was arranged in a typical equipment configuration and placed on a 1 x 1.5-meter wooden bench 80 cm above the conducting ground plane, floor of a screen room. The bench was positioned 40 cm away from the wall of the screen room. The LISN was positioned on the floor of the screen room 80-cm from the rear of the EUT. The manufacturer supplied AC power adapter for the EUT was connected to the LISN. A second LISN was positioned on the floor of the screen room 80-cm from the rear of the supporting equipment of the EUT. All power cords except the EUT were then powered from the second LISN. EMI was coupled to the spectrum analyzer through a 0.1 μ F capacitor, internal to the LISN. Power line conducted emissions testing were carried out individually for each current carrying conductor of the EUT. The excess length of lead between the system and the LISN receptacle was folded back and forth to form a bundle not exceeding 40 cm in length. The screen room, conducting ground plane, analyzer, and LISN were bonded together to the protective earth ground. Preliminary testing was performed to identify the frequency of each radio frequency emission displaying the highest amplitude. The cables were repositioned to obtain maximum amplitude of measured EMI level. Once the worst-case configuration was identified, plots were made of the EMI from 0.15 MHz to 30 MHz then the data was recorded with maximum conducted emissions levels. Refer to figures one and two for plots of the EUT powered by AC adapter, AC Power Line conducted emissions.




Figure One AC Line Conducted Emissions Line 1




Figure Two AC Line Conducted Emissions Line 2



AC Line Conducted Emissions Data (Highest Emissions)

Line 1

Trace	Frequency	Level (dBµV)	Detector	Delta Limit/dB
2	514.000000000 kHz	35.54	Average	-10.46
1	538.000000000 kHz	44.99	Quasi Peak	-11.01
1	698.000000000 kHz	44.07	Quasi Peak	-11.93
1	750.000000000 kHz	44.79	Quasi Peak	-11.21
2	9.940000000 MHz	31.46	Average	-18.54
1	10.264000000 MHz	44.15	Quasi Peak	-15.85
1	12.812000000 MHz	55.29	Quasi Peak	-4.71
2	12.992000000 MHz	45.77	Average	-4.23
2	13.568000000 MHz	45.89	Average	-4.11
1	13.736000000 MHz	55.09	Quasi Peak	-4.91
2	16.228000000 MHz	40.34	Average	-9.66
2	19.708000000 MHz	38.38	Average	-11.62
2	21.664000000 MHz	38.99	Average	-11.01
1	21.664000000 MHz	46.56	Quasi Peak	-13.44

Line 2

Trace	Frequency	Level (dBµV)	Detector	Delta Limit/dB
2	514.000000000 kHz	38.36	Average	-7.64
1	530.000000000 kHz	47.03	Quasi Peak	-8.97
2	722.000000000 kHz	34.74	Average	-11.26
1	1.178000000 MHz	45.20	Quasi Peak	-10.80
1	1.498000000 MHz	45.10	Quasi Peak	-10.90
1	1.818000000 MHz	44.53	Quasi Peak	-11.47
1	2.462000000 MHz	44.70	Quasi Peak	-11.30
1	13.256000000 MHz	52.03	Quasi Peak	-7.97
2	13.424000000 MHz	43.68	Average	-6.32
1	13.916000000 MHz	55.32	Quasi Peak	-4.68
2	14.024000000 MHz	45.17	Average	-4.83
2	21.664000000 MHz	39.16	Average	-10.84
2	23.128000000 MHz	40.92	Average	-9.08

Other emissions present had amplitudes at least 20 dB below the limit.

Summary of Results for AC Line Conducted Emissions

The EUT demonstrated compliance to the conducted emissions requirements of CFR47 Part 15C equipment. The EUT demonstrated minimum margin of -4.1 dB below the limit. Measurements were taken using the peak, quasi peak, and average, measurement function for each emissions amplitude and were below the limits stated in the specification. Other emissions were present with recorded data representing worst-case amplitudes.

General Radiated Emissions Procedure

The EUT was arranged in a typical equipment configuration and operated through all available modes with worst-case data recorded. Preliminary testing was performed in a screen room with the EUT positioned 1 meter from the FSM. Radiated emissions measurements were performed to identify the frequencies, which produced the highest emissions. Plots were made of the radiated frequency spectrum from 30 MHz to 40,000 MHz for the preliminary testing. Refer to figures three through eleven for plots of the general radiated emissions spectrum taken in a screen room. Each radiated emission was then maximized at the OATS location before final radiated emissions measurements were performed. Final data was taken with the EUT located at the OATS at a distance of 3 meters between the EUT and the receiving antenna. The frequency spectrum from 30 MHz to 60,000 MHz was searched for general radiated emissions. Measured emission levels were maximized by EUT placement on the table, rotating the turntable through 360 degrees, varying the antenna height between 1 and 4 meters above the ground plane and changing antenna position between horizontal and vertical polarization. Antennas used were Broadband Biconical from 30 to 200 MHz, Biconilog from 30 to 6000 MHz, Log Periodic from 200 MHz to 5 GHz and or double Ridge or pyramidal horns and mixers from 4 GHz to 60 GHz, notch filters and appropriate amplifiers and external mixers were utilized.




Figure Three General Radiated Emissions taken at 1 meter in screen room




Figure Four General Radiated Emissions taken at 1 meter in screen room




Figure Five General Radiated Emissions taken at 1 meter in screen room




Figure Six General Radiated Emissions taken at 1 meter in screen room




Figure Seven General Radiated Emissions taken at 1 meter in screen room




Figure Eight General Radiated Emissions taken at 1 meter in screen room




Figure Nine General Radiated Emissions taken at 1 meter in screen room




Figure Ten General Radiated Emissions taken at 1 meter in screen room




Figure Eleven General Radiated Emissions taken at 1 meter in screen room

General Radiated Emissions from EUT Data (Highest Emissions all antenna options)

Frequency in MHz	Horizontal Peak (dBµV/m)	Horizontal Quasi-Peak (dBµV/m)	Horizontal Average (dBµV/m)	Vertical Peak (dBµV/m)	Vertical Quasi-Peak (dBµV/m)	Vertical Average (dBµV/m)	Limit @ 3m (dBµV/m)
77.2	36.4	33.8	N/A	39.0	36.9	N/A	40.0
81.2	36.6	32.6	N/A	39.8	36.5	N/A	40.0
94.4	34.4	30.8	N/A	43.2	39.3	N/A	43.5
95.8	40.5	35.5	N/A	43.2	39.2	N/A	43.5
96.3	39.4	36.1	N/A	44.2	39.6	N/A	43.5
98.4	40.6	36.4	N/A	44.4	40.4	N/A	43.5
100.0	37.5	32.1	N/A	46.1	40.2	N/A	43.5
108.2	37.6	32.7	N/A	43.8	39.8	N/A	43.5
108.8	43.3	37.7	N/A	44.9	40.1	N/A	43.5
114.2	37.1	33.3	N/A	41.0	38.9	N/A	43.5
200.0	44.3	39.1	N/A	38.1	31.9	N/A	43.5
212.0	35.8	28.3	N/A	29.4	22.9	N/A	43.5
250.0	40.7	39.4	N/A	41.2	39.5	N/A	46.0
400.0	43.5	42.1	N/A	42.0	38.3	N/A	46.0
800.0	45.2	43.5	N/A	43.5	41.3	N/A	46.0
1200.0	50.9	N/A	43.4	54.7	N/A	43.6	54.0
1600.0	50.8	N/A	46.5	49.8	N/A	44.5	54.0

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded above for frequency range of 30-1000 MHz. Peak and Average amplitude emissions are recorded above for frequency range above 1000 MHz.

Summary of Results for General Radiated Emissions

The EUT demonstrated compliance with the radiated emissions requirements of CFR47 Part 15C paragraph 15.209 Intentional Radiators. The EUT demonstrated a minimum margin of -2.5 dB below the requirements. Other emissions were present with amplitudes at least 20 dB below the Limits.

Operation in the Band 5725 – 5850 MHz

The power output was measured at the open area test site at a three-meter distance. The EUT and test configurations were placed on a wooden turntable 0.8 meters above the ground plane at a distance of 3 meters from the FSM antenna. The peak and quasi-peak amplitude of the frequencies below 1000 MHz were measured using a spectrum analyzer. The peak and average amplitude of emissions above 1000 MHz including were measured using a spectrum analyzer. Data was recorded from the analyzer measurement result. Plots taken in a screen room were made of transmitter in band performance. Refer to figures twelve through twenty-nine showing plots of the EUT emissions performance displaying compliance with the specifications.

As this product utilizes permanently attached antenna and offers no provision for antenna port measurements. Alternative test procedures as defined in publication number KDB 558074 and da000705 were utilized for demonstration of compliance with antenna port requirements. Radiated emission data measurements were taken using spectrum analyzer additionally with power meter, recorded, and calculations processed for comparison with limits per KDB guidelines. Calculations were made for Maximum Peak Output Power and Maximum Peak Power Spectral Density offering comparison with limits. Note plots taken for Peak Power Spectral Density require correction for bandwidth using bandwidth correction factor (BWCF) where $BWCF = 10 \log (3 \text{ kHz}/100 \text{ kHz})$. Calculation for EIRP levels may utilize the relationship $EIRP \text{ (dBm)} = E \text{ (dB}\mu\text{V/m)} - 95.2$ or conversion of measured levels to linear units then using relationship for Power where, $E =$ measured maximum field strength in V/m, $d =$ the distance in meters, $G =$ the numeric gain of the transmitting antenna, then $\text{Power (dBm)} = (E \times d)^2 / 30G$. Measurements taking using power meter registered higher output power as bandwidth limitations were reduced using the wideband power sensor.




Figure Twelve Plot of Transmitter Emissions (Across Operational Band, 20MHz Mode)




Figure Thirteen Plot of Transmitter Emissions (Across Operational Band, 40MHz Mode)




Figure Fourteen Plot of 6dB Band width (20 MHz Mode, 5745 MHz)




Figure Fifteen Plot of 6dB Band width (20 MHz Mode, 5785 MHz)




Figure Sixteen Plot of 6dB Band width (20 MHz Mode, 5825 MHz)




Figure Seventeen Plot of 6dB Band width (40 MHz Mode, 5755 MHz)




Figure Eighteen Plot of 6dB Band width (40 MHz Mode, 5795 MHz)




Figure Nineteen Plot of 6dB Band width (40 MHz Mode, 5815 MHz)




Figure Twenty Plot of Power Spectral Density (20 MHz Mode, 5745 MHz)




Figure Twenty-one Plot of Power Spectral Density (20 MHz Mode, 5785 MHz)




Figure Twenty-two Plot of Power Spectral Density (20 MHz Mode, 5825 MHz)




Figure Twenty-three Plot of Power Spectral Density (40 MHz Mode, 5755 MHz)




Figure Twenty-four Plot of Power Spectral Density (40 MHz Mode, 5795 MHz)




Figure Twenty-five Plot of Power Spectral Density (40 MHz Mode, 5815 MHz)




Figure Twenty-six Plot of Lower Band Edge (20 MHz Mode)




Figure Twenty-seven Plot of Upper Band Edge (20 MHz Mode)




Figure Twenty-eight Plot of Lower Band Edge (40 MHz Mode)




Figure Twenty-nine Plot of Upper Band Edge (40 MHz Mode)

Transmitter Emissions Data

Calculated Transmitter Antenna Port Power

Frequency MHz	Calculated Peak Conducted Output Power (dBm)	Power Spectral Density (dBm)
20 MHz Channel		
5745	25.8	4.9
5785	25.0	5.1
5825	25.1	5.1
40 MHz Channel		
5755	26.3	1.2
5795	25.6	-0.1
5815	24.0	0.6

Transmitter Radiated Emission (worst-case)

Frequency in MHz	Horizontal Peak (dBμV/m)	Horizontal Average (dBμV/m)	Vertical Peak (dBμV/m)	Vertical Average (dBμV/m)	Limit @ 3m (dBμV/m)
5745.0	125.8	114.0	122.8	110.6	--
11490.0	48.2	35.7	48.0	35.5	54.0
17235.0	53.7	41.3	53.8	41.3	54.0
22980.0	37.5	24.7	37.3	24.7	54.0
28725.0	37.6	25.1	37.2	25.1	54.0
5785.0	125.0	113.3	122.1	110.6	--
11570.0	48.1	35.7	47.5	35.0	54.0
17355.0	53.7	41.2	53.8	41.2	54.0
23140.0	38.2	25.4	39.1	25.5	54.0
28925.0	38.8	26.3	38.6	26.2	54.0
5825.0	125.1	113.2	122.3	110.3	--
11650.0	48.9	36.0	48.5	35.4	54.0
17475.0	53.7	41.2	53.7	41.2	54.0
23300.0	36.6	23.4	36.3	23.2	54.0
29125.0	37.6	24.7	37.2	24.5	54.0

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded above for frequency range of 30-1000 MHz. Peak and Average amplitude emissions are recorded above for frequency range above 1000 MHz.



Summary of Results for Transmitter Radiated Emissions of Intentional Radiator

The EUT demonstrated compliance with the radiated emissions requirements of CFR47 Part 15.247. Antenna port conducted power of 26.3 dBm, 0.4 Watts was calculated from data obtained using the spectrum analyzer. The calculated peak power spectral density presented a minimum margin of -2.9 dB below the requirements. The EUT demonstrated a minimum margin of -12.7 dB below the harmonic emissions requirements. There were no other significantly measurable emissions in the restricted bands other than those recorded in this report. Other emissions were present with amplitudes at least 20 dB below the requirements. Alternative procedures for antenna port conducted emissions were utilized in demonstration of compliance with regulations. There were no other deviations or exceptions to the requirements.

Statement of Modifications and Deviations

No modifications to the EUT were required for the unit to demonstrate compliance with the CFR47 Part 15C emissions standards. There were no deviations to the specifications.



NVLAP Lab Code 200087-0

Annex

- Annex A Measurement Uncertainty Calculations
- Annex B Rogers Labs Test Equipment List
- Annex C Rogers Qualifications
- Annex D FCC Site Registration Letter
- Annex E Industry Canada Site Registration Letter

Annex A Measurement Uncertainty Calculations

Radiated Emissions Measurement Uncertainty Calculation

Measurement of vertically polarized radiated field strength over the frequency range 30 MHz to 1 GHz on an open area test site at 3m and 10m includes following uncertainty:

Contribution	Probability Distribution	Uncertainty (dB)
Antenna factor calibration	normal (k = 2)	±0.58
Cable loss calibration	normal (k = 2)	±0.2
Receiver specification	rectangular	±1.0
Antenna directivity	rectangular	±0.1
Antenna factor variation with height	rectangular	±2.0
Antenna factor frequency interpolation	rectangular	±0.1
Measurement distance variation	rectangular	±0.2
Site Imperfections	rectangular	±1.5
Combined standard uncertainty $u_c(y)$ is		

$$U_c(y) = \pm \sqrt{\left[\frac{1.0}{2}\right]^2 + \left[\frac{0.2}{2}\right]^2 + \left[\frac{1.0^2 + 0.1^2 + 2.0^2 + 0.1^2 + 0.2^2 + 1.5^2}{3}\right]}$$

$$U_c(y) = \pm 1.6 \text{ dB}$$

It is probable that $u_c(y) / s(q_k) > 3$, where $s(q_k)$ is estimated standard deviation from a sample of n readings unless the repeatability of the EUT is particularly poor, and a coverage factor of $k = 2$ will ensure that the level of confidence will be approximately 95%, therefore:

$$s(q_k) = \sqrt{\frac{1}{(n-1)} \sum_{k=1}^n (q_k - \bar{q})^2}$$

$$U = 2 U_c(y) = 2 \times \pm 1.6 \text{ dB} = \pm 3.2 \text{ dB}$$

Notes:

- 1.1 Uncertainties for the antenna and cable were estimated, based on a normal probability distribution with $k = 2$.
- 1.2 The receiver uncertainty was obtained from the manufacturer's specification for which a rectangular distribution was assumed.
- 1.3 The antenna factor uncertainty does not take account of antenna directivity.
- 1.4 The antenna factor varies with height and since the height was not always the same in use as when the antenna was calibrated an additional uncertainty is added.
- 1.5 The uncertainty in the measurement distance is relatively small but has some effect on the received signal strength. The increase in measurement distance as the antenna height is increased is an inevitable consequence of the test method and is therefore not considered a contribution to uncertainty.
- 1.6 Site imperfections are difficult to quantify but may include the following contributions:
 - Unwanted reflections from adjacent objects.
 - Ground plane imperfections: reflection coefficient, flatness, and edge effects.
 - Losses or reflections from "transparent" cabins for the EUT or site coverings.
 - Earth currents in antenna cable (mainly effect Biconical antennas).



The specified limits for the difference between measured site attenuation and the theoretical value (± 4 dB) were not included in total since the measurement of site attenuation includes uncertainty contributions already allowed for in this budget, such as antenna factor.

Conducted Measurements Uncertainty Calculation

Measurement of conducted emissions over the frequency range 9 kHz to 30 MHz includes following uncertainty:

Contribution	Probability Distribution	Uncertainty (dB)
Receiver specification	rectangular	± 1.5
LISN coupling specification	rectangular	± 1.5
Cable and input attenuator calibration	normal (k=2)	± 0.5
Combined standard uncertainty $u_c(y)$ is		

$$U_c(y) = \pm \sqrt{\left[\frac{0.5}{2}\right]^2 + \frac{1.5^2 + 1.5^2}{3}}$$

$$U_c(y) = \pm 1.2 \text{ dB}$$

As with radiated field strength uncertainty, it is probable that $u_c(y) / s(q_k) > 3$ and a coverage factor of $k = 2$ will suffice, therefore:

$$U = 2 U_c(y) = 2 \times \pm 1.2 \text{ dB} = \pm 2.4 \text{ dB}$$



Annex B Rogers Labs Test Equipment List

The test equipment is maintained in calibration and good operating condition. Use of this calibrated equipment ensures measurements are traceable to national standards.

List of Test Equipment	Calibration Date
Spectrum Analyzer: Rohde & Schwarz ESU40	5/11
Spectrum Analyzer: HP 8562A, HP Adapters: 11518, 11519, and 11520	5/11
Mixers: 11517A, 11970A, 11970K, 11970U, 11970V, 11970W	
Spectrum Analyzer: HP 8591EM	5/11
Antenna: EMCO Biconilog Model: 3143	5/11
Antenna: Sunol Biconilog Model: JB6	10/10
Antenna: EMCO Log Periodic Model: 3147	10/10
Antenna: Antenna Research Biconical Model: BCD 235	10/10
LISN: Compliance Design Model: FCC-LISN-2.Mod.cd, 50 µHy/50 ohm/0.1 µf	10/10
R.F. Preamp CPPA-102	10/10
Attenuator: HP Model: HP11509A	10/10
Attenuator: Mini Circuits Model: CAT-3	10/10
Attenuator: Mini Circuits Model: CAT-3	10/10
Cable: Belden RG-58 (L1)	10/10
Cable: Belden RG-58 (L2)	10/10
Cable: Belden 8268 (L3)	10/10
Cable: Time Microwave: 4M-750HF290-750	10/10
Cable: Time Microwave: 10M-750HF290-750	10/10
Frequency Counter: Leader LDC825	2/11
Oscilloscope Scope: Tektronix 2230	2/11
Wattmeter: Bird 43 with Load Bird 8085	2/11
Power Supplies: Sorensen SRL 20-25, SRL 40-25, DCR 150, DCR 140	2/11
R.F. Generators: HP 606A, HP 8614A, HP 8640B	2/11
R.F. Power Amp 65W Model: 470-A-1010	2/11
R.F. Power Amp 50W M185- 10-501	2/11
R.F. Power Amp A.R. Model: 10W 1010M7	2/11
R.F. Power Amp EIN Model: A301	2/11
LISN: Compliance Eng. Model 240/20	2/11
LISN: Fischer Custom Communications Model: FCC-LISN-50-16-2-08	2/11
Antenna: EMCO Dipole Set 3121C	2/11
Antenna: C.D. B-101	2/11
Antenna: Solar 9229-1 & 9230-1	2/11
Antenna: EMCO 6509	2/11
Audio Oscillator: H.P. 201CD	2/11
Peavey Power Amp Model: IPS 801	2/11
ELGAR Model: 1751	2/11
ELGAR Model: TG 704A-3D	2/11
ESD Test Set 2010i	2/11
Fast Transient Burst Generator Model: EFT/B-101	2/11
Field Intensity Meter: EFM-018	2/11
KEYTEK Ecat Surge Generator	2/11
Shielded Room 5 M x 3 M x 3.0 M	



Annex C Rogers Qualifications

Scot D. Rogers, Engineer

Rogers Labs, Inc.

Mr. Rogers has approximately 17 years experience in the field of electronics. Engineering experience includes six years in the automated controls industry and remaining years working with the design, development and testing of radio communications and electronic equipment.

Positions Held

Systems Engineer: A/C Controls Mfg. Co., Inc. 6 Years

Electrical Engineer: Rogers Consulting Labs, Inc. 5 Years

Electrical Engineer: Rogers Labs, Inc. Current

Educational Background

- 1) Bachelor of Science Degree in Electrical Engineering from Kansas State University.
- 2) Bachelor of Science Degree in Business Administration Kansas State University.
- 3) Several Specialized Training courses and seminars pertaining to Microprocessors and Software programming.

Scot D. Rogers



NVLAP Lab Code 200087-0

Annex D FCC Site Registration Letter

FEDERAL COMMUNICATIONS COMMISSION

**Laboratory Division
7435 Oakland Mills Road
Columbia, MD 21046**

May 18, 2010

Registration Number: 90910

Rogers Labs, Inc.
4405 West 259th Terrace,
Louisburg, KS 66053

Attention: Scot Rogers,


Re: Measurement facility located at Louisburg
~~3 & 10 meter site~~
Date of Renewal: May 18, 2010

Dear Sir or Madam:

Your request for renewal of the registration of the subject measurement facility has been received. The information submitted has been placed in your file and the registration has been renewed. The name of your organization will remain on the list of facilities whose measurement data will be accepted in conjunction with applications for Certification under Parts 15 or 18 of the Commission's Rules. Please note that the file must be updated for any changes made to the facility and the registration must be renewed at least every three years.

Measurement facilities that have indicated that they are available to the public to perform measurement services on a fee basis may be found on the FCC website www.fcc.gov under E-Filing, OET Equipment Authorization Electronic Filing, Test Firms.

Sincerely,



Phyllis Farrish
Industry Analyst

Rogers Labs, Inc.
4405 W. 259th Terrace
Louisburg, KS 66053
Phone/Fax: (913) 837-3214
Revision 1

Mikrotikls SIA
Model: SXT-5HPnD
Test #: 110914B
Test to: CFR47 (15.247)
File: Mikrotikls SXT5HPnD 110914B TstRpt

SN: 34A101DD0BF3
FCC ID#: TV7SXT-5HPND
Date: October 30, 2011
Page 40 of 41



NVLAP Lab Code 200087-0

Annex E Industry Canada Site Registration Letter



May 26, 2010

OUR FILE: 46405-3041
Submission No: 140719

Rogers Labs Inc.

4405 West 259th Terrace
Louisburg, KY, 66053
USA

Attention: Mr. Scot D. Rogers

Dear Sir/Madame:

The Bureau has received your application for the renewal of a 3/10m OATS. Be advised that the information received was satisfactory to Industry Canada. The following number(s) is now associated to the site(s) for which registration / renewal was sought (**3041A-1**). Please reference the appropriate site number in the body of test reports containing measurements performed on the site. In addition, please keep for your records the following information;

- Your primary code is: **3041**
- The company number associated to the site(s) located at the above address is: **3041A**

Furthermore, to obtain or renew a unique site number, the applicant shall demonstrate that the site has been accredited to ANSI C63.4-2003 or later. A scope of accreditation indicating the accreditation by a recognized accreditation body to ANSI C63.4-2003 or later shall be accepted. Please indicate in a letter the previous assigned site number if applicable and the type of site (example: 3 metre OATS or 3 metre chamber). If the test facility is not accredited to ANSI C63.4-2003 or later, the test facility shall submit test data demonstrating full compliance with the ANSI standard. The Bureau will evaluate the filing to determine if recognition shall be granted.

The frequency for re-validation of the test site and the information that is required to be filed or retained by the testing party shall comply with the requirements established by the accrediting organization. However, in all cases, test site re-validation shall occur on an interval not to exceed two years. There is no fee or form associated with an OATS filing. OATS submissions are encouraged to be submitted electronically to the Bureau using the following URL;

http://strategis.ic.gc.ca/epic/internet/inceb-bhst.nsf/en/h_tt00052e.html.

If you have any questions, you may contact the Bureau by e-mail at certification.bureau@ic.gc.ca Please reference our file and submission number above for all correspondence.

Yours sincerely,

Dalwinder Gill
For: Wireless Laboratory Manager
Certification and Engineering Bureau
3701 Carling Ave., Building 94
P.O. Box 11490, Station "H"
Ottawa, Ontario K2H 8S2
Email: dalwinder.gill@ic.gc.ca
Tel. No. (613) 998-3363
Fax. No. (613) 990-4752

Rogers Labs, Inc.
4405 W. 259th Terrace
Louisburg, KS 66053
Phone/Fax: (913) 837-3214
Revision 1

Mikrotikls SIA
Model: SXT-5HPnD
Test #: 110914B
Test to: CFR47 (15.247)
File: Mikrotikls SXT5HPnD 110914B TstRpt

SN: 34A101DD0BF3
FCC ID#: TV7SXT-5HPND
Date: October 30, 2011
Page 41 of 41