



# RF Exposure Evaluation Report

**Equipment** : RouterBOARD wAP G-60ad  
**Brand Name** : RouterBOARD  
**Model No.** : RBwAPG-60ad  
**FCC ID** : TV7WAPG60AD  
**Standard** : 47 CFR Part 2.1091  
**Applicant** : Mikrotiks SIA  
Pernavas 46, Riga, LV-1009 Latvia  
**Manufacturer** : Mikrotiks SIA  
Pernavas 46, Riga, LV-1009 Latvia

The product sample received on Jun. 29, 2017 and completely tested on Aug. 03, 2017. We, SPORTON, would like to declare that the tested sample has been evaluated in accordance with 47 CFR Part 2.1091, and pass the limit.

Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

  
Cliff Chang  
SPORTON INTERNATIONAL INC.





## TABLE OF CONTENTS

**1 GENERAL DESCRIPTION .....4**

1.1 EUT General Information .....4

1.2 Testing Location .....4

**2 MAXIMUM PERMISSIBLE EXPOSURE .....5**

2.1 Limit of Maximum Permissible Exposure .....5

2.2 MPE Calculation Method .....5

2.3 Calculated Result and Limit .....6

**PHOTOGRAPHS OF EUT V01**



# 1 General Description

## 1.1 EUT General Information

The Channel Plan(s)			
Evaluation Mode	Frequency Range	Operating Frequency (GHz)	Modulation Type
60GHz	57-64 GHz	58.32 GHz 60.48 GHz 62.64 GHz	$\pi/2 - BPSK, \pi/2 - QPSK, \pi/2 - 16QAM$

## 1.2 Testing Location

Testing Location		
<input type="checkbox"/>	HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456      FAX : 886-3-327-0973
<input checked="" type="checkbox"/>	JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065      FAX : 886-3-656-9085

## 2 Maximum Permissible Exposure

### 2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; \*Plane-wave equivalent power density

### 2.2 MPE Calculation Method

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \qquad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

**E** = Electric field (V/m)

**P** = RF output power (W)

**G** = EUT Antenna numeric gain (numeric)

**d** = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$



### 2.3 Calculated Result and Limit

<b>Exposure Environment</b>	General Population / Uncontrolled Exposure				
<b>Temp</b>	22°C	<b>Humidity</b>	54%		
<b>Test Engineer</b>	DK Chang	<b>Test Date</b>	Jul. 08, 2017 ~ Jul. 15, 2017		
<b>Gain (dBi)</b>	60.48 GHz: 13.48				
<b>Test results</b>					
<b>Maximum EIPR Power of Test Frequency (GHz)</b>	<b>Average EIRP Power (dBm)</b>	<b>Average EIRP Power (mW)</b>	<b>Power Density (S) (mW/cm<sup>2</sup>)</b>	<b>Separation Distance (cm)</b>	<b>Limit of Power Density (S) (mW/cm<sup>2</sup>)</b>
60.48	30.58	1142.56	0.227	20	1.00