


PSA

佳邦科技股份有限公司


INPAQ TECHNOLOGY CO., LTD.

INPAQ P/N: WA-F-LA-02-114



PSA

PASSIVE SYSTEM ALLIANCE
INPAQ TECHNOLOGY CO., LTD.





FG-1501G

**FG-1500G, FG-1500G-DC, FG-1501G-DC, FG-801F, FG-800F, FG-800F-DC,
FG-801F-DC**

Presented by :Kevin Chen, RF R&D Dept.

Checked by :Leeting Hsieh

Approved by :ZhiWei Chen

INPAQ Technology Co., Ltd.

Last updated in Sep. 22 , 2022

Version:V0.1

Contents

Content Details

- Revised History
- Requirement of Antenna Design and Specification
- Results Summary (VSWR , peak gain, efficiency)
- 2D Radiation Pattern Results
- Conclusion & Comments

Revision History

Released Date	Version	Record
Aug. 24 th , 2022	0.0	Initial Release
Sep. 22 th , 2022	0.1	Factory sample

Requirements of Antenna Design and Specification

Requirements of Antenna Design

RF Function	Number of ANT	Frequency Band	Remark
BT	1	2400 – 2500MHz	

Requirements of Antenna Design and Specification


Requirements of Measurement

Item	Specification
Antenna Type	PIFA
Operating Frequency (MHz)	2400-2500
Bandwidth	100MHz
Return Loss	6 dB Typical
Polarization	Linear
Azimuth Bandwidth	Omni-directional
Peak Gain	0.73 dBi (Max)
Impedance	50Ω
Material	FPC
Maximum Power	1W
V.S.W.R	3:1
Radiation	Omni directional
Efficiency	50% (Max)
Connector / Cable Type	MHF I / O.D 1.13

VSWR Results

BT [2400 – 2500 MHz]

INPAQ



Results Summary


Peak gain & Efficiency – BT

INPAQ

Frequency (MHz)	Avg. Gain (dB)	Efficiency (%)	Peak Gain (dBi)	Peak Gain w/o Cable Loss (dBi)	Cable Loss
2400	-4.54	35.16	-1.75	-1.37	0.380
2410	-3.91	40.69	-1.22	-0.84	0.381
2420	-3.61	43.55	-0.24	0.14	0.381
2430	-3.35	46.21	0.06	0.44	0.382
2440	-3.38	45.93	0.1	0.48	0.382
2450	-3.12	48.75	0.49	0.88	0.385
2460	-2.93	50.92	0.73	1.12	0.385
2470	-3.12	48.75	0.48	0.87	0.385
2480	-3.41	45.64	0.28	0.67	0.386
2490	-3.71	42.58	-0.02	0.37	0.387
2500	-4.21	37.89	-0.6	-0.21	0.388


2D Radiation Pattern Results

BT@ 2400MHz




2D Radiation Pattern Results

BT@ 2450MHz



2D Radiation Pattern Results

BT@ 2500MHz



Conclusion & Comments

Antenna Performance Summary

- The efficiency of BT Antenna is 35.16~50.92%.
- The peak gain of BT Antenna is -1.75~0.73dB.

Thank you

本資料均屬機密，僅供指定之收件人使用，未經寄件人許可不得揭露、複製或散佈本信件。

This message and any attachments are confidential and may be legally privileged. Any unauthorized review, use or distribution by anyone other than the intended recipient is strictly prohibited. If you are not the intended recipient, please immediately notify the sender, completely delete this documents, and destroy all copies. Your cooperation will be highly appreciated.