

# RF EXPOSURE REPORT

## **CERTIFICATE OF CONFORMITY**

FCC Rule Part: FCC Part 2 (Section 2.1091)

Report No.: MFBDYS-WTW-P20080137B

**FCC ID:** TVE-2317069

**Product:** Secured Wireless Access Point

**Brand:** Fortinet

Model No.: FAP-231FL

Series Model: FORTIAP-231FLxxxxxx, FortiAP 231FLxxxxxx, FAP-231FLxxxxxx

(where "x" can be used as "A-Z", or "0-9", or "-", or blank for software changes or

marketing purposes only)

Received Date: 2022/9/12

Test Date: 2022/10/5

Issued Date: 2022/12/01

Applicant: Fortinet, Inc.

Address: 899 Kifer Road, Sunnyvale, CA 94086 USA

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kewi Shan Dist., Taoyuan City 33383, Taiwan

FCC Registration / 788550 / TW0003

**Designation Number:** 

Jeremy Lin / Project Engineer

This test report consists of 10 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The test results in the report only apply to the tested sample. The test results in this report are traceable to the national or international standards.





Prepared by : Polly Chien / Specialist

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <a href="http://www.bureauveritas.com/home/about-us/curbusiness/cps/about-us/terms-conditions/">http://www.bureauveritas.com/home/about-us/curbusiness/cps/about-us/terms-conditions/</a> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



# **Table of Contents**

Relea	ase Control Record	3
	Certificate	
	Applicable RF Exposure Limit	
	Applicable Evaluation Criteria	
	Test Results	
4.1	RF Exposure	8
5	Conclusion	9
6	Information of the Testing Laboratories	10



### **Release Control Record**

Issue No.	Description	Date Issued
MFBDYS-WTW-P20080137B	Original release.	2022/12/01

Report No.: MFBDYS-WTW-P20080137B Page No. 3 / 10 Reference No.: BDYS-WTW-P22090347 Page No. 3 / 10



#### 1 Certificate

**Product:** Secured Wireless Access Point

**Brand:** Fortinet

Test Model: FAP-231FL

Series Model: FORTIAP-231FLxxxxxx, FortiAP 231FLxxxxxx, FAP-231FLxxxxxx

(where "x" can be used as "A-Z", or "0-9", or "-", or blank for software changes or marketing

purposes only)

Sample Status: Engineering sample

Applicant: Fortinet, Inc.

**Test Date:** 2022/10/5

FCC Rule Part: FCC Part 2 (Section 2.1091)

Standard: KDB 447498 D04 Interim General RF Exposure Guidance v01

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.



#### 2 **Applicable RF Exposure Limit**

- § 1.1310 Radiofrequency radiation exposure limits.
- (a) Specific absorption rate (SAR) shall be used to evaluate the environmental impact of human exposure to radiofrequency (RF) radiation as specified in § 1.1307(b) of this part within the frequency range of 100 kHz to 6 GHz (inclusive).
- (b) The SAR limits for occupational/controlled exposure are 0.4 W/kg, as averaged over the whole body, and a peak spatialaverage SAR of 8 W/kg, averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube). Exceptions are the parts of the human body treated as extremities, such as hands, wrists, feet, ankles, and pinnae, where the peak spatial-average SAR limit for occupational/controlled exposure is 20 W/kg, averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube). Exposure may be averaged over a time period not to exceed 6 minutes to determine compliance with occupational/controlled SAR limits.
- (c) The SAR limits for general population/uncontrolled exposure are 0.08 W/kg, as averaged over the whole body, and a peak spatial-average SAR of 1.6 W/kg, averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube). Exceptions are the parts of the human body treated as extremities, such as hands, wrists, feet, ankles, and pinnae, where the peak spatial-average SAR limit is 4 W/kg, averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube). Exposure may be averaged over a time period not to exceed 30 minutes to determine compliance with general population/uncontrolled SAR limits.

#### (e) Maximum Permissible Exposure (MPE) to radiofrequency electromagnetic fields

## ➤ Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	. , .		Power Density (mW/cm <sup>2</sup> )	Average Time (minutes)						
	Limits For General Population / Uncontrolled Exposure									
0.3-1.34	614	1.63	(100)*	30						
1.34-30	824/f	2.19/f	(180/f <sup>2</sup> )*	30						
30-300	27.5	0.073	0.2	30						
300-1500			f/1500	30						
1500-100,000			1.0	30						

f = frequency in MHz. \* = Plane-wave equivalent power density.

#### Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (minutes)					
	Limits For General Population / Uncontrolled Exposure								
0.3-3.0	614	1.63	*(100)	⊴6					
3.0-30	1842/f	4.89/f	*(900/f <sup>2</sup> )	<6					
30-300	61.4	0.163	1.0	<6					
300-1,500			f/300	<6					
1,500-100,000			5	<6					

f = frequency in MHz. \* = Plane-wave equivalent power density.

Report No.: MFBDYS-WTW-P20080137B Page No. 5 / 10 Report Format Version: 7.1.0

Reference No.: BDYS-WTW-P22090347



# 3 Applicable Evaluation Criteria

#### **Exemption Evaluation**

MPE-based Exemption - §1.1307(b)(3)(i)(B)

For mobile devices that are not exempt per Table 1 of §1.1307(b)(1)(i)(C) and device at distances from 20 cm to 40 cm and in 0.3 GHz to 6 GHz. The MPE-based test exemption condition is in terms of ERP, defined as the product of the maximum antenna gain and the delivered maximum time-averaged power.

$$P_{\text{th}} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \le f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \le f \le 6 \text{ GHz} \end{cases}$$

Report No.: MFBDYS-WTW-P20080137B Page No. 6 / 10 Reference No.: BDYS-WTW-P22090347 Report Format Version: 7.1.0



#### **Multiple RF Sources (Simultaneous Operations)**

Fixed RF sources operating in the same time-averaging period – §1.1307(b)(3)(ii)(B)

Either SAR-based or MPE-based exemption may be considered for test exemption for fixed, mobile, or portable device exposure conditions; therefore, the contributions from each exemption in conjunction with the measured SAR (Evaluatedk term) should be used to determine exemption for simultaneous transmission according to Formula below,

$$\sum_{i=1}^{a} \frac{P_i}{P_{th,i}} + \sum_{j=1}^{b} \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^{c} \frac{Evaluated_k}{Exposure\ Limit_k} \le 1$$

The sum of the ratios of the applicable terms for SAR-based, MPE-based and measured SAR or MPE should be less than 1, to determine simultaneous transmission exposure compliance.

#### Where:

a = number of fixed, mobile, or portable RF sources claiming exemption using <u>paragraph (b)(3)(i)(B)</u> of this section for  $P_{th}$ , including existing exempt transmitters and those being added.

c = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters.

 $P_{th,i}$  = the exemption threshold power ( $P_{th}$ ) according to <u>paragraph</u> (<u>b)(3)(i)(B)</u> of this section for fixed, mobile, or portable RF source *i.*  $ERP_{th,j}$  = exemption threshold ERP for fixed, mobile, or portable RF source *j*, at a distance of at least  $\lambda/2\pi$  according to the applicable formula of paragraph (b)(3)(i)(C) of this section.

Exposure  $Limit_k$  = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source k, as applicable from § 1.1310 of this chapter.

Reference No.: BDYS-WTW-P22090347

b = number of fixed, mobile, or portable RF sources claiming exemption using <u>paragraph (b)(3)(i)(C)</u> of this section for Threshold ERP, including existing exempt transmitters and those being added.

 $P_i$  = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive).

 $ERP_j$  = the ERP of fixed, mobile, or portable RF source j.

 $Evaluated_k$  = the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure.



### 4 Test Results

### 4.1 RF Exposure

Input	Power:	120 Vac,	60 Hz	Environmental Conditions:	23°C, 65% RH	Tested By:	Tim Chen	
-------	--------	----------	-------	---------------------------	--------------	------------	----------	--

#### For Single RF Source

MPE-based Exemption §1.1307(b)(3)(i)(B)									
Operation Mode	Frequency Band (MHz)	Average Power (mW)	Antenna Gain (dBi)	Maximum ERP (mW)	Distance (cm)	Limit Threshold (mW)	Test Result		
CDD_WLAN 2.4 GHz	2412-2462	365.668	4.9	688.79	20	3060	Pass		
BF_WLAN 2.4 GHz	2412-2462	173.207	7.91	652.477	20	3060	Pass		
Scan_WLAN 2.4 GHz	2412-2462	128.825	4	197.242	20	3060	Pass		
CDD_WLAN 5 GHz	5180-5825	373.084	5.5	806.876	20	3060	Pass		
BF_WLAN 5 GHz	5180-5825	180.811	8.51	782.033	20	3060	Pass		
Scan_WLAN 5 GHz	5180-5825	142.889	5.1	281.838	20	3060	Pass		

## For Multiple RF Sources (Simultaneous Operations Condition 1)

of manapiera Courses (emidicanocae operations condition 1)									
Multiple RF Sources (Simultaneous Operations)									
Operation Mode	Frequency Band (MHz)	Maximum ERP (mW)	Limit Threshold (mW)	Ratio	Sum of Ratios	Limit of Ratios	Test Result		
CDD_WLAN 2.4 GHz	2412-2462	688.790	3060	0.225					
CDD_WLAN 5 GHz	5180-5825	806.876	3060	0.264	0.581	1	Pass		
Scan_WLAN 5 GHz	5180-5825	281.838	3060	0.092					

## For Multiple RF Sources (Simultaneous Operations Condition 2)

Multiple RF Sources (Simultaneous Operations)									
Operation Mode	Frequency Band (MHz)	Maximum ERP (mW)	Limit Threshold (mW)	Ratio	Sum of Ratios	Limit of Ratios	Test Result		
Scan_WLAN 2.4 GHz	2412-2462	197.242	3060	0.064	0.328	1	Pass		
CDD_WLAN 5 GHz	5180-5825	806.876	3060	0.264		-			

Report No.: MFBDYS-WTW-P20080137B Page No. 8 / 10 Reference No.: BDYS-WTW-P22090347 Page No. 8 / 10



#### 5 Conclusion

Source-base time average power is below Exemption Criteria and/or Routine Evaluation MPE thresholds, therefore the device is compliant FCC RF exposure requirement.

Report No.: MFBDYS-WTW-P20080137B Page No. 9 / 10 Reference No.: BDYS-WTW-P22090347 Page No. 9 / 10



#### 6 Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

Hsin Chu EMC/RF/Telecom Lab

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180 Tel: 886-3-6668565 Fax: 886-2-26051924 Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232 Fax: 886-3-3270892

Email: <a href="mailto:service.adt@bureauveritas.com">service.adt@bureauveritas.com</a>. <a href="mailto:web.bureauveritas.com.tw">web Site: <a href="mailto:http://ee.bureauveritas.com.tw">http://ee.bureauveritas.com.tw</a>.

The address and road map of all our labs can be found in our web site also.

--- END ---

Report No.: MFBDYS-WTW-P20080137B Page No. 10 / 10 Reference No.: BDYS-WTW-P22090347