RF EXPOSURE EVALUATION REPORT

FCC ID : TVE-240701

Equipment : Network Switch

Brand Name : FORTINET F RTINET.

Model Name : FortiSwitch 124G-FPOExxxxxxxxxxx,

FS-124G-FPOExxxxxxxxxx

(where "x" can be used as "A-Z", or "0-9", or "-", or blank for software changes or marketing purposes only)

Marketing Name : FortiSwitch 124G-FPOE

Applicant : Fortinet, Inc.

909 Kifer Road, Sunnyvale, CA. 94086 USA

Manufacturer : Fortinet, Inc.

909 Kifer Road, Sunnyvale, CA. 94086 USA

Standard : 47 CFR Part 2.1091

We, SPORTON INTERNATIONAL INC has been evaluated this product in accordance with 47 CFR Part2.1091 and it complies with applicable limit.

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 1190) and the FCC designation No. TW1190 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC evaluation.

The results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. Laboratory, the test report shall not be reproduced except in full.

Approved by: Cona Huang / Deputy Manager



Report No. : FA451712

Sporton International Inc. Wensan Laboratory

No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan

TEL: 886-3-327-3456 Page: 1 of 6
FAX: 886-3-328-4978 Issued Date: Jan. 16, 2024

SPORTON LAB. RF EXPOSURE EVALUATION REPORT

Report No. : FA451712

Table of Contents

1.	DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	4
	MAXIMUM RF AVERAGE OUTPUT POWER AMONG PRODUCTION UNITS	
3.	RF EXPOSURE LIMIT INTRODUCTION	5
4.	RADIO FREQUENCY RADIATION EXPOSURE EVALUATION	6
	4.1 Standalone Power Density Calculation	6

TEL: 886-3-327-3456 Page: 2 of 6
FAX: 886-3-328-4978 Issued Date: Jan. 16, 2024

History of this test report

Report No. : FA451712

Report No. Version		Description	Issued Date
FA451712 Rev. 01		Initial issue of report	Jan. 16, 2024

TEL: 886-3-327-3456 Page: 3 of 6
FAX: 886-3-328-4978 Issued Date: Jan. 16, 2024

1. <u>Description of Equipment Under Test (EUT)</u>

Product Feature & Specification				
EUT Type Network Switch				
Brand Name	FORTINET FEIRTINET.			
Model Name	FortiSwitch 124G-FPOExxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx			
Marketing Name	FortiSwitch 124G-FPOE			
FCC ID	TVE-240701			
Wireless Technology and Frequency Range	Bluetooth: 2400 MHz ~ 2483.5 MHz			
Mode	Bluetooth LE			

Report No. : FA451712

Reviewed by: <u>Jason Wang</u> Report Producer: <u>Paula Chen</u>

2. Maximum RF average output power among production units

BLE 1Mbps				
Channel	Frequacy(MHz)	Maximum power(dBm)		
0	2402	7		
19	2440	6.9		
39	2480	7		

BLE 2Mbps				
Channel	Frequacy(MHz)	Maximum power(dBm)		
0	2402	7		
19	2440	6.9		
39	2480	7		

TEL: 886-3-327-3456 Page: 4 of 6
FAX: 886-3-328-4978 Issued Date: Jan. 16, 2024

SPORTON LAB. RF EXPOSURE EVALUATION REPORT

3. RF Exposure Limit Introduction

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Report No. : FA451712

Page: 5 of 6

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)	
800 St.	(A) Limits for O	ccupational/Controlled Expos	sures	W	
0.3-3.0	614	1.63	*(100)	6	
3.0-30	1842/	f 4.89/1	*(900/f2)	6	
30-300	61.4	0.163	1.0	6	
300-1500			f/300	6	
1500-100,000			5	6	
	(B) Limits for Gene	ral Population/Uncontrolled I	Exposure		
0.3-1.34	614	1.63	*(100)	30	
1.34-30 824		f 2.19/1	*(180/f2)	30	
30-300	27.5	0.073	0.2	30	
300-1500			f/1500	30	
1500-100,000			1.0	30	

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$S=\frac{PG}{4\pi R^2}$$

Where:

S = Power Density

P = Output Power at Antenna Terminals

G = Gain of Transmit Antenna (linear gain)

R = Distance from Transmitting Antenna

TEL: 886-3-327-3456 FAX: 886-3-328-4978 Issued Date : Jan. 16, 2024

SPORTON LAB. RF EXPOSURE EVALUATION REPORT

4. Radio Frequency Radiation Exposure Evaluation

4.1. Standalone Power Density Calculation

Band	Antenna Gain (dBi)	Maximum Power (dBm)	Maximum PG (mW)	Power Density at 20cm (mW/cm^2)	Limit (mW/cm^2)
Bluetooth	2.0	7.0	7.94	0.002	1.000

Report No. : FA451712

Conclusion:

According to 47 CFR §2.1091, the RF exposure analysis concludes that the RF Exposure is FCC compliant.

TEL: 886-3-327-3456 Page: 6 of 6 FAX: 886-3-328-4978 Issued Date : Jan. 16, 2024