

RF Exposure Report

Report No.: SA161026C20D

FCC ID: TVE-241BC041

Test Model: FortiAP U221EV, FortiAP U223EV

Series Model: FortiAP U221EVxxxxxx, FAP-U221EVxxxxxx, FORTIAP-U221EVxxxxxx, FortiAP U223EVxxxxxx, FAP-U223EVxxxxxx, FORTIAP-U223EVxxxxxx (where "x" can be used as "A-Z" or "0-9" or "-" or blank for software changes or marketing purposes only)

Received Date: Mar. 28, 2018

Test Date: Mar. 28 ~ Jun. 01, 2018

Issued Date: Jun. 04, 2018

Applicant: Fortinet Inc.

Address: 899 Kifer Road Sunnyvale, CA 94086 USA

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan, R.O.C.

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 33383, TAIWAN (R.O.C.)



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE).....	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
3 Calculation Result of Maximum Conducted Power	6



Release Control Record

Issue No.	Description	Date Issued
SA161026C20D	Original release	Jun. 04, 2018

1 Certificate of Conformity

Product: Secured Wireless Access Point

Brand: Fortinet Inc.

Test Model: FortiAP U221EV, FortiAP U223EV

Series Model: FortiAP U221EVxxxxxx, FAP-U221EVxxxxxx, FORTIAP-U221EVxxxxxx, FortiAP U223EVxxxxxx, FAP-U223EVxxxxxx, FORTIAP-U223EVxxxxxx (where "x" can be used as "A-Z" or "0-9" or "-" or blank for software changes or marketing purposes only)

Sample Status: Engineering sample

Applicant: Fortinet Inc.

Test Date: Mar. 28 ~ Jun. 01, 2018

Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

IEEE C95.1-1992

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by : Pettie Chen , **Date:** Jun. 04, 2018
Pettie Chen / Senior Specialist

Approved by : Bruce Chen , **Date:** Jun. 04, 2018
Bruce Chen / Project Engineer

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	f/1500	30
1500-100,000	1.0	30

f = Frequency in MHz; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

3 Calculation Result of Maximum Conducted Power

Frequency Band (MHz)	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WLAN					
Internal antenna					
CDD mode					
2412-2462	22.49	7.96	20	0.221	1
5180-5240	21.71	8.84	20	0.226	1
5250-5350	21.03	8.84	20	0.193	1
5470-5725	21.08	8.84	20	0.195	1
5745-5825	21.64	8.84	20	0.222	1
Beamforming mode					
2412-2462	18.64	7.96	20	0.091	1
5180-5240	18.71	8.84	20	0.113	1
5250-5350	18.02	8.84	20	0.097	1
5470-5725	18.07	8.84	20	0.098	1
5745-5825	18.64	8.84	20	0.111	1
External antenna					
CDD mode					
2412-2462	22.49	7.59	20	0.203	1
5180-5240	21.71	8.36	20	0.202	1
5250-5350	21.43	8.36	20	0.190	1
5470-5725	21.46	8.36	20	0.191	1
5745-5825	21.64	8.36	20	0.199	1
Beamforming mode					
2412-2462	18.64	7.59	20	0.084	1
5180-5240	18.71	8.36	20	0.101	1
5250-5350	18.39	8.36	20	0.094	1
5470-5725	18.45	8.36	20	0.095	1
5745-5825	18.64	8.36	20	0.100	1
BT					
BT EDR	10.69	3.67	20	0.005	1
BT LE	6.58	3.67	20	0.002	1

Note:

Internal antenna 2412~2462MHz: Directional gain = 4.95dBi + 10log(2) = 7.96dBi

Internal antenna 5180~5825MHz: Directional gain = 5.83dBi + 10log(2) = 8.84dBi

External antenna 2412~2462MHz: Directional gain = 4.58dBi + 10log(2) = 7.59dBi

External antenna 5180~5825MHz: Directional gain = 5.35dBi + 10log(2) = 8.36dBi

Frequency Band	Max. Power (dBm)		Total Power (dBm)	Power Limit (dBm)
	WLAN 2.4GHz	BT EDR		
2.4GHz	22.49	10.69	22.77	30

Frequency Band	Max. Power (dBm)		Total Power (dBm)	Power Limit (dBm)
	WLAN 2.4GHz	BT LE		
2.4GHz	22.49	6.58	22.60	30

CONCLUSION:

Both of the WLAN 2.4G & WLAN 5G & BT can transmit simultaneously, the formula of calculated the MPE is:

$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$

CPD = Calculation power density

LPD = Limit of power density

WLAN 2.4GHz (Internal antenna) + WLAN 5GHz (Internal antenna) + BT EDR = $0.221 + 0.226 + 0.005 = 0.452 < 1$

WLAN 2.4GHz (Internal antenna) + WLAN 5GHz (Internal antenna) + BT LE = $0.221 + 0.226 + 0.002 = 0.449 < 1$

WLAN 2.4GHz (External antenna) + WLAN 5GHz (External antenna) + BT EDR = $0.203 + 0.202 + 0.005 = 0.410 < 1$

WLAN 2.4GHz (External antenna) + WLAN 5GHz (External antenna) + BT LE = $0.203 + 0.202 + 0.002 = 0.407 < 1$

Therefore the maximum calculations of above situations are less than the "1" limit.

---END---