



Radio Exposure Evaluation Report

FCC ID : TVE-4111BBE0671

Equipment : Secured Wireless Access Point

Brand Name : FORTINET

Model Name : FortiAP U432Fxxxxxx, FAP-U432Fxxxxxx,
FORTIAP-U432Fxxxxxx
(where “x” can be “A-Z”, or “0-9”, or “-“, or blank for software purposes or marketing purposes only)

Applicant : Fortinet, Inc.
899 Kifer Road, Sunnyvale, CA 94086, USA

Manufacturer : Fortinet, Inc.
899 Kifer Road, Sunnyvale, CA 94086, USA

Standard : 47 CFR FCC Part 2 Subpart J, section 2.1091

The product was received on Feb. 09, 2022, and testing was started from May 26, 2022 and completed on Aug. 25, 2022. We, SPORTON INTERNATIONAL INC. Hsinhua Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in 47 CFR FCC Part 2 Subpart J, section 2.1091 and shown compliance with the applicable technical standards.

The test results in this variant report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. Hsinhua Laboratory, the test report shall not be reproduced except in full.

Approved by: Jackson Tsai

SPORTON INTERNATIONAL INC. Hsinhua Laboratory
No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.)



Table of Contents

HISTORY OF THIS TEST REPORT3

1 GENERAL DESCRIPTION5

1.1 Information.....5

1.2 Applicable Standards8

1.3 Testing Location8

2 MAXIMUM PERMISSIBLE EXPOSURE9

2.1 Limit of Maximum Permissible Exposure9

2.2 RF Exposure Exempt Measurement10

2.3 Multiple RF Sources Exposure11

2.4 MPE Calculation Method12

2.5 Calculated Result and Limit.....13

Photographs of EUT V01



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
2	-	Exposure evaluation	PASS	-

Declaration of Conformity:
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
Comments and Explanations:
None

Reviewed by: Barry Hsiao

Report Producer: Debby Hung

1 General Description

1.1 Information

1.1.1 EUT General Information

RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
2.4GHz WLAN	2400-2483.5	2412-2462	802.11b: DSSS (DBPSK, DQPSK, CCK) 802.11g/n/VHT/ax: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)
5GHz WLAN	5150-5250 5250-5350 5470-5725 5725-5850	5180-5240 5260-5320 5500-5700 5745-5825	802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac/ax: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)
Bluetooth	2400-2483.5	2402-2480	LE: DSSS (GFSK)
ZigBee	2400-2483.5	2405-2480	DSSS (O-QPSK)

1.1.2 Antenna Information

Ant.	Brand	Model Name	Antenna Type	Connector
1	SENAO	5718A0619300	Dipole	N-type
2	SENAO	5718A0619300	Dipole	N-type
3	SENAO	5718A0619300	Dipole	N-type
4	SENAO	5718A0619300	Dipole	N-type
5	SENAO	5718A0620300	Dipole	N-type
6	SENAO	5718A0620300	Dipole	N-type
7	SENAO	5718A0620300	Dipole	N-type
8	SENAO	5718A0620300	Dipole	N-type
9	SENAO	5718A0619300	Dipole	N-type
10	SENAO	5718A0619300	Dipole	N-type
11	SENAO	5718A0618300	Dipole	N-type
12	Fortinet	FANT-10ACAX-1213-D-N	Directional	N-type



Radio	Ant.	Port	Antenna Gain (dBi)				Cable Loss Gain (dBi)			
			2.4G	5G	BT	Zigbee	2.4G	5G	BT	Zigbee
1	1	1	5.5	7.2	-	-	0.6	1	-	-
	2	2	5.5	7.2	-	-	0.6	1	-	-
	3	3	5.5	7.2	-	-	0.5	0.8	-	-
	4	4	5.5	7.2	-	-	0.4	0.7	-	-
2	5	1	-	6.3	-	-	-	1	-	-
	6	2	-	6.3	-	-	-	1.1	-	-
	7	3	-	6.3	-	-	-	0.9	-	-
	8	4	-	6.3	-	-	-	0.9	-	-
3	9	1	5.5	7.2	-	-	0.6	1	-	-
	10	2	5.5	7.2	-	-	0.6	1	-	-
BT+Zigbee	11	1	-	-	4.5	4.5	-	-	0.5	0.5
1	12	1	12	13	-	-	0.6	1	-	-
1	12	2	12	13	-	-	0.6	1	-	-
1	12	3	12	13	-	-	0.5	0.8	-	-
1	12	4	12	13	-	-	0.4	0.7	-	-
2	12	1	12	13	-	-	-	1	-	-
2	12	2	12	13	-	-	-	1.1	-	-
2	12	3	12	13	-	-	-	0.9	-	-
2	12	4	12	13	-	-	-	0.9	-	-
3	12	1	12	13	-	-	0.6	1	-	-
3	12	2	12	13	-	-	0.6	1	-	-

Note 1: The EUT has twelve antennas.

For 2.4GHz function:

Radio 1

For IEEE 802.11 b/g/n/VHT/ax mode (4TX/4RX)

Ant. 1 (port 1), Ant. 2 (port 2), Ant. 3 (port 3) and Ant. 4 (port 4) could transmit/receive simultaneously.

Ant. 12 could transmit/receive simultaneously.

Radio 3

For IEEE 802.11 b/g/n/VHT/ax mode (2TX/2RX)

Ant. 9 (port 1) and Ant. 10 (port 2) could transmit/receive simultaneously.

Ant. 12 could transmit/receive simultaneously.

For 5GHz function:

Radio 1

For IEEE 802.11 a/n/ac/ax mode (4TX/4RX)

Ant. 1 (port 1), Ant. 2 (port 2), Ant. 3 (port 3) and Ant. 4 (port 4) could transmit/receive simultaneously.



Ant. 12 could transmit/receive simultaneously.

Radio 2

For IEEE 802.11 a/n/ac/ax mode (4TX/4RX)

Ant. 5 (port 1), Ant. 6 (port 2), Ant. 7 (port 3) and Ant. 8 (port 4) could transmit/receive simultaneously.

Ant. 12 could transmit/receive simultaneously.

Radio 3

For IEEE 802.11 a/n/ac/ax mode (2TX/2RX)

Ant. 9 (port 1) and Ant. 10 (port 2) could transmit/receive simultaneously.

Ant. 12 could transmit/receive simultaneously.

For Bluetooth function:

For IEEE 802.15.1 Bluetooth mode (1TX/1RX)

Only Ant. 11 (port 1) could transmit/receive.

For Zigbee function:

For Zigbee mode (1TX/1RX)

Only Ant. 11 (port 1) could transmit/receive.

1.1.3 Table for Permissive Change

This product is an extension of original one reported under Sporton project number: FA0D1422 and FA0D1422-01 Below is the table for the change of the product with respect to the original one.

Modifications	Performance Checking
Antenna 12 was added	All

1.1.4 Table for Multiple Listing

The brand/model names in the following table are all refer to the identical product.

Brand Name	Model Name	Description
FORTINET	FortiAP U432Fxxxxxx	All the models are identical, the difference model for served as marketing strategy.
	FAP-U432Fxxxxxx	
	FORTIAP-U432Fxxxxxx	



1.1.5 Accessories

Accessories				
PoE Adapter	Brand Name	Senao Inc.	Model Name	PIN060-54PR
	Power Rating	I/P: 100-240Vac, 1.5A, 50-60Hz, O/P: 54Vdc, 1.11A		
AC CORD	Brand Name	I-SHENG	Model Name	AC CORD 600mm
	Signal Line	0.5 meter, shielded cable, w/o ferrite core		
Ground Wire	Brand Name	BO YAO	Model Name	WIRE GEN AWG10 180cm
	Signal Line	1.8 meter, shielded cable, w/o ferrite core		
Bracket wall mount	Brand Name	XIERTEK	Model Name	BRACKET WALL MOUNT
Bracket pole mount	Brand Name	CUN SHENG	Model Name	BRACKET POLE MOUN

Reminder: Regarding to more detail and other information, please refer to user manual.

1.2 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR FCC Part 2 Subpart J, section 2.1091
- ♦ KDB 447498 D04 Interim General RF Exposure Guidance v01

The following reference test guidance is not within the scope of accreditation of TAF.

- ♦ 47 CFR Part 1.1307
- ♦ 47 CFR Part 1.1310

1.3 Testing Location

Test Lab. : Sporton International Inc. Hsinhua Laboratory				
<input checked="" type="checkbox"/>	Hsinhua (TAF: 3785)	ADD: No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.)	TEL: 886-3-327-3456	FAX: 886-3-327-0973
Test site Designation No. TW3785 with FCC.				
<input type="checkbox"/>	Wen 33rd.St. (TAF: 3785)	ADD: No.14-1, Ln. 19, Wen 33rd St., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)	TEL: 886-3-318-0787	FAX: 886-3-318-0287
Test site Designation No. TW0008 with FCC.				

2 Maximum Permissible Exposure

2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f ²)*	6
30-300	61.4	0.163	1.0	6
300-1500	-	-	F/300	6
1500-100,000	-	-	5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	F/1500	30
1500-100,000	-	-	1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

Multiple Transmitters Condition	
Co-location as simultaneously transmitting (co-transmitting) and the evaluation shall be consider that simultaneous transmissions from co-located devices the individual transmitters are evaluated separately. After sum of the individual value (basic restriction / reference level) are measured/calculated also have to under basic restriction / reference level.	
Co-transmitting mode:	
1.	Radio 1(2.4G)+ Radio 2(5G)+ Radio 3(2.4G)+ Bluetooth
2.	Radio 1(5G)+ Radio 2(5G)+ Radio 3(2.4G)+ Bluetooth
3.	Radio 1(5G)+ Radio 2(5G)+ Radio 3(5G)+ Bluetooth
4.	Radio 1(2.4G)+ Radio 2(5G)+ Radio 3(5G)+ Bluetooth
5.	Radio 1(2.4G)+ Radio 2(5G)+ Radio 3(2.4G)+Zigbee
6.	Radio 1(5G)+ Radio 2(5G)+ Radio 3(2.4G)+Zigbee
7.	Radio 1(5G)+ Radio 2(5G)+ Radio 3(5G)+Zigbee
8.	Radio 1(2.4G)+ Radio 2(5G)+ Radio 3(5G)+Zigbee

2.2 RF Exposure Exempt Measurement

Option	Refer Std.	Exemption Exposure Thresholds (TL)
A	§1.1307(b)(3)(i)(A)	Available maximum time-averaged power is no more than 1 mW
B	§1.1307(b)(3)(i)(B)	$P_{th}(mW) = \begin{cases} ERP_{20cm} (d / 20cm)^x & \rightarrow d \leq 20cm \\ ERP_{20cm} & \rightarrow 20cm < d \leq 40cm \end{cases}$ $x = -\log_{10} \left(\frac{60}{ERP_{20cm} \sqrt{f}} \right) \text{ and } f \text{ is in GHz}$ $\begin{cases} ERP_{20cm} : 0.3GHz \leq f < 1.5GHz \rightarrow 2040f(mW) \\ ERP_{20cm} : 1.5GHz \leq f \leq 6GHz \rightarrow 3060(mW) \end{cases}$
C	§1.1307(b)(3)(i)(C)	$\begin{cases} 0.3 \sim 1.34MHz \rightarrow ERP(W) = 1920R^2 \\ 1.34 \sim 30MHz \rightarrow ERP(W) = 3450R^2 / f^2 \\ 30 \sim 300MHz \rightarrow ERP(W) = 3.83R^2 \\ 300 \sim 1500MHz \rightarrow ERP(W) = 0.0128R^2 f \\ 1500 \sim 100000MHz \rightarrow ERP(W) = 19.2R^2 \end{cases}$ <p>f is in MHz; R is in m; $R > \lambda / 2\pi$</p>

2.3 Multiple RF Sources Exposure

Refer Std.	Exemption Exposure Thresholds (TL)
§1.1307(b)(3)(ii)(A)	<p>The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required)</p>
§1.1307(b)(3)(ii)(B)	$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{ExposureLimit_k} \leq 1$ <p>a = number of fixed, mobile, or portable RF sources claiming exemption using paragraph §1.1307(b)(3)(i)(B) of this section for P , including existing exempt transmitters and those being added.</p> <p>b = number of fixed, mobile, or portable RF sources claiming exemption using paragraph §1.1307(b)(3)(i)(C) of this section for Threshold ERP, including existing exempt transmitters and those being added.</p> <p>c = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters.</p> <p>P_i = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive).</p> <p>P_{th,i} = the exemption threshold power (P_{th}) according to paragraph §1.1307(b)(3)(i)(B) of this section for fixed, mobile, or portable RF source i.</p> <p>ERP_j = the ERP of fixed, mobile, or portable RF source j.</p> <p>ERP_{th,j} = exemption threshold ERP for fixed, mobile, or portable RF source j, at a distance of at least λ/2π according to the applicable formula of paragraph §1.1307(b)(3)(i)(C) of this section.</p> <p>Evaluated_k = the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure.</p> <p>Evaluated Limit_k = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source k, as applicable from § 1.1310 of this chapter.</p>



2.4 MPE Calculation Method

The MPE was calculated at 62 cm to show compliance with the power density limit. The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \qquad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

2.5 Calculated Result and Limit

Exposure Environment: General Population / Uncontrolled Exposure

Radio 1(2.4G) _Non-Beamforming

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (dBm)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL EIRP (dBm)	TL Ratio
2.4G;G1D	11.60	24.24	35.84	0.00	2339.43	62	0.07943	1.00000	C	7380.480	0.31698
2.4G;D1D	11.60	24.34	35.94	0.00	2393.92	62	0.08128	1.00000	C	7380.480	0.32436

Radio 3(2.4G) _Non-Beamforming

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (dBm)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL EIRP (dBm)	TL Ratio
2.4G;G1D	11.40	24.52	35.92	0.00	2382.92	62	0.08091	1.00000	C	7380.480	0.32287
2.4G;D1D	11.40	23.47	34.87	0.00	1871.16	62	0.06353	1.00000	C	7380.480	0.25353

Radio 1(2.4G) _Beamforming

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (dBm)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL EIRP (dBm)	TL Ratio
2.4G;D1D	17.50	18.47	35.97	0.00	2410.52	62	0.08185	1.00000	C	7380.480	0.32661

Radio 3(2.4G) _Beamforming

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (dBm)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL EIRP (dBm)	TL Ratio
2.4G;D1D	14.41	21.43	35.84	0.00	2339.43	62	0.07943	1.00000	C	7380.480	0.31698

Radio 1(5G) _Non-Beamforming

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (dBm)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL EIRP (dBm)	TL Ratio
5.6G;D1D	12.30	17.47	29.77	0.00	578.24	62	0.01963	1.00000	C	7380.480	0.07835
5.8G;D1D	12.30	23.68	35.98	0.00	2416.07	62	0.08204	1.00000	C	7380.480	0.32736

Radio 2(5G) _Non-Beamforming

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (dBm)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL EIRP (dBm)	TL Ratio
5.2G;D1D	12.10	20.76	32.86	0.00	1177.90	62	0.04000	1.00000	C	7380.480	0.15960
5.3G;D1D	12.10	17.79	29.89	0.00	594.44	62	0.02018	1.00000	C	7380.480	0.08054
5.6G;D1D	12.10	17.86	29.96	0.00	604.10	62	0.02051	1.00000	C	7380.480	0.08185
5.8G;D1D	12.10	23.83	35.93	0.00	2388.42	62	0.08110	1.00000	C	7380.480	0.32361



Radio 3(5G) _Non-Beamforming

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (dBm)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL EIRP (dBm)	TL Ratio
5.2G;D1D	12.00	21.21	33.21	0.00	1276.76	62	0.04335	1.00000	C	7380.480	0.17299
5.3G;D1D	12.00	17.19	29.19	0.00	505.95	62	0.01718	1.00000	C	7380.480	0.06855
5.6G;D1D	12.00	17.94	29.94	0.00	601.33	62	0.02042	1.00000	C	7380.480	0.08148
5.8G;D1D	12.00	23.93	35.93	0.00	2388.42	62	0.08110	1.00000	C	7380.480	0.32361

Radio 1(5G) _Beamforming

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (dBm)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL EIRP (dBm)	TL Ratio
5.6G;D1D	18.15	11.82	29.97	0.00	605.49	62	0.02056	1.00000	C	7380.480	0.08204
5.8G;D1D	18.15	17.81	35.96	0.00	2404.97	62	0.08166	1.00000	C	7380.480	0.32586

Radio 2(5G) _Beamforming

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (dBm)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL EIRP (dBm)	TL Ratio
5.2G;D1D	18.05	17.88	35.93	0.00	2388.42	62	0.08110	1.00000	C	7380.480	0.32361
5.3G;D1D	18.05	11.70	29.75	0.00	575.59	62	0.01954	1.00000	C	7380.480	0.07799
5.6G;D1D	18.05	11.86	29.91	0.00	597.19	62	0.02028	1.00000	C	7380.480	0.08091
5.8G;D1D	18.05	17.92	35.97	0.00	2410.52	62	0.08185	1.00000	C	7380.480	0.32661

Radio 3(5G) _Beamforming

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (dBm)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL EIRP (dBm)	TL Ratio
5.2G;D1D	15.01	20.86	35.87	0.00	2355.65	62	0.07998	1.00000	C	7380.480	0.31917
5.3G;D1D	15.01	14.94	29.95	0.00	602.71	62	0.02046	1.00000	C	7380.480	0.08166
5.6G;D1D	15.01	14.93	29.94	0.00	601.33	62	0.02042	1.00000	C	7380.480	0.08148
5.8G;D1D	15.01	20.90	35.91	0.00	2377.44	62	0.08072	1.00000	C	7380.480	0.32213

Bluetooth

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
2.4G;BT-LE	4.00	10.48	14.48	0.00	17.10	62	0.00058	1.00000	C	7380.480	0.00232

Zigbee

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
2.4G;G1D	4.00	10.35	14.35	0.00	16.60	62	0.00056	1.00000	C	7380.480	0.00225

Radio 1(2.4G)+Radio 2(5G)+Radio 3(2.4G)+Bluetooth

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
2.4G;D1D	17.50	18.47	35.97	0.00	2410.52	62	0.08185	1.00000	C	7380.480	0.32661
5.8G;D1D	18.05	17.92	35.97	0.00	2410.52	62	0.08185	1.00000	C	7380.480	0.32661
2.4G;G1D	11.40	24.52	35.92	0.00	2382.92	62	0.08091	1.00000	C	7380.480	0.32287
2.4G;BT-LE	4.00	10.48	14.48	0.00	17.10	62	0.00058	1.00000	C	7380.480	0.00232
										Sum Ratio	0.97840
										Ratio Limit	1.00000

Radio 1(2.4G)+Radio 2(5G)+Radio 3(2.4G)+Zigbee

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
2.4G;D1D	17.50	18.47	35.97	0.00	2410.52	62	0.08185	1.00000	C	7380.480	0.32661
5.8G;D1D	18.05	17.92	35.97	0.00	2410.52	62	0.08185	1.00000	C	7380.480	0.32661
2.4G;G1D	11.40	24.52	35.92	0.00	2382.92	62	0.08091	1.00000	C	7380.480	0.32287
2.4G;G1D	4.00	10.35	14.35	0.00	16.60	62	0.00056	1.00000	C	7380.480	0.00225
										Sum Ratio	0.97833
										Ratio Limit	1.00000

Radio 1(2.4G)+Radio 2(5G)+Radio 3(5G)+Bluetooth

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
2.4G;D1D	17.50	18.47	35.97	0.00	2410.52	62	0.08185	1.00000	C	7380.480	0.32661
5.8G;D1D	18.05	17.92	35.97	0.00	2410.52	62	0.08185	1.00000	C	7380.480	0.32661
5.8G;D1D	12.00	23.93	35.93	0.00	2388.42	62	0.08110	1.00000	C	7380.480	0.32361
2.4G;BT-LE	4.00	10.48	14.48	0.00	17.10	62	0.00058	1.00000	C	7380.480	0.00232
										Sum Ratio	0.97914
										Ratio Limit	1.00000



Radio 1(2.4G)+Radio 2(5G)+Radio 3(5G)+Zigbee

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
2.4G;D1D	17.50	18.47	35.97	0.00	2410.52	62	0.08185	1.00000	C	7380.480	0.32661
5.8G;D1D	18.05	17.92	35.97	0.00	2410.52	62	0.08185	1.00000	C	7380.480	0.32661
2.4G;G1D	12.00	23.93	35.93	0.00	2388.42	62	0.08110	1.00000	C	7380.480	0.32361
2.4G;G1D	4.00	10.35	14.35	0.00	16.60	62	0.00056	1.00000	C	7380.480	0.00225
										Sum Ratio	0.97908
										Ratio Limit	1.00000

Radio 1(5G)+Radio 2(5G)+Radio 3(2.4G)+Bluetooth

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
5.8G;D1D	12.30	23.68	35.98	0.00	2416.07	62	0.08204	1.00000	C	7380.480	0.32736
5.8G;D1D	18.05	17.92	35.97	0.00	2410.52	62	0.08185	1.00000	C	7380.480	0.32661
2.4G;G1D	11.40	24.52	35.92	0.00	2382.92	62	0.08091	1.00000	C	7380.480	0.32287
2.4G;BT-LE	4.00	10.48	14.48	0.00	17.10	62	0.00058	1.00000	C	7380.480	0.00232
										Sum Ratio	0.97915
										Ratio Limit	1.00000

Radio 1(5G)+Radio 2(5G)+Radio 3(2.4G)+Zigbee

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
5.8G;D1D	12.30	23.68	35.98	0.00	2416.07	62	0.08204	1.00000	C	7380.480	0.32736
5.8G;D1D	18.05	17.92	35.97	0.00	2410.52	62	0.08185	1.00000	C	7380.480	0.32661
2.4G;G1D	11.40	24.52	35.92	0.00	2382.92	62	0.08091	1.00000	C	7380.480	0.32287
2.4G;G1D	4.00	10.35	14.35	0.00	16.60	62	0.00056	1.00000	C	7380.480	0.00225
										Sum Ratio	0.97908
										Ratio Limit	1.00000



Radio 1(5G)+Radio 2(5G)+Radio 3(5G)+Bluetooth

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
5.8G;D1D	12.30	23.68	35.98	0.00	2416.07	62	0.08204	1.00000	C	7380.480	0.32736
5.8G;D1D	18.05	17.92	35.97	0.00	2410.52	62	0.08185	1.00000	C	7380.480	0.32661
5.8G;D1D	12.00	23.93	35.93	0.00	2388.42	62	0.08110	1.00000	C	7380.480	0.32361
2.4G;BT-LE	4.00	10.48	14.48	0.00	17.10	62	0.00058	1.00000	C	7380.480	0.00232
										Sum Ratio	0.97990
										Ratio Limit	1.00000

Radio 1(5G)+Radio 2(5G)+Radio 3(5G)+Zigbee

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)	Option	TL ERP (mW)	TL Ratio
5.8G;D1D	12.30	23.68	35.98	0.00	2416.07	62	0.08204	1.00000	C	7380.480	0.32736
5.8G;D1D	18.05	17.92	35.97	0.00	2410.52	62	0.08185	1.00000	C	7380.480	0.32661
5.8G;D1D	12.00	23.93	35.93	0.00	2388.42	62	0.08110	1.00000	C	7380.480	0.32361
2.4G;G1D	4.00	10.35	14.35	0.00	16.60	62	0.00056	1.00000	C	7380.480	0.00225
										Sum Ratio	0.97983
										Ratio Limit	1.00000

Note 1: Option A, B and C refer as clause 2.2

Note 2: For option B, P_{th}(mW) convert to TL ERP(mW); For option C, ERP(W) convert to TL ERP(mW)

Note 3: TL Ratio=Tune-up ERP(mW)/TL ERP(mW)

Note 4: Refer as clause 2.3 Multiple RF Sources Exposure. Please follow below option and sum TL ration table.

Option	Sum TL Ratio_B	Option	Sum TL Ratio_C	Option	Sum TL Ratio_E
B	$\sum_{i=1}^a \frac{P_i}{P_{th,i}}$	C	$\sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}}$	E	$\sum_{k=1}^c \frac{Evaluated_k}{ExposureLimit_k}$

Note: The above antenna gain was declared by manufacturer.

—————THE END—————