

Maximum Permissible Exposure (MPE) & Exposure evaluation

Report identification number: 1-8978/19-02-05 MPE (FCC_ISED)

Certification numbers and labeling requirements	
FCC ID	TVU-BOX100A
ISED number	8023A-BOX100A
HVIN (Hardware Version Identification Number)	Gigaset Box 100A
PMN (Product Marketing Name)	Gigaset E630A
FVIN (Firmware Version Identification Number)	-/-
HMN (Host Marketing Name)	-/-

This report is electronically signed and valid without handwriting signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

Document authorised:



Alexander Hnatovskiy
Lab Manager
Radio Communications & EMC



Marco Scigliano
Testing Manager
Radio Communications & EMC

EUT technologies:

Technologies:	Max. power [dBm]		Antenna gain max.: [dBi]	Declared by customer
	conducted	EIRP		
DECT UPCS 1925	decl. 20.5 (peak) meas. 19.6 (peak)	meas. 21.6 (peak)	2.0	18.5 dBm +/- 2 dB (conducted peak)

DECT UPCS test results see CTC advanced test report 1-8978/19-02-02

Prediction of MPE limit at given distance - FCC

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG / 4\pi R^2$$

where: S = Power density
 P = Power input to the antenna
 G = Antenna gain
 R = Distance to the center of radiation of the antenna
 PG = Output Power including antenna gain

The table below is excerpted from Table 1B of 47 CFR 1.1310 titled "Limits for Maximum Permissible Exposure (MPE), Limits for General Population/Uncontrolled Exposure"

Frequency Range (MHz)	Power Density (mW/cm ²)	Averaging Time (minutes)
300 -1500	f/1500	30
1500 - 100000	1.0	30

where f = Frequency (MHz)

Prediction: worst case

Technologies:	UPCS	
Frequency (MHz)	1925	
PG Declared max power (EIRP)	22.5	dBm
R Distance	20	cm
S MPE limit for uncontrolled exposure	1	mW/cm ²
Calculated Power density:	0.0354	mW/cm ²
Calculated percentage of Limit:	3.54%	

This prediction demonstrates the following:

The power density levels for FCC at a distance of 20 cm are below the maximum levels allowed by regulations.

Prediction of MPE limit at given distance - ISED

RSS-102, Issue 5, 2.5.2

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $4.49/f^{0.5}W$ (adjusted for tune-up tolerance), where f is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834} W$ (adjusted for tune-up tolerance), where f is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

Prediction: worst case

		UPCS	
	Frequency	1925	MHz
R	Distance	20	cm
P	Max power input to the antenna	20.5	dBm
G	Antenna gain	2	dBi
PG	Maximum EIRP	22.5	dBm
PG	Maximum EIRP	177.8	mW
	Exclusion Limit from above:	2.30	W
	Calculated percentage of Limit:	7.73%	

Conclusion: RF exposure evaluation is not required.