

RF Exposure / Safety

Calculation of Maximum Permissible Exposure (MPE)
based on Section 1.1307(b) Requirements

- a) FCC limit is: 1mW/cm²
- b) The Wimax CPE can be configured in one of three different setups:
 - Setup 1: CPE with 9dBi internal antenna
 - Setup 2: CPE with 9dBi external desktop antenna
 - Setup 3: CPE with 15dBi external outdoor antenna

c) The power density produced by the EUT is:

$$S_{peak} = \frac{P_t \cdot G_t}{4\pi R^2}$$

$$S_{average} = \frac{P_t \cdot G_t \cdot dc}{4\pi R^2 \cdot 100}$$

- P_t – Transmitted power 251mW (rms peak) (24dBm)
- G_t – Antenna gain dependant on setup
- R – Distance from transmitter
- Dc – duty cycle

d) The power density is:

	Setup 1	Setup 2	Setup 3
P _t - Power output (rms peak) 24dBm	24dBm 251mW	24dBm 251mW	24dBm 251mW
G _t – Antenna gain	9dBi 8	9dBi - 1dB cable loss 6.3	15dBi - 1dB cable loss 25.1
Duty cycle (worst case)	100%	100%	100%
R – Distance from antenna (cm)	20	20	50
S _{peak} – peak power density (mW/cm ²)	0.40	0.31	0.2

e) S_{peak} < 1mW/cm²