

P1_DECT_Top Side Tilt_0mm_2410MHz**DUT: EUT**

Communication System: DECT; Frequency: 2410 MHz; Duty Cycle: 1:50

Medium: H2450 Medium parameters used: $f = 2410$ MHz; $\sigma = 1.72$ mho/m; $\epsilon_r = 40.4$; $\rho = 1000$ kg/m³

DASY4 Configuration:

- Probe: ES3DV3 - SN3090; ConvF(4.61, 4.61, 4.61); Calibrated: 2020/5/9
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn662; Calibrated: 2020/5/6
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1125
- ; Postprocessing SW: SEMCAD, V1.8 Build 186

Test/Area Scan (171x51x1): Measurement grid: dx=12mm, dy=12mm
Maximum value of SAR (interpolated) = 0.021 mW/g



Test/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 1.90 V/m; Power Drift = 0.0664 dB

Peak SAR (extrapolated) = 0.036 W/kg

SAR(1 g) = 0.018 mW/g; SAR(10 g) = 0.010 mW/g

Maximum value of SAR (measured) = 0.023 mW/g



0 dB = 0.023mW/g