

# RF EXPOSURE **EVALUATION REPORT**

**APPLICANT** : ShenZhen Gospell Smarthome Electronic Co., Ltd.

PRODUCT NAME : HD Outdoor WiFi Camera

**MODEL NAME** : T5923HAA

**BRAND NAME** : N/A

**FCC ID** : TW5T5923HAA

: 47CFR 2.1091 STANDARD(S)

KDB 447498 D01 General RF Exposure Guidance v06

**ISSUE DATE** : 2017-12-05

Tested by:

Approved by:

Peng Huarui (Supervisor)

NOTE: This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

SHENZHEN MORLAB COMMUNICATIONS TECHNOLOGY Co., Ltd.

Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China

FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road,





## **DIRECTORY**

1. Technical Information	. 3
1.1. Applicant and Manufacturer Information	. 3
1.2. Equipment Under Test (EUT) Description	. 3
1.3. Photographs of the EUT·······	. 2
1.4. Applied Reference Documents ······	. 5
2. Device Category And RF Exposure Limit······	. (
3. Measurement Of conducted Peak Output Power······	. 7
4. RF Exposure Evaluation ······	. 7
Annex A General Information······	. ş

Change History				
Issue	Date	Reason for change		
1.0 2017-12-05		First edition		



# 1. Technical Information

Note: Provide by manufacturer.

### 1.1. Applicant and Manufacturer Information

Applicant:	ShenZhen Gospell Smarthome Electronic Co., Ltd.		
Applicant Address.	5Floor/Block 2, Vision (SZ) Park, Hi-Tech Industrial Park,		
Applicant Address:	Shenzhen, China		
Manufacturer: ShenZhen Gospell Smarthome Electronic Co., Ltd.			
	East of 01st-04st Floor,Block A,No.1 Industrial		
Manufacturer Address:	park,Fenghuanggang,South of No.1 Baotian Road,Xixiang		
	street,Bao'an District,Shenzhen City,Guangdong Province		
	518126,P.R.China		

#### 1.2. Equipment Under Test (EUT) Description

EUT Type:	HD Outdoor WiFi Camera	
Hardware Version:	T5923HAA_M03	
Software Version:	E_900.T5923HAA.010.318	
Frequency Bands:	<b>quency Bands:</b> 802.11b/g/n-20MHz: 2.412GHz - 2.462GHz	
	802.11n-40MHz: 2.422GHz - 2.452GHz	
Modulation Mode: 802.11b :DSSS;		
	802.11g/n:OFDM;	
Antenna type:	Dipole Antenna	





## 1.3. Photographs of the EUT

#### 1. EUT front view



#### 2. EUT rear view





#### 1.3.1. Identification of all used EUT

The EUT identity consists of numerical and letter characters, the letter character indicates the test sample, and the following two numerical characters indicate the software version of the test sample.

EUT Identity	Hardware Version	Software Version
1#	T5923HAA_M03	E_900.T5923HAA.010.318

### 1.4. Applied Reference Documents

Leading reference documents for testing:

No.	Identity	Document Title
1	47 CFR§2.1091	Radiofrequency Radiation Exposure Evaluation: mobile
		devices
2	KDB 447498 D01v06	General RF Exposure Guidance

Tel: 86-755-36698555

Http://www.morlab.cn



## 2. Device Category And RF Exposure Limit

Per user manual, Based on 47CFR 2.1091, this device belongs to mobile device category with General Population/Uncontrolled exposure.

#### **Mobile Devices:**

47CFR 2.1091(b)

For purposes of this section, a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons. In this context, the term "fixed location" means that the device is physically secured at one location and is not able to be easily moved to another location. Transmitting devices designed to be used by consumers or workers that can be easily re-located, such as wireless devices associated with a personal computer, are considered to be mobile devices if they meet the 20 centimeter separation requirement.

#### **GENERAL POPULATION / UNCONTROLLED EXPOSURE**

The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity. Warning labels placed on low-power consumer devices such as cellular telephones are not considered sufficient to allow the device to be considered under the occupational/controlled category, and the general population/uncontrolled exposure limits apply to these devices.

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm²)	Averaging time (minutes)
(E	3) Limits for General	Population/Uncontro	lled Exposure	
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	f/1500	30
1500-100,000	-	-	1.0	30

f = frequency in MHz



<sup>\* =</sup> Plane-wave equivalent power density



# 3. Measurement Of conducted Peak Output Power

#### 1. Wi-Fi Average output power

Band	01	Frequency	Ou	utput Power(dE	Bm)
	Channel	(MHz)	802.11b	802.11g	802.11n20
	1	2412	19.86	17.92	17.87
Wi-Fi	6	2437	19.26	18.11	18.03
	11	2462	19.41	18.22	18.17

Band	Channel	Frequency (MHz)	Output Power(dBm) 802.11n40
	3	2422	17.43
Wi-Fi	6	2437	17.57
	9	2452	17.72

# 4. RF Exposure Evaluation

#### Standalone transmission MPE evaluation

Bands	Frequency (MHz)	Antenna Gain (dBi)	Conducted Average Power (dBm)	Time-averaging EIRP (mW)	Power density (mW/cm²)	Limit for MPE (mW/cm²)
2.4GHz	2412	2.0	19.86	153.462	0.031	1.0

1. MPE calculation method

Power Density = EIRP/ $4\pi$ R<sup>2</sup>

Where: EIRP = P·G

P = Peak out power

G = Antenna gain

R = Separation distance (20cm)



# **Annex A General Information**

#### 1. Identification of the Responsible Testing Laboratory

	<u> </u>		
Company Name:	Shenzhen Morlab Communications Technology Co., Ltd.		
Department:	Morlab Laboratory		
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang		
	Road, Block 67, BaoAn District, ShenZhen, GuangDong		
	Province, P. R. China		
Responsible Test Lab Manager:	Mr. Su Feng		
Telephone:	+86 755 36698555		
Facsimile:	+86 755 36698525		

#### 2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd.
	Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang
	Road, Block 67, BaoAn District, ShenZhen, GuangDong
	Province, P. R. China

END OF REPORT	

