

## INTERTEK TESTING SERVICES

---

### RF Exposure

The equipment under test (EUT) is a Chat Mixer (Includes Charge Cable) with Bluetooth function operating in 2402-2480MHz. The EUT is powered by DC 3.7V by rechargeable battery or DC 5V by USB port. For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna

Modulation Type: GFSK,  $\pi/4$  - DQPSK and 8 - DPSK

Antenna Gain: 0dBi

Bluetooth Version: 5.0(Single mode)

The normal radiated output power (e.i.r.p) is: -15.0dBm (tolerance: +/- 3dB).

The normal conducted output power is -15.0dBm (tolerance: +/- 3dB).

According to the KDB 447498:

The Maximum peak radiated emission for the EUT is 80.2 dB $\mu$ V/m at 3m in the frequency 2480MHz

The EIRP =  $[(FS \cdot D)^2 / 30]$  mW = -15.03dBm

which is within the production variation.

The Minimum peak radiated emission for the EUT is 79.5dB $\mu$ V/m at 3m in the frequency 2402MHz

The EIRP =  $[(FS \cdot D)^2 / 30]$  mW = -15.73dBm

which is within the production variation.

The maximum conducted output power specified is -12.0dBm= 0.06mW

The source- based time-averaging conducted output power  
=0.06\* Duty cycle mW =0.06 mW(Duty cycle =100%)

The SAR Exclusion Threshold Level:

=  $3.0 \cdot (\text{min. test separation distance, mm}) / \sqrt{\text{freq. in GHz}}$

=  $3.0 \cdot 5 / \sqrt{2.480}$  mW

= 9.53 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.