



FCC C2PC Test Report

Equipment : 802.11abgn 1x with BT
Brand Name : Summit
Model No. : SDC-SSD40NBT
FCC ID : TWG-SDCSSD40NBT
Standard : 47 CFR FCC Part 15.407
Operating Band : 5150 MHz – 5250 MHz
5250 MHz – 5350 MHz
5470 MHz – 5725 MHz
FCC Classification : NII
Applicant : Summit Data Communications, Inc.
526 South Main Street Suite 805 Akron, OH 44311

The product sample received on Mar. 07, 2013 and completely tested on Mar. 18, 2013. We, SPORTON, would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.10-2009 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by:



Wayne Hsu / Assistant Manager





Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information.....	5
1.2	Accessories and Support Equipment	7
1.3	Testing Applied Standards	7
1.4	Testing Location Information	7
1.5	Measurement Uncertainty	8
2	TEST CONFIGURATION OF EUT.....	9
2.1	The Worst Case Modulation Configuration	9
2.2	Test Channel Frequencies Configuration.....	9
2.3	The Worst Case Power Setting Parameter	10
2.4	The Worst Case Measurement Configuration.....	11
2.5	Test Setup Diagram	12
3	TRANSMITTER TEST RESULT	13
3.1	AC Power-line Conducted Emissions	13
3.2	RF Output Power.....	16
3.3	Transmitter Radiated Bandedge Emissions	19
3.4	Transmitter Radiated Unwanted Emissions	27
4	TEST EQUIPMENT AND CALIBRATION DATA	68
	APPENDIX A. TEST PHOTOS	A1
	APPENDIX B. PHOTOGRAPHS OF EUT	B1



Summary of Test Result

Conformance Test Specifications					
Report Clause	Ref. Std. Clause	Description	Measured	Limit	Result
1.1.3	15.203	Antenna Requirement	Antenna connector mechanism complied	FCC 15.203	Complied
3.1	15.207	AC Power-line Conducted Emissions	[dBuV]: 0.1721540MHz 47.17 (Margin 7.69dB) - AV 53.34 (Margin 11.52dB) - QP	FCC 15.207	Complied
3.2	15.407(a)	RF Output Power (Maximum Conducted Output Power)	Power [dBm] 5150-5250MHz: 10.83 5250-5350MHz: 14.32 5470-5725MHz: 15.22	Power [dBm] 5150-5250MHz:17 5250-5350MHz:24 5470-5725MHz:24	Complied
3.3	15.407(b)	Transmitter Radiated Bandedge Emissions	Restricted Bands [dBuV/m at 3m]: 5469.92MHz 67.16 (Margin 1.14dB) - PK	Non-Restricted Bands: ≤ -27dBm (68.3dBuV/m@3m) Restricted Bands: FCC 15.209	Complied
3.4	15.407(b)	Transmitter Radiated Unwanted Emissions	Restricted Bands [dBuV/m at 3m]: 292.45MHz 44.85 (Margin 1.15dB) - QP	Non-Restricted Bands: ≤ -27dBm (68.3dBuV/m@3m) Restricted Bands: FCC 15.209	Complied

Remark: This is a C2PC Report only, and please see Section 1.1.1 for the detail description and information.



Revision History

Report No.	Version	Description	Issued Date
FR330859AN	Rev. 01	Initial issue of report	Mar. 20, 2013



1 General Description

1.1 Information

1.1.1 Product Details

This report is prepared for FCC class II permissive change. The difference compared with original design is adding two sets of antenna. Please refer to item 1.1.3 for antenna information. In this report, conducted output power, conducted emission and radiated emission tests had been re-tested and only its data was recorded in the following sections.

1.1.2 RF General Information

RF General Information						
Frequency Range (MHz)	IEEE Std. 802.11	Ch. Freq. (MHz)	Channel Number	Transmit Chains (N _{TX})	RF Output Power (dBm)	Co-location
5150-5250	a	5180-5240	36-48 [4]	1	10.83	N/A
5250-5350		5260-5320	52-64 [4]	1	14.32	
5470-5725		5500-5700	100-140 [8]	1	15.22	
5150-5250	n (HT20)	5180-5240	36-48 [4]	1	9.91	N/A
5250-5350		5260-5320	52-64 [4]	1	13.01	
5470-5725		5500-5700	100-140 [8]	1	13.41	

Note 1: RF output power specifies that Maximum Conducted Output Power.
 Note 2: 802.11a/n uses a combination of OFDM-BPSK, QPSK, 16QAM, 64QAM modulation.
 Note 3: Co-location, Co-location is generally defined as simultaneously transmitting (co-transmitting) antennas within 20 cm of each other. (i.e., EUT has simultaneously co-transmitting that operating 2.4GHz and 5GHz.)

1.1.3 Antenna Information

Antenna Category	
<input type="checkbox"/>	Equipment placed on the market without antennas
<input type="checkbox"/>	Integral antenna (antenna permanently attached)
<input type="checkbox"/>	Temporary RF connector provided
<input type="checkbox"/>	No temporary RF connector provided Transmit chains bypass antenna and soldered temporary RF connector provided for connected measurement. In case of conducted measurements the transmitter shall be connected to the measuring equipment via a suitable attenuator and correct for all losses in the RF path.
<input checked="" type="checkbox"/>	External antenna (dedicated antennas)
<input checked="" type="checkbox"/>	Single power level with corresponding antenna(s).
<input type="checkbox"/>	Multiple power level and corresponding antenna(s).
<input checked="" type="checkbox"/>	RF connector provided
<input checked="" type="checkbox"/>	Unique antenna connector. (e.g., MMCX, U.FL, IPX, and RP-SMA, RP-N type...)
<input type="checkbox"/>	Standard antenna connector. (e.g., SMA, N, BNC, and TNC type...)



Antenna General Information							
No.	Ant. Cat.	Brand	Model	Ant. Type	Connector	Gain	Cable
1	External	Venture	M01-50908010-R	Omni-directional	MHF IPEX	2 dBi	Length 100mm
2	External	Venture	M01-50908011-R	Omni-directional	MHF IPEX	2 dBi	Length 180mm

Note: The antenna No.1 and No.2 had been pre-tested and found that the **antenna No. 2** was the worst case for final test.

1.1.4 Type of EUT

Identify EUT	
EUT Serial Number	N/A
Presentation of Equipment	<input type="checkbox"/> Production ; <input checked="" type="checkbox"/> Pre-Production ; <input type="checkbox"/> Prototype
Type of EUT	
<input type="checkbox"/>	Stand-alone
<input type="checkbox"/>	Combined (EUT where the radio part is fully integrated within another device) Combined Equipment - Brand Name / Model No.: ...
<input checked="" type="checkbox"/>	Plug-in radio (EUT intended for a variety of host systems) Host System - Brand Name / Model No.: ...
<input type="checkbox"/>	Other:

1.1.5 EUT Operational Condition

Supply Voltage	<input type="checkbox"/> AC mains	<input checked="" type="checkbox"/> DC	
Type of DC Source	<input type="checkbox"/> Internal DC supply	<input checked="" type="checkbox"/> Host	<input type="checkbox"/> Battery

1.2 Accessories and Support Equipment

Support Equipment				
No.	Equipment	Brand Name	Model Name	Serial No.
1	PDA	HP	HSTNH-L05C-WL	-
2	Cradle	HP	HSTNH-F02X	-

1.3 Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ◆ 47 CFR FCC Part 15
- ◆ ANSI C63.10-2009
- ◆ FCC KDB 789033
- ◆ FCC KDB 662911
- ◆ FCC KDB 412172

1.4 Testing Location Information

Testing Location				
<input checked="" type="checkbox"/>	HWA YA	ADD : No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-327-0973		
Test Condition	Test Site No.	Test Engineer	Test Environment	Test Date
AC Conduction	CO04-HY	Bill Hsiao	22°C / 54%	Mar. 18, 2013
RF Conducted	TH01-HY	Ian Du	24°C / 65%	Mar. 07, 2013
Radiated Emission	03CH05-HY	Daniel Hsu	25°C / 65 %	Mar. 12 ~ Mar. 15, 2013



1.5 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

Measurement Uncertainty			
Test Item		Uncertainty	Limit
AC power-line conducted emissions		±2.26 dB	N/A
RF output power, conducted		±0.63 dB	N/A
Unwanted emissions, conducted	30 – 1000 MHz	±0.51 dB	N/A
	1 – 18 GHz	±0.67 dB	N/A
	18 – 40 GHz	±0.83 dB	N/A
	40 – 200 GHz	N/A	N/A
All emissions, radiated	30 – 1000 MHz	±2.56 dB	N/A
	1 – 18 GHz	±3.59 dB	N/A
	18 – 40 GHz	±3.82 dB	N/A
	40 – 200 GHz	N/A	N/A
Temperature		±0.8 °C	N/A
Humidity		±3 %	N/A
DC and low frequency voltages		±3 %	N/A
Time		±1.42 %	N/A
Duty Cycle		±1.42 %	N/A

2 Test Configuration of EUT

2.1 The Worst Case Modulation Configuration

Worst Modulation Used for Conformance Testing (5150-5250MHz)				
Modulation Mode	Transmit Chains (N _{TX})	Data Rate / MCS	Worst Data Rate / MCS	Output Power (dBm)
11a,6-54Mbps	1	6-54Mbps	6 Mbps	10.83
HT20,M0-7	1	M0-7	M0	9.91
Worst Modulation Used for Conformance Testing (5250-5350MHz)				
Modulation Mode	Transmit Chains (N _{TX})	Data Rate / MCS	Worst Data Rate / MCS	Output Power (dBm)
11a,6-54Mbps	1	6-54Mbps	6 Mbps	14.32
HT20,M0-7	1	M0-7	M0	13.01
Worst Modulation Used for Conformance Testing (5470-5725MHz)				
Modulation Mode	Transmit Chains (N _{TX})	Data Rate / MCS	Worst Data Rate / MCS	Output Power (dBm)
11a,6-54Mbps	1	6-54Mbps	6 Mbps	15.22
HT20,M0-7	1	M0-7	M0	13.41
Note 1: IEEE Std. 802.11n modulation consists of HT20 (HT: High Throughput). Then EUT support HT20.				
Note 2: Modulation modes consist of below configuration: 11a: IEEE 802.11a, HT20/HT40: IEEE 802.11n.				

2.2 Test Channel Frequencies Configuration

Test Channel Frequencies Configuration		
Frequency Range (MHz)	IEEE Std. 802.11	Test Channel Freq. (MHz) – FX (Frequencies Abbreviations)
5150-5250	a, n (HT20)	5180-(F1), 5200-(F2), 5240-(F3)
5250-5350	a, n (HT20)	5260-(F4), 5300-(F5), 5320-(F6)
5470-5725	a, n (HT20)	5500-(F7), 5580-(F8), 5700-(F9)



2.3 The Worst Case Power Setting Parameter

The Worst Case Power Setting Parameter (5150-5250 MHz band)				
Test Software Version	SRU V3.03.09.00			
Modulation Mode	N _{TX}	Test Frequency (MHz)		
		NCB: 20MHz		
		5180	5200	5240
11a,6-54Mbps	1	default	default	default
HT20,M0-M7	1	default	default	default




The Worst Case Power Setting Parameter (5250-5350 MHz band)				
Test Software Version	SRU V3.03.09.00			
Modulation Mode	N _{TX}	Test Frequency (MHz)		
		NCB: 20MHz		
		5260	5300	5320
11a,6-54Mbps	1	default	default	default
HT20,M0-M7	1	default	default	default

The Worst Case Power Setting Parameter (5470-5725 MHz band)				
Test Software Version	SRU V3.03.09.00			
Modulation Mode	N _{TX}	Test Frequency (MHz)		
		NCB: 20MHz		
		5500	5580	5700
11a,6-54Mbps	1	default	default	default
HT20,M0-M7	1	default	default	default




2.4 The Worst Case Measurement Configuration

The Worst Case Mode for Following Conformance Tests	
Tests Item	AC power-line conducted emissions
Condition	AC power-line conducted measurement for line and neutral Test Voltage: 120Vac / 60Hz
Operating Mode	Operating Mode Description
1	Radio link (WLAN)

The Worst Case Mode for Following Conformance Tests	
Tests Item	RF Output Power
Test Condition	Conducted measurement at transmit chains
Modulation Mode	11a, HT20

The Worst Case Mode for Following Conformance Tests			
Tests Item	Transmitter Radiated Unwanted Emissions Transmitter Radiated Bandedge Emissions		
Test Condition	Radiated measurement If EUT consist of multiple antenna assembly (multiple antenna are used in EUT regardless of spatial multiplexing MIMO configuration), the radiated test should be performed with highest antenna gain of each antenna type.		
User Position	<input type="checkbox"/> EUT will be placed in fixed position.		
	<input type="checkbox"/> EUT will be placed in mobile position and operating multiple positions. EUT shall be performed two orthogonal planes. The worst planes is X.		
	<input checked="" type="checkbox"/> EUT will be a hand-held or body-worn battery-powered devices and operating multiple positions. EUT shall be performed two or three orthogonal planes. The worst planes is Z.		
Operating Mode < 1GHz	<input checked="" type="checkbox"/> 1. Radio link (WLAN)		
Modulation Mode	11a, HT20		
Orthogonal Planes of EUT	X Plane	Y Plane	Z Plane
			

2.5 Test Setup Diagram



3 Transmitter Test Result

3.1 AC Power-line Conducted Emissions

3.1.1 AC Power-line Conducted Emissions Limit

AC Power-line Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: * Decreases with the logarithm of the frequency.


3.1.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.


3.1.3 Test Procedures

Test Method
<input checked="" type="checkbox"/> Refer as ANSI C63.10-2009, clause 6.2 for AC power-line conducted emissions.

3.1.4 Test Setup




3.1.5 Test Result of AC Power-line Conducted Emissions

AC Power-line Conducted Emissions Result																																																																																																																																	
Operating Mode	1	Power Phase	Neutral																																																																																																																														
Operating Function	Radio link (WLAN)																																																																																																																																
 <p style="text-align: right; font-size: small;">Date: 2013-03-18</p>																																																																																																																																	
<table border="1" style="width: 100%; border-collapse: collapse; font-size: x-small;"> <thead> <tr> <th></th> <th>Freq</th> <th>Level</th> <th>Over Limit</th> <th>Limit Line</th> <th>Read Level</th> <th>LISN Factor</th> <th>Cable Loss</th> <th>Remark</th> </tr> <tr> <th></th> <th>MHz</th> <th>dBuV</th> <th>dB</th> <th>dBuV</th> <th>dBuV</th> <th>dB</th> <th>dB</th> <th></th> </tr> </thead> <tbody> <tr><td>1</td><td>0.1721540</td><td>53.15</td><td>-11.71</td><td>64.86</td><td>52.66</td><td>0.11</td><td>0.38</td><td>QP</td></tr> <tr><td>2</td><td>0.1721540</td><td>18.82</td><td>-36.04</td><td>54.86</td><td>18.33</td><td>0.11</td><td>0.38</td><td>Average</td></tr> <tr><td>3</td><td>0.2353310</td><td>43.78</td><td>-18.48</td><td>62.26</td><td>43.35</td><td>0.11</td><td>0.32</td><td>QP</td></tr> <tr><td>4</td><td>0.2353310</td><td>35.52</td><td>-16.74</td><td>52.26</td><td>35.09</td><td>0.11</td><td>0.32</td><td>Average</td></tr> <tr><td>5</td><td>1.290</td><td>8.47</td><td>-37.53</td><td>46.00</td><td>8.01</td><td>0.12</td><td>0.34</td><td>Average</td></tr> <tr><td>6</td><td>1.290</td><td>23.66</td><td>-32.34</td><td>56.00</td><td>23.20</td><td>0.12</td><td>0.34</td><td>QP</td></tr> <tr><td>7</td><td>2.260</td><td>25.88</td><td>-20.12</td><td>46.00</td><td>25.37</td><td>0.13</td><td>0.38</td><td>Average</td></tr> <tr><td>8</td><td>2.260</td><td>32.47</td><td>-23.53</td><td>56.00</td><td>31.96</td><td>0.13</td><td>0.38</td><td>QP</td></tr> <tr><td>9</td><td>4.250</td><td>20.56</td><td>-35.44</td><td>56.00</td><td>20.10</td><td>0.16</td><td>0.30</td><td>QP</td></tr> <tr><td>10</td><td>4.250</td><td>14.76</td><td>-31.24</td><td>46.00</td><td>14.30</td><td>0.16</td><td>0.30</td><td>Average</td></tr> <tr><td>11</td><td>11.260</td><td>17.96</td><td>-42.04</td><td>60.00</td><td>17.38</td><td>0.25</td><td>0.33</td><td>QP</td></tr> <tr><td>12</td><td>11.260</td><td>11.89</td><td>-38.11</td><td>50.00</td><td>11.31</td><td>0.25</td><td>0.33</td><td>Average</td></tr> </tbody> </table>					Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark		MHz	dBuV	dB	dBuV	dBuV	dB	dB		1	0.1721540	53.15	-11.71	64.86	52.66	0.11	0.38	QP	2	0.1721540	18.82	-36.04	54.86	18.33	0.11	0.38	Average	3	0.2353310	43.78	-18.48	62.26	43.35	0.11	0.32	QP	4	0.2353310	35.52	-16.74	52.26	35.09	0.11	0.32	Average	5	1.290	8.47	-37.53	46.00	8.01	0.12	0.34	Average	6	1.290	23.66	-32.34	56.00	23.20	0.12	0.34	QP	7	2.260	25.88	-20.12	46.00	25.37	0.13	0.38	Average	8	2.260	32.47	-23.53	56.00	31.96	0.13	0.38	QP	9	4.250	20.56	-35.44	56.00	20.10	0.16	0.30	QP	10	4.250	14.76	-31.24	46.00	14.30	0.16	0.30	Average	11	11.260	17.96	-42.04	60.00	17.38	0.25	0.33	QP	12	11.260	11.89	-38.11	50.00	11.31	0.25	0.33	Average
	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark																																																																																																																									
	MHz	dBuV	dB	dBuV	dBuV	dB	dB																																																																																																																										
1	0.1721540	53.15	-11.71	64.86	52.66	0.11	0.38	QP																																																																																																																									
2	0.1721540	18.82	-36.04	54.86	18.33	0.11	0.38	Average																																																																																																																									
3	0.2353310	43.78	-18.48	62.26	43.35	0.11	0.32	QP																																																																																																																									
4	0.2353310	35.52	-16.74	52.26	35.09	0.11	0.32	Average																																																																																																																									
5	1.290	8.47	-37.53	46.00	8.01	0.12	0.34	Average																																																																																																																									
6	1.290	23.66	-32.34	56.00	23.20	0.12	0.34	QP																																																																																																																									
7	2.260	25.88	-20.12	46.00	25.37	0.13	0.38	Average																																																																																																																									
8	2.260	32.47	-23.53	56.00	31.96	0.13	0.38	QP																																																																																																																									
9	4.250	20.56	-35.44	56.00	20.10	0.16	0.30	QP																																																																																																																									
10	4.250	14.76	-31.24	46.00	14.30	0.16	0.30	Average																																																																																																																									
11	11.260	17.96	-42.04	60.00	17.38	0.25	0.33	QP																																																																																																																									
12	11.260	11.89	-38.11	50.00	11.31	0.25	0.33	Average																																																																																																																									
<p>Note 1: ">20dB" means emission levels that exceed the level of 20 dB below the applicable limit. Note 2: "N/F" means Nothing Found emissions (No emissions were detected.)</p>																																																																																																																																	

AC Power-line Conducted Emissions Result

Operating Mode	1	Power Phase	Line
Operating Function	Radio link (WLAN)		



	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
			dB	dBuV	dBuV	dB	dB	
1	0.1721540	53.34	-11.52	64.86	52.72	0.24	0.38	QP
2	80.1721540	47.17	-7.69	54.86	46.55	0.24	0.38	Average
3	0.2303960	46.23	-16.21	62.44	45.68	0.23	0.32	QP
4	0.2303960	33.63	-18.81	52.44	33.08	0.23	0.32	Average
5	0.4083060	32.18	-25.50	57.68	31.56	0.22	0.40	QP
6	0.4083060	24.43	-23.25	47.68	23.81	0.22	0.40	Average
7	1.780	11.93	-34.07	46.00	11.30	0.25	0.38	Average
8	1.780	29.28	-26.72	56.00	28.65	0.25	0.38	QP
9	2.270	31.71	-24.29	56.00	31.07	0.26	0.38	QP
10	2.270	15.34	-30.66	46.00	14.70	0.26	0.38	Average
11	4.430	26.81	-29.19	56.00	26.21	0.30	0.30	QP
12	4.430	9.58	-36.42	46.00	8.98	0.30	0.30	Average
13	9.300	11.66	-38.34	50.00	10.95	0.41	0.30	Average
14	9.300	15.53	-44.47	60.00	14.82	0.41	0.30	QP

Note 1: ">20dB" means emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found emissions (No emissions were detected.)

3.2 RF Output Power

3.2.1 RF Output Power Limit

Maximum Conducted Output Power Limit	
UNII Devices	
<input checked="" type="checkbox"/>	For the 5.15-5.25 GHz band, the maximum conducted output power (P_{Out}) shall not exceed the lesser of 50 mW or $4 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in MHz. If $G_{TX} > 6 \text{ dBi}$, then $P_{Out} = 17 - (G_{TX} - 6)$.
<input checked="" type="checkbox"/>	For the 5.25-5.35 GHz band, the maximum conducted output power (P_{Out}) shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in MHz. If $G_{TX} > 6 \text{ dBi}$, then $P_{Out} = 24 - (G_{TX} - 6)$.
<input checked="" type="checkbox"/>	For the 5.47-5.725 GHz band, the maximum conducted output power (P_{Out}) shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in MHz. If $G_{TX} > 6 \text{ dBi}$, then $P_{Out} = 24 - (G_{TX} - 6)$.
<input type="checkbox"/>	For the 5.725-5.825 GHz band:
<input type="checkbox"/>	Point-to-multipoint systems (P2M): the maximum conducted output power (P_{Out}) shall not exceed the lesser of 1 W or $17 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in MHz. If $G_{TX} > 6 \text{ dBi}$, then $P_{Out} = 30 - (G_{TX} - 6)$.
<input type="checkbox"/>	Point-to-point systems (P2P): the maximum conducted output power (P_{Out}) shall not exceed the lesser of 1 W or $17 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in MHz. If $G_{TX} > 23 \text{ dBi}$, then $P_{Out} = 30 - (G_{TX} - 23)$.
LE-LAN Devices	
<input checked="" type="checkbox"/>	For the 5.15-5.25 GHz band, the maximum e.i.r.p. shall not exceed 200 mW or $10 + 10 \log B$, dBm, whichever power is less. B is the 99% emission bandwidth in MHz.
<input checked="" type="checkbox"/>	For the 5.25-5.35 GHz band, the maximum e.i.r.p. shall not exceed 1.0 W or $17 + 10 \log B$, dBm, whichever power is less. B is the 99% emission bandwidth in MHz.
<input checked="" type="checkbox"/>	For the 5.47-5.6 GHz band and 5.65-5.725 GHz band, the maximum e.i.r.p. shall not exceed 1.0 W or $17 + 10 \log B$, dBm, whichever power is less. B is the 99% emission bandwidth in MHz.
<input type="checkbox"/>	For the 5.725-5.825 GHz band, the maximum e.i.r.p. shall not exceed 4.0 W or $23 + 10 \log B$, dBm, whichever power is less. B is the 99% emission bandwidth in MHz.
<input type="checkbox"/>	Point-to-multipoint systems (P2M): the maximum e.i.r.p. shall not exceed 4.0 W or $23 + 10 \log B$, dBm, whichever power is less. B is the 99% emission bandwidth in MHz.
<input type="checkbox"/>	Point-to-point systems (P2P): the maximum e.i.r.p. shall not exceed 4.0 W or $23 + 10 \log B$, dBm, whichever power is less. B is the 99% emission bandwidth in MHz. If e.i.r.p. > 36 dBm, $G_{TX} \leq P_{Out}$.
P_{Out} = maximum conducted output power in dBm, G_{TX} = the maximum transmitting antenna directional gain in dBi.	


3.2.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.2.3 Test Procedures

Test Method	
<input checked="" type="checkbox"/>	Maximum Conducted Output Power
	[duty cycle ≥ 98% or external video / power trigger]
	<input type="checkbox"/> Refer as FCC KDB 789033, clause C Method SA-1 (spectral trace averaging).
	<input type="checkbox"/> Refer as FCC KDB 789033, clause C Method SA-1 Alt. (RMS detection with slow sweep speed)
	duty cycle < 98% and average over on/off periods with duty factor
	<input type="checkbox"/> Refer as FCC KDB 789033, clause C Method SA-2 (spectral trace averaging).
	<input type="checkbox"/> Refer as FCC KDB 789033, clause C Method SA-2 Alt. (RMS detection with slow sweep speed)
	Wideband RF power meter and average over on/off periods with duty factor
	<input checked="" type="checkbox"/> Refer as FCC KDB 789033, clause C Method PM (using an RF average power meter).
<input checked="" type="checkbox"/>	For conducted measurement.
	<input checked="" type="checkbox"/> The EUT supports single transmit chain and measurements performed on this transmit chain.
	<input type="checkbox"/> The EUT supports diversity transmitting and the results on transmit chain port 1 is the worst case.
	<input type="checkbox"/> The EUT supports multiple transmit chains using options given below: Refer as FCC KDB 662911, In-band power measurements. Using the measure-and-sum approach, measured all transmit ports individually. Sum the power (in linear power units e.g., mW) of all ports for each individual sample and save them.
	<input type="checkbox"/> If multiple transmit chains, EIRP calculation could be following as methods: $P_{total} = P_1 + P_2 + \dots + P_n$ (calculated in linear unit [mW] and transfer to log unit [dBm]) $EIRP_{total} = P_{total} + DG$

3.2.4 Test Setup





3.2.5 Test Result of Maximum Conducted Output Power



Maximum Conducted Output Power (5150-5250MHz band)						
Condition		RF Output Power (dBm)				
Modulation Mode	Freq. (MHz)	RF Output Power	Power Limit	Antenna Gain (dBi)	EIRP Power	EIRP Limit
11a	5180	9.68	17	2	11.68	23
11a	5200	10.11	17	2	12.11	23
11a	5240	10.83	17	2	12.83	23
HT-20	5180	8.89	17	2	10.89	23
HT-20	5200	8.83	17	2	10.83	23
HT-20	5240	9.91	17	2	11.91	23
Result		Complied				


Maximum Conducted Output Power (5250-5350MHz band)						
Condition		RF Output Power (dBm)				
Modulation Mode	Freq. (MHz)	RF Output Power	Power Limit	Antenna Gain (dBi)	EIRP Power	EIRP Limit
11a	5260	12.89	24	2	14.89	30
11a	5300	14.32	24	2	16.32	30
11a	5320	10.56	24	2	12.56	30
HT-20	5260	11.81	24	2	13.81	30
HT-20	5300	13.01	24	2	15.01	30
HT-20	5320	8.56	24	2	10.56	30
Result		Complied				

Maximum Conducted Output Power (5470-5725MHz band)						
Condition		RF Output Power (dBm)				
Modulation Mode	Freq. (MHz)	RF Output Power	Power Limit	Antenna Gain (dBi)	EIRP Power	EIRP Limit
11a	5500	15.22	24	2	17.22	30
11a	5580	13.59	24	2	15.59	30
11a	5700	8.28	24	2	10.28	30
HT-20	5500	13.41	24	2	15.41	30
HT-20	5580	12.48	24	2	14.48	30
HT-20	5700	10.89	24	2	12.89	30
Result		Complied				

3.3 Transmitter Radiated Bandedge Emissions

3.3.1 Transmitter Radiated Bandedge Emissions Limit





3.3.2 Measuring Instruments


Refer a test equipment and calibration data table in this test report.



3.3.3 Test Procedures

Test Method	
<input checked="" type="checkbox"/>	Measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements). Measurements in the bandedge are typically made at a closer distance 3m, because the instrumentation noise floor is typically close to the radiated emission limit.
<input checked="" type="checkbox"/>	The average emission levels shall be measured in [duty cycle ≥ 98 or duty factor].
<input checked="" type="checkbox"/>	Refer as ANSI C63.10, clause 6.9.2.2 bandedge testing shall be performed at the lowest frequency channel and highest frequency channel within the allowed operating band.
<input type="checkbox"/>	If EUT operate in adjacent contiguous bands, bandedge testing performed at the lowest frequency channel at lower-band and highest frequency channel at higher-band. Transmitter in-band emissions will consist of adjacent contiguous bands (e.g., IEEE 802.11ac VHT160 The lowest frequency channel at lower-band and highest frequency channel at higher-band in-band emissions will consist of two adjacent contiguous bands.)
<input type="checkbox"/>	<input type="checkbox"/> Operating in 5.15-5.25 GHz band (lower-band) and 5.25-5.35 GHz band (higher-band). <input type="checkbox"/> Operating in 5.47-5.725 GHz band (lower-band) and 5.725-5.825 GHz band (higher-band).
<input type="checkbox"/>	If EUT operate in individual non-contiguous bands, bandedge testing performed at the lowest frequency channel and highest frequency channel within lower-band and higher-band. (e.g., (e.g., IEEE 802.11ac VHT160)
<input type="checkbox"/>	<input type="checkbox"/> Operating in 5.25-5.35 GHz band (lower-band) and 5.47-5.725 GHz band (higher-band). <input type="checkbox"/> Operating in 5.15-5.25 GHz band (lower-band) and 5.725-5.825 GHz band (higher-band).
<input checked="" type="checkbox"/>	For the transmitter unwanted emissions shall be measured using following options below:
<input checked="" type="checkbox"/>	Refer as FCC KDB 789033, clause G)2) for unwanted emissions into non-restricted bands.
<input checked="" type="checkbox"/>	Refer as FCC KDB 789033, clause G)1) for unwanted emissions into restricted bands.
<input type="checkbox"/>	Refer as FCC KDB 789033, G)6) Method AD (Trace Averaging).
<input type="checkbox"/>	Refer as FCC KDB 789033, G)6) Method VB (Reduced VBW).
<input checked="" type="checkbox"/>	Refer as ANSI C63.10, clause 4.2.3.2.3 (Reduced VBW). VBW ≥ 1/T, where T is pulse time.
<input type="checkbox"/>	Refer as ANSI C63.10, clause 4.2.3.2.4 average value of pulsed emissions.
<input checked="" type="checkbox"/>	Refer as FCC KDB 789033, clause G)5) measurement procedure peak limit.
<input type="checkbox"/>	Refer as ANSI C63.10, clause 4.2.3.2.2 measurement procedure peak limit.
<input checked="" type="checkbox"/>	For the transmitter bandedge emissions shall be measured using following options below:
<input type="checkbox"/>	Refer as FCC KDB 789033, clause G)3)d) marker-delta method for band-edge measurements.
<input checked="" type="checkbox"/>	Refer as ANSI C63.10, clause 6.9.2 for band-edge testing.
<input type="checkbox"/>	Refer as ANSI C63.10, clause 6.9.3 for marker-delta method for band-edge measurements.
<input checked="" type="checkbox"/>	For radiated measurement, refer as ANSI C63.10, clause 6.5 for radiated emissions from above 1 GHz.

3.3.4 Test Setup





3.3.5 Test Result of Transmitter Radiated Bandedge Emissions

Transmitter Radiated Bandedge Emissions Result								
Modulation	11a		N _{TX}	1				
Restricted Band (MHz)	Test Ch. Freq. (MHz)	In-band PSD [i] (dBuV/1MHz)	RBE Freq. (MHz)	Measure Distance (m)	Out-Band Level (dBuV/m)	Limit (dBuV/m)	Level Type	Pol. note 1
4500-5150	5180	104.39	5149.70	3	56.68	74	PK	V
4500-5150	5180	94.00	5100.70	3	38.99	54	AV	V
5350-5460	5320	104.52	5350.18	3	61.65	74	PK	V
5350-5460	5320	94.14	5350.60	3	43.92	54	AV	V

5.2GHz Lower-band (Lowest Ch.)	5.3GHz Higher-band (Highest Ch.)

Note 1: Measurement worst emissions of receive antenna polarization: H (Horizontal) or V (Vertical).



Transmitter Radiated Bandedge Emissions Result								
Modulation	11a		N _{TX}	1				
Non-restricted Band (MHz)	Test Ch. Freq. (MHz)	In-band PSD [i] (dBuV/1MHz)	NBE Freq. (MHz)	Measure Distance (m)	Out-Band Level (dBuV/m)	Limit (dBuV/m)	Level Type	Pol. note 1
5460-5470	5500	108.12	5470.00	3	67.15	68.3	PK	V
5725-7250	5700	101.96	5725.49	3	60.05	68.3	PK	V
5.6GHz band (Lowest Ch.)				5.6GHz band (Highest Ch.)				
Note 1: Measurement worst emissions of receive antenna polarization: H (Horizontal) or V (Vertical).								



Transmitter Radiated Bandedge Emissions Result								
Modulation	HT-20		N _{TX}	1				
Restricted Band (MHz)	Test Ch. Freq. (MHz)	In-band PSD [i] (dBuV/1MHz)	RBE Freq. (MHz)	Measure Distance (m)	Out-Band Level (dBuV/m)	Limit (dBuV/m)	Level Type	Pol. note 1
4500-5150	5180	103.41	5149.90	3	55.60	74	PK	V
4500-5150	5180	93.15	5142.90	3	39.24	54	AV	V
5350-5460	5320	100.87	5320.15	3	56.62	74	PK	V
5350-5460	5320	91.05	5352.91	3	41.13	54	AV	V
5.2GHz Lower-band (Lowest Ch.)				5.3GHz Higher-band (Highest Ch.)				

Note 1: Measurement worst emissions of receive antenna polarization: H (Horizontal) or V (Vertical).



Transmitter Radiated Bandedge Emissions Result								
Modulation	HT-20		N _{TX}	1				
Non-restricted Band (MHz)	Test Ch. Freq. (MHz)	In-band PSD [i] (dBuV/1MHz)	NBE Freq. (MHz)	Measure Distance (m)	Out-Band Level (dBuV/m)	Limit (dBuV/m)	Level Type	Pol. note 1
5460-5470	5500	106.33	5469.92	3	67.16	68.3	PK	V
5725-7250	5700	104.13	5726.53	3	65.46	68.3	PK	V
5.6GHz band (Lowest Ch.)				5.6GHz band (Highest Ch.)				
Note 1: Measurement worst emissions of receive antenna polarization: H (Horizontal) or V (Vertical).								

3.4 Transmitter Radiated Unwanted Emissions

3.4.1 Transmitter Radiated Unwanted Emissions Limit

Unwanted emissions below 1 GHz and restricted band emissions above 1GHz limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1: Test distance for frequencies at or above 30 MHz, measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).

Note 2: Test distance for frequencies at below 30 MHz, measurements may be performed at a distance closer than the EUT limit distance; however, an attempt should be made to avoid making measurements in the near field. When performing measurements below 30 MHz at a closer distance than the limit distance, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two or more distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). The test report shall specify the extrapolation method used to determine compliance of the EUT.

Un-restricted band emissions above 1GHz Limit	
Operating Band	Limit
5.15 - 5.25 GHz	e.i.r.p. -27 dBm [68.2 dBuV/m@3m]
5.25 - 5.35 GHz	e.i.r.p. -27 dBm [68.2 dBuV/m@3m]
5.47 - 5.725 GHz	e.i.r.p. -27 dBm [68.2 dBuV/m@3m]
5.725 - 5.825 GHz	5.715 5.725 GHz: e.i.r.p. -17 dBm [78.2 dBuV/m@3m] 5.825 5.835 GHz: e.i.r.p. -17 dBm [78.2 dBuV/m@3m] Other un-restricted band: e.i.r.p. -27 dBm [68.2 dBuV/m@3m]

Note 1: Measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).

3.4.2 Measuring Instruments


Refer a test equipment and calibration data table in this test report.



3.4.3 Test Procedures

Test Method	
<input checked="" type="checkbox"/>	Measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. Measurements shall not be performed at a distance greater than 30 m for frequencies above 30 MHz, unless it can be further demonstrated that measurements at a distance of 30 m or less are impractical. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).
<input type="checkbox"/>	Measurements in the frequency range 5 GHz - 10GHz are typically made at a closer distance 3m, because the instrumentation noise floor is typically close to the radiated emission limit.
<input type="checkbox"/>	Measurements in the frequency range 10 GHz - 18GHz are typically made at a closer distance 1m, because the instrumentation noise floor is typically close to the radiated emission limit.
<input type="checkbox"/>	Measurements in the frequency range above 18 GHz - 40GHz are typically made at a closer distance 0.5m, because the instrumentation noise floor is typically close to the radiated emission limit.
<input checked="" type="checkbox"/>	The average emission levels shall be measured in [duty cycle \geq 98 or duty factor].
<input checked="" type="checkbox"/>	For the transmitter unwanted emissions shall be measured using following options below:
<input checked="" type="checkbox"/>	Refer as FCC KDB 789033, clause G)2) for unwanted emissions into non-restricted bands.
<input checked="" type="checkbox"/>	Refer as FCC KDB 789033, clause G)1) for unwanted emissions into restricted bands.
<input type="checkbox"/>	Refer as FCC KDB 789033, G)6) Method AD (Trace Averaging).
<input type="checkbox"/>	Refer as FCC KDB 789033, G)6) Method VB (Reduced VBW).
<input checked="" type="checkbox"/>	Refer as ANSI C63.10, clause 4.2.3.2.3 (Reduced VBW). VBW \geq 1/T, where T is pulse time.
<input type="checkbox"/>	Refer as ANSI C63.10, clause 4.2.3.2.4 average value of pulsed emissions.
<input checked="" type="checkbox"/>	Refer as FCC KDB 789033, clause G)5) measurement procedure peak limit.
<input type="checkbox"/>	Refer as ANSI C63.10, clause 4.2.3.2.2 measurement procedure peak limit.
<input checked="" type="checkbox"/>	For radiated measurement.
<input checked="" type="checkbox"/>	Refer as ANSI C63.10, clause 6.4 for radiated emissions from below 30 MHz.
<input checked="" type="checkbox"/>	Refer as ANSI C63.10, clause 6.5 for radiated emissions from 30 MHz to 1000 MHz.
<input checked="" type="checkbox"/>	Refer as ANSI C63.10, clause 6.6 for radiated emissions from above 1 GHz.

3.4.4 Test Setup




3.4.5 Transmitter Radiated Unwanted Emissions (Below 30MHz)

All amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.



3.4.6 Transmitter Radiated Unwanted Emissions (Below 1GHz)

Transmitter Radiated Unwanted Emissions (Below 1GHz)			
Operating Mode	1	Polarization	V
Operating Function	Radio link (WLAN)		




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	253.16	32.35	-13.65	46.00	48.56	13.01	1.71	30.93	---	---	Peak
2	291.27	34.96	-11.04	46.00	50.92	13.31	1.84	31.11	---	---	Peak
3	331.26	35.12	-10.88	46.00	50.39	13.84	1.93	31.04	---	---	Peak
4	644.74	33.96	-12.04	46.00	41.19	20.46	2.45	30.14	---	---	Peak
5	682.88	36.83	-9.17	46.00	43.98	20.46	2.57	30.18	---	---	Peak
6	721.26	36.24	-9.76	46.00	42.14	21.65	2.65	30.20	---	---	Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)



Transmitter Radiated Unwanted Emissions (Below 1GHz)

Operating Mode	1	Polarization	H
Operating Function	Radio link (WLAN)		




	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	cm	deg	
1	253.07	44.05	-1.95	46.00	60.28	13.00	1.70	30.93	---	QP
2	292.45	44.85	-1.15	46.00	60.77	13.32	1.84	31.08	---	QP
3	331.52	44.21	-1.79	46.00	59.47	13.85	1.93	31.04	---	QP
4	370.52	42.81	-3.19	46.00	56.87	14.92	2.05	31.03	---	Peak
5	682.59	44.15	-1.85	46.00	51.31	20.45	2.57	30.18	---	QP
6	721.53	43.23	-2.77	46.00	49.12	21.66	2.65	30.20	---	QP

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)



3.4.7 Transmitter Radiated Unwanted Emissions (Above 1GHz) for 11a

Transmitter Radiated Unwanted Emissions (Above 1GHz)			
Modulation Mode	11a	Test Freq. (FX)	F1
N _{TX}	1	Polarization	V




	Freq	Level	Over Limit	Limit Line	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	cm	deg	
1	1228.00	39.95	-14.05	54.00	46.38	27.95	3.18	37.56	---	Average
2	1228.00	44.00	-30.00	74.00	50.43	27.95	3.18	37.56	---	Peak
3	3453.00	46.79	-21.51	68.30	44.05	32.71	5.67	35.64	---	Peak
4	10360.00	53.78	-14.52	68.30	41.77	37.72	9.73	35.44	---	Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.



Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11a	Test Freq. (FX)	F1
N _{TX}	1	Polarization	H




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Loss	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	1228.00	47.47	-6.53	54.00	53.90	27.95	3.18	37.56	---	---	Average
2	1228.00	50.17	-23.83	74.00	56.60	27.95	3.18	37.56	---	---	Peak
3	3453.00	45.53	-22.77	68.30	42.79	32.71	5.67	35.64	---	---	Peak
4	10360.00	53.70	-14.60	68.30	41.69	37.72	9.73	35.44	---	---	Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.



Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11a	Test Freq. (FX)	F2
N _{TX}	1	Polarization	V




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Loss	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	1228.00	39.69	-14.31	54.00	46.12	27.95	3.18	37.56	---	---	Average
2	1228.00	43.57	-30.43	74.00	50.00	27.95	3.18	37.56	---	---	Peak
3	10400.00	54.11	-14.19	68.30	42.01	37.74	9.76	35.40	---	---	Peak
4	15600.00	44.17	-9.83	54.00	27.43	40.12	11.74	35.12	---	---	Average
5	15600.00	56.97	-17.03	74.00	40.23	40.12	11.74	35.12	---	---	Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.



Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11a	Test Freq. (FX)	F2
N _{TX}	1	Polarization	H




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Loss	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	1228.00	47.30	-6.70	54.00	53.73	27.95	3.18	37.56	---	---	Average
2	1228.00	49.16	-24.84	74.00	55.59	27.95	3.18	37.56	---	---	Peak
3	10400.00	54.94	-13.36	68.30	42.84	37.74	9.76	35.40	---	---	Peak
4	15600.00	44.20	-9.80	54.00	27.46	40.12	11.74	35.12	---	---	Average
5	15600.00	57.44	-16.56	74.00	40.70	40.12	11.74	35.12	---	---	Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.



Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11a	Test Freq. (FX)	F3
N _{TX}	1	Polarization	V




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Loss	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	1228.00	39.56	-14.44	54.00	45.99	27.95	3.18	37.56	---	---	Average
2	1228.00	43.66	-30.34	74.00	50.09	27.95	3.18	37.56	---	---	Peak
3	3493.00	44.68	-23.62	68.30	41.90	32.70	5.69	35.61	---	---	Peak
4	10480.00	54.54	-13.76	68.30	42.27	37.79	9.80	35.32	---	---	Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.




Transmitter Radiated Unwanted Emissions (Above 1GHz)


Modulation Mode	11a	Test Freq. (FX)	F3
N _{TX}	1	Polarization	H




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	1228.00	47.00	-7.00	54.00	53.43	27.95	3.18	37.56	---	---	Average
2	1228.00	48.82	-25.18	74.00	55.25	27.95	3.18	37.56	---	---	Peak
3	3493.00	42.79	-25.51	68.30	40.01	32.70	5.69	35.61	---	---	Peak
4	10480.00	54.37	-13.93	68.30	42.10	37.79	9.80	35.32	---	---	Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.










Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11a	Test Freq. (FX)	F5
N _{TX}	1	Polarization	H




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Loss	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	1228.00	47.48	-6.52	54.00	53.91	27.95	3.18	37.56	---	---	Average
2	1228.00	49.26	-24.74	74.00	55.69	27.95	3.18	37.56	---	---	Peak
3	10600.00	41.95	-12.05	54.00	29.50	37.84	9.87	35.26	---	---	Average
4	10600.00	55.53	-18.47	74.00	43.08	37.84	9.87	35.26	---	---	Peak
5	15900.00	43.06	-10.94	54.00	26.64	40.18	11.72	35.48	---	---	Average
6	15900.00	55.86	-18.14	74.00	39.44	40.18	11.72	35.48	---	---	Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.



Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11a	Test Freq. (FX)	F6
N _{TX}	1	Polarization	V




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Loss	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	1228.00	37.29	-16.71	54.00	43.72	27.95	3.18	37.56	---	---	Average
2	1228.00	41.56	-32.44	74.00	47.99	27.95	3.18	37.56	---	---	Peak
3	3547.00	43.52	-24.78	68.30	40.55	32.77	5.71	35.51	---	---	Peak
4	10640.00	43.69	-10.31	54.00	31.17	37.86	9.90	35.24	---	---	Average
5	10640.00	56.13	-17.87	74.00	43.61	37.86	9.90	35.24	---	---	Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.



Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11a	Test Freq. (FX)	F6
N _{TX}	1	Polarization	H




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Loss	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	1228.00	47.13	-6.87	54.00	53.56	27.95	3.18	37.56	---	---	Average
2	1228.00	48.86	-25.14	74.00	55.29	27.95	3.18	37.56	---	---	Peak
3	3547.00	43.12	-25.18	68.30	40.15	32.77	5.71	35.51	---	---	Peak
4	10640.00	41.57	-12.43	54.00	29.05	37.86	9.90	35.24	---	---	Average
5	10640.00	55.23	-18.77	74.00	42.71	37.86	9.90	35.24	---	---	Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.



Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11a	Test Freq. (FX)	F7
N _{TX}	1	Polarization	V




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Loss	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	1228.00	37.48	-16.52	54.00	43.91	27.95	3.18	37.56	---	---	Average
2	1228.00	41.65	-32.35	74.00	48.08	27.95	3.18	37.56	---	---	Peak
3	11000.00	42.16	-11.84	54.00	29.15	38.00	10.11	35.10	---	---	Average
4	11000.00	55.62	-18.38	74.00	42.61	38.00	10.11	35.10	---	---	Peak
5	16500.00	58.45	-9.85	68.30	40.55	41.40	12.00	35.50	---	---	Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.



Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11a	Test Freq. (FX)	F7
N _{TX}	1	Polarization	H




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	1228.00	47.65	-6.35	54.00	54.08	27.95	3.18	37.56	---	---	Average
2	1228.00	49.52	-24.48	74.00	55.95	27.95	3.18	37.56	---	---	Peak
3	11000.00	42.36	-11.64	54.00	29.35	38.00	10.11	35.10	---	---	Average
4	11000.00	55.92	-18.08	74.00	42.91	38.00	10.11	35.10	---	---	Peak
5	16500.00	58.18	-10.12	68.30	40.28	41.40	12.00	35.50	---	---	Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.



Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11a	Test Freq. (FX)	F8
N _{TX}	1	Polarization	V




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Loss	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	1228.00	37.25	-16.75	54.00	43.68	27.95	3.18	37.56	---	---	Average
2	1228.00	41.62	-32.38	74.00	48.05	27.95	3.18	37.56	---	---	Peak
3	11160.00	42.23	-11.77	54.00	28.92	38.16	10.19	35.04	---	---	Average
4	11160.00	55.69	-18.31	74.00	42.38	38.16	10.19	35.04	---	---	Peak
5	16740.00	58.24	-10.06	68.30	39.92	41.54	12.14	35.36	---	---	Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.



Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11a	Test Freq. (FX)	F8
N _{TX}	1	Polarization	H




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Loss	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	1228.00	47.56	-6.44	54.00	53.99	27.95	3.18	37.56	---	---	Average
2	1228.00	49.51	-24.49	74.00	55.94	27.95	3.18	37.56	---	---	Peak
3	11160.00	42.14	-11.86	54.00	28.83	38.16	10.19	35.04	---	---	Average
4	11160.00	55.86	-18.14	74.00	42.55	38.16	10.19	35.04	---	---	Peak
5	16740.00	58.24	-10.06	68.30	39.92	41.54	12.14	35.36	---	---	Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.



Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11a	Test Freq. (FX)	F9
N _{TX}	1	Polarization	V




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Loss	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	1228.00	38.21	-15.79	54.00	44.64	27.95	3.18	37.56	---	---	Average
2	1228.00	42.51	-31.49	74.00	48.94	27.95	3.18	37.56	---	---	Peak
3	11400.00	42.65	-11.35	54.00	28.88	38.40	10.31	34.94	---	---	Average
4	11400.00	55.93	-18.07	74.00	42.16	38.40	10.31	34.94	---	---	Peak
5	17100.00	59.14	-9.16	68.30	40.13	41.58	12.45	35.02	---	---	Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.



Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11a	Test Freq. (FX)	F9
N _{TX}	1	Polarization	H




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Loss	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	1228.00	46.35	-7.65	54.00	52.78	27.95	3.18	37.56	---	---	Average
2	1228.00	48.14	-25.86	74.00	54.57	27.95	3.18	37.56	---	---	Peak
3	11400.00	42.66	-11.34	54.00	28.89	38.40	10.31	34.94	---	---	Average
4	11400.00	56.14	-17.86	74.00	42.37	38.40	10.31	34.94	---	---	Peak
5	17100.00	59.03	-9.27	68.30	40.02	41.58	12.45	35.02	---	---	Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.




3.4.8 Transmitter Radiated Unwanted Emissions (Above 1GHz) for HT20

Transmitter Radiated Unwanted Emissions (Above 1GHz)			
Modulation Mode	HT20	Test Freq. (FX)	F1
N _{TX}	1	Polarization	V



	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	1228.00	38.24	-15.76	54.00	44.67	27.95	3.18	37.56	---	---	Average
2	1228.00	42.53	-31.47	74.00	48.96	27.95	3.18	37.56	---	---	Peak
3	3453.00	46.85	-21.45	68.30	44.11	32.71	5.67	35.64	---	---	Peak
4	10360.00	55.86	-12.44	68.30	43.85	37.72	9.73	35.44	---	---	Peak


Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.





Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT20	Test Freq. (FX)	F2
N _{TX}	1	Polarization	V




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	1228.00	39.24	-14.76	54.00	45.67	27.95	3.18	37.56	---	---	Average
2	1228.00	43.45	-30.55	74.00	49.88	27.95	3.18	37.56	---	---	Peak
3	10400.00	55.66	-12.64	68.30	43.56	37.74	9.76	35.40	---	---	Peak
4	15600.00	46.85	-7.15	54.00	30.11	40.12	11.74	35.12	---	---	Average
5	15600.00	59.24	-14.76	74.00	42.50	40.12	11.74	35.12	---	---	Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.



Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT20	Test Freq. (FX)	F2
N _{TX}	1	Polarization	H




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	1228.00	48.12	-5.88	54.00	54.55	27.95	3.18	37.56	---	---	Average
2	1228.00	50.04	-23.96	74.00	56.47	27.95	3.18	37.56	---	---	Peak
3	10400.00	56.45	-11.85	68.30	44.35	37.74	9.76	35.40	---	---	Peak
4	15600.00	46.13	-7.87	54.00	29.39	40.12	11.74	35.12	---	---	Average
5	15600.00	59.22	-14.78	74.00	42.48	40.12	11.74	35.12	---	---	Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.



Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT20	Test Freq. (FX)	F3
N _{TX}	1	Polarization	V




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Loss	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	1228.00	39.25	-14.75	54.00	45.68	27.95	3.18	37.56	---	---	Average
2	1228.00	43.61	-30.39	74.00	50.04	27.95	3.18	37.56	---	---	Peak
3	3493.00	43.24	-25.06	68.30	40.46	32.70	5.69	35.61	---	---	Peak
4	10480.00	56.25	-12.05	68.30	43.98	37.79	9.80	35.32	---	---	Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.



Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT20	Test Freq. (FX)	F3
N _{TX}	1	Polarization	H




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	1228.00	47.24	-6.76	54.00	53.67	27.95	3.18	37.56	---	---	Average
2	1228.00	49.05	-24.95	74.00	55.48	27.95	3.18	37.56	---	---	Peak
3	3493.00	42.96	-25.34	68.30	40.18	32.70	5.69	35.61	---	---	Peak
4	10480.00	55.12	-13.18	68.30	42.85	37.79	9.80	35.32	---	---	Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.



Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT20	Test Freq. (FX)	F4
N _{TX}	1	Polarization	V




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Loss	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	1228.00	38.26	-15.74	54.00	44.69	27.95	3.18	37.56	---	---	Average
2	1228.00	42.45	-31.55	74.00	48.88	27.95	3.18	37.56	---	---	Peak
3	3507.00	45.82	-22.48	68.30	43.01	32.71	5.69	35.59	---	---	Peak
4	10520.00	42.61	-25.69	68.30	30.26	37.81	9.83	35.29	---	---	Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.




Transmitter Radiated Unwanted Emissions (Above 1GHz)			
Modulation Mode	HT20	Test Freq. (FX)	F4
N _{TX}	1	Polarization	H



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Loss	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	1228.00	48.25	-5.75	54.00	54.68	27.95	3.18	37.56	---	---	Average
2	1228.00	50.25	-23.75	74.00	56.68	27.95	3.18	37.56	---	---	Peak
3	3507.00	43.24	-25.06	68.30	40.43	32.71	5.69	35.59	---	---	Peak
4	10520.00	42.43	-25.87	68.30	30.08	37.81	9.83	35.29	---	---	Peak


Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.





Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT20	Test Freq. (FX)	F5
N _{TX}	1	Polarization	H




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	1228.00	47.12	-6.88	54.00	53.55	27.95	3.18	37.56	---	---	Average
2	1228.00	48.89	-25.11	74.00	55.32	27.95	3.18	37.56	---	---	Peak
3	10600.00	42.23	-11.77	54.00	29.78	37.84	9.87	35.26	---	---	Average
4	10600.00	56.01	-17.99	74.00	43.56	37.84	9.87	35.26	---	---	Peak
5	15900.00	46.11	-7.89	54.00	29.69	40.18	11.72	35.48	---	---	Average
6	15900.00	58.69	-15.31	74.00	42.27	40.18	11.72	35.48	---	---	Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.



Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT20	Test Freq. (FX)	F6
N _{TX}	1	Polarization	V




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Loss	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	1228.00	38.25	-15.75	54.00	44.68	27.95	3.18	37.56	---	---	Average
2	1228.00	42.26	-31.74	74.00	48.69	27.95	3.18	37.56	---	---	Peak
3	3547.00	45.92	-22.38	68.30	42.95	32.77	5.71	35.51	---	---	Peak
4	10640.00	42.24	-11.76	54.00	29.72	37.86	9.90	35.24	---	---	Average
5	10640.00	55.61	-18.39	74.00	43.09	37.86	9.90	35.24	---	---	Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.



Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT20	Test Freq. (FX)	F6
N _{TX}	1	Polarization	H




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Loss	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	1228.00	46.91	-7.09	54.00	53.34	27.95	3.18	37.56	---	---	Average
2	1228.00	48.69	-25.31	74.00	55.12	27.95	3.18	37.56	---	---	Peak
3	3547.00	43.84	-24.46	68.30	40.87	32.77	5.71	35.51	---	---	Peak
4	10640.00	42.38	-11.62	54.00	29.86	37.86	9.90	35.24	---	---	Average
5	10640.00	56.14	-17.86	74.00	43.62	37.86	9.90	35.24	---	---	Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.



Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT20	Test Freq. (FX)	F7
N _{TX}	1	Polarization	V




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Loss	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	1228.00	38.51	-15.49	54.00	44.94	27.95	3.18	37.56	---	---	Average
2	1228.00	43.04	-30.96	74.00	49.47	27.95	3.18	37.56	---	---	Peak
3	11000.00	42.53	-11.47	54.00	29.52	38.00	10.11	35.10	---	---	Average
4	11000.00	55.96	-18.04	74.00	42.95	38.00	10.11	35.10	---	---	Peak
5	16500.00	59.24	-9.06	68.30	41.34	41.40	12.00	35.50	---	---	Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.



Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT20	Test Freq. (FX)	F7
N _{TX}	1	Polarization	H




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Loss	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	1228.00	47.56	-6.44	54.00	53.99	27.95	3.18	37.56	---	---	Average
2	1228.00	49.41	-24.59	74.00	55.84	27.95	3.18	37.56	---	---	Peak
3	11000.00	41.76	-12.24	54.00	28.75	38.00	10.11	35.10	---	---	Average
4	11000.00	55.32	-18.68	74.00	42.31	38.00	10.11	35.10	---	---	Peak
5	16500.00	46.23	-7.77	54.00	28.33	41.40	12.00	35.50	---	---	Average
6	16500.00	58.94	-9.36	68.30	41.04	41.40	12.00	35.50	---	---	Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.



Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT20	Test Freq. (FX)	F8
N _{TX}	1	Polarization	V




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Loss	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	1228.00	37.24	-16.76	54.00	43.67	27.95	3.18	37.56	---	---	Average
2	1228.00	41.95	-32.05	74.00	48.38	27.95	3.18	37.56	---	---	Peak
3	11160.00	42.93	-11.07	54.00	29.62	38.16	10.19	35.04	---	---	Average
4	11160.00	52.64	-21.36	74.00	39.33	38.16	10.19	35.04	---	---	Peak
5	16740.00	59.25	-9.05	68.30	40.93	41.54	12.14	35.36	---	---	Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.



Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT20	Test Freq. (FX)	F8
N _{TX}	1	Polarization	H




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Loss	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	1228.00	46.21	-7.79	54.00	52.64	27.95	3.18	37.56	---	---	Average
2	1228.00	48.15	-25.85	74.00	54.58	27.95	3.18	37.56	---	---	Peak
3	11160.00	42.11	-11.89	54.00	28.80	38.16	10.19	35.04	---	---	Average
4	11160.00	55.86	-18.14	74.00	42.55	38.16	10.19	35.04	---	---	Peak
5	16740.00	59.03	-9.27	68.30	40.71	41.54	12.14	35.36	---	---	Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.



Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT20	Test Freq. (FX)	F9
N _{TX}	1	Polarization	V




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Loss	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	1128.00	39.52	-14.48	54.00	46.38	27.93	3.05	37.84	---	---	Average
2	1128.00	43.84	-30.16	74.00	50.70	27.93	3.05	37.84	---	---	Peak
3	11400.00	42.93	-11.07	54.00	29.16	38.40	10.31	34.94	---	---	Average
4	11400.00	56.45	-17.55	74.00	42.68	38.40	10.31	34.94	---	---	Peak
5	17100.00	59.65	-8.65	68.30	40.64	41.58	12.45	35.02	---	---	Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.



Transmitter Radiated Unwanted Emissions (Above 1GHz)			
Modulation Mode	HT20	Test Freq. (FX)	F9
N _{TX}	1	Polarization	H



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Loss	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	1228.00	46.25	-7.75	54.00	52.68	27.95	3.18	37.56	---	---	Average
2	1228.00	49.03	-24.97	74.00	55.46	27.95	3.18	37.56	---	---	Peak
3	11400.00	42.86	-11.14	54.00	29.09	38.40	10.31	34.94	---	---	Average
4	11400.00	56.31	-17.69	74.00	42.54	38.40	10.31	34.94	---	---	Peak
5	17100.00	59.72	-8.58	68.30	40.71	41.58	12.45	35.02	---	---	Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.



4 Test Equipment and Calibration Data

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMC Receiver	R&S	ESCS 30	100174	9 kHz ~ 2.75 GHz	Nov. 22, 2012	Conduction (CO04-HY)
LISN	SCHWARZBECK MESS-ELEKTRO NIK	NSLK 8127	8127-477	9kHz ~ 30MHz	Jan. 21, 2013	Conduction (CO04-HY)
LISN (Support Unit)	EMCO	3810/2NM	9703-1839	9 kHz ~ 30 MHz	Apr. 20, 2012	Conduction (CO04-HY)
RF Cable-CON	HUBER+SUHNER	RG213/U	7.61183201e+012	9kHz ~ 30MHz	Nov. 09, 2012	Conduction (CO04-HY)

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Spectrum Analyzer	R&S	FSP 30	100023/030	9KHz ~ 30GHz	Apr. 27, 2012	Conducted (TH01-HY)
DC Power Source	G.W.	GPC-6030D	C671845	DC 1V ~ 60V	Jun. 19, 2012	Conducted (TH01-HY)
Temp. and Humidity Chamber	Giant Force	GTH-225-20- SP-SD	MAA1112-007	-20 ~ 100°C	Nov. 21, 2012	Conducted (TH01-HY)
Signal Generator	R&S	SMR40	100116	10MHz ~ 40GHz	Jun. 26, 2012	Conducted (TH01-HY)
Power Sensor	Anritsu	MA2411B	1027452	300MHz ~ 40GHz	Sep. 08, 2012	Conducted (TH01-HY)
Power Meter	Anritsu	ML2495A	1124009	300MHz ~ 40GHz	Sep. 08, 2012	Conducted (TH01-HY)
RF Cable-2m	HUBER+SUHNER	SUCOFLEX_ 104	SN 345675/4	1GHz ~ 26.5GHz	NA	Conducted (TH01-HY)
RF Cable-3m	HUBER+SUHNER	SUCOFLEX_ 104	SN 345669/4	1GHz ~ 26.5GHz	NA	Conducted (TH01-HY)

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
AC Power Source	G.W	APS-9102	EL920581	AC 0V ~ 300V	Jul. 02, 2012	Conducted (TH01-HY)

Note: Calibration Interval of instruments listed above is two year.



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Spectrum Analyzer	R&S	FSP	100055	9Kz – 40GHz	Jun. 06, 2012	Radiation (03CH05-HY)
Receiver	R&S	ESIB26	100337	20Hz – 26.5GHz	Jun.21, 2012	Radiation (03CH05-HY)
3m Semi Anechoic Chamber	TDK	SAC-3M	03CH05-HY	30 MHz - 1 GHz 3m	N/A	Radiation (03CH05-HY)
Amplifier	COM-POWER	PA-103	161050	1 MHz ~ 1 GHz	Mar. 20, 2012	Radiation (03CH05-HY)
Amplifier	Agilent	8449B	3008A02665	1GHz – 26.5 GHz	Aug. 28, 2012	Radiation (03CH05-HY)
Horn Antenna	ETS-LINDGREN	3117	66584	1GHz~18GHz	Aug. 09, 2012	Radiation (03CH05-HY)
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA 9170517	18G~40G	Jan. 14, 2013	Radiation (03CH05-HY)
RF Cable-R03m	Jye Bao	RG142	03CH05-HY	30 MHz - 1 GHz	Oct. 14, 2012	Radiation (03CH05-HY)
RF Cable-HIGH	SUHNER	SUCOFLEX104	03CH05-HY	1GHz~40GHz	Oct. 14, 2012	Radiation (03CH05-HY)
Bilog Antenna	SCHAFFNER	CBL6111C	2725	30 MHz - 1 GHz	Oct. 06, 2012	Radiation (03CH05-HY)
Turn Table	HD	HD100	420/611	0 - 360 degree	N/A	Radiation (03CH05-HY)
Antenna Mast	HD	HD100	240/666	1 m - 4 m	N/A	Radiation (03CH05-HY)

Note: Calibration Interval of instruments listed above is one year.