

FCC ID : TWS-WAP-001R2

APPENDIX I MAXIMUM PERMISSIBLE EXPOSURE

According to FCC 1.1310 : The criteria listed in the following table shall be used to evaluate theenvironment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time					
(A) Limits for Occupational / Control Exposures									
300-1,500			F/300	6					
1,500-100,000			5	6					
(B) Limits for General Population / Uncontrol Exposures									
300-1,500			F/1500	6					
1,500-100,000			1	30					

CALCULATIONS

Given

$$\mathsf{E} = \frac{\sqrt{30 \times \mathsf{P} \times \mathsf{G}}}{\mathsf{d}} \quad \& \quad \mathsf{S} = \frac{\mathsf{E}^2}{3770}$$

Where E = Field strength in Volts / meter
P = Power in Watts
G = Numeric antenna gain
d = Distance in meters
S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{3770d^2}$$

Changing to units of mW and cm, using:

$$P(mW) = P(W) / 1000$$
 and
 $d(cm) = d(m) / 100$

Yields

$$S = \frac{30 \times (P/1000) \times G}{3770 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2}$$

Where
$$d = Distance$$
 in cm
 $P = Power$ in mW
 $G = Numeric$ antenna gain
 $S = Power$ density in mW / cm2

This report shall not be reproduced, except in full, without the written approval of Compliance Certification Services Inc.



Compliance Certification Services Inc. FCC ID : TWS-WAP-001R2

Power Density Limit, S=1.0mW/cm²

TEST RESULTS

Mode	Chain	Antenna Gain (dBi)	Minimum separation distance (cm)	Output Power (dBm)	Total Output Power (dBm)	Numeric antenna gain (mW)	Density Limit	Power Density at 20cm (mW/cm ²)
IEEE 802.11b	0	2.3	20	21.63	21.63	1.7	1.00	0.049150
IEEE 802.11g	0	2.3	20	25.07	25.07	1.7	1.00	0.108573
IEEE 802.11n HT20	0	2.3	20	23.05	26.21	1.7	1.00	0.141119
	1	2.3	20	23.34		1.7		
IEEE 802.11n HT40	0	2.3	20	20.85	23.95	1.7	1.00	0.083916
	1	2.3	20	21.03		1.7		

Remark: For mobile or fixed location transmitters, the maximum power density is 1.0 mW/cm² even if the calculation indicates that the power density would be larger.