

### #01 802.11b\_Front\_1.7cm\_Ch11

**DUT: 1N2318-01**

Communication System: 802.11b ; Frequency: 2462 MHz;Duty Cycle: 1:1

Medium: MSL\_2450\_120210 Medium parameters used:  $f = 2462$  MHz;  $\sigma = 2.03$  mho/m;  $\epsilon_r = 53.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.3 °C ; Liquid Temperature : 21.3 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3831; ConvF(6.82, 6.82, 6.82); Calibrated: 2012-01-04
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn679; Calibrated: 2011-06-24
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch11/Area Scan (31x131x1):** Measurement grid: dx=5mm, dy=5mm

Maximum value of SAR (interpolated) = 0.361 mW/g


**Ch11/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 11.6 V/m; Power Drift = 0.088 dB

Peak SAR (extrapolated) = 0.661 W/kg

**SAR(1 g) = 0.334 mW/g; SAR(10 g) = 0.173 mW/g**

Maximum value of SAR (measured) = 0.365 mW/g



0 dB = 0.365mW/g

## #02 802.11b\_Back\_1.7cm\_Ch11

**DUT: 1N2318-01**

Communication System: 802.11b ; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: MSL\_2450\_120210 Medium parameters used:  $f = 2462$  MHz;  $\sigma = 2.03$  mho/m;  $\epsilon_r = 53.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.3 °C ; Liquid Temperature : 21.3 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3831; ConvF(6.82, 6.82, 6.82); Calibrated: 2012-01-04
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn679; Calibrated: 2011-06-24
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch11/Area Scan (31x131x1):** Measurement grid: dx=5mm, dy=5mm

Maximum value of SAR (interpolated) = 0.403 mW/g


**Ch11/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 12.0 V/m; Power Drift = 0.046 dB

Peak SAR (extrapolated) = 0.713 W/kg

**SAR(1 g) = 0.368 mW/g; SAR(10 g) = 0.196 mW/g**

Maximum value of SAR (measured) = 0.399 mW/g



0 dB = 0.399mW/g

**#03 802.11b\_Left Side\_1.7cm\_Ch11****DUT: 1N2318-01**

Communication System: 802.11b ; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: MSL\_2450\_120210 Medium parameters used:  $f = 2462$  MHz;  $\sigma = 2.03$  mho/m;  $\epsilon_r = 53.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.3 °C ; Liquid Temperature : 21.3 °C

**DASY4 Configuration:**

- Probe: EX3DV4 - SN3831; ConvF(6.82, 6.82, 6.82); Calibrated: 2012-01-04
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn679; Calibrated: 2011-06-24
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch11/Area Scan (61x51x1):** Measurement grid: dx=5mm, dy=5mm

Maximum value of SAR (interpolated) = 0.048 mW/g

**Ch11/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.55 V/m; Power Drift = 0.169 dB

Peak SAR (extrapolated) = 0.084 W/kg

**SAR(1 g) = 0.045 mW/g; SAR(10 g) = 0.025 mW/g**

Maximum value of SAR (measured) = 0.050 mW/g


**Ch11/Zoom Scan (5x5x7)/Cube 1:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 4.55 V/m; Power Drift = 0.169 dB

Peak SAR (extrapolated) = 0.086 W/kg

**SAR(1 g) = 0.044 mW/g; SAR(10 g) = 0.024 mW/g**

Maximum value of SAR (measured) = 0.047 mW/g



### #04 802.11b\_Right Side\_1.7cm\_Ch11

**DUT: 1N2318-01**

Communication System: 802.11b ; Frequency: 2462 MHz;Duty Cycle: 1:1

Medium: MSL\_2450\_120210 Medium parameters used:  $f = 2462$  MHz;  $\sigma = 2.03$  mho/m;  $\epsilon_r = 53.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.3 °C ; Liquid Temperature : 21.3 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3831; ConvF(6.82, 6.82, 6.82); Calibrated: 2012-01-04
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn679; Calibrated: 2011-06-24
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch11/Area Scan (61x51x1):** Measurement grid: dx=5mm, dy=5mm

Maximum value of SAR (interpolated) = 0.089 mW/g


**Ch11/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.25 V/m; Power Drift = -0.122 dB

Peak SAR (extrapolated) = 0.148 W/kg

**SAR(1 g) = 0.084 mW/g; SAR(10 g) = 0.047 mW/g**

Maximum value of SAR (measured) = 0.091 mW/g



0 dB = 0.091mW/g

## #05 802.11b\_Top Side\_1.7cm\_Ch11

**DUT: 1N2318-01**

Communication System: 802.11b ; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: MSL\_2450\_120210 Medium parameters used:  $f = 2462$  MHz;  $\sigma = 2.03$  mho/m;  $\epsilon_r = 53.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.3 °C ; Liquid Temperature : 21.3 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3831; ConvF(6.82, 6.82, 6.82); Calibrated: 2012-01-04
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn679; Calibrated: 2011-06-24
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch11/Area Scan (61x131x1):** Measurement grid: dx=5mm, dy=5mm

Maximum value of SAR (interpolated) = 0.388 mW/g


**Ch11/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.96 V/m; Power Drift = 0.088 dB

Peak SAR (extrapolated) = 0.706 W/kg

**SAR(1 g) = 0.374 mW/g; SAR(10 g) = 0.203 mW/g**

Maximum value of SAR (measured) = 0.403 mW/g



0 dB = 0.403mW/g

### #05 802.11b\_Top Side\_1.7cm\_Ch11\_2D

**DUT: 1N2318-01**

Communication System: 802.11b ; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: MSL\_2450\_120210 Medium parameters used:  $f = 2462$  MHz;  $\sigma = 2.03$  mho/m;  $\epsilon_r = 53.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.3 °C ; Liquid Temperature : 21.3 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3831; ConvF(6.82, 6.82, 6.82); Calibrated: 2012-01-04
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn679; Calibrated: 2011-06-24
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch11/Area Scan (61x131x1):** Measurement grid: dx=5mm, dy=5mm

Maximum value of SAR (interpolated) = 0.388 mW/g


**Ch11/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 9.96 V/m; Power Drift = 0.088 dB

Peak SAR (extrapolated) = 0.706 W/kg

**SAR(1 g) = 0.374 mW/g; SAR(10 g) = 0.203 mW/g**

Maximum value of SAR (measured) = 0.403 mW/g



## #06 802.11b\_Bottom Side\_1.7cm\_Ch11

**DUT: 1N2318-01**

Communication System: 802.11b ; Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: MSL\_2450\_120210 Medium parameters used:  $f = 2462$  MHz;  $\sigma = 2.03$  mho/m;  $\epsilon_r = 53.8$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature : 22.3 °C ; Liquid Temperature : 21.3 °C

DASY4 Configuration:

- Probe: EX3DV4 - SN3831; ConvF(6.82, 6.82, 6.82); Calibrated: 2012-01-04
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn679; Calibrated: 2011-06-24
- Phantom: SAM\_Right; Type: SAM; Serial: TP-1303
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Ch11/Area Scan (31x131x1):** Measurement grid: dx=5mm, dy=5mm

Maximum value of SAR (interpolated) = 0.276 mW/g


**Ch11/Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 10.3 V/m; Power Drift = 0.131 dB

Peak SAR (extrapolated) = 0.495 W/kg

**SAR(1 g) = 0.259 mW/g; SAR(10 g) = 0.140 mW/g**

Maximum value of SAR (measured) = 0.273 mW/g



0 dB = 0.273mW/g