



<b>RF Mode</b>	802.11a	<b>Channel</b>	CH 60 : 5300 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5300.00	117.4 PK			1.51 H	83	103.0	14.4
2	*5300.00	107.1 AV			1.51 H	83	92.7	14.4
3	10600.00	61.2 PK	74.0	-12.8	1.20 H	36	36.9	24.3
4	10600.00	46.7 AV	54.0	-7.3	1.20 H	36	22.4	24.3

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5300.00	112.7 PK			1.32 V	313	98.3	14.4
2	*5300.00	102.6 AV			1.32 V	313	88.2	14.4
3	10600.00	60.6 PK	74.0	-13.4	1.00 V	277	36.3	24.3
4	10600.00	46.1 AV	54.0	-7.9	1.00 V	277	21.8	24.3

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.



<b>RF Mode</b>	802.11a	<b>Channel</b>	CH 64 : 5320 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5320.00	116.1 PK			1.81 H	83	101.7	14.4
2	*5320.00	105.9 AV			1.81 H	83	91.5	14.4
3	5350.00	71.3 PK	74.0	-2.7	1.81 H	83	57.0	14.3
<b>4</b>	<b>5350.00</b>	<b>52.5 AV</b>	<b>54.0</b>	<b>-1.5</b>	<b>1.81 H</b>	<b>83</b>	<b>38.2</b>	<b>14.3</b>
5	10640.00	61.3 PK	74.0	-12.7	1.49 H	42	36.5	24.8
6	10640.00	46.8 AV	54.0	-7.2	1.49 H	42	22.0	24.8

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5320.00	111.5 PK			1.61 V	307	97.1	14.4
2	*5320.00	101.1 AV			1.61 V	307	86.7	14.4
3	5350.00	69.1 PK	74.0	-4.9	1.61 V	307	54.8	14.3
4	5350.00	50.8 AV	54.0	-3.2	1.61 V	307	36.5	14.3
5	10640.00	60.8 PK	74.0	-13.2	1.39 V	271	36.0	24.8
6	10640.00	46.3 AV	54.0	-7.7	1.39 V	271	21.5	24.8

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.



<b>RF Mode</b>	802.11a	<b>Channel</b>	CH 100 : 5500 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	60.3 PK	74.0	-13.7	2.49 H	102	46.0	14.3
2	5460.00	46.0 AV	54.0	-8.0	2.49 H	102	31.7	14.3
<b>3</b>	<b>#5470.00</b>	<b>66.7 PK</b>	<b>68.2</b>	<b>-1.5</b>	<b>2.49 H</b>	<b>102</b>	<b>52.4</b>	<b>14.3</b>
4	*5500.00	115.2 PK			2.49 H	102	100.9	14.3
5	*5500.00	105.0 AV			2.49 H	102	90.7	14.3
6	11000.00	59.7 PK	74.0	-14.3	1.23 H	120	34.3	25.4
7	11000.00	45.4 AV	54.0	-8.6	1.23 H	120	20.0	25.4

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	58.4 PK	74.0	-15.6	1.76 V	288	44.1	14.3
2	5460.00	44.6 AV	54.0	-9.4	1.76 V	288	30.3	14.3
3	#5470.00	62.6 PK	68.2	-5.6	1.76 V	288	48.3	14.3
4	*5500.00	111.0 PK			1.76 V	288	96.7	14.3
5	*5500.00	100.7 AV			1.76 V	288	86.4	14.3
6	11000.00	59.2 PK	74.0	-14.8	1.35 V	324	33.8	25.4
7	11000.00	44.9 AV	54.0	-9.1	1.35 V	324	19.5	25.4

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11a	<b>Channel</b>	CH 116 : 5580 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5580.00	116.7 PK			2.65 H	96	102.6	14.1
2	*5580.00	106.7 AV			2.65 H	96	92.6	14.1
3	11160.00	61.3 PK	74.0	-12.7	1.39 H	114	34.9	26.4
4	11160.00	47.1 AV	54.0	-6.9	1.39 H	114	20.7	26.4

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5580.00	112.5 PK			1.92 V	282	98.4	14.1
2	*5580.00	102.2 AV			1.92 V	282	88.1	14.1
3	11160.00	60.8 PK	74.0	-13.2	1.51 V	318	34.4	26.4
4	11160.00	46.6 AV	54.0	-7.4	1.51 V	318	20.2	26.4

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.



<b>RF Mode</b>	802.11a	<b>Channel</b>	CH 140 : 5700 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5700.00	112.7 PK			2.67 H	96	98.8	13.9
2	*5700.00	102.4 AV			2.67 H	96	88.5	13.9
3	#5725.00	66.3 PK	68.2	-1.9	2.67 H	96	52.5	13.8
4	11400.00	63.5 PK	74.0	-10.5	1.41 H	114	36.7	26.8
5	11400.00	47.9 AV	54.0	-6.1	1.41 H	114	21.1	26.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5700.00	109.4 PK			1.94 V	294	95.5	13.9
2	*5700.00	99.0 AV			1.94 V	294	85.1	13.9
3	#5725.00	62.9 PK	68.2	-5.3	1.94 V	294	49.1	13.8
4	11400.00	61.7 PK	74.0	-12.3	1.53 V	330	34.9	26.8
5	11400.00	47.4 AV	54.0	-6.6	1.53 V	330	20.6	26.8

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11a	<b>Channel</b>	CH 144 : 5720 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5470.00	59.0 PK	68.2	-9.2	2.78 H	96	44.7	14.3
2	*5720.00	118.0 PK			2.78 H	96	104.1	13.9
3	*5720.00	108.0 AV			2.78 H	96	94.1	13.9
4	11440.00	62.4 PK	74.0	-11.6	1.52 H	144	35.2	27.2
5	11440.00	48.1 AV	54.0	-5.9	1.52 H	144	20.9	27.2

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5470.00	58.8 PK	68.2	-9.4	2.05 V	294	44.5	14.3
2	*5720.00	114.2 PK			2.05 V	294	100.3	13.9
3	*5720.00	104.2 AV			2.05 V	294	90.3	13.9
4	11440.00	61.9 PK	74.0	-12.1	1.64 V	319	34.7	27.2
5	11440.00	47.6 AV	54.0	-6.4	1.64 V	319	20.4	27.2

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11a	<b>Channel</b>	CH 149 : 5745 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5634.40	59.0 PK	68.2	-9.2	2.54 H	87	45.1	13.9
2	*5745.00	118.6 PK			2.54 H	87	104.8	13.8
3	*5745.00	108.5 AV			2.54 H	87	94.7	13.8
4	#5960.00	59.3 PK	68.2	-8.9	2.54 H	87	44.8	14.5
5	11490.00	63.7 PK	74.0	-10.3	1.28 H	135	36.1	27.6
6	11490.00	49.4 AV	54.0	-4.6	1.28 H	135	21.8	27.6

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5602.80	58.3 PK	68.2	-9.9	1.81 V	303	44.4	13.9
2	*5745.00	115.0 PK			1.81 V	303	101.2	13.8
3	*5745.00	104.7 AV			1.81 V	303	90.9	13.8
4	#5951.20	58.9 PK	68.2	-9.3	1.81 V	303	44.5	14.4
5	11490.00	63.2 PK	74.0	-10.8	1.40 V	310	35.6	27.6
6	11490.00	48.9 AV	54.0	-5.1	1.40 V	310	21.3	27.6

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11a	<b>Channel</b>	CH 157 : 5785 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5628.40	58.6 PK	68.2	-9.6	2.51 H	88	44.7	13.9
2	*5785.00	118.8 PK			2.51 H	88	105.1	13.7
3	*5785.00	108.7 AV			2.51 H	88	95.0	13.7
4	#5992.40	59.5 PK	68.2	-8.7	2.51 H	88	45.0	14.5
5	11570.00	63.2 PK	74.0	-10.8	1.25 H	134	35.8	27.4
6	11570.00	48.9 AV	54.0	-5.1	1.25 H	134	21.5	27.4

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5638.40	58.0 PK	68.2	-10.2	1.78 V	302	44.2	13.8
2	*5785.00	114.9 PK			1.78 V	302	101.2	13.7
3	*5785.00	104.9 AV			1.78 V	302	91.2	13.7
4	#6000.00	59.8 PK	68.2	-8.4	1.78 V	302	45.3	14.5
5	11570.00	62.7 PK	74.0	-11.3	1.37 V	311	35.3	27.4
6	11570.00	48.4 AV	54.0	-5.6	1.37 V	311	21.0	27.4

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.





<b>RF Mode</b>	802.11a	<b>Channel</b>	CH 165 : 5825 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBUV)	Correction Factor (dB/m)
1	#5610.80	58.1 PK	68.2	-10.1	2.49 H	88	44.2	13.9
2	*5825.00	118.9 PK			2.49 H	88	105.0	13.9
3	*5825.00	108.7 AV			2.49 H	88	94.8	13.9
4	#5992.40	59.5 PK	68.2	-8.7	2.49 H	88	45.0	14.5
5	11650.00	63.4 PK	74.0	-10.6	1.23 H	133	35.7	27.7
6	11650.00	49.1 AV	54.0	-4.9	1.23 H	133	21.4	27.7

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBUV)	Correction Factor (dB/m)
1	#5625.60	59.1 PK	68.2	-9.1	1.76 V	304	45.2	13.9
2	*5825.00	115.1 PK			1.76 V	304	101.2	13.9
3	*5825.00	104.9 AV			1.76 V	304	91.0	13.9
4	#5994.40	59.5 PK	68.2	-8.7	1.76 V	304	45.0	14.5
5	11650.00	62.9 PK	74.0	-11.1	1.35 V	309	35.2	27.7
6	11650.00	48.6 AV	54.0	-5.4	1.35 V	309	20.9	27.7

**Remarks:**

1. Emission Level(dBUV/m) = Raw Value(dBUV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20)	<b>Channel</b>	CH 36 : 5180 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	72.4 PK	74.0	-1.6	2.48 H	99	59.1	13.3
2	5150.00	49.1 AV	54.0	-4.9	2.48 H	99	35.8	13.3
3	*5180.00	117.5 PK			2.48 H	99	104.1	13.4
4	*5180.00	103.8 AV			2.48 H	99	90.4	13.4
5	#10360.00	62.1 PK	68.2	-6.1	1.86 H	124	38.1	24.0

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	67.1 PK	74.0	-6.9	2.28 V	329	53.8	13.3
2	5150.00	46.4 AV	54.0	-7.6	2.28 V	329	33.1	13.3
3	*5180.00	112.6 PK			2.28 V	329	99.2	13.4
4	*5180.00	99.0 AV			2.28 V	329	85.6	13.4
5	#10360.00	61.5 PK	68.2	-6.7	1.89 V	293	37.5	24.0

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20)	<b>Channel</b>	CH 40 : 5200 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5200.00	118.9 PK			2.48 H	101	105.3	13.6
2	*5200.00	106.7 AV			2.48 H	101	93.1	13.6
3	#10400.00	62.0 PK	68.2	-6.2	1.87 H	126	37.9	24.1

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5200.00	114.0 PK			2.29 V	327	100.4	13.6
2	*5200.00	101.9 AV			2.29 V	327	88.3	13.6
3	#10400.00	61.4 PK	68.2	-6.8	1.90 V	295	37.3	24.1

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # ": The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20)	<b>Channel</b>	CH 48 : 5240 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5240.00	119.5 PK			2.45 H	103	105.7	13.8
2	*5240.00	106.8 AV			2.45 H	103	93.0	13.8
3	5350.00	58.3 PK	74.0	-15.7	2.45 H	103	44.0	14.3
4	5350.00	44.8 AV	54.0	-9.2	2.45 H	103	30.5	14.3
5	#10480.00	63.0 PK	68.2	-5.2	1.83 H	128	38.8	24.2

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5240.00	114.9 PK			2.33 V	325	101.1	13.8
2	*5240.00	102.7 AV			2.33 V	325	88.9	13.8
3	5350.00	58.0 PK	74.0	-16.0	2.33 V	325	43.7	14.3
4	5350.00	44.4 AV	54.0	-9.6	2.33 V	325	30.1	14.3
5	#10480.00	62.4 PK	68.2	-5.8	1.84 V	297	38.2	24.2

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # ": The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20)	<b>Channel</b>	CH 52 : 5260 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	59.1 PK	74.0	-14.9	2.43 H	103	45.8	13.3
2	5150.00	44.6 AV	54.0	-9.4	2.43 H	103	31.3	13.3
3	*5260.00	119.9 PK			2.43 H	103	105.8	14.1
4	*5260.00	108.1 AV			2.43 H	103	94.0	14.1
5	#10520.00	63.1 PK	68.2	-5.1	1.81 H	120	38.8	24.3

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	58.5 PK	74.0	-15.5	2.33 V	325	45.2	13.3
2	5150.00	44.2 AV	54.0	-9.8	2.33 V	325	30.9	13.3
3	*5260.00	115.2 PK			2.33 V	325	101.1	14.1
4	*5260.00	103.7 AV			2.33 V	325	89.6	14.1
5	#10520.00	62.5 PK	68.2	-5.7	1.84 V	297	38.2	24.3

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20)	<b>Channel</b>	CH 60 : 5300 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5300.00	119.4 PK			2.45 H	101	105.0	14.4
2	*5300.00	107.6 AV			2.45 H	101	93.2	14.4
3	10600.00	62.3 PK	74.0	-11.7	1.79 H	122	38.0	24.3
4	10600.00	47.6 AV	54.0	-6.4	1.79 H	122	23.3	24.3
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5300.00	114.7 PK			2.36 V	322	100.3	14.4
2	*5300.00	103.2 AV			2.36 V	322	88.8	14.4
3	10600.00	61.7 PK	74.0	-12.3	1.95 V	321	37.4	24.3
4	10600.00	47.0 AV	54.0	-7.0	1.95 V	321	22.7	24.3

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.



<b>RF Mode</b>	802.11be (EHT20)	<b>Channel</b>	CH 64 : 5320 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5320.00	115.3 PK			2.73 H	101	100.9	14.4
2	*5320.00	103.1 AV			2.73 H	101	88.7	14.4
3	5350.00	72.1 PK	74.0	-1.9	2.73 H	101	57.8	14.3
4	5350.00	50.7 AV	54.0	-3.3	2.73 H	101	36.4	14.3
5	10640.00	62.7 PK	74.0	-11.3	2.07 H	121	37.9	24.8
6	10640.00	48.0 AV	54.0	-6.0	2.07 H	121	23.2	24.8

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5320.00	111.8 PK			2.64 V	321	97.4	14.4
2	*5320.00	99.6 AV			2.64 V	321	85.2	14.4
3	5350.00	65.6 PK	74.0	-8.4	2.64 V	321	51.3	14.3
4	5350.00	46.5 AV	54.0	-7.5	2.64 V	321	32.2	14.3
5	10640.00	62.1 PK	74.0	-11.9	2.23 V	320	37.3	24.8
6	10640.00	47.4 AV	54.0	-6.6	2.23 V	320	22.6	24.8

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.



<b>RF Mode</b>	802.11be (EHT20)	<b>Channel</b>	CH 100 : 5500 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	62.3 PK	74.0	-11.7	2.58 H	99	48.0	14.3
2	5460.00	45.4 AV	54.0	-8.6	2.58 H	99	31.1	14.3
3	#5470.00	66.3 PK	68.2	-1.9	2.58 H	99	52.0	14.3
4	*5500.00	114.8 PK			2.58 H	99	100.5	14.3
5	*5500.00	102.7 AV			2.58 H	99	88.4	14.3
6	11000.00	62.9 PK	74.0	-11.1	1.92 H	124	37.5	25.4
7	11000.00	48.2 AV	54.0	-5.8	1.92 H	124	22.8	25.4

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	60.1 PK	74.0	-13.9	2.49 V	322	45.8	14.3
2	5460.00	44.8 AV	54.0	-9.2	2.49 V	322	30.5	14.3
3	#5470.00	62.7 PK	68.2	-5.5	2.49 V	322	48.4	14.3
4	*5500.00	110.4 PK			2.49 V	322	96.1	14.3
5	*5500.00	98.2 AV			2.49 V	322	83.9	14.3
6	11000.00	62.4 PK	74.0	-11.6	2.08 V	319	37.0	25.4
7	11000.00	47.7 AV	54.0	-6.3	2.08 V	319	22.3	25.4

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.





<b>RF Mode</b>	802.11be (EHT20)	<b>Channel</b>	CH 116 : 5580 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5580.00	117.8 PK			2.77 H	94	103.7	14.1
2	*5580.00	105.8 AV			2.77 H	94	91.7	14.1
3	11160.00	63.1 PK	74.0	-10.9	2.11 H	129	36.7	26.4
4	11160.00	48.4 AV	54.0	-5.6	2.11 H	129	22.0	26.4

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5580.00	113.4 PK			2.68 V	317	99.3	14.1
2	*5580.00	101.3 AV			2.68 V	317	87.2	14.1
3	11160.00	62.6 PK	74.0	-11.4	2.27 V	324	36.2	26.4
4	11160.00	47.9 AV	54.0	-6.1	2.27 V	324	21.5	26.4

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.



<b>RF Mode</b>	802.11be (EHT20)	<b>Channel</b>	CH 140 : 5700 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5700.00	113.2 PK			2.77 H	91	99.3	13.9
2	*5700.00	100.9 AV			2.77 H	91	87.0	13.9
3	#5725.00	66.4 PK	68.2	-1.8	2.77 H	91	52.6	13.8
4	11400.00	63.6 PK	74.0	-10.4	1.73 H	132	36.8	26.8
5	11400.00	48.9 AV	54.0	-5.1	1.73 H	132	22.1	26.8

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5700.00	108.9 PK			2.68 V	313	95.0	13.9
2	*5700.00	96.5 AV			2.68 V	313	82.6	13.9
3	#5725.00	63.4 PK	68.2	-4.8	2.68 V	313	49.6	13.8
4	11400.00	63.1 PK	74.0	-10.9	2.28 V	327	36.3	26.8
5	11400.00	48.4 AV	54.0	-5.6	2.28 V	327	21.6	26.8

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20)	<b>Channel</b>	CH 144 : 5720 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5470.00	59.1 PK	68.2	-9.1	2.54 H	86	44.8	14.3
2	*5720.00	119.0 PK			2.54 H	86	105.1	13.9
3	*5720.00	107.4 AV			2.54 H	86	93.5	13.9
4	11440.00	64.3 PK	74.0	-9.7	1.96 H	137	37.1	27.2
5	11440.00	49.6 AV	54.0	-4.4	1.96 H	137	22.4	27.2

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5470.00	58.5 PK	68.2	-9.7	2.45 V	309	44.2	14.3
2	*5720.00	114.9 PK			2.45 V	309	101.0	13.9
3	*5720.00	103.2 AV			2.45 V	309	89.3	13.9
4	11440.00	63.8 PK	74.0	-10.2	2.04 V	306	36.6	27.2
5	11440.00	49.1 AV	54.0	-4.9	2.04 V	306	21.9	27.2

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20)	<b>Channel</b>	CH 149 : 5745 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5622.00	58.7 PK	68.2	-9.5	2.86 H	91	44.8	13.9
2	*5745.00	118.0 PK			2.86 H	91	104.2	13.8
3	*5745.00	106.7 AV			2.86 H	91	92.9	13.8
4	#5929.20	58.8 PK	68.2	-9.4	2.86 H	91	44.5	14.3
5	11490.00	64.1 PK	74.0	-9.9	1.64 H	132	36.5	27.6
6	11490.00	49.6 AV	54.0	-4.4	1.64 H	132	22.0	27.6

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5612.80	58.3 PK	68.2	-9.9	2.13 V	304	44.4	13.9
2	*5745.00	114.3 PK			2.13 V	304	100.5	13.8
3	*5745.00	102.9 AV			2.13 V	304	89.1	13.8
4	#5992.80	59.3 PK	68.2	-8.9	2.13 V	304	44.8	14.5
5	11490.00	63.6 PK	74.0	-10.4	1.72 V	311	36.0	27.6
6	11490.00	49.1 AV	54.0	-4.9	1.72 V	311	21.5	27.6

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20)	<b>Channel</b>	CH 157 : 5785 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5617.60	58.1 PK	68.2	-10.1	2.85 H	90	44.2	13.9
2	*5785.00	120.2 PK			2.85 H	90	106.5	13.7
3	*5785.00	107.3 AV			2.85 H	90	93.6	13.7
4	#5948.80	59.4 PK	68.2	-8.8	2.85 H	90	45.0	14.4
5	11570.00	63.6 PK	74.0	-10.4	1.63 H	131	36.2	27.4
6	11570.00	49.1 AV	54.0	-4.9	1.63 H	131	21.7	27.4

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5607.20	58.6 PK	68.2	-9.6	2.14 V	305	44.7	13.9
2	*5785.00	116.6 PK			2.14 V	305	102.9	13.7
3	*5785.00	103.9 AV			2.14 V	305	90.2	13.7
4	#5933.20	59.5 PK	68.2	-8.7	2.14 V	305	45.1	14.4
5	11570.00	63.1 PK	74.0	-10.9	1.73 V	312	35.7	27.4
6	11570.00	48.6 AV	54.0	-5.4	1.73 V	312	21.2	27.4

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20)	<b>Channel</b>	CH 165 : 5825 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5605.20	58.2 PK	68.2	-10.0	2.49 H	87	44.3	13.9
2	*5825.00	121.6 PK			2.49 H	87	107.7	13.9
3	*5825.00	107.8 AV			2.49 H	87	93.9	13.9
4	#5971.20	58.9 PK	68.2	-9.3	2.49 H	87	44.4	14.5
5	11650.00	63.7 PK	74.0	-10.3	1.27 H	134	36.0	27.7
6	11650.00	49.2 AV	54.0	-4.8	1.27 H	134	21.5	27.7

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5606.40	55.2 PK	68.2	-13.0	1.76 V	300	41.3	13.9
2	*5825.00	118.0 PK			1.76 V	300	104.1	13.9
3	*5825.00	104.2 AV			1.76 V	300	90.3	13.9
4	#5997.20	56.6 PK	68.2	-11.6	1.76 V	300	42.1	14.5
5	11650.00	63.2 PK	74.0	-10.8	1.35 V	315	35.5	27.7
6	11650.00	48.7 AV	54.0	-5.3	1.35 V	315	21.0	27.7

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT40)	<b>Channel</b>	CH 38 : 5190 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	72.2 PK	74.0	-1.8	2.47 H	99	58.9	13.3
2	5150.00	49.2 AV	54.0	-4.8	2.47 H	99	35.9	13.3
3	*5190.00	112.3 PK			2.47 H	99	98.8	13.5
4	*5190.00	99.6 AV			2.47 H	99	86.1	13.5
5	#10380.00	61.8 PK	68.2	-6.4	1.85 H	123	37.8	24.0

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	68.6 PK	74.0	-5.4	2.29 V	330	55.3	13.3
2	5150.00	47.1 AV	54.0	-6.9	2.29 V	330	33.8	13.3
3	*5190.00	107.6 PK			2.29 V	330	94.1	13.5
4	*5190.00	95.0 AV			2.29 V	330	81.5	13.5
5	#10380.00	61.2 PK	68.2	-7.0	1.90 V	292	37.2	24.0

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT40)	<b>Channel</b>	CH 46 : 5230 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5230.00	116.9 PK			2.45 H	103	103.1	13.8
2	*5230.00	104.4 AV			2.45 H	103	90.6	13.8
3	5350.00	64.2 PK	74.0	-9.8	2.45 H	103	49.9	14.3
4	5350.00	46.5 AV	54.0	-7.5	2.45 H	103	32.2	14.3
5	#10460.00	61.2 PK	68.2	-7.0	1.89 H	128	37.1	24.1

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5230.00	112.1 PK			2.31 V	333	98.3	13.8
2	*5230.00	99.9 AV			2.31 V	333	86.1	13.8
3	5350.00	61.5 PK	74.0	-12.5	2.31 V	333	47.2	14.3
4	5350.00	45.1 AV	54.0	-8.9	2.31 V	333	30.8	14.3
5	#10460.00	60.6 PK	68.2	-7.6	1.86 V	289	36.5	24.1

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.





<b>RF Mode</b>	802.11be (EHT40)	<b>Channel</b>	CH 54 : 5270 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	64.3 PK	74.0	-9.7	2.44 H	103	51.0	13.3
2	5150.00	45.1 AV	54.0	-8.9	2.44 H	103	31.8	13.3
3	*5270.00	116.8 PK			2.44 H	103	102.6	14.2
4	*5270.00	104.5 AV			2.44 H	103	90.3	14.2
5	#10540.00	61.9 PK	68.2	-6.3	1.78 H	120	37.6	24.3

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	61.5 PK	74.0	-12.5	2.37 V	324	48.2	13.3
2	5150.00	44.5 AV	54.0	-9.5	2.37 V	324	31.2	13.3
3	*5270.00	112.1 PK			2.37 V	324	97.9	14.2
4	*5270.00	99.8 AV			2.37 V	324	85.6	14.2
5	#10540.00	61.3 PK	68.2	-6.9	1.94 V	319	37.0	24.3

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # ": The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT40)	<b>Channel</b>	CH 62 : 5310 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5310.00	112.6 PK			2.40 H	100	98.2	14.4
2	*5310.00	100.2 AV			2.40 H	100	85.8	14.4
3	5350.00	70.9 PK	74.0	-3.1	2.40 H	100	56.6	14.3
4	5350.00	52.0 AV	54.0	-2.0	2.40 H	100	37.7	14.3
5	10620.00	61.8 PK	74.0	-12.2	1.74 H	123	37.2	24.6
6	10620.00	47.1 AV	54.0	-6.9	1.74 H	123	22.5	24.6

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5310.00	108.0 PK			2.31 V	323	93.6	14.4
2	*5310.00	95.8 AV			2.31 V	323	81.4	14.4
3	5350.00	67.6 PK	74.0	-6.4	2.31 V	323	53.3	14.3
4	5350.00	49.6 AV	54.0	-4.4	2.31 V	323	35.3	14.3
5	10620.00	61.2 PK	74.0	-12.8	1.90 V	320	36.6	24.6
6	10620.00	46.7 AV	54.0	-7.3	1.90 V	320	22.1	24.6

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.



<b>RF Mode</b>	802.11be (EHT40)	<b>Channel</b>	CH 102 : 5510 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	61.1 PK	74.0	-12.9	2.47 H	103	46.8	14.3
2	5460.00	45.6 AV	54.0	-8.4	2.47 H	103	31.3	14.3
3	#5470.00	66.3 PK	68.2	-1.9	2.47 H	103	52.0	14.3
4	*5510.00	111.1 PK			2.47 H	103	96.8	14.3
5	*5510.00	98.0 AV			2.47 H	103	83.7	14.3
6	11020.00	61.9 PK	74.0	-12.1	1.43 H	120	36.3	25.6
7	11020.00	47.2 AV	54.0	-6.8	1.43 H	120	21.6	25.6

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	59.6 PK	74.0	-14.4	2.38 V	318	45.3	14.3
2	5460.00	44.9 AV	54.0	-9.1	2.38 V	318	30.6	14.3
3	#5470.00	60.5 PK	68.2	-7.7	2.38 V	318	46.2	14.3
4	*5510.00	107.0 PK			2.38 V	318	92.7	14.3
5	*5510.00	93.7 AV			2.38 V	318	79.4	14.3
6	11020.00	61.4 PK	74.0	-12.6	1.97 V	315	35.8	25.6
7	11020.00	46.7 AV	54.0	-7.3	1.97 V	315	21.1	25.6

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT40)	<b>Channel</b>	CH 110 : 5550 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5550.00	116.9 PK			3.02 H	103	102.5	14.4
2	*5550.00	104.7 AV			3.02 H	103	90.3	14.4
3	11100.00	62.7 PK	74.0	-11.3	2.36 H	128	36.5	26.2
4	11100.00	48.0 AV	54.0	-6.0	2.36 H	128	21.8	26.2
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5550.00	112.5 PK			2.93 V	326	98.1	14.4
2	*5550.00	100.3 AV			2.93 V	326	85.9	14.4
3	11100.00	62.2 PK	74.0	-11.8	2.52 V	315	36.0	26.2
4	11100.00	47.5 AV	54.0	-6.5	2.52 V	315	21.3	26.2

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.



<b>RF Mode</b>	802.11be (EHT40)	<b>Channel</b>	CH 134 : 5670 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5670.00	112.8 PK			2.80 H	90	98.9	13.9
2	*5670.00	99.7 AV			2.80 H	90	85.8	13.9
3	#5725.00	66.6 PK	68.2	-1.6	2.80 H	90	52.8	13.8
4	11340.00	63.7 PK	74.0	-10.3	2.14 H	115	36.9	26.8
5	11340.00	49.0 AV	54.0	-5.0	2.14 H	115	22.2	26.8

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5670.00	108.5 PK			2.71 V	313	94.6	13.9
2	*5670.00	95.3 AV			2.71 V	313	81.4	13.9
3	#5725.00	64.0 PK	68.2	-4.2	2.71 V	313	50.2	13.8
4	11340.00	63.2 PK	74.0	-10.8	2.30 V	328	36.4	26.8
5	11340.00	48.5 AV	54.0	-5.5	2.30 V	328	21.7	26.8

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # ": The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT40)	<b>Channel</b>	CH 142 : 5710 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5470.00	58.8 PK	68.2	-9.4	2.55 H	86	44.5	14.3
2	*5710.00	116.9 PK			2.55 H	86	103.1	13.8
3	*5710.00	104.0 AV			2.55 H	86	90.2	13.8
4	11420.00	63.8 PK	74.0	-10.2	1.95 H	111	36.9	26.9
5	11420.00	49.1 AV	54.0	-4.9	1.95 H	111	22.2	26.9

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5470.00	58.5 PK	68.2	-9.7	2.46 V	309	44.2	14.3
2	*5710.00	112.6 PK			2.46 V	309	98.8	13.8
3	*5710.00	99.9 AV			2.46 V	309	86.1	13.8
4	11420.00	63.3 PK	74.0	-10.7	2.05 V	306	36.4	26.9
5	11420.00	48.6 AV	54.0	-5.4	2.05 V	306	21.7	26.9

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT40)	<b>Channel</b>	CH 151 : 5755 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5647.20	60.3 PK	68.2	-7.9	2.53 H	88	46.5	13.8
2	*5755.00	117.9 PK			2.53 H	88	104.0	13.9
3	*5755.00	104.8 AV			2.53 H	88	90.9	13.9
4	#5959.20	59.6 PK	68.2	-8.6	2.53 H	88	45.1	14.5
5	11510.00	63.0 PK	74.0	-11.0	1.31 H	133	35.3	27.7
6	11510.00	48.5 AV	54.0	-5.5	1.31 H	133	20.8	27.7

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5646.40	60.2 PK	68.2	-8.0	1.80 V	307	46.4	13.8
2	*5755.00	114.3 PK			1.80 V	307	100.4	13.9
3	*5755.00	101.3 AV			1.80 V	307	87.4	13.9
4	#5965.20	59.1 PK	68.2	-9.1	1.80 V	307	44.6	14.5
5	11510.00	62.5 PK	74.0	-11.5	1.39 V	314	34.8	27.7
6	11510.00	48.0 AV	54.0	-6.0	1.39 V	314	20.3	27.7

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT40)	<b>Channel</b>	CH 159 : 5795 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5647.60	58.4 PK	68.2	-9.8	2.61 H	89	44.6	13.8
2	*5795.00	117.3 PK			2.61 H	89	103.5	13.8
3	*5795.00	105.0 AV			2.61 H	89	91.2	13.8
4	#5934.00	59.5 PK	68.2	-8.7	2.61 H	89	45.1	14.4
5	11590.00	63.1 PK	74.0	-10.9	1.39 H	135	35.8	27.3
6	11590.00	48.6 AV	54.0	-5.4	1.39 H	135	21.3	27.3

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5649.20	55.9 PK	68.2	-12.3	1.88 V	301	42.1	13.8
2	*5795.00	113.6 PK			1.88 V	301	99.8	13.8
3	*5795.00	101.6 AV			1.88 V	301	87.8	13.8
4	#5984.00	57.8 PK	68.2	-10.4	1.88 V	301	43.3	14.5
5	11590.00	62.6 PK	74.0	-11.4	1.47 V	308	35.3	27.3
6	11590.00	48.1 AV	54.0	-5.9	1.47 V	308	20.8	27.3

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.





<b>RF Mode</b>	802.11be (EHT80)	<b>Channel</b>	CH 42 : 5210 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	72.5 PK	74.0	-1.5	2.46 H	100	59.2	13.3
2	5150.00	52.1 AV	54.0	-1.9	2.46 H	100	38.8	13.3
3	*5210.00	110.3 PK			2.46 H	100	96.6	13.7
4	*5210.00	97.3 AV			2.46 H	100	83.6	13.7
5	5350.00	59.4 PK	74.0	-14.6	2.46 H	100	45.1	14.3
6	5350.00	45.3 AV	54.0	-8.7	2.46 H	100	31.0	14.3
7	#10420.00	61.7 PK	68.2	-6.5	1.84 H	125	37.6	24.1

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	70.0 PK	74.0	-4.0	2.26 V	330	56.7	13.3
2	5150.00	48.6 AV	54.0	-5.4	2.26 V	330	35.3	13.3
3	*5210.00	105.4 PK			2.26 V	330	91.7	13.7
4	*5210.00	92.5 AV			2.26 V	330	78.8	13.7
5	5350.00	59.0 PK	74.0	-15.0	2.26 V	330	44.7	14.3
6	5350.00	44.9 AV	54.0	-9.1	2.26 V	330	30.6	14.3
7	#10420.00	61.1 PK	68.2	-7.1	1.87 V	294	37.0	24.1

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT80)	<b>Channel</b>	CH 58 : 5290 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	62.7 PK	74.0	-11.3	2.41 H	103	49.4	13.3
2	5150.00	45.1 AV	54.0	-8.9	2.41 H	103	31.8	13.3
3	*5290.00	109.7 PK			2.41 H	103	95.4	14.3
4	*5290.00	97.7 AV			2.41 H	103	83.4	14.3
5	5350.00	71.4 PK	74.0	-2.6	2.41 H	103	57.1	14.3
6	5350.00	52.2 AV	54.0	-1.8	2.41 H	103	37.9	14.3
7	#10580.00	61.6 PK	68.2	-6.6	1.83 H	120	37.4	24.2

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	60.3 PK	74.0	-13.7	2.32 V	324	47.0	13.3
2	5150.00	44.6 AV	54.0	-9.4	2.32 V	324	31.3	13.3
3	*5290.00	105.4 PK			2.32 V	324	91.1	14.3
4	*5290.00	93.4 AV			2.32 V	324	79.1	14.3
5	5350.00	67.0 PK	74.0	-7.0	2.32 V	324	52.7	14.3
6	5350.00	49.0 AV	54.0	-5.0	2.32 V	324	34.7	14.3
7	#10580.00	61.0 PK	68.2	-7.2	1.91 V	319	36.8	24.2

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT80)	<b>Channel</b>	CH 106 : 5530 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	64.4 PK	74.0	-9.6	2.58 H	104	50.1	14.3
2	5460.00	46.2 AV	54.0	-7.8	2.58 H	104	31.9	14.3
3	#5470.00	66.4 PK	68.2	-1.8	2.58 H	104	52.1	14.3
4	*5530.00	106.5 PK			2.58 H	104	92.1	14.4
5	*5530.00	94.5 AV			2.58 H	104	80.1	14.4
6	11060.00	63.0 PK	74.0	-11.0	1.93 H	129	37.1	25.9
7	11060.00	48.3 AV	54.0	-5.7	1.93 H	129	22.4	25.9

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	61.0 PK	74.0	-13.0	2.50 V	327	46.7	14.3
2	5460.00	45.1 AV	54.0	-8.9	2.50 V	327	30.8	14.3
3	#5470.00	61.9 PK	68.2	-6.3	2.50 V	327	47.6	14.3
4	*5530.00	102.1 PK			2.50 V	327	87.7	14.4
5	*5530.00	90.2 AV			2.50 V	327	75.8	14.4
6	11060.00	62.5 PK	74.0	-11.5	2.07 V	314	36.6	25.9
7	11060.00	47.8 AV	54.0	-6.2	2.07 V	314	21.9	25.9

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT80)	<b>Channel</b>	CH 122 : 5610 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5610.00	109.4 PK			2.61 H	89	95.5	13.9
2	*5610.00	96.0 AV			2.61 H	89	82.1	13.9
3	#5725.00	66.3 PK	68.2	-1.9	2.61 H	89	52.5	13.8
4	11220.00	63.1 PK	74.0	-10.9	1.89 H	114	36.5	26.6
5	11220.00	48.4 AV	54.0	-5.6	1.89 H	114	21.8	26.6

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5610.00	105.3 PK			2.46 V	312	91.4	13.9
2	*5610.00	91.6 AV			2.46 V	312	77.7	13.9
3	#5725.00	61.7 PK	68.2	-6.5	2.46 V	312	47.9	13.8
4	11220.00	62.6 PK	74.0	-11.4	2.05 V	309	36.0	26.6
5	11220.00	47.9 AV	54.0	-6.1	2.05 V	309	21.3	26.6

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # ": The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT80)	<b>Channel</b>	CH 138 : 5690 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5470.00	58.9 PK	68.2	-9.3	2.56 H	86	44.6	14.3
2	*5690.00	111.2 PK			2.56 H	86	97.4	13.8
3	*5690.00	98.2 AV			2.56 H	86	84.4	13.8
4	#5850.00	66.6 PK	68.2	-1.6	2.56 H	86	52.6	14.0
5	11380.00	64.2 PK	74.0	-9.8	1.90 H	137	37.4	26.8
6	11380.00	49.5 AV	54.0	-4.5	1.90 H	137	22.7	26.8

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5470.00	58.6 PK	68.2	-9.6	2.47 V	335	44.3	14.3
2	*5690.00	106.9 PK			2.47 V	335	93.1	13.8
3	*5690.00	94.1 AV			2.47 V	335	80.3	13.8
4	#5850.00	63.3 PK	68.2	-4.9	2.47 V	335	49.3	14.0
5	11380.00	63.7 PK	74.0	-10.3	2.06 V	306	36.9	26.8
6	11380.00	49.3 AV	54.0	-4.7	2.06 V	306	22.5	26.8

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT80)	<b>Channel</b>	CH 155 : 5775 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5643.60	66.6 PK	68.2	-1.6	2.63 H	88	52.8	13.8
2	*5775.00	111.5 PK			2.63 H	88	97.7	13.8
3	*5775.00	98.6 AV			2.63 H	88	84.8	13.8
4	#5924.80	63.5 PK	68.2	-4.7	2.63 H	88	49.2	14.3
5	11550.00	62.5 PK	74.0	-11.5	1.37 H	136	35.0	27.5
6	11550.00	48.0 AV	54.0	-6.0	1.37 H	136	20.5	27.5

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5646.80	64.9 PK	68.2	-3.3	1.90 V	307	51.1	13.8
2	*5775.00	107.9 PK			1.90 V	307	94.1	13.8
3	*5775.00	95.5 AV			1.90 V	307	81.7	13.8
4	#5932.40	60.7 PK	68.2	-7.5	1.90 V	307	46.3	14.4
5	11550.00	62.0 PK	74.0	-12.0	1.49 V	315	34.5	27.5
6	11550.00	47.5 AV	54.0	-6.5	1.49 V	315	20.0	27.5

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT160)	<b>Channel</b>	CH 50 : 5250 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	72.3 PK	74.0	-1.7	2.44 H	102	59.0	13.3
2	<b>5150.00</b>	<b>52.5 AV</b>	<b>54.0</b>	<b>-1.5</b>	<b>2.44 H</b>	<b>102</b>	<b>39.2</b>	<b>13.3</b>
3	*5250.00	104.1 PK			2.44 H	102	90.2	13.9
4	*5250.00	91.5 AV			2.44 H	102	77.6	13.9
5	5350.00	66.8 PK	74.0	-7.2	2.44 H	102	52.5	14.3
6	5350.00	50.7 AV	54.0	-3.3	2.44 H	102	36.4	14.3
7	#10500.00	61.4 PK	68.2	-6.8	1.82 H	127	37.2	24.2

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	71.2 PK	74.0	-2.8	2.32 V	326	57.9	13.3
2	5150.00	51.9 AV	54.0	-2.1	2.32 V	326	38.6	13.3
3	*5250.00	99.6 PK			2.32 V	326	85.7	13.9
4	*5250.00	87.0 AV			2.32 V	326	73.1	13.9
5	5350.00	64.2 PK	74.0	-9.8	2.32 V	326	49.9	14.3
6	5350.00	48.1 AV	54.0	-5.9	2.32 V	326	33.8	14.3
7	#10500.00	60.8 PK	68.2	-7.4	1.93 V	290	36.6	24.2

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT160)	<b>Channel</b>	CH 114 : 5570 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	64.9 PK	74.0	-9.1	2.54 H	89	50.6	14.3
2	5460.00	45.8 AV	54.0	-8.2	2.54 H	89	31.5	14.3
3	#5470.00	59.9 PK	68.2	-8.3	2.54 H	89	45.6	14.3
4	*5570.00	101.0 PK			2.54 H	89	86.8	14.2
5	*5570.00	88.4 AV			2.54 H	89	74.2	14.2
<b>6</b>	<b>#5725.00</b>	<b>66.7 PK</b>	<b>68.2</b>	<b>-1.5</b>	<b>2.54 H</b>	<b>89</b>	<b>52.9</b>	<b>13.8</b>
7	11140.00	63.2 PK	74.0	-10.8	1.88 H	134	36.8	26.4
8	11140.00	48.5 AV	54.0	-5.5	1.88 H	134	22.1	26.4

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	62.9 PK	74.0	-11.1	2.45 V	332	48.6	14.3
2	5460.00	44.8 AV	54.0	-9.2	2.45 V	332	30.5	14.3
3	#5470.00	59.2 PK	68.2	-9.0	2.45 V	332	44.9	14.3
4	*5570.00	96.6 PK			2.45 V	332	82.4	14.2
5	*5570.00	83.9 AV			2.45 V	332	69.7	14.2
6	#5725.00	63.5 PK	68.2	-4.7	2.45 V	332	49.7	13.8
7	11140.00	62.7 PK	74.0	-11.3	2.12 V	309	36.3	26.4
8	11140.00	48.0 AV	54.0	-6.0	2.12 V	309	21.6	26.4

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.





<b>RF Mode</b>	802.11be (EHT20) 26-tone RU	<b>Channel</b>	CH 36 : 5180 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23.4°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	58.1 PK	74.0	-15.9	2.53 H	93	44.8	13.3
2	5150.00	42.5 AV	54.0	-11.5	2.53 H	93	29.2	13.3
3	*5180.00	114.5 PK			2.53 H	93	101.1	13.4
4	*5180.00	102.6 AV			2.53 H	93	89.2	13.4
5	#10360.00	61.2 PK	68.2	-7.0	2.70 H	141	37.2	24.0

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	57.4 PK	74.0	-16.6	1.74 V	70	44.1	13.3
2	5150.00	42.3 AV	54.0	-11.7	1.74 V	70	29.0	13.3
3	*5180.00	111.2 PK			1.74 V	70	97.8	13.4
4	*5180.00	99.4 AV			1.74 V	70	86.0	13.4
5	#10360.00	60.6 PK	68.2	-7.6	1.29 V	308	36.6	24.0

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20) 26-tone RU	<b>Channel</b>	CH 40 : 5200 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23.4°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5200.00	113.9 PK			2.54 H	94	100.3	13.6
2	*5200.00	102.8 AV			2.54 H	94	89.2	13.6
3	#10400.00	60.5 PK	68.2	-7.7	2.69 H	142	36.4	24.1

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5200.00	110.6 PK			1.75 V	71	97.0	13.6
2	*5200.00	99.5 AV			1.75 V	71	85.9	13.6
3	#10400.00	59.9 PK	68.2	-8.3	1.30 V	309	35.8	24.1

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20) 26-tone RU	<b>Channel</b>	CH 48 : 5240 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23.4°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5240.00	116.1 PK			2.22 H	96	102.3	13.8
2	*5240.00	104.8 AV			2.22 H	96	91.0	13.8
3	5350.00	56.0 PK	74.0	-18.0	2.22 H	96	41.7	14.3
4	5350.00	42.1 AV	54.0	-11.9	2.22 H	96	27.8	14.3
5	#10480.00	61.6 PK	68.2	-6.6	2.39 H	144	37.4	24.2

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5240.00	112.6 PK			1.43 V	73	98.8	13.8
2	*5240.00	101.3 AV			1.43 V	73	87.5	13.8
3	5350.00	55.6 PK	74.0	-18.4	1.43 V	73	41.3	14.3
4	5350.00	41.8 AV	54.0	-12.2	1.43 V	73	27.5	14.3
5	#10480.00	61.0 PK	68.2	-7.2	1.60 V	311	36.8	24.2

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20) 26-tone RU	<b>Channel</b>	CH 52 : 5260 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23.4°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	54.7 PK	74.0	-19.3	2.60 H	97	41.4	13.3
2	5150.00	41.1 AV	54.0	-12.9	2.60 H	97	27.8	13.3
3	*5260.00	115.2 PK			2.60 H	97	101.1	14.1
4	*5260.00	104.5 AV			2.60 H	97	90.4	14.1
5	#10520.00	61.4 PK	68.2	-6.8	2.77 H	145	37.1	24.3

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	54.5 PK	74.0	-19.5	1.81 V	74	41.2	13.3
2	5150.00	40.9 AV	54.0	-13.1	1.81 V	74	27.6	13.3
3	*5260.00	111.8 PK			1.81 V	74	97.7	14.1
4	*5260.00	101.2 AV			1.81 V	74	87.1	14.1
5	#10520.00	60.8 PK	68.2	-7.4	1.36 V	304	36.5	24.3

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20) 26-tone RU	<b>Channel</b>	CH 60 : 5300 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23.4°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5300.00	115.2 PK			2.79 H	100	100.8	14.4
2	*5300.00	104.1 AV			2.79 H	100	89.7	14.4
3	10600.00	61.4 PK	74.0	-12.6	2.96 H	148	37.1	24.3
4	10600.00	47.2 AV	54.0	-6.8	2.96 H	148	22.9	24.3

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5300.00	111.9 PK			2.00 V	77	97.5	14.4
2	*5300.00	100.9 AV			2.00 V	77	86.5	14.4
3	10600.00	60.8 PK	74.0	-13.2	1.55 V	315	36.5	24.3
4	10600.00	46.6 AV	54.0	-7.4	1.55 V	315	22.3	24.3

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.



<b>RF Mode</b>	802.11be (EHT20) 26-tone RU	<b>Channel</b>	CH 64 : 5320 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23.4°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5320.00	116.8 PK			2.79 H	101	102.4	14.4
2	*5320.00	105.6 AV			2.79 H	101	91.2	14.4
3	5350.00	56.1 PK	74.0	-17.9	2.79 H	101	41.8	14.3
4	5350.00	42.3 AV	54.0	-11.7	2.79 H	101	28.0	14.3
5	10640.00	61.3 PK	74.0	-12.7	2.95 H	147	36.5	24.8
6	10640.00	47.1 AV	54.0	-6.9	2.95 H	147	22.3	24.8

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5320.00	113.4 PK			2.01 V	78	99.0	14.4
2	*5320.00	102.2 AV			2.01 V	78	87.8	14.4
3	5350.00	55.9 PK	74.0	-18.1	2.01 V	78	41.6	14.3
4	5350.00	42.1 AV	54.0	-11.9	2.01 V	78	27.8	14.3
5	10640.00	60.7 PK	74.0	-13.3	1.54 V	314	35.9	24.8
6	10640.00	46.5 AV	54.0	-7.5	1.54 V	314	21.7	24.8

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.



<b>RF Mode</b>	802.11be (EHT20) 26-tone RU	<b>Channel</b>	CH 100 : 5500 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23.4°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	55.2 PK	74.0	-18.8	2.64 H	98	40.9	14.3
2	5460.00	41.9 AV	54.0	-12.1	2.64 H	98	27.6	14.3
3	#5470.00	56.2 PK	68.2	-12.0	2.64 H	98	41.9	14.3
4	*5500.00	114.5 PK			2.64 H	98	100.2	14.3
5	*5500.00	103.8 AV			2.64 H	98	89.5	14.3
6	11000.00	61.6 PK	74.0	-12.4	2.22 H	100	36.2	25.4
7	11000.00	47.7 AV	54.0	-6.3	2.22 H	100	22.3	25.4

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	54.9 PK	74.0	-19.1	1.62 V	203	40.6	14.3
2	5460.00	41.6 AV	54.0	-12.4	1.62 V	203	27.3	14.3
3	#5470.00	55.9 PK	68.2	-12.3	1.62 V	203	41.6	14.3
4	*5500.00	109.4 PK			1.62 V	203	95.1	14.3
5	*5500.00	98.7 AV			1.62 V	203	84.4	14.3
6	11000.00	61.0 PK	74.0	-13.0	2.96 V	8	35.6	25.4
7	11000.00	47.1 AV	54.0	-6.9	2.96 V	8	21.7	25.4

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20) 26-tone RU	<b>Channel</b>	CH 116 : 5580 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23.4°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5580.00	114.3 PK			2.60 H	105	100.2	14.1
2	*5580.00	103.2 AV			2.60 H	105	89.1	14.1
3	11160.00	61.6 PK	74.0	-12.4	2.18 H	107	35.2	26.4
4	11160.00	47.7 AV	54.0	-6.3	2.18 H	107	21.3	26.4

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5580.00	110.3 PK			1.58 V	210	96.2	14.1
2	*5580.00	99.1 AV			1.58 V	210	85.0	14.1
3	11160.00	61.0 PK	74.0	-13.0	2.92 V	15	34.6	26.4
4	11160.00	47.1 AV	54.0	-6.9	2.92 V	15	20.7	26.4

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.





<b>RF Mode</b>	802.11be (EHT20) 26-tone RU	<b>Channel</b>	CH 140 : 5700 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23.4°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5700.00	117.0 PK			2.42 H	88	103.1	13.9
2	*5700.00	104.1 AV			2.42 H	88	90.2	13.9
3	#5725.00	55.5 PK	68.2	-12.7	2.42 H	88	41.7	13.8
4	11400.00	63.9 PK	74.0	-10.1	2.00 H	90	37.1	26.8
5	11400.00	50.0 AV	54.0	-4.0	2.00 H	90	23.2	26.8

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5700.00	112.0 PK			1.40 V	193	98.1	13.9
2	*5700.00	98.1 AV			1.40 V	193	84.2	13.9
3	#5725.00	55.2 PK	68.2	-13.0	1.40 V	193	41.4	13.8
4	11400.00	63.3 PK	74.0	-10.7	2.74 V	18	36.5	26.8
5	11400.00	49.4 AV	54.0	-4.6	2.74 V	18	22.6	26.8

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20) 26-tone RU	<b>Channel</b>	CH 144 : 5720 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23.4°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5470.00	55.5 PK	68.2	-12.7	2.60 H	87	41.2	14.3
2	*5720.00	115.2 PK			2.60 H	87	101.3	13.9
3	*5720.00	103.6 AV			2.60 H	87	89.7	13.9
4	11440.00	62.3 PK	74.0	-11.7	2.18 H	89	35.1	27.2
5	11440.00	48.4 AV	54.0	-5.6	2.18 H	89	21.2	27.2

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5470.00	55.3 PK	68.2	-12.9	1.58 V	192	41.0	14.3
2	*5720.00	110.2 PK			1.58 V	192	96.3	13.9
3	*5720.00	98.7 AV			1.58 V	192	84.8	13.9
4	11440.00	61.7 PK	74.0	-12.3	2.92 V	19	34.5	27.2
5	11440.00	47.8 AV	54.0	-6.2	2.92 V	19	20.6	27.2

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20) 26-tone RU	<b>Channel</b>	CH 149 : 5745 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23.4°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5608.80	55.4 PK	68.2	-12.8	2.60 H	86	41.5	13.9
2	*5745.00	124.1 PK			2.60 H	86	110.3	13.8
3	*5745.00	113.0 AV			2.60 H	86	99.2	13.8
4	#5985.60	57.2 PK	68.2	-11.0	2.60 H	86	42.7	14.5
5	11490.00	63.7 PK	74.0	-10.3	2.26 H	112	36.1	27.6
6	11490.00	49.6 AV	54.0	-4.4	2.26 H	112	22.0	27.6
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5614.00	55.4 PK	68.2	-12.8	1.66 V	191	41.5	13.9
2	*5745.00	119.0 PK			1.66 V	191	105.2	13.8
3	*5745.00	107.8 AV			1.66 V	191	94.0	13.8
4	#5985.60	56.7 PK	68.2	-11.5	1.66 V	191	42.2	14.5
5	11490.00	63.1 PK	74.0	-10.9	3.00 V	20	35.5	27.6
6	11490.00	49.0 AV	54.0	-5.0	3.00 V	20	21.4	27.6

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # ": The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20) 26-tone RU	<b>Channel</b>	CH 157 : 5785 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23.4°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5606.00	55.6 PK	68.2	-12.6	3.11 H	91	41.7	13.9
2	*5785.00	123.8 PK			3.11 H	91	110.1	13.7
3	*5785.00	112.5 AV			3.11 H	91	98.8	13.7
4	#5992.00	56.6 PK	68.2	-11.6	3.11 H	91	42.1	14.5
5	11570.00	63.3 PK	74.0	-10.7	2.77 H	117	35.9	27.4
6	11570.00	49.2 AV	54.0	-4.8	2.77 H	117	21.8	27.4

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5605.60	55.0 PK	68.2	-13.2	2.17 V	196	41.1	13.9
2	*5785.00	118.9 PK			2.17 V	196	105.2	13.7
3	*5785.00	107.6 AV			2.17 V	196	93.9	13.7
4	#5952.00	56.7 PK	68.2	-11.5	2.17 V	196	42.3	14.4
5	11570.00	62.7 PK	74.0	-11.3	3.51 V	25	35.3	27.4
6	11570.00	48.9 AV	54.0	-5.1	3.51 V	25	21.5	27.4

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # ": The radiated frequency is out of the restricted band.

<b>RF Mode</b>	802.11be (EHT20) 26-tone RU	<b>Channel</b>	CH 165 : 5825 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23.4°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5641.20	55.6 PK	68.2	-12.6	2.20 H	86	41.8	13.8
2	*5825.00	124.2 PK			2.20 H	86	110.3	13.9
3	*5825.00	113.9 AV			2.20 H	86	100.0	13.9
4	#5959.60	58.0 PK	68.2	-10.2	2.20 H	86	43.5	14.5
5	11650.00	63.4 PK	74.0	-10.6	1.86 H	111	35.7	27.7
6	11650.00	49.3 AV	54.0	-4.7	1.86 H	111	21.6	27.7

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5637.20	55.8 PK	68.2	-12.4	1.26 V	190	42.0	13.8
2	*5825.00	119.2 PK			1.26 V	190	105.3	13.9
3	*5825.00	108.9 AV			1.26 V	190	95.0	13.9
4	#5933.60	56.6 PK	68.2	-11.6	1.26 V	190	42.2	14.4
5	11650.00	62.8 PK	74.0	-11.2	2.60 V	19	35.1	27.7
6	11650.00	48.7 AV	54.0	-5.3	2.60 V	19	21.0	27.7

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # ": The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20) 52-tone RU	<b>Channel</b>	CH 36 : 5180 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23.4°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	55.1 PK	74.0	-18.9	2.53 H	96	41.8	13.3
2	5150.00	41.3 AV	54.0	-12.7	2.53 H	96	28.0	13.3
3	*5180.00	114.7 PK			2.53 H	96	101.3	13.4
4	*5180.00	102.8 AV			2.53 H	96	89.4	13.4
5	#10360.00	61.4 PK	68.2	-6.8	2.71 H	144	37.4	24.0

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	54.9 PK	74.0	-19.1	1.75 V	67	41.6	13.3
2	5150.00	41.2 AV	54.0	-12.8	1.75 V	67	27.9	13.3
3	*5180.00	111.4 PK			1.75 V	67	98.0	13.4
4	*5180.00	99.6 AV			1.75 V	67	86.2	13.4
5	#10360.00	60.8 PK	68.2	-7.4	1.30 V	305	36.8	24.0

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20) 52-tone RU	<b>Channel</b>	CH 40 : 5200 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23.4°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5200.00	115.8 PK			2.54 H	94	102.2	13.6
2	*5200.00	103.0 AV			2.54 H	94	89.4	13.6
3	#10400.00	61.4 PK	68.2	-6.8	2.69 H	140	37.3	24.1

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5200.00	112.5 PK			1.73 V	69	98.9	13.6
2	*5200.00	99.4 AV			1.73 V	69	85.8	13.6
3	#10400.00	60.8 PK	68.2	-7.4	1.28 V	307	36.7	24.1

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20) 52-tone RU	<b>Channel</b>	CH 48 : 5240 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23.4°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5240.00	119.1 PK			2.22 H	97	105.3	13.8
2	*5240.00	104.8 AV			2.22 H	97	91.0	13.8
3	5350.00	56.3 PK	74.0	-17.7	2.22 H	97	42.0	14.3
4	5350.00	42.0 AV	54.0	-12.0	2.22 H	97	27.7	14.3
5	#10480.00	61.2 PK	68.2	-7.0	2.39 H	145	37.0	24.2

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5240.00	115.8 PK			1.43 V	74	102.0	13.8
2	*5240.00	101.5 AV			1.43 V	74	87.7	13.8
3	5350.00	56.1 PK	74.0	-17.9	1.43 V	74	41.8	14.3
4	5350.00	41.8 AV	54.0	-12.2	1.43 V	74	27.5	14.3
5	#10480.00	60.6 PK	68.2	-7.6	1.60 V	312	36.4	24.2

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.





<b>RF Mode</b>	802.11be (EHT20) 52-tone RU	<b>Channel</b>	CH 52 : 5260 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23.4°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	55.3 PK	74.0	-18.7	2.71 H	98	42.0	13.3
2	5150.00	41.1 AV	54.0	-12.9	2.71 H	98	27.8	13.3
3	*5260.00	115.3 PK			2.71 H	98	101.2	14.1
4	*5260.00	104.6 AV			2.71 H	98	90.5	14.1
5	#10520.00	61.0 PK	68.2	-7.2	2.88 H	146	36.7	24.3

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	55.1 PK	74.0	-18.9	1.92 V	75	41.8	13.3
2	5150.00	40.8 AV	54.0	-13.2	1.92 V	75	27.5	13.3
3	*5260.00	111.9 PK			1.92 V	75	97.8	14.1
4	*5260.00	101.4 AV			1.92 V	75	87.3	14.1
5	#10520.00	60.4 PK	68.2	-7.8	1.47 V	313	36.1	24.3

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20) 52-tone RU	<b>Channel</b>	CH 60 : 5300 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23.4°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5300.00	116.5 PK			2.28 H	96	102.1	14.4
2	*5300.00	105.1 AV			2.28 H	96	90.7	14.4
3	10600.00	61.7 PK	74.0	-12.3	2.45 H	144	37.4	24.3
4	10600.00	47.5 AV	54.0	-6.5	2.45 H	144	23.2	24.3

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5300.00	113.2 PK			1.49 V	73	98.8	14.4
2	*5300.00	101.9 AV			1.49 V	73	87.5	14.4
3	10600.00	61.1 PK	74.0	-12.9	1.04 V	311	36.8	24.3
4	10600.00	46.9 AV	54.0	-7.1	1.04 V	311	22.6	24.3

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.

<b>RF Mode</b>	802.11be (EHT20) 52-tone RU	<b>Channel</b>	CH 64 : 5320 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23.4°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5320.00	116.8 PK			2.78 H	97	102.4	14.4
2	*5320.00	105.5 AV			2.78 H	97	91.1	14.4
3	5350.00	56.2 PK	74.0	-17.8	2.78 H	97	41.9	14.3
4	5350.00	42.5 AV	54.0	-11.5	2.78 H	97	28.2	14.3
5	10640.00	61.3 PK	74.0	-12.7	2.95 H	145	36.5	24.8
6	10640.00	47.1 AV	54.0	-6.9	2.95 H	145	22.3	24.8

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5320.00	113.6 PK			1.99 V	74	99.2	14.4
2	*5320.00	102.3 AV			1.99 V	74	87.9	14.4
3	5350.00	55.7 PK	74.0	-18.3	1.99 V	74	41.4	14.3
4	5350.00	42.4 AV	54.0	-11.6	1.99 V	74	28.1	14.3
5	10640.00	60.7 PK	74.0	-13.3	1.54 V	312	35.9	24.8
6	10640.00	46.5 AV	54.0	-7.5	1.54 V	312	21.7	24.8

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.



<b>RF Mode</b>	802.11be (EHT20) 52-tone RU	<b>Channel</b>	CH 100 : 5500 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23.4°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	56.0 PK	74.0	-18.0	2.65 H	103	41.7	14.3
2	5460.00	41.9 AV	54.0	-12.1	2.65 H	103	27.6	14.3
3	#5470.00	56.1 PK	68.2	-12.1	2.65 H	103	41.8	14.3
4	*5500.00	115.0 PK			2.65 H	103	100.7	14.3
5	*5500.00	103.7 AV			2.65 H	103	89.4	14.3
6	11000.00	62.1 PK	74.0	-11.9	2.23 H	105	36.7	25.4
7	11000.00	48.2 AV	54.0	-5.8	2.23 H	105	22.8	25.4

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	55.8 PK	74.0	-18.2	1.63 V	208	41.5	14.3
2	5460.00	41.6 AV	54.0	-12.4	1.63 V	208	27.3	14.3
3	#5470.00	55.8 PK	68.2	-12.4	1.63 V	208	41.5	14.3
4	*5500.00	110.4 PK			1.63 V	208	96.1	14.3
5	*5500.00	99.0 AV			1.63 V	208	84.7	14.3
6	11000.00	61.5 PK	74.0	-12.5	2.97 V	13	36.1	25.4
7	11000.00	47.6 AV	54.0	-6.4	2.97 V	13	22.2	25.4

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20) 52-tone RU	<b>Channel</b>	CH 116 : 5580 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23.4°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5580.00	115.9 PK			2.61 H	106	101.8	14.1
2	*5580.00	102.9 AV			2.61 H	106	88.8	14.1
3	11160.00	63.2 PK	74.0	-10.8	2.19 H	102	36.8	26.4
4	11160.00	49.3 AV	54.0	-4.7	2.19 H	102	22.9	26.4

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5580.00	110.8 PK			1.59 V	211	96.7	14.1
2	*5580.00	99.2 AV			1.59 V	211	85.1	14.1
3	11160.00	62.6 PK	74.0	-11.4	2.93 V	16	36.2	26.4
4	11160.00	48.7 AV	54.0	-5.3	2.93 V	16	22.3	26.4

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.



<b>RF Mode</b>	802.11be (EHT20) 52-tone RU	<b>Channel</b>	CH 140 : 5700 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23.4°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5700.00	116.1 PK			2.61 H	88	102.2	13.9
2	*5700.00	104.6 AV			2.61 H	88	90.7	13.9
3	#5725.00	55.7 PK	68.2	-12.5	2.61 H	88	41.9	13.8
4	11400.00	62.0 PK	74.0	-12.0	2.18 H	90	35.2	26.8
5	11400.00	48.1 AV	54.0	-5.9	2.18 H	90	21.3	26.8

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5700.00	111.0 PK			1.65 V	193	97.1	13.9
2	*5700.00	99.4 AV			1.65 V	193	85.5	13.9
3	#5725.00	55.5 PK	68.2	-12.7	1.65 V	193	41.7	13.8
4	11400.00	61.4 PK	74.0	-12.6	2.99 V	18	34.6	26.8
5	11400.00	47.5 AV	54.0	-6.5	2.99 V	18	20.7	26.8

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20) 52-tone RU	<b>Channel</b>	CH 144 : 5720 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23.4°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5470.00	55.5 PK	68.2	-12.7	2.60 H	89	41.2	14.3
2	*5720.00	115.9 PK			2.60 H	89	102.0	13.9
3	*5720.00	104.1 AV			2.60 H	89	90.2	13.9
4	11440.00	63.0 PK	74.0	-11.0	2.17 H	91	35.8	27.2
5	11440.00	49.1 AV	54.0	-4.9	2.17 H	91	21.9	27.2

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5470.00	55.1 PK	68.2	-13.1	1.66 V	194	40.8	14.3
2	*5720.00	111.0 PK			1.66 V	194	97.1	13.9
3	*5720.00	99.2 AV			1.66 V	194	85.3	13.9
4	11440.00	62.4 PK	74.0	-11.6	3.00 V	17	35.2	27.2
5	11440.00	48.5 AV	54.0	-5.5	3.00 V	17	21.3	27.2

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.

<b>RF Mode</b>	802.11be (EHT20) 52-tone RU	<b>Channel</b>	CH 149 : 5745 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23.4°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5608.80	55.9 PK	68.2	-12.3	2.91 H	89	42.0	13.9
2	*5745.00	122.9 PK			2.91 H	89	109.1	13.8
3	*5745.00	111.8 AV			2.91 H	89	98.0	13.8
4	#5975.60	57.7 PK	68.2	-10.5	2.91 H	89	43.2	14.5
5	11490.00	63.5 PK	74.0	-10.5	2.57 H	115	35.9	27.6
6	11490.00	49.4 AV	54.0	-4.6	2.57 H	115	21.8	27.6

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5625.20	55.5 PK	68.2	-12.7	1.97 V	194	41.6	13.9
2	*5745.00	118.0 PK			1.97 V	194	104.2	13.8
3	*5745.00	106.9 AV			1.97 V	194	93.1	13.8
4	#5973.20	56.4 PK	68.2	-11.8	1.97 V	194	41.9	14.5
5	11490.00	62.9 PK	74.0	-11.1	2.69 V	23	35.3	27.6
6	11490.00	48.8 AV	54.0	-5.2	2.69 V	23	21.2	27.6

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.





<b>RF Mode</b>	802.11be (EHT20) 52-tone RU	<b>Channel</b>	CH 157 : 5785 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23.4°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5647.20	56.2 PK	68.2	-12.0	2.66 H	87	42.4	13.8
2	*5785.00	123.3 PK			2.66 H	87	109.6	13.7
3	*5785.00	110.9 AV			2.66 H	87	97.2	13.7
4	#5976.40	56.7 PK	68.2	-11.5	2.66 H	87	42.2	14.5
5	11570.00	62.8 PK	74.0	-11.2	2.20 H	111	35.4	27.4
6	11570.00	48.7 AV	54.0	-5.3	2.20 H	111	21.3	27.4

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5626.00	54.9 PK	68.2	-13.3	1.72 V	192	41.0	13.9
2	*5785.00	118.3 PK			1.72 V	192	104.6	13.7
3	*5785.00	105.9 AV			1.72 V	192	92.2	13.7
4	#5986.40	56.6 PK	68.2	-11.6	1.72 V	192	42.1	14.5
5	11570.00	62.2 PK	74.0	-11.8	2.94 V	21	34.8	27.4
6	11570.00	48.1 AV	54.0	-5.9	2.94 V	21	20.7	27.4

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # ": The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20) 52-tone RU	<b>Channel</b>	CH 165 : 5825 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23.4°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5612.00	55.7 PK	68.2	-12.5	2.55 H	91	41.8	13.9
2	*5825.00	123.3 PK			2.55 H	91	109.4	13.9
3	*5825.00	111.8 AV			2.55 H	91	97.9	13.9
4	#5946.00	56.4 PK	68.2	-11.8	2.55 H	91	42.0	14.4
5	11650.00	62.9 PK	74.0	-11.1	2.09 H	115	35.2	27.7
6	11650.00	48.8 AV	54.0	-5.2	2.09 H	115	21.1	27.7

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5627.20	55.0 PK	68.2	-13.2	1.61 V	196	41.1	13.9
2	*5825.00	118.2 PK			1.61 V	196	104.3	13.9
3	*5825.00	106.8 AV			1.61 V	196	92.9	13.9
4	#5994.80	57.0 PK	68.2	-11.2	1.61 V	196	42.5	14.5
5	11650.00	62.3 PK	74.0	-11.7	2.95 V	25	34.6	27.7
6	11650.00	48.2 AV	54.0	-5.8	2.95 V	25	20.5	27.7

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # ": The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20) 106-tone RU	<b>Channel</b>	CH 36 : 5180 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23.4°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	60.0 PK	74.0	-14.0	2.66 H	102	46.7	13.3
2	5150.00	42.2 AV	54.0	-11.8	2.66 H	102	28.9	13.3
3	*5180.00	116.5 PK			2.66 H	102	103.1	13.4
4	*5180.00	103.7 AV			2.66 H	102	90.3	13.4
5	#10360.00	62.2 PK	68.2	-6.0	2.83 H	150	38.2	24.0

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	58.6 PK	74.0	-15.4	1.87 V	79	45.3	13.3
2	5150.00	41.8 AV	54.0	-12.2	1.87 V	79	28.5	13.3
3	*5180.00	113.1 PK			1.87 V	79	99.7	13.4
4	*5180.00	100.3 AV			1.87 V	79	86.9	13.4
5	#10360.00	61.6 PK	68.2	-6.6	1.42 V	317	37.6	24.0

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20) 106-tone RU	<b>Channel</b>	CH 40 : 5200 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23.4°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5200.00	116.4 PK			2.65 H	102	102.8	13.6
2	*5200.00	104.1 AV			2.65 H	102	90.5	13.6
3	#10400.00	62.0 PK	68.2	-6.2	2.82 H	149	37.9	24.1

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5200.00	113.1 PK			1.86 V	80	99.5	13.6
2	*5200.00	100.9 AV			1.86 V	80	87.3	13.6
3	#10400.00	61.4 PK	68.2	-6.8	1.41 V	318	37.3	24.1

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20) 106-tone RU	<b>Channel</b>	CH 48 : 5240 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23.4°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5240.00	117.7 PK			2.22 H	98	103.9	13.8
2	*5240.00	105.2 AV			2.22 H	98	91.4	13.8
3	5350.00	55.8 PK	74.0	-18.2	2.22 H	98	41.5	14.3
4	5350.00	41.8 AV	54.0	-12.2	2.22 H	98	27.5	14.3
5	#10480.00	62.2 PK	68.2	-6.0	2.39 H	145	38.0	24.2

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5240.00	114.4 PK			1.42 V	65	100.6	13.8
2	*5240.00	101.8 AV			1.42 V	65	88.0	13.8
3	5350.00	55.5 PK	74.0	-18.5	1.42 V	65	41.2	14.3
4	5350.00	41.6 AV	54.0	-12.4	1.42 V	65	27.3	14.3
5	#10480.00	61.6 PK	68.2	-6.6	1.61 V	303	37.4	24.2

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20) 106-tone RU	<b>Channel</b>	CH 52 : 5260 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23.4°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	55.1 PK	74.0	-18.9	2.82 H	99	41.8	13.3
2	5150.00	41.2 AV	54.0	-12.8	2.82 H	99	27.9	13.3
3	*5260.00	117.9 PK			2.82 H	99	103.8	14.1
4	*5260.00	105.3 AV			2.82 H	99	91.2	14.1
5	#10520.00	62.4 PK	68.2	-5.8	2.99 H	149	38.1	24.3

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	54.9 PK	74.0	-19.1	2.03 V	76	41.6	13.3
2	5150.00	41.1 AV	54.0	-12.9	2.03 V	76	27.8	13.3
3	*5260.00	114.7 PK			2.03 V	76	100.6	14.1
4	*5260.00	102.3 AV			2.03 V	76	88.2	14.1
5	#10520.00	61.8 PK	68.2	-6.4	1.58 V	314	37.5	24.3

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20) 106-tone RU	<b>Channel</b>	CH 60 : 5300 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23.4°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5300.00	120.3 PK			2.69 H	101	105.9	14.4
2	*5300.00	106.2 AV			2.69 H	101	91.8	14.4
3	10600.00	61.5 PK	74.0	-12.5	2.86 H	147	37.2	24.3
4	10600.00	47.3 AV	54.0	-6.7	2.86 H	147	23.0	24.3

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5300.00	117.0 PK			1.90 V	78	102.6	14.4
2	*5300.00	103.0 AV			1.90 V	78	88.6	14.4
3	10600.00	60.9 PK	74.0	-13.1	1.45 V	316	36.6	24.3
4	10600.00	46.7 AV	54.0	-7.3	1.45 V	316	22.4	24.3

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.



<b>RF Mode</b>	802.11be (EHT20) 106-tone RU	<b>Channel</b>	CH 64 : 5320 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23.4°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5320.00	116.5 PK			2.18 H	95	102.1	14.4
2	*5320.00	104.2 AV			2.18 H	95	89.8	14.4
<b>3</b>	<b>5350.00</b>	<b>72.5 PK</b>	<b>74.0</b>	<b>-1.5</b>	<b>2.18 H</b>	<b>95</b>	<b>58.2</b>	<b>14.3</b>
4	5350.00	42.6 AV	54.0	-11.4	2.18 H	95	28.3	14.3
5	10640.00	62.2 PK	74.0	-11.8	2.35 H	143	37.4	24.8
6	10640.00	48.0 AV	54.0	-6.0	2.35 H	143	23.2	24.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5320.00	113.4 PK			1.39 V	72	99.0	14.4
2	*5320.00	101.2 AV			1.39 V	72	86.8	14.4
3	5350.00	71.4 PK	74.0	-2.6	1.39 V	72	57.1	14.3
4	5350.00	42.3 AV	54.0	-11.7	1.39 V	72	28.0	14.3
5	10640.00	61.6 PK	74.0	-12.4	2.16 V	310	36.8	24.8
6	10640.00	47.4 AV	54.0	-6.6	2.16 V	310	22.6	24.8

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.





<b>RF Mode</b>	802.11be (EHT20) 106-tone RU	<b>Channel</b>	CH 100 : 5500 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23.4°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	58.7 PK	74.0	-15.3	2.28 H	99	44.4	14.3
2	5460.00	43.9 AV	54.0	-10.1	2.28 H	99	29.6	14.3
3	#5470.00	66.3 PK	68.2	-1.9	2.28 H	99	52.0	14.3
4	*5500.00	116.4 PK			2.28 H	99	102.1	14.3
5	*5500.00	103.5 AV			2.28 H	99	89.2	14.3
6	11000.00	60.5 PK	74.0	-13.5	1.85 H	79	35.1	25.4
7	11000.00	46.6 AV	54.0	-7.4	1.85 H	79	21.2	25.4

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	57.4 PK	74.0	-16.6	1.26 V	204	43.1	14.3
2	5460.00	42.5 AV	54.0	-11.5	1.26 V	204	28.2	14.3
3	#5470.00	62.9 PK	68.2	-5.3	1.26 V	204	48.6	14.3
4	*5500.00	111.4 PK			1.26 V	204	97.1	14.3
5	*5500.00	98.3 AV			1.26 V	204	84.0	14.3
6	11000.00	59.9 PK	74.0	-14.1	2.60 V	9	34.5	25.4
7	11000.00	46.0 AV	54.0	-8.0	2.60 V	9	20.6	25.4

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20) 106-tone RU	<b>Channel</b>	CH 116 : 5580 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23.4°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5580.00	116.6 PK			3.05 H	106	102.5	14.1
2	*5580.00	104.3 AV			3.05 H	106	90.2	14.1
3	11160.00	61.9 PK	74.0	-12.1	2.62 H	86	35.5	26.4
4	11160.00	48.1 AV	54.0	-5.9	2.62 H	86	21.7	26.4

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5580.00	111.5 PK			2.03 V	211	97.4	14.1
2	*5580.00	99.2 AV			2.03 V	211	85.1	14.1
3	11160.00	61.3 PK	74.0	-12.7	3.37 V	16	34.9	26.4
4	11160.00	47.5 AV	54.0	-6.5	3.37 V	16	21.1	26.4

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.



<b>RF Mode</b>	802.11be (EHT20) 106-tone RU	<b>Channel</b>	CH 140 : 5700 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23.4°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5700.00	115.3 PK			3.05 H	90	101.4	13.9
2	*5700.00	102.5 AV			3.05 H	90	88.6	13.9
3	#5725.00	66.2 PK	68.2	-2.0	3.05 H	90	52.4	13.8
4	11400.00	62.2 PK	74.0	-11.8	2.61 H	70	35.4	26.8
5	11400.00	48.4 AV	54.0	-5.6	2.61 H	70	21.6	26.8

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5700.00	110.4 PK			2.03 V	195	96.5	13.9
2	*5700.00	97.6 AV			2.03 V	195	83.7	13.9
3	#5725.00	61.8 PK	68.2	-6.4	2.03 V	195	48.0	13.8
4	11400.00	61.6 PK	74.0	-12.4	3.37 V	16	34.8	26.8
5	11400.00	47.8 AV	54.0	-6.2	3.37 V	16	21.0	26.8

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20) 106-tone RU	<b>Channel</b>	CH 144 : 5720 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23.4°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5470.00	56.0 PK	68.2	-12.2	2.60 H	87	41.7	14.3
2	*5720.00	117.1 PK			2.60 H	87	103.2	13.9
3	*5720.00	104.7 AV			2.60 H	87	90.8	13.9
4	11440.00	62.8 PK	74.0	-11.2	2.18 H	93	35.6	27.2
5	11440.00	48.9 AV	54.0	-5.1	2.18 H	93	21.7	27.2

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5470.00	55.6 PK	68.2	-12.6	1.58 V	214	41.3	14.3
2	*5720.00	112.0 PK			1.58 V	214	98.1	13.9
3	*5720.00	99.6 AV			1.58 V	214	85.7	13.9
4	11440.00	62.2 PK	74.0	-11.8	2.92 V	19	35.0	27.2
5	11440.00	48.3 AV	54.0	-5.7	2.92 V	19	21.1	27.2

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20) 106-tone RU	<b>Channel</b>	CH 149 : 5745 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23.4°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5615.60	56.1 PK	68.2	-12.1	2.91 H	90	42.2	13.9
2	*5745.00	121.1 PK			2.91 H	90	107.3	13.8
3	*5745.00	108.5 AV			2.91 H	90	94.7	13.8
4	#5974.80	57.1 PK	68.2	-11.1	2.91 H	90	42.6	14.5
5	11490.00	62.7 PK	74.0	-11.3	2.45 H	114	35.1	27.6
6	11490.00	48.6 AV	54.0	-5.4	2.45 H	114	21.0	27.6

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5618.00	55.2 PK	68.2	-13.0	1.97 V	195	41.3	13.9
2	*5745.00	116.2 PK			1.97 V	195	102.4	13.8
3	*5745.00	103.6 AV			1.97 V	195	89.8	13.8
4	#5944.40	56.6 PK	68.2	-11.6	1.97 V	195	42.2	14.4
5	11490.00	62.1 PK	74.0	-11.9	2.69 V	24	34.5	27.6
6	11490.00	48.0 AV	54.0	-6.0	2.69 V	24	20.4	27.6

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # ": The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20) 106-tone RU	<b>Channel</b>	CH 157 : 5785 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23.4°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5648.00	55.5 PK	68.2	-12.7	2.91 H	40	41.7	13.8
2	*5785.00	119.0 PK			2.91 H	40	105.3	13.7
3	*5785.00	107.5 AV			2.91 H	40	93.8	13.7
4	#5968.00	56.7 PK	68.2	-11.5	2.91 H	40	42.2	14.5
5	11570.00	61.5 PK	74.0	-12.5	2.44 H	164	34.1	27.4
6	11570.00	47.4 AV	54.0	-6.6	2.44 H	164	20.0	27.4

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5612.80	55.5 PK	68.2	-12.7	1.97 V	145	41.6	13.9
2	*5785.00	114.7 PK			1.97 V	145	101.0	13.7
3	*5785.00	103.3 AV			1.97 V	145	89.6	13.7
4	#5988.00	56.8 PK	68.2	-11.4	1.97 V	145	42.3	14.5
5	11570.00	60.9 PK	74.0	-13.1	2.69 V	66	33.5	27.4
6	11570.00	46.8 AV	54.0	-7.2	2.69 V	66	19.4	27.4

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # ": The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20) 106-tone RU	<b>Channel</b>	CH 165 : 5825 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23.4°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5649.60	55.5 PK	68.2	-12.7	2.77 H	41	41.7	13.8
2	*5825.00	119.6 PK			2.77 H	41	105.7	13.9
3	*5825.00	107.9 AV			2.77 H	41	94.0	13.9
4	#5984.40	56.2 PK	68.2	-12.0	2.77 H	41	41.7	14.5
5	11650.00	62.2 PK	74.0	-11.8	2.30 H	165	34.5	27.7
6	11650.00	48.1 AV	54.0	-5.9	2.30 H	165	20.4	27.7

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5608.00	55.4 PK	68.2	-12.8	1.83 V	146	41.5	13.9
2	*5825.00	114.7 PK			1.83 V	146	100.8	13.9
3	*5825.00	103.0 AV			1.83 V	146	89.1	13.9
4	#5990.00	56.4 PK	68.2	-11.8	1.83 V	146	41.9	14.5
5	11650.00	61.6 PK	74.0	-12.4	2.83 V	65	33.9	27.7
6	11650.00	47.5 AV	54.0	-6.5	2.83 V	65	19.8	27.7

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # ": The radiated frequency is out of the restricted band.

2Tx

<b>RF Mode</b>	802.11a	<b>Channel</b>	CH 36 : 5180 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	60.5 PK	74.0	-13.5	2.06 H	267	47.2	13.3
2	5150.00	42.9 AV	54.0	-11.1	2.06 H	267	29.6	13.3
3	*5180.00	112.2 PK			2.06 H	267	98.8	13.4
4	*5180.00	100.5 AV			2.06 H	267	87.1	13.4
5	#10360.00	62.5 PK	68.2	-5.7	2.24 H	315	38.5	24.0

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	58.7 PK	74.0	-15.3	1.49 V	322	45.4	13.3
2	5150.00	42.3 AV	54.0	-11.7	1.49 V	322	29.0	13.3
3	*5180.00	109.8 PK			1.49 V	322	96.4	13.4
4	*5180.00	98.6 AV			1.49 V	322	85.2	13.4
5	#10360.00	62.0 PK	68.2	-6.2	1.08 V	347	38.0	24.0

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.





<b>RF Mode</b>	802.11a	<b>Channel</b>	CH 40 : 5200 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5200.00	112.4 PK			2.06 H	260	98.8	13.6
2	*5200.00	101.7 AV			2.06 H	260	88.1	13.6
3	#10400.00	62.4 PK	68.2	-5.8	2.23 H	313	38.3	24.1

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5200.00	109.9 PK			1.48 V	324	96.3	13.6
2	*5200.00	99.6 AV			1.48 V	324	86.0	13.6
3	#10400.00	61.9 PK	68.2	-6.3	1.06 V	349	37.8	24.1

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # ": The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11a	<b>Channel</b>	CH 48 : 5240 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5240.00	114.0 PK			2.04 H	256	100.2	13.8
2	*5240.00	103.9 AV			2.04 H	256	90.1	13.8
3	5350.00	55.8 PK	74.0	-18.2	2.04 H	256	41.5	14.3
4	5350.00	42.0 AV	54.0	-12.0	2.04 H	256	27.7	14.3
5	#10480.00	62.3 PK	68.2	-5.9	2.26 H	311	38.1	24.2

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5240.00	111.3 PK			1.51 V	326	97.5	13.8
2	*5240.00	101.4 AV			1.51 V	326	87.6	13.8
3	5350.00	55.6 PK	74.0	-18.4	1.51 V	326	41.3	14.3
4	5350.00	41.8 AV	54.0	-12.2	1.51 V	326	27.5	14.3
5	#10480.00	61.8 PK	68.2	-6.4	1.10 V	351	37.6	24.2

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11a	<b>Channel</b>	CH 52 : 5260 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	56.0 PK	74.0	-18.0	1.71 H	57	42.7	13.3
2	5150.00	41.8 AV	54.0	-12.2	1.71 H	57	28.5	13.3
3	*5260.00	113.5 PK			1.71 H	57	99.4	14.1
4	*5260.00	104.1 AV			1.71 H	57	90.0	14.1
5	#10520.00	62.2 PK	68.2	-6.0	1.89 H	105	37.9	24.3

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	55.3 PK	74.0	-18.7	1.14 V	112	42.0	13.3
2	5150.00	41.2 AV	54.0	-12.8	1.14 V	112	27.9	13.3
3	*5260.00	110.4 PK			1.14 V	112	96.3	14.1
4	*5260.00	100.1 AV			1.14 V	112	86.0	14.1
5	#10520.00	61.6 PK	68.2	-6.6	1.43 V	137	37.3	24.3

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # ": The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11a	<b>Channel</b>	CH 60 : 5300 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5300.00	114.2 PK			1.71 H	251	99.8	14.4
2	*5300.00	104.2 AV			1.71 H	251	89.8	14.4
3	10600.00	61.7 PK	74.0	-12.3	1.88 H	299	37.4	24.3
4	10600.00	47.7 AV	54.0	-6.3	1.88 H	299	23.4	24.3

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5300.00	110.3 PK			1.13 V	306	95.9	14.4
2	*5300.00	100.0 AV			1.13 V	306	85.6	14.4
3	10600.00	61.1 PK	74.0	-12.9	1.42 V	286	36.8	24.3
4	10600.00	47.0 AV	54.0	-7.0	1.42 V	286	22.7	24.3

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.



<b>RF Mode</b>	802.11a	<b>Channel</b>	CH 64 : 5320 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5320.00	115.1 PK			1.39 H	96	100.7	14.4
2	*5320.00	105.1 AV			1.39 H	96	90.7	14.4
3	5350.00	70.3 PK	74.0	-3.7	1.39 H	96	56.0	14.3
4	5350.00	51.4 AV	54.0	-2.6	1.39 H	96	37.1	14.3
5	10640.00	61.3 PK	74.0	-12.7	1.56 H	144	36.5	24.8
6	10640.00	47.2 AV	54.0	-6.8	1.56 H	144	22.4	24.8

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5320.00	111.1 PK			1.45 V	151	96.7	14.4
2	*5320.00	100.8 AV			1.45 V	151	86.4	14.4
3	5350.00	66.2 PK	74.0	-7.8	1.45 V	151	51.9	14.3
4	5350.00	48.1 AV	54.0	-5.9	1.45 V	151	33.8	14.3
5	10640.00	60.7 PK	74.0	-13.3	1.10 V	131	35.9	24.8
6	10640.00	46.6 AV	54.0	-7.4	1.10 V	131	21.8	24.8

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.



<b>RF Mode</b>	802.11a	<b>Channel</b>	CH 100 : 5500 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	59.5 PK	74.0	-14.5	3.26 H	264	45.2	14.3
2	5460.00	43.2 AV	54.0	-10.8	3.26 H	264	28.9	14.3
3	#5470.00	63.3 PK	68.2	-4.9	3.26 H	264	49.0	14.3
4	*5500.00	114.9 PK			3.26 H	264	100.6	14.3
5	*5500.00	105.0 AV			3.26 H	264	90.7	14.3
6	11000.00	62.0 PK	74.0	-12.0	3.43 H	312	36.6	25.4
7	11000.00	47.9 AV	54.0	-6.1	3.43 H	312	22.5	25.4

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	59.2 PK	74.0	-14.8	2.68 V	319	44.9	14.3
2	5460.00	43.1 AV	54.0	-10.9	2.68 V	319	28.8	14.3
3	#5470.00	63.2 PK	68.2	-5.0	2.68 V	319	48.9	14.3
4	*5500.00	110.9 PK			2.68 V	319	96.6	14.3
5	*5500.00	100.9 AV			2.68 V	319	86.6	14.3
6	11000.00	61.5 PK	74.0	-12.5	2.97 V	299	36.1	25.4
7	11000.00	47.4 AV	54.0	-6.6	2.97 V	299	22.0	25.4

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11a	<b>Channel</b>	CH 116 : 5580 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5580.00	115.8 PK			2.10 H	191	101.7	14.1
2	*5580.00	105.3 AV			2.10 H	191	91.2	14.1
3	11160.00	62.9 PK	74.0	-11.1	2.27 H	239	36.5	26.4
4	11160.00	48.8 AV	54.0	-5.2	2.27 H	239	22.4	26.4
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5580.00	111.8 PK			1.52 V	246	97.7	14.1
2	*5580.00	101.7 AV			1.52 V	246	87.6	14.1
3	11160.00	62.4 PK	74.0	-11.6	1.81 V	226	36.0	26.4
4	11160.00	48.3 AV	54.0	-5.7	1.81 V	226	21.9	26.4

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.



<b>RF Mode</b>	802.11a	<b>Channel</b>	CH 140 : 5700 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5700.00	114.7 PK			2.11 H	190	100.8	13.9
2	*5700.00	105.0 AV			2.11 H	190	91.1	13.9
3	#5725.00	66.4 PK	68.2	-1.8	2.11 H	190	52.6	13.8
4	11400.00	62.9 PK	74.0	-11.1	2.28 H	238	36.1	26.8
5	11400.00	48.8 AV	54.0	-5.2	2.28 H	238	22.0	26.8

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5700.00	110.2 PK			1.53 V	245	96.3	13.9
2	*5700.00	99.7 AV			1.53 V	245	85.8	13.9
3	#5725.00	60.2 PK	68.2	-8.0	1.53 V	245	46.4	13.8
4	11400.00	62.4 PK	74.0	-11.6	1.82 V	225	35.6	26.8
5	11400.00	48.3 AV	54.0	-5.7	1.82 V	225	21.5	26.8

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.





<b>RF Mode</b>	802.11a	<b>Channel</b>	CH 144 : 5720 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5470.00	62.3 PK	68.2	-5.9	1.62 H	89	48.0	14.3
2	*5720.00	113.3 PK			1.62 H	89	99.4	13.9
3	*5720.00	103.3 AV			1.62 H	89	89.4	13.9
4	11440.00	64.3 PK	74.0	-9.7	1.99 H	142	37.1	27.2
5	11440.00	49.9 AV	54.0	-4.1	1.99 H	142	22.7	27.2

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5470.00	57.9 PK	68.2	-10.3	1.44 V	10	47.4	10.5
2	*5720.00	111.0 PK			1.44 V	10	97.1	13.9
3	*5720.00	101.2 AV			1.44 V	10	87.3	13.9
4	11440.00	62.0 PK	74.0	-12.0	2.15 V	317	36.5	25.5
5	11440.00	47.2 AV	54.0	-6.8	2.15 V	317	21.7	25.5

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11a	<b>Channel</b>	CH 149 : 5745 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5618.80	56.1 PK	68.2	-12.1	3.28 H	261	42.2	13.9
2	*5745.00	113.6 PK			3.28 H	261	99.8	13.8
3	*5745.00	103.3 AV			3.28 H	261	89.5	13.8
4	#5988.80	57.0 PK	68.2	-11.2	3.28 H	261	42.5	14.5
5	11490.00	62.9 PK	74.0	-11.1	3.77 H	327	35.3	27.6
6	11490.00	48.8 AV	54.0	-5.2	3.77 H	327	21.2	27.6

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5623.20	54.5 PK	68.2	-13.7	3.80 V	207	40.6	13.9
2	*5745.00	110.4 PK			3.80 V	207	96.6	13.8
3	*5745.00	100.4 AV			3.80 V	207	86.6	13.8
4	#5984.00	55.8 PK	68.2	-12.4	3.80 V	207	41.3	14.5
5	11490.00	62.3 PK	74.0	-11.7	3.67 V	116	34.7	27.6
6	11490.00	48.2 AV	54.0	-5.8	3.67 V	116	20.6	27.6

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



RF Mode	802.11a	Channel	CH 157 : 5785 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23°C, 71.3% RH
Tested By	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5630.40	55.0 PK	68.2	-13.2	2.07 H	193	41.1	13.9
2	*5785.00	115.9 PK			2.07 H	193	102.2	13.7
3	*5785.00	105.5 AV			2.07 H	193	91.8	13.7
4	#5959.20	56.5 PK	68.2	-11.7	2.07 H	193	42.0	14.5
5	11570.00	62.4 PK	74.0	-11.6	2.56 H	259	35.0	27.4
6	11570.00	48.3 AV	54.0	-5.7	2.56 H	259	20.9	27.4

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5620.40	55.3 PK	68.2	-12.9	2.59 V	139	41.4	13.9
2	*5785.00	112.6 PK			2.59 V	139	98.9	13.7
3	*5785.00	103.1 AV			2.59 V	139	89.4	13.7
4	#5998.00	56.1 PK	68.2	-12.1	2.59 V	139	41.6	14.5
5	11570.00	61.8 PK	74.0	-12.2	2.46 V	48	34.4	27.4
6	11570.00	47.7 AV	54.0	-6.3	2.46 V	48	20.3	27.4

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11a	<b>Channel</b>	CH 165 : 5825 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5638.40	55.0 PK	68.2	-13.2	2.05 H	192	41.2	13.8
2	*5825.00	115.5 PK			2.05 H	192	101.6	13.9
3	*5825.00	105.9 AV			2.05 H	192	92.0	13.9
4	#5960.00	56.6 PK	68.2	-11.6	2.05 H	192	42.1	14.5
5	11650.00	62.1 PK	74.0	-11.9	2.54 H	260	34.4	27.7
6	11650.00	48.0 AV	54.0	-6.0	2.54 H	260	20.3	27.7

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5615.20	55.2 PK	68.2	-13.0	2.57 V	138	41.3	13.9
2	*5825.00	112.3 PK			2.57 V	138	98.4	13.9
3	*5825.00	102.1 AV			2.57 V	138	88.2	13.9
4	#5998.00	56.3 PK	68.2	-11.9	2.57 V	138	41.8	14.5
5	11650.00	61.5 PK	74.0	-12.5	2.44 V	47	33.8	27.7
6	11650.00	47.4 AV	54.0	-6.6	2.44 V	47	19.7	27.7

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20)	<b>Channel</b>	CH 36 : 5180 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	65.5 PK	74.0	-8.5	2.06 H	260	52.2	13.3
2	5150.00	42.6 AV	54.0	-11.4	2.06 H	260	29.3	13.3
3	*5180.00	112.2 PK			2.06 H	260	98.8	13.4
4	*5180.00	100.5 AV			2.06 H	260	87.1	13.4
5	#10360.00	62.5 PK	68.2	-5.7	2.24 H	315	38.5	24.0

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	63.7 PK	74.0	-10.3	1.49 V	322	50.4	13.3
2	5150.00	41.9 AV	54.0	-12.1	1.49 V	322	28.6	13.3
3	*5180.00	109.8 PK			1.49 V	322	96.4	13.4
4	*5180.00	98.6 AV			1.49 V	322	85.2	13.4
5	#10360.00	62.0 PK	68.2	-6.2	1.08 V	347	38.0	24.0

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20)	<b>Channel</b>	CH 40 : 5200 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5200.00	113.5 PK			2.22 H	267	99.9	13.6
2	*5200.00	100.8 AV			2.22 H	267	87.2	13.6
3	#10400.00	61.9 PK	68.2	-6.3	2.44 H	322	37.8	24.1
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5200.00	111.1 PK			1.65 V	329	97.5	13.6
2	*5200.00	99.9 AV			1.65 V	329	86.3	13.6
3	#10400.00	61.4 PK	68.2	-6.8	1.24 V	340	37.3	24.1

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # ": The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20)	<b>Channel</b>	CH 48 : 5240 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5240.00	115.1 PK			2.02 H	258	101.3	13.8
2	*5240.00	103.5 AV			2.02 H	258	89.7	13.8
3	5350.00	56.3 PK	74.0	-17.7	2.02 H	258	42.0	14.3
4	5350.00	42.0 AV	54.0	-12.0	2.02 H	258	27.7	14.3
5	#10480.00	60.6 PK	68.2	-7.6	2.24 H	313	36.4	24.2

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5240.00	112.4 PK			1.53 V	320	98.6	13.8
2	*5240.00	101.3 AV			1.53 V	320	87.5	13.8
3	5350.00	55.4 PK	74.0	-18.6	1.53 V	320	41.1	14.3
4	5350.00	41.8 AV	54.0	-12.2	1.53 V	320	27.5	14.3
5	#10480.00	60.1 PK	68.2	-8.1	1.12 V	345	35.9	24.2

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20)	<b>Channel</b>	CH 52 : 5260 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	55.9 PK	74.0	-18.1	1.55 H	93	42.6	13.3
2	5150.00	41.7 AV	54.0	-12.3	1.55 H	93	28.4	13.3
3	*5260.00	114.1 PK			1.55 H	93	100.0	14.1
4	*5260.00	103.5 AV			1.55 H	93	89.4	14.1
5	#10520.00	61.9 PK	68.2	-6.3	1.72 H	141	37.6	24.3

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	55.6 PK	74.0	-18.4	1.29 V	148	42.3	13.3
2	5150.00	41.4 AV	54.0	-12.6	1.29 V	148	28.1	13.3
3	*5260.00	110.2 PK			1.29 V	148	96.1	14.1
4	*5260.00	98.1 AV			1.29 V	148	84.0	14.1
5	#10520.00	61.3 PK	68.2	-6.9	1.26 V	128	37.0	24.3

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # ": The radiated frequency is out of the restricted band.





<b>RF Mode</b>	802.11be (EHT20)	<b>Channel</b>	CH 60 : 5300 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5300.00	115.7 PK			1.55 H	52	101.3	14.4
2	*5300.00	104.2 AV			1.55 H	52	89.8	14.4
3	10600.00	61.2 PK	74.0	-12.8	1.72 H	100	36.9	24.3
4	10600.00	47.1 AV	54.0	-6.9	1.72 H	100	22.8	24.3

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5300.00	111.8 PK			1.29 V	107	97.4	14.4
2	*5300.00	99.9 AV			1.29 V	107	85.5	14.4
3	10600.00	60.6 PK	74.0	-13.4	1.26 V	87	36.3	24.3
4	10600.00	46.7 AV	54.0	-7.3	1.26 V	87	22.4	24.3

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.



<b>RF Mode</b>	802.11be (EHT20)	<b>Channel</b>	CH 64 : 5320 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5320.00	116.8 PK			3.14 H	267	102.4	14.4
2	*5320.00	105.1 AV			3.14 H	267	90.7	14.4
3	5350.00	70.5 PK	74.0	-3.5	3.14 H	267	56.2	14.3
4	5350.00	50.1 AV	54.0	-3.9	3.14 H	267	35.8	14.3
5	10640.00	61.6 PK	74.0	-12.4	3.31 H	283	36.8	24.8
6	10640.00	47.4 AV	54.0	-6.6	3.31 H	283	22.6	24.8

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5320.00	112.9 PK			2.56 V	290	98.5	14.4
2	*5320.00	100.1 AV			2.56 V	290	85.7	14.4
3	5350.00	68.3 PK	74.0	-5.7	2.56 V	290	54.0	14.3
4	5350.00	47.1 AV	54.0	-6.9	2.56 V	290	32.8	14.3
5	10640.00	61.0 PK	74.0	-13.0	2.85 V	270	36.2	24.8
6	10640.00	46.8 AV	54.0	-7.2	2.85 V	270	22.0	24.8

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.



<b>RF Mode</b>	802.11be (EHT20)	<b>Channel</b>	CH 100 : 5500 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	59.6 PK	74.0	-14.4	2.12 H	188	45.3	14.3
2	5460.00	44.0 AV	54.0	-10.0	2.12 H	188	29.7	14.3
<b>3</b>	<b>#5470.00</b>	<b>66.7 PK</b>	<b>68.2</b>	<b>-1.5</b>	<b>2.12 H</b>	<b>188</b>	<b>52.4</b>	<b>14.3</b>
4	*5500.00	116.8 PK			2.12 H	188	102.5	14.3
5	*5500.00	104.8 AV			2.12 H	188	90.5	14.3
6	11000.00	61.1 PK	74.0	-12.9	2.27 H	236	35.7	25.4
7	11000.00	47.0 AV	54.0	-7.0	2.27 H	236	21.6	25.4

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	58.6 PK	74.0	-15.4	1.54 V	243	44.3	14.3
2	5460.00	43.0 AV	54.0	-11.0	1.54 V	243	28.7	14.3
3	#5470.00	64.6 PK	68.2	-3.6	1.54 V	243	50.3	14.3
4	*5500.00	112.8 PK			1.54 V	243	98.5	14.3
5	*5500.00	101.2 AV			1.54 V	243	86.9	14.3
6	11000.00	60.6 PK	74.0	-13.4	1.83 V	224	35.2	25.4
7	11000.00	46.5 AV	54.0	-7.5	1.83 V	224	21.1	25.4

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # ": The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20)	<b>Channel</b>	CH 116 : 5580 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5580.00	117.7 PK			2.08 H	192	103.6	14.1
2	*5580.00	105.9 AV			2.08 H	192	91.8	14.1
3	11160.00	62.0 PK	74.0	-12.0	2.23 H	240	35.6	26.4
4	11160.00	47.9 AV	54.0	-6.1	2.23 H	240	21.5	26.4
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5580.00	113.5 PK			1.50 V	247	99.4	14.1
2	*5580.00	102.2 AV			1.50 V	247	88.1	14.1
3	11160.00	61.5 PK	74.0	-12.5	1.79 V	226	35.1	26.4
4	11160.00	47.4 AV	54.0	-6.6	1.79 V	226	21.0	26.4

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.



<b>RF Mode</b>	802.11be (EHT20)	<b>Channel</b>	CH 140 : 5700 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5700.00	115.6 PK			2.11 H	192	101.7	13.9
2	*5700.00	102.9 AV			2.11 H	192	89.0	13.9
3	#5725.00	66.4 PK	68.2	-1.8	2.11 H	192	52.6	13.8
4	11400.00	61.4 PK	74.0	-12.6	2.26 H	241	34.6	26.8
5	11400.00	47.3 AV	54.0	-6.7	2.26 H	241	20.5	26.8

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5700.00	111.5 PK			1.36 V	246	97.6	13.9
2	*5700.00	99.1 AV			1.36 V	246	85.2	13.9
3	#5725.00	60.0 PK	68.2	-8.2	1.36 V	246	46.2	13.8
4	11400.00	60.9 PK	74.0	-13.1	1.65 V	225	34.1	26.8
5	11400.00	46.8 AV	54.0	-7.2	1.65 V	225	20.0	26.8

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20)	<b>Channel</b>	CH 144 : 5720 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5470.00	62.2 PK	68.2	-6.0	1.49 H	88	47.9	14.3
2	*5720.00	115.0 PK			1.49 H	88	101.1	13.9
3	*5720.00	103.6 AV			1.49 H	88	89.7	13.9
4	11440.00	64.1 PK	74.0	-9.9	1.86 H	147	36.9	27.2
5	11440.00	49.7 AV	54.0	-4.3	1.86 H	147	22.5	27.2

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5470.00	61.5 PK	68.2	-6.7	1.43 V	10	47.2	14.3
2	*5720.00	112.6 PK			1.43 V	10	98.7	13.9
3	*5720.00	101.2 AV			1.43 V	10	87.3	13.9
4	11440.00	62.8 PK	74.0	-11.2	2.11 V	307	35.6	27.2
5	11440.00	48.6 AV	54.0	-5.4	2.11 V	307	21.4	27.2

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20)	<b>Channel</b>	CH 149 : 5745 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5637.20	56.0 PK	68.2	-12.2	2.33 H	197	42.2	13.8
2	*5745.00	116.0 PK			2.33 H	197	102.2	13.8
3	*5745.00	104.6 AV			2.33 H	197	90.8	13.8
4	#5959.20	56.8 PK	68.2	-11.4	2.33 H	197	42.3	14.5
5	11490.00	62.8 PK	74.0	-11.2	2.82 H	265	35.2	27.6
6	11490.00	48.5 AV	54.0	-5.5	2.82 H	265	20.9	27.6
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5629.60	55.7 PK	68.2	-12.5	2.85 V	143	41.8	13.9
2	*5745.00	112.7 PK			2.85 V	143	98.9	13.8
3	*5745.00	101.3 AV			2.85 V	143	87.5	13.8
4	#5950.00	56.1 PK	68.2	-12.1	2.85 V	143	41.7	14.4
5	11490.00	62.2 PK	74.0	-11.8	2.72 V	52	34.6	27.6
6	11490.00	47.9 AV	54.0	-6.1	2.72 V	52	20.3	27.6

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20)	<b>Channel</b>	CH 157 : 5785 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5622.40	55.5 PK	68.2	-12.7	2.07 H	199	41.6	13.9
2	*5785.00	116.9 PK			2.07 H	199	103.2	13.7
3	*5785.00	105.6 AV			2.07 H	199	91.9	13.7
4	#5994.40	56.5 PK	68.2	-11.7	2.07 H	199	42.0	14.5
5	11570.00	61.6 PK	74.0	-12.4	2.56 H	263	34.2	27.4
6	11570.00	47.3 AV	54.0	-6.7	2.56 H	263	19.9	27.4

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5627.20	54.7 PK	68.2	-13.5	2.59 V	145	40.8	13.9
2	*5785.00	113.4 PK			2.59 V	145	99.7	13.7
3	*5785.00	102.4 AV			2.59 V	145	88.7	13.7
4	#5965.20	56.1 PK	68.2	-12.1	2.59 V	145	41.6	14.5
5	11570.00	61.0 PK	74.0	-13.0	2.46 V	54	33.6	27.4
6	11570.00	46.7 AV	54.0	-7.3	2.46 V	54	19.3	27.4

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.





<b>RF Mode</b>	802.11be (EHT20)	<b>Channel</b>	CH 165 : 5825 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBUV)	Correction Factor (dB/m)
1	#5606.40	55.6 PK	68.2	-12.6	2.06 H	197	41.7	13.9
2	*5825.00	117.0 PK			2.06 H	197	103.1	13.9
3	*5825.00	106.1 AV			2.06 H	197	92.2	13.9
4	#5970.40	56.3 PK	68.2	-11.9	2.06 H	197	41.8	14.5
5	11650.00	61.8 PK	74.0	-12.2	2.57 H	261	34.1	27.7
6	11650.00	47.5 AV	54.0	-6.5	2.57 H	261	19.8	27.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBUV)	Correction Factor (dB/m)
1	#5624.40	55.2 PK	68.2	-13.0	2.58 V	143	41.3	13.9
2	*5825.00	113.8 PK			2.58 V	143	99.9	13.9
3	*5825.00	102.6 AV			2.58 V	143	88.7	13.9
4	#5989.60	57.0 PK	68.2	-11.2	2.58 V	143	42.5	14.5
5	11650.00	61.2 PK	74.0	-12.8	2.45 V	52	33.5	27.7
6	11650.00	46.9 AV	54.0	-7.1	2.45 V	52	19.2	27.7

**Remarks:**

1. Emission Level(dBUV/m) = Raw Value(dBUV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT40)	<b>Channel</b>	CH 38 : 5190 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	72.3 PK	74.0	-1.7	2.52 H	95	59.0	13.3
2	5150.00	49.8 AV	54.0	-4.2	2.52 H	95	36.5	13.3
3	*5190.00	111.2 PK			2.52 H	95	97.7	13.5
4	*5190.00	98.0 AV			2.52 H	95	84.5	13.5
5	#10380.00	61.4 PK	68.2	-6.8	2.70 H	150	37.4	24.0

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	68.3 PK	74.0	-5.7	1.95 V	157	55.0	13.3
2	5150.00	45.2 AV	54.0	-8.8	1.95 V	157	31.9	13.3
3	*5190.00	108.4 PK			1.95 V	157	94.9	13.5
4	*5190.00	94.8 AV			1.95 V	157	81.3	13.5
5	#10380.00	60.9 PK	68.2	-7.3	1.54 V	182	36.9	24.0

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT40)	<b>Channel</b>	CH 46 : 5230 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5230.00	112.3 PK			2.21 H	264	98.5	13.8
2	*5230.00	99.5 AV			2.21 H	264	85.7	13.8
3	5350.00	56.0 PK	74.0	-18.0	2.21 H	264	41.7	14.3
4	5350.00	42.1 AV	54.0	-11.9	2.21 H	264	27.8	14.3
5	#10460.00	62.3 PK	68.2	-5.9	2.39 H	319	38.2	24.1

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5230.00	109.9 PK			1.64 V	326	96.1	13.8
2	*5230.00	96.5 AV			1.64 V	326	82.7	13.8
3	5350.00	55.1 PK	74.0	-18.9	1.64 V	326	40.8	14.3
4	5350.00	41.9 AV	54.0	-12.1	1.64 V	326	27.6	14.3
5	#10460.00	61.8 PK	68.2	-6.4	1.23 V	343	37.7	24.1

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT40)	<b>Channel</b>	CH 54 : 5270 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	55.5 PK	74.0	-18.5	1.70 H	47	42.2	13.3
2	5150.00	41.5 AV	54.0	-12.5	1.70 H	47	28.2	13.3
3	*5270.00	111.9 PK			1.70 H	47	97.7	14.2
4	*5270.00	101.4 AV			1.70 H	47	87.2	14.2
5	#10540.00	61.6 PK	68.2	-6.6	1.87 H	95	37.3	24.3

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	55.1 PK	74.0	-18.9	1.14 V	102	41.8	13.3
2	5150.00	41.3 AV	54.0	-12.7	1.14 V	102	28.0	13.3
3	*5270.00	107.9 PK			1.14 V	102	93.7	14.2
4	*5270.00	95.6 AV			1.14 V	102	81.4	14.2
5	#10540.00	61.0 PK	68.2	-7.2	1.41 V	82	36.7	24.3

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT40)	<b>Channel</b>	CH 62 : 5310 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5310.00	113.7 PK			3.18 H	267	99.3	14.4
2	*5310.00	101.5 AV			3.18 H	267	87.1	14.4
<b>3</b>	<b>5350.00</b>	<b>72.5 PK</b>	<b>74.0</b>	<b>-1.5</b>	<b>3.18 H</b>	<b>267</b>	<b>58.2</b>	<b>14.3</b>
4	5350.00	51.0 AV	54.0	-3.0	3.18 H	267	36.7	14.3
5	10620.00	61.5 PK	74.0	-12.5	3.35 H	315	36.9	24.6
6	10620.00	47.4 AV	54.0	-6.6	3.35 H	315	22.8	24.6

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5310.00	109.9 PK			2.60 V	290	95.5	14.4
2	*5310.00	97.5 AV			2.60 V	290	83.1	14.4
3	5350.00	69.9 PK	74.0	-4.1	2.60 V	290	55.6	14.3
4	5350.00	48.8 AV	54.0	-5.2	2.60 V	290	34.5	14.3
5	10620.00	60.9 PK	74.0	-13.1	2.89 V	302	36.3	24.6
6	10620.00	46.8 AV	54.0	-7.2	2.89 V	302	22.2	24.6

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.



<b>RF Mode</b>	802.11be (EHT40)	<b>Channel</b>	CH 102 : 5510 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	63.7 PK	74.0	-10.3	2.62 H	99	49.4	14.3
2	5460.00	47.6 AV	54.0	-6.4	2.62 H	99	33.3	14.3
3	#5470.00	66.3 PK	68.2	-1.9	2.62 H	99	52.0	14.3
4	*5510.00	111.6 PK			2.62 H	99	97.3	14.3
5	*5510.00	98.6 AV			2.62 H	99	84.3	14.3
6	11020.00	62.0 PK	74.0	-12.0	1.95 H	122	36.4	25.6
7	11020.00	47.3 AV	54.0	-6.7	1.95 H	122	21.7	25.6

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	62.7 PK	74.0	-11.3	1.72 V	9	48.4	14.3
2	5460.00	46.2 AV	54.0	-7.8	1.72 V	9	31.9	14.3
3	#5470.00	61.8 PK	68.2	-6.4	1.72 V	9	47.5	14.3
4	*5510.00	108.3 PK			1.72 V	9	94.0	14.3
5	*5510.00	96.1 AV			1.72 V	9	81.8	14.3
6	11020.00	61.4 PK	74.0	-12.6	2.01 V	299	35.8	25.6
7	11020.00	46.8 AV	54.0	-7.2	2.01 V	299	21.2	25.6

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT40)	<b>Channel</b>	CH 110 : 5550 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5550.00	114.6 PK			2.81 H	102	100.2	14.4
2	*5550.00	100.2 AV			2.81 H	102	85.8	14.4
3	11100.00	56.4 PK	74.0	-17.6	2.03 H	305	30.2	26.2
4	11100.00	43.5 AV	54.0	-10.5	2.03 H	305	17.3	26.2

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5550.00	110.8 PK			1.85 V	6	96.4	14.4
2	*5550.00	108.9 AV			1.85 V	6	94.5	14.4
3	11100.00	56.7 PK	74.0	-17.3	2.22 V	185	30.5	26.2
4	11100.00	42.9 AV	54.0	-11.1	2.22 V	185	16.7	26.2

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.



<b>RF Mode</b>	802.11be (EHT40)	<b>Channel</b>	CH 134 : 5670 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5670.00	112.7 PK			2.94 H	89	98.8	13.9
2	*5670.00	100.3 AV			2.94 H	89	86.4	13.9
3	#5725.00	66.3 PK	68.2	-1.9	2.94 H	89	52.5	13.8
4	11340.00	62.8 PK	74.0	-11.2	2.18 H	130	36.0	26.8
5	11340.00	49.3 AV	54.0	-4.7	2.18 H	130	22.5	26.8

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5670.00	109.2 PK			1.81 V	11	95.3	13.9
2	*5670.00	96.8 AV			1.81 V	11	82.9	13.9
3	#5725.00	64.0 PK	68.2	-4.2	1.81 V	11	50.2	13.8
4	11340.00	62.6 PK	74.0	-11.4	2.36 V	306	35.8	26.8
5	11340.00	48.4 AV	54.0	-5.6	2.36 V	306	21.6	26.8

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # ": The radiated frequency is out of the restricted band.





<b>RF Mode</b>	802.11be (EHT40)	<b>Channel</b>	CH 142 : 5710 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5470.00	62.0 PK	68.2	-6.2	1.62 H	91	47.7	14.3
2	*5710.00	114.2 PK			1.62 H	91	100.4	13.8
3	*5710.00	99.9 AV			1.62 H	91	86.1	13.8
4	11420.00	63.8 PK	74.0	-10.2	2.03 H	135	36.9	26.9
5	11420.00	49.7 AV	54.0	-4.3	2.03 H	135	22.8	26.9

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5470.00	61.2 PK	68.2	-7.0	1.77 V	43	46.9	14.3
2	*5710.00	111.3 PK			1.77 V	43	97.5	13.8
3	*5710.00	99.4 AV			1.77 V	43	85.6	13.8
4	11420.00	62.5 PK	74.0	-11.5	2.17 V	287	35.6	26.9
5	11420.00	48.8 AV	54.0	-5.2	2.17 V	287	21.9	26.9

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT40)	<b>Channel</b>	CH 151 : 5755 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBUV)	Correction Factor (dB/m)
1	#5612.40	56.2 PK	68.2	-12.0	2.07 H	198	42.3	13.9
2	*5755.00	114.6 PK			2.07 H	198	100.7	13.9
3	*5755.00	103.2 AV			2.07 H	198	89.3	13.9
4	#5942.00	56.5 PK	68.2	-11.7	2.07 H	198	42.1	14.4
5	11510.00	62.2 PK	74.0	-11.8	2.58 H	262	34.5	27.7
6	11510.00	47.9 AV	54.0	-6.1	2.58 H	262	20.2	27.7

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBUV)	Correction Factor (dB/m)
1	#5649.60	57.1 PK	68.2	-11.1	2.59 V	144	43.3	13.8
2	*5755.00	111.4 PK			2.59 V	144	97.5	13.9
3	*5755.00	99.8 AV			2.59 V	144	85.9	13.9
4	#5986.80	57.1 PK	68.2	-11.1	2.59 V	144	42.6	14.5
5	11510.00	61.6 PK	74.0	-12.4	2.46 V	53	33.9	27.7
6	11510.00	47.3 AV	54.0	-6.7	2.46 V	53	19.6	27.7

**Remarks:**

1. Emission Level(dBUV/m) = Raw Value(dBUV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT40)	<b>Channel</b>	CH 159 : 5795 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5627.20	55.9 PK	68.2	-12.3	2.07 H	194	42.0	13.9
2	*5795.00	115.0 PK			2.07 H	194	101.2	13.8
3	*5795.00	103.3 AV			2.07 H	194	89.5	13.8
4	#5958.40	57.6 PK	68.2	-10.6	2.07 H	194	43.1	14.5
5	11590.00	61.3 PK	74.0	-12.7	2.59 H	258	34.0	27.3
6	11590.00	47.0 AV	54.0	-7.0	2.59 H	258	19.7	27.3

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5629.60	55.3 PK	68.2	-12.9	2.59 V	140	41.4	13.9
2	*5795.00	111.9 PK			2.59 V	140	98.1	13.8
3	*5795.00	100.5 AV			2.59 V	140	86.7	13.8
4	#5996.40	56.6 PK	68.2	-11.6	2.59 V	140	42.1	14.5
5	11590.00	60.7 PK	74.0	-13.3	2.46 V	49	33.4	27.3
6	11590.00	46.4 AV	54.0	-7.6	2.46 V	49	19.1	27.3

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT80)	<b>Channel</b>	CH 42 : 5210 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	72.3 PK	74.0	-1.7	2.31 H	94	59.0	13.3
2	5150.00	49.0 AV	54.0	-5.0	2.31 H	94	35.7	13.3
3	*5210.00	107.7 PK			2.31 H	94	94.0	13.7
4	*5210.00	96.0 AV			2.31 H	94	82.3	13.7
5	5350.00	65.4 PK	74.0	-8.6	2.31 H	94	51.1	14.3
6	5350.00	45.3 AV	54.0	-8.7	2.31 H	94	31.0	14.3
7	#10420.00	61.8 PK	68.2	-6.4	2.49 H	149	37.7	24.1

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	71.3 PK	74.0	-2.7	1.74 V	156	58.0	13.3
2	5150.00	47.2 AV	54.0	-6.8	1.74 V	156	33.9	13.3
3	*5210.00	105.0 PK			1.74 V	156	91.3	13.7
4	*5210.00	92.6 AV			1.74 V	156	78.9	13.7
5	5350.00	61.7 PK	74.0	-12.3	1.74 V	156	47.4	14.3
6	5350.00	43.4 AV	54.0	-10.6	1.74 V	156	29.1	14.3
7	#10420.00	61.3 PK	68.2	-6.9	1.33 V	181	37.2	24.1

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT80)	<b>Channel</b>	CH 58 : 5290 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	59.0 PK	74.0	-15.0	3.04 H	266	45.7	13.3
2	5150.00	42.8 AV	54.0	-11.2	3.04 H	266	29.5	13.3
3	*5290.00	109.6 PK			3.04 H	266	95.3	14.3
4	*5290.00	97.8 AV			3.04 H	266	83.5	14.3
5	5350.00	71.2 PK	74.0	-2.8	3.04 H	266	56.9	14.3
6	5350.00	52.0 AV	54.0	-2.0	3.04 H	266	37.7	14.3
7	#10580.00	61.1 PK	68.2	-7.1	3.21 H	314	36.9	24.2

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	56.9 PK	74.0	-17.1	2.46 V	321	43.6	13.3
2	5150.00	41.7 AV	54.0	-12.3	2.46 V	321	28.4	13.3
3	*5290.00	105.6 PK			2.46 V	321	91.3	14.3
4	*5290.00	93.1 AV			2.46 V	321	78.8	14.3
5	5350.00	66.2 PK	74.0	-7.8	2.46 V	321	51.9	14.3
6	5350.00	49.7 AV	54.0	-4.3	2.46 V	321	35.4	14.3
7	#10580.00	60.5 PK	68.2	-7.7	2.75 V	301	36.3	24.2

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT80)	<b>Channel</b>	CH 106 : 5530 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	65.3 PK	74.0	-8.7	1.70 H	256	51.0	14.3
2	5460.00	47.9 AV	54.0	-6.1	1.70 H	256	33.6	14.3
3	#5470.00	66.3 PK	68.2	-1.9	1.70 H	256	52.0	14.3
4	*5530.00	105.4 PK			1.70 H	256	91.0	14.4
5	*5530.00	93.7 AV			1.70 H	256	79.3	14.4
6	11060.00	63.0 PK	74.0	-11.0	1.92 H	136	37.1	25.9
7	11060.00	48.5 AV	54.0	-5.5	1.92 H	136	22.6	25.9

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	64.1 PK	74.0	-9.9	1.71 V	13	49.8	14.3
2	5460.00	47.7 AV	54.0	-6.3	1.71 V	13	33.4	14.3
3	#5470.00	65.3 PK	68.2	-2.9	1.71 V	13	51.0	14.3
4	*5530.00	104.0 PK			1.71 V	13	89.6	14.4
5	*5530.00	92.2 AV			1.71 V	13	77.8	14.4
6	11060.00	62.4 PK	74.0	-11.6	2.10 V	321	36.5	25.9
7	11060.00	47.6 AV	54.0	-6.4	2.10 V	321	21.7	25.9

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT80)	<b>Channel</b>	CH 122 : 5610 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5610.00	108.5 PK			2.10 H	95	94.6	13.9
2	*5610.00	96.5 AV			2.10 H	95	82.6	13.9
3	#5725.00	66.5 PK	68.2	-1.7	2.27 H	84	52.7	13.8
4	11220.00	63.1 PK	74.0	-10.9	1.84 H	135	36.5	26.6
5	11220.00	48.4 AV	54.0	-5.6	1.84 H	135	21.8	26.6

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5610.00	105.9 PK			1.55 V	6	92.0	13.9
2	*5610.00	94.4 AV			1.55 V	6	80.5	13.9
3	#5725.00	62.8 PK	68.2	-5.4	1.55 V	6	49.0	13.8
4	11220.00	62.3 PK	74.0	-11.7	2.15 V	311	35.7	26.6
5	11220.00	47.5 AV	54.0	-6.5	2.15 V	311	20.9	26.6

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT80)	<b>Channel</b>	CH 138 : 5690 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBUV)	Correction Factor (dB/m)
1	#5470.00	63.8 PK	68.2	-4.4	1.49 H	91	49.5	14.3
2	*5690.00	110.0 PK			1.49 H	91	96.2	13.8
3	*5690.00	97.1 AV			1.49 H	91	83.3	13.8
4	#5850.00	63.7 PK	68.2	-4.5	1.49 H	91	49.7	14.0
5	11380.00	63.7 PK	74.0	-10.3	1.98 H	157	36.9	26.8
6	11380.00	49.7 AV	54.0	-4.3	1.98 H	157	22.9	26.8

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBUV/m)	Limit (dBUV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBUV)	Correction Factor (dB/m)
1	#5470.00	60.3 PK	68.2	-7.9	2.01 V	37	46.0	14.3
2	*5690.00	107.5 PK			2.01 V	37	93.7	13.8
3	*5690.00	96.1 AV			2.01 V	37	82.3	13.8
4	#5850.00	61.4 PK	68.2	-6.8	2.01 V	37	47.4	14.0
5	11380.00	62.6 PK	74.0	-11.4	1.88 V	306	35.8	26.8
6	11380.00	48.7 AV	54.0	-5.3	1.88 V	306	21.9	26.8

**Remarks:**

1. Emission Level(dBUV/m) = Raw Value(dBUV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.





<b>RF Mode</b>	802.11be (EHT80)	<b>Channel</b>	CH 155 : 5775 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5646.80	66.7 PK	68.2	-1.5	2.15 H	193	52.9	13.8
2	*5775.00	111.2 PK			2.15 H	193	97.4	13.8
3	*5775.00	99.5 AV			2.15 H	193	85.7	13.8
4	#5928.80	61.5 PK	68.2	-6.7	2.15 H	193	47.2	14.3
5	11550.00	62.3 PK	74.0	-11.7	2.67 H	259	34.8	27.5
6	11550.00	48.0 AV	54.0	-6.0	2.67 H	259	20.5	27.5

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5648.40	64.6 PK	68.2	-3.6	2.67 V	139	50.8	13.8
2	*5775.00	108.0 PK			2.67 V	139	94.2	13.8
3	*5775.00	95.7 AV			2.67 V	139	81.9	13.8
4	#5940.40	58.6 PK	68.2	-9.6	2.67 V	139	44.2	14.4
5	11550.00	61.7 PK	74.0	-12.3	2.54 V	48	34.2	27.5
6	11550.00	47.4 AV	54.0	-6.6	2.54 V	48	19.9	27.5

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT160)	<b>Channel</b>	CH 50 : 5250 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	72.4 PK	74.0	-1.6	2.20 H	265	59.1	13.3
2	5150.00	51.8 AV	54.0	-2.2	2.20 H	265	38.5	13.3
3	*5250.00	102.4 PK			2.20 H	265	88.5	13.9
4	*5250.00	90.0 AV			2.20 H	265	76.1	13.9
5	5350.00	68.0 PK	74.0	-6.0	2.20 H	265	53.7	14.3
6	5350.00	50.8 AV	54.0	-3.2	2.20 H	265	36.5	14.3
7	#10500.00	62.4 PK	68.2	-5.8	2.38 H	320	38.2	24.2

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	62.6 PK	74.0	-11.4	1.63 V	327	49.3	13.3
2	5150.00	48.5 AV	54.0	-5.5	1.63 V	327	35.2	13.3
3	*5250.00	99.9 PK			1.63 V	327	86.0	13.9
4	*5250.00	87.6 AV			1.63 V	327	73.7	13.9
5	5350.00	67.3 PK	74.0	-6.7	1.63 V	327	53.0	14.3
6	5350.00	50.0 AV	54.0	-4.0	1.63 V	327	35.7	14.3
7	#10500.00	61.9 PK	68.2	-6.3	1.22 V	352	37.7	24.2

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT160)	<b>Channel</b>	CH 114 : 5570 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	65.6 PK	74.0	-8.4	1.68 H	263	51.3	14.3
2	5460.00	47.6 AV	54.0	-6.4	1.68 H	263	33.3	14.3
3	#5470.00	59.5 PK	68.2	-8.7	1.68 H	263	45.2	14.3
4	*5570.00	101.7 PK			1.68 H	263	87.5	14.2
5	*5570.00	89.2 AV			1.68 H	263	75.0	14.2
6	#5725.00	66.6 PK	68.2	-1.6	1.68 H	263	52.8	13.8
7	11140.00	63.3 PK	74.0	-10.7	1.95 H	154	36.9	26.4
8	11140.00	48.9 AV	54.0	-5.1	1.95 H	154	22.5	26.4

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5460.00	64.7 PK	74.0	-9.3	1.50 V	292	50.4	14.3
2	5460.00	48.3 AV	54.0	-5.7	1.50 V	292	34.0	14.3
3	#5470.00	61.7 PK	68.2	-6.5	1.50 V	292	47.4	14.3
4	*5570.00	97.5 PK			1.50 V	292	83.3	14.2
5	*5570.00	85.5 AV			1.50 V	292	71.3	14.2
6	#5725.00	62.8 PK	68.2	-5.4	1.50 V	292	49.0	13.8
7	11140.00	62.2 PK	74.0	-11.8	2.15 V	333	35.8	26.4
8	11140.00	48.1 AV	54.0	-5.9	2.15 V	333	21.7	26.4

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20) 26-tone RU	<b>Channel</b>	CH 36 : 5180 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	62.0 PK	74.0	-12.0	3.14 H	60	48.7	13.3
2	5150.00	48.3 AV	54.0	-5.7	3.14 H	60	35.0	13.3
3	*5180.00	111.5 PK			3.14 H	60	98.1	13.4
4	*5180.00	99.7 AV			3.14 H	60	86.3	13.4
5	#10360.00	60.6 PK	68.2	-7.6	1.87 H	219	36.6	24.0

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	62.3 PK	74.0	-11.7	1.68 V	21	49.0	13.3
2	5150.00	48.3 AV	54.0	-5.7	1.68 V	21	35.0	13.3
3	*5180.00	110.2 PK			1.68 V	21	96.8	13.4
4	*5180.00	98.6 AV			1.68 V	21	85.2	13.4
5	#10360.00	59.8 PK	68.2	-8.4	2.66 V	194	35.8	24.0

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20) 26-tone RU	<b>Channel</b>	CH 40 : 5200 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5200.00	112.4 PK			1.13 H	95	98.8	13.6
2	*5200.00	99.9 AV			1.13 H	95	86.3	13.6
3	#10400.00	60.6 PK	68.2	-7.6	1.68 H	274	36.5	24.1

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5200.00	109.1 PK			1.84 V	356	95.5	13.6
2	*5200.00	98.5 AV			1.84 V	356	84.9	13.6
3	#10400.00	59.7 PK	68.2	-8.5	2.34 V	306	35.6	24.1

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # ": The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20) 26-tone RU	<b>Channel</b>	CH 48 : 5240 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5240.00	112.2 PK			2.10 H	96	98.4	13.8
2	*5240.00	101.1 AV			2.10 H	96	87.3	13.8
3	5350.00	65.5 PK	74.0	-8.5	2.10 H	96	51.2	14.3
4	5350.00	51.1 AV	54.0	-2.9	2.10 H	96	36.8	14.3
5	#10480.00	60.7 PK	68.2	-7.5	1.82 H	225	36.5	24.2

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5240.00	111.0 PK			2.65 V	36	97.2	13.8
2	*5240.00	99.0 AV			2.65 V	36	85.2	13.8
3	5350.00	65.6 PK	74.0	-8.4	2.65 V	36	51.3	14.3
4	5350.00	51.1 AV	54.0	-2.9	2.65 V	36	36.8	14.3
5	#10480.00	59.8 PK	68.2	-8.4	2.55 V	311	35.6	24.2

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20) 26-tone RU	<b>Channel</b>	CH 52 : 5260 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	62.4 PK	74.0	-11.6	1.88 H	253	49.1	13.3
2	5150.00	48.4 AV	54.0	-5.6	1.88 H	253	35.1	13.3
3	*5260.00	113.0 PK			1.88 H	253	98.9	14.1
4	*5260.00	101.2 AV			1.88 H	253	87.1	14.1
5	#10520.00	61.1 PK	68.2	-7.1	2.55 H	157	36.8	24.3

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	60.9 PK	74.0	-13.1	1.97 V	25	47.6	13.3
2	5150.00	50.1 AV	54.0	-3.9	1.97 V	25	36.8	13.3
3	*5260.00	111.2 PK			1.97 V	25	97.1	14.1
4	*5260.00	99.5 AV			1.97 V	25	85.4	14.1
5	#10520.00	60.0 PK	68.2	-8.2	2.73 V	222	35.7	24.3

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20) 26-tone RU	<b>Channel</b>	CH 60 : 5300 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5300.00	113.1 PK			2.02 H	262	98.7	14.4
2	*5300.00	102.2 AV			2.02 H	262	87.8	14.4
3	10600.00	61.2 PK	74.0	-12.8	2.58 H	164	36.9	24.3
4	10600.00	47.1 AV	54.0	-6.9	2.58 H	164	22.8	24.3

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5300.00	111.4 PK			1.80 V	346	97.0	14.4
2	*5300.00	100.2 AV			1.80 V	346	85.8	14.4
3	10600.00	60.0 PK	74.0	-14.0	1.68 V	251	35.7	24.3
4	10600.00	46.1 AV	54.0	-7.9	1.68 V	251	21.8	24.3

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.





<b>RF Mode</b>	802.11be (EHT20) 26-tone RU	<b>Channel</b>	CH 64 : 5320 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5320.00	116.1 PK			1.70 H	261	101.7	14.4
2	*5320.00	102.2 AV			1.70 H	261	87.8	14.4
3	5350.00	61.5 PK	74.0	-12.5	1.70 H	261	47.2	14.3
4	5350.00	48.2 AV	54.0	-5.8	1.70 H	261	33.9	14.3
5	10640.00	62.0 PK	74.0	-12.0	2.57 H	166	37.2	24.8
6	10640.00	47.8 AV	54.0	-6.2	2.57 H	166	23.0	24.8

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5320.00	114.3 PK			1.49 V	350	99.9	14.4
2	*5320.00	101.0 AV			1.49 V	350	86.6	14.4
3	5350.00	61.4 PK	74.0	-12.6	1.49 V	350	47.1	14.3
4	5350.00	47.8 AV	54.0	-6.2	1.49 V	350	33.5	14.3
5	10640.00	61.0 PK	74.0	-13.0	1.95 V	294	36.2	24.8
6	10640.00	46.9 AV	54.0	-7.1	1.95 V	294	22.1	24.8

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.

<b>RF Mode</b>	802.11be (EHT20) 26-tone RU	<b>Channel</b>	CH 100 : 5500 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5350.00	61.9 PK	74.0	-12.1	1.69 H	269	47.6	14.3
2	5350.00	48.5 AV	54.0	-5.5	1.69 H	269	34.2	14.3
3	*5500.00	112.4 PK			1.69 H	269	98.1	14.3
4	*5500.00	100.8 AV			1.69 H	269	86.5	14.3
5	11000.00	61.5 PK	74.0	-12.5	1.68 H	257	36.1	25.4
6	11000.00	47.7 AV	54.0	-6.3	1.68 H	257	22.3	25.4

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5350.00	61.0 PK	74.0	-13.0	1.50 V	354	46.8	14.2
2	5350.00	48.1 AV	54.0	-5.9	1.50 V	354	33.9	14.2
3	*5500.00	110.3 PK			1.50 V	354	96.1	14.2
4	*5500.00	98.5 AV			1.50 V	354	84.3	14.2
5	11000.00	60.6 PK	74.0	-13.4	2.94 V	305	35.3	25.3
6	11000.00	46.7 AV	54.0	-7.3	2.94 V	305	21.4	25.3

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.



<b>RF Mode</b>	802.11be (EHT20) 26-tone RU	<b>Channel</b>	CH 116 : 5580 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5580.00	109.5 PK			2.34 H	267	95.5	14.0
2	*5580.00	99.1 AV			2.34 H	267	85.1	14.0
3	11160.00	62.4 PK	74.0	-11.6	1.67 H	247	36.1	26.3
4	11160.00	48.4 AV	54.0	-5.6	1.67 H	247	22.1	26.3

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5580.00	107.8 PK			1.78 V	358	93.8	14.0
2	*5580.00	97.4 AV			1.78 V	358	83.4	14.0
3	11160.00	61.2 PK	74.0	-12.8	2.69 V	311	34.9	26.3
4	11160.00	47.1 AV	54.0	-6.9	2.69 V	311	20.8	26.3

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.

<b>RF Mode</b>	802.11be (EHT20) 26-tone RU	<b>Channel</b>	CH 140 : 5700 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5700.00	110.6 PK			1.29 H	266	97.0	13.6
2	*5700.00	99.5 AV			1.29 H	266	85.9	13.6
3	#5725.00	61.7 PK	68.2	-6.5	1.29 H	266	48.0	13.7
4	11400.00	63.1 PK	74.0	-10.9	2.67 H	298	36.5	26.6
5	11400.00	49.0 AV	54.0	-5.0	2.67 H	298	22.4	26.6

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5700.00	110.1 PK			2.75 V	28	96.5	13.6
2	*5700.00	98.9 AV			2.75 V	28	85.3	13.6
3	#5725.00	60.6 PK	68.2	-7.6	2.75 V	28	46.9	13.7
4	11400.00	62.2 PK	74.0	-11.8	1.64 V	302	35.6	26.6
5	11400.00	48.0 AV	54.0	-6.0	1.64 V	302	21.4	26.6

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20) 26-tone RU	<b>Channel</b>	CH 144 : 5720 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5470.00	62.8 PK	68.2	-5.4	1.48 H	105	48.5	14.3
2	*5720.00	113.3 PK			1.48 H	105	99.4	13.9
3	*5720.00	101.2 AV			1.48 H	105	87.3	13.9
4	11440.00	63.9 PK	74.0	-10.1	1.88 H	264	36.7	27.2
5	11440.00	49.9 AV	54.0	-4.1	1.88 H	264	22.7	27.2

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5470.00	61.8 PK	68.2	-6.4	1.50 V	20	47.5	14.3
2	*5720.00	112.3 PK			1.50 V	20	98.4	13.9
3	*5720.00	99.7 AV			1.50 V	20	85.8	13.9
4	11440.00	62.4 PK	74.0	-11.6	2.64 V	302	35.2	27.2
5	11440.00	48.5 AV	54.0	-5.5	2.64 V	302	21.3	27.2

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20) 26-tone RU	<b>Channel</b>	CH 149 : 5745 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5650.34	59.3 PK	68.2	-8.9	2.09 H	101	45.5	13.8
2	*5745.00	121.4 PK			2.09 H	101	107.6	13.8
3	*5745.00	111.0 AV			2.09 H	101	97.2	13.8
4	#5933.27	60.8 PK	68.2	-7.4	2.09 H	101	46.4	14.4
5	11490.00	64.4 PK	74.0	-9.6	2.65 H	186	36.8	27.6
6	11490.00	50.3 AV	54.0	-3.7	2.65 H	186	22.7	27.6

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5618.00	55.0 PK	68.2	-13.2	1.42 V	15	41.1	13.9
2	*5745.00	120.5 PK			1.42 V	15	106.7	13.8
3	*5745.00	108.5 AV			1.42 V	15	94.7	13.8
4	#5958.80	56.1 PK	68.2	-12.1	1.42 V	15	41.6	14.5
5	11490.00	63.2 PK	74.0	-10.8	1.73 V	299	35.6	27.6
6	11490.00	49.3 AV	54.0	-4.7	1.73 V	299	21.7	27.6

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20) 26-tone RU	<b>Channel</b>	CH 157 : 5785 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5610.00	55.2 PK	68.2	-13.0	2.91 H	99	41.3	13.9
2	*5785.00	121.1 PK			2.91 H	99	107.4	13.7
3	*5785.00	109.6 AV			2.91 H	99	95.9	13.7
4	#5935.00	56.8 PK	68.2	-11.4	2.91 H	99	42.4	14.4
5	11570.00	64.1 PK	74.0	-9.9	2.67 H	168	36.7	27.4
6	11570.00	50.2 AV	54.0	-3.8	2.67 H	168	22.8	27.4

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5605.60	54.3 PK	68.2	-13.9	3.31 V	59	40.4	13.9
2	*5785.00	119.1 PK			3.31 V	59	105.4	13.7
3	*5785.00	107.6 AV			3.31 V	59	93.9	13.7
4	#5973.20	55.8 PK	68.2	-12.4	3.31 V	59	41.3	14.5
5	11570.00	62.6 PK	74.0	-11.4	1.67 V	258	35.2	27.4
6	11570.00	49.0 AV	54.0	-5.0	1.67 V	258	21.6	27.4

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.

<b>RF Mode</b>	802.11be (EHT20) 26-tone RU	<b>Channel</b>	CH 165 : 5825 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5634.00	53.0 PK	68.2	-15.2	3.35 H	101	39.1	13.9
2	*5825.00	124.1 PK			3.35 H	101	110.2	13.9
3	*5825.00	112.1 AV			3.35 H	101	98.2	13.9
4	#5949.00	55.9 PK	68.2	-12.3	3.35 H	101	41.5	14.4
5	11650.00	37.2 PK	74.0	-36.8	2.75 H	176	9.5	27.7
6	11650.00	23.1 AV	54.0	-30.9	2.75 H	176	-4.6	27.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5646.80	55.0 PK	68.2	-13.2	N/A V	N/A	41.2	13.8
2	*5825.00	120.8 PK			1.65 V	20	106.9	13.9
3	*5825.00	109.6 AV			1.65 V	20	95.7	13.9
4	#5946.00	56.1 PK	68.2	-12.1	N/A V	N/A	41.7	14.4
5	11650.00	63.3 PK	74.0	-10.7	2.84 V	176	35.6	27.7
6	11650.00	49.4 AV	54.0	-4.6	2.84 V	176	21.7	27.7

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.





<b>RF Mode</b>	802.11be (EHT20) 52-tone RU	<b>Channel</b>	CH 36 : 5180 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	61.7 PK	74.0	-12.3	1.65 H	41	48.4	13.3
2	5150.00	48.3 AV	54.0	-5.7	1.65 H	41	35.0	13.3
3	*5180.00	112.8 PK			1.65 H	41	99.4	13.4
4	*5180.00	101.4 AV			1.65 H	41	88.0	13.4
5	#10360.00	60.7 PK	68.2	-7.5	1.88 H	258	36.7	24.0

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	61.9 PK	74.0	-12.1	3.17 V	76	48.6	13.3
2	5150.00	48.5 AV	54.0	-5.5	3.17 V	76	35.2	13.3
3	*5180.00	108.9 PK			3.17 V	76	95.5	13.4
4	*5180.00	98.2 AV			3.17 V	76	84.8	13.4
5	#10360.00	59.8 PK	68.2	-8.4	2.41 V	299	35.8	24.0

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20) 52-tone RU	<b>Channel</b>	CH 40 : 5200 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5200.00	113.4 PK			1.78 H	93	99.8	13.6
2	*5200.00	101.4 AV			1.78 H	93	87.8	13.6
3	#10400.00	60.7 PK	68.2	-7.5	1.75 H	268	36.6	24.1

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5200.00	110.1 PK			2.57 V	148	96.5	13.6
2	*5200.00	99.2 AV			2.57 V	148	85.6	13.6
3	#10400.00	59.7 PK	68.2	-8.5	2.22 V	311	35.6	24.1

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20) 52-tone RU	<b>Channel</b>	CH 48 : 5240 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5240.00	114.5 PK			1.48 H	92	100.7	13.8
2	*5240.00	102.7 AV			1.48 H	92	88.9	13.8
3	5350.00	62.5 PK	74.0	-11.5	1.48 H	92	48.2	14.3
4	5350.00	47.8 AV	54.0	-6.2	1.48 H	92	33.5	14.3
5	#10480.00	61.0 PK	68.2	-7.2	1.78 H	259	36.8	24.2

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5240.00	112.9 PK			1.74 V	347	99.1	13.8
2	*5240.00	101.5 AV			1.74 V	347	87.7	13.8
3	5350.00	61.9 PK	74.0	-12.1	1.74 V	347	47.6	14.3
4	5350.00	48.3 AV	54.0	-5.7	1.74 V	347	34.0	14.3
5	#10480.00	60.0 PK	68.2	-8.2	2.27 V	274	35.8	24.2

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.

<b>RF Mode</b>	802.11be (EHT20) 52-tone RU	<b>Channel</b>	CH 52 : 5260 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	61.6 PK	74.0	-12.4	2.05 H	257	48.3	13.3
2	5150.00	47.5 AV	54.0	-6.5	2.05 H	257	34.2	13.3
3	*5260.00	115.1 PK			2.05 H	257	101.0	14.1
4	*5260.00	102.8 AV			2.05 H	257	88.7	14.1
5	#10520.00	60.8 PK	68.2	-7.4	2.47 H	184	36.5	24.3

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	62.3 PK	74.0	-11.7	1.50 V	10	49.0	13.3
2	5150.00	48.3 AV	54.0	-5.7	1.50 V	10	35.0	13.3
3	*5260.00	112.7 PK			1.50 V	10	98.6	14.1
4	*5260.00	100.6 AV			1.50 V	10	86.5	14.1
5	#10520.00	59.9 PK	68.2	-8.3	2.26 V	267	35.6	24.3

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20) 52-tone RU	<b>Channel</b>	CH 60 : 5300 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5300.00	114.8 PK			2.01 H	259	100.4	14.4
2	*5300.00	104.5 AV			2.01 H	259	90.1	14.4
3	10600.00	60.9 PK	74.0	-13.1	1.94 H	305	36.6	24.3
4	10600.00	46.8 AV	54.0	-7.2	1.94 H	305	22.5	24.3

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5300.00	110.6 PK			2.53 V	8	96.2	14.4
2	*5300.00	99.6 AV			2.53 V	8	85.2	14.4
3	10600.00	59.9 PK	74.0	-14.1	2.68 V	314	35.6	24.3
4	10600.00	46.0 AV	54.0	-8.0	2.68 V	314	21.7	24.3

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.



<b>RF Mode</b>	802.11be (EHT20) 52-tone RU	<b>Channel</b>	CH 64 : 5320 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5320.00	116.9 PK			1.54 H	260	102.5	14.4
2	*5320.00	102.9 AV			1.54 H	260	88.5	14.4
3	5350.00	62.8 PK	74.0	-11.2	1.54 H	260	48.5	14.3
4	5350.00	48.5 AV	54.0	-5.5	1.54 H	260	34.2	14.3
5	10640.00	61.5 PK	74.0	-12.5	2.63 H	247	37.3	24.2
6	10640.00	47.3 AV	54.0	-6.7	2.63 H	247	23.1	24.2
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5320.00	115.4 PK			1.08 V	300	101.0	14.4
2	*5320.00	101.8 AV			1.08 V	300	87.4	14.4
3	5350.00	62.5 PK	74.0	-11.5	1.08 V	300	48.2	14.3
4	5350.00	48.0 AV	54.0	-6.0	1.08 V	300	33.7	14.3
5	10640.00	61.1 PK	74.0	-12.9	2.64 V	321	36.3	24.8
6	10640.00	47.2 AV	54.0	-6.8	2.64 V	321	22.4	24.8

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.

<b>RF Mode</b>	802.11be (EHT20) 52-tone RU	<b>Channel</b>	CH 100 : 5500 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5350.00	62.8 PK	74.0	-11.2	3.27 H	269	48.6	14.2
2	5350.00	48.7 AV	54.0	-5.3	3.27 H	269	34.5	14.2
3	*5500.00	114.6 PK			3.27 H	269	100.4	14.2
4	*5500.00	103.3 AV			3.27 H	269	89.1	14.2
5	11100.00	62.8 PK	74.0	-11.2	1.85 H	247	36.8	26.0
6	11100.00	48.7 AV	54.0	-5.3	1.85 H	247	22.7	26.0

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5350.00	62.5 PK	74.0	-11.5	1.63 V	358	48.3	14.2
2	5350.00	48.7 AV	54.0	-5.3	1.63 V	358	34.5	14.2
3	*5500.00	112.7 PK			1.63 V	358	98.5	14.2
4	*5500.00	101.1 AV			1.63 V	358	86.9	14.2
5	11100.00	61.2 PK	74.0	-12.8	2.68 V	307	35.2	26.0
6	11100.00	47.4 AV	54.0	-6.6	2.68 V	307	21.4	26.0

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.



<b>RF Mode</b>	802.11be (EHT20) 52-tone RU	<b>Channel</b>	CH 116 : 5580 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5580.00	113.6 PK			1.67 H	264	99.6	14.0
2	*5580.00	101.8 AV			1.67 H	264	87.8	14.0
3	11160.00	63.1 PK	74.0	-10.9	1.94 H	264	36.8	26.3
4	11160.00	49.0 AV	54.0	-5.0	1.94 H	264	22.7	26.3

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5580.00	111.5 PK			1.50 V	292	97.5	14.0
2	*5580.00	99.4 AV			1.50 V	292	85.4	14.0
3	11160.00	60.2 PK	74.0	-13.8	2.45 V	299	35.7	24.5
4	11160.00	46.3 AV	54.0	-7.7	2.45 V	299	21.8	24.5

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.





<b>RF Mode</b>	802.11be (EHT20) 52-tone RU	<b>Channel</b>	CH 140 : 5700 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5700.00	113.2 PK			1.43 H	265	99.3	13.9
2	*5700.00	102.3 AV			1.43 H	265	88.4	13.9
3	#5725.00	61.9 PK	68.2	-6.3	1.43 H	265	48.1	13.8
4	11400.00	63.6 PK	74.0	-10.4	1.69 H	258	36.8	26.8
5	11400.00	49.7 AV	54.0	-4.3	1.69 H	258	22.9	26.8

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*5700.00	111.0 PK			1.53 V	360	97.1	13.9
2	*5700.00	99.3 AV			1.53 V	360	85.4	13.9
3	#5725.00	61.8 PK	68.2	-6.4	1.53 V	360	48.0	13.8
4	11400.00	62.5 PK	74.0	-11.5	2.66 V	301	35.7	26.8
5	11400.00	48.4 AV	54.0	-5.6	2.66 V	301	21.6	26.8

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20) 52-tone RU	<b>Channel</b>	CH 144 : 5720 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5470.00	61.8 PK	68.2	-6.4	1.84 V	3	47.5	14.3
2	*5720.00	114.2 PK			1.84 V	3	100.3	13.9
3	*5720.00	101.1 AV			1.84 V	3	87.2	13.9
4	11440.00	62.8 PK	74.0	-11.2	2.67 V	311	35.6	27.2
5	11440.00	48.9 AV	54.0	-5.1	2.67 V	311	21.7	27.2

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5470.00	62.5 PK	68.2	-5.7	1.58 H	222	48.2	14.3
2	*5720.00	113.0 PK			1.58 H	222	99.1	13.9
3	*5720.00	100.4 AV			1.58 H	222	86.5	13.9
4	11440.00	63.7 PK	74.0	-10.3	1.86 H	257	36.5	27.2
5	11440.00	49.6 AV	54.0	-4.4	1.86 H	257	22.4	27.2

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20) 52-tone RU	<b>Channel</b>	CH 149 : 5745 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5616.80	56.5 PK	68.2	-11.7	3.47 H	118	42.6	13.9
2	*5745.00	120.2 PK			3.47 H	118	106.4	13.8
3	*5745.00	108.8 AV			3.47 H	118	95.0	13.8
4	#5965.20	56.1 PK	68.2	-12.1	3.47 H	118	41.6	14.5
5	11490.00	64.1 PK	74.0	-9.9	2.84 H	175	36.5	27.6
6	11490.00	50.3 AV	54.0	-3.7	2.84 H	175	22.7	27.6

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5625.60	54.8 PK	68.2	-13.4	1.56 V	295	40.9	13.9
2	*5745.00	117.4 PK			1.56 V	295	103.6	13.8
3	*5745.00	106.4 AV			1.56 V	295	92.6	13.8
4	#5948.40	55.4 PK	68.2	-12.8	1.56 V	295	41.0	14.4
5	11490.00	63.2 PK	74.0	-10.8	1.84 V	237	35.6	27.6
6	11490.00	49.1 AV	54.0	-4.9	1.84 V	237	21.5	27.6

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20) 52-tone RU	<b>Channel</b>	CH 157 : 5785 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5600.40	55.5 PK	68.2	-12.7	2.90 H	170	41.6	13.9
2	*5785.00	121.1 PK			2.90 H	170	107.4	13.7
3	*5785.00	108.4 AV			2.90 H	170	94.7	13.7
4	#5962.80	56.7 PK	68.2	-11.5	2.90 H	170	42.2	14.5
5	11570.00	64.1 PK	74.0	-9.9	2.47 H	168	36.7	27.4
6	11570.00	50.0 AV	54.0	-4.0	2.47 H	168	22.6	27.4

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5635.20	55.0 PK	68.2	-13.2	3.02 V	251	41.1	13.9
2	*5785.00	119.6 PK			3.02 V	251	105.9	13.7
3	*5785.00	106.8 AV			3.02 V	251	93.1	13.7
4	#5942.40	55.9 PK	68.2	-12.3	3.02 V	251	41.5	14.4
5	11570.00	62.8 PK	74.0	-11.2	2.68 V	304	35.4	27.4
6	11570.00	49.0 AV	54.0	-5.0	2.68 V	304	21.6	27.4

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.

<b>RF Mode</b>	802.11be (EHT20) 52-tone RU	<b>Channel</b>	CH 165 : 5825 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5637.60	55.0 PK	68.2	-13.2	3.27 H	266	41.2	13.8
2	*5825.00	120.9 PK			3.27 H	266	107.0	13.9
3	*5825.00	110.2 AV			3.27 H	266	96.3	13.9
4	#5953.60	55.5 PK	68.2	-12.7	3.27 H	266	41.1	14.4
5	11650.00	64.4 PK	74.0	-9.6	2.67 H	159	36.7	27.7
6	11650.00	50.5 AV	54.0	-3.5	2.67 H	159	22.8	27.7

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#5630.40	55.0 PK	68.2	-13.2	1.98 V	0	41.1	13.9
2	*5825.00	117.4 PK			1.98 V	0	103.5	13.9
3	*5825.00	106.4 AV			1.98 V	0	92.5	13.9
4	#5947.20	56.3 PK	68.2	-11.9	1.98 V	0	41.9	14.4
5	11650.00	63.3 PK	74.0	-10.7	1.94 V	286	35.6	27.7
6	11650.00	49.1 AV	54.0	-4.9	1.94 V	286	21.4	27.7

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.



<b>RF Mode</b>	802.11be (EHT20) 106-tone RU	<b>Channel</b>	CH 36 : 5180 MHz
<b>Frequency Range</b>	1 GHz ~ 40 GHz	<b>Detector Function &amp; Bandwidth</b>	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	23°C, 71.3% RH
<b>Tested By</b>	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	63.8 PK	74.0	-10.2	2.09 H	256	50.5	13.3
2	5150.00	48.5 AV	54.0	-5.5	2.09 H	256	35.2	13.3
3	*5180.00	114.6 PK			2.09 H	256	101.2	13.4
4	*5180.00	102.2 AV			2.09 H	256	88.8	13.4
5	#10360.00	61.1 PK	68.2	-7.1	1.62 H	251	37.1	24.0

**Antenna Polarity & Test Distance : Vertical at 3 m**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	5150.00	60.9 PK	74.0	-13.1	1.50 V	44	47.6	13.3
2	5150.00	46.8 AV	54.0	-7.2	1.50 V	44	33.5	13.3
3	*5180.00	110.7 PK			1.50 V	44	97.3	13.4
4	*5180.00	97.9 AV			1.50 V	44	84.5	13.4
5	#10360.00	59.7 PK	68.2	-8.5	2.67 V	247	35.7	24.0

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* " : Fundamental frequency, the limit was restricted at the RF Output Power.
6. " # " : The radiated frequency is out of the restricted band.