

ELECTROMAGNETIC EMISSION COMPLIANCE REPORT FOR LOW-POWER, NON-LICENSED TRANSMITTER

Test Report No. : W17NR-D087
AGR No. : A17OA-122
Applicant : Remote Solution Co., Ltd.
Address : 92, Chogokri, Nammyun, Kimchon City, Kyungbuk, 740-871, South Korea
Manufacturer : Remote Solution Co., Ltd.
Address : 326-14, Apo-daero, Nam-myeon, Gimcheon-si, Gyeongsangbuk-do, Republic of Korea
Type of Equipment : Zigbee Module
FCC ID. : TX4MC85A00
Model Name : MC85A00
Serial number : N/A
Total page of Report : 6 pages (including this page)
Date of Incoming : November 20, 2017
Date of issue : November 30, 2017

SUMMARY

The equipment complies with the regulation; *FCC PART 15 SUBPART C Section 15.247*

This test report only contains the result of a single test of the sample supplied for the examination.

It is not a generally valid assessment of the features of the respective products of the mass-production.

Reviewed by: 
Ki-Hong, Nam / Asst, Chief Engineer
ONETECH Corp.

Approved by: 
Keun-Young, Choi / Vice President
ONETECH Corp.

CONTENTS**PAGE**

1. VERIFICATION OF COMPLIANCE	4
2. GENERAL INFORMATION	5
2.1 PRODUCT DESCRIPTION.....	5
2.2 ALTERNATIVE TYPE(S)/MODEL(S); ALSO COVERED BY THIS TEST REPORT.....	5
3. EUT MODIFICATIONS.....	5
4. RADIO FREQUENCY EXPOSURE	6
4.1 RF EXPOSURE LIMIT	6
4.2 EUT DESCRIPTION.....	6
4.3 TEST RESULT	6

Revision History

Issued Report No.	Issued Date	Revisions	Effect Section
W17NR-D087	November 30, 2017	Initial Issue	All

1. VERIFICATION OF COMPLIANCE

Applicant : Remote Solution Co., Ltd.
 Address : 92, Chogokri, Nammyun, Kimchon City, Kyungbuk, 740-871, South Korea
 Contact Person : Shin Sang Hyun / Researcher
 Telephone No. : +82-54-420-4517
 FCC ID : TX4MC85A00
 Model Name : MC85A00
 Brand Name : -
 Serial Number : N/A
 Date : November 30, 2017

EQUIPMENT CLASS	DTS – DIGITAL TRNSMISSION SYSTEM
E.U.T. DESCRIPTION	Zigbee Module
THIS REPORT CONCERNS	Original Grant
MEASUREMENT PROCEDURES	ANSI C63.10: 2013
TYPE OF EQUIPMENT TESTED	Pre-Production
KIND OF EQUIPMENT AUTHORIZATION REQUESTED	Certification
EQUIPMENT WILL BE OPERATED UNDER FCC RULES PART(S)	FCC PART 15 SUBPART C Section 15.247
Modifications on the Equipment to Achieve Compliance	None
Final Test was Conducted On	3 m, Semi Anechoic Chamber

-. The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

2. GENERAL INFORMATION

2.1 Product Description

The Remote Solution Co., Ltd., Model MC85A00 (referred to as the EUT in this report) is a Zigbee Module. The product specification described herein was obtained from product data sheet or user's manual.

Device Type	Zigbee Module
Temperature Range	-40 °C ~ 80 °C
Operating Frequency	2 405 MHz ~ 2 480 MHz
RF Output Power	-0.24 dBm
Number of Channel	16 Channel
Modulation Type	O-QPSK (Zigbee)
Antenna Type	PCB Pattern Antenna
Antenna Gain	2.55 dBi
List of each Osc. or crystal Freq.(Freq. >= 1 MHz)	32.768 kHz, 24 MHz

2.2 Alternative type(s)/model(s); also covered by this test report.

-. None

3. EUT MODIFICATIONS

-. None

4. RADIO FREQUENCY EXPOSURE

4.1 RF Exposure Limit

According to the FCC rule §1.1310, the limit for General Population/Uncontrolled exposure is 1 mW/cm² for the device operating 1 500 ~ 100 000 MHz.

4.2 EUT Description

Kind of EUT	Zigbee Module
Operating Frequency Band	<input type="checkbox"/> Wireless Microphone: 494.000 MHz ~ 501.000 MHz and 498.200 MHz ~ 505.200 MHz <input type="checkbox"/> WLAN: 2 412 MHz ~ 2 462 MHz <input type="checkbox"/> WLAN: 5 180 MHz ~ 5 320 MHz / 5 500 MHz ~ 5 700 MHz <input type="checkbox"/> WLAN: 5 745 MHz ~ 5 825 MHz <input type="checkbox"/> Bluetooth: 2 402 MHz ~ 2 480 MHz <input checked="" type="checkbox"/> Zigbee: 2 405 MHz ~ 2 480 MHz
Device Category	<input type="checkbox"/> Portable (< 20 cm separation) <input type="checkbox"/> Mobile (> 20 cm separation) <input checked="" type="checkbox"/> Others
Max. Output Power	-0.24 dBm
Used Antenna	PCB Pattern Antenna
Used Antenna Gain	2.55 dBi
Exposure Evaluation Applied	<input checked="" type="checkbox"/> MPE <input type="checkbox"/> SAR <input type="checkbox"/> N/A

4.3 Test Result

According to above equation, the following result was obtained.

Operating Mode	Target Power	Max tune up power		Antenna Gain		Safe Distance (cm)	Power Density (mW/cm ²) @ 20 cm Separation	Limit (mW/cm ²)
	W/tolerance (dBm)	(dBm)	(mW)	Log	Linear			
Zigbee	0.00 ± 0.50	0.50	1.12	2.55	1.80	0.40	0.000 4	1.00


Tested by: Hyung-Kwon, Oh / Assistant Manager