

# ELECTROMAGNETIC EMISSION COMPLIANCE REPORT FOR LOW-POWER, NON-LICENSED TRANSMITTER

**Test Report No.** : E124R-022  
**AGR No** : A122A-109  
**Applicant** : Remote Solution Co., Ltd.  
**Address** : 92, Chogok-ri, Nam-myun, Kimchon-city, Kyungbuk, 740-871, Korea  
**Manufacturer** : Remote Solution Co., Ltd.  
**Address** : 92, Chogok-ri, Nam-myun, Kimchon-city, Kyungbuk, 740-871, Korea  
**Type of Equipment** : IR&RF Remote  
**FCC ID.** : TX4RC10A  
**Model Name** : RC10A  
**Multiple Model Name** : XR3  
**Serial number** : None  
**Total page of Report** : 27 pages (including this page)  
**Date of Incoming** : April 06, 2012  
**Date of issue** : April 12, 2012

## SUMMARY

The equipment complies with the regulation; **FCC Part 15 Subpart C Section 15.249.**  
 This test report only contains the result of a single test of the sample supplied for the examination.  
 It is not a generally valid assessment of the features of the respective products of the mass-production.

Prepared by:   
 \_\_\_\_\_  
 Ki-Hong, Nam / Senior Engineer  
 ONETECH Corp.

Reviewed by:   
 \_\_\_\_\_  
 Y. K. Kwon / Exe. Managing Director  
 ONETECH Corp.

**CONTENTS**

	<b>PAGE</b>
<b>1. VERIFICATION OF COMPLIANCE .....</b>	<b>4</b>
<b>2. TEST SUMMARY .....</b>	<b>5</b>
2.1 TEST ITEMS AND RESULTS .....	5
2.2 ADDITIONS, DEVIATIONS, EXCLUSIONS FROM STANDARDS .....	5
2.3 RELATED SUBMITTAL(S) / GRANT(S) .....	5
2.4 PURPOSE OF THE TEST .....	5
2.5 TEST METHODOLOGY .....	5
2.6 TEST FACILITY .....	5
<b>3. GENERAL INFORMATION .....</b>	<b>6</b>
3.1 PRODUCT DESCRIPTION .....	6
3.2 MODEL DIFFERENCES .....	6
<b>4. EUT MODIFICATIONS .....</b>	<b>6</b>
<b>5. SYSTEM TEST CONFIGURATION .....</b>	<b>7</b>
5.1 JUSTIFICATION .....	7
5.2 PERIPHERAL EQUIPMENT .....	7
5.3 MODE OF OPERATION DURING THE TEST .....	7
5.4 CONFIGURATION OF TEST SYSTEM .....	7
5.5 ANTENNA REQUIREMENT .....	7
<b>6. PRELIMINARY TEST .....</b>	<b>8</b>
6.1 AC POWER LINE CONDUCTED EMISSIONS TESTS .....	8
6.2 GENERAL RADIATED EMISSIONS TESTS .....	8
<b>7. RADIATED EMISSION TEST .....</b>	<b>9</b>
7.1 TEST SET-UP .....	9
7.2 MEASUREMENT UNCERTAINTY .....	9
7.3 TEST EQUIPMENT USED .....	9
7.4 FINAL RESULT OF MEASUREMENT .....	10
7.4.1 <i>Field Strength of the Fundamental Frequency</i> .....	10
7.4.2 <i>Emissions Radiated Outside of the Specified Frequency Bands</i> .....	11
<b>8. 20 DB BANDWIDTH .....</b>	<b>25</b>
8.1 OPERATING ENVIRONMENT .....	25
8.2 TEST SET-UP .....	25
8.3 TEST EQUIPMENT USED .....	25
8.4 TEST DATA FOR BANDWIDTH .....	25

**Revision History**

Issue Report No.	Issued Date	Revisions	Effect Section
E124R-022	April 12, 2012	Initial Release	All

## 1. VERIFICATION OF COMPLIANCE

APPLICANT : Remote Solution Co., Ltd.  
 ADDRESS : 92, Chogok-ri, Nam-myun, Kimchon-city, Kyungbuk, 740-871, Korea  
 CONTACT PERSON : Mr. Dae-Gyu, Lim / Assistant Research Engineer  
 TELEPHONE NO : +82-54-420-4500  
 FCC ID : TX4RC10A  
 MODEL NAME : RC10A  
 BRAND NAME : N/A  
 SERIAL NUMBER : N/A  
 DATE : April 12, 2012

EQUIPMENT CLASS	<b>DXX – Low Power Communications Transmitter</b>
KIND OF EQUIPMENT	IR&RF Remote
THIS REPORT CONCERNS	Original Grant
MEASUREMENT PROCEDURES	ANSI C63.4: 2009
TYPE OF EQUIPMENT TESTED	Pre-Production
KIND OF EQUIPMENT AUTHORIZATION REQUESTED	Certification
EQUIPMENT WILL BE OPERATED UNDER FCC RULES PART(S)	FCC PART 15 SUBPART C Section 15.249
MODIFICATIONS ON THE EQUIPMENT TO ACHIEVE COMPLIANCE	No
FINAL TEST WAS CONDUCTED ON	3 m, semi anechoic chamber

-. The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

## 2. TEST SUMMARY

### 2.1 Test items and results

SECTION	TEST ITEMS	RESULTS
15.249 (a)	Field Strength of Emission	Met the Limit / PASS
15.249 (c)	Measurement distance	Met the Requirement / PASS
15.249 (d)	Emissions Radiated Outside of the Specified Frequency Band	Met the Limit / PASS
15.249 (e)	Radiated Emissions above 1 000 MHz	Met the Limit / PASS
15.209	Radiated Emission Limits, General Requirement	Met the Limit / PASS
15.207	Conducted Limits	N/A (See Note)
15.203	Antenna Requirement	Met the Requirement / PASS

Note: This test is not performed because the EUT is operated by DC battery.

### 2.2 Additions, deviations, exclusions from standards

No additions, deviations or exclusions have been made from standard.

### 2.3 Related Submittal(s) / Grant(s)

Original submittal only

### 2.4 Purpose of the test

To determine whether the equipment under test fulfills the requirements of the regulation stated in section 2.1.

### 2.5 Test Methodology

Radiated testing was performed according to the procedures in ANSI C63.4: 2009 at a distance of 3 m from EUT to the antenna.

### 2.6 Test Facility

The open area test site and conducted measurement facilities are located on at 301-14, Daessangryung-ri, Chowol-eup, Gwangju-si, Gyeonggi-do, 464-862, Korea. The Onetech Corp. has been accredited as a Conformity Assessment Body (CAB) with designation number KR0013.

### 3. GENERAL INFORMATION

#### 3.1 Product Description

The Remote Solution Co., Ltd., Model: RC10A (referred to as the EUT in this report) is an IR&RF Remote. Product specification information described herein was obtained from product data sheet or user's manual.

DEVICE TYPE	Portable Device
OPERATING FREQUENCY	2 405 MHz ~ 2 480 MHz
RATED RF OUTPUT POWER	0 dBm
ANTENNA TYPE	Inserted into the main board (Pattern Antenna)
MODULATION	O-QPSK
Tx DATA SPEED	250 kbps
USED RF CHIP	Maker: GreenPeak, Model Name: GP541
LIST OF EACH OSC. OR CRY. FREQ.(FREQ. >= 1 MHz)	16 MHz
RATED SUPPLY VOLTAGE	DC 3 V from a battery

#### 3.2 Model Differences

-. The following lists consist of the added model and their differences.

Model Name	Differences	Tested
RC10A	Basic Model	<input checked="" type="checkbox"/>
XR3	This model is identical to basic model except for model designation only according to buyer's request.	<input type="checkbox"/>

Note: 1. Applicant consigns only basic model to test. Therefore this test report just guarantees the units, which have been tested.

2. The Applicant/manufacturer is responsible for the compliance of all variants.

### 4. EUT MODIFICATIONS

-. None

## 5. SYSTEM TEST CONFIGURATION

### 5.1 Justification

This device was configured for testing in a typical way as a normal customer is supposed to be used. During the test, the following components were installed inside of the EUT.

DEVICE TYPE	MANUFACTURER	MODEL/PART NUMBER	FCC ID
Main Board	N/A	RS-Ver 0.05	N/A

### 5.2 Peripheral equipment

Defined as equipment needed for correct operation of the EUT, but not considered as tested: None

### 5.3 Mode of operation during the test

For the testing, software used to control the EUT for staying in continuous transmitting is programmed.

For final testing, the EUT was set at Low Channel (2 405 MHz), Middle Channel (2 450 MHz), and High Channel (2 480 MHz). To get a maximum emission levels from the EUT, the EUT was moved throughout the XY, XZ, and YZ planes and the worst case is “XY” axis.

### 5.4 Configuration of Test System

**Line Conducted Test** : It is not need to test this requirement, because the EUT shall be operated by DC battery.

**Radiated Emission Test** : Preliminary radiated emissions test were conducted using the procedure in ANSI C63.4: 2009 8.3.1.1 and 13.4.1 to determine the worse operating conditions. Final radiated emission tests were conducted at 3 m open area test site.

The turntable was rotated through 360 degrees and the EUT was tested by positioned three orthogonal planes to obtain the highest reading on the field strength meter. Once maximum reading was determined, the search antenna was raised and lowered in both vertical and horizontal polarization.

### 5.5 Antenna Requirement

According to section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

#### Antenna Construction:

The antenna of the EUT is a pattern antenna on the main board in the EUT, so no consideration of replacement by the user.

## 6. PRELIMINARY TEST

### 6.1 AC Power line Conducted Emissions Tests

During Preliminary Tests, the following operating mode was investigated

Operation Mode	The Worse operating condition (Please check one only)
It is not need to test this requirement, because the power of the EUT is supplied by battery.	

### 6.2 General Radiated Emissions Tests

During Preliminary Tests, the following operating modes were investigated

Operation Mode	The Worse operating condition (Please check one only)
TX Mode	X



## 7. RADIATED EMISSION TEST

### 7.1 Test set-up

The radiated emissions measurements were on the 3 m, semi anechoic chamber. The EUT and other support equipment were placed on a non-conductive turntable above the ground plane. The interconnecting cables from outside test site were inserted into ferrite clamps at the point where the cables reach the turntable.

The frequency spectrum from up to 25 GHz was scanned and emission levels maximized at each frequency recorded. The system was rotated 360°, and the antenna was varied in height between 1.0 m and 4.0 m in order to determine the maximum emission levels. This procedure was performed for both horizontal and vertical polarization of the receiving antenna.

Test set-up photos are included in appendix I.

### 7.2 Measurement uncertainty

Radiated emission electric field intensity, 0.15 MHz ~ 30 MHz : ± 2.61 dB

Radiated emission electric field intensity, 30 MHz ~ 300 MHz : ± 4.43 dB

Radiated emission electric field intensity, 300 MHz ~ 1 000 MHz : ± 3.80 dB

Radiated emission electric field intensity, 1 000 MHz ~ 3 000 MHz : ± 4.40 dB

Measurement uncertainty is calculated in accordance with CISPR 16-4-2. The measurement uncertainty is given with a confidence of 95 % with the coverage factor,  $k = 2$ .

### 7.3 Test equipment used

Model Number	Manufacturer	Description	Serial Number	Last Cal. (Interval)
□ - ESCI	Rohde & Schwarz	EMI Test Receiver	101012	Feb. 06, 2012 (1Y)
■ - ESU	Rohde & Schwarz	EMI Test Receiver	100261	SEP/11, 2012 (1Y)
□ - 8564E	HP	Spectrum Analyzer	3650A00756	Jun. 10, 2011 (1Y)
□ - FSP	Rohde & Schwarz	Spectrum Analyzer	100017	Mar 12, 2012(1Y)
■ - 310N	Sonoma Instrument	AMPLIFIER	312544	Oct 11, 2012(1Y)
■ - FSV30	Rohde & Schwarz	Signal Analyzer	101372	Aug. 29, 2011(1Y)
■ - SCU-18	Rohde & Schwarz	PRE-AMPLIFIER	10041	Dec 15, 2011 (1Y)
■ - MA240	HD GmbH	Antenna Master	N/A	N/A
■ - HD100	HD GmbH	Position Controller	N/A	N/A
■ - DS420S	HD GmbH	Turn Table	N/A	N/A
■ - HFH2-Z2	Rohde & Schwarz	Loop Antenna	889 285 / 26	Nov. 08, 2010(2Y)
■ - VULB9163	Schwarzbeck	TRILOG Broadband Antenna	VULB9163-202	May 27, 2010(2Y)
■ - BBHA9120D	Schwarzbeck	Horn Antenna	BBHA9120D294	Jun. 17, 2011 (2Y)
■ - BBHA9170	Schwarzbeck	Horn Antenna	BBHA9170178	Jun. 17, 2011 (2Y)

All test equipment used is calibrated on a regular basis.

## 7.4 Final Result of Measurement

### 7.4.1 Field Strength of the Fundamental Frequency


The following table shows the highest levels of radiated emissions on both polarizations of horizontal and vertical.

Humidity Level : 47 % R.H. Temperature: 22 °C  
 Limits apply to : FCC CFR 47, PART 15, SUBPART C, SECTION 15.249(a)  
 Result : PASSED BY -6.19 dB at 2 405.00 MHz

EUT : IR&RF Remote Date: April 10, 2012  
 Operating Condition : TX mode  
 Distance : 3 m

Channel	Radiated Emissions			Ant	Correction Factors			Total	FCC Limit	
	Carrier Freq. (MHz)	Amplitude (dBμV)	Detect Mode	Pol.	Antenna (dB/m)	Cable (dB)	Pre-Amp (dB)	Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
Low	2 405.00	102.22	Peak	H	27.15	5.02	43.10	91.29	113.98	-22.69
		98.72	Average	H				87.79	93.98	-6.19
		95.13	Peak	V				84.20	113.98	-29.78
		88.83	Average	V				77.90	93.98	-16.08
Middle	2 450.00	99.87	Peak	H	27.22	5.04	43.10	89.03	113.98	-24.95
		96.46	Average	H				85.62	93.98	-8.36
		92.38	Peak	V				81.54	113.98	-32.44
		88.52	Average	V				77.68	93.98	-16.30
High	2 480.00	100.06	Peak	H	27.28	5.06	43.10	89.30	113.98	-24.68
		95.58	Average	H				84.82	93.98	-9.16
		93.16	Peak	V				82.40	113.98	-31.58
		88.93	Average	V				78.17	93.98	-15.81

\*Remark: To get a maximum emission level from the EUT, the EUT was moved throughout the XY, XZ, and YZ planes, but the worst plane data were recorded in the report.



**Tested by: Chang-Uk, Jun / Engineer**

### 7.4.2 Emissions Radiated Outside of the Specified Frequency Bands

#### 7.4.2.1 Test Data for Harmonic


Humidity Level : 47 % R.H. Temperature: 22 °C  
 Limits apply to : FCC CFR 47, PART 15, SUBPART C, SECTION 15.249(a)  
 Result : PASSED BY -4.70 dB at 4 900.00 MHz

EUT : IR&RF Remote Date: April 10, 2012  
 Operating Condition : TX mode  
 Distance : 3 m

Channel	Frequency (MHz)	Reading (dBµV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	Pre-Amp (dB)	Total (dBµV/m)	Limits (dBµV/m)	Margin (dB)
Low	4 810.00*	66.75	Peak	H	31.14	6.90	42.80	61.99	73.98	-11.99
		52.74	Average	H				47.98	53.98	-6.00
		56.77	Peak	V				52.01	73.98	-21.97
		45.96	Average	V				41.20	53.98	-12.78
Other frequencies were not found up to 25 GHz.										
Middle	4 900.00*	64.52	Peak	H	31.22	6.93	42.80	59.87	73.98	-14.11
		53.93	Average	H				49.28	53.98	-4.70
		58.67	Peak	V				54.02	73.98	-19.96
		45.60	Average	V				40.95	53.98	-13.03
Other frequencies were not found up to 25 GHz.										
High	4 960.00*	62.73	Peak	H	31.30	6.97	42.80	58.20	73.98	-15.78
		51.74	Average	H				47.21	53.98	-6.77
		55.95	Peak	V				51.42	73.98	-22.56
		45.62	Average	V				41.09	53.98	-12.89
Other frequencies were not found up to 25 GHz.										

Tabulated test data for Restricted Band

Remark: "H": Horizontal, "V": Vertical, "\*" Frequency fall in restricted band



**Tested by: Chang-Uk, Jun / Engineer**

**7.4.2.2 Test Data for Frequency range: 30 MHz ~ 1 000 MHz**

Humidity Level : 45 % R.H. Temperature: 24 °C

Limits apply to : FCC CFR 47, PART 15, SUBPART C, SECTION 15.249 (d)



Result : PASSED BY -14.40 dB at 845.76 MHz at high channel

EUT : IR&RF Remote

Date: April 10, 2012

Detector : CISPR Quasi-Peak (6 dB Bandwidth: 120 kHz)


Operating condition : Low Channel



No.	FREQ [MHz]	READING PEAK [dBuV]	ANT FACTOR [dB]	LOSS [dB]	GAIN [dB]	RESULT [dBuV/m]	LIMIT [dBuV/m]	MARGIN [dB]	ANTENNA [cm]	TABLE [DEG]
----- Horizontal -----										
1	37.760	28.8	13.0	1.0	32.9	9.9	40.0	30.1	100	0
2	84.320	35.6	8.3	1.6	32.9	12.6	40.0	27.4	200	359
3	224.000	31.7	11.4	2.8	33.0	12.9	46.0	33.1	100	0
4	256.010	30.5	12.4	3.0	32.9	13.0	46.0	33	100	291
5	824.421	32.4	20.9	5.8	33.2	25.9	46.0	20.1	100	328
6	919.478	29.7	22.1	6.2	32.5	25.5	46.0	20.5	300	246
----- Vertical -----										
7	37.760	27.9	13.0	1.0	32.9	9.0	40.0	31	400	32
8	84.320	27.1	8.3	1.6	32.9	4.1	40.0	35.9	400	0
9	224.000	28.3	11.4	2.8	33.0	9.5	46.0	36.5	300	359
10	256.010	27.9	12.4	3.0	32.9	10.4	46.0	35.6	200	78
11	824.421	27.8	20.9	5.8	33.2	21.3	46.0	24.7	100	319
12	919.478	27.3	22.1	6.2	32.5	23.1	46.0	22.9	300	134


Remark: Margin (dB) = Limit – Result and Result = Reading Peak + Antenna Factor + Loss - Gain

Loss and Gain in above table means Cable Loss and Pre-amplifier gain.



**Tested by: Chang-Uk, Jun / Engineer**


Operating condition : Middle Channel



No.	FREQ [MHz]	READING PEAK [dBuV]	ANT FACTOR [dB]	LOSS [dB]	GAIN [dB]	RESULT [dBuV/m]	LIMIT [dBuV/m]	MARGIN [dB]	ANTENNA [cm]	TABLE [DEG]
----- Horizontal -----										
1	40.670	28.6	13.4	1.0	32.9	10.1	40.0	29.9	300	71
2	49.400	29.2	13.6	1.2	32.9	11.1	40.0	28.9	400	100
3	68.800	28.2	9.8	1.4	32.9	6.5	40.0	33.5	400	359
4	82.380	28.4	7.7	1.6	32.9	4.8	40.0	35.2	100	0
5	224.000	31.1	11.4	2.8	33.0	12.3	46.0	33.7	200	359
6	649.826	30.6	19.1	4.9	33.2	21.4	46.0	24.6	200	158
----- Vertical -----										
7	40.670	28.5	13.4	1.0	32.9	10.0	40.0	30	200	144
8	49.400	27.8	13.6	1.2	32.9	9.7	40.0	30.3	300	359
9	68.800	33.4	9.8	1.4	32.9	11.7	40.0	28.3	300	359
10	82.380	32.7	7.7	1.6	32.9	9.1	40.0	30.9	300	359
11	224.000	27.3	11.4	2.8	33.0	8.5	46.0	37.5	300	359
12	649.826	29.1	19.1	4.9	33.2	19.9	46.0	26.1	300	228


Remark: Margin (dB) = Limit – Result and Result = Reading Peak + Antenna Factor + Loss - Gain

Loss and Gain in above table means Cable Loss and Pre-amplifier gain.



**Tested by: Chang-Uk, Jun / Engineer**

Operating condition : High Channel






No.	FREQ [MHz]	READING PEAK [dBuV]	ANT FACTOR [dB]	LOSS [dB]	GAIN [dB]	RESULT [dBuV/m]	LIMIT [dBuV/m]	MARGIN [dB]	ANTENNA [cm]	TABLE [DEG]
----- Horizontal -----										
1	36.790	29.5	12.8	1.0	32.9	10.4	40.0	29.6	400	138
2	41.640	28.3	13.5	1.0	32.9	9.9	40.0	30.1	200	359
3	99.840	28.3	11.8	1.8	33.0	8.9	43.5	34.6	300	0
4	131.850	30.6	8.7	2.1	32.9	8.5	43.5	35	100	0
5	224.000	31.7	11.4	2.8	33.0	12.9	46.0	33.1	100	67
6	256.010	30.2	12.4	3.0	32.9	12.7	46.0	33.3	100	239
7	845.761	37.6	21.2	5.8	33.0	31.6	46.0	14.4	200	359
----- Vertical -----										
8	36.790	28.3	12.8	1.0	32.9	9.2	40.0	30.8	400	170
9	41.640	27.3	13.5	1.0	32.9	8.9	40.0	31.1	100	359
10	99.840	29.3	11.8	1.8	33.0	9.9	43.5	33.6	100	281
11	131.850	27.7	8.7	2.1	32.9	5.6	43.5	37.9	300	224
12	224.000	27.6	11.4	2.8	33.0	8.8	46.0	37.2	200	0
13	256.010	27.6	12.4	3.0	32.9	10.1	46.0	35.9	400	0

Remark: Margin (dB) = Limit – Result and Result = Reading Peak + Antenna Factor + Loss - Gain

Loss and Gain in above table means Cable Loss and Pre-amplifier gain.




**Tested by: Chang-Uk, Jun / Engineer**

**7.4.2.3 Test Data for Below 30 MHz**

Humidity Level : 47 % R.H. Temperature: 22 °C  
 Resolution bandwidth : 200 Hz (from 9 kHz to 0.15 MHz), 9 kHz (from 0.15 MHz to 30 MHz)  
 Frequency range : 9 kHz ~ 30 MHz  
 Measurement distance : 3 m  
 Limits apply to : FCC CFR 47, PART 15, SUBPART C, SECTION 15.249 (d)  
 Result : PASSED

EUT : IR&RF Remote Date: April 10, 2012  
 Detector : CISPR Quasi-Peak (Resolution Bandwidth: 9 kHz)

Frequency (MHz)	Reading (dB $\mu$ V)	Ant. Pol. (H/V)	Ant. Height (m)	Angle (°)	Ant. Factor (dB/m)	Cable Loss	Emission Level(dB $\mu$ V/m)	Limits (dB $\mu$ V/m)	Margin (dB)
It was not observed any emissions from the EUT.									




**Tested by: Chang-Uk, Jun / Engineer**

**7.4.2.4 Test Data above 1 GHz except for harmonic**

- Test Date : April 10, 2012
- Humidity Level : 47 % R.H.
- Temperature : 22 °C
- Resolution bandwidth : 1 MHz for Peak and Average Mode
- Video bandwidth : 1 MHz for Peak Mode, 10 Hz for Average Mode
- Frequency range : 1 GHz ~ 25 GHz
- Measurement distance : 3 m
- Limits apply to : FCC CFR 47, PART 15, SUBPART C, SECTION 15.249 (d)
- Result : PASSED

Frequency (MHz)	Reading (dBμV)	Ant. Pol. (H/V)	Ant. Height (m)	Angle (°)	Ant. Factor (dB/m)	Cable Loss	Emission Level(dBμV/m)	Limits (dBμV/m)	Margin (dB)
It was not observed any emissions from the EUT.									




**Tested by: Chang-Uk, Jun / Engineer**

**7.4.2.5 Band Edge**


- . Test Date : April 10, 2012
- . Resolution bandwidth : 1 MHz for Peak and Average Mode
- . Video bandwidth : 1 MHz for Peak Mode, 10 Hz for Average Mode
- . Measurement distance : 3 m
- . Operating Condition : Low / High Channel
- . Limits apply to : FCC CFR 47, PART 15, SUBPART C, SECTION 15.249 (d)
- . Result : PASSED BY -8.44 dB at high Channel

Frequency (MHz)	Reading (dBμV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	Pre-Amp (dB)	Total (dBμV/m)	Limits (dBμV/m)	Margin (dB)
<b>Test Data for Low Channel</b>									
2 400.00	64.29	Peak	H	27.05	3.14	43.10	51.38	74.00	-22.62
2 400.00	56.70	Average	H				43.79	54.00	-10.21
2 400.00	58.17	Peak	V				45.26	74.00	-28.74
2 400.00	47.74	Average	V				34.83	54.00	-19.17
<b>Test Data for High Channel</b>									
2 483.50	67.72	Peak	H	27.31	3.17	43.10	55.10	74.00	-18.90
2 483.50	58.18	Average	H				45.56	54.00	-8.44
2 483.50	63.46	Peak	V				50.84	74.00	-23.16
2 483.50	50.91	Average	V				38.29	54.00	-15.71




**Tested by: Chang-Uk, Jun / Engineer**


Plotted Data for band edge



Low Channel – Horizontal (Peak)




Low Channel – Horizontal (Average)




Low Channel - Vertical (Peak)




Low Channel - Vertical (Average)




High Channel - Horizontal (Peak)



High Channel - Horizontal (Average)



High Channel - Vertical (Peak)



High Channel - Vertical (Average)




**8. 20 dB BANDWIDTH**

**8.1 Operating environment**

Temperature : 27 °C  
 Relative humidity : 47 % R.H.

**8.2 Test set-up**

The output signal of EUT was received by the spectrum analyzer. The resolution bandwidth is set to 10 kHz, and peak detection was used. The 20 dB bandwidth is defined as the total spectrum over which the power is higher than the peak power minus 20 dB.



**8.3 Test equipment used**

Model Number	Manufacturer	Description	Serial Number	Last Cal. (Interval)
■ - FSV30	R/S	Spectrum Analyzer	101372	Aug. 29, 2011 (1Y)


**8.4 Test data for Bandwidth**

-. Test Date : April 10, 2012  
 -. Limits apply to : FCC CFR 47, PART 15, SUBPART C, SECTION 15.215(c)


Channel	Operating Freq. (MHz)	20 dB Bandwidth (kHz)
Low	2 405.00	2 630.0
Middle	2 450.00	2 630.0
High	2 480.00	2 620.0

Remark: See next page for 20 dB Bandwidth test data

**Tested by: Chang-Uk, Jun / Engineer**



Low Channel



Middle Channel

