

FCC TEST REPORT

The Reputation of LG Defense Industry Continues with NEX1 Future.

Locations & Offices

NEX1 GUMI

133 Gongdan-dong, Gumi, Gyongsangbuk-do,
730-030, Korea

Tel : +82-54-469-8213
Fax : +82-54-469-8065



Network Navigation

• SEOUL
• YONGIN
• GUMI

March 19, 2007

NEX 1 Future Co., Ltd.

TEST REPORT CERTIFICATION

Applicant : Remote Solution Co., Ltd.

Address : 92, Chogokri, Nammyun, Kimchon city, Kyungbuk, 740-871, Korea

EUT Name : Color LCD Touch screen universal remote control

Model No. : RH60B and XTR39

Serial No. : Engineering Sample

FCCID : TX4RH60B

Testing location : Nex1 Future Co., Ltd.
133, Kongdan-Dong, Gumi-City, Kyeongsangbuk-Do, 730-030, R.O.K

Applied specification : FCC Part 15


Test result : The above mentioned test item passed.

Test Date March 19, 2007 **Review Date** March 19, 2007

Tested by Hyo-Jeung, Cho **Reviewed by** Jeong-Hi, Jin

Title Engineer **Title** EMC Manager

Signature



조효정

Signature



진경희

I HEREBY CERTIFY THAT the data shown in this report were made in accordance with the procedures given in the applied specification and I assume full responsibility for accuracy and completeness of these data.

Note : This test report relates to the a. m. test item. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark on this or similar products.

Contents

1. GENERAL INFORMATION.....	5
1.1 PRODUCT DESCRIPTION	5
1.2 PROJECT DATA.....	5
1.3 APPLICANT	5
1.4 MANUFACTURER	5
2. EUT INFORMATION.....	6
2.1 GENERAL EUT INFORMATION.....	6
2.2 CENTER FREQUENCY OF TESTED CHANNEL.....	6
2.3 TEST ENVIRONMENT	6
2.4 ACCESSORIES AND ANCILLARY EQUIPMENT	6
3. TESTING FACILITIES.....	7
4. EUT DESCRIPTION AND OPERATIONAL DESCRIPTION.....	7
5. TEST SET-UP.....	8
5.1 PRINCIPLE OF CONFIGURATION	8
5.2 OPERATIONAL MODES	8
5.3 APPLIED SPECIFICATION	8
6. TEST REPORT SUMMARY	9
7. TEST RESULTS.....	10
7.1 ANTENNA CONNECTOR REQUIREMENTS	10
7.2 AC CONNECTED EMISSION	11
7.3 6dB BANDWIDTH.....	16
7.4 POWER SPECTRAL DENSITY	20
7.5 PEAK OUTPUT POWER.....	24
7.6 BAND-EDGE COMPLIANCE	28
7.7 FIELD STRENGTH MEASUREMENT FOR BAND-EDGE COMPLIANCE	31
7.8 SPURIOUS CONDUCTED EMISSIONS	36



REPORT NO :
NF-TA-R070008

NEX1 Future Co., Ltd.

7.9 SPURIOUS RADIATED EMISSIONS	47
8. LIST OF TEST AND MEASUREMENT INSTRUMENTS	50
9. NOTES.....	51

1. General Information

1.1 Product Description

Product Name : Color LCD Touch screen universal remote control
Product ID : RH60B and XTR39
Serial No. : Prototype
FCC ID : TX4RH60B

1.2 Project data

Receipt of EUT : March 2, 2007
Date of Test : March 19, 2007
Data of report : March 19, 2007

1.3 Applicant

Company Name : Remote Solution Co., Ltd.
Address : 92, Chogokri, Nammyun, Kimchon city, Kyungbuk,
740-871, Korea
Contact Person : Mr. Byung-Cheol, Kim

1.4 Manufacturer

Company Name : Remote Solution Co., Ltd.
Address : 92, Chogokri, Nammyun, Kimchon city, Kyungbuk,
740-871, Korea
Contact Person : Mr. Byung-Cheol, Kim

2. EUT Information

2.1 General EUT Information

Type	Transmitter	Receiver
FCC Classification	Direct Sequence Spread Spectrum(DSSS)	Direct Sequence Spread Spectrum(DSSS)
EUT Type	Zigbee (802.15.4)	Zigbee (802.15.4)
Modulation Type	OQPSK	OQPSK
Operating frequency range	2405 – 2480 MHz	2405 – 2480 MHz
Bands of operation	2.400 – 2.4835 GHz	2.400 – 2.4835 GHz
Number of Channels	16	16
Channel Separation	5MHz	5MHz
Type of Antenna	Dielectric Chip Antenna	Dielectric Chip Antenna
Power Supply	DC 3.7 V Lithium Ion	DC 3.7 V Lithium Ion

2.2 Center Frequency of Tested Channel

Frequency	Tx (MHz)	Rx (MHz)
Lowest	2405	2405
Middle	2445	2445
Highest	2480	2480

2.3 Test Environment

Temperature	25°C
Relative Humidity	30 ~ 60%
Voltage(DC)	DC 3.7V
Voltage(AC)	115V AC , 50Hz

2.4 Accessories and Ancillary Equipment

Equipment	Model No.	Serial Number	Maker
Laptop PC	PS428L-OE142	30014068J	Toshiba

3. Testing Facilities

Nex1 Future Co., Ltd.

133, Kongdan-Dong, Gumi-City, Kyeongsangbuk-Do, 730-030, R.O.K

4. EUT Description and Operational Description

The RH60 is designed to control various home appliances and sensor equipment safely and easily.

Using 3.9" full color touch screen makes everyone use easily the product and allows to redesign and recompose the control button according to the uses of each user.

The control system for the appliances is the infrared, and the 2.4GHz Zigbee is available as well.

The RH60 is designed to control all home appliances with only the 2.4GHz RF by Using the Zigbee to IR converter instead of using the infrared, which solve the distance and space problem caused by using the infrared.

There are various entertainment features. The alarm, clock, bio-rhythm, memo pad and game are supported.

With the manager program, the database and firmware are upgraded and the LCD screen and button are recomposed simply via USB.

It is possible to use the product for around 100 hours without charging because of The excellent power management and the high capacity rechargeable battery.

While the RH60 is sitting on the charging cradle, the appliances control is allowed in case of using its sub-remote.

5. Test Set-up

5.1 Principle of configuration

Conducted : The equipment under test (EUT) was configured with a temporary SMA Connector and EUT transmits its maximum power level.

Emission:The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes and test settings were adapted accordingly in reference to the instructions for use.

For details, please refer to the Operation mode in chapter 7.

15B compliance : The equipment under test (EUT) was connected to the Ancillary PC via USB cable and data was transmitted into EUT from the PC continuously during the test for Part 15.107 and 15.109.

5.2 Operational Modes

Fixed mode (2405Mhz, 2445Mhz and 2480Mhz)

5.3 Applied Specification

FCC Part 15

6. Test Report Summary

Related Clause	Test Cases	FCC Part Sections	Result (Note1)
7.1	Antenna Connector Requirements	15.203 15.204	C
7.2	AC Connected Emission	15.107and15.207	Pass
7.3	6dB Bandwidth	15.247(a)(2)	Pass
7.4	Power Spectral Density	15.247(e)	Pass
7.5	Peak Output Power	15.247(b)(3)	Pass
7.6	Band-edge Compliance	15.247(d)	Pass
7.7	Field Strength measurement	15.247(d)	Pass
7.8	Spurious Conducted emissions	15.247(d)	Pass
7.9	Spurious Radiated emissions	15.109 and 15.247(d)	Pass

* Note1: C: Complies, Pass: Passed, Fail : Failed and NA : Not Applicable

7. Test Results

7.1 Antenna Connector Requirements

Requirements

Subclause 15.203 and 15.204(c)

According to the Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section.

The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

And according to the Part 15.204(c), only the antenna with which an intentional radiator is authorized may be used with the intentional radiator.

Test results

RESULT:

Complies

The antenna is permanently attached on the PCB.

The EUT has a Dielectric Chip Antenna.

For more information on the antenna:

Antenna gain : 0 dBi
Manufacturer : High Technology Provider
Model No. : IMABC01
Type : Dielectric Chip Antenna

7.2 AC Connected Emission

Test Mode and conditions

The power is supplied by a DC 3.7 V Lithium Ion or it can be charged with AC/DC adaptor.

Data is transmitted into the PC with USB port.

Requirements

Subclause 15.107 and 15.207(a)


For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN).

Frequency of Emission (M Hz)	Conducted Limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66-56*	56-46*
0.5-5	56	46
5-30	60	50


* Decreases with the logarithm of the frequency.

Test results

< AC/DC Adaptor >



< Fig 1. Conducted emission-Hot line >




< Fig 2. Conducted emission-Neutral line >

Frequency (MHz)	Insertion Loss	Cable Loss	Pol.	Quasi-Peak[dBuV]			Average[dBuV]			Margin[dBuV]	
				Limit	Reading	Result	Limit	Reading	Result	Quasi	Average
0.15	0.50	-0.14	N	66.00	37.3	37.65	56.00	28.9	29.25	28.35	26.75
0.205	0.81	-0.23	H	63.41	47.3	47.87	53.41	44.5	45.07	15.53	8.33
0.305	0.81	-0.38	H	60.11	45.3	45.73	50.11	45.5	45.93	14.38	4.18
0.405	0.82	-0.21	H	57.75	36.4	37.00	47.75	36.1	36.70	20.75	11.05
0.51	0.82	-0.05	H	56.00	37.9	38.67	46.00	38.8	39.57	17.33	6.43
0.61	0.82	-0.05	H	56.00	36.7	37.47	46.00	37.6	38.37	18.53	7.63
0.71	0.82	-0.05	H	56.00	29.8	30.57	46.00	30.3	31.07	25.43	14.93
2.43	0.87	-0.03	H	56.00	30.8	31.64	46.00	29.6	30.44	24.36	15.56
3.04	0.88	-0.01	H	56.00	35.3	36.17	46.00	32.3	33.17	19.83	12.83
26.395	1.58	0.18	N	60.00	46.5	48.26	50.00	43.1	44.86	11.74	5.14
26.505	1.60	0.18	N	60.00	47	48.78	50.00	43.2	44.98	11.22	5.02
26.62	1.80	0.18	H	60.00	42.4	44.38	50.00	42.5	44.48	15.62	5.52


*Comment : Pol : H (Live), N(Neut)
 Insertion Loss : Insertion Loss of LISN
 Cable Loss : Cable Loss + Pulse Limiter Insertion loss value

4.

< USB part >



< Fig 3. Conducted emission-Hot line with data >



< Fig 4. Conducted emission-Neut line with data >

Frequency (MHz)	Insertion Loss	Cable Loss	Pol.	Quasi-Peak[dBuV]			Average[dBuV]			Margin[dBuV]	
				Limit	Reading	Result	Limit	Reading	Result	Quasi	Average
0.165	0.08	-0.17	N	65.21	51.4	51.32	55.21	43.3	43.22	13.89	11.99
0.190	0.10	-0.21	N	64.04	44.0	43.89	54.04	39.7	39.59	20.15	14.45
0.305	0.11	-0.17	N	60.11	38.8	38.74	50.11	38.0	37.94	21.36	12.16
0.445	0.12	-0.14	N	56.97	39.4	39.37	46.97	39.1	39.07	17.59	7.89
0.580	0.12	-0.22	N	56.00	30.0	29.91	46.00	28.5	28.41	26.10	17.60
0.720	0.13	-0.23	N	56.00	26.0	25.90	46.00	24.7	24.60	30.10	21.40
1.150	0.16	-0.24	L1	56.00	28.7	28.61	46.00	22.9	22.81	27.39	23.19
2.170	0.19	-0.29	N	56.00	30.2	30.10	46.00	19.4	19.30	25.90	26.70
3.215	0.22	-0.14	N	56.00	25.2	25.28	46.00	17.9	17.98	30.72	28.02
4.650	0.27	-0.15	N	56.00	21.5	21.62	46.00	18.5	18.62	34.38	27.38

*Comment : Pol : L1 (Live), N(Neut)

Insertion Loss : Insertion Loss of LISN

Cable Loss : Cable Loss + Pulse Limiter Insertion loss value

7.3 6dB Bandwidth

Test Mode and conditions

Mode of operation : Tx mode
Measurement Method : Conducted
Detector : PK
Trace : Max hold
RBW/VBW : 100kHz/100kHz

Requirements


Subclause 15.247(a)(2)

Systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test results

Test frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)	Results
2405.000	1.54	> 0.5	Pass
2445.000	1.62	> 0.5	Pass
2480.000	1.58	> 0.5	Pass

6dB Bandwidth Plot-2405



Date: 19.MAR.2007 09:48:22

6dB Bandwidth Plot-2480




*RBW 100 kHz Delta 1 [T1]
*VBW 100 kHz -0.10 dB
SWT 2.5 ms 1.580000000 MHz

Ref 10 dBm

*Att 20 dB

1 PK
MAXH



Center 2.48 GHz

500 kHz/

Span 5 MHz

Date: 19.MAR.2007 09:56:56

7.4 Power Spectral Density

Test Mode and conditions

Mode of operation : Tx mode
Measurement Method : Conducted
Detector : PK
Trace : Max hold
RBW/VBW : 3kHz/10kHz

Requirements


Subclause 15.247(e)

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

Test results

Test frequency (MHz)	Reading (dBm)	Cable attenuation (dB)	Power Spectral Density (dBm)	Limit (dBm)	Results
2405.000	-14.25	1.80	-12.45	8	Pass
2445.000	-14.23	1.83	-12.40	8	Pass
2480.000	-15.00	1.85	-13.15	8	Pass

Power Spectral Density Plot- 2405



Date: 19.MAR.2007 10:04:13

Power Spectral Density Plot- 2445




*RBW 3 kHz Marker 1 [T1]
*VBW 10 kHz -14.23 dBm
SWT 340 ms 2.445144000 GHz

Ref 10 dBm

*Att 20 dB

1 PK
MAXH



Center 2.445 GHz

300 kHz/

Span 3 MHz

Date: 19.MAR.2007 10:05:44

Power Spectral Density Plot- 2480




*RBW 3 kHz Marker 1 [T1]
*VBW 10 kHz -15.00 dBm
SWT 340 ms 2.480522000 GHz

Ref 10 dBm

*Att 20 dB

1 PK
MAXH



Center 2.48 GHz 300 kHz/ Span 3 MHz

Date: 19.MAR.2007 10:06:51

7.5 Peak Output Power

Test Mode and conditions

Mode of operation : Tx mode
Measurement Method : Conducted
Detector : PK
Trace : Max hold
RBW/VBW : 3MHz/3MHz

Requirements

Subclause 15.247(b)(3)

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt.

Test results

Test Frequency (MHz)	Reading (dBm)	Cable attenuation (dB)	Peak Output Power (W)	Limit (W)	Results
2405	0.65	1.80	0.001757924	1.0	Pass
2445	0.30	1.83	0.001633100	1.0	Pass
2480	0.20	1.85	0.001603245	1.0	Pass

Peak Output Power Plot - 2405




*RBW 3 MHz Marker 1 [T1]
*VBW 3 MHz 0.65 dBm
SWT 2.5 ms 2.405560000 GHz

Ref 10 dBm

*Att 20 dB

1 PK
MAXH




Center 2.405 GHz

1 MHz/

Span 10 MHz


Date: 19.MAR.2007 10:58:16

Peak Output Power Plot – 2445



Date: 19.MAR.2007 11:03:46

Peak Output Power Plot – 2480



Date: 19.MAR.2007 11:18:08

7.6 Band-edge Compliance

Test Mode and conditions

Mode of operation : Tx mode
Measurement Method : Conducted
Detector : PK
Trace : Max hold
RBW/VBW : 100kHz/300kHz

Requirements

Subclause 15.247(d)


In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required.

Test results

There is no peak found outside any 100kHz bandwidth of the operating frequency band in the three transmit frequency.


Tx Frequency (MHz)	RF power outside 100kHz BW (MHz)	Limit	Results
2405	No peak above 20dB	20dB below	Pass
2480	No peak above 20dB	20dB below	Pass

Band-edge Compliance Plot - 2405



Date: 19.MAR.2007 11:29:46

Band-edge Compliance Plot – 2480



Date: 19.MAR.2007 11:32:01

7.7 Field Strength measurement for Band-edge Compliance

Test Mode and conditions

Mode of operation	:	Tx mode (2402MHz, 2480MHz), DH1 packet
Trace	:	Max hold
Measurement Method	:	Radiated- Enclosure
Measurement Distance	:	3m
RB/VB in Restricted band	:	1 MHz/1MHz for Peak, 1MHz/10Hz for Average
RB/VB in Non-Restricted band	:	100KHz/100KHz for Peak

Requirements


Subclause 15.247(c)

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100k Hz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required.


Test results

Frequency (MHz)	Polarization (H/V)	Corr. Factor (dB)	Result (dBuV/m)		Limit (dBuV/m)		Margin (dB)		Table Angle (Deg.)	Ant. Height (m)
			A	P	A	P	A	P		
Operating frequency : 2405Mhz										
2390	V	16.1	34.0	49.13	54	74	20.00	24.84	120	1.2
2390	H	16.1	33.9	50.94	54	74	20.10	23.06	75	0.9
Operating frequency : 2480Mhz										
2483.5	V	16.1	34.3	54.14	54	74	19.7	19.86	120	1.2
2483.5	H	16.1	34.7	61.74	54	74	19.3	12.26	75	0.9


Band-edge emissions plot- 2405 (Vertical)




Band-edge emissions plot- 2405 (Horizontal)



Band-edge emissions plot- 2480 (Vertical)



Band-edge emissions plot- 2480 (Horizontal)



7.8 Spurious Conducted emissions

Test Mode and conditions

Mode of operation : Tx mode
 Measurement Method : Conducted
 Detector : PK
 Trace : Max hold
 RBW/VBW : 100kHz/300kHz

Requirements

Subclause 15.247(d)

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100k Hz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required.


Test results

Frequency (MHz)	Reading Value (dBm)	Correction Factor (dB)	Results (dBm)	Reference Value (dBm)	Delta to Reference (dB)
<i>Operating frequency : 2405MHz</i>					
4815.6	-37.96	3.4	-34.56	-22.980	11.58
7228.34	-48.43	5.6	-42.83	-22.980	19.85
14880	-51.96	6.0	-45.96	-22.980	22.98
20000	-47.46	6.7	-40.76	-22.980	17.78

Frequency (MHz)	Reading Value (dBm)	Correction Factor (dB)	Results (dBm)	Reference Value (dBm)	Delta to Reference (dB)
<i>Operating frequency : 2445MHz</i>					
4895.36	-39.81	3.4	-36.41	-25.290	11.12
7437.98	-50.66	5.6	-45.06	-25.290	19.77
15120	-52.02	6.0	-46.02	-25.290	20.73
20060	-47.12	6.7	-40.42	-25.290	15.13


Frequency (MHz)	Reading Value (dBm)	Correction Factor (dB)	Results (dBm)	Reference Value (dBm)	Delta to Reference (dB)
<i>Operating frequency : 2480MHz</i>					
4955.18	-40.61	3.4	-37.21	-24.910	12.3
7447.68	-53.4	5.6	-47.8	-24.910	22.89
14920	-51.43	6.0	-45.43	-24.910	20.52
20050	-46.77	6.7	-40.07	-24.910	15.16

Spurious Conducted emissions plot- 2405 (30MHz~10GHz)




Date: 19.MAR.2007 09:09:48

Spurious Conducted emissions plot- 2405 (10GHz~20GHz)




Date: 19.MAR.2007 09:14:04

Spurious Conducted emissions plot- 2405 (20GHz~25GHz)




Date: 19.MAR.2007 09:16:53

Spurious Conducted emissions plot- 2445 (30MHz~10GHz)




Date: 19.MAR.2007 09:20:17

Spurious Conducted emissions plot- 2445 (10GHz~20GHz)




Date: 19.MAR.2007 11:45:34

Spurious Conducted emissions plot- 2480 (30MHz~10GHz)




Date: 19.MAR.2007 09:34:04

Spurious Conducted emissions plot- 2480 (10GHz~20GHz)



Date: 19.MAR.2007 09:37:23

Spurious Conducted emissions plot- 2480 (20GHz~25GHz)



Date: 19.MAR.2007 09:40:44

7.9 Spurious Radiated emissions

Test Mode and conditions

Mode of operation	: Tx mode
Detector	: PK
Trace	: Max hold
Measurement Method	: Radiated- Enclosure
Measurement Distance	: 3m
Measurement BW	: 1 MHz for $f \geq 1$ GHz, 100kHz for $f < 1$ GHz

Requirements

Subclause 15.109 and 15.247(c)

In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

According to Section 15.209(a) , except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field strength (microvolts/meter)	Field strength (dB μ V/m)	Measurement distance (meters)
30-88	100**	$20 \cdot \log(100) = 40.0$	3
88-216	150**	$20 \cdot \log(150) = 43.5$	3
216-960	200	$20 \cdot \log(200) = 46.0$	3
960-2500	500	$20 \cdot \log(500) = 54.0$	3

** Except as provided in paragraph(g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72Mhz, 76-88Mhz, 174-216Mhz or 470-806Mhz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241. According to section 15.35(b), on any frequency or frequencies above 1000 MHz the radiated limits shown are based upon the use of measurement instrumentation employing an average detector function. When average radiated emission measurements are specified in this part, including emission measurements below

1000 MHz, there also is a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit for the frequency being investigated

Test results

Frequency (MHz)	Polarization (H/V)	Corr. Factor (dB)	Result (dBuV/m)		Limit (dBuV/m)		Margin (dB)		Table Angle (Deg.)	Ant. Height (m)
			A	P	A	P	A	P		
Operating frequency : 2405Mhz										
4810	V	16.3	34.0	53.5	54	74	20.0	20.5	120	1.2
4810	H	16.3	33.9	53.3	54	74	20.1	20.7	75	0.9

Frequency (MHz)	Polarization (H/V)	Corr. Factor (dB)	Result (dBuV/m)		Limit (dBuV/m)		Margin (dB)		Table Angle (Deg.)	Ant. Height (m)
			A	P	A	P	A	P		
Operating frequency : 2445Mhz										
4890	V	16.4	34.1	53.4	54	74	19.9	20.6	120	1.2
4890	H	16.4	34.4	58.6	54	74	19.6	15.4	75	0.9
7335	V	20.1	39.6	61.6	54	74	14.4	12.4	120	1.2

Frequency (MHz)	Polarization (H/V)	Corr. Factor (dB)	Result (dBuV/m)		Limit (dBuV/m)		Margin (dB)		Table Angle (Deg.)	Ant. Height (m)
			A	P	A	P	A	P		
Operating frequency : 2480Mhz										
4960	V	16.4	34.3	53.4	54	74	19.7	20.6	120	1.2
4960	H	16.4	34.7	60.2	54	74	19.3	13.8	75	0.9
7440	V	20.1	39.7	59.7	54	74	14.3	14.3	120	1.2

* Note :

1. Remark “*” means that the emission frequency is produced by local oscillator.
2. Remark”- - “ means that the emission level is too low to be measured.
3. The measurement uncertainty of the radiated emission test is $\pm 3\text{dB}$
4. “A” and “P” mean average and peak measurement respectively.
5. There are no spurious emissions found between the lowest internal oscillating frequency and 30 MHz.
6. There are no spurious emissions found for Class B digital device.

8. List of Test and Measurement Instruments

	Kind of Equipment	Type	Manufacturer	S/N
<input checked="" type="checkbox"/>	EMI Test Receiver	ESI26	R/S	8340.0010.02
<input checked="" type="checkbox"/>	Spectrum Analyzer	FSP30	R/S	1093.4495.30
<input type="checkbox"/>	Tracking Generator	ESMI-B1	R/S	1033.3240.52
<input checked="" type="checkbox"/>	Spectrum Analyzer	8566B	HP	3638A0857E
<input type="checkbox"/>	Spectrum Analyzer	E4407B	HP	MY41310181
<input checked="" type="checkbox"/>	Wave Dipole Antenna	HZ-12	R/S	842006/0012
<input checked="" type="checkbox"/>	Wave Dipole Antenna	HZ-12	R/S	846556/0004
<input checked="" type="checkbox"/>	Biconical Antenna	3104C	EMCO	9408-4667
<input type="checkbox"/>	Biconical Antenna	3109	EMCO	9405-2812
<input checked="" type="checkbox"/>	Log-Periodic Antenna	3146A	EMCO	1064
<input checked="" type="checkbox"/>	Biconilog Antenna	HLP2603	EMC Automaion	080100
<input type="checkbox"/>	V-Network	ESH3-Z5	R/S	847265/030
<input type="checkbox"/>	V-Network	ESH3-Z6	R/S	847250/016
<input type="checkbox"/>	T-Network	E-Z10	R/S	84480/011
<input checked="" type="checkbox"/>	LISN	ESH3-Z5	R/S	838979/020
<input checked="" type="checkbox"/>	Turn Table	2081	EMCO	
<input checked="" type="checkbox"/>	Antenna Tower	1072-5	EMCO	9202-1651
<input checked="" type="checkbox"/>	Positioning Controller	1090	EMCO	
<input type="checkbox"/>	Printer	C4569A	HP	SG78K1H1FS
<input checked="" type="checkbox"/>	Absorbing Clamp	MDS 21	R/S	847905/005
<input type="checkbox"/>	Signal Generator	2023	MARCONI	112246067
<input type="checkbox"/>	Swept Signal Generator	83620B	HP	3722A00549
<input type="checkbox"/>	10dB Attenuator	23-10-34	Weinschel co	BD4316
<input type="checkbox"/>	10dB Attenuator	33-10-34	Weinschel co	BB9784
<input checked="" type="checkbox"/>	Antenna	3142	EMCO	9710-1220
<input checked="" type="checkbox"/>	Antenna	3115	EMCO	9202-3820
<input checked="" type="checkbox"/>	Antenna	3160-08	EMCO	1168

<input checked="" type="checkbox"/>	Antenna	3160-09	EMCO	1304
<input checked="" type="checkbox"/>	Loop Antenna	6507	EMCO	9408-1327
<input checked="" type="checkbox"/>	Amplifier	HP8447F	HP	3113A06911
<input checked="" type="checkbox"/>	Amplifier	HP83006	HP	3104A00611
<input checked="" type="checkbox"/>	Amplifier	HP8449B	HP	3008A00859
<input checked="" type="checkbox"/>	EMI test receiver	ESCS30	R&S	839809/003
<input checked="" type="checkbox"/>	Artificial mains network	ESH2-Z5	R&S	829991/009
<input checked="" type="checkbox"/>	Artificial hand	FCC-AH-1	Fischer custom communications Inc.	2008

9. Notes

The test was conducted with RH60B model which has additional EL Backlight Controller compared to TRX39.

The other designs to be effected to the electrical characteristics are identical for both models.