



**NOTES:**

MATERIAL - 2 MIL POLYESTER BASE WITH 3 MIL MATTE CLEAR POLYESTER LAMINATE. COPY TO BE SUBSURFACE PRINTED. ADHESIVE SUITABLE FOR ADHERING TO NYLON POLYCARBONATE OR ABS PLASTICS. MATERIAL & SUPPLIER TO BE UL & CSA RECOGNIZED. ARTWORK - REQUEST FROM RRT BY PART NUMBER INITIAL ORDER- SUPPLIER TO SUBMIT PROOF TO RRT FOR APPROVAL. APPLICABLE STANDARDS - Cg-EPS -170, 2610928230. PET Transparent glossy, permanent glue; Flexcon Thermfilm PM 200 C T/C-387 L-23 40# Glassine + lamination 3M FM 1492

0,5 ...3	> 3 ...6	> 6 ...30	> 30 ...120	> 120 ...400	> 400 ...1000
non-toleranced dimensions / Nicht tolerierte Masse					
± 0.1	± 0.1	± 0.2	± 0.3	± 0.5	± 0.8
non-tol.broken edges / Nicht tol.gebrochene Kanten					
± 0.2	± 0.5	± 1			
angles, dimension of the shorter side / Winkel, Laenge des kuerzeren Schenkels					
to / bis 10	> 10 ...50	> 50 ...120	> 120 ...400	> 400	X
± 1°	± 30'	± 20'	± 10'	± 5'	
all linear dimensions in/ Alle Laengenmasse in					mm
tol. principle/ Tol.-grundsatz			ISO 8015:1985-12		

AA	20110124	A. MOUSHON		191	PT-MT/MKB1.1				
Ind.	Change/Aend.	YYYYMMDD	Drawn/Gez.	Checked/Gepr.	Releas./Freig.	BWN	Resp. dept./Verantw. Abt.	Add. info./Zus. Info.	
Treatment/ Behandlung						Missed details/Fehlende Angaben		Size/Gst.	
Mat./Stoff						From/Aus			
Lang./Spr. en/de		Wght./Gew.	<b>BOSCH</b>			ARTWORK		Sheet/Bl.	
	Crit. P.	Scale/M.stab 1:1				Nameplate for D-tect150		1/1	
MNR --		Mat.meets/Stoffe s N2580-1	Syst. AI	Doc.type DRW	1 601 118 T58		DP/TD	Ind. AA	Format A4
						Repl. for	Repl. by		