

Report on the FCC and IC Testing of the Robert Bosch Power Tools GmbH

Model: GCY 300-42

In accordance with FCC 47 CFR Part 15C, ISED Canada RSS-210 and ISED Canada RSS-GEN

Prepared for: Robert Bosch Power Tools GmbH
70538 Stuttgart
Germany

FCC ID: TXTGCY300-42
IC: 909H-GCY30042



Product Service

Choose certainty.
Add value.

COMMERCIAL-IN-CONFIDENCE

Date: 2021-07-19

Document Number: TR-57696-17551-03 | Issue: 02

RESPONSIBLE FOR	NAME	DATE	SIGNATURE
Project Management	Michael Ingerl	2021-07-19	 SIGN-ID 538027
Authorised Signatory	Alex Fink	2021-08-06	 SIGN-ID 540208

Signatures in this approval box have checked this document in line with the requirements of TÜV SÜD Product Service document control rules.

ENGINEERING STATEMENT

The measurements shown in this report were made in accordance with the procedures described on test pages. All reported testing was carried out on a sample equipment to demonstrate limited compliance with FCC 47 CFR Part 15C and ISED Canada RSS-210 and ISED Canada RSS-GEN. The sample tested was found to comply with the requirements defined in the applied rules.

RESPONSIBLE FOR	NAME	DATE	SIGNATURE
Testing	Michael Ingerl	2021-07-19	 SIGN-ID 538028

Laboratory Accreditation

DAkkS Reg. No. D-PL-11321-11-02

DAkkS Reg. No. D-PL-11321-11-03

Laboratory recognition

Registration No. BNetzA-CAB-16/21-15

ISED Canada test site registration

3050A-2

EXECUTIVE SUMMARY

A sample of this product was tested and found to be compliant with FCC 47 CFR Part 15C, ISED Canada RSS-210, Issue 10 (2019-12) and ISED Canada RSS-GEN, Issue 5 (2018-04).

DISCLAIMER AND COPYRIGHT

This non-binding report has been prepared by TÜV SÜD Product Service with all reasonable skill and care. The document is confidential to the potential Client and TÜV SÜD Product Service. No part of this document may be reproduced without the prior written approval of TÜV SÜD Product Service. © 2021 TÜV SÜD Product Service.

ACCREDITATION

Our BNetzA Accreditation does not cover opinions and interpretations and any expressed are outside the scope of our BNetzA Accreditation. Results of tests not covered by our BNetzA Accreditation Schedule are marked NBA (Not BNetzA Accredited).

Trade Register Munich
HRB 85742
VAT ID No. DE129484267
Information pursuant to Section 2(1)
DL-InfoV (Germany) at
www.tuev-sued.com/imprint

Managing Directors:
Walter Reithmaier (Sprecher / CEO)
Dr. Jens Butenandt
Patrick van Welij

Phone: +49 (0) 9421 55 22-0
Fax: +49 (0) 9421 55 22-99
www.tuev-sued.de

TÜV SÜD Product Service GmbH
Äußere Frühlingstraße 45
94315 Straubing
Germany



Contents

1	Report Summary	2
1.1	Report Modification Record.....	2
1.2	Introduction.....	2
1.3	Brief Summar of Results	3
1.4	Basic information of EUT	4
1.5	EUT Modification Record	5
1.6	Test Location	5
2	Test Setup	6
2.1	Radiated Emission in Fully or Semi Anechoic Room.....	6
2.2	Radiated Emission at Alternative Test Site.....	8
3	Test Details	10
3.1	Spurious Emissions.....	10
3.2	Restricted Band Edges.....	21
3.3	Authorised Band Edges	24
3.4	Emission Bandwidth.....	27
3.5	Power Spectral Density	35
3.6	Maximum Conducted Output Power	37
3.7	Transmitter frequency stability	39
4	Measurement Uncertainty	41
	Annex A: Test Setup Photos	
	Annex B: External Photos	
	Annex C: Internal Photos	



1 Report Summary

1.1 Report Modification Record

Alterations and additions to this report will be issued to the holders of each copy in the form of a complete document.

Issue	Description of Change	Date of Issue
1	First Issue	2021-06-30
2	Added Serial Numbers, HW and SW Version at chapter 1.2. Corrected Type of equipment and Type of Antennas at chapter 1.4.	2021-07-19

Table 1

1.2 Introduction

Applicant Robert Bosch Power Tools GmbH

Manufacturer Robert Bosch Power Tools GmbH

Model Number(s) GCY 300-42

Serial Number(s)

Description	Conducted	Radiated	Modulation	Remarks	Serial Number
CW, max power application, high channel		X	modulated	potted	124V00224 2480MHZ
prepared with control wires, antenna port fitted on PCB	X			no potting needed	124V00222

Hardware Version(s) 1.1.6

Software Version(s) 2.6.0

Number of Samples Tested 2

Test Specification/Issue/Date FCC 47 CFR Part 15C, ISED Canada RSS-210, Issue 10 (2019-12) and ISED Canada RSS-GEN, Issue 5 (2018-04)

Test Plan/Issue/Date ---

Order Number 5487175

Date of Receipt of EUT 2021-06-04

Start of Test 2021-06-08

Finish of Test 2021-06-25

Name of Engineer(s) Michael Ingerl

Related Document(s) ANSI C63.10 (2013)



1.3 Brief Summar of Results

A brief summary of the tests carried out in accordance with FCC 47 CFR Part 15C and ISED Canada RSS-210 and ISED Canada RSS-GEN is shown below.

Section	Specification Clause	Test Description	Result	Comments/Base Standard
Configuration and Mode: Continuously Transmitting				
3.1	15.247 (d), 15.205, B.10 and 6.13	Spurious Radiated Emissions	Pass	ANSI C63.10 (2013)
3.2	15.205 N/A and 8.10	Restricted Band Edges	Pass	ANSI C63.10 (2013)
3.3	15.247 (d), B.10 and N/A	Authorised Band Edges	Pass	ANSI C63.10 (2013)
3.4	15.247 (a)(2), N/A and 6.6	Emission Bandwidth	Pass	ANSI C63.10 (2013)
3.5	15.247 (e), N/A and 6.12	Power Spectral Density	Pass	ANSI C63.10 (2013)
3.6	15.247 (b), 5.4 and 6.12	Maximum Conducted Output Power	Pass	ANSI C63.10 (2013)
3.7	RSS-Gen, 6.11	Transmitter frequency stability	Pass	---

Table 2



1.4 Basic information of EUT

Equipment characteristics:			
Type designation	GCY 300-42		
Type of equipment:	Connectivity Module		
Power supply:	<input type="checkbox"/> AC Nominal: Minimum: Maximum: Nominal frequency: Hz	<input checked="" type="checkbox"/> DC Nominal: 5V Minimum: 4.75V Maximum: 5.25V	<input type="checkbox"/> Batterie Nominal:
Note for power supply:	Coin cell was at any test in the EUT but power supplied over 5V DC		
Kind of equipment:	Transceiver		
Frequency range:	2400-2483.5 MHz		
Number of RF-channels:	40		
Channel spacing	2 MHz		
Adaptive	No		
FHHS	No		
Type(s) of Modulation (e.g. BPSK, FSK, ASK, ...)	As per Bluetooth 4.2 Low Energy Standard		
Type of radio transmission / Use of frequency spectrum (e.g. DSSS, OFDM,.)	As per Bluetooth 4.2 Low Energy Standard		
Number / Type of Antenna(s)	Integral Antenna		
Antenna Gain:	2402 MHz: -0.22 dBi 2440 MHz: -1.08 dBi 2480 MHz: -1.82 dBi		
Temperature Range:	-20°C – 50°C		



1.5 EUT Modification Record

The table below details modifications made to the EUT during the test programme. The modifications incorporated during each test are recorded on the appropriate test pages.

Modification State	Description of Modification still fitted to EUT	Modification Fitted By	Date Modification Fitted
0	As supplied by the customer (TX 2480 MHz) SN: 124V00224	Not Applicable	Not Applicable

Table 3

Modification State	Description of Modification still fitted to EUT	Modification Fitted By	Date Modification Fitted
0	As supplied by the customer (Conducted Sample) SN: 124V00222	Not Applicable	Not Applicable

Table 4

1.6 Test Location

TÜV SÜD Product Service conducted the following tests at our Straubing Test Laboratory.

Test Name	Name of Engineer(s)
Configuration and Mode: Continuously Transmitting	
Spurious Radiated Emissions	Michael Ingerl
Restricted Band Edges	Michael Ingerl
Authorised Band Edges	Michael Ingerl
Emission Bandwidth	Michael Ingerl
Power Spectral Density	Michael Ingerl
Maximum Conducted Output Power	Michael Ingerl
Transmitter frequency stability	Michael Ingerl


Table 5

Office Address:

Äußere Frühlingstraße 45
 94315 Straubing
 Germany

2 Test Setup

2.1 Radiated Emission in Fully or Semi Anechoic Room



Radiated emission in fully or semi anechoic room is measured in the frequency range from 30 MHz to the maximum frequency as specified in CFR 47 Part 15 section 15.33.

Measurements are made in both the horizontal and vertical planes of polarization using a spectrum analyzer with the detector function set to peak and resolution as well as video bandwidth set to 100 kHz (below 1 GHz) or 1 MHz (above 1 GHz).

Testing up to 1 GHz is performed with a linear polarized logarithmic periodic antenna combined with a 4:1 broadband dipole ("Trilog broadband antenna"). For testing above 1 GHz horn antennas are used.

All tests below 8.2 GHz are performed at a test distance D of 3 meters. For higher frequencies the test distance may be reduced (e.g. to 1 meter) due to the sensitivity of the measuring instrument(s) and the test results are calculated according to CFR 47 Part 15 section 15.31(f)(1) using an extrapolation factor of 20 dB/decade. If required, preamplifiers are used for the whole frequency range. Special care is taken to avoid overload, using appropriate attenuators and filters, if necessary.

If the radiated emission limits are expressed in terms of the average value of the emission there also is a peak limit corresponding to 20 dB above the maximum permitted average limit. Additionally, if pulsed operation is employed, the average field strength is determined by averaging over one complete pulse train, including blanking intervals, as specified in CFR 47 Part 15 section 15.35(c). If the pulse train exceeds 0.1 second that 0.1 second interval during which the value of the emission is at its maximum is selected for calculation. The pulse train correction is added to the peak value of the emission to get the average value.

Hand-held or body-worn devices are rotated through three orthogonal axes to determine which attitude and configuration produces the highest emission relative to the limit and therefore shall be used for final testing.

During testing the EUT is rotated all around to find the maximum levels of emissions. Equipment and cables are placed and moved within the range of position likely to find their maximum emissions.

For final testing below 1 GHz a semi anechoic room complying with the NSA requirements of ANSI C63.4 for alternative test sites is used (see 2.2). If prescans are recorded in fully anechoic room they are indicated appropriately.



According to section 13 of KDB558074 the requirement for radiated emissions on the band edges was performed with a reduced bandwidth of 100 kHz instead of 1 MHz.

Radiated emission in the frequency range 9 kHz to 30 MHz is measured using an active loop antenna. First the whole spectrum of emission caused by the equipment is recorded at a distance of 3 meters in a fully or semi anechoic room with the detector of the spectrum analyzer or EMI receiver set to peak. This configuration is also used for recording the spectrum of intentional radiators.

Hand-held or body-worn devices are rotated through three orthogonal axes to determine which attitude and configuration produces the highest emission relative to the limit and therefore shall be used for final testing.


EUT is rotated all around to find the maximum levels of emissions. Equipment and cables are placed and moved within the range of position likely to find their maximum emissions.

If worst case emission of the EUT cannot be recorded with EUT in standard position and loop antenna in vertical polarization the EUT (or the radiating part of the EUT) is rotated by 90 degrees instead of changing the loop antenna to horizontal polarization. This procedure is selected to minimize the influence of the environment (e.g. effects caused by the floor especially with longer distances).

Final measurement is performed at a test distance D of 30 meters using an open field test site. In case the regulation requires testing at other distances, the result is extrapolated by either making measurements at an additional distance D of 10 meters to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). In cases of very low emissions measurements are performed at shorter distances and results are extrapolated to the required distance. The provisions of CFR 47 Part 15 sections 15.31(d) and (f)(2) apply. According to CFR 47 Part 15 section 15.209(d) final measurement is performed with detector function set to quasi-peak except for the frequency bands 9 to 90 kHz and 110 to 490 kHz where, for non-pulsed operation, average detector is employed.

If the radiated emission limits are expressed in terms of the average value of the emission there also is a peak limit corresponding to 20 dB above the maximum permitted average limit. Additionally, if pulsed operation is employed, the average field strength is determined by averaging over one complete pulse train, including blanking intervals, as specified in CFR 47 Part 15 section 15.35(c). If the pulse train exceeds 0.1 second that 0.1 second interval during which the value of the emission is at its maximum is selected for calculation. The pulse train correction is added to the peak value of the emission to get the average value.

2.2 Radiated Emission at Alternative Test Site



Alternate test site (semi anechoic room)

Radiated emission in the frequency range 30 MHz to 1 GHz is measured within a semi-anechoic room with groundplane complying with the NSA requirements of ANSI C63.4 for alternative test sites. A linear polarized logarithmic periodic antenna combined with a 4:1 broadband dipole ("Trilog broadband antenna") is used. The measurement bandwidth of the test receiver is set to 120 kHz with quasi-peak detector selected.

If the radiated emission limits are expressed in terms of the average value of the emission there also is a peak limit corresponding to 20 dB above the maximum permitted average limit. Additionally, if pulsed operation is employed, the average field strength is determined by averaging over one complete pulse train, including blanking intervals, as specified in CFR 47 Part 15 section 15.35(c). If the pulse train exceeds 0.1 second that 0.1 second interval during which the value of the emission is at its maximum is selected for calculation. The pulse train correction is added to the peak value of the emission to get the average value.

Hand-held or body-worn devices are tested in the position producing the highest emission relative to the limit as verified by prescans in fully anechoic room.

If no prescan in a fully anechoic room is used first a peak scan is performed in four positions to get the whole spectrum of emission caused by EUT with the measuring antenna raised and lowered from 1 to 4 m to find table position, antenna height and antenna polarization for the maximum emission levels. Data reduction is applied to these results to select those levels having less margin than 10 dB to or exceeding the limit using subranges and limited number of maximums. Further maximization is following.

With detector of the test receiver set to quasi-peak final measurements are performed immediately after frequency zoom (for drifting disturbances) and maximum adjustment.

Equipment and cables are placed and moved within the range of position likely to find their maximum emissions.

In cases where prescans in a fully anechoic room are taken (e. g. if EUT is operating for a short time only or battery is discharged quickly) final measurements with quasi-peak detector are performed manually at frequencies indicated by prescan with EUT rotating all around and receiving antenna raising and lowering within 1 meter to 4 meters to find the maximum levels of emission.

Equipment and cables are placed and moved within the range of position likely to find their maximum emissions.



Product Service

For measuring emissions of intentional radiators and receivers a test distance D of 3 meters is selected. Testing of unintentional radiators is performed at a distance of 10 meters. If limits specified for 3 meters shall be used for measurements performed at 10 meters distance the limits are calculated according to CFR 47 Part 15 section 15.31(d) and (f)(1) using an inverse linear-distance extrapolation factor of 20 dB/decade.



3 Test Details

3.1 Spurious Emissions

3.1.1 Specification Reference

FCC 47 CFR Part 15C, ISED Canada RSS-210 and ISED Canada RSS-GEN

3.1.2 Equipment Under Test and Modification State

GCY 300-42 (TX 2480 MHz), S/N: 124V00224 - Modification State 0
GCY 300-42 (Conducted Sample), S/N: 124V00222 - Modification State 0

3.1.3 Date of Test

2021-06-08 - 2021-06-09

3.1.4 Test Method

Plots for average measurements were taken in accordance with ANSI C63.10-2013 clause 4.1.4.2.3 to characterize the EUT. Where emissions were detected, final average measurements were taken in accordance with ANSI C63.10-2013 clause 4.1.4.2.2.

The plots shown are the characterization of the EUT. The limits on the plots represent the most stringent case for restricted bands, (54/74 dBuV/m) when compared to 20 dBc outside restricted bands. The limits shown have been used as a threshold to determine where further measurements are necessary. Where results are within 10 dB of the limits shown on the plots, further investigation was carried out and reported in results tables.

The following conversion can be applied to convert from dB μ V/m to μ V/m:
 $10^{(\text{Field Strength in dB}\mu\text{V/m}/20)}$.

3.1.5 Environmental Conditions

Ambient Temperature	23.0 °C
Relative Humidity	32.0 %

3.1.6 Test Results


Sample calculation of final values:

$$\begin{aligned} \text{Final Value (dB}\mu\text{V/m)} &= \text{Reading Value (dB}\mu\text{V)} + \text{Cable Correction Factor (dB)} \\ &+ \text{Antenna Correction Factor (dB/m)} \\ &+ \text{Pulse Train Correction (dB)} \end{aligned}$$



Transmission on 2402 MHz, conducted measurement:


Spurious



— Limit — Sum Level - - - Threshold × Critical × Final Critical

Transmission on 2440 MHz, conducted measurement:

Spurious




— Limit — Sum Level - - - Threshold × Critical × Final Critical



Transmission on 2480 MHz, conducted measurement:

Spurious




— Limit — Sum Level - - - - Threshold × Critical × Final Critical




Transmission on 2480 MHz, radiated measurement:

Note: Radiated only measured at Worst Case Position and Channel



Final Results 1:


Frequency	QuasiPeak	Limit	Margin	Meas. Time	Bandwidth	Pol	Azimuth	Corr.
MHz	dBµV/m	dBµV/m	dB	ms	kHz		deg	dB/m
1.560750	9.76	42.87	33.11	1000.0	9.000	V	158.0	19.7



— Preview Result 1H-PK+ FCC 15.209_3m
— Preview Result 1V-PK+ Final_Result QPK
— *

Final Results 1:

Frequency MHz	QuasiPeak dBµV/m	Limit dBµV/m	Margin dB	Meas. Time ms	Bandwidth kHz	Height cm	Pol	Azimuth deg	Corr. dB/m
927.450000	25.22	46.00	20.78	1000.0	120.000	107.0	V	59.0	30.2




- Preview Result 2H-AVG
- Preview Result 1V-PK+
- * Final_Result PK+
- Preview Result 1H-PK+
- FCC 15.2093 m PK
- ◇ Final_Result CAV
- Preview Result 2V-AVG
- FCC 15.2093 m AV

Final Results 1:

Frequency MHz	MaxPeak dBµV/m	CAverage dBµV/m	Limit dBµV/m	Margin dB	Meas. Time ms	Bandwidth kHz	Height cm	Pol	Azimuth deg	Corr. dB/m
2480.000000	---	76.01	#1	#1	1000.0	1000.000	152.0	H	-62.0	34.8
2480.000000	86.40	---	#1	#1	1000.0	1000.000	152.0	H	-62.0	34.8


#1 Intentional radiator



- Preview Result 2H-AVG
- Preview Result 1H-PK+
- Preview Result 2V-AVG
- Preview Result 1V-PK+
- FCC 15.209 (1m) PK
- - - FCC 15.209 (1m) AV
- * Final_Result PK+
- ◇ Final_Result AVG

Final Results 1:


<i>Frequency</i>	<i>MaxPeak</i>	<i>Limit</i>	<i>Margin</i>	<i>Meas. Time</i>	<i>Bandwidth</i>	<i>Height</i>	<i>Pol</i>	<i>Azimuth</i>	<i>Corr.</i>
<i>MHz</i>	<i>dBµV/m</i>	<i>dBµV/m</i>	<i>dB</i>	<i>ms</i>	<i>kHz</i>	<i>cm</i>		<i>deg</i>	<i>dB/m</i>
11566.100000	53.15	83.50	30.35	5.0	1000.000	150.0	H	152.0	37



- Preview Result 2H-AVG
- Preview Result 1V-PK+
- Preview Result 1H-PK+
- Preview Result 2V-AVG
- * Final_Result PK+
- ◇ Final_Result AVG
- FCC 15.209 (1m) PK
- - - FCC 15.209 (1m) AV

Final Results 1:

Frequency	MaxPeak	Limit	Margin	Meas. Time	Bandwidth	Height	Pol	Azimuth	Corr.
MHz	dBµV/m	dBµV/m	dB	ms	kHz	cm		deg	dB/m
17666.100000	51.45	83.50	32.05	5.0	1000.000	150.0	H	152.0	37



— Preview Result 2H-AVG — Preview Result 1H-PK+ — Preview Result 2V-AVG
— Preview Result 1V-PK+ — FCC 15.209 (1m) PK - - - - - FCC 15.209 (1m) AV
* Final_Result PK+ ◇ Final_Result AVG

Final Results 1:

Frequency	MaxPeak	Limit	Margin	Meas. Time	Bandwidth	Height	Pol	Azimuth	Corr.
MHz	dBµV/m	dBµV/m	dB	ms	kHz	cm		deg	dB/m
25481.062500	57.75	89.50	31.75	5.0	1000.000	150.0	H	160.0	40



FCC 47 CFR Part 15, Limit Clause 15.209

Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (m)
0.009 to 0.490	2400/F (kHz)	300
0.490 to 1.705	24000/F (kHz)	30
1705 to 30	30	30
30 to 88	100**	3
88 to 216	150**	3
216 to 960	200**	3
Above 960	500	5

ISED Canada RSS-210

Frequency	Electric Field Strength ($\mu\text{V/m}$)	Magnetic Field Strength (H-Field) ($\mu\text{A/m}$)	Measurement Distance (m)
9 - 490 kHz	2,400/F (F in kHz)	2,400/377F (F in kHz)	300
490 - 1,705 kHz	24,000/F (F in kHz)	24,000/377F (F in kHz)	30
1,705 kHz - 30 MHz	30	N/A	30

Frequency (MHz)	Field Strength ($\mu\text{V/m}$ at 3 m)
30 - 88	100
88 - 216	150
216 - 960	200
> 960	500



3.1.7 Test Location and Test Equipment Used

Radiated Tests were carried out in cabin No.8 and cabin No. 11 and conducted tests were carried out with test system TS8997.

Instrument	Manufacturer	Type No	TE No	Calibration Period (months)	Calibration Due
EMI test receiver	Rohde & Schwarz	ESW26	28268	12	2021-09-30
Trilog Antenna	Schwarzbeck	VULB9162	20116	36	2022-01-31
EMC measurement software	Rohde & Schwarz	EMC32 Emission K11 - V10.50.10	19927	---	---
Semi Anechoic Room	Albatross	Cabin No. 8	19917	36	2023-10-31
EMI test receiver	Rohde & Schwarz	ESW44	39897	12	2022-04-30
Double ridged horn antenna	Rohde & Schwarz	HF907	40089	24	2023-02-28
Loop antenna	Schwarzbeck	FMZB 1519 B	44334	36	2023-01-31
ULTRALOG Antenna	Rohde & Schwarz	HL562E	39969	36	2022-11-30
Horn Antenna with preamplifier	Rohde & Schwarz	A-INFOMW LB-180400H-KF+ TS-	43661	12	2021-10-31
EMC measurement software	Rohde & Schwarz	EMC32 Emission K11 - V10.50.10	42986	---	---
Semi Anechoic Room	Frankonia	Cabin No. 11	42961	36	2022-08-31
Spectrum Analyzer	Rohde & Schwarz	FSV40	20219	12	2022-01-31
Vector Signal Generator	Rohde & Schwarz	SMBV100A	20238	36	2022-11-30
Signal Generator	Rohde & Schwarz	SMB100A	20215	36	2023-12-31
Switching Device	Rohde & Schwarz	OSP120 I	20248	24	2022-02-28
Switching Device	Rohde & Schwarz	OSP120 II	38807	36	2023-11-30
EMC Measurement Software	Rohde & Schwarz	EMC32 TS8997 - V10.50.00	44381	---	---

Table 6

TU - Traceability Unscheduled
 O/P Mon – Output Monitored using calibrated equipment
 N/A - Not Applicable



3.2 Restricted Band Edges

3.2.1 Specification Reference

FCC 47 CFR Part 15C, ISED Canada RSS-210 and ISED Canada RSS-GEN

3.2.2 Equipment Under Test and Modification State

GCY 300-42 (TX 2480 MHz), S/N: 124V00224 - Modification State 0
GCY 300-42 (Conducted Sample), S/N: 124V00222 - Modification State 0

3.2.3 Date of Test

2021-06-08 - 2021-06-09

3.2.4 Test Method

This test was performed in accordance with ANSI C63.10, clause 6.10.5.

Plots for average measurements were taken in accordance with ANSI C63.10 clause 4.1.4.2.3. These are shown for information purposes and were used to determine the worst case measurement point. Final average measurements were then taken in accordance with ANSI C63.10 clause 4.1.4.2.2. to obtain the measurement result recorded in the test results tables.

The following conversion can be applied to convert from dB μ V/m to μ V/m:
 $10^{(\text{Field Strength in dB}\mu\text{V/m}/20)}$.

3.2.5 Environmental Conditions

Ambient Temperature	23.0 °C
Relative Humidity	32.0 %

3.2.6 Test Results

Results are shown in chapter 3.1



FCC 47 CFR Part 15, Limit Clause 15.209

Frequency (MHz)	Field Strength ($\mu\text{V}/\text{m}$ at 3 m)
30 to 88	100
88 to 216	150
216 to 960	200
Above 960	500

Table 7

ISED Canada RSS-GEN, Limit Clause 8.9

Frequency (MHz)	Field Strength ($\mu\text{V}/\text{m}$ at 3 metres)
30-88	100
88-216	150
216-960	200
Above 960*	500

Table 8

*Unless otherwise specified, for all frequencies greater than 1 GHz, the radiated emission limits for licence-exempt radio apparatus stated in applicable RSSs (including RSS-Gen) are based on measurements using a linear average detector function having a minimum resolution bandwidth of 1 MHz. If an average limit is specified for the EUT, then the peak emission shall also be measured with instrumentation properly adjusted for such factors as pulse desensitization to ensure the peak emission is less than 20 dB above the average limit.



3.2.7 Test Location and Test Equipment Used

Radiated Tests were carried out in cabin No.8 and cabin No. 11 and conducted tests were carried out with test system TS8997.

Instrument	Manufacturer	Type No	TE No	Calibration Period (months)	Calibration Due
EMI test receiver	Rohde & Schwarz	ESW26	28268	12	2021-09-30
Trilog Antenna	Schwarzbeck	VULB9162	20116	36	2022-01-31
EMC measurement software	Rohde & Schwarz	EMC32 Emission K11 - V10.50.10	19927	---	---
Semi Anechoic Room	Albatross	Cabin No. 8	19917	36	2023-10-31
EMI test receiver	Rohde & Schwarz	ESW44	39897	12	2022-04-30
Double ridged horn antenna	Rohde & Schwarz	HF907	40089	24	2023-02-28
Loop antenna	Schwarzbeck	FMZB 1519 B	44334	36	2023-01-31
ULTRALOG Antenna	Rohde & Schwarz	HL562E	39969	36	2022-11-30
Horn Antenna with preamplifier	Rohde & Schwarz	A-INFOMW LB-180400H-KF+ TS-	43661	12	2021-10-31
EMC measurement software	Rohde & Schwarz	EMC32 Emission K11 - V10.50.10	42986	---	---
Semi Anechoic Room	Frankonia	Cabin No. 11	42961	36	2022-08-31
Spectrum Analyzer	Rohde & Schwarz	FSV40	20219	12	2022-01-31
Vector Signal Generator	Rohde & Schwarz	SMBV100A	20238	36	2022-11-30
Signal Generator	Rohde & Schwarz	SMB100A	20215	36	2023-12-31
Switching Device	Rohde & Schwarz	OSP120 I	20248	24	2022-02-28
Switching Device	Rohde & Schwarz	OSP120 II	38807	36	2023-11-30
EMC Measurement Software	Rohde & Schwarz	EMC32 TS8997 - V10.50.00	44381	---	---

Table 9

TU - Traceability Unscheduled
 O/P Mon – Output Monitored using calibrated equipment
 N/A - Not Applicable



3.3 Authorised Band Edges

3.3.1 Specification Reference

FCC 47 CFR Part 15C, ISED Canada RSS-210 and ISED Canada RSS-GEN

3.3.2 Equipment Under Test and Modification State

GCY 300-42 (Conducted Sample), S/N: 124V00222 - Modification State 0

3.3.3 Date of Test

2021-06-25

3.3.4 Test Method

Test according to FCC title 47 part 15 §15.247(d), KDB 558074 D01 DTS Meas Guidance v05 8.7 and ANSI C63.10-2013

3.3.5 Environmental Conditions


Ambient Temperature	22.0 °C
Relative Humidity	35.0 %

3.3.6 Test Results




Transmission on 2402 MHz

Band Edge Low



Transmission on 2480 MHz

Band Edge High





FCC 47 CFR Part 15, Limit Clause 15.247 (d)

20 dB below the fundamental measured in a 100 kHz bandwidth using a peak detector. If the transmitter complies with the conducted power limits, based on the use of RMS averaging over a time interval, the attenuation required shall be 30 dB below the fundamental instead of 20 dB.

3.3.7 Test Location and Test Equipment Used

Conducted test was carried out in Non-shielded room with Test system TS8997.

Instrument	Manufacturer	Type No	TE No	Calibration Period (months)	Calibration Due
Spectrum Analyzer	Rohde & Schwarz	FSV40	20219	12	2022-01-31
Vector Signal Generator	Rohde & Schwarz	SMBV100A	20238	36	2022-11-30
Signal Generator	Rohde & Schwarz	SMB100A	20215	36	2023-12-31
Switching Device	Rohde & Schwarz	OSP120 I	20248	24	2022-02-28
Switching Device	Rohde & Schwarz	OSP120 II	38807	36	2023-11-30
EMC Measurement Software	Rohde & Schwarz	EMC32 TS8997 - V10.50.00	44381	---	---

Table 10

TU - Traceability Unscheduled
 O/P Mon – Output Monitored using calibrated equipment
 N/A - Not Applicable



Product Service

3.4 Emission Bandwidth

3.4.1 Specification Reference

FCC 47 CFR Part 15C, ISED Canada RSS-210 and ISED Canada RSS-GEN

3.4.2 Equipment Under Test and Modification State

GCY 300-42 (Conducted Sample), S/N: 124V00222 - Modification State 0

3.4.3 Date of Test

2021-06-25

3.4.4 Test Method

Test according to FCC title 47 part 15 §15.247(a), KDB 558074 D01 DTS Meas Guidance v05 and ANSI C63.10-2013 11.8.1

3.4.5 Environmental Conditions

Ambient Temperature 22.0 °C
Relative Humidity 35.0 %


3.4.6 Test Results

Frequency (MHz)	20 dB Bandwidth (MHz)	6 dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Limit
2402	1.100	0.752	1.093	≥ 500 kHz
2442	1.100	0.792	1.068	≥ 500 kHz
2480	1.100	0.792	1.143	≥ 500 kHz




Transmission on 2402 MHz

20 dB Bandwidth



20dB-BW, 2402 MHz,


6 dB Bandwidth



6dB-BW, 2402 MHz



99 % Bandwidth




99%-BW, 2402 MHz




Transmission on 2440 MHz

20 dB Bandwidth




20dB-BW, 2440 MHz

6 dB Bandwidth



6dB-BW, 2440 MHz




99%-BW, 2440 MHz




Transmission on 2480 MHz

20 dB Bandwidth




20dB-BW, 2480 MHz

6 dB Bandwidth



6dB-BW, 2480 MHz



99%-BW, 2480 MHz

FCC 47 CFR Part 15, Limit Clause 15.247(a)(2) and ISED Canada RSS-210, Clause 5.2(a)

The minimum 6 dB Bandwidth shall be at least 500 kHz.



3.4.7 Test Location and Test Equipment Used

Conducted test was carried out in Non-shielded room with Test system TS8997.

Instrument	Manufacturer	Type No	TE No	Calibration Period (months)	Calibration Due
Spectrum Analyzer	Rohde & Schwarz	FSV40	20219	12	2022-01-31
Vector Signal Generator	Rohde & Schwarz	SMBV100A	20238	36	2022-11-30
Signal Generator	Rohde & Schwarz	SMB100A	20215	36	2023-12-31
Switching Device	Rohde & Schwarz	OSP120 I	20248	24	2022-02-28
Switching Device	Rohde & Schwarz	OSP120 II	38807	36	2023-11-30
EMC Measurement Software	Rohde & Schwarz	EMC32 TS8997 - V10.50.00	44381	---	---

Table 11

TU - Traceability Unscheduled

O/P Mon – Output Monitored using calibrated equipment

N/A - Not Applicable



Product Service

3.5 Power Spectral Density

3.5.1 Specification Reference

FCC 47 CFR Part 15C, ISED Canada RSS-210 and ISED Canada RSS-GEN

3.5.2 Equipment Under Test and Modification State

GCY 300-42 (Conducted Sample), S/N: 124V00222 - Modification State 0

3.5.3 Date of Test

2021-06-25

3.5.4 Test Method

This test was performed in accordance with ANSI C63.10, clause 11.10.2.

3.5.5 Environmental Conditions

Ambient Temperature 22.0 °C
Relative Humidity 35.0 %

3.5.6 Test Results

Frequency (MHz)	PSD (dBm)	Limit (dBm)
2402	-10.59	8.0
2440	-10.87	8.0
2480	-11.08	8.0



FCC 47 CFR Part 15, Limit Clause 15.247 (e)

The power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

3.5.7 Test Location and Test Equipment Used

Conducted test was carried out in Non-shielded room with Test system TS8997.

Instrument	Manufacturer	Type No	TE No	Calibration Period (months)	Calibration Due
Spectrum Analyzer	Rohde & Schwarz	FSV40	20219	12	2022-01-31
Vector Signal Generator	Rohde & Schwarz	SMBV100A	20238	36	2022-11-30
Signal Generator	Rohde & Schwarz	SMB100A	20215	36	2023-12-31
Switching Device	Rohde & Schwarz	OSP120 I	20248	24	2022-02-28
Switching Device	Rohde & Schwarz	OSP120 II	38807	36	2023-11-30
EMC Measurement Software	Rohde & Schwarz	EMC32 TS8997 - V10.50.00	44381	---	---

Table 12

TU - Traceability Unscheduled
O/P Mon – Output Monitored using calibrated equipment
N/A - Not Applicable



Product Service

3.6 Maximum Conducted Output Power

3.6.1 Specification Reference

FCC 47 CFR Part 15C, ISED Canada RSS-210 and ISED Canada RSS-GEN

3.6.2 Equipment Under Test and Modification State

GCY 300-42 (Conducted Sample), S/N: 124V00222 - Modification State 0

3.6.3 Date of Test

2021-06-25

3.6.4 Test Method

This test was performed in accordance with ANSI C63.10, clause 11.9.1.1.

3.6.5 Environmental Conditions

Ambient Temperature	22.0 °C
Relative Humidity	35.0 %



3.6.6 Test Results

Frequency (MHz)	Peak Power (dBm)	Limit Max (dBm)
2402	-0.80	30
2440	-0.70	30
2480	-0.90	30

FCC 47 CFR Part 15, Limit Clause 15.247 (b)(3)

For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt.

3.6.7 Test Location and Test Equipment Used

Conducted test was carried out in Non-shielded room with Test system TS8997.

Instrument	Manufacturer	Type No	TE No	Calibration Period (months)	Calibration Due
Spectrum Analyzer	Rohde & Schwarz	FSV40	20219	12	2022-01-31
Vector Signal Generator	Rohde & Schwarz	SMBV100A	20238	36	2022-11-30
Signal Generator	Rohde & Schwarz	SMB100A	20215	36	2023-12-31
Switching Device	Rohde & Schwarz	OSP120 I	20248	24	2022-02-28
Switching Device	Rohde & Schwarz	OSP120 II	38807	36	2023-11-30
EMC Measurement Software	Rohde & Schwarz	EMC32 TS8997 - V10.50.00	44381	---	---

Table 13

TU - Traceability Unscheduled
 O/P Mon – Output Monitored using calibrated equipment
 N/A - Not Applicable



3.7 Transmitter frequency stability

3.7.1 Specification Reference

RSS-Gen

3.7.2 Equipment Under Test and Modification State

GCY 300-42 (Conducted Sample), S/N: 124V00222 - Modification State 0

3.7.3 Date of Test

2021-06-25

3.7.4 Test Method

RSS-Gen, Issue 5, March 2019, chapter 6.11


3.7.5 Environmental Conditions


Ambient Temperature 22.0 °C
Relative Humidity 35.0 %

3.7.6 Test Results

Note: - Measured Frequency Error does not affect any band edge requirements.
- Measurement was performed with modulated transmitter signal

Sample screenshots:





3.7.7 Test Location and Test Equipment Used

Conducted test was carried out in Non-shielded room with Test system TS8997.

Instrument	Manufacturer	Type No	TE No	Calibration Period (months)	Calibration Due
Spectrum Analyzer	Rohde & Schwarz	FSV40	20219	12	2022-01-31
Vector Signal Generator	Rohde & Schwarz	SMBV100A	20238	36	2022-11-30
Signal Generator	Rohde & Schwarz	SMB100A	20215	36	2023-12-31
Switching Device	Rohde & Schwarz	OSP120 I	20248	24	2022-02-28
Switching Device	Rohde & Schwarz	OSP120 II	38807	36	2023-11-30
EMC Measurement Software	Rohde & Schwarz	EMC32 TS8997 - V10.50.00	44381	---	---

Table 14

TU - Traceability Unscheduled
 O/P Mon – Output Monitored using calibrated equipment
 N/A - Not Applicable



4 Measurement Uncertainty

The measurement uncertainty in the laboratory is less than or equal to the maximum measurement uncertainty according to EN 55016-4-2: 2011 + A1 + A2 + AC and CISPR16-4-2: 2011 + A1 + A2 + Cor1 (UCISPR). This normative regulation means that the measured value is also the value to be assessed in relation to the limit value.

For a 95% confidence level, the measurement uncertainties for defined systems are:

Radio Testing			
Test Name	kp	Expanded Uncertainty	Note
Occupied Bandwidth	2.0	±1.14 %	2
RF-Frequency error	1.96	±1 · 10 ⁻⁷	7
RF-Power, conducted carrier	2	±0.079 dB	2
RF-Power uncertainty for given BER	1.96	+0.94 dB / -1.05	7
RF power, conducted, spurious emissions	1.96	+1.4 dB / -1.6 dB	7
RF power, radiated			
25 MHz – 4 GHz	1.96	+3.6 dB / -5.2 dB	8
1 GHz – 18 GHz	1.96	+3.8 dB / -5.6 dB	8
18 GHz – 26.5 GHz	1.96	+3.4 dB / -4.5 dB	8
40 GHz – 170 GHz	1.96	+4.2 dB / -7.1 dB	8
Spectral Power Density, conducted	2.0	±0.53 dB	2
Maximum frequency deviation			
300 Hz – 6 kHz	2	±2,89 %	2
6 kHz – 25 kHz	2	±0.2 dB	2
Maximum frequency deviation for FM	2	±2,89 %	2
Adjacent channel power 25 MHz – 1 GHz	2	±2.31 %	2
Temperature	2	±0.39 K	4
(Relative) Humidity	2	±2.28 %	2
DC- and low frequency AC voltage			
DC voltage	2	±0.01 %	2
AC voltage up to 1 kHz	2	±1.2 %	2
Time	2	±0.6 %	2

Table 15



Radio Interference Emission Testing			
Test Name	kp	Expanded Uncertainty	Note
Conducted Voltage Emission			
9 kHz to 150 kHz (50Ω/50μH AMN)	2	± 3.8 dB	1
150 kHz to 30 MHz (50Ω/50μH AMN)	2	± 3.4 dB	1
100 kHz to 200 MHz (50Ω/5μH AMN)	2	± 3.6 dB	1
Discontinuous Conducted Emission			
9 kHz to 150 kHz (50Ω/50μH AMN)	2	± 3.8 dB	1
150 kHz to 30 MHz (50Ω/50μH AMN)	2	± 3.4 dB	1
Conducted Current Emission			
9 kHz to 200 MHz	2	± 3.5 dB	1
Magnetic Fieldstrength			
9 kHz to 30 MHz (with loop antenna)	2	± 3.9 dB	1
9 kHz to 30 MHz (large-loop antenna 2 m)	2	± 3.5 dB	1
Radiated Emission			
Test distance 1 m (ALSE)			
9 kHz to 150 kHz	2	± 4.6 dB	1
150 kHz to 30 MHz	2	± 4.1 dB	1
30 MHz to 200 MHz	2	± 5.2 dB	1
200 MHz to 2 GHz	2	± 4.4 dB	1
2 GHz to 3 GHz	2	± 4.6 dB	1
Test distance 3 m			
30 MHz to 300 MHz	2	± 4.9 dB	1
300 MHz to 1 GHz	2	± 5.0 dB	1
1 GHz to 6 GHz	2	± 4.6 dB	1
Test distance 10 m			
30 MHz to 300 MHz	2	± 4.9 dB	1
300 MHz to 1 GHz	2	± 4.9 dB	1
Radio Interference Power			
30 MHz to 300 MHz	2	± 3.5 dB	1
Harmonic Current Emissions			4
Voltage Changes, Voltage Fluctuations and Flicker			4

Table 16



Immunity Testing			
Test Name	kp	Expanded Uncertainty	Note
Electrostatic Discharges			4
Radiated RF-Field			
Pre-calibrated field level	2	+32.2 / -24.3 %	5
Dynamic feedback field level	2.05	+21.2 / -17.5 %	3
Electrical Fast Transients (EFT) / Bursts			4
Surges			4
Conducted Disturbances, induced by RF-Fields			
via CDN	2	+15.1 / -13.1 %	6
via EM clamp	2	+42.6 / -29.9 %	6
via current clamp	2	+43.9 / -30.5 %	6
Power Frequency Magnetic Field	2	+20.7 / -17.1 %	2
Pulse Magnetic Field			4
Voltage Dips, Short Interruptions and Voltage Variations			4
Oscillatory Waves		a	4
Conducted Low Frequency Disturbances			
Voltage setting	2	± 0.9 %	2
Frequency setting	2	± 0.1 %	2
Electrical Transient Transmission in Road Vehicles			4

Table 17

Note 1:

The expanded uncertainty reported according to CISPR 16-4-2:2003-11 is based on a standard uncertainty multiplied by a coverage factor of $kp = 2$, providing a level of confidence of $p = 95.45\%$

Note 2:

The expanded uncertainty reported according to UKAS Lab 34 (Edition 1, 2002-08) is based on a standard uncertainty multiplied by a coverage factor of $kp = 2$, providing a level of confidence of $p = 95.45\%$

Note 3:

The expanded uncertainty reported according to UKAS Lab 34 (Edition 1, 2002-08) is based on a standard uncertainty multiplied by a coverage factor of $kp = 2.05$, providing a level of confidence of $p = 95.45\%$

Note 4:

It has been demonstrated that the used test equipment meets the specified requirements in the standard with at least a 95%confidence.

Note 5:

The expanded uncertainty reported according to IEC 61000-4-3 is based on a standard uncertainty multiplied by a coverage factor of $kp = 2$, providing a level of confidence of $p = 95.45\%$

Note 6:

The expanded uncertainty reported according to IEC 61000-4-6 is based on a standard uncertainty multiplied by a coverage factor of $kp = 2$, providing a level of confidence of $p = 95.45\%$

Note 7:

The expanded uncertainty reported according ETSI TR 100 028 V1.4.1 (all parts) to is based on a standard uncertainty multiplied by a coverage factor of $kp = 1.96$, providing a level of confidence of $p = 95.45\%$

Note 8:

The expanded uncertainty reported according to ETSI TR 102 273 V1.2.1 (all parts) is based on a standard uncertainty multiplied by a coverage factor of $kp = 1.96$, providing a level of confidence of $p = 95.45\%$