
Appendix for the Report

Dosimetric Assessment of the Avaya Tenovis BlueVoice L Home (FCC ID: TYM-BLUEVOICEL)

According to the FCC Requirements

SAR Distribution Plots

July 10, 2006
IMST GmbH
Carl-Friedrich-Gauß-Str. 2
D-47475 Kamp-Lintfort

Customer
Phoenix Testlab GmbH
Königswinkel 10
D-32825 Blomberg

The test results only relate to the items tested.
This report shall not be reproduced except in full without the written
approval of the testing laboratory.

Table of Contents

1 SAR DISTRIBUTION PLOTS, BODY MEASUREMENTS 3

2 SAR Z-AXIS SCANS (VALIDATION) 7

3 SAR Z-AXIS SCANS (MEASUREMENTS)..... 8

1 SAR Distribution Plots, Body Measurements

Test Laboratory: IMST GmbH, DASY Blue (I); File Name: [Tenb2hl_1.da4](#)

DUT: Tenovis ; Type: Blue Voice L; Serial: 00 07 3b 00 0 C0 EWM01 04 NR16

Program Name: Body Worn

Communication System: Bluetooth; Frequency: 2402 MHz; Duty Cycle: 1:1.2

Medium parameters used (interpolated): $f = 2402$ MHz; $\sigma = 2.03$ mho/m; $\epsilon_r = 52.5$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(7.58, 7.58, 7.58); Calibrated: 23.09.2005

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE3 Sn335; Calibrated: 09.03.2006

- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176

- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Body Worn/Area Scan (9x14x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 1.46 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.96 V/m; Power Drift = 0.192 dB

Peak SAR (extrapolated) = 3.58 W/kg

SAR(1 g) = 1.46 mW/g; SAR(10 g) = 0.601 mW/g

Maximum value of SAR (measured) = 1.68 mW/g




Fig. 1: SAR distribution for Bluetooth, channel 0, body worn configuration, display towards the ground, without accessory and 0 mm distance (July 06, 2006; Ambient Temperature: 22.1° C; Liquid Temperature: 21.5° C).

Test Laboratory: IMST GmbH, DASY Blue (I); File Name: [Tenb2hl 2 HS.da4](#)

DUT: Tenovis ; Type: Blue Voice L; Serial: 00 07 3b 00 0 C0 EWM01 04 NR16

Program Name: Body Worn

Communication System: Bluetooth; Frequency: 2402 MHz; Duty Cycle: 1:1.2

Medium parameters used (interpolated): $f = 2402$ MHz; $\sigma = 2.03$ mho/m; $\epsilon_r = 52.3$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(7.58, 7.58, 7.58); Calibrated: 23.09.2005

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE3 Sn335; Calibrated: 09.03.2006

- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176

- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Body Worn/Area Scan (9x14x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 1.43 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 6.99 V/m; Power Drift = -0.084 dB

Peak SAR (extrapolated) = 3.57 W/kg

SAR(1 g) = 1.49 mW/g; SAR(10 g) = 0.611 mW/g

Maximum value of SAR (measured) = 1.77 mW/g




Fig. 2: SAR distribution for Bluetooth, channel 0, body worn configuration, display towards the ground, with headset and 0 mm distance (July 06, 2006; Ambient Temperature: 22.1° C; Liquid Temperature: 21.5° C).

Test Laboratory: IMST GmbH, DASY Blue (I); File Name: [Tenb2hl 3 HS Clip.da4](#)

DUT: Tenovis ; Type: Blue Voice L; Serial: 00 07 3b 00 0 C0 EWM01 04 NR16

Program Name: Body Worn

Communication System: Bluetooth; Frequency: 2402 MHz; Duty Cycle: 1:1.2

Medium parameters used (interpolated): $f = 2402$ MHz; $\sigma = 2.03$ mho/m; $\epsilon_r = 52.5$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(7.58, 7.58, 7.58); Calibrated: 23.09.2005

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE3 Sn335; Calibrated: 09.03.2006

- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176

- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Body Worn/Area Scan (9x14x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 1.05 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 8.30 V/m; Power Drift = 0.003 dB

Peak SAR (extrapolated) = 2.23 W/kg

SAR(1 g) = 1.05 mW/g; SAR(10 g) = 0.463 mW/g

Maximum value of SAR (measured) = 1.21 mW/g




Fig. 3: SAR distribution for Bluetooth, channel 0, body worn configuration, display towards the ground, with headset and clip, with 3 mm distance (July 06, 2006; Ambient Temperature: 22.0° C; Liquid Temperature: 21.5° C).

Test Laboratory: IMST GmbH, DASY Blue (I); File Name: [Tenb2hm 4 HS Tasche.da4](#)

DUT: Tenovis ; Type: Blue Voice L; Serial: 00 07 3b 00 0 C0 EWM01 04 NR16

Program Name: Body Worn

Communication System: Bluetooth; Frequency: 2480 MHz; Duty Cycle: 1:1.2

Medium parameters used (interpolated): $f = 2480$ MHz; $\sigma = 2.03$ mho/m; $\epsilon_r = 52.2$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: EX3DV4 - SN3536; ConvF(7.58, 7.58, 7.58); Calibrated: 23.09.2005

- Sensor-Surface: 4mm (Mechanical Surface Detection)

- Electronics: DAE3 Sn335; Calibrated: 09.03.2006

- Phantom: SAM Glycol 1176; Type: Speag; Serial: 1176

- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 171

Body Worn/Area Scan (9x14x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.036 mW/g

Body Worn/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.09 V/m; Power Drift = -0.114 dB

Peak SAR (extrapolated) = 0.059 W/kg

SAR(1 g) = 0.026 mW/g; SAR(10 g) = 0.010 mW/g

Maximum value of SAR (measured) = 0.035 mW/g




Fig. 4: SAR distribution for Bluetooth, channel 39, body worn configuration, display towards the ground, with headset and leather case and rotation clip, with 30 mm distance (July 06, 2006; Ambient Temperature: 22.0° C; Liquid Temperature: 21.4° C).

2 SAR z-axis scans (Validation)




Fig. 5: SAR versus liquid depth, 2450 MHz, body (July 06, 2006; Ambient Temperature: 22.5° C; Liquid Temperature : 21.4° C).

3 SAR z-axis scans (Measurements)

The following picture shows the plot of SAR versus liquid depth for the worst case values.




Fig. 6: SAR versus liquid depth, body: Bluetooth 2450, channel 0, headset and 0 mm distance (July 06, 2006; Ambient Temperature: 22.° C; Liquid Temperature: 21.5° C).