## Series Part Numbers

S141AT-2450	SMA Plug Reverse Thread S141AT-2450	АТ
S141AH-2450	SMA Plug Reverse Polarity S141AH-2450	АН
S141AM-2450	SMA Plug	AM
P/N	Description	-XX-

#### Electrical Properties:

Frequency Range: 2.4~2.5 GHz Impedance: 50Ω nominal VSWR: <2.0:1

Gain: 2 dBi
Radiation: Omni
Polarization: Vertical

Half Wave Dipole

Wave:

### Mechanical Properties:

Connector\*: SMA type


Material: Whip:

Polyurethene(Black)

Operation Temp.: -20°C to +65°C Storage Temp.: -30°C to +75°C

\*Connector is covered by the overmold.

# This is a RoHS compliant product.



## Connector Interface



SMA Plug (AM)




SMA Plug Reverse Polarity
(AH)



	SMA
_	Plug R
AT)	Reverse
	Thread


### E-Plane Pattern @ 2.45GHz



Ø0.31(8)

### H-Plane Pattern @ 2.45GHz

4.0(101)



	in (mm)		TITLE	
1	DWG NO		!	2.4G
		UNIT DWG NO S141XX-2450	-141 Model	2 4GHz Straight Antenna
			01/08/06	Rev. Date   SHEET
			1 of 1	SHEET

NEARSON

SCALE none