



**EMC Technologies Pty Ltd**  
ABN 82 057 105 549  
57 Assembly Drive  
Tullamarine Victoria Australia 3043

Ph: + 613 9335 3333  
Fax: + 613 9338 9260  
email: melb@emctech.com.au

## **SAR Test Report**

**Report Number: M060235**

**Test Sample:** THURAYA Satellite Phone

**Model Number:** SG-2520

**FCC ID:** TZ5SO-2510

**Tested For:** Asia Pacific Satellite Industries Co.,  
Ltd.

**Date of Issue:** 4<sup>th</sup> April 2006

EMC Technologies Pty Ltd reports apply only to the specific samples tested under stated test conditions. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. EMC Technologies Pty Ltd shall have no liability for any deductions, inferences or generalisations drawn by the client or others from EMC Technologies Pty Ltd issued reports. This report shall not be used to claim, constitute or imply product endorsement by EMC Technologies Pty Ltd.



NATA Accredited Laboratory  
Number: 5292

The tests, calibrations or measurements covered by this document have been performed in accordance with NATA requirements, which include the requirements of ISO/IEC 17025 and are traceable to national standards of measurement. This document shall not be reproduced, except in full. The certificate on page 2 may be reproduced in full.

## CONTENTS

<b>CONTENTS</b> .....	<b>2</b>
<b>1.0 GENERAL INFORMATION</b> .....	<b>3</b>
<b>2.0 DESCRIPTION OF DEVICE</b> .....	<b>4</b>
2.1 Description of Test Sample.....	4
2.2 Test sample Accessories.....	4
2.2.1 Battery Types .....	4
2.3 Test Signal, Frequency and Output Power .....	4
2.4 Conducted Power Measurements.....	4
2.5 Battery Status .....	5
2.5 Details of Test Laboratory.....	5
2.5.1 Location.....	5
2.5.2 Accreditations .....	5
2.5.3 Environmental Factors.....	5
<b>3.0 DESCRIPTION OF SAR MEASUREMENT SYSTEM</b> .....	<b>6</b>
3.1 Probe Positioning System.....	6
3.2 E-Field Probe Type and Performance.....	6
3.3 Data Acquisition Electronics .....	6
3.4 Calibration and Validation Procedures and Data .....	6
3.4.1 Validation Results (1640 MHz) .....	6
3.4.2 Deviation from reference validation values .....	7
3.4.3 Liquid Depth 15cm.....	7
3.5 Phantom Properties (Size, Shape, Shell Thickness).....	7
3.6 Tissue Material Properties .....	8
3.6.1 Liquid Temperature and Humidity.....	8
3.7 Simulated Tissue Composition Used for SAR Test.....	8
3.8 Device Holder for DASY4 .....	8
<b>4.0 SAR MEASUREMENT PROCEDURE USING DASY4</b> .....	<b>9</b>
<b>5.0 MEASUREMENT UNCERTAINTY</b> .....	<b>10</b>
<b>7.0 SAR TEST METHOD</b> .....	<b>13</b>
7.1 Description of the Test Positions .....	13
7.1.1 “Touch Position” .....	13
7.1.2 “Tilted Position” .....	13
7.2 List of All Test Cases (Antenna In/Out, Test Frequencies, User Modes) .....	13
7.3 FCC RF Exposure Limits for Occupational/ Controlled Exposure .....	13
7.4 FCC RF Exposure Limits for Un-controlled/Non-occupational .....	13
<b>8.0 SAR MEASUREMENT RESULTS</b> .....	<b>14</b>
<b>9.0 COMPLIANCE STATEMENT</b> .....	<b>14</b>
<b>APPENDIX A1 Test Sample Photographs</b> .....	<b>15</b>
<b>Appendix A2 Test Setup Photographs</b> .....	<b>16</b>
<b>Appendix A3 Test Setup Photographs</b> .....	<b>17</b>
<b>Appendix A4 Test Setup Photographs</b> .....	<b>18</b>
<b>Appendix A5 Test Setup Photographs</b> .....	<b>19</b>
<b>APPENDIX B PLOTS OF THE SAR MEASUREMENTS</b> .....	<b>20</b>

**SAR EVALUATION**  
THURAYA Satellite Phone, **Model:** SG-2520  
**Report Number:** M060235  
**FCC ID:** TZ5SO-2510

## 1.0 GENERAL INFORMATION

**Test Sample:** THURAYA Satellite Phone  
**Model Number:** SG-2520  
**IMEI Number:** 35601300-030053-6  
**FCC ID:** TZ5SO-2510  
**Device Category:** Portable Transmitter  
**Test Device:** Production Unit / Prototype Sample  
**RF exposure Category:** General Public/Unaware user


**Tested for:** Asia Pacific Satellite Industries Co., Ltd.  
**Address:** 9FL, IT Castle 2-Dong, #550-1, Gasan-Dong,  
GeumCheon-Gu, Seoul, Korea  
**Contact:** Sung-Hee, Lee  
**Phone:** +82-2-2026-7893  
**Email:** [shlee@apsat.co.kr](mailto:shlee@apsat.co.kr)

**Test Standard/s:** Evaluating Compliance with FCC Guidelines For Human Exposure to  
Radiofrequency Electromagnetic Fields  
Supplement C (Edition 01-01) to OET Bulletin 65 (Edition 97-01)

**Statement Of Compliance:** The THURAYA Satellite Phone, model SG-2520. Complied with the  
FCC General public/uncontrolled RF exposure limits of 1.6mW/g per  
requirements of 47CFR2.1093(d).

**Test Dates:** 16<sup>th</sup> – 17<sup>th</sup> February 2006

**Test Officer:**   
**Peter Jakubiec**  
Assoc Dip Elec Eng

**Authorised Signature:**   
**Aaron Sargent B.Eng**  
EMR Engineer

## 2.0 DESCRIPTION OF DEVICE

### 2.1 Description of Test Sample

The device tested was a THURAYA Satellite Phone, Model: SG-2520 operating in 1626 MHz to 1660 MHz frequency band. The test device was tested in the Touch and Tilted Positions with the antenna retracted and extended.

**Table: EUT Parameters**

Operating Mode during Testing	: See Clause 2.3
Operating Mode production sample	: Continuous Transmission
Modulation:	: $\pi/4$ -CQPSK
Device Power Rating for test sample and identical production unit	: 32.5 dBm
Device Dimensions (LxWxH)	: 118x53x24mm
Antenna type	: Extendable
Applicable Head Configurations	: Touch and Tilted
Applicable Body Worn-Configurations	: Not tested at Customer's request
Battery Options	: One Battery Type

### 2.2 Test sample Accessories

#### 2.2.1 Battery Types

A 3.7V 1280 mAh Li-Poly Battery Pack is used to power the THURAYA Satellite Phone, Model: SG-2520. SAR measurements were performed with a standard 3.7 V battery.

### 2.3 Test Signal, Frequency and Output Power

The test was performed on Iridium Satellite Phone, for this evaluation. The test sample operates in the 1626 MHz to 1660 MHz frequency band. The test sample was configured into a test mode and was put into maximum continuous transmit mode for the duration of each SAR scan. The channels utilised in the measurements were the traffic channels shown in the table below.

**Table: Test Frequencies**

Frequency Range	Traffic Channels	Band Power Class	Nominal Power (dBm)
1626 – 1660 MHz	0001, 0544, and 1087	N/A	32.5

### 2.4 Conducted Power Measurements

The conducted power of the EUT was measured in the 1626 MHz to 1660 MHz frequency range with a calibrated Power Meter. The results of this measurement are listed in table below.

**Table: Frequency and Output Power**

Channel	Channel Frequency MHz	Maximum Conducted Output Power dBm
0001	1626.0	32.36
0544	1643.0	32.40
1087	1660.0	32.24

**Note:** The loss's due to cabling and attenuation has been taken into account.

## 2.5 Battery Status

The device battery was fully charged prior to commencement of measurement. Each SAR test was completed within 30 minutes. The battery condition was monitored by measuring the RF power at a defined position inside the phantom before the commencement of each test and again after the completion of the test.

**Table: Battery Details**

<b>Battery #1:</b>	Li-Poly 3.7V 1280 mAh	<b>Battery #2:</b>	Li-Poly 3.7V 1280 mAh
<b>Model No.:</b>	N/A	<b>Model No.:</b>	N/A
<b>Serial No.:</b>	N/A	<b>Serial No.:</b>	N/A

## 2.6 Details of Test Laboratory

### 2.6.1 Location

EMC Technologies Pty Ltd - ACN/ABN: 82057105549  
57 Assembly Drive  
Tullamarine, (Melbourne) Victoria  
Australia 3043

**Telephone:** +61 3 9335 3333  
**Facsimile:** +61 3 9338 9260  
**email:** [melb@emctech.com.au](mailto:melb@emctech.com.au)  
**website:** [www.emctech.com.au](http://www.emctech.com.au)

### 2.6.2 Accreditations

EMC Technologies Pty. Ltd. is accredited by the National Association of Testing Authorities, Australia (NATA). **NATA Accredited Laboratory Number: 5292**

EMC Technologies Pty Ltd is NATA accredited for the following standards:

<b>ARPANSA Standard</b>	RF and microwave radiation hazard measurement
<b>AS/NZS 2772.2:</b>	
<b>ACA:</b>	Radio communications (Electromagnetic Radiation - Human Exposure) Standard 2003
<b>FCC:</b>	Guidelines for Human Exposure to RF Electromagnetic Field OET65C 01/01
<b>CENELEC:</b>	ES59005: 1998
<b>EN 50360: 2001</b>	Product standard to demonstrate the compliance of mobile phones with the basic restrictions related to human exposure to electromagnetic fields (300 MHz – 3 GHz)
<b>EN 50361: 2001</b>	Basic standard for the measurement of Specific Absorption Rate related to human exposure to electromagnetic fields from mobile phones (300MHz – 3GHz)
<b>IEEE 1528: 2003</b>	Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head Due to Wireless Communications Devices: Measurement Techniques.

Refer to NATA website [www.nata.asn.au](http://www.nata.asn.au) for the full scope of accreditation.

### 2.6.3 Environmental Factors

The measurements were performed in a shielded room with no background network signals. The temperature in the laboratory was controlled to within  $21 \pm 1$  °C, the humidity was 62 to 64 %. The liquid parameters were measured prior to the commencement of the tests. Tests were performed to check that reflections within the environment did not influence the SAR measurements. The noise floor of the DASY4 SAR measurement system using the SN1380 probe is less than  $5\mu\text{V}$  in both air and liquid mediums.

### 3.0 DESCRIPTION OF SAR MEASUREMENT SYSTEM

#### 3.1 Probe Positioning System

The measurements were performed with the state of the art automated near-field scanning system **DASY4 Version V4.5 Build 19** from Schmid & Partner Engineering AG (SPEAG). The system is based on a high precision 6-axis robot (working range greater than 1.1m), which positions the SAR measurement probes with a positional repeatability of better than  $\pm 0.02$  mm. The DASY4 fully complies with the OET65 C (01-01), IEEE 1528 and EN50361 SAR measurement requirements.

#### 3.2 E-Field Probe Type and Performance

The SAR measurements were conducted with the dosimetric probe ET3DV6 Serial: 1380 (manufactured by SPEAG) designed in the classical triangular configuration and optimised for dosimetric evaluation. The probe has been calibrated and found to be accurate to better than  $\pm 0.25$  dB. The probe is suitable for measurements close to material discontinuity at the surface of the phantom. The sensors of the probe are directly loaded with Schottky diodes and connected via highly resistive lines (length = 300 mm) to the data acquisition unit.

#### 3.3 Data Acquisition Electronics

The data acquisition electronics (DAE3) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. The input impedance of the DAE3 box is 200 M $\Omega$ ; the inputs are symmetrical and floating. Common mode rejection is above 80dB. Transmission to the PC-card is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock.

The mechanical probe-mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection.

#### 3.4 Calibration and Validation Procedures and Data

Prior to the SAR assessment, the system validation kit was used to verify that the DASY4 was operating within its specifications. The validation was performed at 1640 MHz with the SPEAG D1640V2 calibrated dipole.

The validation dipoles are highly symmetric and matched at the centre frequency for the specified liquid and distance to the phantom. The accurate distance between the liquid surface and the dipole centre is achieved with a distance holder that snaps onto the dipole.

System validation is performed by feeding a known power level into a reference dipole, set at a known distance from the phantom. The measured SAR is compared to the theoretically derived level.

##### 3.4.1 Validation Results (1640 MHz)

The following table lists the dielectric properties of the tissue simulating liquid measured prior to each SAR validation. The results of the validation for each day are listed in columns 5 and 6. The forward power into the reference dipole for each SAR validation was adjusted to 250 mW.

**Table: Validation Results (SPEAG calibrated dipoles)**

1 Validation Date	2 Frequency (MHz)	3 $\epsilon_r$ (measured)	4 $\sigma$ (mho/m) (measured)	5 Measured SAR 1g	6 Measured SAR 10g
16 <sup>th</sup> Feb. 2006	1640	40.3	1.25	8.99	4.76
17 <sup>th</sup> Feb. 2006	1640	40.3	1.26	8.85	4.70

### 3.4.2 Deviation from reference validation values

The SPEAG calibration reference SAR value is the SAR validation result obtained in a specific dielectric liquid using the validation dipole (DV1640V2) during calibration. The measured one-gram SAR should be within 10% of the expected target reference values shown in table below.

**Table: Deviation from reference validation values**


Validation Frequency	Measured SAR 1g (input power = 250mW)	Measured SAR 1g (Normalized to 1W)	SPEAG Calibration Reference SAR Value 1g (mW/g)	Deviation From SPEAG 1g (%)
1640 MHz	8.99	35.9	33.0	8.97
1640 MHz	8.85	35.4	33.0	7.27

**Note:** All reference validation values are referenced to 1W input power.

### 3.4.3 Liquid Depth 15cm

During the SAR measurement process the liquid level was maintained to a level of 15cm with a tolerance of  $\pm 0.5$ cm. The following photo shows the depth of the liquid maintained during the testing.

**Photo of liquid Depth in Flat Phantom**



### 3.5 Phantom Properties (Size, Shape, Shell Thickness)

The phantom used during the SAR testing in Touch, Tilted positions and the validation was the "SAM" phantom from SPEAG. The phantom thickness is 2.0mm $\pm$ 0.2 mm and was filled with the required tissue simulating liquid.

### 3.6 Tissue Material Properties

The dielectric parameters of the tissue simulating liquid were measured prior to SAR assessment using the HP85070A dielectric probe kit and HP8714B Network Analyser. The actual dielectric parameters are shown in the following table.

**Table: Measured Brain Simulating Liquid Dielectric Values**

Frequency Band	$\epsilon_r$ (measured range)	$\epsilon_r$ (target)	$\sigma$ (mho/m) (measured range)	$\sigma$ (target)	$\rho$ kg/m <sup>3</sup>
1626 MHz Brain	40.3	40.3 $\pm$ 5% (38.3 to 42.3)	1.24 to 1.25	1.29 $\pm$ 5% (1.23 to 1.35)	1000
1643 MHz Brain	40.2 to 40.3	40.3 $\pm$ 5% (38.3 to 42.3)	1.25 to 1.26	1.29 $\pm$ 5% (1.23 to 1.35)	1000
1660 MHz Brain	40.2	40.3 $\pm$ 5% (38.3 to 42.3)	1.26 to 1.27	1.29 $\pm$ 5% (1.23 to 1.35)	1000

**Note:** The brain and muscle liquid parameters were within the required tolerances of  $\pm$ 5%.

#### 3.6.1 Liquid Temperature and Humidity

The humidity and dielectric/ambient temperatures are recorded during the assessment of the tissue material dielectric parameters. The difference between the ambient temperature of the liquid during the dielectric measurement and the temperature during tests was less than  $|2|^\circ\text{C}$ .

**Table: Temperature and Humidity recorded for each day**

Date	Ambient Temperature ( $^\circ\text{C}$ )	Liquid Temperature ( $^\circ\text{C}$ )	Humidity (%)
16 <sup>th</sup> Feb. 2006	21.2	20.9	64.0
17 <sup>th</sup> Feb. 2006	21.7	21.2	62.0

### 3.7 Simulated Tissue Composition Used for SAR Test

The tissue simulating liquids are created prior to the SAR evaluation and often require slight modification each day to obtain the correct dielectric parameters.

**Table: Tissue Type: Brain @ 1600MHz**

Volume of Liquid: 30 Litres

Approximate Composition	% By Weight
Distilled Water	61.17
Salt	0.31
Bactericide	0.29
Triton X-100	38.23

\*Refer "OET Bulletin 65 97/01 P38"

### 3.8 Device Holder for DASY4

The DASY4 device holder supplied by SPEAG is designed to cope with different positions given in the standard. It has two scales for the device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear openings). The rotation centres for both scales is the ear opening. Thus the device needs no repositioning when changing the angles.

The DASY4 device holder is made of low-loss material having the following dielectric parameters: relative permittivity  $\epsilon=3$  and loss tangent  $\delta=0.02$ . The amount of dielectric material has been reduced in the closest vicinity of the device, to reduce the influence on the clamp on the test results.

Refer to Appendix A for photographs of device positioning



#### 4.0 SAR MEASUREMENT PROCEDURE USING DASY4

The SAR evaluation was performed with the SPEAG DASY4 System (**VERSION V4.5 BUILD 19**). A summary of the procedure follows:

- a) A measurement of the conducted power value at the antenna port is used as a reference value for assessing the power drop of the EUT. Also a measurement of the SAR value at a fixed location is used. The power is measured at the start of the test and then again at the end of the test.
- b) The SAR distribution at the exposed side of the head or the flat section of the flat phantom is measured at a distance of 3.9 mm from the inner surface of the shell. The area covers the entire dimension of the head and the horizontal grid spacing is 15 mm x 15 mm. The actual Area Scan has dimensions of 171 mm x 61 mm and also 131 mm x 61mm, surrounding the test device. Based on this data, the area of the maximum absorption is determined by Spline interpolation.
- c) Around this point, a volume of 30 mm x 30 mm x 30 mm is assessed by measuring 7 x 7 x 7 points. On the basis of this data set, the spatial peak SAR value is evaluated with the following procedure:
  - (i) The data at the surface are extrapolated, since the centre of the dipoles is 2.7 mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 1.3 mm. The extrapolation is based on a least square algorithm. A polynomial of the fourth order is calculated through the points in z-axis. This polynomial is then used to evaluate the points between the surface and the probe tip.
  - (ii) The maximum interpolated value is searched with a straightforward algorithm. Around this maximum the SAR values averaged over the spatial volumes (1 g and 10 g) are computed using the 3D-Spline interpolation algorithm. The 3D-Spline is composed of three one-dimensional splines with the "Not a knot"- condition (in x, y and z-direction). The volume is integrated with the trapezoidal – algorithm. One thousand points (10 x 10 x 10) are interpolated to calculate the averages.
  - (iii) All neighbouring volumes are evaluated until no neighbouring volume with a higher average value is found.
  - (iv) The SAR value at the same location as in Step (a) is again measured

## 5.0 MEASUREMENT UNCERTAINTY

The uncertainty analysis is based on the template listed in the IEEE Std 1528-2003 for both Handset SAR tests and Validation uncertainty. The measurement uncertainty of a specific device is evaluated independently and the total uncertainty for both evaluations (95% confidence level) must be less than 30%.

**Table: Uncertainty Budget for DASY4 Version V4.5 Build 19 – EUT SAR test**

a	b	c	d	e= f(d,k)	f	g	h=cxf/e	i=cxg/e	k
Uncertainty Component	Sec.	Tol. (%)	Prob. Dist.	Div.	C <sub>i</sub> (1g)	C <sub>i</sub> (10g)	1g u <sub>i</sub> (%)	10g u <sub>i</sub> (%)	v <sub>i</sub>
<b>Measurement System</b>									
Probe Calibration (k=1) (standard calibration)	E.2.1	4.8	N	1	1	1	4.8	4.8	∞
Axial Isotropy	E.2.2	4.7	R	1.73	0.707	0.707	1.9	1.9	∞
Hemispherical Isotropy	E.2.2	9.6	R	1.73	0.707	0.707	3.9	3.9	∞
Boundary Effect	E.2.3	1	R	1.73	1	1	0.6	0.6	∞
Linearity	E.2.4	4.7	R	1.73	1	1	2.7	2.7	∞
System Detection Limits	E.2.5	1	R	1.73	1	1	0.6	0.6	∞
Readout Electronics	E.2.6	1	N	1	1	1	1.0	1.0	∞
Response Time	E.2.7	0.8	R	1.73	1	1	0.5	0.5	∞
Integration Time	E.2.8	2.6	R	1.73	1	1	1.5	1.5	∞
RF Ambient Conditions	E.6.1	0.05	R	1.73	1	1	0.0	0.0	∞
Probe Positioner Mechanical Tolerance	E.6.2	0.4	R	1.73	1	1	0.2	0.2	∞
Probe Positioning with respect to Phantom Shell	E.6.3	2.9	R	1.73	1	1	1.7	1.7	∞
Extrapolation, interpolation and Integration Algorithms for Max. SAR Evaluation	E.5	1	R	1.73	1	1	0.6	0.6	∞
<b>Test Sample Related</b>									
Test Sample Positioning	E.4.2	1.61	N	1	1	1	1.6	1.6	11
Device Holder Uncertainty	E.4.1								
Output Power Variation – SAR Drift Measurement	6.6.2	4.37	R	1.73	1	1	2.5	2.5	∞
<b>Phantom and Tissue Parameters</b>									
Phantom Uncertainty (shape and thickness tolerances)	E.3.1	4	R	1.73	1	1	2.3	2.3	∞
Liquid Conductivity – Deviation from target values	E.3.2	5	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Conductivity – Measurement uncertainty	E.3.3	4.3	N	1	0.64	0.43	2.8	1.8	5
Liquid Permittivity – Deviation from target values	E.3.2	5	R	1.73	0.6	0.49	1.7	1.4	∞
Liquid Permittivity – Measurement uncertainty	E.3.3	4.3	N	1	0.6	0.49	2.6	2.1	5
Combined standard Uncertainty			RSS				<b>9.6</b>	<b>9.1</b>	154
Expanded Uncertainty (95% CONFIDENCE LEVEL)			k=2				<b>19.2</b>	<b>18.16</b>	

Estimated total measurement uncertainty for the DASY4 measurement system was  $\pm 9.6$ . The extended uncertainty (K = 2) was assessed to be  $\pm 19.2$  based on 95% confidence level. The uncertainty is not added to the measurement result.

**Table: Uncertainty Budget for DASY4 Version V4.5 Build 19 - Validation**

a	b	c	d	e= f(d,k)	f	g	h=cxf/e	i=cxg/e	k
Uncertainty Component	Sec.	Tol. (%)	Prob. Dist.	Div.	C <sub>i</sub> (1g)	C <sub>i</sub> (10g)	1g u <sub>i</sub> (%)	10g u <sub>i</sub> (%)	v <sub>i</sub>
<b>Measurement System</b>									
Probe Calibration (k=1) (standard calibration)	E.2.1	4.8	N	1	1	1	4.8	4.8	∞
Axial Isotropy	E.2.2	4.7	R	1.73	1	1	2.7	2.7	∞
Hemispherical Isotropy	E.2.2	0	R	1.73	1	1	0.0	0.0	∞
Boundary Effect	E.2.3	1	R	1.73	1	1	0.6	0.6	∞
Linearity	E.2.4	4.7	R	1.73	1	1	2.7	2.7	∞
System Detection Limits	E.2.5	1	R	1.73	1	1	0.6	0.6	∞
Readout Electronics	E.2.6	1	N	1	1	1	1.0	1.0	∞
Response Time	E.2.7	0	R	1.73	1	1	0.0	0.0	∞
Integration Time	E.2.8	0	R	1.73	1	1	0.0	0.0	∞
RF Ambient Conditions	E.6.1	0.05	R	1.73	1	1	0.0	0.0	∞
Probe Positioner Mechanical Tolerance	E.6.2	0.4	R	1.73	1	1	0.2	0.2	∞
Probe Positioning with respect to Phantom Shell	E.6.3	2.9	R	1.73	1	1	1.7	1.7	∞
Extrapolation, interpolation and Integration Algorithms for Max. SAR Evaluation	E.5	1	R	1.73	1	1	0.6	0.6	∞
<b>Test Sample Related</b>									
Dipole Axis to Liquid Surface		2	R	1.73	1	1	1.2	1.2	∞
Power Drift		4.7	R	1.73	1	1	2.7	2.7	∞
<b>Phantom and Tissue Parameters</b>									
Phantom Uncertainty (shape and thickness tolerances)	E.3.1	4	R	1.73	1	1	2.3	2.3	∞
Liquid Conductivity – Deviation from target values	E.3.2	5	R	1.73	0.6	0.43	1.7	1.2	∞
Liquid Conductivity – Measurement uncertainty	E.3.3	2.5	N	1.73	0.6	0.43	0.9	0.6	5
Liquid Permittivity – Deviation from target values	E.3.2	5	R	1.73	0.6	0.49	1.7	1.4	∞
Liquid Permittivity – Measurement uncertainty	E.3.3	2.5	N	1.73	0.6	0.49	0.9	0.7	5
Combined standard Uncertainty			RSS				<b>8.0</b>	<b>7.8</b>	154
Expanded Uncertainty (95% CONFIDENCE LEVEL)			k=2				16.0	15.63	

Estimated total measurement uncertainty for the DASY4 measurement system was  $\pm 8.0\%$ . The extended uncertainty ( $K = 2$ ) was assessed to be  $\pm 16.0\%$  based on 95% confidence level. The uncertainty is not added to the Validation measurement result.

## 6.0 EQUIPMENT LIST AND CALIBRATION DETAILS

**Table: SPEAG DASY4 Version V4.5 Build 19**

Equipment Type	Manufacturer	Model Number	Serial Number	Calibration Due	Used For this Test?
Robot - Six Axes	Staubli	RX90BL	N/A	Not applicable	Yes
Robot Remote Control	SPEAG	CS7MB	RX90B	Not applicable	Yes
SAM Phantom	SPEAG	N/A	1260	Not applicable	Yes
SAM Phantom	SPEAG	N/A	1060	Not applicable	No
Flat Phantom	AndreT	10.1	P 10.1	Not Applicable	No
Flat Phantom	AndreT	9.1	P 9.1	Not Applicable	No
Flat Phantom	SPEAG	PO1A 6mm	1003	Not Applicable	No
Data Acquisition Electronics	SPEAG	DAE3 V1	359	07-July-2006	No
Data Acquisition Electronics	SPEAG	DAE3 V1	442	08-Dec-2006	Yes
Probe E-Field - Dummy	SPEAG	DP1	N/A	Not applicable	No
Probe E-Field	SPEAG	ET3DV6	1380	14-Dec-2006	Yes
Probe E-Field	SPEAG	ET3DV6	1377	14-July-2006	No
Probe E-Field	SPEAG	ES3DV6	3029	1-Nov-2005	No
Probe E-Field	SPEAG	EX3DV4	3563	1-July-2006	No
Antenna Dipole 300 MHz	SPEAG	D300V2	1005	26-Oct-2007	No
Antenna Dipole 450 MHz	SPEAG	D450V2	1009	15-Dec-2006	No
Antenna Dipole 900 MHz	SPEAG	D900V2	047	12-July-2006	No
Antenna Dipole 1640 MHz	SPEAG	D1640V2	314	25-May-2006	Yes
Antenna Dipole 1800 MHz	SPEAG	D1800V2	242	13-July-2006	No
Antenna Dipole 2450 MHz	SPEAG	D2450V2	724	2-Nov-2006	No
Antenna Dipole 3500 MHz	SPEAG	D3500V2	1002	1-July-2007	No
Antenna Dipole 5600 MHz	SPEAG	D5GHzV2	1008	27-Oct-2007	No
RF Amplifier	EIN	603L	N/A	In test	No
RF Amplifier	Mini-Circuits	ZHL-42	N/A	In test	Yes
RF Amplifier	Mini-Circuits	ZVE-8G	N/A	In test	Yes
Synthesized signal generator	Hewlett Packard	ESG-D3000A	GB37420238	*Not Required	Yes
RF Power Meter Dual	Hewlett Packard	437B	3125012786	28-May-2006	Yes
RF Power Sensor 0.01 - 18 GHz	Hewlett Packard	8481H	1545A01634	30-May-2006	Yes
RF Power Meter Dual	Gigatronics	8542B	1830125	13-April-2006	Yes
RF Power Sensor	Gigatronics	80301A	1828805	13-April-2006	Yes
RF Power Meter Dual	Hewlett Packard	435A	1733A05847	*Not Required	Yes
RF Power Sensor	Hewlett Packard	8482A	2349A10114	*Not Required	Yes
Network Analyser	Hewlett Packard	8714B	GB3510035	31-Aug-2006	No
Network Analyser	Hewlett Packard	8753ES	JP39240130	11-Aug-2006	Yes
Dual Directional Coupler	Hewlett Packard	778D	1144 04700	In test	No
Dual Directional Coupler	NARDA	3022	75453	In test	Yes

\*Note: Reference power meter only.

## 7.0 SAR TEST METHOD

### 7.1 Description of the Test Positions

The SAR measurements are performed on the left and right sides of the head in the Touch/Tilted positions using the centre frequency of each operating band. The configuration giving the maximum mass-averaged SAR is used to test the low-end and high-end frequencies of the transmitting band. All SAR measurements were performed in the SAM phantom. See Appendix A for photos of test positions.

#### 7.1.1 “Touch Position”

The devices was positioned with the vertical centre line of the body of the device and the horizontal line crossing the centre of the ear piece in a plane parallel to the sagittal plane of the phantom. While maintaining the device in this plane, the vertical centre line was aligned with the reference plane containing the three ear and mouth reference points. (Left Ear, Right Ear and Mouth). The centre of the earpiece was then aligned with the Right Ear and Left Ear.

The phone was then moved towards the phantom with the earpiece aligned with the line between the Left Ear and the Right Ear, until the phone just touched the ear. With the device maintained in the reference plane, and the phone in contact with the ear, the bottom of the phone was moved until the front side of the phone was in contact with the cheek of the phantom, or until contact with the ear was lost.

#### 7.1.2 “Tilted Position”

The device was positioned in the “Touch” position described above. While maintaining the device in the reference plane describe above, and pivoting against the ear, the device was moved away from the mouth by an angle of 15 degrees or until contact with the ear was lost

### 7.2 List of All Test Cases (Antenna In/Out, Test Frequencies, User Modes)

The SAR was measured at three test channels for each band of operation with the test sample operating as maximum power, as specified in section 2.2. The satellite mode antenna was extended and adjusted as per user’s manual.

### 7.3 FCC RF Exposure Limits for Occupational/ Controlled Exposure

SPATIAL PEAK SAR LIMITS FOR:	
Partial-Body:	8.0 mW/g (averaged over any 1g cube of tissue)
Hands, Wrists, Feet and Ankles:	20.0 mW/g (averaged over 10g cube of tissue)

### 7.4 FCC RF Exposure Limits for Un-controlled/Non-occupational

SPATIAL PEAK SAR LIMITS FOR:	
Partial-Body:	1.6 mW/g (averaged over any 1g cube of tissue)
Hands, Wrists, Feet and Ankles:	4.0 mW/g (averaged over 10g cube of tissue)

## 8.0 SAR MEASUREMENT RESULTS

The SAR values averaged over 1 g tissue masses were determined for the sample device for the Left and Right ear configurations of the phantom. The results are given in table below.

The plots with the corresponding SAR distributions, which reveal information about the location of the maximum SAR with respect to the devices, are contained in Appendix B of this report.

**Table: SAR Measurement Results**

Test Position	Antenna	Plot Number	Test Channel	Test Freq. (MHz)	SAR Level for (1g) mW/g	DASY4 Measured Drift (dB)
Touch Left	Retracted	1	544	1643	0.187	0.083
Touch Left	Extended	2	544	1643	0.085	-0.061
Tilted Left	Retracted	3	544	1643	0.214	0.000
Tilted Left	Extended	4	001	1626	0.330	0.050
Tilted Left	Extended	5	544	1643	0.372	0.226
Tilted Left	Extended	6	1087	1660	0.315	-0.051
Touch Right	Retracted	7	544	1643	0.222	0.010
Touch Right	Extended	8	544	1643	0.058	-0.096
Tilted Right	Retracted	9	544	1643	0.212	0.189
Tilted Right	Extended	10	544	1643	0.174	-0.047

**Note:** The uncertainty of the system ( $\pm 19.2\%$ ) has not been added to the results.

The maximum measured SAR level in the 1600 MHz band was 0.372 mW/g for a 1 gram cube this value was measured in the Tilted Left position with Antenna Extended at a frequency of 1643 MHz (Channel 544).

The FCC SAR limit for Non-occupational exposure is 1.6 m W/g measurement in a 1g cube of tissue.

## 9.0 COMPLIANCE STATEMENT

The THURAYA Satellite Phone, Model SG-2520, FCC ID: TZ5SO-2510 was tested on behalf of Asia Pacific Satellite Industries Co., Ltd. It complied with the FCC SAR requirements.

The highest SAR level recorded for the 1600 MHz Satellite band was 0.372 mW/g, which is below the uncontrolled limit of 1.6 mW/g, even taking into account the measurement uncertainty of 19.2 %.

### APPENDIX A1 Test Sample Photographs

Battery 1



Battery 2



THURAYA Satellite Phone, SG-2520




THURAYA Satellite Phone, SG-2520



## Appendix A2 Test Setup Photographs

Touch Left Position - Antenna Extended




Touch Right Position - Antenna Extended





### Appendix A3 Test Setup Photographs

Tilted Left Position - Antenna Extended



Tilted Right Position - Antenna Extended




### Appendix A4 Test Setup Photographs

Tilted Left Position - Antenna Retracted




Tilted Right Position - Antenna Retracted



## Appendix A5 Test Setup Photographs

Touch Left Position - Antenna Retracted



Touch Right Position - Antenna Retracted

