


A1. Measurement result – Plot no.1


Sub-clause	: RF Output Power		
Measurement method	: Conducted measurement @ Antenna port		
Measured channel	: Lower channel (channel no. 3) = 1626.59375 MHz		
Operating condition	: Max. Power output with modulated rf-carrier		
Environment condition		Test date	: 08-21-2008
Temperature & Humidity	: 23 °C	45 %RH	
Test voltage	: 3.7 Vdc		
Test setup		Video BW	: 1000 kHz
Measured Frequency	: 1626.59375 MHz	Video-Averaging	: 1 sweep
Center frequency	: MHz	Detector mode	: 2 Pos Peak
Frequency Span	: MHz		
Resolution BW	: 100 kHz		
Remark	:		Max. Hold
Test Result	: Passed		



FCC Test Report


A1. Measurement result – Plot no.2

Sub-clause	: RF Output Power		
Measurement method	: Conducted measurement @ Antenna port		
Measured channel	: Mid channel (channel no. 544) = 1643.5 MHz		
Operating condition	: Max. Power output with modulated rf-carrier		
Environment condition		Test date	: 08-21-2008
Temperature & Humidity	: 23 °C	45 %RH	
Test voltage	: 3.7 Vdc		
Test setup		Video BW	: 1000 kHz
Measured Frequency	: 1643.5000 MHz	Video-Averaging	: 1 sweep
Center frequency	: MHz	Detector mode	: 2 Pos Peak
Frequency Span	: MHz		
Resolution BW	: 100 kHz		
Remark	:		Max. Hold
Test Result	: Passed		




A1. Measurement result – Plot no.3

Sub-clause	: RF Output Power		
Measurement method	: Conducted measurement @ Antenna port		
Measured channel	: High channel (channel no.1087) = 1660.46875 MHz		
Operating condition	: Max. Power output with modulated rf-carrier		
Environment condition		Test date	: 08-21-2008
Temperature & Humidity	: 23 °C	45 %RH	
Test voltage	: 3.7 Vdc		
Test setup		Video BW	: 1000 kHz
Measured Frequency	: 1626.59375 MHz	Video-Averaging	: 1 sweep
Center frequency	: MHz	Detector mode	: 2 Pos Peak
Frequency Span	: MHz		
Resolution BW	: 100 kHz		
Remark	:		Max. Hold
Test Result	: Passed		




A1. Measurement result – Plot no.4

Sub-clause	: Occupied Bandwidth		
Measurement method	: Conducted measurement @ Antenna port		
Measured channel	: Low channel (channel no. 3) = 1626.59375MHz		
Operating condition	: Max. Power output with modulated rf-carrier		
Environment condition		Test date	: 08-29-2008
Temperature & Humidity	: 23 °C	45 %RH	
Test voltage	: 3.7 Vdc		
Test setup		Video BW	: 3 kHz
Measured Frequency	: 1626.5 – 1660.5 MHz	Video-Averaging	: 1 sweep
Center frequency	: MHz	Detector mode	: 2 Pos Peak
Frequency Span	: MHz		Max. Hold
Resolution BW	: 3 kHz		
Remark	: The measured value is about 33.21 kHz with 3 kHz resolution		
Test Result	:		



A1. Measurement result – Plot no.5


Sub-clause	: Occupied Bandwidth			
Measurement method	: Conducted measurement @ Antenna port			
Measured channel	: Low channel (channel no. 544) = 1643.5 MHz			
Operating condition	: Max. Power output with modulated rf-carrier			
Environment condition		Test date	: 08-29-2008	
Temperature & Humidity	: 23 °C	45 %RH		
Test voltage	: 3.7 Vdc			
Test setup		Video BW	: 3 kHz	
Measured Frequency	: 1626.5 – 1660.5 MHz		Video-Averaging	: 1 sweep
Center frequency	: MHz		Detector mode	: 2 Pos Peak
Frequency Span	: MHz			Max. Hold
Resolution BW	: 3 kHz			
Remark	: The measured value is about 33.54 kHz with 3 kHz resolution			
Test Result	:			



A1. Measurement result – Plot no.6


Sub-clause	: Occupied Bandwidth		
Measurement method	: Conducted measurement @ Antenna port		
Measured channel	: Low channel (channel no. 1087) = 1660.46875 MHz		
Operating condition	: Max. Power output with modulated rf-carrier		
Environment condition		Test date	: 08-21-2008
Temperature & Humidity	: 23 °C	45 %RH	
Test voltage	: 3.7 Vdc		
Test setup		Video BW	: 3 kHz
Measured Frequency	: 1626.5 – 1660.5 MHz	Video-Averaging	: 1 sweep
Center frequency	: MHz	Detector mode	: 2 Pos Peak
Frequency Span	: MHz		Max. Hold
Resolution BW	: 3 kHz		
Remark	: The measured value is about 32.86 kHz with 3 kHz resolution		
Test Result	:		

Agilent 19:46:38 Aug 21, 2008 R T

<p>Ch Freq 1.66047 GHz Trig Free</p> <p>Occupied Bandwidth █</p>	<p>Meas Setup</p> <p>Avg Number 10 On Off</p> <p>Avg Mode Repeat Exp</p> <p>Max Hold Off On</p> <p>Occ BW % Pwr 99.00 %</p> <p>OBW Span 100.000000 kHz</p> <p>x dB -3.00 dB</p> <p>Optimize Ref Level</p>
<p>Ref 40.47 dBm Atten 40 dB</p>  <p>Center 1.660 468 8 GHz Span 100 kHz</p> <p>#Res BW 5.1 kHz #VBW 5.1 kHz Sweep 4.693 ms (1601 pts)</p>	<p>Correction</p> <p>Directional coupler : Offset : 10.5 dB -. Attenuation(10dB) : (10.2 dB) -. Test cable : (0.3 dB)</p> <p>BW correction factor : Antenna Gain : 3.0 dBi Total correction : 3.0 dB</p> <p>Measured level : Emission level : Limit</p>
<p>Occupied Bandwidth 32.8633 kHz</p> <p>Occ BW % Pwr 99.00 %</p> <p>x dB -3.00 dB</p> <p>Transmit Freq Error -273.357 Hz</p> <p>x dB Bandwidth 21.564 kHz</p>	<p>File Operation Status, C:\S10001.AMP file loaded</p>


A1. Measurement result – Plot no.7

Sub-clause	: Emission Limitations		
Measurement method	: Conducted measurement		
Measured channel	: Low channel (channel no. 3) = 1626.59375MHz		
Operating condition	: Max. Power output with modulated rf-carrier		
Environment condition		Test date	: 08-29-2008
Temperature & Humidity	: 23 °C	45 %RH	
Test voltage	: 3.7 Vdc		
Test setup		Video BW	: 3 kHz
Measured Frequency	: 1626.5 – 1660.5 MHz	Video-Averaging	: 1 sweep
Center frequency	: MHz	Detector mode	: 2 Pos Peak
Frequency Span	: MHz		Max. Hold
Resolution BW	: 10 kHz		
Remark	: Function test to verify general characteristic for measurement orientation		
Test Result	:		




A1. Measurement result – Plot no.8

Sub-clause	: Emission Limitations		
Measurement method	: Conducted measurement		
Measured channel	: Low channel (channel no. 3) = 1626.59375MHz		
Operating condition	: Max. Power output with modulated rf-carrier		
Environment condition		Test date	: 08-29-2008
Temperature & Humidity	: 23 °C	45 %RH	
Test voltage	: 3.7 Vdc		
Test setup		Video BW	: 3 kHz
Measured Frequency	: 1626.59375 Hz	Video-Averaging	: 1 sweep
Center frequency	: 1626.59375 Hz	Detector mode	: 2 Pos Peak
Frequency Span	: 500 kHz		: Max. Hold
Resolution BW	: 3 kHz		
Remark	: Carrier at the lower edge of the band. For EIRP calculation, worst case = maximum antenna gain		
Test Result	: Passed		



A1. Measurement result – Plot no.9

Sub-clause	: Emission Limitations		
Measurement method	: Conducted measurement		
Measured channel	: Low channel (channel no. 3) = 1626.59375MHz		
Operating condition	: Max. Power output with modulated rf-carrier		
Environment condition		Test date	: 08-29-2008
Temperature & Humidity	: 23 °C	45 %RH	
Test voltage	: 3.7 Vdc		
Test setup		Video BW	: 3 kHz
Measured Frequency	: 1626.5 – 1660.5 MHz	Video-Averaging	: 1 sweep
Center frequency	: MHz	Detector mode	: 2 Pos Peak
Frequency Span	: MHz		Max. Hold
Resolution BW	: 3 kHz		
Remark	: Carrier at the lower edge of the band. For EIRP calculation, worst case = maximum antenna gain Out of the band limit (worst case : 34dBm-47dBc = -13dBm)		
Test Result	: Passed		



A1. Measurement result – Plot no.10

Sub-clause	: Emission Limitations		
Measurement method	: Conducted measurement		
Measured channel	: Low channel (channel no. 3) = 1626.59375MHz		
Operating condition	: Max. Power output with modulated rf-carrier		
Environment condition		Test date	: 08-29-2008
Temperature & Humidity	: 23 °C	45 %RH	
Test voltage	: 3.7 Vdc		
Test setup		Video BW	: 3 kHz
Measured Frequency	: 30 – 100 MHz	Video-Averaging	: 1 sweep
Center frequency	: MHz	Detector mode	: 2 Pos Peak
Frequency Span	: MHz		Max. Hold
Resolution BW	: 3 kHz		
Remark	: Carrier at the lower edge of the band. For EIRP calculation, worst case = maximum antenna gain		
	: Out of the band limit (worst case : 34dBm-47dBc = -13dBm)		
Test Result	: Passed		

Agilent 16:09:34 Aug 29, 2008 R T

Ref 16.9 dBm #Atten 30 dB Mkr1 73.98 MHz
 #Avg -68.63 dBm

Log 10 dB/Offst 15.9 dB

PAvg

M1 S2
 S3 FC
 A AA

£(f):
 FTun Swp


Start 30.00 MHz Stop 100.00 MHz
 #Res BW 10 kHz VBW 10 kHz Sweep 2.669 s (601 pts)

No Peak Found

Trace	Correction
Trace 1 2 3	Directional coupler : Offset : 15.9 dB
Clear Write	-. Attenuation(16dB) : (15.5 dB) -. Test cable : (0.4 dB)
Max Hold	BW correction factor : -4.0 dB (10k →4k)
Min Hold	Antenna Gain : 3.0 dBi Total correction : -1.0 dB
View	Measured level : -68.63 dBm Emission level : -69.63 dBm
Blank	Limit
More	50-100% of Ass' bw: -25dBc/4kHz 100-250% of Ass'bw: -35dBc/4kHz 1 of 2 >250% of Ass' bw:-47dBc/4kHz


A1. Measurement result – Plot no.11

Sub-clause	: Emission Limitations		
Measurement method	: Conducted measurement		
Measured channel	: Low channel (channel no. 3) = 1626.59375MHz		
Operating condition	: Max. Power output with modulated rf-carrier		
Environment condition		Test date	: 08-29-2008
Temperature & Humidity	: 23 °C	45 %RH	
Test voltage	: 3.7 Vdc		
Test setup		Video BW	: 10 kHz
Measured Frequency	: 100 – 1000 MHz	Video-Averaging	: 1 sweep
Center frequency	: MHz	Detector mode	: 2 Pos Peak
Frequency Span	: MHz		Max. Hold
Resolution BW	: 10 kHz		
Remark	Carrier at the lower edge of the band. For EIRP calculation, worst case := maximum antenna gain Out of the band limit (worst case : 34dBm-47dBc = -13dBm)		
Test Result	: Passed		




A1. Measurement result – Plot no.12

Sub-clause	: Emission Limitations		
Measurement method	: Conducted measurement		
Measured channel	: Low channel (channel no. 3) = 1626.59375MHz		
Operating condition	: Max. Power output with modulated rf-carrier		
Environment condition		Test date	: 08-29-2008
Temperature & Humidity	: 23 °C	45 %RH	
Test voltage	: 3.7 Vdc		
Test setup		Video BW	: 10 kHz
Measured Frequency	: 1,620.0 GHz – 1,626.5 GHz	Video-Averaging	: 1 sweep
Center frequency	: MHz	Detector mode	: 2 Pos Peak
Frequency Span	: MHz		Max. Hold
Resolution BW	: 10 kHz		
Remark	Carrier at the lower edge of the band. For EIRP calculation, worst case := maximum antenna gain Out of the band limit (worst case : 34dBm-47dBc = -13dBm)		
Test Result	: Passed		



A1. Measurement result – Plot no.13


Sub-clause	: Emission Limitations		
Measurement method	: Conducted measurement		
Measured channel	: Low channel (channel no. 3) = 1626.59375MHz		
Operating condition	: Max. Power output with modulated rf-carrier		
Environment condition		Test date	: 08-29-2008
Temperature & Humidity	: 23 °C	45 %RH	
Test voltage	: 3.7 Vdc		
Test setup		Video BW	: 10 kHz
Measured Frequency	: 1660.5 – 30005 MHz	Video-Averaging	: 1 sweep
Center frequency	: MHz	Detector mode	: 2 Pos Peak
Frequency Span	: MHz		Max. Hold
Resolution BW	: 10 kHz		
Remark	Carrier at the lower edge of the band. For EIRP calculation, worst case := maximum antenna gain Out of the band limit (worst case : 34dBm-47dBc = -13dBm)		
Test Result	: Passed		



FCC Test Report


A1. Measurement result – Plot no.14

Sub-clause	: Emission Limitations		
Measurement method	: Conducted measurement		
Measured channel	: Low channel (channel no. 3) = 1626.59375MHz		
Operating condition	: Max. Power output with modulated rf-carrier		
Environment condition		Test date	: 08-29-2008
Temperature & Humidity	: 23 °C	45 %RH	
Test voltage	: 3.7 Vdc		
Test setup		Video BW	: 2 MHz
Measured Frequency	: 2.5 – 12.75 MHz	Video-Averaging	: 1 sweep
Center frequency	: MHz	Detector mode	: 2 Pos Peak
Frequency Span	: MHz		Max. Hold
Resolution BW	: 2 MHz		
Remark	: Investigation of harmonics		
Test Result	:		




A1. Measurement result – Plot no.15

Sub-clause	: Emission Limitations		
Measurement method	: Conducted measurement		
Measured channel	: Low channel (channel no. 3) = 1626.59375MHz		
Operating condition	: Max. Power output with modulated rf-carrier		
Environment condition		Test date	: 08-29-2008
Temperature & Humidity	: 23 °C	45 %RH	
Test voltage	: 3.7 Vdc		
Test setup		Video BW	: 2 MHz
Measured Frequency	: 5.0 – 10.0 GHz	Video-Averaging	: 1 sweep
Center frequency	: MHz	Detector mode	: 2 Pos Peak
Frequency Span	: MHz		Max. Hold
Resolution BW	: 100 KHz		
Remark	: Investigation of harmonics		
Test Result	:		




A1. Measurement result – Plot no.16

Sub-clause	: Emission Limitations		
Measurement method	: Conducted measurement		
Measured channel	: Low channel (channel no. 3) = 1626.59375MHz		
Operating condition	: Max. Power output with modulated rf-carrier		
Environment condition		Test date	: 08-29-2008
Temperature & Humidity	: 23 °C	45 %RH	
Test voltage	: 3.7 Vdc		
Test setup		Video BW	: 2 MHz
Measured Frequency	: 10.0 – 20.0 GHz	Video-Averaging	: 1 sweep
Center frequency	: MHz	Detector mode	: 2 Pos Peak
Frequency Span	: MHz		Max. Hold
Resolution BW	: 100 KHz		
Remark	: Investigation of harmonics		
Test Result	:		




A1. Measurement result – Plot no.17

Sub-clause	: Emission Limitations		
Measurement method	: Conducted measurement		
Measured channel	: Low channel (channel no. 3) = 1626.59375MHz		
Operating condition	: Max. Power output with modulated rf-carrier		
Environment condition		Test date	: 08-29-2008
Temperature & Humidity	: 23 °C	45 %RH	
Test voltage	: 3.7 Vdc		
Test setup		Video BW	: 10 kHz
Measured Frequency	: 3253.066 MHz	Video-Averaging	: 1 sweep
Center frequency	: MHz	Detector mode	: 2 Pos Peak
Frequency Span	: 500 kHz		Max. Hold
Resolution BW	: 10 kHz		
Remark	Carrier at the lower edge of the band. For EIRP calculation, worst case : = maximum antenna gain Out of the band limit (worst case : 34dBm-47dBc = -13dBm)		
Test Result	: Passed		




A1. Measurement result – Plot no.18

Sub-clause	: Emission Limitations		
Measurement method	: Conducted measurement		
Measured channel	: Low channel (channel no. 3) = 1626.59375MHz		
Operating condition	: Max. Power output with modulated rf-carrier		
Environment condition		Test date	: 08-29-2008
Temperature & Humidity	: 23 °C	45 %RH	
Test voltage	: 3.7 Vdc		
Test setup		Video BW	: 10 kHz
Measured Frequency	: 4879.602 MHz	Video-Averaging	: 1 sweep
Center frequency	: MHz	Detector mode	: 2 Pos Peak
Frequency Span	: 500 kHz		Max. Hold
Resolution BW	: 10 kHz		
Remark	Carrier at the lower edge of the band. For EIRP calculation, worst case := maximum antenna gain Out of the band limit (worst case : 34dBm-47dBc = -13dBm)		
Test Result	: Passed		




A1. Measurement result – Plot no.19

Sub-clause	: Emission Limitations		
Measurement method	: Conducted measurement		
Measured channel	: Low channel (channel no. 3) = 1626.59375MHz		
Operating condition	: Max. Power output with modulated rf-carrier		
Environment condition		Test date	: 08-29-2008
Temperature & Humidity	: 23 °C	45 %RH	
Test voltage	: 3.7 Vdc		
Test setup		Video BW	: 10 kHz
Measured Frequency	: 6506.136 MHz	Video-Averaging	: 1 sweep
Center frequency	: MHz	Detector mode	: 2 Pos Peak
Frequency Span	: 500 kHz		Max. Hold
Resolution BW	: 10 kHz		
Remark	Carrier at the lower edge of the band. For EIRP calculation, worst case : = maximum antenna gain Out of the band limit (worst case : 34dBm-47dBc = -13dBm)		
Test Result	: Passed		




A1. Measurement result – Plot no.20

Sub-clause	: Emission Limitations		
Measurement method	: Conducted measurement		
Measured channel	: Low channel (channel no. 3) = 1626.59375MHz		
Operating condition	: Max. Power output with modulated rf-carrier		
Environment condition		Test date	: 08-29-2008
Temperature & Humidity	: 23 °C	45 %RH	
Test voltage	: 3.7 Vdc		
Test setup		Video BW	: 10 kHz
Measured Frequency	: 8132.637 MHz	Video-Averaging	: 1 sweep
Center frequency	: MHz	Detector mode	: 2 Pos Peak
Frequency Span	: 500 kHz		Max. Hold
Resolution BW	: 10 kHz		
Remark	Carrier at the lower edge of the band. For EIRP calculation, worst case := maximum antenna gain Out of the band limit (worst case : 34dBm-47dBc = -13dBm)		
Test Result	: Passed		




A1. Measurement result – Plot no.21

Sub-clause	: Emission Limitations		
Measurement method	: Conducted measurement		
Measured channel	: Low channel (channel no. 3) = 1626.59375MHz		
Operating condition	: Max. Power output with modulated rf-carrier		
Environment condition		Test date	: 08-29-2008
Temperature & Humidity	: 23 °C	45 %RH	
Test voltage	: 3.7 Vdc		
Test setup		Video BW	: 10 kHz
Measured Frequency	: 11.385 746 GHz	Video-Averaging	: 1 sweep
Center frequency	: MHz	Detector mode	: 2 Pos Peak
Frequency Span	: 500 kHz		Max. Hold
Resolution BW	: 10 kHz		
Remark	Carrier at the lower edge of the band. For EIRP calculation, worst case := maximum antenna gain Out of the band limit (worst case : 34dBm-47dBc = -13dBm)		
Test Result	: Passed		




A1. Measurement result – Plot no.22

Sub-clause	: Emission Limitations		
Measurement method	: Conducted measurement		
Measured channel	: Mid. channel (channel no. 544) = 1643.5 MHz		
Operating condition	: Max. Power output with modulated rf-carrier		
Environment condition		Test date	: 08-29-2008
Temperature & Humidity	: 23 °C	45 %RH	
Test voltage	: 3.7 Vdc		
Test setup		Video BW	: 3 kHz
Measured Frequency	: 1643.5 MHz	Video-Averaging	: 1 sweep
Center frequency	: 1643.5 MHz	Detector mode	: 2 Pos Peak
Frequency Span	: 500 kHz		Max. Hold
Resolution BW	: 3 kHz		
Remark	: Carrier at the middle of the band. For EIRP calculation, worst case = maximum antenna gain		
Test Result	: Passed		




A1. Measurement result – Plot no.23

Sub-clause	: Emission Limitations		
Measurement method	: Conducted measurement		
Measured channel	: Mid. channel (channel no. 544) = 1643.5 MHz		
Operating condition	: Max. Power output with modulated rf-carrier		
Environment condition		Test date	: 08-28-2008
Temperature & Humidity	: 23 °C	45 %RH	
Test voltage	: 3.7 Vdc		
Test setup		Video BW	: 3 kHz
Measured Frequency	: 1626.5 – 1660.5 MHz	Video-Averaging	: 1 sweep
Center frequency	: MHz	Detector mode	: 2 Pos Peak
Frequency Span	: MHz		Max. Hold
Resolution BW	: 3 kHz		
Remark	Carrier at the lower edge of the band. For EIRP calculation, worst case := maximum antenna gain Out of the band limit (worst case : 34dBm-47dBc = -13dBm)		
Test Result	: Passed		




A1. Measurement result – Plot no.24

Sub-clause	: Emission Limitations		
Measurement method	: Conducted measurement		
Measured channel	: Mid. channel (channel no. 544) = 1643.5 MHz		
Operating condition	: Max. Power output with modulated rf-carrier		
Environment condition		Test date	: 08-29-2008
Temperature & Humidity	: 23 °C	45 %RH	
Test voltage	: 3.7 Vdc		
Test setup		Video BW	: 3 kHz
Measured Frequency	: 30 - 100 MHz	Video-Averaging	: 1 sweep
Center frequency	: MHz	Detector mode	: 2 Pos Peak
Frequency Span	: MHz		Max. Hold
Resolution BW	: 3 kHz		
Remark	Carrier at the lower edge of the band. For EIRP calculation, worst case := maximum antenna gain Out of the band limit (worst case : 34dBm-47dBc = -13dBm)		
Test Result	: Passed		




A1. Measurement result – Plot no.25

Sub-clause	: Emission Limitations		
Measurement method	: Conducted measurement		
Measured channel	: Mid. channel (channel no. 544) = 1643.5 MHz		
Operating condition	: Max. Power output with modulated rf-carrier		
Environment condition		Test date	: 08-29-2008
Temperature & Humidity	: 23 °C	45 %RH	
Test voltage	: 3.7 Vdc		
Test setup		Video BW	: 10 kHz
Measured Frequency	: 100 – 1626.5 MHz	Video-Averaging	: 1 sweep
Center frequency	: MHz	Detector mode	: 2 Pos Peak
Frequency Span	: MHz		Max. Hold
Resolution BW	: 10 kHz		
Remark	Carrier at the lower edge of the band. For EIRP calculation, worst case := maximum antenna gain Out of the band limit (worst case : 34dBm-47dBc = -13dBm)		
Test Result	: Passed		




A1. Measurement result – Plot no.26

Sub-clause	: Emission Limitations		
Measurement method	: Conducted measurement		
Measured channel	: Mid. channel (channel no. 544) = 1643.5 MHz		
Operating condition	: Max. Power output with modulated rf-carrier		
Environment condition		Test date	: 08-29-2008
Temperature & Humidity	: 23 °C	45 %RH	
Test voltage	: 3.7 Vdc		
Test setup		Video BW	: 10 kHz
Measured Frequency	: 1660.5 – 2500 MHz	Video-Averaging	: 1 sweep
Center frequency	: MHz	Detector mode	: 2 Pos Peak
Frequency Span	: MHz		Max. Hold
Resolution BW	: 10 kHz		
Remark	Carrier at the lower edge of the band. For EIRP calculation, worst case : = maximum antenna gain Out of the band limit (worst case : 34dBm-47dBc = -13dBm)		
Test Result	: Passed		




A1. Measurement result – Plot no.27

Sub-clause	: Emission Limitations		
Measurement method	: Conducted measurement		
Measured channel	: Mid. channel (channel no. 544) = 1643.5 MHz		
Operating condition	: Max. Power output with modulated rf-carrier		
Environment condition		Test date	: 08-29-2008
Temperature & Humidity	: 23 °C	45 %RH	
Test voltage	: 3.7 Vdc		
Test setup		Video BW	: 300 kHz
Measured Frequency	: 2.0 – 5 GHz	Video-Averaging	: 1 sweep
Center frequency	: MHz	Detector mode	: 2 Pos Peak
Frequency Span	: MHz		Max. Hold
Resolution BW	: 300 kHz		
Remark	: Investigation of harmonics		
	Out of the band limit (worst case : 34dBm-47dBc = -13dBm)		
Test Result	: Passed		




A1. Measurement result – Plot no.28

Sub-clause	: Emission Limitations		
Measurement method	: Conducted measurement		
Measured channel	: Mid. channel (channel no. 544) = 1643.5 MHz		
Operating condition	: Max. Power output with modulated rf-carrier		
Environment condition		Test date	: 08-29-2008
Temperature & Humidity	: 23 °C	45 %RH	
Test voltage	: 3.7 Vdc		
Test setup		Video BW	: 10 kHz
Measured Frequency	: 3.286 992 GHz	Video-Averaging	: 1 sweep
Center frequency	: MHz	Detector mode	: 2 Pos Peak
Frequency Span	: MHz		Max. Hold
Resolution BW	: 10 kHz		
Remark	Carrier at the lower edge of the band. For EIRP calculation, worst case := maximum antenna gain Out of the band limit (worst case : 34dBm-47dBc = -13dBm)		
Test Result	: Passed		




A1. Measurement result – Plot no.29

Sub-clause	: Emission Limitations		
Measurement method	: Conducted measurement		
Measured channel	: Mid. channel (channel no. 544) = 1643.5 MHz		
Operating condition	: Max. Power output with modulated rf-carrier		
Environment condition		Test date	: 08-29-2008
Temperature & Humidity	: 23 °C	45 %RH	
Test voltage	: 3.7 Vdc		
Test setup		Video BW	: 10 kHz
Measured Frequency	: 4.903 508 GHz	Video-Averaging	: 1 sweep
Center frequency	: MHz	Detector mode	: 2 Pos Peak
Frequency Span	: MHz		Max. Hold
Resolution BW	: 10 kHz		
Remark	: Carrier at the lower edge of the band. For EIRP calculation, worst case = maximum antenna gain		
	: Out of the band limit (worst case : 34dBm-47dBc = -13dBm)		
Test Result	: Passed		




A1. Measurement result – Plot no.30

Sub-clause	: Emission Limitations		
Measurement method	: Conducted measurement		
Measured channel	: Mid. channel (channel no. 544) = 1643.5 MHz		
Operating condition	: Max. Power output with modulated rf-carrier		
Environment condition		Test date	: 08-29-2008
Temperature & Humidity	: 23 °C	45 %RH	
Test voltage	: 3.7 Vdc		
Test setup		Video BW	: 300 kHz
Measured Frequency	: 5.0 – 10.0 GHz	Video-Averaging	: 1 sweep
Center frequency	: MHz	Detector mode	: 2 Pos Peak
Frequency Span	: MHz		Max. Hold
Resolution BW	: 300 kHz		
Remark	: Investigation of harmonics		
	Out of the band limit (worst case : 34dBm-47dBc = -13dBm)		
Test Result	: Passed		



A1. Measurement result – Plot no.31


Sub-clause	: Emission Limitations		
Measurement method	: Conducted measurement		
Measured channel	: Mid. channel (channel no. 544) = 1643.5 MHz		
Operating condition	: Max. Power output with modulated rf-carrier		
Environment condition		Test date	: 08-29-2008
Temperature & Humidity	: 23 °C	45 %RH	
Test voltage	: 3.7 Vdc		
Test setup		Video BW	: 10 kHz
Measured Frequency	: 6.574 010 GHz	Video-Averaging	: 1 sweep
Center frequency	: MHz	Detector mode	: 2 Pos Peak
Frequency Span	: MHz		Max. Hold
Resolution BW	: 10 kHz		
Remark	: Carrier at the lower edge of the band. For EIRP calculation, worst case = maximum antenna gain		
	: Out of the band limit (worst case : 34dBm-47dBc = -13dBm)		
Test Result	: Passed		



FCC Test Report


A1. Measurement result – Plot no.32

Sub-clause	: Emission Limitations		
Measurement method	: Conducted measurement		
Measured channel	: Mid. channel (channel no. 544) = 1643.5 MHz		
Operating condition	: Max. Power output with modulated rf-carrier		
Environment condition		Test date	: 08-29-2008
Temperature & Humidity	: 23 °C	45 %RH	
Test voltage	: 3.7 Vdc		
Test setup		Video BW	: 10 kHz
Measured Frequency	: 8.217 484 GHz	Video-Averaging	: 1 sweep
Center frequency	: MHz	Detector mode	: 2 Pos Peak
Frequency Span	: MHz		Max. Hold
Resolution BW	: 10 kHz		
Remark	: Carrier at the lower edge of the band. For EIRP calculation, worst case = maximum antenna gain		
Out of the band limit (worst case : 34dBm-47dBc = -13dBm)			
Test Result	: Passed		



A1. Measurement result – Plot no.33


Sub-clause	: Emission Limitations		
Measurement method	: Conducted measurement		
Measured channel	: Mid. channel (channel no. 544) = 1643.5 MHz		
Operating condition	: Max. Power output with modulated rf-carrier		
Environment condition		Test date	: 08-29-2008
Temperature & Humidity	: 23 °C	45 %RH	
Test voltage	: 3.7 Vdc		
Test setup		Video BW	: 10 kHz
Measured Frequency	: 9.860 982 GHz	Video-Averaging	: 1 sweep
Center frequency	: MHz	Detector mode	: 2 Pos Peak
Frequency Span	: MHz		Max. Hold
Resolution BW	: 10 kHz		
Remark	: Carrier at the lower edge of the band. For EIRP calculation, worst case = maximum antenna gain		
	: Out of the band limit (worst case : 34dBm-47dBc = -13dBm)		
Test Result	: Passed		



FCC Test Report


A1. Measurement result – Plot no.34

Sub-clause	: Emission Limitations		
Measurement method	: Conducted measurement		
Measured channel	: High channel (channel no. 1087) = 1660.46875 MHz		
Operating condition	: Max. Power output with modulated rf-carrier		
Environment condition		Test date	: 08-28-2008
Temperature & Humidity	: 23 °C	45 %RH	
Test voltage	: 3.7 Vdc		
Test setup		Video BW	: 3 kHz
Measured Frequency	: 1660.46875 MHz	Video-Averaging	: 1 sweep
Center frequency	: MHz	Detector mode	: 2 Pos Peak
Frequency Span	: MHz		Max. Hold
Resolution BW	: 3 kHz		
Remark	Carrier at the lower edge of the band. For EIRP calculation, worst case : = maximum antenna gain Out of the band limit (worst case -43dBc)		
Test Result	: Passed		




A1. Measurement result – Plot no.35

Sub-clause	: Emission Limitations		
Measurement method	: Conducted measurement		
Measured channel	: High channel (channel no. 1087) = 1660.46875 MHz		
Operating condition	: Max. Power output with modulated rf-carrier		
Environment condition		Test date	: 08-28-2008
Temperature & Humidity	: 23 °C	45 %RH	
Test voltage	: 3.7 Vdc		
Test setup		Video BW	: 10 kHz
Measured Frequency	: 30 – 100 MHz	Video-Averaging	: 1 sweep
Center frequency	: MHz	Detector mode	: 2 Pos Peak
Frequency Span	: MHz		Max. Hold
Resolution BW	: 10 kHz		
Remark	Carrier at the lower edge of the band. For EIRP calculation, worst case : = maximum antenna gain Out of the band limit (worst case : 34dBm-47dBc = -13dBm)		
Test Result	: Passed		




A1. Measurement result – Plot no.36

Sub-clause	: Emission Limitations		
Measurement method	: Conducted measurement		
Measured channel	: High channel (channel no. 1087) = 1660.46875 MHz		
Operating condition	: Max. Power output with modulated rf-carrier		
Environment condition		Test date	: 08-28-2008
Temperature & Humidity	: 23 °C	45 %RH	
Test voltage	: 3.7 Vdc		
Test setup		Video BW	: 10 kHz
Measured Frequency	: 100 – 1626.5 MHz	Video-Averaging	: 1 sweep
Center frequency	: MHz	Detector mode	: 2 Pos Peak
Frequency Span	: MHz		Max. Hold
Resolution BW	: 10 kHz		
Remark	Carrier at the lower edge of the band. For EIRP calculation, worst case : = maximum antenna gain Out of the band limit (worst case : 34dBm-47dBc = -13dBm)		
Test Result	: Passed		




A1. Measurement result – Plot no.37

Sub-clause	: Emission Limitations		
Measurement method	: Conducted measurement		
Measured channel	: High channel (channel no. 1087) = 1660.46875 MHz		
Operating condition	: Max. Power output with modulated rf-carrier		
Environment condition		Test date	: 08-28-2008
Temperature & Humidity	: 23 °C	45 %RH	
Test voltage	: 3.7 Vdc		
Test setup		Video BW	: 10 kHz
Measured Frequency	: 1626.5 – 1660.5 GHz	Video-Averaging	: 1 sweep
Center frequency	: MHz	Detector mode	: 2 Pos Peak
Frequency Span	: MHz		Max. Hold
Resolution BW	: 10 kHz		
Remark	Carrier at the lower edge of the band. For EIRP calculation, worst case := maximum antenna gain Out of the band limit (worst case : 34dBm-47dBc = -13dBm)		
Test Result	: Passed		




A1. Measurement result – Plot no.38

Sub-clause	: Emission Limitations		
Measurement method	: Conducted measurement		
Measured channel	: High channel (channel no. 1087) = 1660.46875 MHz		
Operating condition	: Max. Power output with modulated rf-carrier		
Environment condition		Test date	: 08-28-2008
Temperature & Humidity	: 23 °C	45 %RH	
Test voltage	: 3.7 Vdc		
Test setup		Video BW	: 10 kHz
Measured Frequency	: 1660.5 – 2500.0 MHz	Video-Averaging	: 1 sweep
Center frequency	: MHz	Detector mode	: 2 Pos Peak
Frequency Span	: MHz		Max. Hold
Resolution BW	: 10 kHz		
Remark	Carrier at the lower edge of the band. For EIRP calculation, worst case : = maximum antenna gain Out of the band limit (worst case : 34dBm-47dBc = -13dBm)		
Test Result	: Passed		




A1. Measurement result – Plot no.39

Sub-clause	: Emission Limitations		
Measurement method	: Conducted measurement		
Measured channel	: High channel (channel no. 1087) = 1660.46875 MHz		
Operating condition	: Max. Power output with modulated rf-carrier		
Environment condition		Test date	: 08-28-2008
Temperature & Humidity	: 23 °C	45 %RH	
Test voltage	: 3.7 Vdc		
Test setup		Video BW	: 3 kHz
Measured Frequency	: 2.5 – 10.0 GHz	Video-Averaging	: 1 sweep
Center frequency	: MHz	Detector mode	: 2 Pos Peak
Frequency Span	: MHz		Max. Hold
Resolution BW	: 3 kHz		
Remark	: Investigation of Harmonics		
Test Result	: Passed		



A1. Measurement result – Plot no.40


Sub-clause	: Emission Limitations		
Measurement method	: Conducted measurement		
Measured channel	: High channel (channel no. 1087) = 1660.46875 MHz		
Operating condition	: Max. Power output with modulated rf-carrier		
Environment condition		Test date	: 08-28-2008
Temperature & Humidity	: 23 °C	45 %RH	
Test voltage	: 3.7 Vdc		
Test setup		Video BW	: 10 kHz
Measured Frequency	: 3.320 928 MHz	Video-Averaging	: 1 sweep
Center frequency	: MHz	Detector mode	: 2 Pos Peak
Frequency Span	: MHz		Max. Hold
Resolution BW	: 10 kHz		
Remark	Carrier at the lower edge of the band. For EIRP calculation, worst case := maximum antenna gain Out of the band limit (worst case : 34dBm-47dBc = -13dBm)		
Test Result	: Passed		



FCC Test Report


A1. Measurement result – Plot no.41

Sub-clause	: Emission Limitations		
Measurement method	: Conducted measurement		
Measured channel	: High channel (channel no. 1087) = 1660.46875 MHz		
Operating condition	: Max. Power output with modulated rf-carrier		
Environment condition		Test date	: 08-28-2008
Temperature & Humidity	: 23 °C	45 %RH	
Test voltage	: 3.7 Vdc		
Test setup		Video BW	: 10 kHz
Measured Frequency	: 4.981 397 MHz	Video-Averaging	: 1 sweep
Center frequency	: MHz	Detector mode	: 2 Pos Peak
Frequency Span	: MHz		Max. Hold
Resolution BW	: 10 kHz		
Remark	Carrier at the lower edge of the band. For EIRP calculation, worst case := maximum antenna gain Out of the band limit (worst case : 34dBm-47dBc = -13dBm)		
Test Result	: Passed		




A1. Measurement result – Plot no.42

Sub-clause	: Emission Limitations		
Measurement method	: Conducted measurement		
Measured channel	: High channel (channel no. 1087) = 1660.46875 MHz		
Operating condition	: Max. Power output with modulated rf-carrier		
Environment condition		Test date	: 08-28-2008
Temperature & Humidity	: 23 °C	45 %RH	
Test voltage	: 3.7 Vdc		
Test setup		Video BW	: 10 kHz
Measured Frequency	: 6.641 889 MHz	Video-Averaging	: 1 sweep
Center frequency	: MHz	Detector mode	: 2 Pos Peak
Frequency Span	: MHz		Max. Hold
Resolution BW	: 10 kHz		
Remark	Carrier at the lower edge of the band. For EIRP calculation, worst case := maximum antenna gain Out of the band limit (worst case : 34dBm-47dBc = -13dBm)		
Test Result	: Passed		




A1. Measurement result – Plot no.43

Sub-clause	: Emission Limitations		
Measurement method	: Conducted measurement		
Measured channel	: High channel (channel no. 1087) = 1660.46875 MHz		
Operating condition	: Max. Power output with modulated rf-carrier		
Environment condition		Test date	: 08-28-2008
Temperature & Humidity	: 23 °C	45 %RH	
Test voltage	: 3.7 Vdc		
Test setup		Video BW	: 10 kHz
Measured Frequency	: 8.302 356 MHz	Video-Averaging	: 1 sweep
Center frequency	: MHz	Detector mode	: 2 Pos Peak
Frequency Span	: MHz		Max. Hold
Resolution BW	: 10 kHz		
Remark	Carrier at the lower edge of the band. For EIRP calculation, worst case := maximum antenna gain Out of the band limit (worst case : 34dBm-47dBc = -13dBm)		
Test Result	: Passed		




A1. Measurement result – Plot no.44

Sub-clause	: Emission Limitations		
Measurement method	: Conducted measurement		
Measured channel	: High channel (channel no. 1087) = 1660.46875 MHz		
Operating condition	: Max. Power output with modulated rf-carrier		
Environment condition		Test date	: 08-28-2008
Temperature & Humidity	: 23 °C	45 %RH	
Test voltage	: 3.7 Vdc		
Test setup		Video BW	: 10 kHz
Measured Frequency	: 9.962 830 MHz	Video-Averaging	: 1 sweep
Center frequency	: MHz	Detector mode	: 2 Pos Peak
Frequency Span	: MHz		Max. Hold
Resolution BW	: 10 kHz		
Remark	Carrier at the lower edge of the band. For EIRP calculation, worst case := maximum antenna gain Out of the band limit (worst case : 34dBm-47dBc = -13dBm)		
Test Result	: Passed		




A1. Measurement result – Plot no.45

Sub-clause	: Emission Limitations		
Measurement method	: Conducted measurement		
Measured channel	: High channel (channel no. 1087) = 1660.46875 MHz		
Operating condition	: Max. Power output with modulated rf-carrier		
Environment condition		Test date	: 08-28-2008
Temperature & Humidity	: 23 °C	45 %RH	
Test voltage	: 3.7 Vdc		
Test setup		Video BW	: 10 kHz
Measured Frequency	: 10 – 12 GHz	Video-Averaging	: 1 sweep
Center frequency	: MHz	Detector mode	: 2 Pos Peak
Frequency Span	: MHz		Max. Hold
Resolution BW	: 10 kHz		
Remark	Carrier at the lower edge of the band. For EIRP calculation, worst case := maximum antenna gain Out of the band limit (worst case : 34dBm-47dBc = -13dBm)		
Test Result	: Passed		



A1. Measurement result – Plot no.46


Sub-clause	: §25.216 Limits on emissions for aeronautical radio navigation-satellite service		
Measurement method	: Conducted measurement		
Measured channel	: Low channel (channel no. 1087) = 1626.59375 MHz		
Operating condition	: Max. Power output with modulated rf-carrier		
Environment condition		Test date	: 09-23-2008
Temperature & Humidity	: 23 °C	38 %RH	
Test voltage	: 3.7 Vdc		
Test setup		Video BW	: 1 MHz
Measured Frequency	: 1559 – 1605 MHz	Video-Averaging	: 100 sweep
Center frequency	: MHz	Detector mode	: RMS
Frequency Span	: MHz		Max. Hold
Resolution BW	: 1 MHz		
Remark	Carrier-on state / Carrier at the lower edge of the band : For EIRP calculation, worst case = maximum antenna gain The EIRP, averaged over any 2 millisecond active transmission interval from the MES		
Test Result	: Passed		



FCC Test Report


A1. Measurement result – Plot no.47

Sub-clause	: §25.216 Limits on emissions for aeronautical radio navigation-satellite service		
Measurement method	: Conducted measurement		
Measured channel	: Low channel (channel no. 1087) = 1626.59375 MHz		
Operating condition	: Max. Power output with modulated rf-carrier		
Environment condition		Test date	: 09-23-2008
Temperature & Humidity	: 23 °C	38 %RH	
Test voltage	: 3.7 Vdc		
Test setup		Video BW	: 1 MHz
Measured Frequency	: 1605 – 1610 MHz	Video-Averaging	: 100 sweep
Center frequency	: MHz	Detector mode	: RMS
Frequency Span	: MHz		Max. Hold
Resolution BW	: 1 MHz		
Remark	Carrier-on state / Carrier at the lower edge of the band : For EIRP calculation, worst case = maximum antenna gain The EIRP, averaged over any 2 millisecond active transmission interval from the MES		
Test Result	: Passed		




A1. Measurement result – Plot no.48

Sub-clause	: §25.216 Limits on emissions for aeronautical radio navigation-satellite service		
Measurement method	: Conducted measurement		
Measured channel	: Mid channel (channel no. 544) = 1643.5 MHz		
Operating condition	: Max. Power output with modulated rf-carrier		
Environment condition		Test date	: 09-11-2008
Temperature & Humidity	: 23 °C	40 %RH	
Test voltage	: 3.7 Vdc		
Test setup		Video BW	: 1 MHz
Measured Frequency	: 1559 – 1605 MHz	Video-Averaging	: 100 sweep
Center frequency	: MHz	Detector mode	: RMS
Frequency Span	: MHz		Max. Hold
Resolution BW	: 1 MHz		
Remark	Carrier-on state / Carrier at the mid channel : For EIRP calculation, worst case = maximum antenna gain The EIRP, averaged over any 2 millisecond active transmission interval from the MES		
Test Result	: Passed		




A1. Measurement result – Plot no.49

Sub-clause	: §25.216 Limits on emissions for aeronautical radio navigation-satellite service		
Measurement method	: Conducted measurement		
Measured channel	: Mid channel (channel no. 544) = 1643.5 MHz		
Operating condition	: Max. Power output with modulated rf-carrier		
Environment condition		Test date	: 09-11-2008
Temperature & Humidity	: 23 °C	40 %RH	
Test voltage	: 3.7 Vdc		
Test setup		Video BW	: 1 MHz
Measured Frequency	: 1605 – 1610 MHz	Video-Averaging	: 100 sweep
Center frequency	: MHz	Detector mode	: RMS
Frequency Span	: MHz		Max. Hold
Resolution BW	: 1 MHz		
Remark	Carrier-on state / Carrier at the mid channel : For EIRP calculation, worst case = maximum antenna gain The EIRP, averaged over any 2 millisecond active transmission interval from the MES		
Test Result	: Passed		




A1. Measurement result – Plot no.50

Sub-clause	: §25.216 Limits on emissions for aeronautical radio navigation-satellite service		
Measurement method	: Conducted measurement		
Measured channel	: High channel (channel no. 1087) = 1660.46875 MHz		
Operating condition	: Max. Power output with modulated rf-carrier		
Environment condition		Test date	: 09-11-2008
Temperature & Humidity	: 23 °C	40 %RH	
Test voltage	: 3.7 Vdc		
Test setup		Video BW	: 1 MHz
Measured Frequency	: 1559 – 1605 MHz	Video-Averaging	: 100 sweep
Center frequency	: MHz	Detector mode	: RMS
Frequency Span	: MHz		Max. Hold
Resolution BW	: 1 MHz		
Remark	Carrier-on state / Carrier at the lower edge of the band : For EIRP calculation, worst case = maximum antenna gain The EIRP, averaged over any 2 millisecond active transmission interval from the MES		
Test Result	: Passed		



A1. Measurement result – Plot no.51

Sub-clause	: §25.216 Limits on emissions for aeronautical radio navigation-satellite service		
Measurement method	: Conducted measurement		
Measured channel	: High channel (channel no. 1087) = 1660.46875 MHz		
Operating condition	: Max. Power output with modulated rf-carrier		
Environment condition		Test date	: 09-11-2008
Temperature & Humidity	: 23 °C	40 %RH	
Test voltage	: 3.7 Vdc		
Test setup		Video BW	: 1 MHz
Measured Frequency	: 1605 – 1610 MHz	Video-Averaging	: 100 sweep
Center frequency	: MHz	Detector mode	: RMS
Frequency Span	: MHz		Max. Hold
Resolution BW	: 1 MHz		
Remark	Carrier-on state / Carrier at the lower edge of the band : For EIRP calculation, worst case = maximum antenna gain The EIRP, averaged over any 2 millisecond active transmission interval from the MES		
Test Result	: Passed		



A1. Measurement result – Plot no.52

Sub-clause	: §25.216 Limits on emissions for aeronautical radio navigation-satellite service		
Measurement method	: Conducted measurement		
Measured channel	:		
Operating condition	: Carrier-off		
Environment condition		Test date	: 09-08-2008
Temperature & Humidity	: 23 °C	40 %RH	
Test voltage	: 3.7 Vdc		
Test setup		Video BW	: 1 MHz
Measured Frequency	: 1559 – 1610 MHz	Video-Averaging	: 100 sweep
Center frequency	: MHz	Detector mode	: RMS
Frequency Span	: MHz		: Max. Hold
Resolution BW	: 1 MHz		
Remark	Carrier-off state, : For EIRP calculation, worst case = maximum antenna gain The EIRP, averaged over any 2 millisecond active transmission interval from the MES		
Test Result	: Passed		

