

FCC RADIO TEST REPORT

according to

47 CFR FCC Part 15 Subpart F § 15.519

Equipment : Wireless USB HMC Module
Model No. : WQ110-HMC
Brand Name : WiQuest
Applicant : WiQuest Communications, Inc
915 Enterprise Blvd. Suite 200 Allen, TX 75013
Manufacturer : Hon Hai Precision Ind. Co., Ltd.
5F-1, 5 Hsin-An Road Hsinchu, Science-Based Industrial Park Taiwan, R.O.C.
FCC ID : TZQWQ110HMC
Test Freq. Range : 3100 ~ 10600MHz
Received Date : Jul. 09, 2008
Final Test Date : Jul. 14, 2008
Filing Type : Existing Change

Statement

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.4-2003** and **47 CFR FCC Part 15 Subpart F**.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



ILAC MRA

SPORTON International Inc.

6F, No. 106, Sec. 1, Hsin Tai Wu Rd., Hsi Chih, Taipei Hsien, Taiwan, R.O.C.

Table of Contents

1. SUMMARY OF THE TEST RESULT	2
2. GENERAL INFORMATION.....	3
2.1. Product Details	3
2.2. Table for Carrier Frequencies	3
2.3. Accessories.....	3
2.4. Table for Existing Change	3
2.5. Table for Test Modes	3
2.6. Table for Testing Locations	4
2.7. Table for Supporting Units.....	4
2.8. Table for Parameters of Test Software Setting	4
2.9. Test Configuration	5
3. TEST RESULT	6
3.1. Operational Limitations.....	6
3.2. UWB Bandwidth Measurement	7
3.3. Radiated Emissions Measurement.....	12
3.4. Radiated Emissions in GPS Bands Measurement.....	38
3.5. Peak Emissions within a 50 MHz Bandwidth Measurement	42
3.6. Labeling and Instruction Manual Requirements.....	46
3.7. Antenna Requirements.....	46
4. LIST OF MEASURING EQUIPMENTS	47
5. TEST LOCATION.....	48
6. TAF CERTIFICATE OF ACCREDITATION	49
APPENDIX A. TEST PHOTOS	A1 ~ A7
APPENDIX B. PHOTOGRAPHS OF EUT	B1 ~ B5

History of This Test Report

Original Issue Date: Jul. 15, 2008

Report No.: FR831717-01

- No additional attachment.
- Additional attachment were issued as following record:

CERTIFICATE OF COMPLIANCE

according to

47 CFR FCC Part 15 Subpart F § 15.519

Equipment : Wireless USB HMC Module

Model No. : WQ110-HMC

Brand Name : WiQuest

Applicant : **WiQuest Communications, Inc**

915 Enterprise Blvd. Suite 200 Allen, TX 75013

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Jul. 09, 2008 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.

Wayne Hsu
Wayne Hsu

SPORTON International Inc.

6F, No.106, Sec. 1, Hsin Tai Wu Rd., Hsi Chih, Taipei Hsien, Taiwan, R.O.C.

1. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart F				
Part	Rule Section	Description of Test	Result	Under Limit
-	15.207	AC Power Line Conducted Emissions	-	-
3.1	15.519(a)	Operational Limitations	Complies	-
3.2	15.519(b)	UWB Bandwidth	Complies	-
3.3	15.519(c)/15.209	Radiated Emissions	Complies	1.96 dB
3.4	15.519(d)	Radiated Emissions in GPS Bands	Complies	1.33 dB
3.5	15.519(e)	Peak Emissions within a 50 MHz Bandwidth	Complies	6.47 dB
3.6	15.517(f)	Labeling Requirements	Complies	-
3.7	15.203	Antenna Requirements	Complies	-

Test Items	Uncertainty	Remark
AC Power Line Conducted Emissions	±2.3dB	Confidence levels of 95%
UWB Bandwidth	±8.5×10 ⁻⁸	Confidence levels of 95%
Radiated Emissions (9kHz~30MHz)	±0.8dB	Confidence levels of 95%
Radiated Emissions (30MHz~1000MHz)	±1.9dB	Confidence levels of 95%
Radiated Emissions / in GPS Bands (1GHz~18GHz)	±1.9dB	Confidence levels of 95%
Radiated Emissions (18GHz~40GHz)	±1.9dB	Confidence levels of 95%
Temperature	±0.7°C	Confidence levels of 95%
Humidity	±3.2%	Confidence levels of 95%
DC / AC Power Source	±1.4%	Confidence levels of 95%

2. GENERAL INFORMATION

2.1. Product Details

Items	Description
Power Type	Host (Notebook)
Modulation	Multi-band OFDM (QPSK / DCM)
Operation Frequency Range	3168 ~ 4752 MHz
10 dB Bandwidth	520.8 MHz
RF Output Rating	-20.44 dBm (EIRP) @ RBW:10MHz
Antenna	External Antenna

2.2. Table for Carrier Frequencies

Band Group	BAND_ID (nb)	Lower Frequency (MHz)	Center Frequency (MHz)	Upper Frequency (MHz)
1	1	3168	3432	3696
	2	3696	3960	4224
	3	4224	4488	4752

2.3. Table for Existing Change

This product is an extension of original one reported under Sporton project number: FR831717. The difference is “Layout minor change”. The new test data had updated in this report.

WiQuest is adding Hon Hai Precision Ind. Co., Ltd. as a manufacturer of the WQ-110HMC.

2.4. Table for Test Modes

Investigation has been done on the entire possible configuration for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	BAND_ID (nb)	Data Rate	Remark
AC Power Line Conducted Emissions	-	-	-	-
UWB Bandwidth	CTX	All Band	TFC 4, 53.3 Mbps	
Radiated Emissions 9kHz~960MHz	CTX	All Band	TFC 4, 53.3 Mbps	
Radiated Emissions above 960MHz	CTX	All Band	TFC 4, 53.3 Mbps	
Peak Emissions within a 50 MHz Bandwidth	CTX	All Band	TFC 4, 53.3 Mbps	

Note:

1. CTX=continuously transmitting; All Band: EUT simultaneously transmitted in band_ID 1, 2, and 3.
2. Investigation has been done on all data rates for searching the worst cases. The EUT with TFC 4, 53.3Mbps, and 4095 packets has been found to be the worst case.

2.6. Table for Testing Locations

Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.	VCCI Reg. No
03CH03-HY	SAC	Hwa Ya	101377	IC 4088	-
TH01-HY	OVEN Room	Hwa Ya	-	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC); Fully Anechoic Chamber (FAC).

2.7. Table for Supporting Units

Test Items	Support Unit	Brand	Model	FCC ID
Radiation	Notebook	DELL	XPS M1330	DoC
Radiation	Mini PCI Test Fixture	WiQuest	WQST110	N/A

2.8. Table for Parameters of Test Software Setting


During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware on the final end product.

UWB

Test Software Version	PSD-Antenna-0-id-0.bat		
BAND_ID (nb)	1	2	3
UWB	Default	Default	Default

2.9. Test Configuration

2.9.1. Radiation Emissions Test Configuration



3. TEST RESULT

3.1. Operational Limitations

3.1.1. Test Result of Operation Restriction

Operation Restriction	Informed the applicant	Not applicable	User Manual Informed	Passed
<input checked="" type="checkbox"/> 47 CFR FCC Part 15 Subpart F 15.519(a)				
UWB devices operating under the provisions of this section must be hand held, i.e., they are relatively small devices that are primarily hand held while being operated and do not employ a fixed infrastructure. [A transmitter that had been connected to portable device e.g. Laptop PC...and be considered sufficient to demonstrate not a fixed infrastructure application.]	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
(1) The radiator shall cease transmission within 10 seconds unless it receives an acknowledgement from the associated receiver				
A UWB device operating under the provisions of this section shall transmit only when it is sending information to an associated receiver. The UWB intentional radiator shall cease transmission within 10 seconds unless it receives an acknowledgement from the associated receiver that its transmission is being received. An acknowledgment of reception must continue to be received by the UWB intentional radiator at least every 10 seconds or the UWB device must cease transmitting. [The applicant has been informed of this requirement and instructs the caution in user manual.]	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
(2) Outdoor mounted antennas				
The use of antennas mounted on outdoor structures, e.g., antennas mounted on the outside of a building or on a telephone pole, or any fixed outdoors infrastructure is prohibited. Antennas may be mounted only on the hand held UWB device. [The applicant has been informed of this requirement.]	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
(5) Indoors or Outdoors				
UWB devices operating under the provisions of this section may operate indoors or outdoors. [The applicant has been informed of this requirement.]	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>

3.2. UWB Bandwidth Measurement

3.2.1. Limit

Ultra-wideband (UWB) transmitter. An intentional radiator that, at any point in time, has a fractional bandwidth equal to or greater than 0.20 or has a UWB bandwidth equal to or greater than 500 MHz, regardless of the fractional bandwidth.

The UWB bandwidth is the frequency band bounded by the points that are 10 dB below the highest radiated emission, as based on the complete transmission system including the antenna. The upper boundary is designated f_H and the lower boundary is designated f_L . The frequency at which the highest radiated emission occurs is designated f_M .

Center frequency. The center frequency, f_C , equals $(f_H + f_L)/2$.

Fractional bandwidth. The fractional bandwidth equals $2(f_H - f_L)/(f_H + f_L)$.

The UWB bandwidth of a UWB system operating under the provisions of this section must be contained between 3100 MHz and 10,600 MHz.

3.2.2. Measuring Instruments and Setting

Please refer to equipments list in section 4 of this report. The following table is the setting of the spectrum analyzer.

Parameter	Setting
RBW / VBW	10 MHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto


3.2.3. Test Procedures

1. The EUT was placed on the top of the turntable that is non-conductive materials (glass fiber) and 0.8 meter above ground. The EUT was flush on the back of the tabletop. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. The horn receiving antenna was varied between 1 meter and 4 meters , 1 meter step above ground while maintaining bore sight alignment to find the maximum emissions field strength of both horizontal and vertical polarization.
3. For maximum emission amplitude, the antenna tower was scanning (from 1 M to 4 M) and the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading and was used to determine the frequency at which the highest radiated emission occurs, f_M . Next, the points that are 10dB or more below the highest radiated emission were observed in a search from f_M in both the lower and higher frequency direction in the measured frequency EIRP graph, they are denoted as f_L and f_H , respectively.

The UWB bandwidth is the difference between f_L and f_H .

4. The individual UWB bandwidths were measured for each BAND_ID (n_b) of the UWB spectrum. Both horizontal and vertical polarizations were taken into account to determine the full UWB BW on the maximized (in azimuth and elevation) signals.

3.2.4. Test Setup Layout



Note: The Horn Antenna maintaining bore sight alignment.

$$\theta = \tan^{-1} \left(\frac{\text{The Antenna's Height} - \text{The Table's Height}}{\text{The Test Distance}} \right)$$

3.2.5. Test Deviation


There is no deviation with the original standard.

3.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode, and TFC 4 and data rate is 53.3Mbps.

3.2.7. Test Result of UWB Bandwidth

UWB Bandwidth on BAND_ID (nb) 1




Date: 10.JUL.2008 18:28:20

UWB BW = 511.00 MHz; F_L = 3178.60 MHz; F_H = 3689.60 MHz; F_C = 3432.00 MHz

Note:

1. Test Distance: 3m
2. Antenna height 1 to 4 meters, 1 meter steps, bore sighted to EUT.
3. There are the absorber on ground plane between the antenna tower and turntable.

UWB Bandwidth on BAND_ID (nb) 2




Date: 10.JUL.2008 18:33:00

UWB BW = 519.40 MHz; $F_L = 3701.00$ MHz; $F_H = 4220.40$ MHz; $F_C = 3960.00$ MHz

Note:

1. Test Distance: 3m
2. Antenna height 1 to 4 meters, 1 meter steps, bore sighted to EUT.
3. There are the absorber on ground plane between the antenna tower and turntable.

UWB Bandwidth on BAND_ID (nb) 3



Date: 10.JUL.2008 18:36:20

UWB BW = 520.80 MHz; F_L = 4223.40 MHz; F_H = 4744.20 MHz; F_C = 4488.00 MHz

Note:

1. Test Distance: 3m
2. Antenna height 1 to 4 meters, 1 meter steps, bore sighted to EUT.
3. There are the absorber on ground plane between the antenna tower and turntable.

3.3. Radiated Emissions Measurement

3.3.1. Limit

1. The radiated emissions at or below 960 MHz from a device shall not exceed the emission levels in section 15.209(a) limit below.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3

2. The radiated emissions above 960 MHz from a device shall not exceed the emission levels in section 15.519(c) limit below.

Freq. (MHz)	EIRP (dBm)
960-1610	-75.3
1610-1990	-63.3
1990-3100	-61.3
3100-10600	-41.3
10600 above	-61.3

3. This may be converted to a peak field strength level at 3 meters using $E(\text{dBuV/m}) = P(\text{dBm EIRP}) + 95.2 \text{ dB}$.

4. For 47 CFR Section 15.521(c): Emissions from digital circuitry used to enable the operation of the UWB transmitter shall comply with the limits in Section 15.209 of this chapter, rather than the limits specified in this subpart, provided it can be clearly demonstrated that those emissions from the UWB device are due solely to emissions from digital circuitry contained within the transmitter and that the emissions are not intended to be radiated from the transmitter's antenna. Emissions from associated digital devices, as defined in Section 15.3(k) of this chapter, e.g., emissions from digital circuitry used to control additional functions or capabilities other than the UWB transmission, are subject to the limits contained in Subpart B of Part 15 of this chapter.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
above 960	500	3

3.3.2. Measuring Instruments and Setting

Please refer to equipments list in section 4 of this report. The following table is the setting of the spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	0 dB
Start Frequency	960 MHz
Stop Frequency	10th carrier harmonic or 40 GHz
RBW / VBW	47 CFR Section15.517(c): 1MHz / 3MHz for RMS, 1 msec averaging time were used for these measurement frequencies. 47 CFR Section 15.521(c): (47 CFR Section 15.209 (a)) 1MHz/1MHz for peak; 1MHz/10Hz for Average. (in accordance with ANSI C63.4)

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RBW 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RBW 9kHz for QP
Start ~ Stop Frequency	30MHz~960MHz / RBW 120kHz for QP

3.3.3. Test Procedures

- Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable that is non-conductive material (glass fiber) and 0.8 meter above ground. The EUT was flush on the back of the tabletop. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed equal or less than 3 meters far away from the turntable, shorter measurement distances may be used to improve the measurement systems noise floor.
- Extrapolation factor when test distance other than 3m. (in accordance with 47 CFR 15.31 (f) (1))

From 3m to 1m : Distance extrapolation factor = $20 \log(\text{specific distance [3m]} / \text{test distance [1m]})$ (dB); Limit line = specific limits (dBuV) + distance extrapolation factor [9.54 dB].

From 3m to 0.5m. Distance extrapolation factor = $20 \log(\text{specific distance [3m]} / \text{test distance [0.5m]})$ (dB); Limit line = specific limits (dBuV) + distance extrapolation factor [15.56 dB].
- Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- The height of the broadband receiving antenna was varied between 1 meter and 4 meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- For each suspected emissions, the antenna tower was scanning (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- The measurements made over the frequency range from 9 kHz to 960 MHz were maximized using an


EMI receiver with peak detector capabilities. If the emissions level of the EUT in peak mode was 3 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 960MHz.

7. Measurements above 960 MHz were maximized using a spectrum analyzer with RMS detector capabilities. A spectrum analyzer was used for the final measurements utilizing an RMS detector at the frequencies with the largest amplitudes. The prescribed RBW of 1 MHz and VBW of 3 MHz, and a 1 msec. averaging time were used for these measurements.
8. The spectrum between 9 kHz and 960 MHz contained no intentional radiation and lies below the limits. The spectrum from 960MHz to 18GHz contained intentional UWB signals between 3100 MHz and 10600 MHz and lie below the limits. No other emissions above 10600 MHz were detected. The maximum frequency tested was 40 GHz.
9. Per 47 CFR, Part 15, Subpart F, §15.521(c) (§15.209) all digital emissions from the transmitter not intended to be radiated from the antenna port meet the 15.209 subpart C limits.
10. Additional measurements in the 960 MHz to 40 GHz range were performed to determine the nature of all unintentional emissions in this span. Conducted antenna port measurement and terminated antenna port measurement were done in the 960 MHz to 18 GHz range to show that all noise peaks have the same frequency and polarization and are determined to be emission from the digital circuit and are not radiated from the antenna.

3.3.4. Test Setup Layout


For radiated emissions below 30MHz

Investigated emissions from digital circuitry used to control additional functions or capabilities other than the UWB transmission





For radiated emissions from 30MHz~1GHz

Investigated emissions from digital circuitry used to control additional functions or capabilities other than the UWB transmission


**For radiated emissions above 960MHz**

Investigated emissions from digital circuitry used to control additional functions or capabilities other than the UWB transmission

**For conducted emissions above 960MHz (Conducted antenna port measurement)**


For radiated emissions above 1GHz

Investigated emissions from UWB transmission



For radiated emissions from 3GHz to 5GHz

Investigated emissions from UWB transmission



Note: The Horn Antenna maintaining bore sight alignment.

$$\theta = \tan^{-1} \left(\frac{\text{The Antenna's Height} - \text{The Table's Height}}{\text{The Test Distance}} \right)$$

3.3.5. Test Deviation

There is no deviation with the original standard.

3.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode, and TFC 4 and data rate is 53.3Mbps.


3.3.7. Results of Radiated Emissions***Radiated Emissions (9kHz~30MHz)***

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB) (in accordance with 47 CFR 15.31 (f) (2)); Limit line = specific limits (dBuV) + distance extrapolation factor.

Radiated Emissions (30MHz~960MHz)


Temperature	27 °C	Humidity	57 %
Test Engineer	Duncan	Configuration	All Band

Test Distance: 3m**Horizontal**

Freq	Level	Over Limit	Limit Line	Read		Antenna Level	Cable Factor	Preamp Loss	Remark
				MHz	dBm/m	dB	dBm/m	dBm	dB/m
1	88.590	33.79	-9.71	43.50	50.91	9.07	1.61	27.80	Peak
2	341.550	31.45	-14.55	46.00	42.15	14.80	3.13	28.62	Peak
3	895.830	32.02	-13.98	46.00	35.08	21.02	5.25	29.32	Peak

Note:

1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Distance: 3m**Vertical**


Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Remark
		Line	Limit	Level	Factor	Loss	Factor	
MHz	dBm/m	dB	dBm/m	dBm	dB/m	dB	dB	
1 3	50.460	38.04	-1.96	40.00	56.59	8.03	1.24	27.82 QP
2	66.270	36.31	-3.69	40.00	56.53	6.13	1.42	27.77 QP
3 3	99.750	41.41	-2.09	43.50	56.30	11.20	1.73	27.82 QP

Note:

1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Radiated Emissions (960MHz~1GHz Emissions)

Temperature	27 °C	Humidity	57 %
Test Engineer	Duncan	Configuration	All Band


Test Distance: 3m**Horizontal**

Freq	Level	Over Limit	Limit	Read		Antenna Factor	Cable Preamp		Remark
				Line	Level		dB	dB/m	
1 @	960.000	-64.94	10.36	-75.30	-62.24	21.24	5.54	29.48	
2 @	998.640	-62.33	12.97	-75.30	-59.41	20.89	5.80	29.60	

Note: Measurements made with 1 MHz RBW/3MHz VBW (RMS detector) at 3m distances. 1 msec averaging time were used for these frequencies per bin point measurements. Emissions (Mark 1, 2) from digital circuitry used to enable the operation of the UWB transmitter shall comply with the limits in 47 CFR, Part 15, Subpart C, §15.209.

Test Distance: 3m

Vertical




Freq	Level	Limit	Over	Limit	Read	Antenna	Cable	Preamp	
			Line	Level	Factor	Loss	Factor	Remark	
MHz	dBm/m		dB	dBm/m		dBm	dB/m		dB
1 @	960.080	-66.39	8.91	-75.30	-63.69	21.24	5.54	29.48	
2 @	996.560	-60.29	15.01	-75.30	-57.42	20.92	5.69	29.47	

Note: Measurements made with 1 MHz RBW/3MHz VBW (RMS detector) at 3m distances. 1 msec averaging time were used for these frequencies per bin point measurements. Emissions (Mark 1, 2) from digital circuitry used to enable the operation of the UWB transmitter shall comply with the limits in 47 CFR, Part 15, Subpart C, §15.209.

Radiated Emissions with terminated antenna port (960MHz~1GHz)

Temperature	27 °C	Humidity	57 %
Test Engineer	Duncan	Configuration	All Band


Test Distance: 3m**Horizontal**

Freq	Level	Over Limit	Limit	Read		Antenna	Cable	Preamp	Loss	Factor	Remark
				MHz	dBm/m	dB	dBm/m	dBm	dB/m	dB	dB
1	960.000	-75.00	-42.00	-33.00	-72.30	21.24	5.54	29.48	Peak		
2	998.640	-75.00	-42.00	-33.00	-72.08	20.89	5.80	29.60	Peak		

Note: For digital circuitry used to enable the operation of the UWB transmitter shall comply with the limits in 47 CFR, Part 15, and Subpart C, §15.209.

Test Distance: 3m

Vertical




Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Remark
		Limit	Line	Antenna	Level Factor	Loss Factor	dB	
MHz	dBm/m	dB	dBm/m	dBm	dB/m	dB	dB	
1	960.080	-79.48	-46.48	-33.00	-76.78	21.24	5.54	29.48 Peak
2	996.560	-73.87	-40.87	-33.00	-71.00	20.92	5.69	29.47 Peak

Note: For digital circuitry used to enable the operation of the UWB transmitter shall comply with the limits in 47 CFR, Part 15, Subpart C, §15.209.

Conducted Antenna Port Emissions (960MHz~1GHz)

Temperature	24 °C	Humidity	54 %
Test Engineer	Sam	Configuration	All Band




Date: 14.JUL.2008 20:35:06

Note: Conducted antenna port measurements made with 1MHz RBW/3MHz VBW (RMS detector) at 50-ohm impedance. 1 msec averaging time were used for these frequencies per bin point measurements.

Radiated Emissions (1GHz~8GHz Emissions)

Temperature	27 °C	Humidity	57 %
Test Engineer	Duncan	Configuration	All Band


Test Distance: 3m**Horizontal**

Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Remark
		Limit	Line	Antenna	Level	Factor	Loss	
MHz	dBm/m	dB	dBm/m	dBm	dB/m	dB	dB	
1 0	1322.000	-66.34	8.96	-75.30	-58.83	25.12	1.21	33.84

Note: Measurements made with 1 MHz RBW/3MHz VBW (RMS detector) at 3m distances. 1 msec averaging time were used for these frequencies per bin point measurements. Emissions (Mark 1) from digital circuitry used to enable the operation of the UWB transmitter shall comply with the limits in 47 CFR, Part 15, Subpart C, §15.209.

Test Distance: 3m

Vertical




Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Remark
		Limit	Line	Level	Factor	Loss	Factor	
MHz	dBm/m	dB	dBm/m	dBm	dB/m	dB	dB	
1322.000	-67.01	8.29	-75.30	-59.50	25.12	1.21	33.84	

Note: Measurements made with 1 MHz RBW/3MHz VBW (RMS detector) at 3m distances. 1 msec averaging time were used for these frequencies per bin point measurements. Emissions (Mark 1) from digital circuitry used to enable the operation of the UWB transmitter shall comply with the limits in 47 CFR, Part 15, Subpart C, §15.209.

Radiated Emissions with terminated antenna port (1GHz~8GHz)

Temperature	27 °C	Humidity	57 %
Test Engineer	Duncan	Configuration	All Band

Test Distance: 3m**Horizontal**


Freq	Level	Over Limit	Limit Line	Read		Antenna	Cable	Preamp	Remark
				MHz	dBm/m	dB	dBm/m	dBm	dB/m
1	1322.000	-54.83	-31.37	-23.46	-47.32	25.12	1.21	33.84	Peak

Note:

1. Digital circuitry used to enable the operation of the UWB transmitter shall comply with the limits in 47 CFR, Part 15, and Subpart C, §15.209.

Test Distance: 3m

Vertical




Freq	Level	Over Limit	Line	ReadAntenna Level	Factor	Cable Loss	Preamp Factor	Remark
MHz	dBm/m	dB	dBm/m	dBm	dB/m	dB	dB	
1322.000	-56.31	-32.85	-23.46	-48.80	25.12	1.21	33.84	Peak

Note:

1. Digital circuitry used to enable the operation of the UWB transmitter shall comply with the limits in 47 CFR, Part 15, and Subpart C, §15.209.

Conducted Antenna Port Emissions (1GHz~8GHz)

Temperature	24 °C	Humidity	54 %
Test Engineer	Sam	Configuration	All Band




Date: 14.JUL.2008 20:36:24

Note:

Conducted antenna port measurements made with 1 MHz RBW/3MHz VBW (RMS detector) at 50-ohm impedance. 1 msec averaging time were used for these frequencies per bin point measurements.

Radiated Emissions (8GHz~12GHz Emissions)

Temperature	24 °C	Humidity	54 %
Test Engineer	Duncan	Configuration	All Band


Test Distance: 0.5m**Horizontal**

Date: 11.JUL.2008 19:35:19

Note: Measurements made with 1 MHz RBW/3MHz VBW (RMS detector) at 0.5m distances. 1 msec averaging time were used for these frequencies per bin point measurements.

Test Distance: 0.5m

Vertical




Date: 11.JUL.2008 19:33:50

Note: Measurements made with 1 MHz RBW/3MHz VBW (RMS detector) at 0.5m distances. 1 msec averaging time were used for these frequencies per bin point measurements.


Radiated Emissions (12GHz~15GHz Emissions)

Temperature	24 °C	Humidity	54 %
Test Engineer	Duncan	Configuration	All Band

Test Distance: 0.5m**Horizontal**

Date: 11.JUL.2008 20:34:14

Note: Measurements made with 1 MHz RBW/3MHz VBW (RMS detector) at 0.5m distances. 1 msec averaging time were used for these frequencies per bin point measurements.


Test Distance: 0.5m**Vertical**

Date: 11.JUL.2008 20:33:07

Note: Measurements made with 1 MHz RBW/3MHz VBW (RMS detector) at 0.5m distances. 1 msec averaging time were used for these frequencies per bin point measurements.

Radiated Emissions (15GHz~26.5GHz Emissions)

Temperature	24 °C	Humidity	54 %
Test Engineer	Duncan	Configuration	All Band


Test Distance: 0.5m**Horizontal**

Date: 11.JUL.2008 20:42:05

Note: Measurements made with 1 MHz RBW/3MHz VBW (RMS detector) at 0.5m distances. 1 msec averaging time were used for these frequencies per bin point measurements.

Test Distance: 0.5m

Vertical




Date: 11.JUL.2008 20:40:49

Note: Measurements made with 1 MHz RBW/3MHz VBW (RMS detector) at 0.5m distances. 1 msec averaging time were used for these frequencies per bin point measurements.

Radiated Emissions (26.5GHz~40GHz Emissions)

Temperature	24 °C	Humidity	54 %
Test Engineer	Duncan	Configuration	All Band


Test Distance: 0.5m**Horizontal**

Date: 11.JUL.2008 20:47:51

Note: Measurements made with 1 MHz RBW/3MHz VBW (RMS detector) at 0.5m distances. 1 msec averaging time were used for these frequencies per bin point measurements.

Test Distance: 0.5m

Vertical



Date: 11.JUL.2008 20:48:34

Note: Measurements made with 1 MHz RBW/3MHz VBW (RMS detector) at 0.5m distances. 1 msec averaging time were used for these frequencies per bin point measurements.

3.4. Radiated Emissions in GPS Bands Measurement

3.4.1. Limit

In addition to the radiated emission limits specified in the table in paragraph 3.5.1 of this report, UWB transmitters operating under the provisions of this section shall not exceed the following average limits when measured using a resolution bandwidth of no less than 1 kHz.

Freq. (MHz)	EIRP (dBm)
1164-1240	-85.3
1559-1610	-85.3

Note 1: This may be converted to a peak field strength level at 3 meters using $E(\text{dBuV/m}) = P(\text{dBm EIRP}) + 95.2 \text{ dB}$.

Note 2: Extrapolation factor when test distance other than 3m. (in accordance with 47 CFR 15.31 (f) (2))

From 3m to 1m. Distance extrapolation factor = $20 \log (\text{specific distance [3m]} / \text{test distance [1m]})$ (dB); Limit line = specific limits (dBuV) + distance extrapolation factor [9.54 dB].

From 3m to 0.5m. Distance extrapolation factor = $20 \log (\text{specific distance [3m]} / \text{test distance [0.5m]})$ (dB); Limit line = specific limits (dBuV) + distance extrapolation factor [15.56 dB].

3.4.2. Measuring Instruments and Setting

Please refer to equipments list in section 4 of this report. The following table is the setting of the spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	0 dB
RBW / VBW	47 CFR Section 15.517(d) 10 kHz / 1kHz for RMS for Average, 1 msec averaging time were used for these measurement frequencies. 47 CFR Section 15.521(c) (47 CFR Section 15.209 (a)) 1MHz/1MHz for peak, 1MHz/10Hz for Average. (in accordance with ANSI C63.4)

3.4.3. Test Procedures

1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable that is non-conductive material (glass fiber) and 0.8 meter above ground. The EUT was flush on the back of the tabletop. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 1 meter far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between 1 meter and 4 meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scanning (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Measurements frequencies were maximized using a spectrum analyzer with RMS detector capabilities.

A spectrum analyzer was used for the final measurements utilizing an RMS detector at the frequencies with the largest amplitudes. The prescribed RBW of 10 kHz and VBW of 1 kHz, and a 1 msec averaging time were used for these measurements.

6. Per 47 CFR, Part 15, Subpart F, §15.521(c) (§15.209) all digital emissions from the transmitter not intended to be radiated from the antenna port meet the 15.209 subpart C limits.

3.4.4. Test Setup Layout

This test setup layout is the same as that shown in section 3.4.4.

3.4.5. Test Deviation

There is no deviation with the original standard.


3.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode, and TFC 4 and data rate is 53.3Mbps.

3.4.7. Results for Radiated Emissions in GPS Bands

Radiated Emissions (1164 MHz to 1240 MHz and 1559 MHz to 1610 MHz) GPS Bands

Temperature	27°C	Humidity	57%
Test Engineer	Duncan	Configuration	All Band


Test Distance: 3m**Horizontal**

Freq	Level	Over Limit	Line	Read		Antenna Factor	Cable Loss	Preamp Factor	Remark
				dB	dBm/m				
1	1229.560	-89.31	-4.01	-85.30	-81.29	24.88	1.11	34.01	
2	1600.190	-87.40	-2.10	-85.30	-81.52	26.04	1.52	33.44	

Note: Measurements made with 10kHz RBW/10KHz VBW (RMS detector) at 3m distances. 1 msec averaging time were used for these frequencies per bin point measurements.

Test Distance: 3m

Vertical



Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Remark
		Limit	Line	Level	Factor	Loss	Factor	
MHz	dBm/m	dB	dBm/m	dBm	dB/m	dB	dB	
1	1217.070	-89.21	-3.91	-85.30	-81.14	24.83	1.11	34.01
2	1600.190	-86.63	-1.33	-85.30	-80.75	26.04	1.52	33.44

Note: Measurements made with 10kHz RBW/10KHz VBW (RMS detector) at 3m distances. 1 msec averaging time were used for these frequencies per bin point measurements.

3.5. Peak Emissions within a 50 MHz Bandwidth Measurement

3.5.1. Limit

There is a limit on the peak level of the emissions contained within a 50 MHz bandwidth centered on the frequency at which the highest radiated emission occurs, f_M . That limit is 0 dBm EIRP. It is acceptable to employ a different resolution bandwidth, and a correspondingly different peak emission limit, EIRP limit has to be adjusted by the resolution bandwidth ratio of $20\log(RBW/50)$ dB, where RBW is the resolution bandwidth used for the measurement expressed in MHz. In addition, This may be converted to a peak field strength level at 3 meters using $E(dBuV/m) = P(dBm EIRP) + 95.2$ dB.

Peak EIRP limit dBm (RB / VB : 50MHz)	Peak EIRP limit dBm (RB / VB: 10MHz)
0	-13.97

3.5.2. Measuring Instruments and Setting


Please refer to equipments list in section 4 of this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Sweep Time	Auto
RBW / VBW	10MHz / 10MHz for Peak

3.5.3. Test Procedures

1. The EUT was placed on the top of the turntable that is non-conductive material (glass fiber) and 0.8 meter above ground. The EUT was flush on the back of the tabletop. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. The horn receiving antenna was varied between 1 meter and 4 meters, 1 meter step above ground while maintaining bore sight alignment to find the maximum emissions field strength of both horizontal and vertical polarization.
3. For maximum peak emission amplitude, the antenna tower was scanning (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading and was used to determine the frequency at which the highest radiated emission occurs, f_M .
4. The individual UWB bandwidths were measured for each BAND_ID (n_b) of the UWB spectrum. Both horizontal and vertical polarizations were taken into account to determine the full UWB BW on the maximized (in azimuth and elevation) signals.
5. A spectrum analyzer was used for the final measurement utilizing a peak detector at the frequency with the largest amplitude. The spectrum analyzer did not support the prescribed resolution bandwidth of 50 MHz. However, when a peak measurement is required, The resolution bandwidth for this measurement was set to 10 MHz, and the measurement was centered on the frequency at which the highest radiated emission occurred, f_M . The video bandwidth was 10 MHz.

3.5.4. Test Setup Layout



Note: The Horn Antenna maintaining bore sight alignment.

$$\theta = \tan^{-1} \left(\frac{\text{The Antenna's Height} - \text{The Table's Height}}{\text{The Test Distance}} \right)$$

3.5.5. Test Deviation


There is no deviation with the original standard.

3.5.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode, and TFC 4 and data rate is 53.3Mbps.

3.5.7. Test Result of Peak Emissions within a 50 MHz Bandwidth

Temperature	27 °C	Humidity	57 %
Test Engineer	Duncan	Configuration	All Band

Horizontal


Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Remark
		Limit	Line	Level	Factor	Loss	Factor	
MHz	dBm/m	dB	dBm/m	dBm	dB/m	dB	dB	
1	3660.000	-20.44	-6.47	-13.97	-22.95	32.17	3.13	32.78 Peak
2	4108.000	-24.03	-10.06	-13.97	-28.92	32.98	4.41	32.49 Peak
3	4294.000	-24.48	-10.51	-13.97	-29.19	32.94	4.27	32.50 Peak

Note:

1. Test distance: 3m, the antenna height 1 to 4 meters, 1-meter steps, bore sighted to EUT.
2. There are the absorber on ground plane between the antenna tower and turntable.

Temperature	27 °C	Humidity	57 %
Test Engineer	Duncan	Configuration	All Band

Vertical



	Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp
			Limit	Line	Level	Factor	Loss	Factor
	MHz	dBm/m	dB	dBm/m	dBm	dB/m	dB	dB
1	3612.000	-23.71	-9.74	-13.97	-25.94	32.09	2.97	32.83 Peak
2	4038.000	-25.23	-11.26	-13.97	-30.21	32.99	4.48	32.49 Peak
3	4468.000	-26.23	-12.26	-13.97	-30.73	32.91	4.10	32.51 Peak

Note:

1. Test distance: 3m, the antenna height 1 to 4 meters, 1-meter steps, bore sighted to EUT.
2. There are the absorber on ground plane between the antenna tower and turntable.

3.6. Labeling and Instruction Manual Requirements

UWB device subject to certification shall be labeled as followed in a conspicuous location on the device: "This device complied with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation."

(1) Where a device is constructed in two or more sections connected by wires and marketed together, the statement specified directly above this section is required to be affixed only to the main control unit.

(2) When the device is so small or for such use that it is not practicable to place the statement specified under paragraph (a) of this section on it, the information required by this paragraph shall be placed in a prominent location in the instruction manual or pamphlet supplied to the user or, alternatively, shall be placed on the container in which the device is marketed. However, the FCC identifier or the unique identifier, as appropriate, must be displayed on the device.

The users' manual or instruction manual for an intentional or unintentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

3.7. Antenna Requirements

3.7.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

3.7.2. Antenna Connector Construction

Please refer to section 2.1 in this test report, antenna connector complied with the requirements.

4. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Spectrum Analyzer	R&S	FSP30	100023	9kHz ~ 30GHz	Jan. 10, 2008	Conducted (TH01-HY)
Power Meter	R&S	NRVS	100444	DC ~ 40GHz	Jul. 11, 2008	Conducted (TH01-HY)
Power Sensor	R&S	NRV-Z51	100458	DC ~ 30GHz	Jul. 11, 2008	Conducted (TH01-HY)
Power Sensor	R&S	NRV-Z32	100057	30MHz ~ 6GHz	Jul. 11, 2008	Conducted (TH01-HY)
AC Power Source	HPC	HPA-500W	HPA-9100024	AC 0 ~ 300V	May 30, 2008*	Conducted (TH01-HY)
DC Power Source	G.W.	GPC-6030D	C671845	DC 1V ~ 60V	Mar. 13, 2008	Conducted (TH01-HY)
Temp. and Humidity Chamber	KSON	THS-C3L	612	N/A	Oct. 01, 2007	Conducted (TH01-HY)
RF CABLE-1m	Jye Bao	RG142	CB034-1m	20MHz ~ 7GHz	Dec. 01, 2007	Conducted (TH01-HY)
RF CABLE-2m	Jye Bao	RG142	CB035-2m	20MHz ~ 1GHz	Dec. 01, 2007	Conducted (TH01-HY)
Vector Signal Generator	R&S	SMU200A	102098	100kHz ~ 6GHz	Nov. 14, 2007	Conducted (TH01-HY)
Signal Generator	R&S	SMR40	100116	10MHz ~ 40GHz	Mar. 10, 2008	Conducted (TH01-HY)
Spectrum Analyzer	R&S	FSP30	100023	9kHz ~ 30GHz	Jan. 10, 2008	Conducted (TH01-HY)
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	30 MHz - 1 GHz 3m	Jun. 13, 2008	Radiation (03CH03-HY)
Amplifier	SCHAFFNER	COA9231A	18667	9 kHz - 2 GHz	Jan. 15, 2008	Radiation (03CH03-HY)
Amplifier	Agilent	8449B	3008A02120	1 GHz - 26.5 GHz	Jun. 06, 2008	Radiation (03CH03-HY)
Amplifier	MITEQ	AMF-6F-260400	9121372	26.5 GHz - 40 GHz	Jan. 22, 2007*	Radiation (03CH03-HY)
Spectrum Analyzer	R&S	FSP40	100004	9 kHz - 40 GHz	Sep. 27, 2007	Radiation (03CH03-HY)
Loop Antenna	R&S	HFH2-Z2	860004/001	9 kHz - 30 MHz	May 23, 2006*	Radiation (03CH03-HY)
Bilog Antenna	SCHAFFNER	CBL 6112D	22237	30 MHz - 1 GHz	Jul. 21, 2007	Radiation (03CH03-HY)
Horn Antenna	EMCO	3115	6741	1GHz ~ 18GHz	Apr. 05, 2008	Radiation (03CH03-HY)
Horn Antenna	SCHWARZBECK	BBHA9170	BBHA9170154	15 GHz - 40 GHz	Jan. 19, 2008	Radiation (03CH03-HY)
RF Cable-R03m	Jye Bao	RG142	CB021	30 MHz - 1 GHz	Dec. 03, 2007	Radiation (03CH03-HY)
RF Cable-HIGH	SUHNER	SUCOFLEX 106	03CH03-HY	1 GHz - 40 GHz	Dec. 03, 2007	Radiation (03CH03-HY)
Turn Table	HD	DS 420	420/650/00	0 - 360 degree	N/A	Radiation (03CH03-HY)
Antenna Mast	HD	MA 240	240/560/00	1 m - 4 m	N/A	Radiation (03CH03-HY)

Note: Calibration Interval of instruments listed above is one year. NCR: Non-Calibration required.

** Calibration Interval of instruments listed above is two year.

5. TEST LOCATION

SHIJR	ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C. TEL : 886-2-2696-2468 FAX : 886-2-2696-2255
HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-318-0055
LINKOU	ADD : No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C TEL : 886-2-2601-1640 FAX : 886-2-2601-1695
DUNGHU	ADD : No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei, Taiwan 114, R.O.C. TEL : 886-2-2631-4739 FAX : 886-2-2631-9740
JUNGHE	ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C. TEL : 886-2-8227-2020 FAX : 886-2-8227-2626
NEIHU	ADD : 4Fl., No. 339, Hsin Hu 2 nd Rd., Taipei 114, Taiwan, R.O.C. TEL : 886-2-2794-8886 FAX : 886-2-2794-9777
JHUBEI	ADD : No.8, Lane 728, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

6. TAF CERTIFICATE OF ACCREDITATION



Certificate No. : L1190-070110

財團法人全國認證基金會
Taiwan Accreditation Foundation

Certificate of Accreditation

This is to certify that

Sporton International Inc.
EMC & Wireless Communications Laboratory
No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien,
Taiwan, R.O.C.

is accredited in respect of laboratory

Accreditation Criteria : ISO/IEC 17025:2005
Accreditation Number : 1190
Originally Accredited : December 15, 2003
Effective Period : January 10, 2007 to January 09, 2010
Accredited Scope : Testing Field, see described in the Appendix
Specific Accreditation Program : Accreditation Program for Designated Testing Laboratory
for Commodities Inspection
Accreditation Program for Telecommunication Equipment
Testing Laboratory


Jay-San Chen
President, Taiwan Accreditation Foundation
Date : January 10, 2007

PI, total 9 pages


The Appendix forms an integral part of this Certificate, which shall be invalid when used without the Appendix.

Appendix A. Test Photos


1. Photographs of Radiated Emissions Test Configuration

For radiated emissions below 30MHz

FRONT VIEW




REAR VIEW




For radiated emissions above 30MHz

FRONT VIEW




REAR VIEW




For radiated emissions from 3GHz to 5GHz


FRONT VIEW



REAR VIEW




REAR VIEW




For radiated emissions above 1GHz


FRONT VIEW





REAR VIEW




REAR VIEW



APPENDIX B. Photographs of EUT





831717-01



831717-01

