

TEST REPORT

Reference No...... : WTX23X11235703W001
FCC ID : TZV-ET10
Applicant : ShenZhen WFLY Technology Development Co., Ltd.
Address : C3 Building,Xiangli Industrial Park,Haoye Road,Zhancheng Community,
Fuhai Subdistrict Office,BaoanShenzhen,Guangdong, China
Manufacturer : The same as Applicant
Address : The same as Applicant
Product Name : Model remote control
Model No...... : ET10
Standards : FCC Part 15.247
Date of Receipt sample : 2023-11-03
Date of Test..... : 2023-11-03 to 2023-11-22
Date of Issue : 2023-11-22
Test Report Form No. : WTX_Part 15_247W
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of approver.

Prepared By:


Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,
Block 70 Bao'an District, Shenzhen, Guangdong, China

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Email: sem@waltek.com.cn

Tested by:

Approved by:



Mike Shi

Silin Chen

TABLE OF CONTENTS

1. GENERAL INFORMATION.....5

1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)5

1.2 TEST STANDARDS.....6

1.3 TEST METHODOLOGY6

1.4 TEST FACILITY6

1.5 EUT SETUP AND TEST MODE7

1.6 MEASUREMENT UNCERTAINTY8

1.7 TEST EQUIPMENT LIST AND DETAILS9

2. SUMMARY OF TEST RESULTS.....12

3 ANTENNA REQUIREMENT.....13

3.1 STANDARD APPLICABLE13

3.2 EVALUATION INFORMATION13

4. FREQUENCY HOPPING SYSTEM REQUIREMENTS.....14

4.1 STANDARD APPLICABLE14

4.2 FREQUENCY HOPPING SYSTEM14

5. QUANTITY OF HOPPING CHANNELS AND CHANNEL SEPARATION.....16

5.1 STANDARD APPLICABLE16

5.2 TEST SETUP BLOCK DIAGRAM16

5.3 TEST PROCEDURE16

5.4 SUMMARY OF TEST RESULTS/PLOTS.....17

6. DWELL TIME OF HOPPING CHANNEL18

6.1 STANDARD APPLICABLE18

6.2 TEST SETUP BLOCK DIAGRAM18

6.3 TEST PROCEDURE18

6.4 SUMMARY OF TEST RESULTS/PLOTS.....19

7. 20DB BANDWIDTH.....20

7.1 STANDARD APPLICABLE20

7.2 TEST SETUP BLOCK DIAGRAM20

7.3 TEST PROCEDURE20

7.4 SUMMARY OF TEST RESULTS/PLOTS.....21

8. RF OUTPUT POWER.....22

8.1 STANDARD APPLICABLE22

8.2 TEST SETUP BLOCK DIAGRAM22

8.3 TEST PROCEDURE22

8.4 SUMMARY OF TEST RESULTS/PLOTS.....22

9. FIELD STRENGTH OF SPURIOUS EMISSIONS.....23

9.1 STANDARD APPLICABLE23

9.2 TEST PROCEDURE23

9.3 CORRECTED AMPLITUDE & MARGIN CALCULATION.....25

9.4 SUMMARY OF TEST RESULTS/PLOTS.....25

10. OUT OF BAND EMISSIONS.....33

10.1 STANDARD APPLICABLE33

10.2 TEST PROCEDURE33

10.3 SUMMARY OF TEST RESULTS/PLOTS34

11. CONDUCTED EMISSIONS.....37

11.1 TEST PROCEDURE37

11.2 BASIC TEST SETUP BLOCK DIAGRAM37

11.3 TEST RECEIVER SETUP37

11.4 SUMMARY OF TEST RESULTS/PLOTS37

APPENDIX SUMMARY38

Reference No.: WTX23X11235703W001

APPENDIX A.....	39
APPENDIX B.....	43
APPENDIX C.....	46
APPENDIX D.....	48
APPENDIX PHOTOGRAPHS.....	53

Report version

Version No.	Date of issue	Description
Rev.00	2023-11-22	Original
/	/	/

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

General Description of EUT	
Product Name:	Model remote control
Trade Name:	WFLY
Model No.:	ET10
Adding Model(s):	ET10S, ET10X, ET10Pro, ET07, ET07S, ET07X, ET07Pro
Rated Voltage:	DC 7.4V by Battery
Rated Current:	≤180mA
Power Adapter:	/
<p><i>Note: The test data is gathered from a production sample, provided by the manufacturer. The appearance of others models listed in the report is different from main-test model ET10, but the circuit and the electronic construction do not change, declared by the manufacturer.</i></p>	

Technical Characteristics of EUT	
Frequency Range:	2405-2475MHz
RF Output Power:	18.23dBm (Conducted)
Modulation:	GFSK
Quantity of Channels:	64
Type of Antenna:	External Antenna
Antenna Gain:	2.56dBi

1.2 Test Standards

The tests were performed according to following standards:

FCC Rules Part 15.247: Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928MHz, 2400-2483.5MHz, and 5725-5850MHz.

558074 D01 15.247 Meas Guidance v05r02: Guidance for Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating under section 15.247 of the FCC rules.

ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions.

1.4 Test Facility

Address of the test laboratory

Laboratory: Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road, Block 70 Bao'an District, Shenzhen, Guangdong, China

FCC – Registration No.: 125990

Waltek Testing Group (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. The Designation Number is CN5010, and Test Firm Registration Number is 125990.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Waltek Testing Group (Shenzhen) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A and the CAB identifier is CN0057.

1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	Low Channel	2405MHz
TM2	Middle Channel	2440MHz
TM3	High Channel	2475MHz
TM4	Hopping	2405-2475MHz

Test Conditions	
Temperature:	22~25 °C
Relative Humidity:	45~55 %
ATM Pressure:	1019 mbar

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
/	/	/	/

1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	$\pm 0.42\text{dB}$
Occupied Bandwidth	Conducted	$\pm 1.5\%$
Conducted Spurious Emission	Conducted	$\pm 2.17\text{dB}$
Conducted Emissions	Conducted	9-150kHz $\pm 3.74\text{dB}$
		0.15-30MHz $\pm 3.34\text{dB}$
Transmitter Spurious Emissions	Radiated	30-200MHz $\pm 4.52\text{dB}$
		0.2-1GHz $\pm 5.56\text{dB}$
		1-6GHz $\pm 3.84\text{dB}$
		6-26GHz $\pm 3.92\text{dB}$

1.7 Test Equipment List and Details

Fixed asset Number	Description	Manufacturer	Model	Serial No.	Cal Date	Due. Date
WTXE1041A 1001	Communication Tester	Rohde & Schwarz	CMW500	148650	2023-02-25	2024-02-24
WTXE1022A 1002	GSM Tester	Rohde & Schwarz	CMU200	114403	2023-02-25	2024-02-24
WTXE1005A 1005	Spectrum Analyzer	Agilent	N9020A	US471401 02	2023-02-25	2024-02-24
WTXE1084A 1001	Spectrum Analyzer	Agilent	N9020A	MY543205 48	2023-02-25	2024-02-24
WTXE1044A 1001	Signal Generator	Agilent	83752A	3610A014 53	2023-02-25	2024-02-24
WTXE1045A 1001	Vector Signal Generator	Agilent	N5182A	MY470702 02	2023-02-25	2024-02-24
WTXE1018A 1001	Power Divider	Weinschel	1506A	PM204	2023-02-25	2024-02-24
WTXE1045A 1001	Power Divider	RF-Lambda	RFLT4W5M18G	14110400 027	2023-02-25	2024-02-24
<input type="checkbox"/> Chamber A: Below 1GHz						
WTXE1005A 1003	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/03 5	2023-02-25	2024-02-24
WTXE1007A 1001	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/00 5	2023-02-25	2024-02-24
WTXE1007A 1001	Amplifier	HP	8447F	2805A034 75	2023-02-25	2024-02-24
WTXE1010A 1007	Loop Antenna	Schwarz beck	FMZB 1516	9773	2021-03-20	2024-03-19
WTXE1010A 1006	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2023-03-20	2026-03-19
<input type="checkbox"/> Chamber A: Above 1GHz						
WTXE1005A 1003	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/03 5	2023-02-25	2024-02-24
WTXE1007A 1001	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/00 5	2023-02-25	2024-02-24
WTXE1065A 1001	Amplifier	C&D	PAP-1G18	14918	2023-02-25	2024-02-24
WTXE1010A 1005	Horn Antenna	ETS	3117	00086197	2021-03-19	2024-03-18
WTXE1010A 1010	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2021-03-19	2024-03-18

WTXE1003A 1001	Pre-amplifier	Schwarzbeck	BBV 9721	9721-031	2023-02-25	2024-02-24
<input type="checkbox"/> Chamber B: Below 1GHz						
WTXE1010A 1006	Trilog Broadband Antenna	Schwarz beck	VULB9163(B)	9163-635	2021-04-09	2024-04-08
WTXE1038A 1001	Amplifier	Agilent	8447D	2944A104 57	2023-02-25	2024-02-24
WTXE1001A 1002	EMI Test Receiver	Rohde & Schwarz	ESPI	101391	2023-02-25	2024-02-24
<input checked="" type="checkbox"/> Chamber C: Below 1GHz						
WTXE1093A 1001	EMI Test Receiver	Rohde & Schwarz	ESIB 26	100401	2023-02-25	2024-02-24
WTXE1010A 1013-1	Trilog Broadband Antenna	Schwarz beck	VULB 9168	1194	2021-05-28	2024-05-27
WTXE1010A 1007	Loop Antenna	Schwarz beck	FMZB 1516	9773	2021-03-20	2024-03-19
WTXE1007A 1002	Amplifier	HP	8447F	2944A038 69	2023-02-25	2024-02-24
<input checked="" type="checkbox"/> Chamber C: Above 1GHz						
WTXE1093A 1001	EMI Test Receiver	Rohde & Schwarz	ESIB 26	100401	2023-02-25	2024-02-24
WTXE1103A 1005	Horn Antenna	POAM	RTF-118A	1820	2023-03-10	2026-03-09
WTXE1103A 1006	Amplifier	Tonscend	TAP01018050	AP22E806 235	2023-02-25	2024-02-24
WTXE1010A 1010	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2021-03-19	2024-03-18
WTXE1003A 1001	Pre-amplifier	Schwarzbeck	BBV 9721	9721-031	2023-02-25	2024-02-24
<input checked="" type="checkbox"/> Conducted Room 1#						
WTXE1001A 1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2023-02-25	2024-02-24
WTXE1002A 1001	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2023-02-25	2024-02-24
WTXE1003A 1001	AC LISN	Schwarz beck	NSLK8126	8126-279	2023-02-25	2024-02-24
<input type="checkbox"/> Conducted Room 2#						
WTXE1001A 1004	EMI Test Receiver	Rohde & Schwarz	ESPI	101259	2023-02-25	2024-02-24
WTXE1003A	LISN	Rohde &	ENV 216	100097	2023-02-25	2024-02-24

Reference No.: WTX23X11235703W001

1003		Schwarz				
------	--	---------	--	--	--	--

Software List			
Description	Manufacturer	Model	Version
EMI Test Software (Radiated Emission)*	Farad	EZ-EMC	RA-03A1
EMI Test Software (Conducted Emission Room 1#)*	Farad	EZ-EMC	RA-03A1
EMI Test Software (Conducted Emission Room 2#)*	SKET	EMC-I	V2.0

*Remark: indicates software version used in the compliance certification testing.

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§15.203; §15.247(b)(4)(i)	Antenna Requirement	Compliant
§15.205	Restricted Band of Operation	Compliant
§15.207(a)	Conducted Emission	N/A
§15.209(a)	Radiated Spurious Emissions	Compliant
§15.247(a)(1)(iii)	Quantity of Hopping Channel	Compliant
§15.247(a)(1)	Channel Separation	Compliant
§15.247(a)(1)(iii)	Time of Occupancy (Dwell time)	Compliant
§15.247(a)	20dB Bandwidth	Compliant
§15.247(b)(1)	RF Power Output	Compliant
§15.247(d)	Band Edge (Out of Band Emissions)	Compliant
§15.247(a)(1)	Frequency Hopping Sequence	Compliant
§15.247(g), (h)	Frequency Hopping System	Compliant

N/A: Not applicable.

3 Antenna Requirement

3.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.2 Evaluation Information

This product has an External Antenna, fulfill the requirement of this section.

4. Frequency Hopping System Requirements

4.1 Standard Applicable

According to FCC Part 15.247(a)(1), the system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

(g) Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

(h) The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

4.2 Frequency Hopping System

This transmitter device is frequency hopping device, and complies with FCC part 15.247 rule.

This device uses transmitter radio which operates in 2400-2483.5MHz band. It uses a radio technology called frequency-hopping spread spectrum.

This device was tested with a system receiver to check that the device maintained hopping synchronization, and the device complied with these requirements for 558074 D01 15.247 Meas Guidance v05r02 and FCC Part 15.247 rule.

The device employs 71 channels as below and select 64 frequency hopping channels randomly for use.


Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2405	19	2423	37	2441	55	2459
2	2406	20	2424	38	2442	56	2460
3	2407	21	2425	39	2443	57	2461
4	2408	22	2426	40	2444	58	2462
5	2409	23	2427	41	2445	59	2463
6	2410	24	2428	42	2446	60	2464
7	2411	25	2429	43	2447	61	2465
8	2412	26	2430	44	2448	62	2466
9	2413	27	2431	45	2449	63	2467
10	2414	28	2432	46	2450	64	2468
11	2415	29	2433	47	2451	65	2469
12	2416	30	2434	48	2452	66	2470
13	2417	31	2435	49	2453	67	2471
14	2418	32	2436	50	2454	68	2472
15	2419	33	2437	51	2455	69	2473
16	2420	34	2438	52	2456	70	2474
17	2421	35	2439	53	2457	71	2475
18	2422	36	2440	54	2458		

5. Quantity of Hopping Channels and Channel Separation

5.1 Standard Applicable

According to FCC 15.247(a)(1), frequency hopping systems operating in the 2400-2483.5MHz band may have hopping channel carrier frequencies that are separated by 25kHz or two-thirds of the 20dB bandwidth of the hopping channel, and frequency hopping systems in the 2400-2483.5MHz band shall use at least 15 channels.

5.2 Test Setup Block Diagram



5.3 Test Procedure

According to KDB 558074 D01 v05r02 Subclause 9 and ANSI C63.10-2013 section 7.8.3, the number of hopping frequencies test method as follows.

- a) Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
- b) RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
- c) VBW \geq RBW.
- d) Sweep: Auto.
- e) Detector function: Peak.
- f) Trace: Max hold.
- g) Allow the trace to stabilize.

According to KDB 558074 D01 v05r02 Subclause 9 and ANSI C63.10-2013 section 7.8.2, the EUT shall have its hopping function enabled, the Carrier frequency separation test method as follows:

- a) Span: Wide enough to capture the peaks of two adjacent channels.
- b) RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
- c) Video (or average) bandwidth (VBW) \geq RBW.
- d) Sweep: Auto.

Reference No.: WTX23X11235703W001

e) Detector function: Peak.

f) Trace: Max hold.

g) Allow the trace to stabilize.

Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

5.4 Summary of Test Results/Plots


Please refer to Appendix A

6. Dwell Time of Hopping Channel

6.1 Standard Applicable

According to 15.247(a)(1)(iii), frequency hopping systems in the 2400–2483.5MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

6.2 Test Setup Block Diagram



6.3 Test Procedure

According to KDB 558074 D01 v05r02 Subclause 9 and ANSI C63.10-2013 section 7.8.4, the dwell time of a hopping channel test method as follows.

- a) Span: Zero span, centered on a hopping channel.
- b) RBW shall be \leq channel spacing and where possible RBW should be set $\gg 1 / T$, where T is the expected dwell time per channel.
- c) Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel.
- d) Detector function: Peak.
- e) Trace: Max hold.

Use the marker-delta function to determine the transmit time per hop. If this value varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation in transmit time.

Repeat the measurement using a longer sweep time to determine the number of hops over the period specified in the requirements. The sweep time shall be equal to, or less than, the period specified in the requirements. Determine the number of hops over the sweep time and calculate the total number of hops in the period specified in the requirements, using the following equation:

$$(\text{Number of hops in the period specified in the requirements}) = (\text{number of hops on spectrum analyzer}) \times (\text{period specified in the requirements} / \text{analyzer sweep time})$$

The average time of occupancy is calculated from the transmit time per hop multiplied by the number of hops

Reference No.: WTX23X11235703W001

in the period specified in the requirements. If the number of hops in a specific time varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation.

The measured transmit time and time between hops shall be consistent with the values described in the operational description for the EUT.

6.4 Summary of Test Results/Plots


Please refer to Appendix B

7. 20dB Bandwidth

7.1 Standard Applicable

According to 15.247(a) and 15.215(c), 20dB bandwidth is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

7.2 Test Setup Block Diagram



7.3 Test Procedure

According to KDB 558074 D01 v05r02 Subclause 9 and ANSI C63.10-2013 section 6.9.2, the 20dB bandwidth test method as follows.

- a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the EMI receiver or spectrum analyzer shall be between two times and five times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately three times RBW, unless otherwise specified by the applicable requirement.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (\text{OBW}/\text{RBW})]$ below the reference level.
- d) Steps a) through c) might require iteration to adjust within the specified tolerances.
- e) The dynamic range of the instrument at the selected RBW shall be more than 10 dB below the target “-xx dB down” requirement; that is, if the requirement calls for measuring the -20 dB OBW, the instrument noise floor at the selected RBW shall be at least 30 dB below the reference value.
- f) Set detection mode to peak and trace mode to max hold.
- g) Determine the reference value: Set the EUT to transmit an unmodulated carrier or modulated signal, as applicable. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace (this is the reference value).
- h) Determine the “-xx dB down amplitude” using $[(\text{reference value}) - \text{xx}]$. Alternatively, this calculation may be made by using the marker-delta function of the instrument.
- i) If the reference value is determined by an unmodulated carrier, then turn the EUT modulation ON, and either clear the existing trace or start a new trace on the spectrum analyzer and allow the new trace to

stabilize. Otherwise, the trace from step g) shall be used for step j).

j) Place two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-xx dB down amplitude” determined in step h). If a marker is below this “-xx dB down amplitude” value, then it shall be as close as possible to this value. The occupied bandwidth is the frequency difference between the two markers. Alternatively, set a marker at the lowest frequency of the envelope of the spectral display, such that the marker is at or slightly below the “-xx dB down amplitude” determined in step h). Reset the marker-delta function and move the marker to the other side of the emission until the delta marker amplitude is at the same level as the reference marker amplitude. The marker-delta frequency reading at this point is the specified emission bandwidth.

k) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

7.4 Summary of Test Results/Plots


Please refer to Appendix C

8. RF Output Power

8.1 Standard Applicable

According to 15.247(b)(1), for frequency hopping systems operating in the 2400–2483.5MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5MHz band: 0.125 watts.

8.2 Test Setup Block Diagram



8.3 Test Procedure

According to KDB 558074 D01 v05r02 Subclause 9 and ANSI C63.10-2013 section 7.8.5, the output power test method as follows.

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

This is an RF-conducted test to evaluate maximum peak output power. Use a direct connection between the antenna port of the unlicensed wireless device and the spectrum analyzer, through suitable attenuation. The hopping shall be disabled for this test:

- a) Use the following spectrum analyzer settings:
 - 1) Span: Approximately five times the 20dB bandwidth, centered on a hopping channel.
 - 2) RBW > 20dB bandwidth of the emission being measured.
 - 3) VBW \geq RBW.
 - 4) Sweep: Auto.
 - 5) Detector function: Peak.
 - 6) Trace: Max hold.
- b) Allow trace to stabilize.
- c) Use the marker-to-peak function to set the marker to the peak of the emission.
- d) The indicated level is the peak output power, after any corrections for external attenuators and cables.
- e) A plot of the test results and setup description shall be included in the test report.

8.4 Summary of Test Results/Plots

Please refer to Appendix D

9. Field Strength of Spurious Emissions

9.1 Standard Applicable

According to §15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30dB instead of 20dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).


The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

9.2 Test Procedure


The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40cm long in the middle. The spacing between the peripherals was 10cm.


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30MHz to 1GHz.



The test setup for emission measurement above 1GHz.



Frequency :9kHz-30MHz
 RBW=10KHz,
 VBW =30KHz
 Sweep time= Auto
 Trace = max hold
 Detector function = peak

Frequency :30MHz-1GHz
 RBW=120KHz,
 VBW=300KHz
 Sweep time= Auto
 Trace = max hold
 Detector function = peak, QP

Frequency :Above 1GHz
 RBW=1MHz,
 VBW=3MHz(Peak), 10Hz(AV)
 Sweep time= Auto
 Trace = max hold
 Detector function = peak, AV

9.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\begin{aligned}\text{Corr. Ampl.} &= \text{Indicated Reading} + \text{Correct} \\ \text{Correct} &= \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}\end{aligned}$$

The "**Margin**" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB μ V means the emission is 6dB μ V below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$


9.4 Summary of Test Results/Plots

Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.

All test modes (different data rate and different modulation) are performed, but only the worst case (GFSK) is recorded in this report.


➤ Spurious Emissions Below 1GHz

Test Channel	Low Channel	Polarity:	Horizontal
--------------	-------------	-----------	------------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	40.0173	28.51	-8.47	20.04	40.00	-19.96	-	-	QP
2	78.0143	28.38	-12.53	15.85	40.00	-24.15	-	-	QP
3	164.3129	29.04	-8.72	20.32	43.50	-23.18	-	-	QP
4	264.9709	39.97	-9.55	30.42	46.00	-15.58	-	-	QP
5	415.4486	35.29	-5.54	29.75	46.00	-16.25	-	-	QP
6	862.8015	31.80	0.85	32.65	46.00	-13.35	-	-	QP

Test Channel	Low Channel	Polarity:	Vertical
--------------	-------------	-----------	----------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	51.8999	27.35	-8.29	19.06	40.00	-20.94	-	-	QP
2	144.7899	39.85	-9.03	30.82	43.50	-12.68	-	-	QP
3	240.1442	44.15	-10.54	33.61	46.00	-12.39	-	-	QP
4	304.9548	35.84	-8.12	27.72	46.00	-18.28	-	-	QP
5	392.7376	37.81	-6.11	31.70	46.00	-14.30	-	-	QP
6	471.4665	35.33	-4.29	31.04	46.00	-14.96	-	-	QP

Test Channel	Middle Channel	Polarity:	Horizontal
--------------	----------------	-----------	------------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	49.4087	28.19	-8.13	20.06	40.00	-19.94	-	-	QP
2	151.0252	34.70	-8.61	26.09	43.50	-17.41	-	-	QP
3	211.6112	36.55	-12.16	24.39	43.50	-19.11	-	-	QP
4	270.6162	40.52	-9.30	31.22	46.00	-14.78	-	-	QP
5	436.3956	37.59	-4.96	32.63	46.00	-13.37	-	-	QP
6	804.2523	34.29	0.34	34.63	46.00	-11.37	-	-	QP

Test Channel	Middle Channel	Polarity:	Vertical
--------------	----------------	-----------	----------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	44.7793	28.96	-8.47	20.49	40.00	-19.51	-	-	QP
2	144.7899	39.85	-9.03	30.82	43.50	-12.68	-	-	QP
3	240.1442	44.15	-10.54	33.61	46.00	-12.39	-	-	QP
4	264.9709	46.80	-9.55	37.25	46.00	-8.75	-	-	QP
5	353.4472	41.19	-7.02	34.17	46.00	-11.83	-	-	QP
6	607.1806	33.72	-1.64	32.08	46.00	-13.92	-	-	QP

Test Channel	High Channel	Polarity:	Horizontal
--------------	--------------	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	41.4483	28.70	-8.48	20.22	40.00	-19.78	-	-	QP
2	151.0252	34.70	-8.61	26.09	43.50	-17.41	-	-	QP
3	270.6162	40.52	-9.30	31.22	46.00	-14.78	-	-	QP
4	379.1780	37.68	-6.38	31.30	46.00	-14.70	-	-	QP
5	448.8361	38.39	-4.61	33.78	46.00	-12.22	-	-	QP
6	932.1405	35.20	1.87	37.07	46.00	-8.93	-	-	QP

Test Channel	High Channel	Polarity:	Vertical
--------------	--------------	-----------	----------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	54.1349	29.42	-8.54	20.88	40.00	-19.12	-	-	QP
2	144.7899	39.85	-9.03	30.82	43.50	-12.68	-	-	QP
3	240.1442	44.15	-10.54	33.61	46.00	-12.39	-	-	QP
4	259.4434	48.58	-9.79	38.79	46.00	-7.21	-	-	QP
5	353.4472	41.19	-7.02	34.17	46.00	-11.83	-	-	QP
6	607.1806	33.72	-1.64	32.08	46.00	-13.92	-	-	QP

Remark: '-' Means the test Degree and Height are not recorded by the test software and only show the worst case in the test report.

➤ Spurious Emissions Above 1GHz

Frequency (MHz)	Reading (dBuV/m)	Correct dB	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Polar H/V	Detector
Low Channel-2405MHz							
4810.00	54.77	-4.52	50.25	74	-23.75	H	PK
4810.00	51.69	-4.52	47.17	54	-6.83	H	AV
7215.00	56.54	-2.20	54.34	74	-19.66	H	PK
7215.00	45.58	-2.20	43.38	54	-10.62	H	AV
4810.00	54.64	-4.52	50.12	74	-23.88	V	PK
4810.00	49.22	-4.52	44.70	54	-9.30	V	AV
7215.00	53.64	-2.20	51.44	74	-22.56	V	PK
7215.00	45.60	-2.20	43.40	54	-10.60	V	AV
Middle Channel-2440MHz							
4880.00	54.46	-4.47	49.99	74	-24.01	H	PK
4880.00	51.68	-4.47	47.21	54	-6.79	H	AV
7320.00	56.93	-2.17	54.76	74	-19.24	H	PK
7320.00	45.45	-2.17	43.28	54	-10.72	H	AV
4880.00	54.47	-4.47	50.00	74	-24.00	V	PK
4880.00	50.53	-4.47	46.06	54	-7.94	V	AV
7320.00	53.80	-2.17	51.63	74	-22.37	V	PK
7320.00	45.16	-2.17	42.99	54	-11.01	V	AV
High Channel-2475MHz							
4950.00	55.37	-4.42	50.95	74	-23.05	H	PK
4950.00	52.38	-4.42	47.96	54	-6.04	H	AV
7425.00	58.12	-2.14	55.98	74	-18.02	H	PK
7425.00	45.26	-2.14	43.12	54	-10.88	H	AV
4950.00	53.51	-4.42	49.09	74	-24.91	V	PK
4950.00	49.47	-4.42	45.05	54	-8.95	V	AV
7425.00	56.33	-2.14	54.19	74	-19.81	V	PK
7425.00	45.82	-2.14	43.68	54	-10.32	V	AV

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

10. Out of Band Emissions

10.1 Standard Applicable

According to §15.247 (d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30dB instead of 20dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

10.2 Test Procedure

According to ANSI C63.10-2013 section 7.8.6, the Band-edge measurements for RF conducted emissions test method as follows.

- a) Connect the EMI receiver or spectrum analyzer to the EUT using an appropriate RF cable connected to the EUT output. Configure the spectrum analyzer settings as described in step e) (be sure to enter all losses between the unlicensed wireless device output and the spectrum analyzer).
- b) Set the EUT to the lowest frequency channel (for the hopping on test, the hopping sequence shall include the lowest frequency channel).
- c) Set the EUT to operate at maximum output power and 100% duty cycle, or equivalent “normal mode of operation” as specified in 6.10.3.
- d) If using the radiated method, then use the applicable procedure(s) of 6.4, 6.5, or 6.6, and orient the EUT and measurement antenna positions to produce the highest emission level.
- e) Perform the test as follows:
 - 1) Span: Wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products that fall outside of the authorized band of operation.
 - 2) Reference level: As required to keep the signal from exceeding the maximum instrument input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than [10 log (OBW/RBW)] below the reference level. Specific guidance is given in 4.1.5.2.
 - 3) Attenuation: Auto (at least 10 dB preferred).
 - 4) Sweep time: Coupled.
 - 5) Resolution bandwidth: 100kHz.
 - 6) Video bandwidth: 300kHz.
 - 7) Detector: Peak.
 - 8) Trace: Max hold.
- f) Allow the trace to stabilize. For the test with the hopping function turned ON, this can take several minutes

to achieve a reasonable probability of intercepting any emissions due to oscillator overshoot.

g) Set the marker on the emission at the band edge, or on the highest modulation product outside of the band, if this level is greater than that at the band edge. Enable the marker-delta function, and then use the marker-to-peak function to move the marker to the peak of the in-band emission.

h) Repeat step c) through step e) for every applicable modulation.

i) Set the EUT to the highest frequency channel (for the hopping on test, the hopping sequence shall include the highest frequency channel) and repeat step c) through step d).

j) The band-edge measurement shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

Restricted-band band-edge test method please refers to ANSI C63.10-2013 section 6.10.5. The emission must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205. Note that the method of measurement KDB publication number: 913591 may be used for the radiated band-edge measurements.


According to ANSI C63.10-2013 section 7.8.8, Conducted spurious emissions shall be measured for the transmit frequency, per 5.5 and 5.6, and at the maximum transmit powers.

Connect the primary antenna port through an attenuator to the spectrum analyzer input; in the results, account for all losses between the unlicensed wireless device output and the spectrum analyzer. The instrument shall span 30MHz to 10 times the operating frequency in GHz, with a resolution bandwidth of 100kHz, video bandwidth of 300kHz, and a coupled sweep time with a peak detector. The band 30MHz to the highest frequency may be split into smaller spans, as long as the entire spectrum is covered.

10.3 Summary of Test Results/Plots


Note: All test modes (different data rate and different modulation) are performed, but only the worst case (GFSK) is recorded in this report.

Test Channel	Low	Polarity:	Vertical(worst case)
--------------	-----	-----------	----------------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	47.89	-19.02	28.87	59.50	-30.63	Average Detector
		71.44	-19.02	52.42	79.50	-27.08	Peak Detector
2	2388.918	70.21	-18.87	51.34	59.50	-8.16	Average Detector
		94.08	-18.87	75.21	79.50	-4.29	Peak Detector
3	2390.000	61.97	-18.87	43.10	59.50	-16.40	Average Detector
		94.08	-18.87	75.21	79.50	-4.29	Peak Detector
4	2404.790	122.93	-18.84	104.09	/	/	Average Detector
		124.67	-18.84	105.83	/	/	Peak Detector

Test Channel	High	Polarity:	Vertical(worst case)
--------------	------	-----------	----------------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2474.870	122.53	-18.70	103.83	/	/	Average Detector
	2474.689	124.77	-18.70	106.07	/	/	Peak Detector
2	2483.500	64.79	-18.68	46.11	54.00	-7.89	Average Detector
	2483.500	88.29	-18.68	69.61	74.00	-4.39	Peak Detector
3	2490.862	70.09	-18.67	51.42	54.00	-2.58	Average Detector
4	2500.000	42.12	-18.65	23.47	54.00	-30.53	Average Detector
	2500.000	79.92	-18.65	61.27	74.00	-12.73	Peak Detector


11. Conducted Emissions

11.1 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40cm long in the middle. The spacing between the peripherals was 10cm.

11.2 Basic Test Setup Block Diagram



11.3 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency	150kHz
Stop Frequency	30MHz
Sweep Speed	Auto
IF Bandwidth.....	10kHz
Quasi-Peak Adapter Bandwidth	9kHz
Quasi-Peak Adapter Mode	Normal

11.4 Summary of Test Results/Plots

Not applicable


APPENDIX SUMMARY

Project No.	WTX23X11235703W	Test Engineer	BAldi Zhong
Start date	2023/11/14	Finish date	2023/11/21
Temperature	21.8°C	Humidity	44%
RF specifications	2.4GHz-FHSS		




APPENDIX	Description of Test Item	Result
A	Hopping Channels and Channel Separation	Compliant
B	Dwell Time of Hopping Channel	Compliant
C	20dB Bandwidth	Compliant
D	RF Output Power	Compliant

APPENDIX A

Hopping Channels Number			
Mode	Test Result	Limit	Result
FHSS	64	≥15	Pass




Channel Separation			
Mode	Channel	Carrier Frequencies Separation (kHz)	Result
FHSS	Low	1010	Pass
	Middle	1002	Pass
	High	1010	Pass

<p style="text-align: center;">Low</p>	 <p> RBW 30 kHz Delta 1 [F1] -0.00 dB VBW 100 kHz SWT 10 ms 1.010000000 MHz Ref 30 dBm +Att 40 dB 30 Offset 0.1 dB Marker 1 [F1] 17.97 dBm 2.448800000 GHz Center 2.405 GHz 500 kHz/ Span 5 MHz </p> <p>Date: 14.NOV.2023 09:10:32</p>
<p style="text-align: center;">Middle</p>	 <p> RBW 30 kHz Delta 1 [F1] -0.07 dB VBW 100 kHz SWT 5 ms 1.002000000 MHz Ref 30 dBm +Att 40 dB 30 Offset 0.1 dB Marker 1 [F1] 17.02 dBm 2.438800000 GHz Center 2.44 GHz 300 kHz/ Span 3 MHz </p> <p>Date: 14.NOV.2023 09:16:37</p>
<p style="text-align: center;">High</p>	 <p> RBW 30 kHz Delta 1 [F1] -0.10 dB VBW 100 kHz SWT 10 ms 1.010000000 MHz Ref 30 dBm +Att 40 dB 30 Offset 0.1 dB Marker 1 [F1] 16.28 dBm 2.472800000 GHz Center 2.475 GHz 500 kHz/ Span 5 MHz </p> <p>Date: 14.NOV.2023 09:17:50</p>


APPENDIX B

Test Channel	Test period (s)	Number of Bursts per Hopping Period	Burst Duration (ms)	Dwell time (ms)	Limit (ms)
Low	2.56	11	0.768	84.48	400
Middle	2.56	11	0.760	83.60	400
High	2.56	11	0.760	83.60	400

Low




Date: 14.NOV.2023 09:27:36






Date: 14.NOV.2023 12:44:11

Middle






Date: 14.NOV.2023 09:28:16

	 <p>Date: 14.NOV.2023 12:44:23</p>
<p>High</p>	 <p>Date: 14.NOV.2023 09:28:36</p>
	 <p>Date: 14.NOV.2023 12:45:52</p>




APPENDIX C

20 dB Bandwidth			
Test Mode	Channel	20 dB Bandwidth MHz	Result
FHSS	Low	1.056	Pass
	Middle	1.056	Pass
	High	1.062	Pass


<p>Low</p>	 <p> Ref 30 dBm +Att 40 dB +RBW 30 kHz Delta 1 [F1] -2.33 dB +VSW 100 kHz +SWT 5 ms 1.056000000 MHz 30 Offset 0.1 dB Marker 1 [F1] -2.33 dBm Marker 2 [F1] -2.33 dBm Marker 2 [F1] 18.06 dBm Marker 2 [F1] -2.33 dBm D1 -1.98 dBm Center 2.405 GHz 300 kHz/ Span 3 MHz Date: 14.NOV.2023 09:06:24 </p>
<p>Middle</p>	 <p> Ref 30 dBm +Att 40 dB +RBW 30 kHz Delta 1 [F1] -1.21 dB +VSW 100 kHz +SWT 5 ms 1.056000000 MHz 30 Offset 0.1 dB Marker 1 [F1] -3.81 dBm Marker 2 [F1] -3.81 dBm Marker 2 [F1] 17.06 dBm Marker 2 [F1] -3.81 dBm D1 -2.98 dBm Center 2.44 GHz 300 kHz/ Span 3 MHz Date: 14.NOV.2023 09:05:23 </p>
<p>High</p>	 <p> Ref 30 dBm +Att 40 dB +RBW 30 kHz Delta 1 [F1] 0.44 dB +VSW 100 kHz +SWT 5 ms 1.062000000 MHz 30 Offset 0.1 dB Marker 1 [F1] -6.80 dBm Marker 2 [F1] -6.80 dBm Marker 2 [F1] 16.32 dBm Marker 2 [F1] -6.80 dBm D1 -4.69 dBm Center 2.475 GHz 300 kHz/ Span 3 MHz Date: 14.NOV.2023 09:04:25 </p>

APPENDIX D


RF Output Power				
Modulation type	Channel	Output power (dBm)	Limit (dBm)	Result
FHSS	Low	18.23	30.00	Pass
	Middle	18.09		
	High	18.20		

<p>Low</p>	 <p>Ref 30 dBm Att 40 dB RBW 1 MHz Marker 1 [T1] 18.23 dBm VBW 3 MHz SWT 2.5 ms 2.404810000 GHz</p> <p>Offset 0.1 dB</p> <p>Center 2.405 GHz 500 kHz/ Span 5 MHz</p> <p>Date: 14.NOV.2023 09:01:49</p>
<p>Middle</p>	 <p>Ref 30 dBm Att 40 dB RBW 1 MHz Marker 1 [T1] 18.09 dBm VBW 3 MHz SWT 2.5 ms 2.439820000 GHz</p> <p>Offset 1 dB</p> <p>Center 2.44 GHz 500 kHz/ Span 5 MHz</p> <p>Date: 15.NOV.2023 14:28:03</p>
<p>High</p>	 <p>Ref 30 dBm Att 40 dB RBW 1 MHz Marker 1 [T1] 18.20 dBm VBW 3 MHz SWT 2.5 ms 2.475200000 GHz</p> <p>Offset 1 dB</p> <p>Center 2.475 GHz 500 kHz/ Span 5 MHz</p> <p>Date: 15.NOV.2023 14:28:18</p>


Conducted Out of Band Emissions



Middle




Date: 14.NOV.2023 09:33:32




Date: 14.NOV.2023 09:34:25


High



Date: 14.NOV.2023 09:35:50



Date: 14.NOV.2023 09:36:16



Date: 14.NOV.2023 09:41:01

APPENDIX PHOTOGRAPHS

Please refer to “ANNEX”

**** END OF REPORT ****