

FCC REPORT

Applicant: Radiolink Electronic Limited

Address of Applicant: 3/F, BLD2, FuGuo industrial park, KaiFeng North Road,
MeiLin Shenzhen China

Equipment Under Test (EUT)

Product Name: 2.4G Digital Proportional R/C system

Model No.: AT9

FCC ID: U2BRL039AT9

Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.247:2013

Date of sample receipt: October 23, 2014

Date of Test: November 24-26, 2014

Date of report issued: November 26, 2014

Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Robinson Lo
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the GTS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of GTS or testing done by GTS in connection with, distribution or use of the product described in this report must be approved by GTS in writing.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2 Version

Version No.	Date	Description
00	November 26, 2014	Original

Prepared By:

Sam. Gao

Date:

November 26, 2014

Project Engineer

Check By:

hank. yan.

Date:

November 26, 2014

Reviewer

3 Contents

	Page
1 COVER PAGE	1
2 VERSION	2
3 CONTENTS	3
4 TEST SUMMARY	4
5 GENERAL INFORMATION	5
5.1 CLIENT INFORMATION	5
5.2 GENERAL DESCRIPTION OF EUT	5
5.3 TEST MODE	7
5.4 TEST FACILITY	7
5.5 TEST LOCATION	7
5.6 OTHER INFORMATION REQUESTED BY THE CUSTOMER	7
5.7 DESCRIPTION OF SUPPORT UNITS	7
5.8 TEST INSTRUMENTS LIST	8
6 TEST RESULTS AND MEASUREMENT DATA	9
6.1 ANTENNA REQUIREMENT	9
6.2 CONDUCTED PEAK OUTPUT POWER	10
6.3 20dB EMISSION BANDWIDTH	12
6.4 CARRIER FREQUENCIES SEPARATION	14
6.5 HOPPING CHANNEL NUMBER	16
6.6 DWELL TIME	17
6.7 BAND EDGE	21
6.7.1 Conducted Emission Method	21
6.7.2 Radiated Emission Method	23
6.8 SPURIOUS EMISSION	26
6.8.1 Conducted Emission Method	26
6.8.2 Radiated Emission Method	28
7 TEST SETUP PHOTO	34
8 EUT CONSTRUCTIONAL DETAILS	36

4 Test Summary

Test Item	Section in CFR 47	Result
Antenna requirement	15.203/15.247 (c)	Pass
AC Power Line Conducted Emission	15.207	N/A
Conducted Peak Output Power	15.247 (b)(3)	Pass
Channel Bandwidth	15.247 (a)(2)	Pass
Power Spectral Density	15.247 (e)	Pass
Band Edge	15.247(d)	Pass
Spurious Emission	15.205/15.209	Pass

Pass: The EUT complies with the essential requirements in the standard.

5 General Information

5.1 Client Information

Applicant:	Radiolink Electronic Limited
Address of Applicant:	3/F, BLD2, FuGuo industrial park, KaiFeng North Road, MeiLin Shenzhen China
Manufacturer:	Radiolink Electronic Limited
Address of Manufacturer:	3/F, BLD2, FuGuo industrial park, KaiFeng North Road, MeiLin Shenzhen China

5.2 General Description of EUT

Product Name:	2.4G Digital Proportional R/C system
Model No.:	AT9
Operation Frequency:	2409MHz ~2474MHz
Channel numbers:	32
Channel separation:	2MHz
Modulation technology:	GFSK
Antenna Type:	Integral Antenna
Antenna gain:	2.00dBi (declare by Applicant)
Power supply:	DC 12V (8*"AA" battery)

Operation Frequency each of channel							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2409.0MHz	9	2425.0MHz	17	2444.0MHz	25	2460.0MHz
2	2411.0MHz	10	2427.0MHz	18	2446.0MHz	26	2462.0MHz
3	2413.0MHz	11	2429.0MHz	19	2448.0MHz	27	2464.0MHz
4	2415.0MHz	12	2431.0MHz	20	2450.0MHz	28	2466.0MHz
5	2417.0MHz	13	2433.0MHz	21	2452.0MHz	29	2468.0MHz
6	2419.0MHz	14	2435.0MHz	22	2454.0MHz	30	2470.0MHz
7	2421.0MHz	15	2437.0MHz	23	2456.0MHz	31	2472.0MHz
8	2423.0MHz	16	2439.0MHz	24	2458.0MHz	32	2474.0MHz

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel	2409MHz
The middle channel	2444MHz
The Highest channel	2474MHz

5.3 Test mode

Transmitting mode	Keep the EUT in transmitting mode.
<i>Remark: During the test, the new battery was used.</i>	

5.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• **CNAS —Registration No.: CNAS L5775**

CNAS has accredited Global United Technology Services Co., Ltd. To ISO/IEC 17025 General Requirements for the competence of testing and calibration laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

• **FCC —Registration No.: 600491**

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 600491, June 28, 2013.

• **Industry Canada (IC) —Registration No.: 9079A-2**

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A-2, June 26, 2013.

5.5 Test Location

All other tests were performed at:
Global United Technology Services Co., Ltd. Address: 2nd Floor, Block No.2, Laodong Industrial Zone, Xixiang Road Baoan District, Shenzhen, China Tel: 0755-27798480 Fax: 0755-27798960

5.6 Other Information Requested by the Customer

None.

5.7 Description of Support Units


None.

5.8 Test Instruments list


Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	Mar. 29 2013	Mar. 28 2015
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	Spectrum Analyzer	Agilent	E4440A	GTS536	Nov. 19, 2014	Nov.18, 2015
4	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	Jul. 05 2014	Jul. 04 2015
5	Loop Antenna	ZHINAN	ZN30900A	GTS534	Feb. 23 2014	Feb. 22 2015
6	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	GTS214	Feb. 23 2014	Feb. 22 2015
7	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	9120D-829	GTS208	Jul. 05 2014	Jul. 04 2015
8	Horn Antenna	ETS-LINDGREN	3160	GTS217	Mar. 29 2013	Mar. 28 2015
9	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
10	Coaxial Cable	GTS	N/A	GTS213	Mar. 29 2013	Mar. 28 2015
11	Coaxial Cable	GTS	N/A	GTS211	Mar. 29 2013	Mar. 28 2015
12	Coaxial cable	GTS	N/A	GTS210	Mar. 29 2013	Mar. 28 2015
13	Coaxial Cable	GTS	N/A	GTS212	Mar. 29 2013	Mar. 28 2015
14	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	Jul. 05 2014	Jul. 04 2015
15	Amplifier(2GHz-20GHz)	HP	8349B	GTS206	Jul. 05 2014	Jul. 04 2015
16	Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	Jul. 05 2014	Jul. 04 2015
17	Band filter	Amindeon	82346	GTS219	Mar. 29 2013	Mar. 28 2015

6 Test results and Measurement Data

6.1 Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(c) (1)(i) requirement: (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.	
E.U.T Antenna:	
<i>The antenna is integral Antenna, the best case gain of the antenna is 2dBi</i> 	

6.2 Conducted Peak Output Power


Test Requirement:	FCC Part15 C Section 15.247 (b)(1)
Test Method:	DA 00-705, ANSI C63.10:2009
Limit:	20.97dBm
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. Below the table is a Ground Reference Plane.
Test Instruments:	Refer to section 5.8 for details
Test mode:	Refer to section 5.3 for details
Test results:	Pass

Measurement Data


Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	14.94	20.97	Pass
Middle	14.42		
Highest	14.97		

Test plot as follows:


Test mode:	GFSK mode
------------	-----------



Lowest channel




Middle channel



Highest channel

6.3 20dB Emission Bandwidth

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)
Test Method:	DA 00-705, ANSI C63.10:2009
Limit:	N/A
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. Below the table is a Ground Reference Plane.
Test Instruments:	Refer to section 5.8 for details
Test mode:	Refer to section 5.3 for details
Test results:	Pass

Measurement Data

Test channel	20dB Emission Bandwidth (MHz)	Result
Lowest	2.715	Pass
Middle	2.764	
Highest	2.744	

Test plot as follows:



Lowest channel




Middle channel



Highest channel

6.4 Carrier Frequencies Separation

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)
Test Method:	DA 00-705, ANSI C63.10:2009
Receiver setup:	RBW=100KHz, VBW=300KHz, detector=Peak
Limit:	0.025MHz or 2/3 of the 20dB bandwidth (whichever is greater)
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T are placed on a Non-Conducted Table. The table is supported by a Ground Reference Plane.
Test Instruments:	Refer to section 5.8 for details
Test mode:	Refer to section 5.3 for details
Test results:	Pass


Measurement Data

Test channel	Carrier Frequencies Separation (MHz)	Limit (kHz)	Result
Lowest	2.0	1843	Pass
Middle	2.0	1843	Pass
Highest	2.0	1843	Pass


Note: According to section 5.3

Mode	20dB bandwidth (kHz) (worse case)	Limit (kHz) (Carrier Frequencies Separation)
GFSK	2764	1843


Test plot as follows:



Lowest channel




Middle channel




Highest channel

6.5 Hopping Channel Number


Test Requirement:	FCC Part15 C Section 15.247 (a)(1)(iii)
Test Method:	DA 00-705, ANSI C63.10:2009
Receiver setup:	RBW=100kHz, VBW=300kHz, Frequency range=2400MHz-2483.5MHz, Detector=Peak
Limit:	15 channels
Test setup:	
Test Instruments:	Refer to section 5.8 for details
Test mode:	Refer to section 5.3 for details
Test results:	Pass

Measurement Data:

Hopping channel numbers	Limit	Result
32	15	Pass



6.6 Dwell Time

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)(iii)
Test Method:	DA 00-705, ANSI C63.10:2009
Receiver setup:	RBW=1MHz, VBW=1MHz, Span=0Hz, Detector=Peak
Limit:	0.4 Second
Test setup:	
Test Instruments:	Refer to section 5.8 for details
Test mode:	Refer to section 5.3 for details
Test results:	Pass

Measurement Data

Frequency	Ton (ms)	Dwell time(ms)	Limit(ms)	Result
2.409GHz	2.017	77.453	400	Pass
2.444GHz	2.017	77.453	400	Pass
2.474GHz	2.025	77.760	400	Pass

The formula as below:


2409MHz: Dwell time = Ton * Ton times in 1s * 0.4s * channel numbers=2.017ms*3*0.4*32=77.453ms

2444MHz: Dwell time = Ton * Ton times in 1s * 0.4s * channel numbers=2.017ms*3*0.4*32=77.453ms


2474MHz: Dwell time = Ton * Ton times in 1s * 0.4s * channel numbers=2.025ms*3*0.4*32=77.760ms

Test plot as follows:

Frequency:	2409MHz
------------	---------




Ton




Ton times in 1s

Frequency:	2444MHz
------------	---------




Ton




Ton times in 1s

Frequency:	2474MHz
------------	---------




Ton



Ton times in 1s


6.7 Band Edge

6.7.1 Conducted Emission Method


Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	DA 00-705, ANSI C63.10:2009
Receiver setup:	RBW=100kHz, VBW=300kHz, Detector=Peak
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. The table is supported by a Ground Reference Plane.
Test Instruments:	Refer to section 5.8 for details
Test mode:	Refer to section 5.3 for details
Test results:	Pass

Test plot as follows:

Test channel:	Lowest channel
---------------	----------------




No-hopping mode




Hopping mode

Test channel:	Highest channel
---------------	-----------------




No-hopping mode



Hopping mode

6.7.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209 and 15.205				
Test Method:	ANSI C63.10: 2009				
Test Frequency Range:	All restriction band have been tested, and 2.3GHz to 2.5GHz band is the worse case				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		Peak	1MHz	10Hz	Average Value
Limit:	Frequency		Limit (dBuV/m @3m)		Remark
	Above 1GHz		54.00		Average Value
			74.00		Peak Value
Test setup:					
Test Procedure:	1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.				
Test Instruments:	Refer to section 5.8 for details				
Test mode:	Refer to section 5.3 for details				
Test results:	Pass				

Remark:

1. Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.

Test channel:	Lowest
---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	52.46	27.91	5.30	30.37	55.30	74.00	-18.70	Horizontal
2390.00	53.65	27.59	5.38	30.18	56.44	74.00	-17.56	Horizontal
2400.00	54.15	27.58	5.39	30.18	56.94	74.00	-17.06	Horizontal
2310.00	53.91	27.91	5.30	30.37	56.75	74.00	-17.25	Vertical
2390.00	55.27	27.59	5.38	30.18	58.06	74.00	-15.94	Vertical
2400.00	55.44	27.58	5.39	30.18	58.23	74.00	-15.77	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	32.63	27.91	5.30	30.37	35.47	54.00	-18.53	Horizontal
2390.00	32.42	27.59	5.38	30.18	35.21	54.00	-18.79	Horizontal
2400.00	33.70	27.58	5.39	30.18	36.49	54.00	-17.51	Horizontal
2310.00	34.08	27.91	5.30	30.37	36.92	54.00	-17.08	Vertical
2390.00	34.04	27.59	5.38	30.18	36.83	54.00	-17.17	Vertical
2400.00	34.99	27.58	5.39	30.18	37.78	54.00	-16.22	Vertical

Test channel:	Highest
---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	53.47	27.53	5.47	29.93	56.54	74.00	-17.46	Horizontal
2500.00	53.56	27.55	5.49	29.93	56.67	74.00	-17.33	Horizontal
2483.50	54.83	27.53	5.47	29.93	57.90	74.00	-16.10	Vertical
2500.00	54.98	27.55	5.49	29.93	58.09	74.00	-15.91	Vertical

Average value:


Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.49	34.55	27.53	5.47	29.93	37.62	54.00	-16.38	Horizontal
2500.00	31.86	27.55	5.49	29.93	34.97	54.00	-19.03	Horizontal
2483.49	35.91	27.53	5.47	29.93	38.98	54.00	-15.02	Vertical
2500.00	33.28	27.55	5.49	29.93	36.39	54.00	-17.61	Vertical

Remark:


1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

6.8 Spurious Emission

6.8.1 Conducted Emission Method


Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	ANSI C63.10:2009
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	 The diagram illustrates the test setup for conducted emission measurement. A Spectrum Analyzer is connected via a red cable to an E.U.T. (Equipment Under Test). Both are placed on a Non-Conducted Table, which is supported by a Ground Reference Plane.
Test Instruments:	Refer to section 5.8 for details
Test mode:	Refer to section 5.3 for details
Test results:	Pass

Test channel:




30MHz~10GHz

Lowest channel




10GHz~25GHz

Test channel:




30MHz~10GHz

Middle channel




10GHz~25GHz

Test channel:





30MHz~10GHz

Highest channel



10GHz~25GHz

6.8.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10: 2009				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average
Limit: (Field strength of the fundamental signal)	Frequency	Limit (dBuV/m @3m)		Remark	
	2400MHz-2483.5MHz	94.00		Average Value	
		114.00		Peak Value	
Test setup:	Below 1GHz				
					
Test setup:	Above 1GHz				
					
Test Procedure:	1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.				

	3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
Test Instruments:	Refer to section 5.8 for details
Test mode:	Refer to section 5.3 for details
Test results:	Pass

Remark:

1. Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.
2. The measured filed strength at frequencies below 30MHz are lower than the limit over 30dB. So the data isn't reported.

Measurement data:

■ 30MHz ~ 1GHz

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
55.22	35.04	15.00	0.82	31.95	18.91	40.00	-21.09	Vertical
107.89	34.52	14.44	1.26	31.80	18.42	43.50	-25.08	Vertical
180.02	35.86	11.68	1.74	32.08	17.20	43.50	-26.30	Vertical
242.53	35.28	14.08	2.08	32.16	19.28	46.00	-26.72	Vertical
492.47	34.80	18.39	3.27	31.59	24.87	46.00	-21.13	Vertical
848.06	33.64	22.55	4.65	31.25	29.59	46.00	-16.41	Vertical
45.22	34.81	15.54	0.72	32.00	19.07	40.00	-20.93	Horizontal
101.64	36.07	15.02	1.21	31.77	20.53	43.50	-22.97	Horizontal
180.65	34.17	11.76	1.74	32.08	15.59	43.50	-27.91	Horizontal
282.99	36.83	14.73	2.28	32.17	21.67	46.00	-24.33	Horizontal
574.63	34.30	20.03	3.63	31.17	26.79	46.00	-19.21	Horizontal
787.85	34.30	21.92	4.41	31.31	29.32	46.00	-16.68	Horizontal

■ Above 1GHz

Test channel:	Lowest
---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4818.00	44.58	31.79	8.61	32.10	52.88	74.00	-21.12	Vertical
7227.00	45.00	36.19	11.66	31.99	60.86	74.00	-13.14	Vertical
9636.00	39.07	38.01	14.16	31.58	59.66	74.00	-14.34	Vertical
12045.00	35.28	39.05	15.05	35.57	53.81	74.00	-20.19	Vertical
4818.00	43.02	31.79	8.61	32.10	51.32	74.00	-22.68	Horizontal
7227.00	43.53	36.19	11.66	31.99	59.39	74.00	-14.61	Horizontal
9636.00	37.39	38.01	14.16	31.58	57.98	74.00	-16.02	Horizontal
12045.00	33.56	39.05	15.05	35.57	52.09	74.00	-21.91	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4818.00	30.47	31.79	8.61	32.10	38.77	54.00	-15.23	Vertical
7227.00	30.55	36.19	11.66	31.99	46.41	54.00	-7.59	Vertical
9636.00	24.45	38.01	14.16	31.58	45.04	54.00	-8.96	Vertical
12045.00	20.54	39.05	15.05	35.57	39.07	54.00	-14.93	Vertical
4818.00	28.91	31.79	8.61	32.10	37.21	54.00	-16.79	Horizontal
7227.00	29.08	36.19	11.66	31.99	44.94	54.00	-9.06	Horizontal
9636.00	22.77	38.01	14.16	31.58	43.36	54.00	-10.64	Horizontal
12045.00	18.82	39.05	15.05	35.57	37.35	54.00	-16.65	Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies are very lower than the limit and not show in test report.

Test channel:	Middle
---------------	--------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4882.00	44.92	31.85	8.67	32.12	53.32	74.00	-20.68	Vertical
7323.00	39.49	36.37	11.72	31.89	55.69	74.00	-18.31	Vertical
9764.00	36.49	38.35	14.25	31.62	57.47	74.00	-16.53	Vertical
12205.00	36.61	38.92	15.16	35.65	55.04	74.00	-18.96	Vertical
4882.00	43.36	31.85	8.67	32.12	51.76	74.00	-22.24	Horizontal
7323.00	38.02	36.37	11.72	31.89	54.22	74.00	-19.78	Horizontal
9764.00	34.81	38.35	14.25	31.62	55.79	74.00	-18.21	Horizontal
12205.00	34.89	38.92	15.16	35.65	53.32	74.00	-20.68	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4882.00	30.64	31.85	8.67	32.12	39.04	54.00	-14.96	Vertical
7323.00	25.75	36.37	11.72	31.89	41.95	54.00	-12.05	Vertical
9764.00	22.40	38.35	14.25	31.62	43.38	54.00	-10.62	Vertical
12205.00	21.77	38.92	15.16	35.65	40.20	54.00	-13.80	Vertical
4882.00	29.08	31.85	8.67	32.12	37.48	54.00	-16.52	Horizontal
7323.00	24.28	36.37	11.72	31.89	40.48	54.00	-13.52	Horizontal
9764.00	20.72	38.35	14.25	31.62	41.70	54.00	-12.30	Horizontal
12205.00	20.05	38.92	15.16	35.65	38.48	54.00	-15.52	Horizontal

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies are very lower than the limit and not show in test report.

Test channel:	Highest
---------------	---------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4948.00	44.24	31.91	8.71	32.16	52.70	74.00	-21.30	Vertical
7422.00	40.64	36.56	11.77	31.80	57.17	74.00	-16.83	Vertical
9896.00	35.47	38.81	14.35	31.82	56.81	74.00	-17.19	Vertical
12050.00	33.81	39.05	15.05	35.57	52.34	74.00	-21.66	Vertical
4948.00	42.68	31.91	8.71	32.16	51.14	74.00	-22.86	Horizontal
7422.00	39.17	36.56	11.77	31.80	55.70	74.00	-18.30	Horizontal
9896.00	33.79	38.81	14.35	31.82	55.13	74.00	-18.87	Horizontal
12050.00	32.09	39.05	15.05	35.57	50.62	74.00	-23.38	Horizontal

Average value:



Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4948.00	30.47	31.91	8.71	32.16	38.93	54.00	-15.07	Vertical
7422.00	25.65	36.56	11.77	31.80	42.18	54.00	-11.82	Vertical
9896.00	20.46	38.81	14.35	31.82	41.80	54.00	-12.20	Vertical
12050.00	18.64	39.05	15.05	35.57	37.17	54.00	-16.83	Vertical
4948.00	28.91	31.91	8.71	32.16	37.37	54.00	-16.63	Horizontal
7422.00	24.18	36.56	11.77	31.80	40.71	54.00	-13.29	Horizontal
9896.00	18.78	38.81	14.35	31.82	40.12	54.00	-13.88	Horizontal
12050.00	16.92	39.05	15.05	35.57	35.45	54.00	-18.55	Horizontal


Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies are very lower than the limit and not show in test report.

7 Test Setup Photo

Radiated Emission









8 EUT Constructional Details


















-----End-----