


# FCC Test Report

**Equipment** : abgn WiFi Module  
**Brand Name** : Senao  
**Model No.** : EUB600-DM  
**FCC ID** : U2M-EUB600DM  
**Standard** : 47 CFR FCC Part 15.247  
**Operating Band** : 5725 MHz – 5850 MHz  
**FCC Classification** : DTS  
**Applicant** : Senao Networks, Inc.  
3F, No. 529, Chung Cheng Rd.,  
Hsintien, Taipei, Taiwan

The product sample received on Aug. 30, 2013 and completely tested on Nov. 01, 2013. We, SPORTON, would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.10-2009 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by:

  
James Fan / Assistant Manager





## Table of Contents

<b>1</b>	<b>GENERAL DESCRIPTION .....</b>	<b>5</b>
1.1	Information.....	5
1.2	Support Equipment.....	6
1.3	Testing Applied Standards .....	7
1.4	Testing Location Information .....	7
1.5	Measurement Uncertainty .....	8
<b>2</b>	<b>TEST CONFIGURATION OF EUT.....</b>	<b>9</b>
2.1	The Worst Case Modulation Configuration .....	9
2.2	The Worst Case Power Setting Parameter .....	9
2.3	The Worst Case Measurement Configuration.....	10
2.4	Test Setup Diagram .....	11
<b>3</b>	<b>TRANSMITTER TEST RESULT .....</b>	<b>12</b>
3.1	AC Power-line Conducted Emissions .....	12
3.2	6dB Bandwidth .....	15
3.3	RF Output Power.....	17
3.4	Power Spectral Density .....	21
3.5	Emissions in non-restricted frequency bands .....	24
3.6	Transmitter Unwanted Emissions.....	31
<b>4</b>	<b>TEST EQUIPMENT AND CALIBRATION DATA .....</b>	<b>54</b>
	<b>APPENDIX A. TEST PHOTOS .....</b>	<b>A1-A6</b>



### Summary of Test Result

Conformance Test Specifications					
Report Clause	Ref. Std. Clause	Description	Measured	Limit	Result
1.1.2	15.203	Antenna Requirement	Antenna connector mechanism complied	FCC 15.203	Complied
3.1	15.207	AC Power-line Conducted Emissions	[dBuV]: 0.267MHz 39.83 (Margin 11.37dB) - AV 46.62 (Margin 14.58dB) - QP	FCC 15.207	Complied
3.2	15.247(a)	6dB Bandwidth	6dB Bandwidth [MHz] 20M:16.41 / 40M: 36.41	≥500kHz	Complied
3.3	15.247(b)	RF Output Power (Maximum Peak Conducted Output Power)	Power [dBm]: 26.49	Power [dBm]:30	Complied
3.4	15.247(e)	Power Spectral Density	PSD [dBm/3kHz]: -5.76	PSD [dBm/3kHz]:8	Complied
3.5	15.247(d)	Emissions in non-restricted frequency bands	Out-of -band emissions are 20dB below the highest power	Non-Restricted Bands: > 20 dBc Restricted Bands: FCC 15.209	Complied
3.6	15.247(d)	Transmitter Unwanted Emissions	Restricted Bands [dBuV/m at 3m]: 11650MHz 52.67 (Margin 1.33dB) - AV	Non-Restricted Bands: > 20 dBc Restricted Bands: FCC 15.209	Complied



# 1 General Description

## 1.1 Information

### 1.1.1 RF General Information

RF General Information						
Frequency Range (MHz)	IEEE Std. 802.11	Ch. Freq. (MHz)	Channel Number	Transmit Chains (N <sub>TX</sub> )	RF Output Power (dBm)	Co-location
5725-5850	a	5745-5825	149-165 [5]	1	24.45	N/A
5725-5850	n (HT20)	5745-5825	149-165 [5]	2	26.49	N/A
5725-5850	n (HT40)	5755-5795	151-159 [2]	2	26.35	N/A

Note 1: RF output power specifies that Maximum Peak Conducted Output Power.  
 Note 2: 802.11a/n uses a combination of OFDM-BPSK, QPSK, 16QAM, 64QAM modulation.

### 1.1.2 Antenna Information

Antenna Category	
<input type="checkbox"/>	Equipment placed on the market without antennas
<input type="checkbox"/>	Integral antenna (antenna permanently attached)
<input type="checkbox"/>	Temporary RF connector provided
<input type="checkbox"/>	No temporary RF connector provided Transmit chains bypass antenna and soldered temporary RF connector provided for connected measurement. In case of conducted measurements the transmitter shall be connected to the measuring equipment via a suitable attenuator and correct for all losses in the RF path.
<input checked="" type="checkbox"/>	External antenna (dedicated antennas)
<input type="checkbox"/>	Single power level with corresponding antenna(s).
<input type="checkbox"/>	Multiple power level and corresponding antenna(s).
<input checked="" type="checkbox"/>	RF connector provided
<input checked="" type="checkbox"/>	Unique antenna connector. (e.g., MMCX, U.FL, IPX, and RP-SMA, RP-N type...)
<input type="checkbox"/>	Standard antenna connector. (e.g., SMA, N, BNC, and TNC type...)

Antenna General Information				
No.	Ant. Cat.	Ant. Type	Gain (dBi)	Connector
1	External	PCB Dipole	3	UFL

Note: The antenna has three combination of different cable length. Combination a. & c. were chosen for final test.  
 a. 19cm black cable / 19.5cm white cable  
 b. 30cm black cable / 20cm white cable  
 c. 30cm black cable / 35cm white cable

1.1.3 Type of EUT

Identify EUT	
EUT Serial Number	N/A
Presentation of Equipment	<input type="checkbox"/> Production ; <input checked="" type="checkbox"/> Pre-Production ; <input type="checkbox"/> Prototype
Type of EUT	
<input type="checkbox"/>	Stand-alone
<input type="checkbox"/>	Combined
<input checked="" type="checkbox"/>	Plug-in radio
<input type="checkbox"/>	Other:

1.1.4 Test Signal Duty Cycle

Operated Mode for Worst Duty Cycle	
<input type="checkbox"/>	Operated normally mode for worst duty cycle
<input checked="" type="checkbox"/>	Operated test mode for worst duty cycle
Test Signal Duty Cycle (x)	Power Duty Factor [dB] – (10 log 1/x)
<input checked="" type="checkbox"/> 100% - IEEE 802.11a	0
<input checked="" type="checkbox"/> 100% - IEEE 802.11n (HT20)	0
<input checked="" type="checkbox"/> 100% - IEEE 802.11n (HT40)	0

1.1.5 EUT Operational Condition

Supply Voltage	<input type="checkbox"/> AC mains	<input checked="" type="checkbox"/> DC (5 Vdc)	
Type of DC Source	<input type="checkbox"/> Internal DC supply	<input type="checkbox"/> External DC adapter	<input checked="" type="checkbox"/> From Host

1.2 Support Equipment

Support Equipment				
No.	Equipment	Brand Name	Model Name	Remarks
1	Notebook	DELL	E6430	DoC

### 1.3 Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ◆ 47 CFR FCC Part 15
- ◆ ANSI C63.10-2009
- ◆ FCC KDB 558074 v03r01
- ◆ FCC KDB 662911 v02r01
- ◆ FCC KDB 412172 v01

### 1.4 Testing Location Information

Testing Location				
<input checked="" type="checkbox"/>	Sporton Lab	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.		
		TEL : 886-3-327-3456	FAX : 886-3-318-0055	
<input checked="" type="checkbox"/>	ICC Lab	ADD : No.3-1, Lane 6, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsein 333, Taiwan (R.O.C.)		
		TEL : 886-3-271-8666	FAX : 886-3-318-0155	
Test Condition	Test Site No.	Test Engineer	Test Environment	Test Date
RF Conducted	TH01-HY	Mark Liao	23°C / 63%	Oct. 25, 2013
*AC Conduction	CO01-WS	Skys Huang	21°C / 63%	Nov. 01, 2013
*Radiated Emission	03CH01-WS	Skys Huang	24°C / 64%	Oct. 07 ~ 08, 2013
Test site registered number [657002] with FCC.				
Test site registered number [10807A-1] with IC.				

Note: \* Sporton Lab subcontracts this test item to ICC lab (TAF: 2732).

ICC lab is a TAF accreditation test firm and also is an approved provider of Sporton lab.

## 1.5 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

Measurement Uncertainty			
Test Item		Uncertainty	Limit
AC power-line conducted emissions		±2.26 dB	N/A
Emission bandwidth, 6dB bandwidth		±1.42 %	N/A
RF output power, conducted		±0.63 dB	N/A
Power density, conducted		±0.81 dB	N/A
All emissions, radiated	30 – 1000 MHz	±3.9 dB	N/A
	Above 1GHz	±4.2 dB	N/A
Temperature		±0.8 °C	N/A
Humidity		±3 %	N/A
DC and low frequency voltages		±3 %	N/A
Time		±1.42 %	N/A
Duty Cycle		±1.42 %	N/A



## 2 Test Configuration of EUT

### 2.1 The Worst Case Modulation Configuration

Worst Modulation Used for Conformance Testing			
Modulation Mode	Transmit Chains (N <sub>TX</sub> )	Data Rate / MCS	Worst Data Rate / MCS
11a	1	6-54 Mbps	6 Mbps
HT20	2	MCS 0-15	MCS 0
HT40	2	MCS 0-15	MCS 0




### 2.2 The Worst Case Power Setting Parameter

The Worst Case Power Setting Parameter (5725-5850MHz band)							
Test Software Version	MT5x7x QA, Version 1.0.4.9						
Modulation Mode	N <sub>TX</sub>	Test Frequency (MHz)					
		NCB: 20MHz			NCB: 40MHz		
		5745	5785	5825	5755	5795	-
11a	1	2B	2B	2B	-	-	-
HT20	2	25/24	27/26	27/26	-	-	-
HT40	2	-	-	-	27/26	28/27	-


### 2.3 The Worst Case Measurement Configuration

The Worst Case Mode for Following Conformance Tests	
<b>Tests Item</b>	AC power-line conducted emissions
<b>Condition</b>	AC power-line conducted measurement for line and neutral Test Voltage: 120Vac / 60Hz
<b>Operating Mode</b>	Operating Mode Description
1	Radio link (WLAN)

The Worst Case Mode for Following Conformance Tests	
<b>Tests Item</b>	RF Output Power, Power Spectral Density, 6 dB Bandwidth
<b>Test Condition</b>	Conducted measurement at transmit chains
<b>Modulation Mode</b>	11a, HT20, HT40


The Worst Case Mode for Following Conformance Tests			
<b>Tests Item</b>	Transmitter Radiated Unwanted Emissions Transmitter Radiated Bandedge Emissions		
<b>Test Condition</b>	Radiated measurement If EUT consist of multiple antenna assembly (multiple antenna are used in EUT regardless of spatial multiplexing MIMO configuration), the radiated test should be performed with highest antenna gain of each antenna type.		
<b>User Position</b>	<input checked="" type="checkbox"/> EUT will be placed in fixed position. The applicant declared that the antenna plane is Y-axis only and the antenna separation distance is 20cm.		
	<input type="checkbox"/> EUT will be placed in mobile position and operating multiple positions. EUT shall be performed two orthogonal planes. The worst planes is X.		
	<input type="checkbox"/> EUT will be operating multiple positions. EUT shall be performed two or three orthogonal planes. The worst plane is Z.		
<b>Operating Mode &lt;1GHz</b>	<input checked="" type="checkbox"/> 1. Radio link (WLAN) with antenna cable length combination a.		
	<input checked="" type="checkbox"/> 2. Radio link (WLAN) with antenna cable length combination c.		
<b>Operating Mode &gt;1GHz</b>	<input checked="" type="checkbox"/> 1. Radio link (WLAN) with antenna cable length combination a.		
<b>Modulation Mode</b>	11a, HT20, HT40		
<b>Orthogonal Planes of EUT</b>	<b>X Plane</b>	<b>Y Plane</b>	<b>Z Plane</b>
			

## 2.4 Test Setup Diagram






3.1.5 Test Result of AC Power-line Conducted Emissions

AC Power-line Conducted Emissions Result																																																																																																																								
Operating Mode	1	Power Phase	Neutral																																																																																																																					
Operating Function	Radio link (WLAN)																																																																																																																							
<div style="display: flex; justify-content: space-between;"> <div>  <p>The graph shows the AC power-line conducted emissions. The y-axis is Level (dBuV) from 0 to 80, and the x-axis is Frequency (MHz) on a logarithmic scale from 0.150.2 to 30. Two red limit lines are shown: CISPR/CNS/VCCI-B (upper) and CISPR/CNS/VCCI-B AV (lower). A blue test signal is plotted, showing several peaks. A peak at 0.267 MHz is highlighted with a box in the table below.</p> </div> <div style="text-align: right;">Date: 2013-11-01</div> </div>																																																																																																																								
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th></th> <th>Freq MHz</th> <th>Level dBuV</th> <th>Limit Line dBuV</th> <th>Over Limit dB</th> <th>Read Level dBuV</th> <th>LISN factor dB</th> <th>cable loss dB</th> <th>Remark</th> </tr> </thead> <tbody> <tr><td>1</td><td>0.183</td><td>38.67</td><td>54.33</td><td>-15.66</td><td>38.50</td><td>0.02</td><td>0.15</td><td>Average</td></tr> <tr><td>2</td><td>0.183</td><td>50.64</td><td>64.33</td><td>-13.69</td><td>50.47</td><td>0.02</td><td>0.15</td><td>QP</td></tr> <tr><td>3</td><td>0.246</td><td>31.88</td><td>51.91</td><td>-20.03</td><td>31.72</td><td>0.02</td><td>0.14</td><td>Average</td></tr> <tr><td>4</td><td>0.246</td><td>46.77</td><td>61.91</td><td>-15.14</td><td>46.61</td><td>0.02</td><td>0.14</td><td>QP</td></tr> <tr style="border: 2px solid black;"><td>5</td><td>0.267</td><td>39.83</td><td>51.20</td><td>-11.37</td><td>39.68</td><td>0.02</td><td>0.13</td><td>Average</td></tr> <tr style="border: 2px solid black;"><td>6</td><td>0.267</td><td>46.62</td><td>61.20</td><td>-14.58</td><td>46.47</td><td>0.02</td><td>0.13</td><td>QP</td></tr> <tr><td>7</td><td>1.928</td><td>26.76</td><td>46.00</td><td>-19.24</td><td>26.58</td><td>0.03</td><td>0.15</td><td>Average</td></tr> <tr><td>8</td><td>1.928</td><td>37.37</td><td>56.00</td><td>-18.63</td><td>37.19</td><td>0.03</td><td>0.15</td><td>QP</td></tr> <tr><td>9</td><td>14.594</td><td>29.73</td><td>50.00</td><td>-20.27</td><td>29.49</td><td>0.11</td><td>0.13</td><td>Average</td></tr> <tr><td>10</td><td>14.594</td><td>33.71</td><td>60.00</td><td>-26.29</td><td>33.47</td><td>0.11</td><td>0.13</td><td>QP</td></tr> <tr><td>11</td><td>21.946</td><td>31.26</td><td>50.00</td><td>-18.74</td><td>30.81</td><td>0.14</td><td>0.31</td><td>Average</td></tr> <tr><td>12</td><td>21.946</td><td>33.29</td><td>60.00</td><td>-26.71</td><td>32.84</td><td>0.14</td><td>0.31</td><td>QP</td></tr> </tbody> </table>					Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	LISN factor dB	cable loss dB	Remark	1	0.183	38.67	54.33	-15.66	38.50	0.02	0.15	Average	2	0.183	50.64	64.33	-13.69	50.47	0.02	0.15	QP	3	0.246	31.88	51.91	-20.03	31.72	0.02	0.14	Average	4	0.246	46.77	61.91	-15.14	46.61	0.02	0.14	QP	5	0.267	39.83	51.20	-11.37	39.68	0.02	0.13	Average	6	0.267	46.62	61.20	-14.58	46.47	0.02	0.13	QP	7	1.928	26.76	46.00	-19.24	26.58	0.03	0.15	Average	8	1.928	37.37	56.00	-18.63	37.19	0.03	0.15	QP	9	14.594	29.73	50.00	-20.27	29.49	0.11	0.13	Average	10	14.594	33.71	60.00	-26.29	33.47	0.11	0.13	QP	11	21.946	31.26	50.00	-18.74	30.81	0.14	0.31	Average	12	21.946	33.29	60.00	-26.71	32.84	0.14	0.31	QP
	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	LISN factor dB	cable loss dB	Remark																																																																																																																
1	0.183	38.67	54.33	-15.66	38.50	0.02	0.15	Average																																																																																																																
2	0.183	50.64	64.33	-13.69	50.47	0.02	0.15	QP																																																																																																																
3	0.246	31.88	51.91	-20.03	31.72	0.02	0.14	Average																																																																																																																
4	0.246	46.77	61.91	-15.14	46.61	0.02	0.14	QP																																																																																																																
5	0.267	39.83	51.20	-11.37	39.68	0.02	0.13	Average																																																																																																																
6	0.267	46.62	61.20	-14.58	46.47	0.02	0.13	QP																																																																																																																
7	1.928	26.76	46.00	-19.24	26.58	0.03	0.15	Average																																																																																																																
8	1.928	37.37	56.00	-18.63	37.19	0.03	0.15	QP																																																																																																																
9	14.594	29.73	50.00	-20.27	29.49	0.11	0.13	Average																																																																																																																
10	14.594	33.71	60.00	-26.29	33.47	0.11	0.13	QP																																																																																																																
11	21.946	31.26	50.00	-18.74	30.81	0.14	0.31	Average																																																																																																																
12	21.946	33.29	60.00	-26.71	32.84	0.14	0.31	QP																																																																																																																
<p>Note 1: "&gt;20dB" means emission levels that exceed the level of 20 dB below the applicable limit.            Note 2: "N/F" means Nothing Found emissions (No emissions were detected.)</p>																																																																																																																								



AC Power-line Conducted Emissions Result

Operating Mode	1	Power Phase	Line
Operating Function	Radio link (WLAN)		



	Freq	Level	Limit	Over	Read	LISN	cable	Remark
	MHz	dBuV	Line	Limit	Level	factor	loss	
			dBuV	dB	dBuV	dB	dB	
1	0.155	40.80	55.74	-14.94	40.70	0.03	0.07	Average
2	0.155	48.19	65.74	-17.55	48.09	0.03	0.07	QP
3	0.183	38.33	54.33	-16.00	38.15	0.03	0.15	Average
4	0.183	50.45	64.33	-13.88	50.27	0.03	0.15	QP
5	0.258	30.07	51.51	-21.44	29.91	0.03	0.13	Average
6	0.258	45.84	61.51	-15.67	45.68	0.03	0.13	QP
7	2.500	26.15	46.00	-19.85	25.91	0.05	0.19	Average
8	2.500	33.96	56.00	-22.04	33.72	0.05	0.19	QP
9	8.729	27.75	50.00	-22.25	27.53	0.09	0.13	Average
10	8.729	31.17	60.00	-28.83	30.95	0.09	0.13	QP
11	15.307	29.18	50.00	-20.82	28.93	0.12	0.13	Average
12	15.307	36.82	60.00	-23.18	36.57	0.12	0.13	QP

Note 1: ">20dB" means emission levels that exceed the level of 20 dB below the applicable limit.  
 Note 2: "N/F" means Nothing Found emissions (No emissions were detected.)

### 3.2 6dB Bandwidth

#### 3.2.1 6dB Bandwidth Limit

6dB Bandwidth Limit
<b>Systems using digital modulation techniques:</b>
<input checked="" type="checkbox"/> 6 dB bandwidth $\geq$ 500 kHz.


#### 3.2.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

#### 3.2.3 Test Procedures

Test Method
<input checked="" type="checkbox"/> For the emission bandwidth shall be measured using one of the options below:
<input checked="" type="checkbox"/> Refer as FCC KDB 558074 v03r01, clause 8.1 Option 1 for 6 dB bandwidth measurement.
<input type="checkbox"/> Refer as FCC KDB 558074 v03r01, clause 8.2 Option 2 for 6 dB bandwidth measurement.
<input type="checkbox"/> Refer as ANSI C63.10, clause 6.9.1 for occupied bandwidth testing.
<input checked="" type="checkbox"/> For conducted measurement.
<input checked="" type="checkbox"/> The EUT supports single transmit chain and measurements performed on this transmit chain.
<input type="checkbox"/> The EUT supports diversity transmitting and the results on transmit chain port 1 is the worst case.
<input checked="" type="checkbox"/> The EUT supports multiple transmit chains using options given below:
<input type="checkbox"/> Option 1: Multiple transmit chains measurements need to be performed on one of the active transmit chains (antenna outputs). All measurement had be performed on transmit chains 1.
<input checked="" type="checkbox"/> Option 2: Multiple transmit chains measurements need to be performed on each transmit chains individually (antenna outputs). All measurement had be performed on all transmit chains.

#### 3.2.4 Test Setup






3.2.5 Test Result of Emission Bandwidth

Emission Bandwidth Result										
Condition			Emission Bandwidth (MHz)							
Modulation Mode	N <sub>TX</sub>	Freq. (MHz)	99% Bandwidth				6dB Bandwidth			
			Chain-Port 1	Chain-Port 2	Chain-Port 3	Chain-Port 4	Chain-Port 1	Chain-Port 2	Chain-Port 3	Chain-Port 4
11a	1	5745	27.26	---	---	---	16.41	---	---	---
11a	1	5785	26.05	---	---	---	16.41	---	---	---
11a	1	5825	25.64	---	---	---	16.41	---	---	---
HT20	2	5745	17.95	19.62	---	---	17.57	17.62	---	---
HT20	2	5785	19.80	18.58	---	---	17.57	17.57	---	---
HT20	2	5825	18.06	18.87	---	---	17.57	17.57	---	---
HT40	2	5755	38.32	39.94	---	---	36.41	36.41	---	---
HT40	2	5795	39.71	38.55	---	---	36.41	36.41	---	---
Limit			N/A				≥500 kHz			
Result			Complied							

Note 1: N<sub>TX</sub> = Number of Transmit Chains





### 3.3 RF Output Power

#### 3.3.1 RF Output Power Limit

RF Output Power Limit	
<b>Maximum Peak Conducted Output Power or Maximum Conducted Output Power Limit</b>	
<input checked="" type="checkbox"/> 5725-5850 MHz Band:	
<input checked="" type="checkbox"/>	If $G_{TX} \leq 6$ dBi, then $P_{Out} \leq 30$ dBm (1 W)
<input checked="" type="checkbox"/>	Point-to-multipoint systems (P2M): If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)$ dBm
<input type="checkbox"/>	Point-to-point systems (P2P): If $G_{TX} > 6$ dBi, then $P_{Out} = 30$ dBm
<b>e.i.r.p. Power Limit:</b>	
<input checked="" type="checkbox"/> 5725-5850 MHz Band	
<input checked="" type="checkbox"/>	Point-to-multipoint systems (P2M): $P_{eirp} \leq 36$ dBm (4 W)
<input type="checkbox"/>	Point-to-point systems (P2P): N/A
$P_{Out}$ = maximum peak conducted output power or maximum conducted output power in dBm, $G_{TX}$ = the maximum transmitting antenna directional gain in dBi. $P_{eirp}$ = e.i.r.p. Power in dBm.	

RF Output Power Limit - IC	
<b>Maximum Peak Conducted Output Power or Maximum Conducted Output Power Limit and e.i.r.p.</b>	
<input checked="" type="checkbox"/> 5725-5850 MHz Band:	
<input checked="" type="checkbox"/>	Point-to-multipoint systems (P2M): $P_{Out} \leq 30$ dBm (1 W); $P_{eirp} \leq 36$ dBm (4 W)
<input type="checkbox"/>	Point-to-point systems (P2P): If $P_{eirp} > 36$ dBm, $G_{TX} \leq P_{Out}$
$P_{Out}$ = maximum peak conducted output power or maximum conducted output power in dBm, $G_{TX}$ = the maximum transmitting antenna directional gain in dBi. $P_{eirp}$ = e.i.r.p. Power in dBm.	


#### 3.3.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.3.3 Test Procedures

Test Method	
<input checked="" type="checkbox"/>	Maximum Peak Conducted Output Power
<input type="checkbox"/>	Refer as FCC KDB 558074 v03r01, clause 9.1.1 Option 1 (RBW ≥ EBW method).
<input type="checkbox"/>	Refer as FCC KDB 558074 v03r01, clause 9.1.2 Option 2 (integrated band power method).
<input checked="" type="checkbox"/>	Refer as FCC KDB 558074 v03r01, clause 9.1.3 Option 2 (peak power meter for VBW ≥ DTS BW)
<input checked="" type="checkbox"/>	Maximum Conducted (Average) Output Power ( For reference only)
	[duty cycle ≥ 98% or external video / power trigger]
<input type="checkbox"/>	Refer as FCC KDB 558074 v03r01, clause 9.2.2.2 Method AVGSA-1 (spectral trace averaging).
<input type="checkbox"/>	Refer as FCC KDB 558074 v03r01, clause 9.2.2.3 Method AVGSA-1 Alt. (slow sweep speed)
<input type="checkbox"/>	Refer as FCC KDB 558074 v03r01, clause 9.2.2.4 Method AVGSA-2 (spectral trace averaging).
<input type="checkbox"/>	Refer as FCC KDB 558074 v03r01, clause 9.2.2.5 Method AVGSA-2 Alt. (slow sweep speed)
	RF power meter and average over on/off periods with duty factor or gated trigger
<input checked="" type="checkbox"/>	Refer as FCC KDB 558074 v03r01, clause 9.2.3 Method AVGPM (using an RF average power meter).
<input checked="" type="checkbox"/>	For conducted measurement.
<input type="checkbox"/>	The EUT supports single transmit chain and measurements performed on this transmit chain.
<input type="checkbox"/>	The EUT supports diversity transmitting and the results on transmit chain port 1 is the worst case.
<input checked="" type="checkbox"/>	The EUT supports multiple transmit chains using options given below: Refer as FCC KDB 662911, In-band power measurements. Using the measure-and-sum approach, measured all transmit ports individually. Sum the power (in linear power units e.g., mW) of all ports for each individual sample and save them.
<input checked="" type="checkbox"/>	If multiple transmit chains, EIRP calculation could be following as methods: $P_{total} = P_1 + P_2 + \dots + P_n$ (calculated in linear unit [mW] and transfer to log unit [dBm]) $EIRP_{total} = P_{total} + DG$

3.3.4 Test Setup





3.3.5 Directional Gain for Power Measurement

Directional Gain (DG) Result					
Transmit Chains No.		1	2	-	-
Maximum G <sub>ANT</sub> (dBi)		3	3	-	-
Modulation Mode	DG (dBi)	N <sub>TX</sub>	N <sub>SS</sub>	STBC	Array Gain (dB)
11a	3	1	1	-	-
HT20	6	2	1	-	3
HT40	6	2	1	-	3

Note: Directional gain = 3 + 10\*log(2/1) = 6 dBi

3.3.6 Test Result of Maximum Conducted Output Power

Maximum Conducted Output Power											
Condition			RF Output Power (dBm)								
Modulation Mode	N <sub>TX</sub>	Freq. (MHz)	Chain Port 1	Chain Port 2	Chain Port 3	Chain Port 4	Sum Chain	Power Limit	DG (dBi)	EIRP Power	EIRP Limit
11a	1	5745	24.45	---	---	---	24.45	30.00	3.00	27.45	36.00
11a	1	5785	24.31	---	---	---	24.31	30.00	3.00	27.31	36.00
11a	1	5825	23.98	---	---	---	23.98	30.00	3.00	26.98	36.00
HT20	2	5745	23.26	23.53	---	---	26.41	30.00	6.00	32.41	36.00
HT20	2	5785	23.35	23.61	---	---	26.49	30.00	6.00	32.49	36.00
HT20	2	5825	23.08	23.14	---	---	26.12	30.00	6.00	32.12	36.00
HT40	2	5755	23.29	23.38	---	---	26.35	30.00	6.00	32.35	36.00
HT40	2	5795	23.41	23.15	---	---	26.29	30.00	6.00	32.29	36.00
<b>Result</b>			<b>Complied</b>								

3.3.7 Test Result of Maximum Conducted (Average) Output Power

Maximum Conducted (Average) Output Power											
Condition			RF Output Power (dBm)								
Modulation Mode	N <sub>TX</sub>	Freq. (MHz)	Chain Port 1	Chain Port 2	Chain Port 3	Chain Port 4	Sum Chain	Power Limit	DG (dBi)	EIRP Power	EIRP Limit
11a	1	5745	21.33	---	---	---	21.33	30.00	3.00	24.33	21.33
11a	1	5785	21.18	---	---	---	21.18	30.00	3.00	24.18	21.18
11a	1	5825	20.69	---	---	---	20.69	30.00	3.00	23.69	20.69
HT20	2	5745	18.14	18.45	---	---	21.31	30.00	3.00	24.31	21.31
HT20	2	5785	18.22	18.51	---	---	21.38	30.00	3.00	24.38	21.38
HT20	2	5825	17.82	17.96	---	---	20.90	30.00	3.00	23.90	20.90
HT40	2	5755	18.35	18.46	---	---	21.42	30.00	3.00	24.42	21.42
HT40	2	5795	18.58	18.21	---	---	21.41	30.00	3.00	24.41	21.41
<b>Result</b>			<b>Complied</b>								

Note: Average power is for reference only

### 3.4 Power Spectral Density

#### 3.4.1 Power Spectral Density Limit

Power Spectral Density Limit
<input checked="" type="checkbox"/> Power Spectral Density (PSD) $\leq$ 8 dBm/3kHz


#### 3.4.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

#### 3.4.3 Test Procedures

Test Method
<input checked="" type="checkbox"/> Peak power spectral density procedures that the same method as used to determine the conducted output power. If maximum peak conducted output power was measured to demonstrate compliance to the output power limit, then the peak PSD procedure below (Method PKPSD) shall be used. If maximum conducted output power was measured to demonstrate compliance to the output power limit, then one of the average PSD procedures shall be used, as applicable based on the following criteria (the peak PSD procedure is also an acceptable option).
<input checked="" type="checkbox"/> Refer as FCC KDB 558074 v03r01, clause 10.2 Method PKPSD (RBW=3kHz; detector=peak).. [duty cycle $\geq$ 98% or external video / power trigger]
<input type="checkbox"/> Refer as FCC KDB 558074 v03r01, clause 10.3 Method AVGPSD-1 (spectral trace averaging).
<input type="checkbox"/> Refer as FCC KDB 558074 v03r01, clause 10.4 Method AVGPSD-1 Alt. (slow sweep speed) duty cycle < 98% and average over on/off periods with duty factor
<input type="checkbox"/> Refer as FCC KDB 558074 v03r01, clause 10.5 Method AVGPSD-2 (spectral trace averaging).
<input type="checkbox"/> Refer as FCC KDB 558074 v03r01, clause 10.6 Method AVGPSD-2 Alt. (slow sweep speed)
<input checked="" type="checkbox"/> For conducted measurement.
<input checked="" type="checkbox"/> The EUT supports single transmit chain and measurements performed on this transmit chain.
<input type="checkbox"/> The EUT supports diversity transmitting and the results on transmit chain port 1 is the worst case.
<input checked="" type="checkbox"/> The EUT supports multiple transmit chains using options given below:
<input checked="" type="checkbox"/> Option 1: Measure and sum the spectra across the outputs. Refer as FCC KDB 662911, In-band power spectral density (PSD). Sample all transmit ports simultaneously using a spectrum analyzer for each transmit port. Where the trace bin-by-bin of each transmit port summing can be performed. (i.e., in the first spectral bin of output 1 is summed with that in the first spectral bin of output 2 and that from the first spectral bin of output 3, and so on up to the N <sub>TX</sub> output to obtain the value for the first frequency bin of the summed spectrum.). Add up the amplitude (power) values for the different transmit chains and use this as the new data trace.
<input type="checkbox"/> Option 2: Measure and add 10 log(N) dB, where N is the number of transmit chains. Refer as FCC KDB 662911, In-band power spectral density (PSD). Performed at each transmit chains and each transmit chains shall be compared with the limit have been reduced with 10 log(N). Or each transmit chains shall be add 10 log(N) to compared with the limit.


### 3.4.4 Test Setup



3.4.5 Test Result of Power Spectral Density

Power Spectral Density Result				
Condition			Power Spectral Density	
Modulation Mode	N <sub>TX</sub>	Freq. (MHz)	Sum Chain (dBm/3kHz)	Power Limit (dBm/3kHz)
11a	1	5745	-7.20	8
11a	1	5785	-7.12	8
11a	1	5825	-8.05	8
HT20	2	5745	-5.76	8
HT20	2	5785	-6.67	8
HT20	2	5825	-6.68	8
HT40	2	5755	-8.16	8
HT40	2	5795	-8.05	8
<b>Result</b>			<b>Complied</b>	

Note: Test result of HT20 / 40 is bin-by-bin summing measured value of each TX port.



### 3.5 Emissions in non-restricted frequency bands

#### 3.5.1 Emissions in non-restricted frequency bands limit

- The peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz.
- The peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD level in 100 kHz.

#### 3.5.2 Test Procedures


##### Reference Level Measurement

1. Set the RBW = 100 kHz, VBW = 300 kHz, Detector = peak.
2. Set Sweep time = auto couple, Trace mode = max hold.
3. Allow trace to fully stabilize.
4. Use the peak marker function to determine the maximum amplitude level.

##### Unwanted Emissions Level Measurement

1. Set RBW = 100 kHz, VBW = 300 kHz, Detector = peak.
2. Trace Mode = max hold, Sweep = auto couple.
3. Allow the trace to stabilize.
4. Use peak marker function to determine maximum amplitude of all unwanted emissions within any 100 kHz bandwidth.

#### 3.5.3 Test Setup



#### 3.5.4 Test Result of Emissions in non-restricted frequency bands


This test item is performed on each TX output individually without summing or adding  $10 \log(N_{ANT})$  since measurements are made relative to the in-band emissions on the individual outputs. Only worst test result of each operating mode is presented.






### 3.5.5 Unwanted Emissions into Non-Restricted Frequency Bands


802.11a









802.11n HT20








802.11n HT40








Tx 5795MHz / 30MHz~40GHz (down 30dBc)




---

---



---



---

### 3.6 Transmitter Unwanted Emissions

#### 3.6.1 Transmitter Radiated Unwanted Emissions Limit

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1: Test distance for frequencies at or above 30 MHz, measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).

Note 2: Test distance for frequencies at below 30 MHz, measurements may be performed at a distance closer than the EUT limit distance; however, an attempt should be made to avoid making measurements in the near field. When performing measurements below 30 MHz at a closer distance than the limit distance, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two or more distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). The test report shall specify the extrapolation method used to determine compliance of the EUT.

Un-restricted Band Emissions Limit	
RF output power procedure	Limit (dB)
Peak output power procedure	20
Average output power procedure	30

Note 1: If the peak output power procedure is used to measure the fundamental emission power to demonstrate compliance to requirements, then the peak conducted output power measured within any 100 kHz outside the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum measured in-band peak PSD level.

Note 2: If the average output power procedure is used to measure the fundamental emission power to demonstrate compliance to requirements, then the power in any 100 kHz outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum measured in-band average PSD level.

#### 3.6.2 Measuring Instruments


Refer a test equipment and calibration data table in this test report.

3.6.3 Test Procedures

Test Method	
<input checked="" type="checkbox"/>	Measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).
<input checked="" type="checkbox"/>	For the transmitter unwanted emissions shall be measured using following options below:
<input checked="" type="checkbox"/>	Refer as FCC KDB 558074 v03r01, clause 11 for unwanted emissions into non-restricted bands.
<input checked="" type="checkbox"/>	Refer as FCC KDB 558074 v03r01, clause 12 for unwanted emissions into restricted bands.
<input type="checkbox"/>	Refer as FCC KDB 558074 v03r01, clause 12.2.5.1 Option 1 (trace averaging for duty cycle $\geq 98\%$ )
<input type="checkbox"/>	Refer as FCC KDB 558074 v03r01, clause 12.2.5.2 Option 2 (trace averaging + duty factor).
<input checked="" type="checkbox"/>	Refer as FCC KDB 558074 v03r01, clause 12.2.5.3 Option 3 (Reduced VBW $\geq 1/T$ ).
<input type="checkbox"/>	Refer as ANSI C63.10, clause 4.2.3.2.3 (Reduced VBW). VBW $\geq 1/T$ , where T is pulse time.
<input type="checkbox"/>	Refer as ANSI C63.10, clause 4.2.3.2.4 average value of pulsed emissions.
<input checked="" type="checkbox"/>	Refer as FCC KDB 558074 v03r01, clause 11.3 and 12.2.4 measurement procedure peak limit.
<input checked="" type="checkbox"/>	Refer as FCC KDB 558074 v03r01, clause 12.2.3 measurement procedure Quasi-Peak limit.
<input checked="" type="checkbox"/>	For radiated measurement, refer as FCC KDB 558074 v03r01, clause 12.2.7.
<input checked="" type="checkbox"/>	Refer as ANSI C63.10, clause 6.4 for radiated emissions from below 30 MHz.
<input checked="" type="checkbox"/>	Refer as ANSI C63.10, clause 6.5 for radiated emissions from 30 MHz to 1000 MHz.
<input checked="" type="checkbox"/>	Refer as ANSI C63.10, clause 6.6 for radiated emissions from above 1 GHz.
<input type="checkbox"/>	For conducted and cabinet radiation measurement, refer as FCC KDB 558074 v03r01, clause 12.2.2.
<input type="checkbox"/>	For conducted unwanted emissions into non-restricted bands (relative emission limits). Devices with multiple transmit chains: Refer as FCC KDB 662911, when testing out-of-band and spurious emissions against relative emission limits, tests may be performed on each output individually without summing or adding $10 \log(N)$ if the measurements are made relative to the in-band emissions on the individual outputs.
<input type="checkbox"/>	For conducted unwanted emissions into restricted bands (absolute emission limits). Devices with multiple transmit chains using options given below: (1) Measure and sum the spectra across the outputs or (2) Measure and add $10 \log(N)$ dB
<input type="checkbox"/>	For FCC KDB 662911 The methodology described here may overestimate array gain, thereby resulting in apparent failures to satisfy the out-of-band limits even if the device is actually compliant. In such cases, compliance may be demonstrated by performing radiated tests around the frequencies at which the apparent failures occurred.




### 3.6.4 Test Setup



### 3.6.5 Transmitter Radiated Unwanted Emissions (Below 30MHz)

All amplitude of spurious emissions that are attenuated by more than 30 dB below the permissible value has no need to be reported.


3.6.6 Transmitter Radiated Unwanted Emissions (Below 1GHz)

Transmitter Radiated Unwanted Emissions (Below 1GHz)									
Operating Mode	1			Polarization	V				
Operating Function	Radio link (WLAN) with antenna cable length combination a.								
 <p>The graph plots Level (dBuV/m) on the y-axis (0 to 90) against Frequency (MHz) on the x-axis (30 to 1000). A red line represents the FCC CLASS-B limit, which is 40 dBuV/m from 30 to 100 MHz, 45 dBuV/m from 100 to 200 MHz, and 50 dBuV/m from 200 to 1000 MHz. Six peaks are labeled with blue numbers 1 through 6, corresponding to the data table below.</p>									
	Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn
	MHz	level	dBuV/m	dB	reading	dB		High	Table
		dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	30.00	32.79	40.00	-7.21	49.83	-17.04	Peak	---	---
2	143.49	36.23	43.50	-7.27	52.82	-16.59	Peak	---	---
3	229.82	36.52	46.00	-9.48	54.63	-18.11	Peak	---	---
4	498.51	28.50	46.00	-17.50	39.47	-10.97	Peak	---	---
5	797.27	38.58	46.00	-7.42	44.69	-6.11	Peak	---	---
6	960.23	41.25	54.00	-12.75	45.02	-3.77	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.  
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)  
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)



Transmitter Radiated Unwanted Emissions (Below 1GHz)			
Operating Mode	1	Polarization	H
Operating Function	Radio link (WLAN) with antenna cable length combination a.		




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	162.89	40.58	43.50	-2.92	57.06	-16.48	Peak	---	---
2	231.76	36.54	46.00	-9.46	54.52	-17.98	Peak	---	---
3	281.23	32.87	46.00	-13.13	48.90	-16.03	Peak	---	---
4	797.27	31.60	46.00	-14.40	37.71	-6.11	Peak	---	---
5	838.98	33.11	46.00	-12.89	38.67	-5.56	Peak	---	---
6	960.23	39.76	54.00	-14.24	43.53	-3.77	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.  
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)  
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)



Transmitter Radiated Unwanted Emissions (Below 1GHz)			
Operating Mode	2	Polarization	V
Operating Function	Radio link (WLAN) with antenna cable length combination c.		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	88.20	34.81	43.50	-8.69	56.94	-22.13	Peak	---	---
2	153.19	41.21	43.50	-2.29	57.55	-16.34	Peak	---	---
3	217.21	36.85	46.00	-9.15	55.53	-18.68	Peak	---	---
4	282.20	30.87	46.00	-15.13	46.87	-16.00	Peak	---	---
5	798.24	43.41	46.00	-2.59	49.51	-6.10	Peak	---	---
6	960.23	41.56	54.00	-12.44	45.33	-3.77	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.  
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)  
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)



Transmitter Radiated Unwanted Emissions (Below 1GHz)									
Operating Mode	2				Polarization	H			
Operating Function	Radio link (WLAN) with antenna cable length combination c.								
<p>The graph displays the radiated unwanted emissions for a transmitter. The y-axis represents the level in dBuV/m, ranging from 0 to 90. The x-axis represents the frequency in MHz, ranging from 30 to 1000. A red line indicates the FCC CLASS-B limit, which is constant at 40 dBuV/m from 30 MHz to 100 MHz, then steps up to 45 dBuV/m from 100 MHz to 1000 MHz. Six peaks are identified and labeled 1 through 6, with their corresponding data listed in the table below.</p>									
	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	158.04	40.06	43.50	-3.44	56.40	-16.34	Peak	---	---
2	223.03	39.63	46.00	-6.37	58.08	-18.45	Peak	---	---
3	277.35	36.73	46.00	-9.27	52.89	-16.16	Peak	---	---
4	407.33	34.31	46.00	-11.69	47.16	-12.85	Peak	---	---
5	797.27	37.63	46.00	-8.37	43.74	-6.11	Peak	---	---
6	960.23	41.83	54.00	-12.17	45.60	-3.77	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.  
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)  
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)




3.6.7 Transmitter Radiated Unwanted Emissions (Above 1GHz) for 802.11a

Transmitter Radiated Unwanted Emissions (Above 1GHz)									
Modulation Mode	11a			Test Freq. (MHz)	5745				
N <sub>TX</sub>	1			Polarization	V				
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	3830.00	45.36	54.00	-8.64	43.33	2.03	Average	---	---
2	3830.00	55.96	74.00	-18.04	53.93	2.03	Peak	---	---
3	7660.00	43.08	54.00	-10.92	33.16	9.92	Average	---	---
4	7660.00	53.83	74.00	-20.17	43.91	9.92	Peak	---	---
5	11490.00	50.44	54.00	-3.56	35.61	14.83	Average	---	---
6	11490.00	65.22	74.00	-8.78	50.39	14.83	Peak	---	---
<p>Note 1: "&gt;20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.</p> <p>Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)</p> <p>Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)</p> <p>Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.</p> <p>Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level.</p>									



Transmitter Radiated Unwanted Emissions (Above 1GHz)			
Modulation Mode	11a	Test Freq. (MHz)	5745
N <sub>TX</sub>	1	Polarization	H




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	3830.00	43.18	54.00	-10.82	41.15	2.03	Average	---	---
2	3830.00	56.48	74.00	-17.52	54.45	2.03	Peak	---	---
3	7660.00	38.33	54.00	-15.67	28.41	9.92	Average	---	---
4	7660.00	51.03	74.00	-22.97	41.11	9.92	Peak	---	---
5	11490.00	47.38	54.00	-6.62	32.55	14.83	Average	---	---
6	11490.00	60.92	74.00	-13.08	46.09	14.83	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.  
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)  
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)  
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.  
 Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level.



Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11a	Test Freq. (MHz)	5785
N <sub>TX</sub>	1	Polarization	V



	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	3856.70	45.62	54.00	-8.38	43.52	2.10	Average	---	---
2	3856.70	56.10	74.00	-17.90	54.00	2.10	Peak	---	---
3	7713.30	43.43	54.00	-10.57	33.50	9.93	Average	---	---
4	7713.30	54.20	74.00	-19.80	44.27	9.93	Peak	---	---
5	11570.00	49.71	54.00	-4.29	35.00	14.71	Average	---	---
6	11570.00	64.11	74.00	-9.89	49.40	14.71	Peak	---	---


Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.  
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)  
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)  
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.  
 Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level.





Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11a	Test Freq. (MHz)	5785
N <sub>TX</sub>	1	Polarization	H




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	3856.70	43.29	54.00	-10.71	41.19	2.10	Average	---	---
2	3856.70	56.66	74.00	-17.34	54.56	2.10	Peak	---	---
3	7713.30	37.96	54.00	-16.04	28.03	9.93	Average	---	---
4	7713.30	50.86	74.00	-23.14	40.93	9.93	Peak	---	---
5	11570.00	47.03	54.00	-6.97	32.32	14.71	Average	---	---
6	11570.00	60.41	74.00	-13.59	45.70	14.71	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.  
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)  
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)  
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.  
 Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level.



Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11a	Test Freq. (MHz)	5825
N <sub>TX</sub>	1	Polarization	V




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	36.29	54.00	-17.71	42.60	-6.31	Average	---	---
2	1500.00	49.53	74.00	-24.47	55.84	-6.31	Peak	---	---
3	3883.30	45.26	54.00	-8.74	43.11	2.15	Average	---	---
4	3883.30	55.65	74.00	-18.35	53.50	2.15	Peak	---	---
5	11650.00	52.67	54.00	-1.33	38.10	14.57	Average	---	---
6	11650.00	66.17	74.00	-7.83	51.60	14.57	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.  
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)  
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)  
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.  
 Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level.




Transmitter Radiated Unwanted Emissions (Above 1GHz)			
Modulation Mode	11a	Test Freq. (MHz)	5825
N <sub>TX</sub>	1	Polarization	H



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	34.29	54.00	-19.71	40.60	-6.31	Average	---	---
2	1500.00	47.53	74.00	-26.47	53.84	-6.31	Peak	---	---
3	3883.30	42.98	54.00	-11.02	40.83	2.15	Average	---	---
4	3883.30	56.25	74.00	-17.75	54.10	2.15	Peak	---	---
5	11650.00	48.99	54.00	-5.01	34.42	14.57	Average	---	---
6	11650.00	62.17	74.00	-11.83	47.60	14.57	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.  
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)  
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)  
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.  
 Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level.


3.6.8 Transmitter Radiated Unwanted Emissions (Above 1GHz) for HT20

Transmitter Radiated Unwanted Emissions (Above 1GHz)									
Modulation Mode	HT20		Test Freq. (MHz)	5745					
N <sub>TX</sub>	錯誤! 找不到參照來源。		Polarization	V					
									
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	3830.00	48.10	54.00	-5.90	46.07	2.03	Average	---	---
2	3830.00	56.97	74.00	-17.03	54.94	2.03	Peak	---	---
3	7660.00	41.77	54.00	-12.23	31.85	9.92	Average	---	---
4	7660.00	54.33	74.00	-19.67	44.41	9.92	Peak	---	---
5	11490.00	50.54	54.00	-3.46	35.71	14.83	Average	---	---
6	11490.00	65.74	74.00	-8.26	50.91	14.83	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.  
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)  
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)  
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.  
 Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level.



Transmitter Radiated Unwanted Emissions (Above 1GHz)			
Modulation Mode	HT20	Test Freq. (MHz)	5745
N <sub>TX</sub>	錯誤! 找不到參照來源。	Polarization	H




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	3830.00	44.23	54.00	-9.77	42.20	2.03	Average	---	---
2	3830.00	55.62	74.00	-18.38	53.59	2.03	Peak	---	---
3	7660.00	39.03	54.00	-14.97	29.11	9.92	Average	---	---
4	7660.00	51.83	74.00	-22.17	41.91	9.92	Peak	---	---
5	11490.00	47.62	54.00	-6.38	32.79	14.83	Average	---	---
6	11490.00	61.22	74.00	-12.78	46.39	14.83	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.  
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)  
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)  
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.  
 Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level.



Transmitter Radiated Unwanted Emissions (Above 1GHz)			
Modulation Mode	HT20	Test Freq. (MHz)	5785
N <sub>TX</sub>	錯誤! 找不到參照來源。	Polarization	V




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	3856.70	47.70	54.00	-6.30	45.60	2.10	Average	---	---
2	3856.70	56.50	74.00	-17.50	54.40	2.10	Peak	---	---
3	7713.30	42.22	54.00	-11.78	32.29	9.93	Average	---	---
4	7713.30	54.81	74.00	-19.19	44.88	9.93	Peak	---	---
5	11570.00	51.71	54.00	-2.29	37.00	14.71	Average	---	---
6	11570.00	67.21	74.00	-6.79	52.50	14.71	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.  
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)  
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)  
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.  
 Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level.



Transmitter Radiated Unwanted Emissions (Above 1GHz)			
Modulation Mode	HT20	Test Freq. (MHz)	5785
N <sub>TX</sub>	錯誤! 找不到參照來源。	Polarization	H




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	3856.70	43.70	54.00	-10.30	41.60	2.10	Average	---	---
2	3856.70	55.20	74.00	-18.80	53.10	2.10	Peak	---	---
3	7713.30	39.45	54.00	-14.55	29.52	9.93	Average	---	---
4	7713.30	52.29	74.00	-21.71	42.36	9.93	Peak	---	---
5	11570.00	48.89	54.00	-5.11	34.18	14.71	Average	---	---
6	11570.00	62.37	74.00	-11.63	47.66	14.71	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.  
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)  
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)  
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.  
 Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level.



Transmitter Radiated Unwanted Emissions (Above 1GHz)			
Modulation Mode	HT20	Test Freq. (MHz)	5825
N <sub>TX</sub>	錯誤! 找不到參照來源。	Polarization	V




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	36.49	54.00	-17.51	42.80	-6.31	Average	---	---
2	1500.00	50.29	74.00	-23.71	56.60	-6.31	Peak	---	---
3	3883.30	47.25	54.00	-6.75	45.10	2.15	Average	---	---
4	3883.30	56.13	74.00	-17.87	53.98	2.15	Peak	---	---
5	11650.00	51.47	54.00	-2.53	36.90	14.57	Average	---	---
6	11650.00	66.47	74.00	-7.53	51.90	14.57	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.  
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)  
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)  
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.  
 Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level.





Transmitter Radiated Unwanted Emissions (Above 1GHz)			
Modulation Mode	HT20	Test Freq. (MHz)	5825
N <sub>TX</sub>	錯誤! 找不到參照來源。	Polarization	H




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1500.00	34.39	54.00	-19.61	40.70	-6.31	Average	---	---
2	1500.00	47.61	74.00	-26.39	53.92	-6.31	Peak	---	---
3	3883.30	43.40	54.00	-10.60	41.25	2.15	Average	---	---
4	3883.30	54.89	74.00	-19.11	52.74	2.15	Peak	---	---
5	11650.00	48.78	54.00	-5.22	34.21	14.57	Average	---	---
6	11650.00	62.58	74.00	-11.42	48.01	14.57	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.  
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)  
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)  
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.  
 Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level.



3.6.9 Transmitter Radiated Unwanted Emissions (Above 1GHz) for HT40

Transmitter Radiated Unwanted Emissions (Above 1GHz)			
Modulation Mode	HT40	Test Freq. (MHz)	5755
N <sub>TX</sub>	錯誤! 找不到參照來源。	Polarization	V




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	3836.66	44.17	54.00	-9.83	42.11	2.06	Average	---	---
2	3836.66	49.01	74.00	-24.99	46.95	2.06	Peak	---	---
3	7673.33	39.10	54.00	-14.90	29.16	9.94	Average	---	---
4	7673.33	51.41	74.00	-22.59	41.47	9.94	Peak	---	---
5	11510.00	50.38	54.00	-3.62	35.58	14.80	Average	---	---
6	11510.00	61.63	74.00	-12.37	46.83	14.80	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.  
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)  
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)  
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.  
 Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level.



Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT40	Test Freq. (MHz)	5755
N <sub>TX</sub>	錯誤! 找不到參照來源。	Polarization	H




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	3836.66	40.32	54.00	-13.68	38.26	2.06	Average	---	---
2	3836.66	46.96	74.00	-27.04	44.90	2.06	Peak	---	---
3	7673.33	38.42	54.00	-15.58	28.48	9.94	Average	---	---
4	7673.33	51.17	74.00	-22.83	41.23	9.94	Peak	---	---
5	11510.00	46.01	54.00	-7.99	31.21	14.80	Average	---	---
6	11510.00	58.13	74.00	-15.87	43.33	14.80	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.  
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)  
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)  
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.  
 Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level.



Transmitter Radiated Unwanted Emissions (Above 1GHz)			
Modulation Mode	HT40	Test Freq. (MHz)	5795
N <sub>TX</sub>	錯誤! 找不到參照來源。	Polarization	V




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	3863.33	44.55	54.00	-9.45	42.44	2.11	Average	---	---
2	3863.33	48.73	74.00	-25.27	46.62	2.11	Peak	---	---
3	7726.66	39.71	54.00	-14.29	29.78	9.93	Average	---	---
4	7726.66	51.46	74.00	-22.54	41.53	9.93	Peak	---	---
5	11590.00	50.55	54.00	-3.45	35.89	14.66	Average	---	---
6	11590.00	61.95	74.00	-12.05	47.29	14.66	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.  
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)  
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)  
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.  
 Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level.



Transmitter Radiated Unwanted Emissions (Above 1GHz)			
Modulation Mode	HT40	Test Freq. (MHz)	5795
N <sub>TX</sub>	錯誤! 找不到參照來源。	Polarization	H



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	3863.33	40.55	54.00	-13.45	38.44	2.11	Average	---	---
2	3863.33	47.68	74.00	-26.32	45.57	2.11	Peak	---	---
3	7726.66	38.51	54.00	-15.49	28.58	9.93	Average	---	---
4	7726.66	51.62	74.00	-22.38	41.69	9.93	Peak	---	---
5	11590.00	46.19	54.00	-7.81	31.53	14.66	Average	---	---
6	11590.00	58.18	74.00	-15.82	43.52	14.66	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.  
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)  
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)  
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.  
 Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level.



## 4 Test Equipment and Calibration Data

Test Item	Conducted Emission				
Test Site	Conduction room 1 / (CO01-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
EMC Receiver	R&S	ESCS 30	100169	Oct. 15, 2013	Oct. 14, 2014
LISN	SCHWARZBECK MESS-ELEKTRONIK	Schwarzbeck 8127	8127-667	Dec. 04, 2012	Dec. 03, 2013
LISN (Support Unit)	SCHWARZBECK MESS-ELEKTRONIK	Schwarzbeck 8127	8127-666	Dec. 04, 2012	Dec. 03, 2013
ISN	TESEQ	ISN T800	34406	Apr. 08, 2013	Apr. 07, 2014
ISN	TESEQ	ISN T200A	30494	Apr. 09, 2013	Apr. 08, 2014
ISN	TESEQ	ISN ST08	22589	Jan. 24, 2013	Jan. 23, 2014
RF Current Probe	FCC	F-33-4	121630	Dec. 04, 2012	Dec. 03, 2013
RF Cable-CON	Woken	CFD200-NL	CFD200-NL-001	Dec. 25, 2012	Dec. 24, 2013
ESH3-Z6 V-Network(+)	R&S	ESH3-Z6	100920	Nov. 21, 2012	Nov. 20, 2013
ESH3-Z6 V-Network(-)	R&S	ESH3-Z6	100951	Jan. 30, 2013	Jan. 29, 2014
Two-Line V-Network	R&S	ENV216	101579	Jan. 07, 2013	Jan. 06, 2014
50 ohm terminal	NA	50	01	Apr. 22, 2013	Apr. 21, 2014
50 ohm terminal	NA	50	02	Apr. 22, 2013	Apr. 21, 2014
50 ohm terminal	NA	50	03	Apr. 22, 2013	Apr. 21, 2014
50 ohm terminal (Support Unit)	NA	50	04	Apr. 22, 2013	Apr. 21, 2014

Note: Calibration Interval of instruments listed above is one year.



<b>Test Item</b>	Radiated Emission above 1GHz				
<b>Test Site</b>	966 chamber1 / (03CH01-WS)				
<b>Instrument</b>	<b>Manufacturer</b>	<b>Model No.</b>	<b>Serial No.</b>	<b>Calibration Date</b>	<b>Calibration Until</b>
3m semi-anechoic chamber	CHAMPRO	SAC-03	03CH01-WS	Jan. 04, 2013	Jan. 03, 2014
Spectrum Analyzer	R&S	FSV40	101498	Jan. 24, 2013	Jan. 23, 2014
Receiver	R&S	ESR3	101658	Jan. 28, 2013	Jan. 27, 2014
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-522	Jan. 11, 2013	Jan. 10, 2014
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1096	Feb. 18, 2013	Feb. 17, 2014
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Jan. 14, 2013	Jan. 13, 2014
Amplifier	Burgeon	BPA-530	100219	Nov. 28, 2012	Nov. 27, 2013
Amplifier	Agilent	83017A	MY39501308	Dec. 18, 2012	Dec. 17, 2013
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16014/4	Dec. 25, 2012	Dec. 24, 2013
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16019/4	Dec. 25, 2012	Dec. 24, 2013
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16139/4	Dec. 25, 2012	Dec. 24, 2013
RF Cable-R03m	Woken	CFD400NL-LW	CFD400NL-001	Dec. 25, 2012	Dec. 24, 2013
RF Cable-R10m	Woken	CFD400NL-LW	CFD400NL-002	Dec. 25, 2012	Dec. 24, 2013
control	EM Electronics	EM1000	60612	N/A	N/A
Note: Calibration Interval of instruments listed above is one year.					

Loop Antenna	R&S	HFH2-Z2	100330	Nov. 15, 2012	Nov. 14, 2014
Amplifier	MITEQ	AMF-6F-260400	9121372	Apr. 19, 2013	Apr. 18, 2015
Note: Calibration Interval of instruments listed above is two year.					

<b>Test Item</b>	RF Conducted				
<b>Test Site</b>	TH01-HY				
<b>Instrument</b>	<b>Manufacturer</b>	<b>Model No.</b>	<b>Serial No.</b>	<b>Calibration Date</b>	<b>Calibration Until</b>
Spectrum Analyzer	R&S	FSV 40	101063	Feb. 18, 2013	Feb. 17, 2014
Spectrum Analyzer	R&S	FSP 40	100305	Mar. 20, 2013	Mar. 19, 2014
Temp. and Humidity Chamber	Giant Force	GTH-225-20-SP-SD	MAA1112-007	Nov. 21, 2012	Nov. 20, 2013
Signal Generator	R&S	SMB100A	175727	Jan. 14, 2013	Jan. 14, 2014
Power Sensor	Anritsu	MA2411B	0917017	Feb. 02, 2013	Feb. 01, 2014
Power Meter	Anritsu	ML2495A	0949003	Feb. 02, 2013	Feb. 01, 2014
DC Power Source	G.W.	GPC-6030D	C671845	Jun. 21, 2013	Jun. 20, 2014
AC Power Source	G.W	APS-9102	EL920581	Jul. 16, 2013	Jul. 15, 2014
Note: Calibration Interval of instruments listed above is one year.					