

# RF EXPOSURE REPORT

**REPORT NO.:** SA981228L01

**MODEL NO.:** EOA7535, EOA7530, EOR7550

FCC ID: U2M-OA7535

**ACCORDING:** FCC Guidelines for Human Exposure

**IEEE C95.1** 

APPLICANT: Senao Networks, Inc.

ADDRESS: 3F, No. 529, Chung Cheng Rd., Hsintien, Taipei,

Taiwan, R.O.C.

**ISSUED BY:** Bureau Veritas Consumer Products Services

(H.K.) Ltd., Taoyuan Branch

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou

Hsiang, Taipei Hsien 244, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei

Shan Hsiang, Taoyuan Hsien 333, Taiwan,

R.O.C.



#### 1. RF EXPOSURE LIMIT

# LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	ELECTRIC FIELD MAGNETIC FIELD POWER DENSITE TRENGTH (V/m) STRENGTH (A/m) (mW/cm²)		AVERAGE TIME (minutes)				
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE								
300-1500			F/1500	30				
1500-100,000			1.0	30				

F = Frequency in MHz

## 2. MPE CALCULATION FORMULA

Pd = (Pout\*G) / (4\*pi\*r2)

where

Pd = power density in mW/cm2

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

## 3. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.



## 4. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

FREQUENCY BAND (MHz)	MAX POWER (dBm)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/ cm <sup>2</sup> )	LIMIT (mW/cm²)
2412-2462	26.4	4.5	20	0.245	1.00
5180-5240	14.8	7.0	20	0.030	1.00
5745-5825	22.6	7.0	20	0.181	1.00

#### **CONCULSION:**

Both of the WLAN 2.4G & 5.0G can transmit simultaneously, the formula of calculated the MPE is:

CPD1 / LPD1 + CPD2 / LPD2 + .....etc. < 1

CPD = Calculation power density

LPD = Limit of power density

1. WLAN 2.4G + WLAN 5.0G = 0.426

Therefore, the maximum calculation of this situation is 0.426, which is less than the "1" limit.