



Modular Approval Request FCC (KDB 996369 D01 & Part 15.212)

FCC ID: U2M-PCE2311M

Items to be covered by Single modular transmitters .	Answer from applicant
1. The radio elements must have the radio frequency circuitry shielded. Physical components and tuning capacitor(s) may be located external to the shield, but must be on the module assembly.	Yes.
2. The module must have buffered modulation/data inputs to ensure that the device will comply with Part 15 requirements with any type of input signal.	Yes.
3. The module must contain power supply regulation on the module.	Yes, the modular has its own power supply regulation.
4. The module must contain a permanently attached antenna, or contain a unique antenna connector, and be marketed and operated only with specific antenna(s), per §§ 15.203, 15.204(b), 15.204(c), 15.212(a), 2.929(b).	Yes, it is dipole antenna.
5. The module must demonstrate compliance in a stand-alone configuration.	Yes, the module was tested in a stand-alone configuration, please refer to test setup photo.
6. The module must be labeled with its permanently affixed FCC ID label, or use an electronic display (see KDB Publication 784748)	Yes, the module has a permanently affixed label with its own FCC ID number. Please refer to label and label location.
7. The module must comply with all specific rules applicable to the transmitter, including all the conditions provided in the integration instructions by the grantee.	Yes, the module complies with this requirement. Please refer to user manual.
8. The module must comply with RF exposure requirements.	Yes, the module comply with this requirement. Modular transmitter final configuration comply with FCC RF Exposure.

Note: A limited modular approval (LMA) may be granted for *single* or *split* modular transmitters that comply partially with the requirements above.

Name and surname of applicant (or authorized representative): Iris Chang

Date: 28 July 2023

Signature: 