


# FCC Test Report

**Equipment** : 802.11n 3x3 bgn PCIE Module  
**Brand Name** : Senao Networks  
**Model No.** : PCE3203AH  
**FCC ID** : U2M-PCE3203AH  
**Standard** : 47 CFR FCC Part 15.247  
**Operating Band** : 2400 MHz – 2483.5 MHz  
**FCC Classification** : DTS  
**Applicant** : Senao Networks, Inc.  
3F, No. 529, Chung Cheng Rd., Hsintien, Taipei, Taiwan

The product sample received on Aug. 30, 2013 and completely tested on Nov. 14, 2014. We, SPORTON, would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.10-2009 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by:

  
James Fan / Assistant Manager





## Table of Contents

<b>1</b>	<b>GENERAL DESCRIPTION .....</b>	<b>5</b>
1.1	Information.....	5
1.2	Testing Applied Standards .....	7
1.3	Testing Location Information .....	7
1.4	Measurement Uncertainty .....	8
<b>2</b>	<b>TEST CONFIGURATION OF EUT.....</b>	<b>9</b>
2.1	The Worst Case Modulation Configuration .....	9
2.2	Test Channel Frequencies Configuration.....	9
2.3	The Worst Case Power Setting Parameter .....	9
2.4	The Worst Case Measurement Configuration.....	10
2.5	Support Equipment.....	11
2.6	Test Setup Diagram .....	11
<b>3</b>	<b>TRANSMITTER TEST RESULT .....</b>	<b>12</b>
3.1	AC Power-line Conducted Emissions .....	12
3.2	6dB Bandwidth .....	15
3.3	RF Output Power.....	17
3.4	Power Spectral Density .....	21
3.5	Emissions in non-restricted frequency bands .....	24
3.6	Transmitter Radiated Unwanted Emissions .....	37
<b>4</b>	<b>TEST EQUIPMENT AND CALIBRATION DATA .....</b>	<b>66</b>
	<b>APPENDIX A. TEST PHOTOS .....</b>	<b>A1-A7</b>



### Summary of Test Result

Conformance Test Specifications					
Report Clause	Ref. Std. Clause	Description	Measured	Limit	Result
1.1.2	15.203	Antenna Requirement	Antenna connector mechanism complied	FCC 15.203	Complied
3.1	15.207	AC Power-line Conducted Emissions	[dBuV]: 0.156MHz 48.09 (Margin 7.60dB) – AV 56.76 (Margin 8.93dB) – QP	FCC 15.207	Complied
3.2	15.247(a)	6dB Bandwidth	6dB Bandwidth [MHz] 20M: 9.62 / 40M: 35.71	≥500kHz	Complied
3.3	15.247(b)	RF Output Power (Maximum Conducted (Average) Output Power)	Power [dBm]: 28.38	Power [dBm]: 30	Complied
3.4	15.247(e)	Power Spectral Density	PSD [dBm/3kHz]: 3.07	PSD [dBm/3kHz]: 8	Complied
3.5	15.247(d)	Emissions in non-restricted frequency bands	Out-of -band emissions are 30dB below the highest power	Non-Restricted Bands: > 30 dBc Restricted Bands: FCC 15.209	Complied
3.6	15.247(d)	Transmitter Radiated Unwanted Emissions	Restricted Bands [dBuV/m at 3m]: 2483.50MHz 73.68 (Margin 0.32dB) – PK	Non-Restricted Bands: > 30 dBc Restricted Bands: FCC 15.209	Complied



### Revision History

Report No.	Version	Description	Issued Date
FR382718	Rev. 01	Initial issue of report	Dec. 23, 2014

# 1 General Description

## 1.1 Information

### 1.1.1 RF General Information

RF General Information					
Frequency Range (MHz)	IEEE Std. 802.11	Ch. Freq. (MHz)	Channel Number	Transmit Chains (N <sub>TX</sub> )	RF Output Power (dBm)
2400-2483.5	b	2412-2462	1-11 [11]	3	25.13
2400-2483.5	g	2412-2462	1-11 [11]	3	28.38
2400-2483.5	HT20	2412-2462	1-11 [11]	3	28.25
2400-2483.5	HT40	2422-2452	3-9 [7]	3	22.50

Note 1: RF output power specifies that Maximum Conducted (Average) Output Power.  
 Note 2: 802.11b uses a combination of DSSS-DBPSK, DQPSK, CCK modulation.  
 Note 3: 802.11g/n uses a combination of OFDM-BPSK, QPSK, 16QAM, 64QAM modulation.

### 1.1.2 Antenna Information

Antenna Category	
<input type="checkbox"/>	Integral antenna (antenna permanently attached)
<input type="checkbox"/>	Temporary RF connector provided
<input type="checkbox"/>	No temporary RF connector provided Transmit chains bypass antenna and soldered temporary RF connector provided for connected measurement. In case of conducted measurements the transmitter shall be connected to the measuring equipment via a suitable attenuator and correct for all losses in the RF path.
<input checked="" type="checkbox"/>	External antenna (dedicated antennas)
<input type="checkbox"/>	Single power level with corresponding antenna(s).
<input type="checkbox"/>	Multiple power level and corresponding antenna(s).
<input checked="" type="checkbox"/>	RF connector provided
<input checked="" type="checkbox"/>	Unique antenna connector. (e.g., MMCX, U.FL, IPX, and RP-SMA, RP-N type...)
<input type="checkbox"/>	Standard antenna connector. (e.g., SMA, N, BNC, and TNC type...)

Antenna General Information				
No.	Ant. Model	Ant. Type	Connector	Gain (dBi)
1	Ant 1 (1002302)	PCB Dipole antenna	UFL	2.1859
2	Ant 3 (1002303)	PCB Dipole antenna	UFL	3.3341
3	Ant 5 (1002304)	PCB Dipole antenna	UFL	4.2057



1.1.3 Type of EUT

Identify EUT	
EUT Serial Number	N/A
Presentation of Equipment	<input type="checkbox"/> Production ; <input checked="" type="checkbox"/> Pre-Production ; <input type="checkbox"/> Prototype
Type of EUT	
<input type="checkbox"/>	Stand-alone
<input type="checkbox"/>	Combined (EUT where the radio part is fully integrated within another device) Combined Equipment - Brand Name / Model No.: ...
<input checked="" type="checkbox"/>	Plug-in radio

1.1.4 Test Signal Duty Cycle

Operated Mode for Worst Duty Cycle	
<input type="checkbox"/> Operated normally mode for worst duty cycle	
<input checked="" type="checkbox"/> Operated test mode for worst duty cycle	
Test Signal Duty Cycle (x)	Power Duty Factor [dB] – (10 log 1/x)
<input checked="" type="checkbox"/> 100.00% - IEEE 802.11b	0.00
<input checked="" type="checkbox"/> 98.45% - IEEE 802.11g	0.07
<input checked="" type="checkbox"/> 98.36% - IEEE 802.11n (HT20)	0.07
<input checked="" type="checkbox"/> 99.29% - IEEE 802.11n (HT40)	0.03

1.1.5 EUT Operational Condition

Power Supply Type	3.3 Vdc from host
-------------------	-------------------



### 1.2 Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ◆ 47 CFR FCC Part 15
- ◆ ANSI C63.10-2009
- ◆ FCC KDB 558074 D01 DTS Meas Guidance v03r02
- ◆ FCC KDB 662911 D01 Multiple Transmitter Output v02r01
- ◆ FCC KDB 412172 D01 Determining ERP and EIRP v01

### 1.3 Testing Location Information

Testing Location				
<input checked="" type="checkbox"/>	HWA YA	ADD : No. 52, Hwa Ya 1 <sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.	TEL : 886-3-327-3456 FAX : 886-3-327-0973	
<input checked="" type="checkbox"/>	ICC Lab	ADD : No. 14-1, Lane 19, Wen San 3rd St., Kwei Shan Hsiang, Tao Yuan Hsien 333, Taiwan, R.O.C.	TEL : 886-3-271-8640 FAX : 886-3-327-0973	
Test Condition	Test Site No.	Test Engineer	Test Environment	Test Date
RF Conducted	TH01-HY	Mark Liao	22°C / 63%	Nov. 14, 2014
AC Conduction	*CO01-WS	Skys Huang	23°C / 55%	Feb. 21, 2014
Radiated Emission	*03CH01-WS	Anderson Hung	22°C / 63%	May 02, 2014
Test site registered number [657002] with FCC Test site registered number [10807A-1] with IC				

Note: \* Sporton Lab subcontracts this test item to ICC lab (TAF:2732).

ICC lab is a TAF accreditation test firm and also is an approved provider of Sporton Lab.



### 1.4 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

Measurement Uncertainty			
Test Item		Uncertainty	Limit
AC power-line conducted emissions		±2.92 dB	N/A
Emission bandwidth, 6dB bandwidth		±1.42 %	N/A
RF output power, conducted		±0.63 dB	N/A
Power density, conducted		±0.81 dB	N/A
All emissions, radiated	30 – 1000 MHz	±3.26 dB	N/A
	Above 1 GHz	±4.94 dB	N/A
Temperature		±0.8 °C	N/A
Humidity		±3 %	N/A
DC and low frequency voltages		±3 %	N/A
Time		±1.42 %	N/A
Duty Cycle		±1.42 %	N/A



## 2 Test Configuration of EUT

### 2.1 The Worst Case Modulation Configuration

Worst Modulation Used for Conformance Testing			
Modulation Mode	Transmit Chains (N <sub>TX</sub> )	Data Rate / MCS	Worst Data Rate / MCS
11b	3	1-11 Mbps	1 Mbps
11g	3	6-54 Mbps	6 Mbps
HT20	3	MCS 0-23	MCS 0
HT40	3	MCS 0-23	MCS 0

### 2.2 Test Channel Frequencies Configuration

Test Channel Frequencies Configuration	
IEEE Std. 802.11	Test Channel Frequencies (MHz)
b, g, n (HT-20)	2412-(F1), 2437-(F2), 2462-(F3)
n (HT-40)	2422-(F4), 2437-(F5), 2452-(F6)




### 2.3 The Worst Case Power Setting Parameter

The Worst Case Power Setting Parameter (2400-2483.5MHz band)							
Test Software	ART2-GUI, Version: 2.3						
Modulation Mode	N <sub>TX</sub>	Test Frequency (MHz)					
		NCB: 20MHz			NCB: 40MHz		
		2412	2437	2462	2422	2437	2452
11b,1-11Mbps	3	20	19.5	19.5	--	--	--
11g,6-54Mbps	3	17.5	25	16.5	--	--	--
HT20,M0-23	3	16.5	25	16	--	--	--
HT40,M0-23	3	--	--	--	14.5	16	13.5

## 2.4 The Worst Case Measurement Configuration

The Worst Case Mode for Following Conformance Tests	
<b>Tests Item</b>	AC power-line conducted emissions
<b>Condition</b>	AC power-line conducted measurement for line and neutral Test Voltage: 120Vac / 60Hz


The Worst Case Mode for Following Conformance Tests	
<b>Tests Item</b>	RF Output Power, 6dB bandwidth, Power Spectral Density
<b>Test Condition</b>	Conducted measurement at transmit chains
<b>Modulation Mode</b>	11b, 11g, HT20, HT40

The Worst Case Mode for Following Conformance Tests			
<b>Tests Item</b>	Transmitter Radiated Unwanted Emissions Transmitter Radiated Bandedge Emissions		
<b>Test Condition</b>	Radiated measurement If EUT consist of multiple antenna assembly (multiple antenna are used in EUT regardless of spatial multiplexing MIMO configuration), the radiated test should be performed with highest antenna gain of each antenna type.		
<b>User Position</b>	<input type="checkbox"/> EUT will be placed in fixed position.		
	<input checked="" type="checkbox"/> EUT will be placed in mobile position and operating multiple positions. EUT shall be performed three orthogonal planes. The worst plane is Y-plane.		
	<input type="checkbox"/> EUT will be a hand-held or body-worn battery-powered devices and operating multiple positions. EUT shall be performed two or three orthogonal planes. The worst planes is X.		
<b>Modulation Mode</b>	11b, 11g, HT20, HT40		
<b>Orthogonal Planes of EUT</b>	<b>X Plane</b>	<b>Y Plane</b>	<b>Z Plane</b>
			

## 2.5 Support Equipment

Support Equipment				
No.	Equipment	Brand Name	Model Name	FCC ID
1	Notebook	DELL	E6430	DoC

## 2.6 Test Setup Diagram



### 3 Transmitter Test Result

#### 3.1 AC Power-line Conducted Emissions

##### 3.1.1 AC Power-line Conducted Emissions Limit

AC Power-line Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 – 56 *	56 – 46 *
0.5-5	56	46
5-30	60	50

Note 1: \* Decreases with the logarithm of the frequency.


##### 3.1.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.


##### 3.1.3 Test Procedures

Test Method
<input checked="" type="checkbox"/> Refer as ANSI C63.10-2009, clause 6.2 for AC power-line conducted emissions.

##### 3.1.4 Test Setup



3.1.5 Test Result of AC Power-line Conducted Emissions






AC Power-line Conducted Emissions Result

Power Phase

Line



	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	LISN factor dB	cable loss dB	Remark
1*	0.156	48.09	55.69	-7.60	47.62	0.40	0.07	Average
2	0.156	56.76	65.69	-8.93	56.29	0.40	0.07	QP
3	0.164	41.25	55.25	-14.00	40.75	0.40	0.10	Average
4	0.164	54.79	65.25	-10.46	54.29	0.40	0.10	QP
5	0.191	33.79	53.98	-20.19	33.24	0.39	0.16	Average
6	0.191	46.36	63.98	-17.62	45.81	0.39	0.16	QP
7	0.544	15.04	46.00	-30.96	14.59	0.40	0.05	Average
8	0.544	28.79	56.00	-27.21	28.34	0.40	0.05	QP
9	3.681	32.85	46.00	-13.15	32.16	0.46	0.23	Average
10	3.681	35.19	56.00	-20.81	34.50	0.46	0.23	QP
11	5.305	18.02	50.00	-31.98	17.34	0.48	0.20	Average
12	5.305	29.42	60.00	-30.58	28.74	0.48	0.20	QP
13	22.535	14.84	50.00	-35.16	13.93	0.55	0.36	Average
14	22.535	27.38	60.00	-32.62	26.47	0.55	0.36	QP

Note 1: ">20dB" means emission levels that exceed the level of 20 dB below the applicable limit.  
 Note 2: "N/F" means Nothing Found emissions (No emissions were detected.)

### 3.2 6dB Bandwidth

#### 3.2.1 6dB Bandwidth Limit

6dB Bandwidth Limit	
Systems using digital modulation techniques:	
<input checked="" type="checkbox"/>	6 dB bandwidth $\geq$ 500 kHz.


#### 3.2.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

#### 3.2.3 Test Procedures

Test Method	
<input checked="" type="checkbox"/>	For the emission bandwidth shall be measured using one of the options below:
<input checked="" type="checkbox"/>	Refer as FCC KDB 558074 D01 DTS Meas Guidance v03r02, clause 8.1 Option 1 for 6 dB bandwidth measurement.
<input type="checkbox"/>	Refer as FCC KDB 558074 D01 DTS Meas Guidance v03r02, clause 8.2 Option 2 for 6 dB bandwidth measurement.
<input type="checkbox"/>	Refer as ANSI C63.10, clause 6.9.1 for occupied bandwidth testing.
<input checked="" type="checkbox"/>	For conducted measurement.
<input type="checkbox"/>	The EUT supports single transmit chain and measurements performed on this transmit chain.
<input type="checkbox"/>	The EUT supports diversity transmitting and the results on transmit chain port 1 is the worst case.
<input checked="" type="checkbox"/>	The EUT supports multiple transmit chains using options given below:
<input type="checkbox"/>	Option 1: Multiple transmit chains measurements need to be performed on one of the active transmit chains (antenna outputs). All measurement had be performed on transmit chains 1.
<input checked="" type="checkbox"/>	Option 2: Multiple transmit chains measurements need to be performed on each transmit chains individually (antenna outputs). All measurement had be performed on all transmit chains.


#### 3.2.4 Test Setup



3.2.5 Test Result of Emission Bandwidth

Emission Bandwidth Result										
Condition			Emission Bandwidth (MHz)							
Modulation Mode	N <sub>TX</sub>	Freq. (MHz)	99% Bandwidth				6dB Bandwidth			
			Chain-Port 1	Chain-Port 2	Chain-Port 3	Chain-Port 4	Chain-Port 1	Chain-Port 2	Chain-Port 3	Chain-Port 4
11b	3	2412	13.89	13.77	13.82	--	10.09	9.62	10.09	--
11b	3	2437	13.92	14.00	13.92	--	10.09	10.09	10.09	--
11b	3	2462	13.89	13.90	13.91	--	10.09	10.03	10.09	--
11g	3	2412	17.00	16.87	16.83	--	16.35	16.35	15.30	--
11g	3	2437	19.67	20.38	22.63	--	16.35	15.77	15.77	--
11g	3	2462	16.99	16.85	16.88	--	16.35	16.35	16.35	--
HT-20	3	2412	18.09	18.01	17.91	--	17.57	16.70	16.87	--
HT-20	3	2437	19.92	20.35	22.18	--	16.35	17.16	16.93	--
HT-20	3	2462	18.14	17.88	17.99	--	17.51	17.22	17.51	--
HT-40	3	2422	38.18	38.00	37.78	--	36.06	35.94	35.71	--
HT-40	3	2437	38.74	37.92	37.74	--	36.41	36.41	36.29	--
HT-40	3	2452	38.24	38.32	37.76	--	36.41	36.41	36.29	--
<b>Limit</b>			<b>N/A</b>				<b>≥500 kHz</b>			
<b>Result</b>			<b>Complied</b>							

Note 1: N<sub>TX</sub> = Number of Transmit Chains





### 3.3 RF Output Power

#### 3.3.1 RF Output Power Limit

RF Output Power Limit	
<b>Maximum Peak Conducted Output Power or Maximum Conducted Output Power Limit</b>	
<input checked="" type="checkbox"/> 2400-2483.5 MHz Band:	
<input checked="" type="checkbox"/>	If $G_{TX} \leq 6$ dBi, then $P_{Out} \leq 30$ dBm (1 W)
<input checked="" type="checkbox"/>	Point-to-multipoint systems (P2M): If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)$ dBm
<input type="checkbox"/>	Point-to-point systems (P2P): If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm
<input type="checkbox"/>	Smart antenna system (SAS):
<input type="checkbox"/>	Single beam: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm
<input type="checkbox"/>	Overlap beam: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm
<input type="checkbox"/>	Aggregate power on all beams: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3 + 8$ dB dBm
<b>e.i.r.p. Power Limit:</b>	
<input checked="" type="checkbox"/> 2400-2483.5 MHz Band	
<input checked="" type="checkbox"/>	Point-to-multipoint systems (P2M): $P_{eirp} \leq 36$ dBm (4 W)
<input type="checkbox"/>	Point-to-point systems (P2P): $P_{eirp} \leq \text{MAX}(36, [P_{Out} + G_{TX}])$ dBm
<input type="checkbox"/>	Smart antenna system (SAS)
<input type="checkbox"/>	Single beam: $P_{eirp} \leq \text{MAX}(36, P_{Out} + G_{TX})$ dBm
<input type="checkbox"/>	Overlap beam: $P_{eirp} \leq \text{MAX}(36, P_{Out} + G_{TX})$ dBm
<input type="checkbox"/>	Aggregate power on all beams: $P_{eirp} \leq \text{MAX}(36, [P_{Out} + G_{TX} + 8])$ dBm
$P_{Out}$ = maximum peak conducted output power or maximum conducted output power in dBm, $G_{TX}$ = the maximum transmitting antenna directional gain in dBi. $P_{eirp}$ = e.i.r.p. Power in dBm.	


#### 3.3.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.3.3 Test Procedures

Test Method	
<input type="checkbox"/>	Maximum Peak Conducted Output Power
<input type="checkbox"/>	Refer as FCC KDB 558074 D01 DTS Meas Guidance v03r02, clause 9.1.1 (RBW ≥ DTS BW).
<input checked="" type="checkbox"/>	Refer as FCC KDB 558074 D01 DTS Meas Guidance v03r02, clause 9.1.2 (Peak power meter)
<input checked="" type="checkbox"/>	Maximum Conducted Output Power ( Reference only)
<input type="checkbox"/>	Refer as FCC KDB 558074 D01 DTS Meas Guidance v03r02, clause 9.2.2.2 Method AVGSA-1 (spectral trace averaging).
<input type="checkbox"/>	Refer as FCC KDB 558074 D01 DTS Meas Guidance v03r02, clause 9.2.2.3 Method AVGSA-1 Alt. (slow sweep speed)
<input type="checkbox"/>	Refer as FCC KDB 558074 D01 DTS Meas Guidance v03r02, clause 9.2.2.4 Method AVGSA-2 (spectral trace averaging).
<input type="checkbox"/>	Refer as FCC KDB 558074 D01 DTS Meas Guidance v03r02, clause 9.2.2.5 Method AVGSA-2 Alt. (slow sweep speed)
	RF power meter and average over on/off periods with duty factor or gated trigger
<input checked="" type="checkbox"/>	Refer as FCC KDB 558074 D01 DTS Meas Guidance v03r02, clause 9.2.3.2 Method AVGPM-G (using a gated RF average power meter)
<input checked="" type="checkbox"/>	For conducted measurement.
<input type="checkbox"/>	The EUT supports single transmit chain and measurements performed on this transmit chain.
<input type="checkbox"/>	The EUT supports diversity transmitting and the results on transmit chain port 1 is the worst case.
<input checked="" type="checkbox"/>	The EUT supports multiple transmit chains using options given below: Refer as FCC KDB 662911, In-band power measurements. Using the measure-and-sum approach, measured all transmit ports individually. Sum the power (in linear power units e.g., mW) of all ports for each individual sample and save them.
<input checked="" type="checkbox"/>	If multiple transmit chains, EIRP calculation could be following as methods: $P_{total} = P_1 + P_2 + \dots + P_n$ (calculated in linear unit [mW] and transfer to log unit [dBm]) $EIRP_{total} = P_{total} + DG$

3.3.4 Test Setup





### 3.3.5 Directional Gain for Power Measurement

Directional Gain (DG) Result					
Transmit Chains No.		1	2	3	-
Maximum $G_{ANT}$ (dBi)		2.1859	3.3341	4.2057	-
Modulation Mode	DG (dBi)	$N_{TX}$	$N_{SS}$	STBC	Array Gain (dB)
11b,1-11Mbps	4.2057	3	1	-	-
11g,6-54Mbps	4.2057	3	1	-	-
HT20,M0-23	4.2057	3	1	-	-
HT40,M0-23	4.2057	3	1	-	-

Note: If antenna gains are not equal, Directional gain may be calculated by using the formulas applicable to equal gain antennas with  $G_{ANT}$  set equal to the gain of the antenna having the highest gain.  
Directional gain = highest antenna gain + Array gain, Array gain = 0dB since the device supports CDD mode.



3.3.6 Test Result of Maximum Conducted Output Power

Maximum Conducted (Average) Output Power											
Condition			RF Output Power (dBm)								
Modulation Mode	N <sub>TX</sub>	Freq. (MHz)	Chain Port 1	Chain Port 2	Chain Port 3	Chain Port 4	Sum Chain	Power Limit	DG (dBi)	EIRP Power	EIRP Limit
11b	3	2412	20.21	20.45	20.42	--	25.13	30.00	4.2057	29.3357	36.00
11b	3	2437	19.82	20.39	19.86	--	24.80	30.00	4.2057	29.0057	36.00
11b	3	2462	19.85	20.39	19.64	--	24.74	30.00	4.2057	28.9457	36.00
11g	3	2412	18.14	18.32	18.21	--	23.00	30.00	4.2057	27.2057	36.00
11g	3	2437	23.72	23.77	23.31	--	28.38	30.00	4.2057	32.5857	36.00
11g	3	2462	17.39	17.58	17.18	--	22.16	30.00	4.2057	26.3657	36.00
HT-20	3	2412	17.45	17.85	17.43	--	22.35	30.00	4.2057	26.5557	36.00
HT-20	3	2437	23.55	23.66	23.20	--	28.25	30.00	4.2057	32.4557	36.00
HT-20	3	2462	16.75	16.54	16.68	--	21.43	30.00	4.2057	25.6357	36.00
HT-40	3	2422	15.94	16.04	16.44	--	20.92	30.00	4.2057	25.1257	36.00
HT-40	3	2437	17.85	17.94	17.38	--	22.50	30.00	4.2057	26.7057	36.00
HT-40	3	2452	14.67	15.36	15.18	--	19.85	30.00	4.2057	24.0557	36.00
<b>Result</b>			<b>Complied</b>								

### 3.4 Power Spectral Density

#### 3.4.1 Power Spectral Density Limit

Power Spectral Density Limit	
<input checked="" type="checkbox"/>	Power Spectral Density (PSD) $\leq$ 8 dBm/30kHz


#### 3.4.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

#### 3.4.3 Test Procedures


Test Method	
<input checked="" type="checkbox"/>	Peak power spectral density procedures that the same method as used to determine the conducted output power. If maximum peak conducted output power was measured to demonstrate compliance to the output power limit, then the peak PSD procedure below (Method PKPSD) shall be used. If maximum conducted output power was measured to demonstrate compliance to the output power limit, then one of the average PSD procedures shall be used, as applicable based on the following criteria (the peak PSD procedure is also an acceptable option).
<input type="checkbox"/>	Refer as FCC KDB 558074 D01 DTS Meas Guidance v03r02, clause 10.2 Method PKPSD (RBW=3kHz; detector=peak)..
<input checked="" type="checkbox"/>	Refer as FCC KDB 558074 D01 DTS Meas Guidance v03r02, clause 10.3 Method AVGPSD-1 (spectral trace averaging).
<input type="checkbox"/>	Refer as FCC KDB 558074 D01 DTS Meas Guidance v03r02, clause 10.4 Method AVGPSD-1 Alt. (slow sweep speed)
<input type="checkbox"/>	Refer as FCC KDB 558074 D01 DTS Meas Guidance v03r02, clause 10.5 Method AVGPSD-2 (spectral trace averaging).
<input type="checkbox"/>	Refer as FCC KDB 558074 D01 DTS Meas Guidance v03r02, clause 10.6 Method AVGPSD-2 Alt. (slow sweep speed)
<input checked="" type="checkbox"/>	For conducted measurement.
<input type="checkbox"/>	The EUT supports single transmit chain and measurements performed on this transmit chain.
<input type="checkbox"/>	The EUT supports diversity transmitting and the results on transmit chain port 1 is the worst case.
<input checked="" type="checkbox"/>	The EUT supports multiple transmit chains using options given below:
<input checked="" type="checkbox"/>	Option 1: Measure and sum the spectra across the outputs. Refer as FCC KDB 662911, In-band power spectral density (PSD). Sample all transmit ports simultaneously using a spectrum analyzer for each transmit port. Where the trace bin-by-bin of each transmit port summing can be performed. (i.e., in the first spectral bin of output 1 is summed with that in the first spectral bin of output 2 and that from the first spectral bin of output 3, and so on up to the N <sub>TX</sub> output to obtain the value for the first frequency bin of the summed spectrum.). Add up the amplitude (power) values for the different transmit chains and use this as the new data trace.
<input type="checkbox"/>	Option 2: Measure and add 10 log(N) dB, where N is the number of transmit chains. Refer as FCC KDB 662911, In-band power spectral density (PSD). Performed at each transmit chains and each transmit chains shall be compared with the limit have been reduced with 10 log(N). Or each transmit chains shall be add 10 log(N) to compared with the limit.

### 3.4.4 Test Setup



### 3.4.5 Test Result of Power Spectral Density

Power Spectral Density Result				
Condition			Power Spectral Density (dBm/3kHz)	
Modulation Mode	N <sub>TX</sub>	Freq. (MHz)	Sum Chain	Power Limit
11b	3	2412	1.60	5.95
11b	3	2437	1.21	5.95
11b	3	2462	0.95	5.95
11g	3	2412	-1.91	5.95
11g	3	2437	3.07	5.95
11g	3	2462	-3.31	5.95
HT-20	3	2412	-3.35	5.95
HT-20	3	2437	2.71	5.95
HT-20	3	2462	-4.05	5.95
HT-40	3	2422	-7.29	5.95
HT-40	3	2437	-5.50	5.95
HT-40	3	2452	-8.00	5.95
<b>Result</b>			<b>Complied</b>	



Note:

1. Test results are bin-by-bin summing measured value of each TX port.
2. Directional gain =  $10 * \log((10^{2.1859/20} + 10^{3.3341/20} + 10^{4.2057/20})^2/3) = 8.05 \text{ dBi} > 6 \text{ dBi}$   
 Limit shall be reduced to  $8 \text{ dBm} - (8.05 \text{ dBi} - 6 \text{ dBi}) = 5.95 \text{ dBm}$

### 3.5 Emissions in non-restricted frequency bands

#### 3.5.1 Emissions in non-restricted frequency bands limit

Peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD level in 100 kHz

#### 3.5.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

#### 3.5.3 Test Procedures


##### Reference level measurement

1. Set RBW=100kHz, VBW = 300kHz , Detector = Peak, Sweep time = Auto
2. Trace = max hold , Allow Trace to fully stabilize
3. Use the peak marker function to determine the maximum PSD level

##### Emission level measurement

1. Set RBW=100kHz, VBW = 300kHz , Detector = Peak, Sweep time = Auto
2. Trace = max hold , Allow Trace to fully stabilize
3. Scan Frequency range is up to 25GHz
4. Use the peak marker function to determine the maximum amplitude level

#### 3.5.4 Test Setup




#### 3.5.5 Test Result of Emissions in non-restricted frequency bands


This test item is performed on each TX output individually without summing or adding  $10 \log(N_{ANT})$  since measurements are made relative to the in-band emissions on the individual outputs. Only worst test result of each operating mode is presented.




### 3.5.6 Test Result of Emissions in non-restricted frequency bands

#### 802.11b












802.11g












802.11n HT20














802.11n HT40







### 3.6 Transmitter Radiated Unwanted Emissions

#### 3.6.1 Transmitter Radiated Unwanted Emissions Limit

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1: Test distance for frequencies at or above 30 MHz, measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).

Note 2: Test distance for frequencies at below 30 MHz, measurements may be performed at a distance closer than the EUT limit distance; however, an attempt should be made to avoid making measurements in the near field. When performing measurements below 30 MHz at a closer distance than the limit distance, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two or more distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). The test report shall specify the extrapolation method used to determine compliance of the EUT.

Un-restricted Band Emissions Limit	
RF output power procedure	Limit (dB)
Peak output power procedure	20
Average output power procedure	30

Note 1: If the peak output power procedure is used to measure the fundamental emission power to demonstrate compliance to requirements, then the peak conducted output power measured within any 100 kHz outside the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum measured in-band peak PSD level.

Note 2: If the average output power procedure is used to measure the fundamental emission power to demonstrate compliance to requirements, then the power in any 100 kHz outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum measured in-band average PSD level.

#### 3.6.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.




3.6.3 Test Procedures

Test Method	
<input checked="" type="checkbox"/>	Measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).
<input checked="" type="checkbox"/>	For the transmitter unwanted emissions shall be measured using following options below:
<input checked="" type="checkbox"/>	Refer as FCC KDB 558074 D01 DTS Meas Guidance v03r02, clause 11 for unwanted emissions into non-restricted bands.
<input checked="" type="checkbox"/>	Refer as FCC KDB 558074 D01 DTS Meas Guidance v03r02, clause 12 for unwanted emissions into restricted bands.
<input type="checkbox"/>	Refer as FCC KDB 558074 D01 DTS Meas Guidance v03r02, clause 12.2.5.1 Option 1 (trace averaging for duty cycle $\geq 98\%$ )
<input type="checkbox"/>	Refer as FCC KDB 558074 D01 DTS Meas Guidance v03r02, clause 12.2.5.2 Option 2 (trace averaging + duty factor).
<input checked="" type="checkbox"/>	Refer as FCC KDB 558074 D01 DTS Meas Guidance v03r02, clause 12.2.5.3 Option 3 (Reduced VBW $\geq 1/T$ ).
<input type="checkbox"/>	Refer as ANSI C63.10, clause 4.2.3.2.3 (Reduced VBW). VBW $\geq 1/T$ , where T is pulse time
<input type="checkbox"/>	Refer as ANSI C63.10, clause 4.2.3.2.4 average value of pulsed emissions.
<input checked="" type="checkbox"/>	Refer as FCC KDB 558074 D01 DTS Meas Guidance v03r02, clause 12.2.4 measurement procedure peak limit.
<input checked="" type="checkbox"/>	Refer as FCC KDB 558074 D01 DTS Meas Guidance v03r02, clause 12.2.3 measurement procedure Quasi-Peak limit.
<input checked="" type="checkbox"/>	For radiated measurement, refer as FCC KDB 558074 D01 DTS Meas Guidance v03r02, clause 12.2.7
<input checked="" type="checkbox"/>	Refer as ANSI C63.10, clause 6.4 for radiated emissions from below 30 MHz.
<input checked="" type="checkbox"/>	Refer as ANSI C63.10, clause 6.5 for radiated emissions from 30 MHz to 1000 MHz.
<input checked="" type="checkbox"/>	Refer as ANSI C63.10, clause 6.6 for radiated emissions from above 1 GHz.

Test Method	
<input type="checkbox"/>	For conducted and cabinet radiation measurement, refer as FCC KDB 558074 D01 DTS Meas Guidance v03r02, clause 12.2
<input type="checkbox"/>	For conducted unwanted emissions into non-restricted bands (relative emission limits). Devices with multiple transmit chains: Refer as FCC KDB 662911, when testing out-of-band and spurious emissions against relative emission limits, tests may be performed on each output individually without summing or adding 10 log(N) if the measurements are made relative to the in-band emissions on the individual outputs.
<input type="checkbox"/>	For conducted unwanted emissions into restricted bands (absolute emission limits). Devices with multiple transmit chains using options given below: (1) Measure and sum the spectra across the outputs or (2) Measure and add 10 log(N) dB

### 3.6.4 Test Setup




Note: Test distance is 3m.

### 3.6.5 Transmitter Radiated Unwanted Emissions (Below 30MHz)

All amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.

3.6.6 Transmitter Radiated Unwanted Emissions (Below 1GHz)








Transmitter Radiated Unwanted Emissions (Below 1GHz)

Modulation Mode	11g	Test Freq. (MHz)	2437
Polarization	V		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	70.51	30.91	40.00	-9.09	50.43	-19.52	Peak	---	---
2	419.72	33.36	46.00	-12.64	46.56	-13.20	Peak	---	---
3	670.36	34.57	46.00	-11.43	43.16	-8.59	Peak	---	---
4	781.55	38.47	46.00	-7.53	45.41	-6.94	Peak	---	---
5	798.31	41.53	46.00	-4.47	48.32	-6.79	Peak	---	---
6	898.46	41.96	46.00	-4.04	47.47	-5.51	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.  
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)  
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)



3.6.7 Transmitter Radiated Unwanted Emissions (Above 1GHz) for 11b

Transmitter Radiated Unwanted Emissions (Above 1GHz)									
Modulation Mode	11b			Test Freq. (MHz)	2412				
N <sub>TX</sub>	3			Polarization	H				
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	46.03	54.00	-7.97	49.71	-3.68	Average	---	---
2	2390.00	56.82	74.00	-17.18	60.50	-3.68	Peak	---	---
3	2498.00	52.15	54.00	-1.85	55.38	-3.23	Average	---	---
4	2498.00	59.89	74.00	-14.11	63.12	-3.23	Peak	---	---
5	4824.00	46.39	54.00	-7.61	41.40	4.99	Average	---	---
6	4824.00	50.85	74.00	-23.15	45.86	4.99	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.  
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)  
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)  
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.  
 Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 30 dB relative to the maximum measured in-band level.



Transmitter Radiated Unwanted Emissions (Above 1GHz)									
Modulation Mode	11b			Test Freq. (MHz)	2412				
N <sub>TX</sub>	3			Polarization	V				
	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	2390.00	43.80	54.00	-10.20	47.48	-3.68	Average	---	---
2	2390.00	51.25	74.00	-22.75	54.93	-3.68	Peak	---	---
3	2498.00	45.91	54.00	-8.09	49.14	-3.23	Average	---	---
4	2498.00	55.58	74.00	-18.42	58.81	-3.23	Peak	---	---
5	4824.00	45.97	54.00	-8.03	40.98	4.99	Average	---	---
6	4824.00	50.39	74.00	-23.61	45.40	4.99	Peak	---	---
<p>Note 1: "&gt;20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.</p> <p>Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)</p> <p>Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)</p> <p>Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.</p> <p>Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 30 dB relative to the maximum measured in-band level.</p>									



Transmitter Radiated Unwanted Emissions (Above 1GHz)									
Modulation Mode	11b			Test Freq. (MHz)	2437				
N <sub>TX</sub>	3			Polarization	H				
	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	2352.00	44.36	54.00	-9.64	48.21	-3.85	Average	---	---
2	2352.00	53.05	74.00	-20.95	56.90	-3.85	Peak	---	---
3	4874.00	42.72	54.00	-11.28	37.62	5.10	Average	---	---
4	4874.00	49.05	74.00	-24.95	43.95	5.10	Peak	---	---
5	7311.00	52.98	54.00	-1.02	43.65	9.33	Average	---	---
6	7311.00	58.93	74.00	-15.07	49.60	9.33	Peak	---	---
<p>Note 1: "&gt;20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.</p> <p>Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)</p> <p>Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)</p> <p>Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.</p> <p>Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 30 dB relative to the maximum measured in-band level.</p>									



Transmitter Radiated Unwanted Emissions (Above 1GHz)									
Modulation Mode	11b			Test Freq. (MHz)	2437				
N <sub>TX</sub>	3			Polarization	V				
	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	2352.00	41.68	54.00	-12.32	45.53	-3.85	Average	---	---
2	2352.00	51.44	74.00	-22.56	55.29	-3.85	Peak	---	---
3	4874.00	37.51	54.00	-16.49	32.41	5.10	Average	---	---
4	4874.00	46.73	74.00	-27.27	41.63	5.10	Peak	---	---
5	7311.00	49.59	54.00	-4.41	40.26	9.33	Average	---	---
6	7311.00	56.49	74.00	-17.51	47.16	9.33	Peak	---	---
<p>Note 1: "&gt;20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.</p> <p>Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)</p> <p>Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)</p> <p>Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.</p> <p>Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 30 dB relative to the maximum measured in-band level.</p>									



Transmitter Radiated Unwanted Emissions (Above 1GHz)									
Modulation Mode	11b			Test Freq. (MHz)	2462				
N <sub>TX</sub>	3			Polarization	H				
	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	2483.50	44.05	54.00	-9.95	47.35	-3.30	Average	---	---
2	2483.50	57.31	74.00	-16.69	60.61	-3.30	Peak	---	---
3	4924.00	44.80	54.00	-9.20	39.60	5.20	Average	---	---
4	4924.00	50.31	74.00	-23.69	45.11	5.20	Peak	---	---
5	7386.00	52.96	54.00	-1.04	43.57	9.39	Average	---	---
6	7386.00	58.63	74.00	-15.37	49.24	9.39	Peak	---	---
<p>Note 1: "&gt;20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.</p> <p>Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)</p> <p>Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)</p> <p>Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.</p> <p>Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 30 dB relative to the maximum measured in-band level.</p>									




Transmitter Radiated Unwanted Emissions (Above 1GHz)									
Modulation Mode	11b			Test Freq. (MHz)	2462				
N <sub>TX</sub>	3			Polarization	V				
	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	2483.50	43.91	54.00	-10.09	47.21	-3.30	Average	---	---
2	2483.50	56.98	74.00	-17.02	60.28	-3.30	Peak	---	---
3	4924.00	44.65	54.00	-9.35	39.45	5.20	Average	---	---
4	4924.00	50.18	74.00	-23.82	44.98	5.20	Peak	---	---
5	7386.00	52.84	54.00	-1.16	43.45	9.39	Average	---	---
6	7386.00	58.49	74.00	-15.51	49.10	9.39	Peak	---	---
<p>Note 1: "&gt;20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.</p> <p>Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)</p> <p>Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)</p> <p>Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.</p> <p>Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 30 dB relative to the maximum measured in-band level.</p>									



3.6.8 Transmitter Radiated Unwanted Emissions (Above 1GHz) for 11g

Transmitter Radiated Unwanted Emissions (Above 1GHz)			
Modulation Mode	11g	Test Freq. (MHz)	2412
N <sub>TX</sub>	3	Polarization	H



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1395.00	31.45	54.00	-22.55	39.30	-7.85	Average	---	---
2	1395.00	49.22	74.00	-24.78	57.07	-7.85	Peak	---	---
3	2390.00	49.83	54.00	-4.17	53.51	-3.68	Average	---	---
4	2390.00	72.96	74.00	-1.04	76.64	-3.68	Peak	---	---
5	4824.00	36.95	54.00	-17.05	31.96	4.99	Average	---	---
6	4824.00	50.24	74.00	-23.76	45.25	4.99	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.  
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)  
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)  
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.  
 Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 30 dB relative to the maximum measured in-band level.






Transmitter Radiated Unwanted Emissions (Above 1GHz)									
Modulation Mode	11g			Test Freq. (MHz)	2412				
N <sub>TX</sub>	3			Polarization	V				
	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	1395.00	29.87	54.00	-24.13	37.72	-7.85	Average	---	---
2	1395.00	46.98	74.00	-27.02	54.83	-7.85	Peak	---	---
3	2390.00	48.87	54.00	-5.13	52.55	-3.68	Average	---	---
4	2390.00	71.85	74.00	-2.15	75.53	-3.68	Peak	---	---
5	4824.00	36.84	54.00	-17.16	31.85	4.99	Average	---	---
6	4824.00	50.13	74.00	-23.87	45.14	4.99	Peak	---	---
<p>Note 1: "&gt;20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.</p> <p>Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)</p> <p>Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)</p> <p>Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.</p> <p>Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 30 dB relative to the maximum measured in-band level.</p>									



Transmitter Radiated Unwanted Emissions (Above 1GHz)			
Modulation Mode	11g	Test Freq. (MHz)	2437
N <sub>TX</sub>	3	Polarization	H



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	50.15	54.00	-3.85	53.83	-3.68	Average	---	---
2	2390.00	69.18	74.00	-4.82	72.86	-3.68	Peak	---	---
3	2483.50	52.36	54.00	-1.64	55.66	-3.30	Average	---	---
4	2483.50	72.95	74.00	-1.05	76.25	-3.30	Peak	---	---
5	4874.00	37.45	54.00	-16.55	32.35	5.10	Average	---	---
6	4874.00	50.92	74.00	-23.08	45.82	5.10	Peak	---	---
7	7311.00	47.24	54.00	-6.76	37.91	9.33	Average	---	---
8	7311.00	61.85	74.00	-12.15	52.52	9.33	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.  
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)  
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)  
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.  
 Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 30 dB relative to the maximum measured in-band level.



Transmitter Radiated Unwanted Emissions (Above 1GHz)									
Modulation Mode	11g			Test Freq. (MHz)	2437				
N <sub>TX</sub>	3			Polarization	V				
	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	2390.00	49.35	54.00	-4.65	53.03	-3.68	Average	---	---
2	2390.00	68.33	74.00	-5.67	72.01	-3.68	Peak	---	---
3	2483.50	51.64	54.00	-2.36	54.94	-3.30	Average	---	---
4	2483.50	72.86	74.00	-1.14	76.16	-3.30	Peak	---	---
5	4874.00	38.95	54.00	-15.05	33.85	5.10	Average	---	---
6	4874.00	53.66	74.00	-20.34	48.56	5.10	Peak	---	---
7	7311.00	45.77	54.00	-8.23	36.44	9.33	Average	---	---
8	7311.00	60.09	74.00	-13.91	50.76	9.33	Peak	---	---
<p>Note 1: "&gt;20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.</p> <p>Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)</p> <p>Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)</p> <p>Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.</p> <p>Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 30 dB relative to the maximum measured in-band level.</p>									



Transmitter Radiated Unwanted Emissions (Above 1GHz)									
Modulation Mode	11g			Test Freq. (MHz)	2462				
N <sub>TX</sub>	3			Polarization	H				
	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	2483.50	51.89	54.00	-2.11	55.19	-3.30	Average	---	---
2	2483.50	72.97	74.00	-1.03	76.27	-3.30	Peak	---	---
3	4924.00	37.65	54.00	-16.35	32.45	5.20	Average	---	---
4	4924.00	50.84	74.00	-23.16	45.64	5.20	Peak	---	---
5	7386.00	41.53	54.00	-12.47	32.14	9.39	Average	---	---
6	7386.00	55.46	74.00	-18.54	46.07	9.39	Peak	---	---
<p>Note 1: "&gt;20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.</p> <p>Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)</p> <p>Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)</p> <p>Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.</p> <p>Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 30 dB relative to the maximum measured in-band level.</p>									



Transmitter Radiated Unwanted Emissions (Above 1GHz)									
Modulation Mode	11g			Test Freq. (MHz)	2462				
N <sub>TX</sub>	3			Polarization	V				
	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	2483.50	48.96	54.00	-5.04	52.26	-3.30	Average	---	---
2	2483.50	71.94	74.00	-2.06	75.24	-3.30	Peak	---	---
3	4924.00	37.41	54.00	-16.59	32.21	5.20	Average	---	---
4	4924.00	50.63	74.00	-23.37	45.43	5.20	Peak	---	---
5	7386.00	41.65	54.00	-12.35	32.26	9.39	Average	---	---
6	7386.00	55.78	74.00	-18.22	46.39	9.39	Peak	---	---
<p>Note 1: "&gt;20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.</p> <p>Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)</p> <p>Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)</p> <p>Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.</p> <p>Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 30 dB relative to the maximum measured in-band level.</p>									



3.6.9 Transmitter Radiated Unwanted Emissions (Above 1GHz) for HT20

Transmitter Radiated Unwanted Emissions (Above 1GHz)									
Modulation Mode	HT20			Test Freq. (MHz)	2412				
N <sub>TX</sub>	3			Polarization	H				
<p>The graph plots Level (dBuV/m) on the y-axis (0 to 90) against Frequency (MHz) on the x-axis (1000 to 25000). Two horizontal red lines represent limits: 'FCC CLASS-B' at approximately 74 dBuV/m and 'FCC CLASS-B (AVG)' at approximately 54 dBuV/m. Six vertical blue lines represent measured peaks, labeled 2 through 6. Peak 4 is the highest, exceeding the FCC CLASS-B limit.</p>									
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1395.00	30.94	54.00	-23.06	38.79	-7.85	Average	---	---
2	1395.00	49.28	74.00	-24.72	57.13	-7.85	Peak	---	---
3	2390.00	49.52	54.00	-4.48	53.20	-3.68	Average	---	---
4	2390.00	72.97	74.00	-1.03	76.65	-3.68	Peak	---	---
5	4824.00	36.87	54.00	-17.13	31.88	4.99	Average	---	---
6	4824.00	50.15	74.00	-23.85	45.16	4.99	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.  
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)  
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)  
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.  
 Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 30 dB relative to the maximum measured in-band level.



Transmitter Radiated Unwanted Emissions (Above 1GHz)									
Modulation Mode	HT20		Test Freq. (MHz)	2412					
N <sub>TX</sub>	3		Polarization	V					
	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	1395.00	29.94	54.00	-24.06	37.79	-7.85	Average	---	---
2	1395.00	47.16	74.00	-26.84	55.01	-7.85	Peak	---	---
3	2390.00	49.35	54.00	-4.65	53.03	-3.68	Average	---	---
4	2390.00	72.81	74.00	-1.19	76.49	-3.68	Peak	---	---
5	4824.00	36.91	54.00	-17.09	31.92	4.99	Average	---	---
6	4824.00	50.25	74.00	-23.75	45.26	4.99	Peak	---	---
<p>Note 1: "&gt;20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.</p> <p>Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)</p> <p>Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)</p> <p>Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.</p> <p>Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 30 dB relative to the maximum measured in-band level.</p>									



Transmitter Radiated Unwanted Emissions (Above 1GHz)									
Modulation Mode	HT20		Test Freq. (MHz)	2437					
N <sub>TX</sub>	3		Polarization	H					
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	48.21	54.00	-5.79	51.89	-3.68	Average	---	---
2	2390.00	65.74	74.00	-8.26	69.42	-3.68	Peak	---	---
3	2483.50	51.16	54.00	-2.84	54.46	-3.30	Average	---	---
4	2483.50	72.96	74.00	-1.04	76.26	-3.30	Peak	---	---
5	4874.00	37.24	54.00	-16.76	32.14	5.10	Average	---	---
6	4874.00	50.76	74.00	-23.24	45.66	5.10	Peak	---	---
7	7311.00	47.18	54.00	-6.82	37.85	9.33	Average	---	---
8	7311.00	61.69	74.00	-12.31	52.36	9.33	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.  
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)  
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)  
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.  
 Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 30 dB relative to the maximum measured in-band level.






Transmitter Radiated Unwanted Emissions (Above 1GHz)																																																																																														
Modulation Mode	HT20	Test Freq. (MHz)	2437																																																																																											
N <sub>TX</sub>	3	Polarization	V																																																																																											
	<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 10%;">Freq.</th> <th style="width: 10%;">Emission level</th> <th style="width: 10%;">Limit</th> <th style="width: 10%;">Margin</th> <th style="width: 10%;">SA reading</th> <th style="width: 10%;">Factor</th> <th style="width: 10%;">Remark</th> <th style="width: 10%;">ANT High</th> <th style="width: 10%;">Turn Table</th> </tr> <tr> <th>MHz</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV</th> <th>dB</th> <th></th> <th>cm</th> <th>deg</th> </tr> </thead> <tbody> <tr><td>1</td><td>2390.00</td><td>49.02</td><td>54.00</td><td>-4.98</td><td>52.70</td><td>-3.68</td><td>Average</td><td>---</td></tr> <tr><td>2</td><td>2390.00</td><td>67.69</td><td>74.00</td><td>-6.31</td><td>71.37</td><td>-3.68</td><td>Peak</td><td>---</td></tr> <tr><td>3</td><td>2483.50</td><td>51.75</td><td>54.00</td><td>-2.25</td><td>55.05</td><td>-3.30</td><td>Average</td><td>---</td></tr> <tr><td>4</td><td>2483.50</td><td>72.88</td><td>74.00</td><td>-1.12</td><td>76.18</td><td>-3.30</td><td>Peak</td><td>---</td></tr> <tr><td>5</td><td>4874.00</td><td>39.15</td><td>54.00</td><td>-14.85</td><td>34.05</td><td>5.10</td><td>Average</td><td>---</td></tr> <tr><td>6</td><td>4874.00</td><td>53.64</td><td>74.00</td><td>-20.36</td><td>48.54</td><td>5.10</td><td>Peak</td><td>---</td></tr> <tr><td>7</td><td>7311.00</td><td>45.62</td><td>54.00</td><td>-8.38</td><td>36.29</td><td>9.33</td><td>Average</td><td>---</td></tr> <tr><td>8</td><td>7311.00</td><td>59.81</td><td>74.00</td><td>-14.19</td><td>50.48</td><td>9.33</td><td>Peak</td><td>---</td></tr> </tbody> </table>	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg	1	2390.00	49.02	54.00	-4.98	52.70	-3.68	Average	---	2	2390.00	67.69	74.00	-6.31	71.37	-3.68	Peak	---	3	2483.50	51.75	54.00	-2.25	55.05	-3.30	Average	---	4	2483.50	72.88	74.00	-1.12	76.18	-3.30	Peak	---	5	4874.00	39.15	54.00	-14.85	34.05	5.10	Average	---	6	4874.00	53.64	74.00	-20.36	48.54	5.10	Peak	---	7	7311.00	45.62	54.00	-8.38	36.29	9.33	Average	---	8	7311.00	59.81	74.00	-14.19	50.48	9.33	Peak	---			
Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table																																																																																						
MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg																																																																																						
1	2390.00	49.02	54.00	-4.98	52.70	-3.68	Average	---																																																																																						
2	2390.00	67.69	74.00	-6.31	71.37	-3.68	Peak	---																																																																																						
3	2483.50	51.75	54.00	-2.25	55.05	-3.30	Average	---																																																																																						
4	2483.50	72.88	74.00	-1.12	76.18	-3.30	Peak	---																																																																																						
5	4874.00	39.15	54.00	-14.85	34.05	5.10	Average	---																																																																																						
6	4874.00	53.64	74.00	-20.36	48.54	5.10	Peak	---																																																																																						
7	7311.00	45.62	54.00	-8.38	36.29	9.33	Average	---																																																																																						
8	7311.00	59.81	74.00	-14.19	50.48	9.33	Peak	---																																																																																						
<p>Note 1: "&gt;20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.</p> <p>Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)</p> <p>Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)</p> <p>Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.</p> <p>Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 30 dB relative to the maximum measured in-band level.</p>																																																																																														



Transmitter Radiated Unwanted Emissions (Above 1GHz)			
Modulation Mode	HT20	Test Freq. (MHz)	2462
N <sub>TX</sub>	3	Polarization	H




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	52.37	54.00	-1.63	55.67	-3.30	Average	---	---
2	2483.50	72.94	74.00	-1.06	76.24	-3.30	Peak	---	---
3	4924.00	37.45	54.00	-16.55	32.25	5.20	Average	---	---
4	4924.00	50.63	74.00	-23.37	45.43	5.20	Peak	---	---
5	7386.00	41.49	54.00	-12.51	32.10	9.39	Average	---	---
6	7386.00	55.38	74.00	-18.62	45.99	9.39	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.  
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)  
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)  
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.  
 Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 30 dB relative to the maximum measured in-band level.



Transmitter Radiated Unwanted Emissions (Above 1GHz)			
Modulation Mode	HT20	Test Freq. (MHz)	2462
N <sub>TX</sub>	3	Polarization	V



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2483.50	47.69	54.00	-6.31	50.99	-3.30	Average	---	---
2	2483.50	72.88	74.00	-1.12	76.18	-3.30	Peak	---	---
3	4924.00	37.29	54.00	-16.71	32.09	5.20	Average	---	---
4	4924.00	50.44	74.00	-23.56	45.24	5.20	Peak	---	---
5	7386.00	41.53	54.00	-12.47	32.14	9.39	Average	---	---
6	7386.00	55.62	74.00	-18.38	46.23	9.39	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.  
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)  
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)  
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.  
 Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 30 dB relative to the maximum measured in-band level.



3.6.10 Transmitter Radiated Unwanted Emissions (Above 1GHz) for HT40

Transmitter Radiated Unwanted Emissions (Above 1GHz)									
Modulation Mode	HT40			Test Freq. (MHz)	2422				
N <sub>TX</sub>	3			Polarization	H				
<p>The graph plots Level (dBuV/m) on the y-axis (0 to 90) against Frequency (MHz) on the x-axis (1000 to 25000). Two horizontal red lines represent limits: 'FCC CLASS-B' at approximately 75 dBuV/m and 'FCC CLASS-B (AVG)' at approximately 55 dBuV/m. Six vertical blue lines represent measured peaks, labeled 2 through 6. Peak 2 is at 1395 MHz (~49 dBuV/m), peak 3 at 2390 MHz (~52 dBuV/m), peak 4 at 2390 MHz (~73 dBuV/m), peak 5 at 4844 MHz (~37 dBuV/m), and peak 6 at 4844 MHz (~50 dBuV/m). All peaks are below the FCC CLASS-B limit.</p>									
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	1395.00	30.74	54.00	-23.26	38.59	-7.85	Average	---	---
2	1395.00	48.85	74.00	-25.15	56.70	-7.85	Peak	---	---
3	2390.00	52.41	54.00	-1.59	56.09	-3.68	Average	---	---
4	2390.00	72.98	74.00	-1.02	76.66	-3.68	Peak	---	---
5	4844.00	36.64	54.00	-17.36	31.61	5.03	Average	---	---
6	4844.00	49.95	74.00	-24.05	44.92	5.03	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.  
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)  
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)  
 Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.  
 Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 30 dB relative to the maximum measured in-band level.



Transmitter Radiated Unwanted Emissions (Above 1GHz)																																																																			
Modulation Mode	HT40	Test Freq. (MHz)	2422																																																																
N <sub>TX</sub>	3	Polarization	V																																																																
	<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 10%;">Freq. MHz</th> <th style="width: 10%;">Emission level dBuV/m</th> <th style="width: 10%;">Limit dBuV/m</th> <th style="width: 10%;">Margin dB</th> <th style="width: 10%;">SA reading dBuV</th> <th style="width: 10%;">Factor dB</th> <th style="width: 10%;">Remark</th> <th style="width: 10%;">ANT High cm</th> <th style="width: 10%;">Turn Table deg</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>1395.00</td> <td>29.85</td> <td>54.00</td> <td>-24.15</td> <td>37.70</td> <td>-7.85</td> <td>Average</td> <td>---</td> </tr> <tr> <td>2</td> <td>1395.00</td> <td>47.36</td> <td>74.00</td> <td>-26.64</td> <td>55.21</td> <td>-7.85</td> <td>Peak</td> <td>---</td> </tr> <tr> <td>3</td> <td>2390.00</td> <td>49.52</td> <td>54.00</td> <td>-4.48</td> <td>53.20</td> <td>-3.68</td> <td>Average</td> <td>---</td> </tr> <tr> <td>4</td> <td>2390.00</td> <td>71.33</td> <td>74.00</td> <td>-2.67</td> <td>75.01</td> <td>-3.68</td> <td>Peak</td> <td>---</td> </tr> <tr> <td>5</td> <td>4844.00</td> <td>36.51</td> <td>54.00</td> <td>-17.49</td> <td>31.48</td> <td>5.03</td> <td>Average</td> <td>---</td> </tr> <tr> <td>6</td> <td>4844.00</td> <td>49.82</td> <td>74.00</td> <td>-24.18</td> <td>44.79</td> <td>5.03</td> <td>Peak</td> <td>---</td> </tr> </tbody> </table>	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	1395.00	29.85	54.00	-24.15	37.70	-7.85	Average	---	2	1395.00	47.36	74.00	-26.64	55.21	-7.85	Peak	---	3	2390.00	49.52	54.00	-4.48	53.20	-3.68	Average	---	4	2390.00	71.33	74.00	-2.67	75.01	-3.68	Peak	---	5	4844.00	36.51	54.00	-17.49	31.48	5.03	Average	---	6	4844.00	49.82	74.00	-24.18	44.79	5.03	Peak	---			
Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																											
1	1395.00	29.85	54.00	-24.15	37.70	-7.85	Average	---																																																											
2	1395.00	47.36	74.00	-26.64	55.21	-7.85	Peak	---																																																											
3	2390.00	49.52	54.00	-4.48	53.20	-3.68	Average	---																																																											
4	2390.00	71.33	74.00	-2.67	75.01	-3.68	Peak	---																																																											
5	4844.00	36.51	54.00	-17.49	31.48	5.03	Average	---																																																											
6	4844.00	49.82	74.00	-24.18	44.79	5.03	Peak	---																																																											
<p>Note 1: "&gt;20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.            Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)            Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)            Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.            Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 30 dB relative to the maximum measured in-band level.</p>																																																																			



Transmitter Radiated Unwanted Emissions (Above 1GHz)									
Modulation Mode	HT40		Test Freq. (MHz)	2437					
N <sub>TX</sub>	3		Polarization	H					
	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	49.65	54.00	-4.35	53.33	-3.68	Average	---	---
2	2390.00	70.90	74.00	-3.10	74.58	-3.68	Peak	---	---
3	2483.50	52.03	54.00	-1.97	55.33	-3.30	Average	---	---
4	2483.50	73.68	74.00	-0.32	76.98	-3.30	Peak	---	---
5	4874.00	36.98	54.00	-17.02	31.88	5.10	Average	---	---
6	4874.00	50.24	74.00	-23.76	45.14	5.10	Peak	---	---
<p>Note 1: "&gt;20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.</p> <p>Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)</p> <p>Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)</p> <p>Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.</p> <p>Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 30 dB relative to the maximum measured in-band level.</p>									



Transmitter Radiated Unwanted Emissions (Above 1GHz)									
Modulation Mode	HT40	Test Freq. (MHz)	2437						
N <sub>TX</sub>	3	Polarization	V						
	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	2390.00	49.39	54.00	-4.61	53.07	-3.68	Average	---	---
2	2390.00	70.49	74.00	-3.51	74.17	-3.68	Peak	---	---
3	2483.50	50.92	54.00	-3.08	54.22	-3.30	Average	---	---
4	2483.50	73.06	74.00	-0.94	76.36	-3.30	Peak	---	---
5	4874.00	36.81	54.00	-17.19	31.71	5.10	Average	---	---
6	4874.00	50.49	74.00	-23.51	45.39	5.10	Peak	---	---
<p>Note 1: "&gt;20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.</p> <p>Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)</p> <p>Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)</p> <p>Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.</p> <p>Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 30 dB relative to the maximum measured in-band level.</p>									



Transmitter Radiated Unwanted Emissions (Above 1GHz)									
Modulation Mode	HT40		Test Freq. (MHz)	2452					
N <sub>TX</sub>	3		Polarization	H					
<p>The graph plots Level (dBuV/m) on the y-axis (0 to 90) against Frequency (MHz) on the x-axis (1000 to 25000). Two horizontal red lines represent FCC CLASS-B (at ~75 dBuV/m) and FCC CLASS-B (AVG) (at ~55 dBuV/m). Six vertical blue lines represent emission peaks labeled 1 through 6. Peak 4 is the highest, exceeding the FCC CLASS-B limit.</p>									
	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	1395.00	29.88	54.00	-24.12	37.73	-7.85	Average	---	---
2	1395.00	47.41	74.00	-26.59	55.26	-7.85	Peak	---	---
3	2483.50	50.92	54.00	-3.08	54.22	-3.30	Average	---	---
4	2483.50	72.99	74.00	-1.01	76.29	-3.30	Peak	---	---
5	4904.00	36.51	54.00	-17.49	31.35	5.16	Average	---	---
6	4904.00	49.88	74.00	-24.12	44.72	5.16	Peak	---	---
<p>Note 1: "&gt;20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.            Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)            Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)            Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.            Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 30 dB relative to the maximum measured in-band level.</p>									





Transmitter Radiated Unwanted Emissions (Above 1GHz)									
Modulation Mode	HT40		Test Freq. (MHz)	2452					
N <sub>TX</sub>	3		Polarization	V					
<p>The graph plots Level (dBuV/m) on the y-axis (0 to 90) against Frequency (MHz) on the x-axis (1000 to 25000). Two horizontal red lines represent limits: 'FCC CLASS-B' at approximately 74 dBuV/m and 'FCC CLASS-B (AVG)' at approximately 54 dBuV/m. Six vertical blue lines represent measured peaks, labeled 1 through 6, with their corresponding data in the table below.</p>									
	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	1395.00	30.79	54.00	-23.21	38.64	-7.85	Average	---	---
2	1395.00	48.87	74.00	-25.13	56.72	-7.85	Peak	---	---
3	2483.50	50.64	54.00	-3.36	53.94	-3.30	Average	---	---
4	2483.50	72.47	74.00	-1.53	75.77	-3.30	Peak	---	---
5	4904.00	36.25	54.00	-17.75	31.09	5.16	Average	---	---
6	4904.00	49.62	74.00	-24.38	44.46	5.16	Peak	---	---
<p>Note 1: "&gt;20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.            Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)            Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)            Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.            Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 30 dB relative to the maximum measured in-band level.</p>									



## 4 Test Equipment and Calibration Data

<b>Test Item</b>	Conducted Emission				
<b>Test Site</b>	Conduction room 1 / (CO01-WS)				
<b>Tested Date</b>	Feb. 21, 2014				
<b>Instrument</b>	<b>Manufacturer</b>	<b>Model No.</b>	<b>Serial No.</b>	<b>Calibration Date</b>	<b>Calibration Until</b>
EMC Receiver	R&S	ESCS 30	100169	Oct. 15, 2013	Oct. 14, 2014
LISN	SCHWARZBECK	Schwarzbeck 8127	8127-667	Nov. 23, 2013	Nov. 22, 2014
LISN (Support Unit)	SCHWARZBECK	Schwarzbeck 8127	8127-666	Dec. 04, 2013	Dec. 03, 2014
RF Cable-CON	Woken	CFD200-NL	CFD200-NL-001	Apr. 24, 2013	Apr. 23, 2014
50 ohm terminal (Support Unit)	NA	50	04	Apr. 22, 2013	Apr. 21, 2014
Measurement Software	AUDIX	e3	6.120210k	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

<b>Test Item</b>	Radiated Emissions				
<b>Test Site</b>	966 chamber1 / (03CH01-WS)				
<b>Tested Date</b>	May 02, 2014				
<b>Instrument</b>	<b>Manufacturer</b>	<b>Model No.</b>	<b>Serial No.</b>	<b>Calibration Date</b>	<b>Calibration Until</b>
Spectrum Analyzer	R&S	FSV40	101498	Jan. 25, 2014	Jan. 24, 2015
Receiver	R&S	ESR3	101658	Jan. 10, 2014	Jan. 09, 2015
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-522	Jan. 02, 2014	Jan. 01, 2015
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1096	Feb. 13, 2014	Feb. 12, 2015
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Dec. 27, 2013	Dec. 26, 2014
Preamplifier	Burgeon	BPA-530	SN:100219	Nov. 28, 2013	Nov. 27, 2014
Preamplifier	Agilent	83017A	MY39501308	Dec. 16, 2013	Dec. 15, 2014
Preamplifier	WM	TF-130N-R1	923365	Oct. 23, 2013	Oct. 22, 2014
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16014/4	Dec. 16, 2013	Dec. 15, 2014
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16019/4	Dec. 16, 2013	Dec. 15, 2014
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16139/4	Dec. 16, 2013	Dec. 15, 2014
LF cable 3M	Woken	CFD400NL-LW	CFD400NL-001	Dec. 16, 2013	Dec. 15, 2014
LF cable 10M	Woken	CFD400NL-LW	CFD400NL-002	Dec. 16, 2013	Dec. 15, 2014
Measurement Software	AUDIX	e3	6.120210g	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

Loop Antenna	R&S	HFH2-Z2	100330	Nov. 15, 2012	Nov. 14, 2014
Note: Calibration Interval of instruments listed above is two year.					



<b>Test Item</b>	RF Conducted				
<b>Test Site</b>	TH01-HY				
<b>Tested Date</b>	Nov. 14, 2014				
<b>Instrument</b>	<b>Manufacturer</b>	<b>Model No.</b>	<b>Serial No.</b>	<b>Calibration Date</b>	<b>Calibration Until</b>
Spectrum Analyzer	R&S	FSV 40	101013	Jan. 25, 2014	Jan. 24, 2015
Signal Generator	R&S	SMR40	100116	Jul. 31, 2014	Jul. 30, 2015
Power Sensor	Anritsu	MA2411B	0917017	Jan. 28, 2014	Jan. 27, 2015
Power Meter	Anritsu	ML2495A	0949003	Jan. 28, 2014	Jan. 27, 2015
Measurement Software	Sporton	Sporton_1	1.3.30	NA	NA
Note: Calibration Interval of instruments listed above is one year.					