



# FCC TEST REPORT (CO-LOCATED)

**REPORT NO.:** RF971218L04B-1

**MODEL NO.:** ESR6650 (refer to item 3.1 for more details)

**RECEIVED:** May 21, 2009

**TESTED:** Jul. 09 ~ Jul. 10, 2009

**ISSUED:** Jul. 13, 2009

**APPLICANT:** Senao Networks Inc.

**ADDRESS:** 3F, No. 529, Chung Cheng Rd., Hsintien, Taipei,  
Taiwan, R.O.C.

**ISSUED BY:** Bureau Veritas Consumer Products Services  
(H.K.) Ltd., Taoyuan Branch

**LAB ADDRESS:** No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou  
Hsiang, Taipei Hsien 244, Taiwan, R.O.C.

**TEST LOCATION:** No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei  
Shan Hsiang, Taoyuan Hsien 333, Taiwan,  
R.O.C.

This test report consists of 42 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by TAF or any government agencies. The test results in the report only apply to the tested sample.





## TABLE OF CONTENTS

1.	CERTIFICATION.....	3
2.	SUMMARY OF TEST RESULTS .....	4
2.1	MEASUREMENT UNCERTAINTY.....	4
3.	GENERAL INFORMATION.....	5
3.1	GENERAL DESCRIPTION OF EUT .....	5
3.2	DESCRIPTION OF TEST MODES .....	8
3.2.1	CONFIGURATION OF SYSTEM UNDER TEST .....	9
3.2.2	TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL .....	10
3.3	GENERAL DESCRIPTION OF APPLIED STANDARDS .....	12
3.4	DESCRIPTION OF SUPPORT UNITS .....	12
4.	TEST TYPES AND RESULTS .....	13
4.1	RADIATED EMISSION MEASUREMENT .....	13
4.1.1	LIMITS OF RADIATED EMISSION MEASUREMENT.....	13
4.1.2	TEST INSTRUMENTS.....	14
4.1.3	TEST PROCEDURES .....	15
4.1.4	DEVIATION FROM TEST STANDARD.....	15
4.1.5	TEST SETUP .....	16
4.1.6	EUT OPERATING CONDITIONS .....	16
4.1.7	TEST RESULTS .....	17
4.2	CONDUCTED EMISSION MEASUREMENT .....	29
4.2.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT.....	29
4.2.2	TEST INSTRUMENTS.....	29
4.2.3	TEST PROCEDURES .....	30
4.2.4	DEVIATION FROM TEST STANDARD.....	30
4.2.5	TEST SETUP.....	31
4.2.6	EUT OPERATING CONDITIONS .....	31
4.2.7	TEST RESULTS .....	32
5.	PHOTOGRAPHS OF THE TEST CONFIGURATION.....	40
6.	INFORMATION ON THE TESTING LABORATORIES .....	41
7.	APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB.....	42



# 1. CERTIFICATION

**PRODUCT:** Wireless Micro Router

**MODEL:** ESR6650 (refer to item 3.1 for more details)

**BRAND:** EnGenius (refer to item 3.1 for more details)

**APPLICANT:** Senao Networks Inc.

**TEST SAMPLE:** ENGINEERING SAMPLE

**TESTED:** Jul. 09 ~ Jul. 10, 2009

**STANDARDS: FCC Part 15, Subpart C (Section 15.247)**

ANSI C63.4-2003

The above equipment (Model: ESR6650) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**PREPARED BY** : Ivy Lin , **DATE:** Jul. 13, 2009  
Ivy Lin / Specialist

**TECHNICAL ACCEPTANCE** : Long Chen , **DATE:** Jul. 13, 2009  
Responsible for RF Long Chen / Senior Engineer

**APPROVED BY** : Gary Chang , **DATE:** Jul. 13, 2009  
Gary Chang / Assistant Manager

## 2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -5.28dB at 0.369MHz.
15.247(d)	Radiated Emissions Limit: Table 15.209	PASS	Meet the requirement of limit. Minimum passing margin is -1.89dB at 33.79MHz.

### 2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	150kHz~30MHz	2.44 dB
Radiated emissions	30MHz ~ 200MHz	3.34 dB
	200MHz ~1000MHz	3.35 dB
	1GHz ~ 18GHz	2.26 dB
	18GHz ~ 40GHz	1.94 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k = 2$ .



A D T

### 3. GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

<b>PRODUCT</b>	Wireless Micro Router
<b>MODEL NO.</b>	ESR6650 (Refer to note for more detail)
<b>FCC ID</b>	U2M-SR97908005
<b>POWER SUPPLY</b>	12Vdc from AC adapter
<b>MODULATION TYPE</b>	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
<b>MODULATION TECHNOLOGY</b>	DSSS, OFDM
<b>TRANSFER RATE</b>	802.11b: 11.0/ 5.5/ 2.0/ 1.0Mbps 802.11g: 54.0/ 48.0/ 36.0/ 24.0/ 18.0/ 12.0/ 9.0/ 6.0Mbps Draft 802.11n: up to 150Mbps
<b>OPERATING FREQUENCY</b>	2412MHz ~ 2462MHz
<b>NUMBER OF CHANNEL</b>	11 for 802.11b, 802.11g, draft 802.11n (20MHz) 7 for draft 802.11n (40MHz)
<b>MAXIMUM OUTPUT POWER</b>	320.627mW
<b>ANTENNA TYPE</b>	Dipole antenna with 2dBi gain
<b>DATA CABLE</b>	NA
<b>I/O PORTS</b>	RJ45, USB
<b>ACCESSORY DEVICES</b>	AC adapter



A D T

**NOTE:**

1. This report is prepared for FCC class II permissive change. The differences compared with original report are the addition of brand, adapter and changing model and interface.
2. The interfaces change are as below:
  - ✧ Four LAN ports change to two LAN ports
  - ✧ Add one USB port (This port can support 3G dongle)
3. The models as below are electrically identical, different brand names and models no. are for marketing purpose.

BRAND NAME	MODEL NO.
EnGenius	ESR6650
	ERB9250
	ECB9300
Rosewill	RNX-N4-3G
HIFULL	OBA-6800

4. The EUT was powered by the following adapter.

**<Original>**

<b>ADAPTER 1</b>	
<b>BRAND:</b>	AMIGO
<b>MODEL:</b>	AMS6-1201000SU
<b>INPUT:</b>	120Vac, 60Hz, 0.5A
<b>OUTPUT:</b>	12Vdc, 1.0A
<b>POWER LINE:</b>	1.8m non-shielded cable without core

<b>ADAPTER 2</b>	
<b>BRAND:</b>	DVE
<b>MODEL:</b>	DSA-12G-12 FUS 120120
<b>INPUT:</b>	100-240Vac, 50/60Hz, 0.3A
<b>OUTPUT:</b>	12Vdc, 1.0A
<b>POWER LINE:</b>	1.8m non-shielded cable without core



A D T

<New >

<b>ADAPTER 1</b>	
<b>BRAND:</b>	Powertron
<b>MODEL:</b>	PA1015-2HU
<b>INPUT:</b>	100-240Vac, 50-60Hz, 0.4A
<b>OUTPUT:</b>	12Vdc, 1.25A
<b>POWER LINE:</b>	1.8m non-shielded cable without core

<b>ADAPTER 2</b>	
<b>BRAND:</b>	DVE
<b>MODEL:</b>	DSA-15P-12 US 120150
<b>INPUT:</b>	100-240Vac, 50/60Hz, 0.5A
<b>OUTPUT:</b>	12Vdc, 1.25A
<b>POWER LINE:</b>	1.8m non-shielded cable without core

5. The EUT provides one completed transmitter and one receiver.
6. USB port of EUT can support 3G Mobile USB dongle, we choice 3 typical dongle which have been sold to the market to confirm inter-modulation between 3G Mobile and 802.11 n.
7. The above EUT information was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

### 3.2 DESCRIPTION OF TEST MODES

Eleven channels are provided for 802.11b, 802.11g and draft 802.11n (20MHz):


CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2412MHz	7	2442MHz
2	2417MHz	8	2447MHz
3	2422MHz	9	2452MHz
4	2427MHz	10	2457MHz
5	2432MHz	11	2462MHz
6	2437MHz		

Seven channels are provided for draft 802.11n (40MHz):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2422MHz	5	2442MHz
2	2427MHz	6	2447MHz
3	2432MHz	7	2452MHz
4	2437MHz		



### 3.2.1 CONFIGURATION OF SYSTEM UNDER TEST



### 3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT CONFIGURE MODE	APPLICABLE TO			DESCRIPTION
	RE $\geq$ 1G	RE $<$ 1G	CE	
A	√	√	√	3G USB Dongle Model: 888U (FCC ID: N7NC888)
B	√	√	√	3G USB Dongle Model: E176 (FCC ID: QISE176)
C	√	√	√	3G USB Dongle Model: MD300 (FCC ID: PY7F3232021)

Where **RE $\geq$ 1G**: Radiated Emission above 1GHz      **RE $<$ 1G**: Radiated Emission below 1GHz  
**CE**: Conducted Emission Measurement

**NOTE:** Test modes as below are composed of the max output power channel of each band.

#### **RADIATED EMISSION TEST (ABOVE 1GHz):**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	FREQ. RANGE (MHz)	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)	AXIS
A	802.11g + WCDMA850	2412~2462	1 to 11	6 + 4182	OFDM	BPSK	1.0	Z
		826.4-846.6	4132 to 4233		-	QPSK	-	
A	802.11g + WCDMA1900	2412~2462	1 to 11	6 + 9262	OFDM	BPSK	1.0	Z
		1852.4-1907.6	9262 to 9538		-	QPSK	-	
B	802.11g + WCDMA850	2412~2462	1 to 11	6 + 4132	OFDM	BPSK	6.0	Z
		826.4-846.6	4132 to 4233		-	QPSK	-	
C	802.11g + WCDMA850	2412~2462	1 to 11	6 + 4182	OFDM	BPSK	6.0	Z
		826.4-846.6	4132 to 4233		-	QPSK	-	



A D T

**RADIATED EMISSION TEST (BELOW 1GHz):**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	FREQ. RANGE (MHz)	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)	AXIS
A	802.11g + WCDMA850	2412~2462 826.4-846.6	1 to 11 4132 to 4233	6 + 4182	OFDM -	BPSK QPSK	1.0 -	Z
	802.11g + WCDMA1900	2412~2462 1852.4-1907.6	1 to 11 9262 to 9538	6 + 9262	OFDM -	BPSK QPSK	1.0 -	Z
B	802.11g + WCDMA850	2412~2462 826.4-846.6	1 to 11 4132 to 4233	6 + 4132	OFDM -	BPSK QPSK	6.0 -	Z
C	802.11g + WCDMA850	2412~2462 826.4-846.6	1 to 11 4132 to 4233	6 + 4182	OFDM -	BPSK QPSK	6.0 -	Z

**CONDUCTED EMISSION TEST:**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	FREQ. RANGE (MHz)	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
A	802.11g + WCDMA850	2412~2462 826.4-846.6	1 to 11 4132 to 4233	6 + 4182	OFDM -	BPSK QPSK	1.0 -
	802.11g + WCDMA1900	2412~2462 1852.4-1907.6	1 to 11 9262 to 9538	6 + 9262	OFDM -	BPSK QPSK	1.0 -
B	802.11g + WCDMA850	2412~2462 826.4-846.6	1 to 11 4132 to 4233	6 + 4132	OFDM -	BPSK QPSK	6.0 -
C	802.11g + WCDMA850	2412~2462 826.4-846.6	1 to 11 4132 to 4233	6 + 4182	OFDM -	BPSK QPSK	6.0 -

### 3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

#### FCC Part 15, Subpart C (Section 15.247)

#### ANSI C63.4-2003

All test items have been performed and recorded as per the above standards.

**NOTE:** The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

### 3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK	DELL	PP05L	12130898320	E2K24CLNS
2	NOTEBOOK	DELL	PP05L	9954115984	E2K24CLNS
3	3G USB DONGLE	Sierra Aircard	888U	NA	N7NC888
4	3G USB DONGLE	HUAWEI	E176	NA	QISE176
5	3G USB DONGLE	Sony Ericsson	MD300	NA	PY7F3232021

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	10m UTP RJ45 cable
2	10m UTP RJ45 cable
3	NA
4	
5	

**NOTE:** 1. All power cords of the above support units are non shielded (1.8m).  
 2. Item 1-2 acted as a communication partner to transfer data.  
 3. Item 3-5 were provided by client.

## 4. TEST TYPES AND RESULTS

### 4.1 RADIATED EMISSION MEASUREMENT

#### 4.1.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

#### 4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESIB7	100212	May 25, 2009	May 24, 2010
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100269	Aug. 08, 2008	Aug. 07, 2009
BILOG Antenna SCHWARZBECK	VULB9168	9168-156	Apr. 30, 2009	Apr. 29, 2010
HORN Antenna SCHWARZBECK	BBHA 9120 D	9120D-563	Aug. 06, 2008	Aug. 05, 2009
HORN Antenna SCHWARZBECK	BBHA 9170	BBHA9170242	Jan. 06, 2009	Jan. 05, 2010
Preamplifier Agilent	8449B	3008A01911	Sep. 10, 2008	Sep. 09, 2009
Preamplifier Agilent	8447D	2944A10638	Dec. 26, 2008	Dec. 25, 2009
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	218190/4 231241/4	May 13, 2009	May 12, 2010
RF signal cable Worken	8D-FB	Cable-HYCH9-01	Aug. 09, 2008	Aug. 08, 2009
Software	ADT_Radiated_ V7.6.15.9.2	NA	NA	NA
Antenna Tower EMCO	2070/2080	512.835.4684	NA	NA
Turn Table EMCO	2087-2.03	NA	NA	NA
Antenna Tower & Turn Table Controller EMCO	2090	NA	NA	NA

- NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HwaYa Chamber 9.
3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
4. The FCC Site Registration No. is 460141.
5. The IC Site Registration No. is IC 7450F-4.

#### 4.1.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.


**NOTE:**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. All modes of operation were investigated and the worst-case emissions are reported.

#### 4.1.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.1.5 TEST SETUP



For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.1.6 EUT OPERATING CONDITIONS

- Placed the EUT on the testing table.
- The necessary accessories enable the system in full functions.
- Prepared the other notebook outside of testing area to act as a communication partner.
- The communication partner connected with EUT via a RJ45 cable and run a test program (provided by manufacturer) to enable EUT under transmission condition continuously at specific channel frequency.



#### 4.1.7 TEST RESULTS

##### 802.11g OFDM MODULATION + WCDMA850

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	CH 6 + CH 4182	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH 1007 hPa	TESTED BY	Kevin Liang
TEST MODE	A		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1672.80	43.48 PK	82.22	-38.74	1.08 H	168	13.69	29.79
2	2384.00	57.90 PK	74.00	-16.10	1.22 H	23	25.70	32.20
3	2384.00	47.53 AV	54.00	-6.47	1.22 H	23	15.33	32.20
4	*2437.00	107.71 PK			1.22 H	23	75.32	32.39
5	*2437.00	96.75 AV			1.22 H	23	64.36	32.39
6	2489.00	57.45 PK	74.00	-16.55	1.22 H	22	24.87	32.58
7	2489.00	46.82 AV	54.00	-7.18	1.22 H	22	14.24	32.58
8	#2506.00	56.60 PK	87.71	-31.11	1.59 H	243	23.96	32.64
9	#2506.00	44.44 AV	76.75	-20.15	1.59 H	243	11.80	32.64
10	3345.00	61.01 PK	82.22	-21.21	1.02 H	169	26.23	34.78
11	4874.00	51.35 PK	74.00	-22.65	1.35 H	6	12.94	38.41
12	4874.00	37.26 AV	54.00	-16.74	1.35 H	6	-1.15	38.41
13	7311.00	62.46 PK	74.00	-11.54	1.49 H	319	17.82	44.64
14	7311.00	48.25 AV	54.00	-5.75	1.49 H	319	3.61	44.64

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
  2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* “: Fundamental frequency.
  6. The limit value of point 1 and point 10 is defined as per 22.917.
  7. “#”:The radiated frequency is out the restricted band.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	CH 6 + CH 4182	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH 1007 hPa	TESTED BY	Kevin Liang
TEST MODE	A		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1672.80	45.35 PK	82.22	-36.87	1.14 V	20	15.56	29.79
2	2384.00	63.87 PK	74.00	-10.13	1.00 V	89	31.67	32.20
3	2384.00	51.76 AV	54.00	-2.24	1.00 V	89	19.56	32.20
4	*2437.00	114.46 PK			1.01 V	78	82.07	32.39
5	*2437.00	104.25 AV			1.01 V	78	71.86	32.39
6	2489.00	64.93 PK	74.00	-9.07	1.00 V	85	32.35	32.58
7	2489.00	51.33 AV	54.00	-7.18	1.00 V	85	18.75	32.58
8	#2506.00	63.92 PK	94.46	-30.54	1.21 V	6	31.28	32.64
9	#2506.00	51.40 AV	84.25	-32.85	1.21 V	6	18.76	32.64
10	3341.00	61.56 PK	82.22	-20.66	1.21 V	329	26.78	34.78
11	4874.00	51.83 PK	74.00	-22.17	1.03 V	96	13.42	38.41
12	4874.00	38.18 AV	54.00	-15.82	1.03 V	96	-0.23	38.41
13	7311.00	61.23 PK	74.00	-12.77	1.00 V	356	16.59	44.64
14	7311.00	47.08 AV	54.00	-6.92	1.00 V	356	2.44	44.64

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
  2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* “: Fundamental frequency.
  6. The limit value of point 1 and point 10 is defined as per 22.917.
  7. “#”:The radiated frequency is out the restricted band.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	CH 6 + CH 4132	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH 1007 hPa	TESTED BY	Kevin Liang
TEST MODE	B		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1652.80	43.87 PK	82.22	-38.35	1.00 H	192	14.14	29.73
2	2384.00	57.52 PK	74.00	-16.48	1.21 H	22	25.32	32.20
3	2384.00	47.16 AV	54.00	-6.84	1.21 H	22	14.96	32.20
4	*2437.00	107.41 PK			1.21 H	22	75.02	32.39
5	*2437.00	96.48 AV			1.21 H	22	64.09	32.39
6	2479.20	43.26 PK	82.22	-38.96	1.03 H	15	10.72	32.55
7	2489.00	57.15 PK	74.00	-16.85	1.21 H	22	24.57	32.58
8	2489.00	46.56 AV	54.00	-7.44	1.21 H	22	13.98	32.58
9	3263.00	46.28 PK	74.00	-27.72	1.05 H	221	11.63	34.65
10	3263.00	33.02 AV	54.00	-20.98	1.05 H	221	-1.63	34.65
11	4874.00	50.12 PK	74.00	-23.88	1.13 H	29	11.71	38.41
12	4874.00	36.84 AV	54.00	-17.16	1.13 H	29	-1.57	38.41
13	7311.00	62.56 PK	74.00	-11.44	1.16 H	288	17.92	44.64
14	7311.00	48.29 AV	54.00	-5.71	1.16 H	288	3.65	44.64

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
  2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* “: Fundamental frequency.
  6. The limit value of point 1 and point 6 are defined as per 22.917.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	CH 6 + CH 4132	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH 1007 hPa	TESTED BY	Kevin Liang
TEST MODE	B		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1652.80	45.08 PK	82.22	-37.17	1.04 V	167	15.35	29.73
2	2384.00	63.71 PK	74.00	-10.29	1.01 V	83	31.51	32.20
3	2384.00	51.59 AV	54.00	-2.41	1.01 V	83	19.39	32.20
4	*2437.00	114.26 PK			1.01 V	83	81.87	32.39
5	*2437.00	104.03 AV			1.01 V	83	71.64	32.39
6	2479.20	46.37 PK	82.22	-35.85	1.01 V	167	13.83	32.55
7	2489.00	64.02 PK	74.00	-9.98	1.01 V	83	31.44	32.58
8	2489.00	50.54 AV	54.00	-3.46	1.01 V	83	17.96	32.58
9	3263.00	45.13 PK	74.00	-28.87	1.00 V	12	10.48	34.65
10	3263.00	34.64 AV	54.00	-19.36	1.00 V	12	-0.01	34.65
11	4874.00	51.62 PK	74.00	-22.38	1.03 V	22	13.21	38.41
12	4874.00	37.94 AV	54.00	-16.06	1.03 V	22	-0.47	38.41
13	7311.00	61.03 PK	74.00	-12.97	1.12 V	95	16.39	44.64
14	7311.00	46.82 AV	54.00	-7.18	1.12 V	95	2.18	44.64

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
  2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* “: Fundamental frequency.
  6. The limit value of point 1 and point 6 are defined as per 22.917.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	CH 6 + CH 4182	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH 1007 hPa	TESTED BY	Kevin Liang
TEST MODE	C		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#1280.00	54.81 PK	87.62	-32.81	1.00 H	108	26.44	28.37
2	#1280.00	43.19 AV	76.66	-33.47	1.00 H	108	14.82	28.37
3	1672.80	43.56 PK	82.22	-38.66	1.45 H	212	13.77	29.79
4	2384.00	57.78 PK	74.00	-16.22	1.20 H	20	25.58	32.20
5	2384.00	47.44 AV	54.00	-6.56	1.20 H	20	15.24	32.20
6	*2437.00	107.62 PK			1.20 H	20	75.23	32.39
7	*2437.00	96.66 AV			1.20 H	20	64.27	32.39
8	2489.00	57.30 PK	74.00	-16.70	1.20 H	20	24.72	32.58
9	2489.00	46.71 AV	54.00	-7.29	1.20 H	20	14.13	32.58
10	#2519.00	42.58 PK	87.62	-45.04	1.26 H	199	9.89	32.69
11	#2519.00	36.26 AV	76.66	-40.40	1.26 H	199	3.57	32.69
12	4874.00	51.25 PK	74.00	-22.75	1.44 H	27	12.84	38.41
13	4874.00	37.14 AV	54.00	-16.86	1.44 H	27	-1.27	38.41
14	7311.00	62.36 PK	74.00	-11.64	1.43 H	317	17.72	44.64
15	7311.00	48.14 AV	54.00	-5.86	1.43 H	317	3.50	44.64

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
  2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* “: Fundamental frequency.
  6. The limit value of point 3 is defined as per 22.917.
  7. "#":The radiated frequency is out the restricted band.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	CH 6 + CH 4182	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH 1007 hPa	TESTED BY	Kevin Liang
TEST MODE	C		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	#1280.00	54.45 PK	94.39	-39.94	1.18 V	258	26.08	28.37
2	#1280.00	44.90 AV	84.15	-39.25	1.18 V	258	16.53	28.37
3	1672.80	49.93 PK	82.22	-24.07	1.14 V	129	20.14	29.79
4	2384.00	63.80 PK	74.00	-10.20	1.00 V	89	31.60	32.20
5	2384.00	51.67 AV	54.00	-2.33	1.00 V	89	19.47	32.20
6	*2437.00	114.39 PK			1.00 V	85	82.00	32.39
7	*2437.00	104.15 AV			1.00 V	85	71.76	32.39
8	2489.00	64.84 PK	74.00	-9.16	1.00 V	86	32.26	32.58
9	2489.00	51.26 AV	54.00	-2.74	1.00 V	86	18.68	32.58
10	#2519.00	49.28 PK	94.39	-45.11	1.14 V	17	16.59	32.69
11	#2519.00	47.39 AV	84.15	-36.75	1.14 V	17	14.70	32.69
12	4874.00	51.69 PK	74.00	-22.31	1.01 V	23	13.28	38.41
13	4874.00	38.13 AV	54.00	-15.87	1.01 V	23	-0.28	38.41
14	7311.00	61.12 PK	74.00	-12.88	1.46 V	10	16.48	44.64
15	7311.00	46.88 AV	54.00	-7.12	1.46 V	10	2.24	44.64

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
  2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* “: Fundamental frequency.
  6. The limit value of point 3 is defined as per 22.917.
  7. “#”:The radiated frequency is out the restricted band.



A D T

## 802.11g OFDM MODULATION + CDMA1900

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	CH 6 + CH 9262	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH 1007 hPa	TESTED BY	Kevin Liang
TEST MODE	A		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*1852.40	118.66 PK			1.31 H	323	88.36	30.30
2	2384.00	57.72 PK	74.00	-16.28	1.22 H	18	25.52	32.20
3	2384.00	47.49 AV	54.00	-6.51	1.22 H	18	15.29	32.20
4	*2437.00	107.58 PK			1.22 H	18	75.19	32.39
5	*2437.00	96.61 AV			1.22 H	18	64.22	32.39
6	2489.00	57.34 PK	74.00	-16.66	1.27 H	19	24.76	32.58
7	2489.00	46.75 AV	54.00	-7.25	1.27 H	19	14.17	32.58
8	3704.80	62.56 PK	82.22	-19.66	1.16 H	262	27.02	35.54
9	4874.00	51.22 PK	74.00	-22.78	1.41 H	2	12.81	38.41
10	4874.00	37.07 AV	54.00	-16.93	1.41 H	2	-1.34	38.41
11	7311.00	62.30 PK	74.00	-11.70	1.40 H	310	17.66	44.64
12	7311.00	48.12 AV	54.00	-5.88	1.40 H	310	3.48	44.64

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
  2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* “: Fundamental frequency.
  6. The limit value of point 8 is defined as per 24.238.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	CH 6 + CH 9262	FREQUENCY RANGE	1 ~ 25GHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH 1007 hPa	TESTED BY	Kevin Liang
TEST MODE	A		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*1852.40	121.02 PK			1.31 V	323	90.72	30.30
2	2384.00	63.75 PK	74.00	-10.25	1.00 V	91	31.55	32.20
3	2384.00	51.62 AV	54.00	-2.38	1.00 V	91	19.42	32.20
4	*2437.00	114.36 PK			1.00 V	87	81.97	32.39
5	*2437.00	104.12 AV			1.00 V	87	71.73	32.39
6	2489.00	64.79 PK	74.00	-9.21	1.00 V	87	32.21	32.58
7	2489.00	51.23 AV	54.00	-2.77	1.00 V	87	18.65	32.58
8	3704.80	65.06 PK	82.22	-17.16	1.10 V	153	29.52	35.54
9	4874.00	51.68 PK	74.00	-22.32	1.00 V	31	13.27	38.41
10	4874.00	38.16 AV	54.00	-15.84	1.00 V	31	-0.25	38.41
11	7311.00	61.09 PK	74.00	-12.91	1.51 V	357	16.45	44.64
12	7311.00	46.84 AV	54.00	-7.16	1.51 V	357	2.20	44.64

- REMARKS:**
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
  2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* “: Fundamental frequency.
  6. The limit value of point 8 is defined as per 24.238.





A D T

## BELOW 1GHz DATA :

## 802.11g OFDM MODULATION + WCDMA850

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	CH 6 + CH 4182	FREQUENCY RANGE	Below 1000MHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	25deg. C, 63%RH 1010 hPa	TESTED BY	Kevin Liang
TEST MODE	A		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 10 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	43.51	31.60 QP	40.00	-8.40	1.00 H	160	19.13	12.47
2	105.73	32.36 QP	43.50	-11.14	1.50 H	286	22.34	10.02
3	267.10	33.36 QP	46.00	-12.64	1.25 H	253	20.25	13.11
4	533.47	39.11 QP	46.00	-6.89	1.50 H	349	18.85	20.26
5	640.41	40.51 QP	46.00	-5.49	1.50 H	358	18.28	22.24
6	794.01	42.07 QP	46.00	-3.93	1.00 H	172	16.92	25.16
7	*836.40	114.10 PK			1.00 H	1	88.55	25.55

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	41.57	37.82 QP	40.00	-2.18	1.00 V	67	25.34	12.48
2	99.89	35.02 QP	43.50	-8.48	1.00 V	211	25.69	9.33
3	426.53	32.40 QP	46.00	-13.60	1.50 V	253	15.46	16.94
4	533.47	41.30 QP	46.00	-4.70	1.00 V	337	21.04	20.26
5	640.41	41.80 QP	46.00	-4.20	1.00 V	10	19.56	22.24
6	794.01	42.86 QP	46.00	-3.14	1.25 V	355	17.71	25.16
7	*836.40	118.99 PK			1.01 V	290	93.44	25.55

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* “: Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	CH 6 + CH 4132	FREQUENCY RANGE	Below 1000MHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	25deg. C, 63%RH 1010 hPa	TESTED BY	Kevin Liang
TEST MODE	B		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	105.73	32.89 QP	43.50	-10.61	1.50 H	268	22.87	10.02
2	267.10	32.51 QP	46.00	-13.49	1.50 H	283	19.40	13.11
3	426.53	31.33 QP	46.00	-14.67	1.00 H	139	14.39	16.94
4	533.47	39.01 QP	46.00	-6.99	1.50 H	346	18.75	20.26
5	640.41	40.47 QP	46.00	-5.53	1.25 H	148	18.23	22.24
6	780.40	35.49 QP	46.00	-10.51	1.00 H	157	10.71	24.78
7	826.40	112.55 PK			1.00 H	0	87.07	25.48
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	33.79	38.11 QP	40.00	-1.89	1.00 V	10	25.95	12.16
2	99.89	34.82 QP	43.50	-8.68	1.00 V	235	25.49	9.33
3	426.53	33.13 QP	46.00	-12.87	1.25 V	250	16.19	16.94
4	533.47	41.34 QP	46.00	-4.66	1.00 V	334	21.08	20.26
5	640.41	42.10 QP	46.00	-3.90	1.00 V	10	19.86	22.24
6	780.40	36.41 QP	46.00	-9.59	1.50 V	4	11.63	24.78
7	826.40	118.23 PK			1.21 V	244	92.75	25.48

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. " \* ": Fundamental frequency.



A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	CH 6 + CH 4182	FREQUENCY RANGE	Below 1000MHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	25deg. C, 63%RH 1010 hPa	TESTED BY	Kevin Liang
TEST MODE	C		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	45.45	33.80 QP	40.00	-6.20	1.00 H	169	21.21	12.58
2	105.73	31.46 QP	43.50	-12.04	1.25 H	250	21.44	10.02
3	249.60	31.78 QP	46.00	-14.22	1.00 H	286	18.96	12.81
4	533.47	38.88 QP	46.00	-7.12	1.25 H	334	18.62	20.26
5	640.41	40.44 QP	46.00	-5.56	1.50 H	10	18.21	22.24
6	795.95	42.43 QP	46.00	-3.57	1.00 H	172	17.22	25.21
7	836.40	115.50 PK			1.00 H	13	89.95	25.55
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	33.79	37.81 QP	40.00	-2.19	1.25 V	46	25.65	12.16
2	99.89	34.76 QP	43.50	-8.74	1.00 V	205	25.43	9.33
3	426.53	31.99 QP	46.00	-14.01	1.00 V	256	15.05	16.94
4	533.47	41.16 QP	46.00	-4.84	1.00 V	328	20.90	20.26
5	640.41	41.98 QP	46.00	-4.02	1.50 V	313	19.74	22.24
6	792.06	43.00 QP	46.00	-3.00	1.25 V	358	17.90	25.10
7	836.40	120.26 PK			1.24 V	354	94.71	25.55

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. " \* ": Fundamental frequency.



A D T

### 802.11g OFDM MODULATION + WCDMA1900

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	CH 6 + CH 9262	FREQUENCY RANGE	Below 1000MHz
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	25deg. C, 63%RH 1010 hPa	TESTED BY	Kevin Liang
TEST MODE	A		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	105.73	31.59 QP	43.50	-11.91	1.25 H	265	21.57	10.02
2	269.05	32.45 QP	46.00	-13.55	1.00 H	238	19.31	13.14
3	426.53	31.72 QP	46.00	-14.28	1.00 H	142	14.78	16.94
4	533.47	40.05 QP	46.00	-5.95	1.50 H	340	19.79	20.26
5	640.41	40.11 QP	46.00	-5.89	1.25 H	154	17.87	22.24
6	854.28	42.92 QP	46.00	-3.08	1.00 H	10	17.25	25.67
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	33.79	38.57 QP	40.00	-1.43	1.25 V	331	26.41	12.16
2	97.95	35.12 QP	43.50	-8.38	1.00 V	274	25.82	9.31
3	426.53	33.98 QP	46.00	-12.02	1.25 V	244	17.04	16.94
4	533.47	40.68 QP	46.00	-5.32	1.00 V	223	20.42	20.26
5	640.41	42.49 QP	46.00	-3.51	1.50 V	319	20.26	22.24
6	854.28	37.69 QP	46.00	-8.31	1.25 V	307	12.02	25.67

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.

## 4.2 CONDUCTED EMISSION MEASUREMENT

### 4.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
  2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
  3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

### 4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESCS30	100288	Sep. 22, 2008	Sep. 21, 2009
RF signal cable Woken	5D-FB	Cable-HYCO2-01	Dec. 31, 2008	Dec. 30, 2009
LISN ROHDE & SCHWARZ	ESH2-Z5	100100	Dec. 29, 2008	Dec. 28, 2009
LISN ROHDE & SCHWARZ	ESH3-Z5	100311	Jul. 30, 2008	Jul. 29, 2009
Software ADT	ADT_Cond_ V7.3.7	NA	NA	NA

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
  2. The test was performed in HwaYa Shielded Room 2.
  3. The VCCI Site Registration No. is C-2047.

#### 4.2.3 TEST PROCEDURES


- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

**NOTE:** All modes of operation were investigated and the worst-case emissions are reported.

#### 4.2.4 DEVIATION FROM TEST STANDARD

No deviation.

## 4.2.5 TEST SETUP



- Note:**
1. Support units were connected to second LISN.
  2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

## 4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6.


### 4.2.7 TEST RESULTS

**CONDUCTED WORST-CASE DATA: 802.11g OFDM MODULATION + WCDMA850**

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	CH 6 + CH 4182	PHASE	Line 1
INPUT POWER (SYSTEM)	120Vac, 60Hz	6dB BANDWIDTH	9kHz
ENVIRONMENTAL CONDITIONS	27deg. C, 66%RH, 1013hPa	TESTED BY	Dean Wang
TEST MODE	A		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.187	0.13	44.15	-	44.28	-	64.19	54.19	-19.91	-
2	0.369	0.14	51.44	42.89	51.58	43.03	58.53	48.53	-6.95	-5.50
3	0.474	0.14	45.92	-	46.06	-	56.44	46.44	-10.38	-
4	0.767	0.16	40.96	-	41.12	-	56.00	46.00	-14.88	-
5	0.999	0.17	41.70	-	41.87	-	56.00	46.00	-14.13	-
6	6.500	0.34	36.14	-	36.48	-	60.00	50.00	-23.52	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.








A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	CH 6 + CH 4182	PHASE	Line 2
INPUT POWER (SYSTEM)	120Vac, 60Hz	6dB BANDWIDTH	9kHz
ENVIRONMENTAL CONDITIONS	27deg. C, 66%RH, 1013hPa	TESTED BY	Dean Wang
TEST MODE	A		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.186	0.13	43.75	-	43.88	-	64.23	54.23	-20.35	-
2	0.364	0.15	48.45	-	48.60	-	58.63	48.63	-10.04	-
3	0.470	0.15	42.15	-	42.30	-	56.51	46.51	-14.21	-
4	0.713	0.16	38.98	-	39.14	-	56.00	46.00	-16.86	-
5	0.986	0.17	38.11	-	38.28	-	56.00	46.00	-17.72	-
6	17.695	0.75	38.56	-	39.31	-	60.00	50.00	-20.69	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.






A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	CH 6 + CH 4132	PHASE	Line 1
INPUT POWER (SYSTEM)	120Vac, 60Hz	6dB BANDWIDTH	9kHz
ENVIRONMENTAL CONDITIONS	27deg. C, 66%RH, 1013hPa	TESTED BY	Dean Wang
TEST MODE	B		

No	Freq. [MHz]	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.180	0.13	45.60	-	45.73	-	64.49	54.49	-18.76	-
2	0.361	0.14	50.60	41.48	50.74	41.62	58.72	48.72	-7.98	-7.10
3	0.395	0.14	44.45	-	44.59	-	57.96	47.96	-13.37	-
4	0.486	0.14	43.60	-	43.74	-	56.24	46.24	-12.49	-
5	0.783	0.16	41.57	-	41.73	-	56.00	46.00	-14.27	-
6	18.246	0.63	38.99	-	39.62	-	60.00	50.00	-20.38	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.






A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	CH 6 + CH 4132	PHASE	Line 2
INPUT POWER (SYSTEM)	120Vac, 60Hz	6dB BANDWIDTH	9kHz
ENVIRONMENTAL CONDITIONS	27deg. C, 66%RH, 1013hPa	TESTED BY	Dean Wang
TEST MODE	B		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.182	0.13	45.00	-	45.13	-	64.40	54.40	-19.27	-
2	0.362	0.15	47.88	-	48.03	-	58.68	48.68	-10.65	-
3	0.392	0.15	42.52	-	42.67	-	58.02	48.02	-15.35	-
4	0.481	0.15	41.54	-	41.69	-	56.33	46.33	-14.63	-
5	0.783	0.16	38.65	-	38.81	-	56.00	46.00	-17.19	-
6	17.698	0.75	38.13	-	38.88	-	60.00	50.00	-21.12	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.






A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	CH 6 + CH 4132	PHASE	Line 1
INPUT POWER (SYSTEM)	120Vac, 60Hz	6dB BANDWIDTH	9kHz
ENVIRONMENTAL CONDITIONS	27deg. C, 66%RH, 1013hPa	TESTED BY	Dean Wang
TEST MODE	C		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.186	0.13	44.82	-	44.95	-	64.19	54.19	-19.24	-
2	<b>0.369</b>	<b>0.14</b>	<b>51.54</b>	<b>43.11</b>	<b>51.68</b>	<b>43.25</b>	<b>58.53</b>	<b>48.53</b>	<b>-6.85</b>	<b>-5.28</b>
3	0.474	0.14	45.94	-	46.08	-	56.44	46.44	-10.35	-
4	0.767	0.16	42.19	-	42.35	-	56.00	46.00	-13.65	-
5	0.994	0.17	41.58	-	41.75	-	56.00	46.00	-14.25	-
6	6.840	0.35	35.87	-	36.22	-	60.00	50.00	-23.78	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.






A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	CH 6 + CH 4132	PHASE	Line 2
INPUT POWER (SYSTEM)	120Vac, 60Hz	6dB BANDWIDTH	9kHz
ENVIRONMENTAL CONDITIONS	27deg. C, 66%RH, 1013hPa	TESTED BY	Dean Wang
TEST MODE	C		

No	Freq. [MHz]	Corr. Factor [dB]	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.185	0.13	44.37	-	44.50	-	64.25	54.25	-19.75	-
2	0.330	0.14	44.89	-	45.03	-	59.46	49.46	-14.43	-
3	0.370	0.15	48.48	40.51	48.63	40.66	58.50	48.50	-9.87	-7.84
4	0.470	0.15	42.17	-	42.32	-	56.51	46.51	-14.19	-
5	0.764	0.16	39.19	-	39.35	-	56.00	46.00	-16.65	-
6	17.695	0.75	38.40	-	39.15	-	60.00	50.00	-20.85	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.






A D T

802.11g OFDM MODULATION + WCDMA1900

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	CH 6 + CH 4132	PHASE	Line 1
INPUT POWER (SYSTEM)	120Vac, 60Hz	6dB BANDWIDTH	9kHz
ENVIRONMENTAL CONDITIONS	27deg. C, 66%RH, 1013hPa	TESTED BY	Dean Wang
TEST MODE	A		

No	Freq.	Corr. Factor	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]	[dB (uV)]	[dB (uV)]	[dB (uV)]	(dB)	(dB)		
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.187	0.13	43.71	-	43.84	-	64.19	54.19	-20.35	-
2	0.369	0.14	51.48	43.03	51.62	43.17	58.53	48.53	-6.91	-5.36
3	0.473	0.14	45.86	-	46.00	-	56.46	46.46	-10.46	-
4	0.760	0.16	42.69	-	42.85	-	56.00	46.00	-13.15	-
5	0.990	0.17	41.50	-	41.67	-	56.00	46.00	-14.33	-
6	17.697	0.62	40.29	-	40.91	-	60.00	50.00	-19.09	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.






A D T

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	CH 6 + CH 4132	PHASE	Line 2
INPUT POWER (SYSTEM)	120Vac, 60Hz	6dB BANDWIDTH	9kHz
ENVIRONMENTAL CONDITIONS	27deg. C, 66%RH, 1013hPa	TESTED BY	Dean Wang
TEST MODE	A		

No	Freq. [MHz]	Corr. Factor	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.186	0.13	43.45	-	43.58	-	64.20	54.20	-20.62	-
2	0.334	0.14	44.73	-	44.87	-	59.36	49.36	-14.49	-
3	0.369	0.15	48.41	40.34	48.56	40.49	58.53	48.53	-9.97	-8.04
4	0.473	0.15	42.63	-	42.78	-	56.46	46.46	-13.68	-
5	0.716	0.16	38.12	-	38.28	-	56.00	46.00	-17.72	-
6	17.698	0.75	38.26	-	39.01	-	60.00	50.00	-20.99	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.





A D T

## 5. PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).





## 6. INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

<b>USA</b>	FCC, NVLAP
<b>Germany</b>	TUV Rheinland
<b>Japan</b>	VCCI
<b>Norway</b>	NEMKO
<b>Canada</b>	INDUSTRY CANADA , CSA
<b>R.O.C.</b>	TAF, BSMI, NCC
<b>Netherlands</b>	Telefication
<b>Singapore</b>	GOST-ASIA(MOU)
<b>Russia</b>	CERTIS(MOU)

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site:

[www.adt.com.tw/index.5/phtml](http://www.adt.com.tw/index.5/phtml). If you have any comments, please feel free to contact us at the following:

**Linko EMC/RF Lab:**

Tel: 886-2-26052180

Fax: 886-2-26051924

**Hsin Chu EMC/RF Lab:**

Tel: 886-3-5935343

Fax: 886-3-5935342

**Hwa Ya EMC/RF/Safety Telecom Lab:**

Tel: 886-3-3183232

Fax: 886-3-3185050

**Web Site:** [www.adt.com.tw](http://www.adt.com.tw)

The address and road map of all our labs can be found in our web site also.



A D T

## **7. APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB**

No any modifications are made to the EUT by the lab during the test.

**---END---**