



# RF EXPOSURE REPORT

**REPORT NO.:** SA981211L16

**MODEL NO.:** ENUWI-XAN3

**ACCORDING:** FCC Guidelines for Human Exposure  
IEEE C95.1

**APPLICANT:** Senao Networks Inc.

**ADDRESS:** 3F, No. 529, Chung Cheng Rd., Hsintien, Taipei,  
Taiwan, R.O.C.

**ISSUED BY:** Bureau Veritas Consumer Products Services  
(H.K.) Ltd., Taoyuan Branch

**LAB ADDRESS:** No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou  
Hsiang, Taipei Hsien 244, Taiwan, R.O.C.

**TEST LOCATION:** No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei  
Shan Hsiang, Taoyuan Hsien 333, Taiwan,  
R.O.C.

No evaluation required if power is below this threshold:

F(GHz)		mW
Low	2.412	24.6
High	2.462	

Maximum measured transmitter power:

Pout (dBm)	Pout (mW)	
Conducted Power	10.6	11.6
EIRP Power	12.8	19.0

**\*Note:** The antenna is Dipole antenna with 2.15dBi gain

Threshold for no SAR evaluation is 24.6mW  
Transmitter power is 19.0mW

Conclusion: No SAR evaluation required since Transmitter Pout is below FCC threshold