



Test report No.: 2380601R-RFUSV01S-A

# TEST REPORT

Product Name	Wireless Access Point
Trademark	Senao
Model and /or type reference	WAP2301A
FCC ID	U2M-WAP2301A
Applicant's name / address	Senao Networks, Inc. 3F, No. 529, Chung Cheng Rd., Hsintien, Taipei, Taiwan
Manufacturer's name	Senao Networks, Inc.
Test method requested, standard	FCC CFR Title 47 Part 15 Subpart C ANSI C63.4: 2014, ANSI C63.10: 2013
Verdict Summary	IN COMPLIANCE
Documented By (Senior Project Specialist / Genie Chang)	<i>Genie Chang</i>
Tested By (Senior Engineer / Ivan Chuang)	<i>Ivan Chuang</i>
Approved By (Senior Engineer / Jack Hsu)	<i>Jack Hsu</i>
Date of Receipt	2023/08/18
Date of Issue	2023/10/24
Report Version	V1.0

---

**INDEX**


---

Page

<b>1. General Information.....</b>	<b>6</b>
1.1. EUT Description.....	6
1.2. Tested System Details.....	8
1.3. Configuration of Tested System .....	8
1.4. EUT Exercise Software .....	8
1.5. Test Facility .....	9
1.6. List of Test Item and Equipment .....	10
1.7. Uncertainty .....	11
<b>2. Conducted Emission .....</b>	<b>12</b>
2.1. Test Setup .....	12
2.2. Limits.....	12
2.3. Test Procedure .....	12
2.4. Test Result of Conducted Emission.....	13
<b>3. Maximum Power Output .....</b>	<b>14</b>
3.1. Test Setup .....	14
3.2. Limits.....	14
3.3. Test Procedure .....	14
3.4. Test Result of Maximum Power Output .....	15
<b>4. Radiated Emission .....</b>	<b>23</b>
4.1. Test Setup .....	23
4.2. Limits.....	24
4.3. Test Procedure .....	25
4.4. Test Result of Radiated Emission.....	27
<b>5. RF Antenna Conducted Test .....</b>	<b>42</b>
5.1. Test Setup .....	42
5.2. Limits.....	42
5.3. Test Procedure .....	42
5.4. Test Result of RF antenna conducted test.....	43
<b>6. Band Edge .....</b>	<b>51</b>
6.1. Test Setup .....	51
6.2. Limits.....	52
6.3. Test Procedure .....	52

---

6.4.	Test Result of Band Edge .....	54
<b>7.</b>	<b>6dB Bandwidth .....</b>	<b>86</b>
7.1.	Test Setup .....	86
7.2.	Limits.....	86
7.3.	Test Procedure .....	86
7.4.	Test Result of 6dB Bandwidth.....	87
<b>8.</b>	<b>Power Density.....</b>	<b>95</b>
8.1.	Test Setup .....	95
8.2.	Limits.....	95
8.3.	Test Procedure .....	95
8.4.	Test Result of Power Density .....	96
<b>9.</b>	<b>Duty Cycle .....</b>	<b>104</b>
9.1.	Test Setup .....	104
9.2.	Test Procedure .....	104
9.3.	Test Result of Duty Cycle.....	105

Appendix 1: EUT Test Photographs

Appendix 2: Product Photos-Please refer to the file: 2380601R-Product Photos

---

## Competences and Guarantees

---

DEKRA is a testing laboratory competent to carry out the tests described in this report.

In order to assure the traceability to other national and international laboratories, DEKRA has a calibration and maintenance program for its measurement equipment.

DEKRA guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated in the report and it is based on the knowledge and technical facilities available at DEKRA at the time of performance of the test.

DEKRA is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

**IMPORTANT:** No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA.

## General conditions

---

1. The test results relate only to the samples tested.
2. The test results shown in the test report are traceable to the national/international standard through the calibration report of the equipment and evaluated measurement uncertainty herein.
3. This report must not be used to claim product endorsement by TAF or any agency of the government.
4. The test report shall not be reproduced without the written approval of DEKRA Testing and Certification Co., Ltd.
5. Measurement uncertainties evaluated for each testing system and associated connections are given here to provide the system information for reference. Compliance determinations do not take into account measurement uncertainties for each testing system, but are based on the results of the compliance measurement.

---

## Revision History

---

Report No.	Version	Description	Issued Date
2380601R-RFUSV01S-A	V1.0	Initial issue of report.	2023/10/24

## 1. General Information

### 1.1. EUT Description

Product Name	Wireless Access Point
Trademark	Senao
Model and /or type reference	WAP2301A
EUT Rated Voltage	AC 100-240V, 50-60Hz
EUT Test Voltage	AC 120V/60Hz
Frequency Range	Radio-1: 802.11b/g/n/ax-20: 2412-2462MHz 802.11n/ax-40: 2422-2452MHz Radio-3: 802.11b/g/n/ac-20: 2412-2462MHz 802.11n/ac-40: 2422-2452MHz
Number of Channels	802.11b/g/n/ac/ax-20MHz: 11CH 802.11n/ac/ax-40MHz: 7CH
Data Rate	Radio-1: 802.11b: 1-11Mbps 802.11g: 6-54Mbps 802.11n: up to 300Mbps 802.11ax: up to 573.5Mbps Radio-3: 802.11b: 1-11Mbps 802.11g: 6-54Mbps 802.11n: up to 150Mbps 802.11ac: up to 200Mbps
Channel separation	802.11b/g/n/ac/ax: 5 MHz
Type of Modulation	802.11b: DSSS (DBPSK, DQPSK, CCK) 802.11g/n/ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM) 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)
Channel Control	Auto
Power Adapter	MFR: SENAO, M/N: EAA65A-54 Input: AC 100-240V~1.8A 50-60Hz Output: 54V=1.2A 64.8W Cable out: Non-shielded, 1.4 m with one ferrite core bonded. Power cord: Non-shielded, 1.7m

#### Antenna List

No.	Manufacturer	Part No.	Antenna Type	Peak Gain
1	SENAO (Radio-1)	7016A307200u -DL1	PIFA	3.39 dBi for 2400 MHz
2	SENAO (Radio-1)	7016A307200u -DL2	PIFA	2.99 dBi for 2400 MHz
3	SENAO (Radio-3)	7016A307200u -SCAN	Monopole	3.94 dBi for 2400 MHz

#### Note:

1. The antenna of EUT is conforming to FCC 15.203.
2. The antenna gain as by the manufacturer provided.
3. Each antenna has been evaluated and only the worst case (higher gain antenna) is presented in the report.

**For Power CDD Directional gain (Radio-1)**

2400MHz: Power Directional gain = 3.99 dBi  
 (Directional gain =  $G_{ANT\ MAX} + \text{Array Gain}$ , Array Gain = 0 dB for  $N_{ANT} \leq 4$ )

**For PSD CDD Directional gain (Radio-1)**

2400MHz: PSD Directional gain = 6.2 dBi  
 (Directional gain =  $10 \log[(10^{G1/20} + 10^{G2/20})^2 / N_{ANT}]$  dBi)

**802.11b/g/n/ac/ax-20 MHz Center Frequency of Each Channel:**

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
01	2412	02	2417	03	2422	04	2427
05	2432	06	2437	07	2442	08	2447
09	2452	10	2457	11	2462	--	--

**802.11n/ac/ax-40 MHz Center Frequency of Each Channel:**

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
03	2422	04	2427	05	2432	06	2437
07	2442	08	2447	09	2452	--	--

**Note:**

- The EUT is a Wireless Access Point with a built-in WLAN transceiver, this report for 2.4GHz WLAN.
- Regarding to the operation frequency, the lowest, middle and highest frequency are selected to perform the test. The other channels are for reference only.
- Lowest data rates are tested in each mode. Only worst case is shown in the report. (802.11b is 1Mbps, 802.11g is 6Mbps, 802.11ac/ax-20MHz/40MHz is HT0/MCS0)
- The modulation and bandwidth are similar for 802.11n mode and 802.11ac/ax mode, therefore investigated worst case (802.11ac/ax) to representative mode.
- The product includes three module cards with the following specifications:
 

Module	Radio-1	Radio-2	Radio-3
WLAN 2.4G	802.11 b/g/n/ax 2T2R		802.11 b/g/n/ac 1T1R
WLAN 5G		802.11 a/n/ac/ax 2T2R	802.11 a/n/ac 1T1R
- The spectrum plot against conducted item only shows the worst case.
- This device does not support partial RU function.
- DEKRA has evaluated each test mode. Only the worst case is shown in the report.
- These tests are conducted on a sample for the purpose of demonstrating compliance of 802.11b/g/n/ac/ax transmitter with Part 15 Subpart C Paragraph 15.247 of spread spectrum devices.

Test Mode	Mode 1	
		Transmit (802.11b) Radio-1
		Transmit (802.11g) Radio-1
		Transmit (802.11ax-20 MHz) Radio-1
		Transmit (802.11ax-40 MHz) Radio-1
		Transmit (802.11b) Radio-3
		Transmit (802.11g) Radio-3
		Transmit (802.11ac-20 MHz) Radio-3
		Transmit (802.11ac-40 MHz) Radio-3


1.2. Tested System Details

The types for all equipment, plus descriptions of all cables used in the tested system (including inserted cards) are:

Product	Manufacturer	Model No.	Serial No.	Power Cord
1 Power Adapter	SENAO	EAA65A-54	N/A	N/A
2 LAN Hub	TP-LINK	TL-SG108	2161597000471	N/A
3 Notebook PC	DELL	P62G	416FJC2	N/A

Cable Type	Cable Description
A Power Cable	Non-shielded, 1.7m with one ferrite core bonded.
B LAN Cable	Non-shielded, 2m, Six PCS.

1.3. Configuration of Tested System



1.4. EUT Exercise Software

1.	Setup the EUT as shown in Section 1.3.
2.	Execute software “QSPR Version v5.0-00202” on the Notebook PC.
3.	Configure the test mode, the test channel, and the data rate.
4.	Press “OK” to start the continuous transmit.
5.	Verify that the EUT works properly.



## 1.5. Test Facility

Ambient conditions in the laboratory:

Performed Item	Items	Required	Actual
Conducted Emission	Temperature (°C)	10~40 °C	23.5 °C
	Humidity (%RH)	10~90 %	56.0 %
Radiated Emission	Temperature (°C)	10~40 °C	22.5 °C
	Humidity (%RH)	10~90 %	53.0 %
Conductive	Temperature (°C)	10~40 °C	22.0 °C
	Humidity (%RH)	10~90 %	55.0 %

USA	FCC Registration Number: TW0033
Canada	CAB Identifier Number: TW3023 / Company Number: 26930

Site Description	Accredited by TAF
	Accredited Number: 3023

Test Laboratory	DEKRA Testing and Certification Co., Ltd.
	Linkou Laboratory
Address	No.5-22, Ruishukeng Linkou District, New Taipei City, 24451, Taiwan, R.O.C.
Performed Location	No. 26, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan, R.O.C.
Phone Number	+886-3-275-7255
Fax Number	+886-3-327-8031

## 1.6. List of Test Item and Equipment

**For Conduction Measurements / HY-SR01**

	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
V	EMI Test Receiver	R&S	ESR7	101601	2023/06/20	2024/06/19
V	Two-Line V-Network	R&S	ENV216	101306	2023/03/16	2024/03/15
V	Two-Line V-Network	R&S	ENV216	101307	2023/08/17	2024/08/16
V	Coaxial Cable	SUHNER	RG400 BNC	RF001	2023/01/10	2024/01/09

Note:

1. All equipments are calibrated every one year.
2. The test instruments marked with “V” are used to measure the final test results.
3. Test Software Version: e3 230303 dekra V9.

**For Conducted Measurements / HY-SR02**

	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
V	Spectrum Analyzer	R&S	FSV30	103466	2022/12/22	2023/12/21
V	Peak Power Analyzer	KEYSIGHT	8990B	MY51000539	2023/05/15	2024/05/14
V	Power Sensor	KEYSIGHT	N1923A	MY59240002	2023/05/18	2024/05/17
V	Power Sensor	KEYSIGHT	N1923A	MY59240003	2023/05/18	2024/05/17

Note:

1. All equipments are calibrated every one year.
2. The test instruments marked with “V” are used to measure the final test results.
3. Test Software Version: RF Conducted Test Tools R3 V3.0.1.14.

**For Radiated Measurements / HY-CB03**

	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
V	Loop Antenna	AMETEK	HLA6121	49611	2023/02/21	2024/02/20
V	Bi-Log Antenna	SCHWARZBECK	VULB9168	9168-0675	2023/08/09	2025/08/08
V	Horn Antenna	Com-Power	AH-840	101100	2021/10/04	2023/10/03
V	Horn Antenna	RF SPIN	DRH18-E	210507A18ES	2023/05/11	2024/05/10
V	Pre-Amplifier	SGH	0301	20211007-11	2023/01/10	2024/01/09
V	Pre-Amplifier	SGH	PRAMP118	20200701	2023/01/10	2024/01/09
V	Pre-Amplifier	EMCI	EMC05820SE	980310	2023/01/10	2024/01/09
V	Pre-Amplifier	EMCI	EMC184045SE	980369	2023/01/10	2024/01/09
	Coaxial Cable	EMCI	EMC102-KM-KM-600	1160314		
	Coaxial Cable	EMCI	EMC102-KM-KM-700	170242		
V	Filter	MICRO TRONICS	BRM50702	G269	2023/01/05	2024/01/04
	Filter	MICRO TRONICS	BRM50716	G196	2023/01/05	2024/01/04
V	EMI Test Receiver	R&S	ESR3	102793	2022/12/05	2023/12/04
V	Spectrum Analyzer	R&S	FSV3044	101113	2023/02/04	2024/02/03
V	Coaxial Cable	SGH	SGH18	2021005-1	2023/01/10	2024/01/09
	Coaxial Cable	SGH	SGH18	202108-4		
	Coaxial Cable	SGH	HA800	GD20110223-1		
	Coaxial Cable	SGH	HA800	GD20110222-3		

Note:

1. Bi-Log Antenna and Horn Antenna(AH-840) is calibrated every two years, the other equipments are calibrated every one year.
2. The test instruments marked with “V” are used to measure the final test results.
3. Test Software Version: e3 230303 dekra V9.

## 1.7. Uncertainty

Uncertainties have been calculated according to the DEKRA internal document.


The reported expanded uncertainties are based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95%.

Measurement uncertainties evaluated for each testing system and associated connections are given here to provide the system information for reference. Compliance determinations do not take into account measurement uncertainties for each testing system, but are based on the results of the compliance measurement.

Test item	Uncertainty
Conducted Emission	$\pm 3.50$ dB
Peak Power Output	Spectrum Analyzer: $\pm 2.14$ dB Power Meter: $\pm 1.05$ dB
Radiated Emission	9 kHz~30 MHz: $\pm 3.88$ dB 30 MHz~1 GHz: $\pm 4.42$ dB 1 GHz~18 GHz: $\pm 4.28$ dB 18 GHz~40 GHz: $\pm 3.90$ dB
RF Antenna Conducted Test	$\pm 2.14$ dB
Band Edge	9 kHz~30 MHz: $\pm 3.88$ dB 30 MHz~1 GHz: $\pm 4.42$ dB 1 GHz~18 GHz: $\pm 4.28$ dB 18 GHz~40 GHz: $\pm 3.90$ dB
6dB Bandwidth	$\pm 1580.61$ Hz
Power Density	$\pm 2.14$ dB
Duty Cycle	$\pm 0.53$ %

## 2. Conducted Emission

### 2.1. Test Setup



### 2.2. Limits

FCC Part 15 Subpart C Paragraph 15.207 (dB $\mu$ V) Limit		
Frequency MHz	Limits	
	QP	AVG
0.15 - 0.50	66-56	56-46
0.50 - 5.0	56	46
5.0 - 30	60	50

### 2.3. Test Procedure



The EUT and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50 ohm / 50  $\mu$ H coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50 ohm /50  $\mu$ H coupling impedance with 50 ohm termination. (Please refers to the block diagram of the test setup and photographs.)

Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2014 on conducted measurement.



Conducted emissions were invested over the frequency range from 0.15 MHz to 30 MHz using a receiver bandwidth of 9 kHz.

2.4. Test Result of Conducted Emission

Radio 1




Radio 3



### 3. Maximum Power Output

#### 3.1. Test Setup



#### 3.2. Limits

The maximum peak power shall be less 1 Watt.

#### 3.3. Test Procedure

The EUT was tested according to C63.10:2013 for compliance to FCC 47CFR 15.247 requirements. The maximum peak conducted output power using C63.10:2013 Section 11.9.1.3 PKPM1 Peak power meter method. The maximum average conducted output power using C63.10:2013 Section 11.9.2.3 Measurement using a power meter (PM). (Measurement using a gated RF average-reading power meter). The maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

##### **For CDD mode:**

2400MHz: Directional gain = 3.99 dBi, Limit= 30dBm

(Directional gain = GANT MAX + Array Gain, Array Gain = 0 dB for NANT ≤ 4)

## 3.4. Test Result of Maximum Power Output

Product : Wireless Access Point  
 Test Item : Maximum Power Output Data  
 Test Mode : Transmit (802.11b)\_Radio-1  
 Test Date : 2023/09/13

Channel No.	Frequency (MHz)	Data Rate (Mbps)	Chain A Average Power (dBm)	Chain B Average Power (dBm)	Chain A+B Average Power (dBm)	Limit (dBm)	Result
01	2412	1	20.91	21.03	23.98	<30	Pass
06	2437	1	21.63	21.61	24.63	<30	Pass
11	2462	1	20.66	20.45	23.57	<30	Pass

Note: Average Power Output Value (dBm) =  $10 \cdot \text{LOG} (\text{Chain A (mW)} + \text{Chain B (mW)})$

Product : Wireless Access Point  
Test Item : Maximum Power Output Data  
Test Mode : Transmit (802.11g)\_Radio-1  
Test Date : 2023/09/13

Channel No.	Frequency (MHz)	Data Rate (Mbps)	Chain A Average Power (dBm)	Chain B Average Power (dBm)	Chain A+B Average Power (dBm)	Limit (dBm)	Result
01	2412	6	17.71	17.62	20.68	<30	Pass
06	2437	6	21.82	21.64	24.74	<30	Pass
11	2462	6	17.98	17.61	20.81	<30	Pass

Note: Average Power Output Value (dBm) =  $10 \cdot \text{LOG} (\text{Chain A (mW)} + \text{Chain B (mW)})$



Product : Wireless Access Point  
Test Item : Maximum Power Output Data  
Test Mode : Transmit (802.11ax-20 MHz)\_Radio-1  
Test Date : 2023/09/13

Channel No.	Frequency (MHz)	Data Rate	Chain A Average Power (dBm)	Chain B Average Power (dBm)	Chain A+B Average Power (dBm)	Limit (dBm)	Result
01	2412	MCS0	15.81	15.92	18.88	<30	Pass
06	2437	MCS0	21.84	21.58	24.72	<30	Pass
11	2462	MCS0	16.97	16.78	19.89	<30	Pass

Note: Average Power Output Value (dBm) =  $10 \cdot \text{LOG} (\text{Chain A (mW)} + \text{Chain B (mW)})$

Product : Wireless Access Point  
Test Item : Maximum Power Output Data  
Test Mode : Transmit (802.11ax-40 MHz)\_Radio-1  
Test Date : 2023/09/13

Channel No.	Frequency (MHz)	Data Rate	Chain A Average Power (dBm)	Chain B Average Power (dBm)	Chain A+B Average Power (dBm)	Limit (dBm)	Result
03	2422	MCS0	12.97	12.75	15.87	<30	Pass
06	2437	MCS0	16.01	15.89	18.96	<30	Pass
09	2452	MCS0	16.05	15.86	18.97	<30	Pass

Note: Average Power Output Value (dBm) =  $10 \cdot \text{LOG} (\text{Chain A (mW)} + \text{Chain B (mW)})$

Product : Wireless Access Point  
Test Item : Maximum Power Output Data  
Test Mode : Transmit (802.11b)\_Radio-3  
Test Date : 2023/09/13

Channel No.	Frequency (MHz)	Data Rate (Mbps)	Average Power (dBm)	Limit (dBm)	Result
01	2412	1	16.91	<30	Pass
06	2437	1	16.93	<30	Pass
11	2462	1	16.94	<30	Pass

Product : Wireless Access Point  
Test Item : Maximum Power Output Data  
Test Mode : Transmit (802.11g)\_Radio-3  
Test Date : 2023/09/13

Channel No.	Frequency (MHz)	Data Rate (Mbps)	Average Power (dBm)	Limit (dBm)	Result
01	2412	6	16.12	<30	Pass
06	2437	6	16.59	<30	Pass
11	2462	6	14.56	<30	Pass

Product : Wireless Access Point  
Test Item : Maximum Power Output Data  
Test Mode : Transmit (802.11ac-20 MHz)\_Radio-3  
Test Date : 2023/09/13

Channel No.	Frequency (MHz)	Data Rate (Mbps)	Average Power (dBm)	Limit (dBm)	Result
01	2412	HT0	14.91	<30	Pass
06	2437	HT0	16.88	<30	Pass
11	2462	HT0	13.34	<30	Pass


Product : Wireless Access Point  
Test Item : Maximum Power Output Data  
Test Mode : Transmit (802.11ac-40 MHz)\_Radio-3  
Test Date : 2023/09/13

Channel No.	Frequency (MHz)	Data Rate (Mbps)	Average Power (dBm)	Limit (dBm)	Result
03	2422	HT0	12.41	<30	Pass
06	2437	HT0	16.35	<30	Pass
09	2452	HT0	10.45	<30	Pass


## 4. Radiated Emission

### 4.1. Test Setup


#### Radiated Emission Under 30 MHz



#### Radiated Emission Below 1 GHz



#### Radiated Emission Above 1 GHz



## 4.2. Limits

➤ **General Radiated Emission Limits**

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 20dB below the level of the fundamental or to the general radiated emission limits in paragraph 15.209, whichever is the lesser attenuation.

<b>FCC Part 15 Subpart C Paragraph 15.209 Limits</b>		
Frequency MHz	Field strength (microvolts/meter)	Measurement distance (meter)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remarks:

1. RF Voltage (dB $\mu$ V) = 20 log RF Voltage ( $\mu$ V)
2. In the Above Table, the tighter limit applies at the band edges.
3. Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.



#### 4.3. Test Procedure

The EUT was setup according to ANSI C63.10: 2013 and tested according to C63.10:2013 Section 11.12.1 for compliance to FCC 47CFR 15.247 requirements.

Measuring the frequency range below 1GHz, the EUT is placed on a turn table which is 0.8 meter above ground, when measuring the frequency range above 1GHz, the EUT is placed on a turn table which is 1.5 meter above ground.

The turn table is rotated 360 degrees to determine the position of the maximum emission level.

The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna is scanned between 1 meter and 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10: 2013 on radiated measurement.

The resolution bandwidth below 30MHz setting on the field strength meter is 9kHz and 30MHz~1GHz is 120kHz and above 1GHz is 1MHz.

Radiated emission measurements below 30MHz are made using Loop Antenna and 30MHz~1GHz are made using broadband Bilog antenna and above 1GHz are made using Horn Antennas.

The measurement is divided into the Preliminary Measurement and the Final Measurement.

The suspected frequencies are searched for in Preliminary Measurement with the measurement antenna kept pointed at the source of the emission both in azimuth and elevation, with the polarization of the antenna oriented for maximum response. The antenna is pointed at an angle towards the source of the emission, and the EUT is rotated in both height and polarization to maximize the measured emission. The emission is kept within the illumination area of the 3 dB bandwidth of the antenna.

The measurement frequency range from 9kHz - 10th Harmonic of fundamental was investigated.

**RBW and VBW Parameter setting:**

According to C63.10 Section 11.12.2.4 Peak measurement procedure.

RBW = as specified in Table 1.

VBW  $\geq$  3 x RBW.

**Table 1 - RBW as a function of frequency**

Frequency	RBW
9-150 kHz	200-300 Hz
0.15-30 MHz	9-10 kHz
30-1000 MHz	100-120 kHz
> 1000 MHz	1 MHz

According to C63.10 Section 11.12.2.5 Average measurement procedure.

RBW = 1MHz.

VBW = 10Hz, when duty cycle  $\geq$  98 %

VBW  $\geq$  1/T, when duty cycle < 98 %

(T refers to the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.)

**Radio 1**

2.4GHz band	Duty Cycle (%)	T (ms)	1/T (Hz)	VBW (Hz)
802.11b	61.20	1.3020	768	1000
802.11g	84.30	2.8560	350	500
802.11ax-20 MHz	94.21	10.9100	92	100
802.11ax-40 MHz	92.94	10.8800	92	100

Note: Duty Cycle Refer to Section 9.





**Radio 3**





2.4GHz band	Duty Cycle (%)	T (ms)	1/T (Hz)	VBW (Hz)
802.11b	98.79	12.2000	82	100
802.11g	94.41	4.0500	247	300
802.11ac-20 MHz	94.38	3.8000	263	300
802.11ac-40 MHz	88.60	1.8650	536	1000





Note: Duty Cycle Refer to Section 9.





### 4.4. Test Result of Radiated Emission





#### Radio 1











































Radio 3




























Co-location



## 5. RF Antenna Conducted Test

### 5.1. Test Setup

RF antenna Conducted Measurement:



### 5.2. Limits

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

### 5.3. Test Procedure


The EUT was tested according to C63.10:2013 Section 11.11 for compliance to FCC 47CFR 15.247 requirements.

Set RBW = 100 kHz, Set VBW > RBW, scan up through 10th harmonic.

5.4. Test Result of RF antenna conducted test

Product : Wireless Access Point  
 Test Item : RF antenna conducted test  
 Test Mode : Transmit (802.11b)\_Radio-1  
 Test Date : 2023/09/13


Channel 06 (2437 MHz) (Chain B)



Date: 13.SEP.2023 14:28:53

Product : Wireless Access Point  
 Test Item : RF Antenna Conducted Spurious  
 Test Mode : Transmit (802.11g)\_Radio-1  
 Test Date : 2023/09/13


Channel 06 (2437MHz) (Chain A)



Date: 13.SEP.2023 14:54:25

Product : Wireless Access Point  
 Test Item : RF Antenna Conducted Spurious  
 Test Mode : Transmit (802.11ax-20 MHz)\_Radio-1  
 Test Date : 2023/09/13


Channel 06 (2437MHz) (Chain A)



Date: 13.SEP.2023 15:13:02

Product : Wireless Access Point  
 Test Item : RF Antenna Conducted Spurious  
 Test Mode : Transmit (802.11ax-40 MHz)\_Radio-1  
 Test Date : 2023/09/13


Channel 06 (2437MHz) (Chain A)



Date: 13.SEP.2023 15:24:53

Product : Wireless Access Point  
 Test Item : RF antenna conducted test  
 Test Mode : Transmit (802.11b)\_Radio-3  
 Test Date : 2023/09/12


Channel 06 (2437MHz)



Date: 12.SEP.2023 15:34:18

Product : Wireless Access Point  
 Test Item : RF Antenna Conducted Spurious  
 Test Mode : Transmit (802.11g)\_Radio-3  
 Test Date : 2023/09/12

Channel 06 (2437MHz)




Date: 12.SEP.2023 15:45:38



Product : Wireless Access Point  
 Test Item : RF Antenna Conducted Spurious  
 Test Mode : Transmit (802.11ac-20 MHz)\_Radio-3  
 Test Date : 2023/09/12


Channel 06 (2437MHz)



Date: 12.SEP.2023 15:54:21

Product : Wireless Access Point  
 Test Item : RF Antenna Conducted Spurious  
 Test Mode : Transmit (802.11ac-40 MHz)\_Radio-3  
 Test Date : 2023/09/12

Channel 06 (2437MHz)




Date: 12.SEP.2023 16:03:15

## 6. Band Edge


### 6.1. Test Setup

RF Conducted Measurement



RF Radiated Measurement:

Above 1GHz



## 6.2. Limits

According to FCC Section 15.247(d). In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

## 6.3. Test Procedure

The EUT was setup according to ANSI C63.10, 2013 and tested according to C63.10:2013 Section 11.12.1 for compliance to FCC 47CFR 15.247 requirements.

The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10:2013 on radiated measurement.

**RBW and VBW Parameter setting:**

According to C63.10 Section 11.12.2.4 Peak measurement procedure.

RBW = as specified in Table 1.

VBW  $\geq$  3 x RBW.

**Table 1 - RBW as a function of frequency**

Frequency	RBW
9-150 kHz	200-300 Hz
0.15-30 MHz	9-10 kHz
30-1000 MHz	100-120 kHz
> 1000 MHz	1 MHz

According to C63.10 Section 11.12.2.5 Average measurement procedure.

RBW = 1MHz.

VBW = 10Hz, when duty cycle  $\geq$  98 %

VBW  $\geq$  1/T, when duty cycle < 98 %

(T refers to the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.)

**Radio 1**

2.4GHz band	Duty Cycle (%)	T (ms)	1/T (Hz)	VBW (Hz)
802.11b	61.20	1.3020	768	1000
802.11g	84.30	2.8560	350	500
802.11ax-20 MHz	94.21	10.9100	92	100
802.11ax-40 MHz	92.94	10.8800	92	100

Note: Duty Cycle Refer to Section 9.





**Radio 3**





2.4GHz band	Duty Cycle (%)	T (ms)	1/T (Hz)	VBW (Hz)
802.11b	98.79	12.2000	82	100
802.11g	94.41	4.0500	247	300
802.11ac-20 MHz	94.38	3.8000	263	300
802.11ac-40 MHz	88.60	1.8650	536	1000





Note: Duty Cycle Refer to Section 9.

### 6.4. Test Result of Band Edge





#### Radio 1




























































Radio 3

