

## 45654

Wireless Lighting Control

### Energy Monitoring Outdoor Module

Z-Wave® Certified Wireless Lighting Control



Add callout for Program/manual control pushbutton

Thank you for your purchase of a GE Z-Wave® control device. Z-Wave technology is designed to automate lighting/home control and provide easy remote operation of all your Z-wave enabled devices. The GE Z-Wave product family includes a variety of devices to control lighting in your home. It is up to you whether you want to control one room or your entire house and whether you want to do it all now or start with one room and add more over time.

This module is one component of a Z-Wave® control system and is designed to work with all other Z-Wave enabled devices in a home control network. It will also act as a wireless repeater to insure that commands intended for another device in the network are received, thereby extending the range of the wireless controller. Z-Wave devices of other types and brands can be added to the system and will also act as range extenders if they support this function of repeating the signal received to other nodes in the system.

***The device plugged into this module must not exceed 900 Watts (Incandescent); 1800W (15A) Resistive; or 1 HP Motor load.***

***There are no user serviceable parts in this unit.***

*To reduce the risk of electric shock, this product has a grounding type plug that has a third (grounding) pin. This plug will only fit into a grounding type power outlet. If the plug does not fit into the outlet, contact a qualified electrician to install the proper outlet. Do not change the plug in any way.*



RISK OF FIRE  
RISK OF ELECTRICAL SHOCK  
RISK OF BURNS

The Load-Sense feature on this Z-Wave product will turn the power to the connected device ON when a change in the load is detected. Z-Wave connected devices should always be unplugged before performing any service or maintenance of the devices. Mount above ground with receptacle pointed down using mounting tab.

**Controlling Appliances:**

Exercise extreme caution when using Z-Wave devices to control appliances. Operation of the Z-Wave device may be in a different room than the controlled appliance, also an unintentional activation may occur if the wrong button on the remote is pressed. Z-Wave devices may automatically be powered on due to timed event programming. Depending upon the appliance, these unattended or unintentional operations could possibly result in a hazardous condition. For these reasons, we recommend the following:

1. Assign Z-Wave controlled appliances to device numbers 10 – 18 on the GE remote. The likelihood of unintentionally turning on the appliance will be reduced significantly because the “Shift” button will need to be pressed before pressing device numbers 10-18.
2. Z-Wave devices controlling appliances should be removed from “All” control setting. Instructions on how to do this are included in the manual for your GE remote.
3. Do Not include Z-Wave devices in Groups or Scenes if they control appliances.
4. Do Not use Z-Wave devices to control electric heaters or any other appliances which may present a hazardous condition due to unattended or unintentional or automatic power on control.
5. Double check programs for accuracy before using them.

**NOT FOR USE WITH MEDICAL OR LIFE SUPPORT EQUIPMENT**

Z-Wave enabled devices should never be used to supply power to or control the On/Off status of medical and/or life support equipment!

***Wireless Range***

This device complies with the Z-Wave standard of open-air, line of sight transmission distances of 65 feet. Actual performance in a home depends on the number of walls between the remote controller and the destination device, the type of construction and the number of Z-Wave enabled devices installed in the control network. Every Z-Wave enabled device acts as a signal repeater and multiple devices result in more possible transmission routes which helps eliminate “RF dead-spots”.

Things to consider regarding RF range:

- Each wall or obstacle (i.e.: refrigerator, big screen TV, etc.) between the remote and the destination device will reduce the maximum range of 100 feet by approximately 25-30%.
- Brick, tile or concrete walls block more of the RF signal than walls made of wooden studs and plasterboard (drywall).
- Wall mounted Z-Wave devices installed in metal junction boxes will suffer a significant loss of range (approximately 20%) since the metal box blocks a large part of the RF signal.

**Effects of Home Construction on Wireless Range Between Z-Wave Enabled Devices**

**Note:** The distances shown in the table below are typical examples. Actual performance in your home will vary.

From the Remote (or repeating Z-Wave module) to destination device:

|   |     | Type of Construction                         |                   |   |                   |
|---|-----|--|-------------------|---|-------------------|
|   |     | Wood Frame w/Drywall<br>Plastic J-<br>Boxes* | Metal J-<br>Boxes | Brick, Tile or Concrete<br>Plastic J-<br>Boxes* | Metal J-<br>Boxes |
| <b>Number of Walls<br/>or Obstacles</b> | 0** | 100'   | 80'               | 100'  | 80'               |
|   | 1   | 70'  | 56'               | 60'   | 48'               |
|   | 2   | 49'  | 39'               | 36'   | 29'               |
|   | 3   | 34'  | 27'               | 21'   | 17'               |

\* For Plug-in Modules or In-Wall Devices Installed in Plastic Junction Boxes

\*\* Line of Sight / no obstructions

**Please Note:** Z-Wave home control networks are designed to work properly alongside 802.11 wireless computer networks, Bluetooth and 2.4GHz, 5.8GHz or DECT devices. Some baby cams, wireless video devices and older cordless phones using the 900MHz frequency range may cause interference and limit Z-Wave functionality. Many 900MHz products have a switch to select channel “A” or “B”. You may find that one of these channels will cause less interference than the other.

**Installation**

This unit is suitable for outdoor use in damp locations. Do not expose to rain or immerse in water. Install at least 3 feet above ground level with the receptacle pointed down. When used outdoors you should plug the unit into a GFCI receptacle with a receptacle cover rated for outdoor use.

A mounting tab with screw key-hole is located at the top of the unit. Install a # 8 round-head screw (not included) in the desired location, leaving approximately 3/16” of the screw exposed. Align the mounting tab with the screw head, slide the tab over the screw and let the unit drop down to lock it in place.



**Key Features**

- One Z-wave remote controlled AC outlet
  - Remote ON/OFF control via the Z-Wave controller
  - Manual ON/OFF control with the pushbutton
  - Load-Sensing turns the light ON if the switch on the connected device is used instead of the remote or pushbutton on the Z-Wave module. This feature is disabled by default. See the section on Advanced Operation for instructions on how to enable it.
- Monitors and reports energy values and Watts consumed by the connected device
- Weather and impact resistant housing; Suitable for use outdoors in damp or wet conditions
- Integrated outlet cover keeps dirt & debris out when the module is not in use
- Grounded 3-wire power connection for safety

## **Energy Monitoring**

This unit incorporates special circuitry to capture and report energy values and the Wattage consumed by the device plugged into it.

- This energy related data includes Voltage (V), Current (A), Watts (W), Kilowatt hours (KWh) and Power Factor (PF). V, A, W & PF are instant readings taken at the time of the request while KWh is an accumulated value.
- This unit is capable of storing readings up to 10,000 KWh. It will automatically reset to zero and start over when it reaches 10,000. It will also reset and start over if the power to it is turned off.
- The Z-Wave controller must poll (request) the information from the device.
- The energy data is transmitted using Z-Wave's Meter Command Class v3. If the unit receives a request for this data from a controller supporting the Meter CC v1, it will report KWh as its default scale.
- Meter Reset is supported so if desired, the unit can delete its previous meter readings and start accumulating new KWh data.

## **Basic Operation**

The connected light can be turned ON in two ways:

1. With a remote
2. Manually with the pushbutton on the Z-Wave module

## **Remote Control**

GE Z-Wave remotes provide control of an Individual device, Groups of devices and Scenes. Other brands of Z-Wave Certified remotes may not offer as much flexibility in how you can set up your lighting control network. Please refer to your remote control's instructions for details on its capabilities and instructions for adding and controlling devices.

## **Manual Control**

The Pushbutton on the 45654 Appliance Module allows the user to:

1. Manually turn the connected equipment ON or OFF by pressing the button.
  - This is a toggle switch; if the device is OFF, pressing the button turns the device ON and vice versa.
2. Include or exclude the module from the Z-Wave home control network with your primary controller.
  - Refer to the instructions for your primary controller to access the network setup function and include or exclude devices.
  - When prompted by your primary controller, tap the button (press and release).
  - The primary controller should indicate that the action was successful. If the controller indicates the action was unsuccessful, please repeat the procedure.
  - Once the module is part of the network, the same basic procedure is used to add the module to groups or scenes. Refer to the primary controller's instructions for details.

Please Note: After a power failure, the 45654 module returns to its last used ON/OFF state.

## **ADVANCED OPERATION**

The following Advanced Operation parameters require that you have an advanced controller like the GE model 45601 LCD remote. Advanced remotes from other manufacturers may also be able to change these settings; however, basic remotes do not have this capability.

### **All On/All Off**

Depending upon your primary controller, the 45654 outdoor module can be set to respond to ALL ON and ALL OFF commands in up to four different ways. Some controllers may not be able to change the response from its default setting. Please refer to your controller's instructions for information on whether or not it supports the configuration function and if so, how to change this setting.

The four possible responses are:

- It **will** respond to ALL ON and the ALL OFF command (default).

- It **will not** respond to ALL ON or ALL OFF commands.
- It **will** respond to the ALL OFF command but **will not** respond to the ALL ON command.
- It **will** respond to the ALL ON command but **will not** respond to the ALL OFF command.

## Restoring Factory Defaults

All network settings and configuration parameters can all be restored to their factory default settings by using your master controller to delete it from your network.

## Over-Current Protection

Over-current protection is provided by an internal fuse which is not user serviceable. Check your home's circuit breakers before concluding that the product must be replaced.

## Interoperability with Z-Wave™ Devices

A Z-Wave™ network can integrate devices of various classes, and these devices can be made by different manufacturers. Although every Z-Wave certified product is designed to work with all other Z-Wave certified products, your controller must include the appropriate device classifications in order to control non-lighting Z-wave devices. As an example, the GE 45600 basic remote is designed only for controlling Z-Wave devices using the lighting control classification. The GE 45601 deluxe remote with LCD readout can control other Z-Wave certified devices like thermostats as well as lighting.

## WARRANTY

JASCO Products warrants this product to be free from manufacturing defects for a period of two years from the original date of consumer purchase. This warranty is limited to the repair or replacement of this product only and does not extend to consequential or incidental damage to other products that may be used with this product. This warranty is in lieu of all other warranties, expressed or implied. Some states do not allow limitations on how long an implied warranty lasts or permit the exclusion or limitation of incidental or consequential damage, so the above limitations may not apply to you. This warranty gives you specific rights, and you may also have other rights which vary from state to state. Please contact Customer Service at 800-654-8483 (option 4) between 7:30AM – 5:00PM CST or via our website ([www.jascopeproducts.com](http://www.jascopeproducts.com)) if the unit should prove defective within the warranty period,

JASCO Products Company  
Building B  
10 E Memorial Rd.  
Oklahoma City, OK 73114

## FCC

U2ZZW4202

The Federal Communication Commission Radio Frequency Interference Statement includes the following paragraph: The equipment has been tested and found to comply with the limits for a Class B Digital Device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment uses, generates and can radiate radio frequency energy and, if not installed and used in accordance with the instruction, may cause harmful interference to radio communication. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna
- Increase the separation between the equipment and receiver
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected
- Consult the dealer or an experienced radio/TV technician for help

Operation is subject to the following two conditions:

- This device may not cause interference
- This device must accept any interference, including interference that may cause undesired operation of the device.

**Important Note:**

Operation is subject to the following two conditions: (1) this device may not cause interference, and (2) this device must accept any interference, including interference that may cause undesired operation of the device.

FCC/IC RF Radiation Exposure Statement:

1.To comply with the FCC RF exposure compliance requirements, no change to the antenna or the device is permitted. Any change to the antenna or the device could result in the device exceeding the RF exposure requirements and void user's authority to operate the device.

2.This equipment complies with FCC RF radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with a minimum distance of 20 centimeters between the radiator and your body.

**Compliance with IC Rules and Regulations**

IC: 6924A-ZW4202

Jasco Products Company

Model: 45654

ZW4202

This Class B digital device complies with Canadian ICES-003.

**SPECIFICATIONS**

Power 120VAC, 60Hz

Signal (Frequency) 908.42 MHz

Maximum Load: 900W Incandescent, 1 HP Motor or 1800W (15A) Resistive

Range: Up to 100 feet line of sight between the Wireless Controller and the closest Z-Wave receiver module.

Energy Monitoring Values: Voltage (V), Current (A), Watts (W), Kilowatt hours (KWh) and Power Factor (PF)

Operating Temperature Range: 14 to 140° F (-10 to 60° C)

Suitable for outdoor use in damp locations

Specifications subject to change without notice due to continuing product improvement

Z-Wave is a registered US trademark of Sigma Designs

© 2010 JASCO Products Company