

ELECTROMAGNETIC EMISSION COMPLIANCE REPORT FOR LOW-POWER, NON-LICENSED TRANSMITTER

Test Report No.	: OT-18O-RWD-001		
AGR No.	: A18OA-005		
Applicant	: BLUECOM Co., Ltd.		
Address	: 116, Venture-ro, Yeonsu-gu, Incheon, Korea		
Manufacturer	: BLUECOM Co., Ltd.		
Address	: 116, Venture-ro, Yeonsu-gu, Incheon, Korea		
Type of Equipment	: Bluetooth Headset		
FCC ID.	: U3WBCS700		
Model Name	: BCS-700		
Serial number	: N/A		
Total page of Report	: 7 pages (including this page)		
Date of Incoming	: September 27, 2018		
Date of issue	: October 02, 2018		

SUMMARY

ONETECH

The equipment complies with the regulation; *FCC PART 15 SUBPART C Section 15.247* This test report only contains the result of a single test of the sample supplied for the examination. It is not a generally valid assessment of the features of the respective products of the mass-production.

Reviewed by:

Jae-Ho Lee / Chief Engineer ONETECH Corp.

Approved by:

Keun-Young, Choi / Vice President ONETECH Corp.

It should not be reproduced except in full, without the written approval of ONETECH Corp.

EMC-003 (Rev.2)

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)



CONTENTS

PAGE

1. VERIFICATION OF COMPLIANCE	4
2. GENERAL INFORMATION	5
2.1 PRODUCT DESCRIPTION	5
2.2 ALTERNATIVE TYPE(S)/MODEL(S); ALSO COVERED BY THIS TEST REPORT.	5
3. EUT MODIFICATIONS	5
4. MAXIMUM PERMISSIBLE EXPOSURE	6
4.1 EUT DESCRIPTION	6
4.3 CALCULATED MPE SAFE DISTANCE	7



Revision History

Rev. No.	Issue Report No.	ssue Report No. Issued Date Revisions		Section Affected
0	OT-18O-RWD-001	October 02, 2018	Initial Issue	All



1. VERIFICATION OF COMPLIANCE

Applicant : BLUECOM Co., Ltd.	: BLUECOM Co., Ltd.			
Address : 116, Venture-ro, Yeonsu-gu, Inc	: 116, Venture-ro, Yeonsu-gu, Incheon, Korea			
Contact Person : Ki-eok Park / Principal Engine	eer			
Telephone No. : 82-32-8100-582				
FCC ID : U3WBCS700				
Model Name : BCS-700				
Brand Name : -				
Serial Number : N/A				
Date : October 02, 2018				
EQUIPMENT CLASS	DSS – PART 15 SPREAD SPECTRUM TRANSMITTER			
E.U.T. DESCRIPTION	Bluetooth Headset			
KIND OD EQUIPMENT	Modular Transmitter			
THIS REPORT CONCERNS	Original Grant			
MEASUREMENT PROCEDURES	ANSI C63.10: 2013			
TYPE OF EQUIPMENT TESTED	Pre-Production			
KIND OF EQUIPMENT				
AUTHORIZATION REQUESTED	Certification			
EQUIPMENT WILL BE OPERATED				
UNDER FCC RULES PART(S)	FCC PART 15 SUBPART C Section 15.247			
Modifications on the Equipment to Achieve				
Compliance	None			
Final Test was Conducted On	3 m, Semi Anechoic Chamber			

-. The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.



2. GENERAL INFORMATION

2.1 Product Description

The BLUECOM Co., Ltd., Model BCS-700 (referred to as the EUT in this report) is a Bluetooth Headset. The product specification described herein was obtained from product data sheet or user's manual.

Device Type	Bluetooth Headset		
Operating Frequency	2 402 MHz ~ 2 480 MHz		
RF Output Power	1 Mbps 2.96 dBm		
	2 Mbps 4.52 dBm		
	3 Mbps 5.67 dBm		
Number of Channel	79 Channels		
Modulation Type	GFSK for 1 Mbps, π/4-DQPSK for 2 Mbps, 8-DPSK for 3Mbps		
Antenna Type	FPCB Antenna		
Antenna Gain	1.94 dBi		
List of each Osc. or crystal Freq.(Freq. >= 1 MHz)	16 MHz		
Rated Supply Voltage	DC 3.7 V		

2.2 Alternative type(s)/model(s); also covered by this test report.

-. None

3. EUT MODIFICATIONS

-. None

4. MAXIMUM PERMISSIBLE EXPOSURE

4.1 EUT Description

Kind of EUT	Bluetooth Headset		
	□ Wireless Microphone: 494.000 MHz ~ 501.000 MHz		
	and 498.200 MHz ~ 505.200 MHz		
	□ WLAN: 2 412 MHz ~ 2 462 MHz		
Operating Frequency Band	□ WLAN: 5 180 MHz ~ 5 240 MHz		
	□ WLAN: 5 745 MHz ~ 5 825 MHz		
	■ Bluetooth: 2 402 MHz ~ 2 480 MHz		
	□ Bluetooth BLE: 2 402 MHz ~ 2 480 MHz		
MAX. RF OUTPUT POWER	1 Mbps	2.96 dBm	
	2 Mbps	4.52 dBm	
	3 Mbps	5.67 dBm	
Antenna Gain	1.94 dBi		
	□ MPE		
Exposure	□ SAR		
Evaluation Applied	■ N/A		



4.3 Calculated MPE Safe Distance

According to the procedure, KDB 447498 D01, the standalone SAR test exclusion threshold is

[(Max. Power of channel, including tune-up tolerance, mW)/(Mim. test separation distance, mm)] X [$\sqrt{f(GHz)}$] < 3

 $= (3.69/5) \mathrm{X} \sqrt{2.480} = 1.16$

Conclusion: The SAR test exclusion threshold is less than 3, so the device meets the RF Exposure Requirement and are excluded from SAR Test.

	Frequency (MHz)	Target Power W/tolerance (dBm)	Max tune up power (dBm)	Max tune up power (mW)	Separation distance (mm)	RF exposure
1 Mbps	2 480	$2.46~\pm~0.5$	2.96	1.98	5	0.62
2 Mbps	2 480	4.02 ± 0.5	4.52	2.83	5	0.89
3 Mbps	2 480	5.17 ± 0.5	5.67	3.69	5	1.16

0

Tested by: Ju Yun Park / Assistant Manager