Test Report



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS

Report No	ES1024-2
Client	ASSA ABLOY Inc.
Address	110 Sargent Drive New Haven, CT 06511
Phone	203-498-5686
Items tested	Aperio V3 iN100
FCC ID IC FRN	U4A-SCYMCA1 6982A-SCYMCA1 0016550824
Equipment Type Equipment Code Emission Designator	Part 15 Low Power Communication Device Transmitter DXX 354KA1D
FCC/IC Rule Parts	CFR Title 47 FCC Part 15.225, ISED Canada RSS-210 Issue 9 Annex B.6
Test Dates	1/7/2019 to 1/10/2019
Results	As detailed within this report
Prepared by	Aik Zwirner Sr. EMC Engineer
Authorized by	Yunus Fazilogur – Sr. EMC Engineer
Issue Date	2/25/2019
Conditions of Issue	This Test Report is issued subject to the conditions stated in the 'Conditions of Testing' section on page 13 of this report.

Curtis-Straus LLC is accredited by the American Association for Laboratory Accreditation for the specific scope of accreditation under Certificate Number 1627-01. This report may contain data which is not covered by the A2LA accreditation.





Curtis-Straus LLC, a wholly owned subsidiary of BV CPS One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828

page 1 of 14

Contents

Contents	2
Summary and Test Methodology	3
Product Tested - Configuration Documentation	4
Modifications Required for Compliance	4
Radiated Spurious Emissions	5
AC Line Conducted Emissions	8
Measurement Uncertainty	12
Conditions of Testing	13

Form Final Report REV 12-07-15



Summary and Test Methodology

This test report supports an application for Class 2 Permissive Change for a transmitter

operating pursuant to:

CFR Title 47 FCC Part 15.225, ISED Canada RSS-210 Issue 9 Annex B.6

EUT is the Aperio V3 iN100. Its operating frequency is 13.56MHz.

All testing was performed according to the following rules/procedures/documents; CFR Title 47 FCC Part 15.209, ISED Canada RSS-210 Issue 9, ISED Canada RSS-Gen Issue 5 and ANSI C63.10-2013.

Radiated Emissions were maximized by rotating the device around its installation axes as well as varying the test antenna's height and polarity. EUT antenna is internal and cannot be maximized separately.

The EUT operating voltage is 9VDC from battery. Fresh batteries were used during testing. The environmental conditions during each test are detailed in the results tables for each section. Following bandwidths were used during radiated spurious and line conducted emissions testing.

Frequency	RBW	VBW
9kHz-150kHz	200Hz	1kHz
0.15-30MHz	9kHz	30kHz
30-1000MHz	120kHz	1MHz

EUT was tested for fundamental level, radiated spurious emissions and AC line conducted emissions and met the corresponding requirements. Test sample was received in good condition.





page 3 of 14

					EUT (Configuration					
Work	Order:	S1024									
Co	mpany:	Assa A	bloy								
Company A	ddress:	110 Sa	rgent Drive								
		New H	aven, CT 06	511							
C	ontact:	Steve M	Morse								
				MN			PN			SN	[
	EUT:		iN100 (with	New BT Modul	e)		iN100			1	
EUT Desc	ription:	Aperio	V3								
EUT Max Free	quency:	2475 N	1Hz								
EUT Min Free	quency:	0.032 N	MHz								
Support Equipment	t			M	N				SN		
AC/DC Brick	/DC Brick S			SYS1308-	2424-W2				SW-241	IPR	
Laptop computer		dell									
Sargent 12V Supply				352	21				Sample	e 1	
Sargent 24V Supply				352	20				Sample	e 1	
Port Label	Port	t Type	# ports	# populated	cable type	shielded	ferrites	length (m)	in/out	under test	comment
DC Power input	Powe	er DC	1	1	Power DC	No	No	10	in	yes	*not used for emissions. emissions done with battery power
USB setup port	USB		1	1	USB	Yes	No	1	in	yes	*used to setup the radio power and channels
Software Operating	Mode D	escriptio	n:								
Commands are giver				up the radio para	ameters. Then th	ne laptop and us	sb are disconne	cted and the EU	Continues	operating in	n that mode until
battery power is rem	oved.		0							2	

Product Tested - Configuration Documentation

 Clock Frequencies

 frequencies (MHz)
 2475, 48, 32, 27.12, 18, 16, 13.56, 8, 0.125, 0.1, 0.032768, 0.03216, 0.032

Modifications Required for Compliance

None.





page 4 of 14

Radiated Spurious Emissions

The field strength of any emissions appearing outside of the 13.110-14.010 MHz band shall not exceed the general radiated emission limits in §15.209. [15.225(d)]

MEASUREMENTS / RESULTS

Dete													
Date	08-Jan-19		Company:	Assa Ablo	у					١	Nork Order:	S1024	
Engineer	AKZ								EUT Operat	ting Voltage	/Frequency:	Battery	
Temp:	24°C		Humidity:	21%		Pressure:	: 1001mbar						
	Freque	ncy Range:	9kHz-1MH	Z					Measureme	nt Distance:	3 m		
Notes	Antenna orient EUT transmitti	,		ontal (parall	el to grou	nd plane)							
Antenna Polarization (0° - 90°)	Frequency (MHz)	Reading (dBµV)	Preamp Factor (dB)	Antenna Factor (dB/m)	Cable Factor (dB)	Adjusted Reading (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Result (Pass/Fail)	Limit (dBµV/m)	Margin (dB)	Result (Pass/Fail)	
(0 50)	(101112)	(ubpv)								(ubµv/iii) 	(ub) 		
NO EMISSIONS	FOUND IN THI	S RANGE.											
CSsoft Radiate	Asset #2093 ed Emissions C ling = Reading	- Preamp Fa			+ Cable F	actor		Antenna:	. Ly Loop		Preselector: Copyright Curti	is-Straus LLC 20	
Engineer: Temp:	: 08-Jan-19 : AKZ : 24°C Freque	ncy Range:	Company: Humidity: : 1-30MHz	21%			: 1001mbar			ting Voltage/ nt Distance:			
Engineer: Temp:	: 08-Jan-19 : AKZ : 24°C	ncy Range:	Company: Humidity: : 1-30MHz	21%			: 1001mbar			ting Voltage/	/Frequency:		
Engineer: Temp:	: 08-Jan-19 : AKZ : 24°C Freque	ncy Range:	Company: Humidity: : 1-30MHz	21%			: 1001mbar			ting Voltage/	/Frequency:	Battery	
Engineer: Temp: Notes:	: 08-Jan-19 : AKZ : 24°C Freque	ncy Range:	Company: Humidity: : 1-30MHz D, and horizo	21% ontal (parall	el to grou	nd plane)	: 1001mbar	 Margin		ting Voltage/	/Frequency: 3 m	Battery	
Engineer: Temp: Notes: Antenna Polarization (0° - 90°)	08-Jan-19 AKZ 24°C Freque Antenna orient Frequency (M+z)	ncy Range: tations: 0, 90 Reading (dBµV)	Company: Humidity: 1-30MHz), and horizo Preamp Factor (dB)	21% ontal (parall Antenna Factor (dB/m)	el to grou Cable Factor (dB)	nd plane) Adjusted Reading (dBµV/m)		 Margin (dB)	Measureme	ting Voltage, nt Distance: Limit (dBµV/m)	/Frequency: 3 m FCC 15.225 Margin (dB)	Battery Result (Pass/Fail)	
Engineer: Temp: Notes: Antenna Polarization (0° - 90°) 90	08-Jan-19 AKZ 24°C Freque Antenna orient Frequency (MHz) 13.56	ncy Range: tations: 0, 90 Reading (dBµV) 54.3	Humidity: 1-30MHz 1-30MHz 0, and horizo Preamp Factor (dB) 32.0	21% ontal (parall Antenna Factor (dB/m) 38.9	el to grou Cable Factor (dB) 0.2	Adjusted Reading (dBµV/m) 61.4	Lim it (dBµV/m) 	(dB) 	Measureme Result (Pass/Fail)	ting Voltage/ nt Distance: Limit (dBµV/m) 124.0	/Frequency: 3 m FCC 15.225 Margin (dB) -62.6	Battery Result (Pass/Fail) Pass	
Engineer: Temp: Notes: Antenna Polarization (0° - 90°) 90 0	08-Jan-19 AKZ 24°C Freque Antenna orient Frequency (MHz) 13.56 13.56	ncy Range: tations: 0, 90 Reading (dBµV) 54.3 57.4	Company: Humidity: : 1-30MHz), and horizo Preamp Factor (dB) 32.0 32.0	21% ontal (parall Antenna Factor (dB/m) 38.9 38.9	el to grou Cable Factor (dB) 0.2 0.2	Adjusted Reading (dBµV/m) 61.4 64.5	Limit (dBµV/m)	(dB)	Result (Pass/Fail)	ting Voltage/ nt Distance: Limit (dBµV/m) 124.0 124.0	/Frequency: 3 m FCC 15.225 Margin (dB) -62.6 -59.5	Battery Result (Pass/Fail) Pass Pass	
Engineer: Temp: Notes: Antenna Polarization (0° - 90°) 90 0 H	08-Jan-19 AKZ 24°C Freque Antenna orient Frequency (MHz) 13.56	ncy Range: tations: 0, 90 Reading (dBµV) 54.3	Humidity: 1-30MHz 1-30MHz 0, and horizo Preamp Factor (dB) 32.0	21% ontal (parall Antenna Factor (dB/m) 38.9	Cable Factor (dB) 0.2 0.2 0.2	Adjusted Reading (dBµV/m) 61.4	Lim it (dBµV/m) 	(dB) 	Result (Pass/Fail)	ting Voltage/ nt Distance: Limit (dBµV/m) 124.0	/Frequency: 3 m FCC 15.225 Margin (dB) -62.6	Battery Result (Pass/Fail) Pass Pass Pass Pass	





page 5 of 14

Curtis Straus - a Bureau Veritas Company Radiated Emissions Electric Field 3m Distance Top Peaks Horizontal 30-1000MHz Operator: AKZ Notes: Work Order - S1024 EUT Power Input - Battery Test Site - CH-1 Conditions - 23°C; 21%RH; 1023mBar

Data Taken at 10:26:54 AM, Monday, January 07, 2019

Frequency (MHz)	Реак Reading (dBµV)	Correction Factor (dB/m)		Lim1: FCC_pt15_1 09_Class_B (dBµV/m)	Lim1 Margin (dB)	Lim1 Test Results (Pass/Fail)	Worst Margin Lim1 (dB)	Lim2: Cispr_Class _B (dBµV/m)	Lim2 Margin (dB)	Lim2 Test Results (Pass/Fail)	Worst Margin Lim2 (dB)	Antenna Height (cm)	EUT Azimuth (degrees)
176.3	51.6	-16.9	34.7	43.5	-8.8	PASS		40.5	-5.8	PASS	-5.8	150	270
189.832	48.3	-16.7	31.6	43.5	-11.9	PASS		40.5	-8.9	PASS		100	270
257.635	53.2	-15.9	37.2	46	-8.8	PASS	-8.8	47.5	-10.3	PASS		100	90
569.538	42.6	-7.9	34.6	46	-11.4	PASS		47.5	-12.9	PASS		100	270
583.07	43.2	-7.7	35.5	46	-10.5	PASS		47.5	-12	PASS		100	270
596.65	42.2	-8	34.1	46	-11.9	PASS		47.5	-13.4	PASS		100	90

Curtis Straus - a Bureau Veritas Company Radiated Emissions Electric Field 3m Distance Top Peaks Vertical 30-1000MHz Operator: AKZ Notes: Work Order - S1024 EUT Power Input - Battery Test Site - CH-1 Conditions - 23°C; 21%RH; 1023mBar

Data Taken at 10:26:54 AM, Monday, January 07, 2019

Frequency (MHz)	Peak Reading (dBµV)	Correction Factor (dB/m)		Lim1: FCC_pt15_1 09_Class_B (dBµV/m)	Lim1 Margin (dB)	Lim1 Test Results (Pass/Fail)	Worst Margin Lim1 (dB)	Lim2: Cispr_Class _B (dBµV/m)	Lim2 Margin (dB)	Lim2 Test Results (Pass/Fail)	Worst Margin Lim2 (dB)	Antenna Height (cm)	Turntable Azimuth (degrees)
176.276	44.1	-16.9	27.2	43.5	-16.3	PASS		40.5	-13.3	PASS	-13.3	200	0
488.18	41.5	-9.1	32.4	46	-13.6	PASS	-13.6	47.5	-15.1	PASS		100	180
501.735	39.9	-9	30.9	46	-15.1	PASS		47.5	-16.6	PASS		100	180
515.267	38.7	-9	29.7	46	-16.3	PASS		47.5	-17.8	PASS		100	180
569.538	37.7	-7.9	29.7	46	-16.3	PASS		47.5	-17.8	PASS		150	0
981.279	31.6	-1.4	30.2	54	-23.8	PASS		47.5	-17.3	PASS		150	135





Rev. 1/5/2019

THEY.	Spectrum Analyzers / Receivers /Preselectors 2093 MXE EMI Receiver	Range 20Hz-26.5GHz	MN N9038A	Mfr Agilent	\$N MY51210181	Asset 2093	Cat	Callbration Due 11/21/2019	Callbrated on 11/21/2018
	Radiated Emissions Sites EMI Chamber 1	FCC Code 719150	IC Code 2762A-6	VCCI Code A-0015	Range 30-1000MHz	Asset 1685	Cat I	Callbration Due 12/7/2020	Callbrated on 12/7/2018
	Preamps /Couplers Attenuators/ Filters 2311 PA	Range 1-1 000MHz	MN PAM-103	Mfr COM-POWER	SN 441174	Asset 2311	Cat	Calibration Due 10/29/2019	Calibrated on 10/29/2018
	An te nra s Small Loop Large Loop	Rainge 10k Hz-30 MHz 20 Hz-5 MHz	MN PLA-130/A 6511	Mfr ARA EMCO	SN 1024 9704-1154	Asset 755 67	Cat	Callbration Due 7/23/2020 7/20/2020	Callbrated on 7/23/2018 7/20/2018
	Meteorological Meters/Chambers Weather Clock (Piessule Only) TH A#2082		MN BA928 HTC-1	Mfr Oregon Scientific HDE	\$N C3166-1	Asset 831 2082	Cat	Callbration Due 5/15/2020 3/23/2019	Callbrated on 5/15/2018 3/23/2018
	Cables Asset #2456 Asset #2460	Range 9KHz-18GHz 9KHz-18GHz		Mfr MegaPhase MegaPhase			Cat	Callbration Due 10/31/2019 10/29/2019	Callbrated on 10/31/2018 10/29/2018

All equipment is calibrated using standards traceable to NIST or other nationally recognized calibration standard.

Rev. 1/5/2019								
Spectrum Analyzers / Receivers / Preselectors	Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
2093 MXE EMI Receiver	20Hz-26.5GHz	N9038A	Agilent	MY51210181	2093	I	11/21/2019	11/21/2018
Radiated Emissions Sites	FCC Code	IC Code	VCCI Code	Range	Asset	Cat	Calibration Due	Calibrated on
EMI Chamber 1	719150	2762A-6	A-0015	30-1000MHz	1685	1	12/7/2020	12/7/2018
EMI Chamber 1	719150	2762A-6	A-0015	1-18GHz	1685	I	12/7/2020	12/7/2018
Preamps /Couplers Attenuators / Filters	Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
2310 PA	1-1000MHz	PAM-103	COM-POWER	441175	2310	Ш	10/29/2019	10/29/2018
Antennas	Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
Red-Black Bilog	30-2000MHz	JB1	Sunol	A091604-2	1106	I	2/28/2019	2/28/2017
Meteorological Meters/Chambers		MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated on
Weather Clock (Pressure Only)		BA928	Oregon Scientific	C3166-1	831	1	5/15/2020	5/15/2018
TH A#2082		HTC-1	HDE		2082	Ш	3/23/2019	3/23/2018
Cables	Range		Mfr			Cat	Calibration Due	Calibrated on
Asset #2456	9KHz-18GHz		MegaPhase			Ш	10/31/2019	10/31/2018
Asset #2464	9KHz-18GHz		MegaPhase			Ш	10/31/2019	10/31/2018
Asset #2480	9KHz-18GHz		MegaPhase			Ш	10/29/2019	10/29/2018
2489(6dB)	9KHz-18GHz		-			Ш	11/27/2019	11/27/2018

All equipment is calibrated using standards traceable to NIST or other nationally recognized calibration standard.





page 7 of 14

AC Line Conducted Emissions

LIMITS

Frequency of emission (MHz)	Quasi-peak limit (dBµV)	Average limit (dBµV)
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency. [47 CFR 15.207(a)]





MEASUREMENTS / RESULTS

Curtis Straus - a Bureau Veritas Company Conducted Emissions per CISPR 16-2-1 Peak Detector Data Notes: EUT Line tested: 120VAC/60Hz; Neutral (line 0) Work Order # - S1024 EUT Power Input - 120VAC/ 60Hz Test Site - CEMI-3 Conditions: - 19.4°C; 35%RH; 1003mBar Test Engineer - Patrick Crozier Witnessed by - Steve Morse

Data Taken at 05:03:45 PM, Friday, January 11, 2019

Frequency (MHz)	Raw Pk Reading (dBμV)	Correction Factor (dB)	Adjusted Pk Amplitude (dBµV)	QP Lim: Mains_FCC&CISP R_QP_Class_B (dBμV)	Margin to the QP Limit (dB)	Pk to QP Limit Results (Pass/Fail)	Worst Margin (QP Limit) (dB)
0.15	36	20.7	56.7	66.0	-9.3	PASS	
0.167	33.8	20.8	54.6	65.1	-10.5	PASS	
0.213	29.9	20.8	50.7	63.1	-12.4	PASS	
0.251	32.8	20.8	53.5	61.7	-8.2	PASS	-8.2
0.315	26.6	20.8	47.3	59.8	-12.5	PASS	
0.51	20.1	20.8	40.8	56.0	-15.2	PASS	

Curtis Straus - a Bureau Veritas Company

Conducted Emissions per CISPR 16-2-1, CISPR Average Detector Quick Average Detector Data Notes:

EUT Line tested: 120VAC/60Hz; Neutral (line 0)

Work Order # - S1024 EUT Power Input - 120VAC/ 60Hz Test Site - CEMI-3 Conditions: - 19.4°C; 35%RH; 1003mBar Test Engineer - Patrick Crozier Witnessed by - Steve Morse

Data Taken at 05:03:45 PM, Friday, January 11, 2019

Frequency (MHz)	Raw Avg Reading (dBµV)	Correction Factor (dB)	Adjusted Avg Amplitude (dBµV)	Av Lim: Mains_FCC&CISP R_Avg_Class_B (dBμV)	Avg Margin (dB)	Avg Results (Pass/Fail)	Worst Avg Margin (dB)
0.155	26.2	20.7	46.9	55.7	-8.8	PASS	
0.251	22.9	20.8	43.6	51.7	-8.1	PASS	-8.1
0.312	20.5	20.8	41.2	49.9	-8.7	PASS	
0.337	18.5	20.8	39.2	49.3	-10.1	PASS	
0.505	12.3	20.8	33.1	46.0	-12.9	PASS	
0.582	12.2	20.8	32.9	46.0	-13.1	PASS	





Curtis Straus - a Bureau Veritas Company Conducted Emissions per CISPR 16-2-1 Peak Detector Data Notes: EUT Line tested: 120VAC/60Hz; Phase (line 1) Work Order # - S1024 EUT Power Input - 120VAC/ 60Hz Test Site - CEMI-3 Conditions: - 19.4°C; 35%RH; 1003mBar Test Engineer - Patrick Crozier Witnessed by - Steve Morse

Frequency (MHz)	Raw Pk Reading (dBμV)	Correction Factor (dB)	Adjusted Pk Amplitude (dBμV)	QP Lim: Mains_FCC&CISP R_QP_Class_B (dBμV)	Margin to the QP Limit (dB)	Pk to QP Limit Results (Pass/Fail)	Worst Margin (QP Limit) (dB)
0.153	37	20.7	57.8	65.8	-8.0	PASS	-8.0
0.184	31.5	20.8	52.2	64.3	-12.1	PASS	
0.25	28.5	20.7	49.3	61.8	-12.5	PASS	
0.332	24.7	20.7	45.4	59.4	-14.0	PASS	
0.508	19.2	20.8	40	56.0	-16.0	PASS	
0.617	19	20.8	39.7	56.0	-16.3	PASS	

Data Taken at 04:43:22 PM, Friday, January 11, 2019

Curtis Straus - a Bureau Veritas Company

Conducted Emissions per CISPR 16-2-1, CISPR Average Detector Quick Average Detector Data Notes:

EUT Line tested: 120VAC/60Hz; Phase (line 1)

Work Order # - S1024

EUT Power Input - 120VAC/ 60Hz Test Site - CEMI-3 Conditions: - 19.4°C; 35%RH; 1003mBar Test Engineer - Patrick Crozier Witnessed by - Steve Morse

Data Taken at 04:43:22 PM, Friday, January 11, 2019

Frequency (MHz)	Raw Avg Reading (dBμV)	Correction Factor (dB)	Adjusted Avg Amplitude (dBµV)	Av Lim: Mains_FCC&CISP R_Avg_Class_B (dBμV)	Avg Margin (dB)	Avg Results (Pass/Fail)	Worst Avg Margin (dB)
0.15	26.7	20.7	47.4	56.0	-8.6	PASS	
0.253	23.4	20.7	44.1	51.7	-7.6	PASS	-7.6
0.306	21	20.7	41.8	50.1	-8.3	PASS	
0.513	12.3	20.8	33	46.0	-13.0	PASS	
0.546	11.9	20.8	32.7	46.0	-13.3	PASS	
0.602	11.4	20.8	32.1	46.0	-13.9	PASS	





v. 1/5/2019								
Spectrum Analyzers / Receivers / Preselectors	Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated of
Rental MXE EMI Receiver(1168255)	20Hz-8.4GHz	N9038A	Agilent	MY53290009	1168255	- 1	8/23/2019	8/23/2018
LISNs/Measurement Probes	Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated o
LISIN Asset 2092	9KHz-30MHz	NNLK 8121	Schwarzbeck	NNLK 8121-66			7/31/2019	7/31/2018
LION A3361 2032	31(112-30)(1112	ININEI OTZT	OCHWAIZDECK		2032		1/31/2013	7/31/2010
Conducted Test Sites (Mains / Telco)	FCC Code		VCCI Code			Cat	Calibration Due	Calibrated of
CEMI 3	719150		A-0015			Ш	NA	N/A
Meteorological Meters/Chambers		MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated o
Weather Clock (Pressure Only)		BA928	Oregon Scientific	C3166-1	831		5/15/2020	5/15/2018
TH A#2077		HTC-1	HDE		2077	II	3/23/2019	3/23/2018
Cables	Range		Mfr			Cat	Calibration Due	Calibrated o
CEMI-18	9kHz - 2GHz		C-S				11/5/2019	11/5/2018
Attenuators	Range	MN	Mfr	SN	Asset	Cat	Calibration Due	Calibrated o
20dB Attenuator-64	9kHz-2GHz			N/A		Ш	11/15/2019	11/15/2018
equipment is calibrated using standards traceable to NIS	T or other pationally	recognized colik	viction standard					





page 11 of 14

Measurement Uncertainty

The listed uncertainties are the worst case uncertainty for the entire range of measurement. Please note that the uncertainty values are provided for informational purposes only and are not used in determining the PASS/FAIL results.

Measurement	Expanded Uncertainty k=2	Maximum allowable uncertainty		
Radiated Emissions (30-1000MHz) NIST	5.6dB	N/A		
CISPR	4.6dB	5.2dB (Ucispr)		
Radiated Emissions (1-26.5GHz)	4.6dB	N/A		
Radiated Emissions (above 26.5GHz)	4.9dB	N/A		
Magnetic Radiated Emissions	5.6dB	N/A		
Conducted Emissions NIST CISPR	3.9dB 3.6dB	N/A 3.6dB (Ucispr)		
Telco Conducted Emissions (Current)	2.9dB	N/A		
Telco Conducted Emissions (Voltage)	4.4dB	N/A		
Electrostatic Discharge	11.5%	N/A		
Radiated RF Immunity (Uniform Field)	1.6dB	N/A		
Electrical Fast Transients	23.1%	N/A		
Surge	23.1%	N/A		
Conducted RF Immunity	3dB	N/A		
Magnetic Immunity	12.8%	N/A		
Dips and Interrupts	2.3V	N/A		
Harmonics	3.5%	N/A		
Flicker	3.5%	N/A		
Radio frequency (@ 2.4GHz)	3.23 x 10 ⁻⁸	1 x 10 ⁻⁷		
RF power, conducted	0.40dB	0.75dB		
Maximum frequency deviation: • Within 300Hz and 6kHz of audio frequency / Within 6kHz and 25kHz of audio frequency	3.4% 0.3dB	5% 3dB		
Adjacent channel power	1.9dB	3dB		
Conducted spurious emission of transmitter, valid up to 12.75GHz	2.39dB	3dB		
Conducted emission of receivers	1.3dB	3dB		
Radiated emission of transmitter, valid up to 26.5GHz	3.9dB	6dB		
Radiated emission of transmitter, valid up to 80GHz	3.3dB	6dB		
Radiated emission of receiver, valid up to 26.5GHz	3.9dB	6dB		
Radiated emission of receiver, valid up to 80GHz	3.3dB	6dB		
Humidity	2.37%	5%		
Temperature	0.7°C	1.0°C		
Time	4.1%	10%		
RF Power Density, Conducted	0.4dB	3dB		
DC and low frequency voltages	1.3%	3%		
Voltage (AC, <10kHz)	1.3%	2%		
Voltage (DC)	0.62%	1%		
The above reflects a 95% confidence level				



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



page 12 of 14

Conditions of Testing

[Bureau Veritas Consumer Products Services, Inc., a Massachusetts corporation], and/or its affiliates (collectively, the "Company") will conduct, at the request of the Submitter ("Client"), the tests specified on the submitted Test Request Form or equivalent in accordance with, and subject to, the following terms and conditions (collectively, "Conditions"):

1. All orders for tests are subject to acceptance by the Company, and no order will constitute a binding commitment of the Company unless and until such order is accepted by it, as evidenced by the issuance of a written report ("Test Report") by the Company. The Test Report is issued solely by the Company, is intended for the exclusive use of Client and shall not be published, used for advertising purposes, copied or replicated for distribution to any other person or entity or otherwise publicly disclosed without the prior written consent of the Company. By submitting a request for services to the Company, Client consents to the disclosure to accreditation bodies of those records of Client relevant to the accreditation body's assessment of the Company's competence and compliance with relevant accreditation criteria. The Company shall not be liable for any loss or damage whatsoever resulting from the failure of the Company to provide its services within any time period for completion estimated by the Company. If Client anticipates using the Test Report in any legal proceeding, arbitration, dispute resolution forum or other proceeding, it shall so notify the Company prior to submitting the Test Report in such proceeding. The Company has no obligation to provide a fact or expert witness at such proceeding unless the Company agrees in advance to do so for a separate and additional fee.

2. The Test Report will set forth the findings of the Company solely with respect to the test samples identified therein. Unless specifically and expressly indicated in the Test Report, the results set forth in such Test Report are not intended to be indicative or representative of the quality or characteristics of the lot from which a test sample is taken, and Client shall not rely upon the Test Report as being so indicative or representative of the lot or of the tested product in general. The Test Report will reflect the findings of the Company at the time of testing only, and the Company shall have no obligation to update the Test Report after its issuance. The Test Report will set forth the results of the tests performed by the Company based upon the written information provided to the Company. The Test Report will be based solely on the samples and written information submitted to the Company by Client, and the Company shall not be obligated to conduct any independent investigation or inquiry with respect thereto.

3. The Company may, in its sole discretion, destroy samples which have been furnished to the Company for testing and which have not been destroyed in the course of testing. The Company may delegate the performance of all or a portion of the services contemplated hereunder to an affiliate, agent or subcontractor of the Company, and Client consents to such delegation.

4. These Conditions and the Test Report represent the entire understanding of the parties hereto with respect to the subject matter hereof and of the Test Report, and no modification, variance or extrapolation with respect thereto shall be permitted without the prior written consent of the Company.

5. The names, service marks, trademarks and copyrights of the Company and its affiliates, including the names "BUREAU VERITAS," "BUREAU VERITAS CONSUMER PRODUCTS SERVICES," "BVCPS", "MTL", "ACTS", "MTL-ACTS" and CURTIS-STRAUS (collectively, the "Marks") are and shall remain the sole property of the Company or its affiliates and shall not be used by Client except solely to the extent that Client obtains the prior written approval of the Company and then only in the manner prescribed by the Company. Client shall not contest the validity of the Marks or take any action that might impair the value or goodwill associated with the Marks or the image or reputation of the Company or its affiliates.

6. Payment in full shall be due 30 days after the date of invoice. Interest shall be due on overdue amounts from the due date until paid at an interest rate of 1.5% per month or, if less, the maximum rate permitted by law. The Company reserves the right, at any time and from time to time, to revoke any credit extended to Client. Client shall reimburse the Company for any costs it incurs in collecting past due amounts, including court costs and fees and expenses of attorneys and collection agencies. The Test Report may not be used or relied upon by Client if and for so long as Client fails to pay when due any invoice issued by the Company or any affiliate of it to Client or any affiliate or subsidiary of Client together with interest and penalties, if any, accrued thereon.

The Company disclaims any and all responsibility or liability arising out of or in connection with e-mail transmissions of such information.
 Client understands and agrees that the Company is neither an insurer nor a guarantor, that the Company does not take the place of Client or any designer, manufacturer, agent, buyer, distributor or transportation or shipping company, and that the Company disclaims all liability in such capacities. Client further understands that if it seeks assurance against loss or damage, it should obtain appropriate insurance.
 Client agrees that the Company, by providing the services, does not take the place of Client nor any third party, nor does the Company release them from any of their obligations, nor does the Company otherwise assume, abridge, abrogate or undertake to discharge any duty of any third party to Client or any third party to any other third party, and Client will not release any third party from its obligations and duties with respect to the tested goods.

10. Client shall, on a timely basis, (a) provide adequate instructions to the Company in order to enable the Company to perform properly its services, (b) provide, or cause Client's suppliers and contractors to provide, the Company with all documents necessary to enable the Company to perform its services, (c) furnish the Company with all relevant information regarding Client's intended use and purposes of the tested goods, (d) advise the Company of essential dates and deadlines relevant to the tested goods and (e) fully exercise all rights and remedies available to Client against third parties in respect of the tested goods.

11. The Company shall undertake due care and ordinary skill in the performance of its services to Client, and the Company shall accept responsibility only were such skill has not been exercised and, even in such event, only to the extent of the limitation of liability set forth herein.

12. If Client desires to assert a claim arising from or relating to (i) the performance, purported performance or non-performance of any services by the Company or (ii) the sale, resale, manufacture, distribution or use of any tested goods, it must submit that claim to the Company in a writing that sets forth with particularity the basis for such claim within 60 days from discovery of the potential claim and not more than six months after the date of issuance of the Test Report to Client. Client waives any and all such claims including, without limitation, claims that the Test Report is inaccurate, incomplete or misleading or that additional or different testing is required, unless and then only to the extent that Client submits a written claim to the Company within both such time periods.

13. CLIÉNT SHALL, EXCEPT TO THE EXTENT OF COMPANY'S LIABILITY TO CLIENT HEREUNDER (WHICH IN NO EVENT SHALL EXCEED THE LIMITATION OF LIABILITY HEREIN), HOLD HARMLESS AND INDEMNIFY THE COMPANY, ITS AFFILIATES AND THEIR RESPECTIVE DIRECTORS, OFFICERS, EMPLOYEES, AGENTS AND SUBCONTRACTORS AGAINST ALL ACTUAL OR ALLEGED THIRD PARTY CLAIMS FOR LOSS, DAMAGE OR EXPENSE OF WHATSOEVER NATURE AND HOWSOEVER ARISING FROM OR RELATING TO (i) THE PERFORMANCE, PURPORTED PERFORMANCE OR NON-PERFORMANCE OF ANY TESTED GOODS. 14. EXCEPT AS MAY OTHERWISE BE EXPRESSLY AGREED TO IN WRITING BY THE COMPANY AND NOTWITHSTANDING ANY

14. EXCEPT AS MAY OTHERWISE BE EXPRESSLY AGREED TO IN WRITING BY THE COMPANY AND NOTWITHSTANDING ANY PROVISION TO THE CONTRARY CONTAINED HEREIN OR IN ANY TEST REPORT, NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR USE, IS MADE.





page 13 of 14

15. (A) IN NO EVENT WHATSOEVER SHALL THE COMPANY BE LIABLE FOR ANY CONSEQUENTIAL, SPECIAL, INCIDENTAL, EXEMPLARY OR PUNITIVE DAMAGES IN CONNECTION WITH, RELATING TO OR ARISING OUT OF THE TEST REPORT OR THE SERVICES PROVIDED BY THE COMPANY HEREUNDER, INCLUDING WITHOUT LIMITATION LOSS OF OR DAMAGE TO PROPERTY; LOSS OF INCOME, PROFIT OR USE; OR ANY CLAIMS OR DEMANDS MADE AGAINST CLIENT OR ANY OTHER PERSON BY ANY THIRD PARTY IN CONNECTION WITH, RELATING TO OR ARISING OUT OF THE SERVICES PROVIDED BY THE COMPANY HEREUNDER.

(B)NOTWITHSTANDING ANY PROVISION TO THE CONTRARY CONTAINED HEREIN, AND IN RECOGNITION OF THE RELATIVE RISKS AND BENEFITS TO CLIENT AND THE COMPANY ASSOCIATED WITH THE TESTING SERVICES CONTEMPLATED HEREBY, THE RISKS HAVE BEEN ALLOCATED SUCH THAT UNDER NO CIRCUMSTANCES WHATSOEVER SHALL THE LIABILITY OF THE COMPANY TO CLIENT OR ANY THIRD PARTY IN RESPECT OF ANY CLAIM FOR LOSS, DAMAGE OR EXPENSE, OF WHATSOEVER NATURE OR MAGNITUDE, AND HOWSOEVER ARISING, EXCEED AN AMOUNT EQUAL TO FIVE (5) TIMES THE AMOUNT OF THE FEES PAID TO THE COMPANY FOR THE SPECIFIC SERVICES WHICH GAVE RISE TO SUCH CLAIM OR U.S.\$10,000, WHICHEVER IS THE LESSER AMOUNT.

16. The Company shall not be liable for any loss or damage resulting from any delay or failure in performance of its obligations hereunder resulting directly or indirectly from any event of force majeure or any event outside the control of the Company. If any such event occurs, the Company may immediately cancel or suspend its performance hereunder without incurring any liability whatsoever to Client.

17. Company's services, including these Conditions, shall be governed by, and construed in accordance with, the local laws of the country where the Company performs the tests or, in the case of tests performed in the United States of America, the laws of Massachusetts without regard to conflicts of laws principles. If any aspect(s) of these Conditions is found to be illegal or unenforceable, the validity, legality and enforceability of all remaining aspects of these Conditions shall not in any way be affected or impaired thereby. Any proceeding related to the subject matter hereof shall be brought, if at all, in the courts of the country where the Company performs the tests or, in the case of tests performed in the United States of America, in the courts of Massachusetts. Client waives the right to interpose any counterclaim or setoffs of any litigation arising hereunder.

The complete list of the Approved Subcontractors Curtis-Straus may use to delegate the performance of work can be provided upon request. Rev.160009121(2)_#684340 v14CS





page 14 of 14