



Excellence in Compliance Testing

## **Certification Test Report**

**FCC ID: U4A-SCYPROX5**

**IC: 6982A-SCYPROX5**

**FCC Rule Part: 15.249**

**IC Radio Standards Specification: RSS-210**

**ACS Report Number: 12-0305.W06.2A**

Manufacturer: Assa Abloy

Model: C2-PA/PK

Test Begin Date: July 25, 2012

Test End Date: July 26, 2012

Report Issue Date: August 10, 2012



FOR THE SCOPE OF ACCREDITATION UNDER LAB Code 200612-0

This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

Reviewed by:

**Kirby Munroe**

**Director, Wireless Certifications**

**ACS, Inc.**

This test report shall not be reproduced except in full. This report may be reproduced in part with prior written consent of ACS, Inc. The results contained in this report are representative of the sample(s) submitted for evaluation.

**This report contains 14 pages**

# TABLE OF CONTENTS

<b>1</b>	<b>GENERAL .....</b>	<b>3</b>
1.1	PURPOSE.....	3
1.2	PRODUCT DESCRIPTION .....	3
1.3	TEST METHODOLOGY AND CONSIDERATIONS .....	3
<b>2</b>	<b>TEST FACILITIES.....</b>	<b>4</b>
2.1	LOCATION .....	4
2.2	LABORATORY ACCREDITATIONS/RECOGNITIONS/CERTIFICATIONS .....	4
2.3	RADIATED EMISSIONS TEST SITE DESCRIPTION .....	5
2.3.1	<i>Semi-Anechoic Chamber Test Site</i> .....	5
2.3.2	<i>Open Area Tests Site (OATS)</i> .....	6
2.4	CONDUCTED EMISSIONS TEST SITE DESCRIPTION .....	7
<b>3</b>	<b>APPLICABLE STANDARD REFERENCES.....</b>	<b>7</b>
<b>4</b>	<b>LIST OF TEST EQUIPMENT.....</b>	<b>8</b>
<b>5</b>	<b>SUPPORT EQUIPMENT.....</b>	<b>9</b>
<b>6</b>	<b>EQUIPMENT UNDER TEST SETUP BLOCK DIAGRAM .....</b>	<b>9</b>
<b>7</b>	<b>SUMMARY OF TESTS.....</b>	<b>10</b>
7.1	ANTENNA REQUIREMENT – FCC: SECTION 15.203 .....	10
7.2	POWER LINE CONDUCTED EMISSIONS – FCC: SECTION 15.207 IC: RSS-GEN 7.2.4.....	10
7.2.1	<i>Measurement Procedure</i> .....	10
7.3	20dB / 99% BANDWIDTH – FCC: SECTION 15.215, IC: RSS-GEN 4.6.1 .....	10
7.3.1	<i>Measurement Procedure</i> .....	10
7.3.2	<i>Measurement Results</i> .....	10
7.4	FUNDAMENTAL FIELD STRENGTH – FCC: SECTION 15.249(A) IC: RSS-210 A2.9(A) .....	12
7.4.1	<i>Measurement Procedure</i> .....	12
7.4.2	<i>Measurement Results</i> .....	12
7.5	RADIATED SPURIOUS EMISSIONS - FCC: SECTION 15.249(A)(D)(E); IC:RSS-210 A2.9(A)(B).....	13
7.5.1	<i>Measurement Procedure</i> .....	13
7.5.2	<i>Measurement Results</i> .....	13
7.5.3	<i>Sample Calculation:</i> .....	14
<b>8</b>	<b>CONCLUSION.....</b>	<b>14</b>

**1 GENERAL****1.1 Purpose**

The purpose of this report is to demonstrate compliance with Part 15 Subpart C of the FCC's Code of Federal Regulations and Industry Canada's Radio Standards Specification RSS-210.

**1.2 Product description**

The C2-PA/PK is a microprocessor controlled networked lock. It uses local wireless communication between the lock and a hub to connect to an access control system. The C2-PA/PK includes a 125kHz proximity reader and a 2.4GHz IEEE 802.15.4 radio.

The report applies to the 2.4GHz IEEE 802.15.4 radio only. A separate test report covers the 125kHz proximity radio operation.

**Technical Information:**

Band of Operation: 2405 – 2480 MHz

Number of Channels: 16

Modulation Format: O-QPSK

Antenna Type/Gain: Chip Antenna, 0.5dBi Gain

Operating Voltage: 9 VDC (Battery)

**Manufacturer Information:**

Assa Abloy Inc.

110 Sargent Dr.

New Haven, CT 06511

Test Sample Serial Number(s): ACS#2

Test Sample Condition: The test samples were provided in good working order with no visible defects.

**1.3 Test Methodology and Considerations**

The EUT was tested in an orientation of typical installation. No deviations from the standards were made or special considerations applicable.

## **2 TEST FACILITIES**

### **2.1 Location**

The radiated and conducted emissions test sites are located at the following address:

Advanced Compliance Solutions  
5015 B.U. Bowman Drive  
Buford, GA 30518  
Phone: (770) 831-8048  
Fax: (770) 831-8598

### **2.2 Laboratory Accreditations/Recognitions/Certifications**

ACS is accredited to ISO/IEC 17025 by the National Institute of Standards and Technology under their National Voluntary Laboratory Accreditation Program (NVLAP), Lab Code 200612-0. Unless otherwise specified, all tests methods described within this report are covered under the ISO/IEC 17025 scope of accreditation.

The Semi-Anechoic Chamber Test Site, Open Area Test Site (OATS) and Conducted Emissions Site have been fully described, submitted to, and accepted by the FCC, Industry Canada and the Japanese Voluntary Control Council for Interference by information technology equipment.

FCC Registration Number: 511277  
Industry Canada Lab Code: 4175A-1  
VCCI Member Number: 1831

- VCCI OATS Registration Number R-1526
- VCCI Conducted Emissions Site Registration Number: C-1608

### 2.3 Radiated Emissions Test Site Description

#### 2.3.1 Semi-Anechoic Chamber Test Site

The Semi-Anechoic Chamber Test Site consists of a 20' x 30' x 18' shielded enclosure. The chamber is lined with Toyo Ferrite Grid Absorber, model number FFG-1000. The ferrite tile grid is 101 x 101 x 19mm thick and weighs approximately 550 grams. These tiles are mounted on steel panels and installed directly on the inner walls of the chamber.

The turntable is 150cm in diameter and is located 160cm from the back wall of the chamber. The chamber is grounded via 1 - 8' copper ground rod, installed at the center of the back wall, it is bound to the ground plane using 3/4" stainless steel braided cable.

The turntable is all steel, flush mounted table installed in an all steel frame. The table is remotely operated from inside the control room located 25' from the range. The turntable is electrically bonded to the surrounding ground plane via steel fingers installed on the edge of the turn table. The steel fingers make constant contact with the ground plane during operation.

Behind the turntable is a 3' x 6' x 4' deep shielded pit used for support equipment if necessary. The pit is equipped with 1 - 4" PVC chases from the turntable to the pit that allow for cabling to the EUT if necessary. The underside of the turntable can be accessed from the pit so cables can be supplied to the EUT from the pit.

A diagram of the Semi-Anechoic Chamber Test Site is shown in Figure 2.3-1 below:




Figure 2.3-1: Semi-Anechoic Chamber Test Site

**2.3.2 Open Area Tests Site (OATS)**


The open area test site consists of a 40' x 66' concrete pad covered with a perforated electro-plated galvanized sheet metal. The perforations in the sheet metal are 1/8" holes that are staggered every 3/16". The individual sheets are placed to overlap each other by 1/4" and are riveted together to provide a continuous seam. Rivets are spaced every 3" in a 3 x 20 meter perimeter around the antenna mast and EUT area. Rivets in the remaining area are spaced as necessary to properly secure the ground plane and maintain the electrical continuity.

The entire ground plane extends 12' beyond the turntable edge and 16' beyond the antenna mast when set to a 10 meter measurement distance. The ground plane is grounded via 4 - 8' copper ground rods, each installed at a corner of the ground plane and bound to the ground plane using 3/4" stainless steel braided cable.

The turntable is an all aluminum 10' flush mounted table installed in an all aluminum frame. The table is remotely operated from inside the control room located 40' from the range. The turntable is electrically bonded to the surrounding ground plane via steel fingers installed on the edge of the turn table. The steel fingers make constant contact with the ground plane during operation.

Adjacent to the turntable is a 7' x 7' square and 4' deep concrete pit used for support equipment if necessary. The pit is equipped with 5 - 4" PVC chases from the pit to the control room that allow for cabling to the EUT if necessary. The underside of the turntable can be accessed from the pit so cables can be supplied to the EUT from the pit. The pit is covered with 2 sheets of 1/4" diamond style re-enforced steel sheets. The sheets are painted to match the perforated steel ground plane; however the underside edges have been masked off to maintain the electrical continuity of the ground plane. All reflecting objects are located outside of the ellipse defined in ANSI C63.4.

A diagram of the Open Area Test Site is shown in Figure 2.3-2 below:



**Figure 2.3-2: Open Area Test Site**

## 2.4 Conducted Emissions Test Site Description

The AC mains conducted EMI site is located in the main EMC lab. It consists of an 8' x 8' solid aluminum horizontal ground reference plane (GRP) bonded every 3" to an 8' X 8' vertical ground plane.

The site is of sufficient size to test table top and floor standing equipment in accordance with section 6.1.4 of ANSI C63.4.

A diagram of the room is shown below in figure 4.1.3-1:




Figure 2.4-1: AC Mains Conducted EMI Site

## 3 APPLICABLE STANDARD REFERENCES

The following standards were used:

- ❖ ANSI C63.4-2003: Method of Measurements of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the 9KHz to 40GHz
- ❖ US Code of Federal Regulations (CFR): Title 47, Part 2, Subpart J: Equipment Authorization Procedures, 2012
- ❖ US Code of Federal Regulations (CFR): Title 47, Part 15, Subpart C: Radio Frequency Devices, Intentional Radiators, 2012
- ❖ Industry Canada Radio Standards Specification: RSS-210 - Low-power License-exempt Radiocommunication Devices (All Frequency Bands): Category I Equipment, Issue 8, December 2010
- ❖ Industry Canada Radio Standards Specification: RSS-GEN – General Requirements and Information for the Certification of Radiocommunication Equipment, Issue 3, December 2010.

#### 4 LIST OF TEST EQUIPMENT

The calibration interval of test equipment is annually or the manufacturer's recommendations. Where the calibration interval deviates from the annual cycle based on the instrument manufacturer's recommendations, it shall be stated below.

**Table 4-1: Test Equipment**

AssetID	Manufacturer	Model #	Equipment Type	Serial #	Last Calibration Date	Calibration Due Date
1	Rohde & Schwarz	ESMI - Display	Spectrum Analyzers	833771/007	9/23/2010	9/23/2012
2	Rohde & Schwarz	ESMI-Receiver	Spectrum Analyzers	839587/003	9/23/2010	9/23/2012
30	Spectrum Technologies	DRH-0118	Antennas	970102	4/27/2011	4/27/2013
41	Electro-Metrics	BIA-25	Antennas	2925	12/21/2010	12/21/2012
73	Agilent	8447D	Amplifiers	2727A05624	9/30/2011	9/30/2012
167	ACS	Chamber EMI Cable Set	Cable Set	167	12/21/2011	12/21/2012
283	Rohde & Schwarz	FSP40	Spectrum Analyzers	1000033	8/26/2011	8/26/2012
291	Florida RF Cables	SMRE-200W-12.0- SMRE	Cables	None	12/2/2011	12/2/2012
292	Florida RF Cables	SMR-290AW- 480.0-SMR	Cables	None	4/2/2012	4/2/2013
334	Rohde&Schwarz	3160-09	Antennas	49404	11/4/2010	NCR
335	Suhner	SF-102A	Cables	882/2A	8/29/2011	8/29/2012
338	Hewlett Packard	8449B	Amplifiers	3008A01111	3/1/2012	8/31/2012
345	Suhner Sucoflex	102A	Cables	1077/2A	8/29/2011	8/29/2012
412	Electro Metrics	LPA-25	Antennas	1241	7/28/2010	7/28/2012
422	Florida RF	SMS-200AW-72.0- SMR	Cables	805	12/2/2011	12/2/2012
432	Microwave Circuits	H3G020G4	Filters	264066	7/2/2012	7/2/2013




5 SUPPORT EQUIPMENT

Table 5-1: Support Equipment

Item	Equipment Type	Manufacturer	Model Number	Serial Number
The EUT operates stand alone therefore no support equipment was utilized.				

6 EQUIPMENT UNDER TEST SETUP BLOCK DIAGRAM



**7 SUMMARY OF TESTS**

Along with the tabular data shown below, plots were taken of all signals deemed important enough to document.

**7.1 Antenna Requirement – FCC: Section 15.203**

The antenna used for the C2-PA/PK is an integral chip antenna with 0.5dBi gain, which therefore meets the requirements of Section 15.203.

**7.2 Power Line Conducted Emissions – FCC: Section 15.207 IC: RSS-Gen 7.2.4****7.2.1 Measurement Procedure**

The EUT is a battery operated device therefore AC power line conducted emissions is not applicable.

**7.3 20dB / 99% Bandwidth – FCC: Section 15.215, IC: RSS-Gen 4.6.1****7.3.1 Measurement Procedure**

The span of the spectrum analyzer display was set between two times and five times the occupied bandwidth (OBW) of the emission. The RBW of the spectrum analyzer was set to approximately 1 % to 5 % of the OBW. The trace was set to max hold with a peak detector active. The Delta function of the analyzer was utilized to determine the 20 dB bandwidth of the emission.

The occupied bandwidth measurement function of the analyzer was used for the 99% bandwidth. The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts. The resolution bandwidth shall be set to as close to 1% of the selected span as is possible without being below 1%. The video bandwidth shall be set to 3 times the resolution bandwidth. A sampling detector was used.

**7.3.2 Measurement Results**

Results are shown below in table 7.3.2-1 and figure 7.3.2-1 to 7.3.2-6:

**Table 7.3.2-1: 20dB / 99% Bandwidth**

<b>Frequency [MHz]</b>	<b>20dB Bandwidth [MHz]</b>	<b>99% Bandwidth [MHz]</b>
2405	2.44	2.46
2440	2.54	2.44
2480	2.54	2.46




Figure 7.3.2-1: 20dB Bandwidth Plot – 2405MHz




Figure 7.3.2-2: 20dB Bandwidth Plot – 2440MHz




Figure 7.3.2-3: 20dB Bandwidth Plot – 2480MHz




Figure 7.3.2-4: 99% Bandwidth Plot – 2405MHz




Figure 7.3.2-5: 99% Bandwidth Plot – 2440MHz




Figure 7.3.2-6: 99% Bandwidth Plot – 2480MHz

**7.4 Fundamental Field Strength – FCC: Section 15.249(a) IC: RSS-210 A2.9(a)****7.4.1 Measurement Procedure**

The EUT was rotated through 360° and the receive antenna height was varied from 1m to 4m so that the maximum radiated emissions level would be detected. Peak and average measurements were made using a resolution bandwidth (RBW) of 3 MHz and a video bandwidth (VBW) of 10 MHz. RBW >> EBW.

**7.4.2 Measurement Results**

Results are shown below in Table 7.4.2-1.

**Table 7.4.2-1: Fundamental Field Strength**

Frequency (MHz)	Level (dBuV)		Antenna Polarity (H/V)	Correction Factors (dB)	Corrected Level (dBuV/m)		Limit (dBuV/m)		Margin (dB)	
	pk	Qpk/Avg			pk	Qpk/Avg	pk	Qpk/Avg	pk	Qpk/Avg
2405	82.94	77.41	H	-5.40	77.54	72.01	114.0	94.0	36.5	22.0
2405	96.67	90.68	V	-5.40	91.27	85.28	114.0	94.0	22.7	8.7
2440	90.12	84.51	H	-5.25	84.87	79.26	114.0	94.0	29.1	14.7
2440	95.51	89.62	V	-5.25	90.26	84.37	114.0	94.0	23.7	9.6
2480	84.59	78.68	H	-5.08	79.51	73.60	114.0	94.0	34.5	20.4
2480	90.05	84.51	V	-5.08	84.97	79.43	114.0	94.0	29.0	14.6

**7.5 Radiated Spurious Emissions - FCC: Section 15.249(a)(d)(e); IC:RSS-210 A2.9(a)(b)**

**7.5.1 Measurement Procedure**

Radiated emissions tests were made over the frequency range of 30MHz to 25 GHz, 10 times the highest fundamental frequency.

The EUT was rotated through 360° and the receive antenna height was varied from 1m to 4m so that the maximum radiated emissions level would be detected. For frequencies below 1000MHz, quasi-peak measurements were made using a resolution bandwidth RBW of 120 kHz and a video bandwidth VBW of 300 kHz. For frequencies above 1000MHz, peak and average measurements were made with RBW and VBW of 1 MHz and 3 MHz respectively.

All out of band emissions were evaluated, including any emissions at or near the band-edge.

**7.5.2 Measurement Results**

Radiated spurious emissions found in the band of 30MHz to 25GHz are reported in the tables 7.5.2-1 to 7.5.2-3 below.

**Table 7.5.2-1: Radiated Spurious Emissions Tabulated Data – 2405MHz**

Frequency (MHz)	Level (dBuV)		Antenna Polarity (H/V)	Correction Factors (dB)	Corrected Level (dBuV/m)		Limit (dBuV/m)		Margin (dB)	
	pk	Qpk/Avg			pk	Qpk/Avg	pk	Qpk/Avg	pk	Qpk/Avg
2400	48.17	36.38	H	-5.42	42.75	30.96	74.0	54.0	31.3	23.0
2400	59.14	47.24	V	-5.42	53.72	41.82	74.0	54.0	20.3	12.2

**Table 7.5.3-2: Radiated Spurious Emissions Tabulated Data – 2440MHz**

Frequency (MHz)	Level (dBuV)		Antenna Polarity (H/V)	Correction Factors (dB)	Corrected Level (dBuV/m)		Limit (dBuV/m)		Margin (dB)	
	pk	Qpk/Avg			pk	Qpk/Avg	pk	Qpk/Avg	pk	Qpk/Avg
All measurements were below the noise floor.										

**Table 7.5.3-3: Radiated Spurious Emissions Tabulated Data – 2480MHz**

Frequency (MHz)	Level (dBuV)		Antenna Polarity (H/V)	Correction Factors (dB)	Corrected Level (dBuV/m)		Limit (dBuV/m)		Margin (dB)	
	pk	Qpk/Avg			pk	Qpk/Avg	pk	Qpk/Avg	pk	Qpk/Avg
2483.5	53.12	41.35	H	-5.07	48.05	36.28	74.0	54.0	25.9	17.7
2483.5	58.07	46.28	V	-5.07	53.00	41.21	74.0	54.0	21.0	12.8

**7.5.3 Sample Calculation:**

$$R_C = R_U + CF_T$$

Where:

$CF_T$	=	Total Correction Factor (AF+CA+AG)-DC (Average Measurements Only)
$R_U$	=	Uncorrected Reading
$R_C$	=	Corrected Level
AF	=	Antenna Factor
CA	=	Cable Attenuation
AG	=	Amplifier Gain
DC	=	Duty Cycle Correction Factor

**Example Calculation: Peak**

Corrected Level:  $48.17 - 5.42 = 42.75\text{dBuV}$

Margin:  $74\text{dBuV} - 42.75\text{dBuV} = 31.3\text{dB}$

**Example Calculation: Average**

Corrected Level:  $36.38 - 5.42 - 0 = 30.96\text{dBuV}$

Margin:  $54\text{dBuV} - 30.96\text{dBuV} = 23.0\text{dB}$

**8 CONCLUSION**

In the opinion of ACS, Inc. the C2-PA/PK, manufactured by Assa Abloy meet the requirements of FCC Part 15 subpart C and Industry Canada's Radio Standards Specification RSS-210.

**END REPORT**