

Test of: Datalogic S.p.A
Skorpio

To: OET Bulletin 65 supplement C

Appendix 4. Photographs

This appendix contains the following photographs:

Photo Reference Number	Title
PHT/48655JD09A/001	Test configuration for the measurement of Specific Absorption Rate (SAR)
PHT/48655JD09A/002	Front Of EUT Facing Phantom At 0mm Separation
PHT/48655JD09A/003	Rear Of EUT Facing Phantom At 0mm Separation
PHT/48655JD09A/004	Front View Of EUT
PHT/48655JD09A/005	Rear View Of EUT
PHT/48655JD09A/006	Internal View Of EUT
PHT/48655JD09A/007	Battery View
PHT/48655JD09A/008	2450 MHz Fluid View

Test of: Datalogic S.p.A
Skorpio

To: OET Bulletin 65 supplement C

PHT/48655JD09A/001: Test configuration for the measurement of Specific Absorption Rate (SAR)



Test of: Datalogic S.p.A
Skorpio

To: OET Bulletin 65 supplement C

PHT/48655JD09A/002: Front Of EUT Facing Phantom At 0mm Separation



Test of: Datalogic S.p.A
Skorpio

To: OET Bulletin 65 supplement C

PHT/48655JD09A/003: Rear Of EUT Facing Phantom At 0mm Separation



Test of: Datalogic S.p.A
Skorpio

To: OET Bulletin 65 supplement C

PHT/48655JD09A/004: Front View Of EUT



Test of: Datalogic S.p.A
Skorpio

To: OET Bulletin 65 supplement C

PHT/48655JD09A/005: Rear View Of EUT



Test of: Datalogic S.p.A
Skorpio

To: OET Bulletin 65 supplement C

PHT/48655JD09A/006: Internal View Of EUT



Test of: Datalogic S.p.A
Skorpio

To: OET Bulletin 65 supplement C

PHT/48655JD09A/007: Battery View



Test of: Datalogic S.p.A
Skorpio

To: OET Bulletin 65 supplement C

PHT/48655JD09A/008: 2450 MHz Fluid View



Test of: Datalogic S.p.A
Skorpio

To: OET Bulletin 65 supplement C

Appendix 5. Validation of System

Prior to the assessment, the system was verified in the flat region of the phantom.

A 2450 MHz dipole was used. A forward power of 250 mW was applied to the dipole and the system was verified to a tolerance of $\pm 5\%$ for the 2450 MHz dipole. The applicable verification (normalised to 1 Watt).

Date: 04 April 2007

Validation Dipole and Serial Number: D2450V2 / SN: 725

Simulant	Frequency (MHz)	Room Temperature (°C)	Liquid Temperature (°C)	Parameters	Target Value	Measured Value	Deviation (%)	Limit (%)
Body	2450	23.0	22.0	ϵ_r	52.70	53.09	0.73	± 5
				σ	1.95	2.04	4.77	± 5
				1g SAR	53.30	53.60	0.56	± 5

Test of: Datalogic S.p.A
Skorpio

To: OET Bulletin 65 supplement C

Appendix 6. Simulated Tissues

The body mixture consists of water and glycol. Visual inspection is made to ensure air bubbles are not trapped during the mixing process. The mixture is calibrated to obtain proper dielectric constant (permittivity) and conductivity of the tissue.

Ingredient	Frequency
	2450 MHz Body
De-Ionised Water	68.64 %
Diglycol Butyl Ether (DGBE)	31.37 %

Test of: Datalogic S.p.A
Skorpio

To: OET Bulletin 65 supplement C

Appendix 7. DASY4 System Details

A.7.1. DASY4 SAR Measurement System

RFI Global Services Ltd, SAR measurement facility utilises the Dosimetric Assessment System (DASY™) manufactured by Schmid & Partner Engineering AG (SPEAG™) of Zurich, Switzerland. The DASY4 system is comprised of the robot controller, computer, near-field probe, probe alignment sensor, and the SAM phantom containing brain or muscle equivalent material. The robot is a six-axis industrial robot performing precise movements to position the probe to the location (points) of maximum electromagnetic field (EMF). A cell controller system contains the power supply, robot controller; teach pendant (Joystick), and remote control. This is used to drive the robot motors. The Staubli robot is connected to the cell controller to allow software manipulation of the robot. The data acquisition electronics (DAE) performs signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection etc. The DAE is connected to the Electro-optical coupler (EOC). The EOC performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC plug-in card. The DAE3 utilises a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16-bit AD-converter and a command decoder and control logic unit. Transmission to the PC-card is accomplished through an optical downlink for data and status information and an optical uplink for commands and clock lines. The mechanical probe-mounting device includes two different sensor systems for frontal and sidewise probe contacts. They are also used for mechanical surface detection and probe collision detection. The robot uses its own controller with a built in VME-bus computer.

Test of: Datalogic S.p.A
Skorpio

To: OET Bulletin 65 supplement C

A.7.2. DASY4 SAR System Specifications

Robot System

Positioner:	Stäubli Unimation Corp. Robot Model: RX90L
Repeatability:	0.025 mm
No. of Axis:	6
Serial Number:	F00/SD89A1/A/01
Reach:	1185 mm
Payload:	3.5 kg
Control Unit:	CS7
Programming Language:	V+

Data Acquisition Electronic (DAE) System

DAE3	SN: 394
------	---------

Cell Controller

PC:	Dell Precision 340
Operating System:	Windows 2000
Data Card:	DASY4 Measurement Server
Serial Number:	1080

Data Converter

Features:	Signal Amplifier, multiplexer, A/D converted and control logic.
Software:	DASY4 Software
Connecting Lines:	Optical downlink for data and status info. Optical uplink for commands and clock.

PC Interface Card

Function:	24 bit (64 MHz) DSP for real time processing Link to DAE3 16 nit A/D converter for surface detection system serial link to robot direct emergency stop output for robot.
-----------	--

Test of: Datalogic S.p.A
Skorpio

To: OET Bulletin 65 supplement C

DASY4 SAR System Specifications (Continued)

E-Field Probe

Model:	ET3DV6
Serial No:	1528
Construction:	Triangular core fibre optic detection system
Frequency:	10 MHz to 3 GHz
Linearity:	± 0.2 dB (30 MHz to 3 GHz)
Probe Length (mm):	337
Probe Diameter (mm):	12
Tip Length (mm):	10
Tip Diameter (mm):	6.8
Sensor X Offset (mm):	2.7
Sensor Y Offset (mm):	2.7
Sensor Z Offset (mm):	2.7

Phantom

Phantom:	SAM Phantom
Shell Material:	Fibreglass
Thickness:	2.0 \pm 0.1 mm

**Test of: Datalogic S.p.A
Skorpio**

To: OET Bulletin 65 supplement C

This page has been left intentionally blank.
