



# TEST REPORT

No. I20D00140-SAR01

*For*

**Client: Datalogic S.r.l.**

**Production: Smartphone**

**Model Name: MEMOR 10**

**Brand Name: Datalogic**

**FCC ID: U4GDL35US**

**Hardware Version: V00 (US)**

**Software Version: 2.05.07.20190919**

**Issued date: 2020-10-16**

## NOTE

1. The test results in this test report relate only to the devices specified in this report.
2. This report shall not be reproduced except in full without the written approval of East China Institute of Telecommunications.
3. KDB has not been approved by A2LA.
4. It has been confirmed with the customer that the Tune-up Power information provided by the customer may affect the validity of the measurement results in this report, and the impact and consequences will be borne by the customer.
5. For the test results, the uncertainty of measurement is not taken into account when judging the compliance with specification, and the results of measurement or the average value of measurement results are taken as the criterion of the compliance with specification directly.

**Test Laboratory:**

East China Institute of Telecommunications

Add: Building 4, No. 766, Jingang Road, Pudong, Shanghai, P. R. China

Tel: +86 21 63843300

FAX: +86 21 63843301

E-Mail: [welcome@ecit.org.cn](mailto:welcome@ecit.org.cn)

**Revision Version**

<b>Report Number</b>	<b>Revision</b>	<b>Date</b>	<b>Memo</b>
I20D00140-SAR01	00	2020-10-16	Initial creation of test report

## CONTENTS

<b>1. TEST LABORATORY</b> .....	<b>7</b>
<b>1.1. TESTING LOCATION</b> .....	<b>7</b>
<b>1.2. TESTING ENVIRONMENT</b> .....	<b>7</b>
<b>1.3. PROJECT DATA</b> .....	<b>7</b>
<b>1.4. SIGNATURE</b> .....	<b>7</b>
<b>2. CLIENT INFORMATION</b> .....	<b>8</b>
<b>2.1. APPLICANT INFORMATION</b> .....	<b>8</b>
<b>2.2. MANUFACTURER INFORMATION</b> .....	<b>8</b>
<b>3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)</b> .....	<b>9</b>
<b>3.1. ABOUT EUT</b> .....	<b>9</b>
<b>3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST</b> .....	<b>11</b>
<b>3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST</b> .....	<b>11</b>
<b>4. REFERENCE DOCUMENTS</b> .....	<b>12</b>
<b>4.1. DOCUMENTS SUPPLIED BY APPLICANT</b> .....	<b>12</b>
<b>4.2. REFERENCE DOCUMENTS</b> .....	<b>12</b>
<b>4.3. CRITERION</b> .....	<b>12</b>
<b>5. TEST SUMMARY AND STATEMENT OF COMPLIANCE</b> .....	<b>13</b>
<b>5.1. TEST SUMMARY</b> .....	<b>13</b>
<b>5.2. STATEMENT OF COMPLIANCE</b> .....	<b>15</b>
<b>6. SPECIFIC ABSORPTION RATE (SAR)</b> .....	<b>16</b>
<b>6.1. INTRODUCTION</b> .....	<b>16</b>
<b>6.2. SAR DEFINITION</b> .....	<b>16</b>
<b>7. SAR MEASUREMENT SYSTEM INTRODUCTION</b> .....	<b>17</b>
<b>7.1. MEASUREMENT SET-UP</b> .....	<b>17</b>
<b>7.2. E-FIELD PROBE SYSTEM</b> .....	<b>18</b>

7.3.	E-FIELD PROBE CALIBRATION.....	18
7.4.	OTHER TEST EQUIPMENT .....	20
8.	TEST POSITION IN RELATION TO THE PHANTOM.....	23
8.1.	GENERAL CONSIDERATIONS .....	23
8.2.	BODY-WORN DEVICE .....	24
8.3.	DESKTOP DEVICE .....	24
9.	TISSUE SIMULATING LIQUIDS.....	25
9.1.	EQUIVALENT TISSUES COMPOSITION.....	25
9.2.	DIELECTRIC PERFORMANCE OF TSL .....	26
10...	SYSTEM VALIDATION.....	27
10.1.	SYSTEM VALIDATION .....	27
10.2.	SYSTEM SETUP .....	27
10.3.	SYSTEM VALIDATION RESULT.....	27
11...	MEASUREMENT PROCEDURES .....	28
11.1.	TEST STEPS.....	28
11.2.	SPATIAL PEAK SAR EVALUATION.....	29
11.3.	GENERAL MEASUREMENT PROCEDURE .....	30
11.4.	WCDMA MEASUREMENT PROCEDURES .....	31
11.5.	LTE MEASUREMENT PROCEDURE .....	32
11.6.	BLUETOOTH & WIFI MEASUREMENT PROCEDURES.....	33
12...	SIMULTANEOUS TRANSMISSION SAR CONSIDERATIONS .....	34
12.1.	REFERENCE DOCUMENT .....	34
12.2.	SAR MEASUREMENT POSITIONS.....	34
12.3.	LOW POWER TRANSMITTERS SAR CONSIDERATION .....	34
12.4.	SIMULTANEOUS TRANSMISSION ANALYSIS .....	34
12.5.	SIMULTANEOUS TRANSMISSION TABLE .....	35

<b>13... CONDUCTED OUTPUT POWER .....</b>	<b>36</b>
<b>13.1. MANUFACTURING TOLERANCE .....</b>	<b>36</b>
<b>13.2. GSM MEASUREMENT RESULT .....</b>	<b>43</b>
<b>13.3. WCDMA MEASUREMENT RESULT .....</b>	<b>45</b>
<b>13.4. LTE MEASUREMENT RESULT .....</b>	<b>46</b>
<b>13.5. WIFI AND BT MEASUREMENT RESULT .....</b>	<b>65</b>
<b>13.6. CDMA MEASUREMENT RESULT .....</b>	<b>68</b>
<b>14.SAR MEASUREMENT RESULT .....</b>	<b>69</b>
<b>14.1. STANDALONE SAR TEST RESULT FOR I19D00137-SAR01 .....</b>	<b>69</b>
<b>14.2. STANDALONE SAR TEST RESULT FOR I20D00140-SAR01 .....</b>	<b>72</b>
<b>14.3. SIMULTANEOUS SAR EVALUATION .....</b>	<b>73</b>
<b>14.4. SAR MEASUREMENT VARIABILITY .....</b>	<b>76</b>
<b>16.TEST EQUIPMENT UTILIZED .....</b>	<b>77</b>
<b>17.MEASUREMENT UNCERTAINTY .....</b>	<b>78</b>
<b>ANNEX A. GRAPH RESULTS .....</b>	<b>80</b>
<b>ANNEX B. SYSTEM VALIDATION PLOT .....</b>	<b>81</b>
<b>ANNEX C. CALIBRATION CERTIFICATION .....</b>	<b>82</b>
<b>ANNEX D. ACCREDITATION CERTIFICATION .....</b>	<b>103</b>

## 1. Test Laboratory

### 1.1. Testing Location

Company Name	East China Institute of Telecommunications
Address	Building 4, No. 766, Jingang Road, Pudong, Shanghai, P. R. China
Postal Code	201206
Telephone	+86 21 63843300
Fax	+86 21 63843301
FCC Designation No	CN1177

### 1.2. Testing Environment

Normal Temperature	18°C-25°C
Relative Humidity	25%RH-75%RH

### 1.3. Project Data

Project Leader	Chen Minfei
Testing Start Date	2020-10-13
Testing End Date	2020-10-13


### 1.4. Signature



**Gong Jiawei**  
(Prepared this test report)



**Yan Hang**  
(Reviewed this test report)



**Zheng Zhongbin**  
(Approved this test report)

## 2. Client Information

### 2.1. Applicant Information

Company Name	Datalogic S.r.l.
Address	Via San Vitalino no. 13, Calderara di Reno – 40012 (BO) - Italy
Telephone	+39 051 314 72 16
Postcode	N/A

### 2.2. Manufacturer Information

Company Name	Datalogic S.r.l.
Address	Via San Vitalino no. 13, Calderara di Reno – 40012 (BO) - Italy
Telephone	+39 051 314 72 16
Postcode	N/A



### 3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

#### 3.1. About EUT

Description:	Smartphone
Model Name:	MEMOR 10
Operation Model(s):	GSM850/GSM900/GSM1800/GSM1900 WCDMA Band I/Band II/Band IV/Band V/BandVIII LTE 2/4/5/7/12/13/17/25/26;CDMA BC0/BC1 BT4.2,BLE;WiFi 802.11a/b/g/n/ac GPS;GLONASS;Beidou;WLC
Tx Frequency:	824-849MHz(GSM850) 1850-1910MHz (GSM1900) 18520-1910 MHz (WCDMA Band II) 1710-1755 MHz (WCDMA Band IV) 824-849MHz (WCDMA Band V) 1850 -1910 MHz (LTE Band 2) 1710 -1755 MHz (LTE Band 4) 824 -849 MHz (LTE Band 5) 2500 – 2570 MHz (LTE Band 7) 699 -716 MHz (LTE Band 12) 777 -787 MHz (LTE Band 13) 704 -716 MHz (LTE Band 17) 1850 -1915 MHz (LTE Band 25) 814 -849 MHz (LTE Band 26) 824-849MHz(CDMA BC0) 1850-1910MHz(CDMA BC1) 2412- 2462 MHz (WiFi) 5150~5250 MHz(U-NII-1) 5250~5350 MHz(U-NII-2A) 5470~5725 MHz(U-NII-2C) 5745~5825 MHz(U-NII-3) 2402 – 2480 MHz (BT)
Test device Production Information:	Production unit
GPRS/EGPRS Class Mode:	B
GPRS/ EGPRS Multislot Class:	12
Device Type:	Portable device
Antenna Type:	Embedded antenna
Accessories/Body-worn Configurations:	Battery

Dimensions:	155x78x18.7mm
Hotspot Mode:	Support
<p>Note:</p> <p>LTE Band 2 is a sub-band of Band 25</p> <p>LTE Band 4 is a sub-band of Band 66</p> <p>LTE Band 5&amp;18&amp;19 is a sub-band of Band 26</p> <p>LTE Band 17 is a sub-band of Band 12</p> <p>LTE Band 38 is a sub-band of Band 41</p> <p>The EUT SAR Test without the charging battery cover is not applicable since no way to have this battery cover removed and replaced by normal battery cover.</p> <p>Photographs of EUT are shown in ANNEX C of this test report.</p>	

### 3.2. Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	SW Version	Date of receipt
N01	358328100030199	V00 (US)	2.05.07.20190919	2020-09-22
N02	359737090161724	V00 (US)	2.05.07.20190919	2020-09-22

\*EUT ID: is used to identify the test sample in the lab internally.

Note: The product has two SIM cards, SIM 1 and SIM 2 does not support simultaneous work, only supports a single transmitter; When SIM 1 is working, SIM 2 will be suspended until SIM 2 is selected. When stop using the SIM 1, SIM 2 would work. SIM1 is the worst case.

### 3.3. Internal Identification of AE used during the test

AE ID*	Description	Type	Manufacturer
BA01	Battery	--	Ten Pao
BA02	Battery	--	Ten Pao

\*AE ID: is used to identify the test sample in the lab internally.

## 4. Reference Documents

### 4.1. Documents supplied by applicant

All technical documents are supplied by the client or manufacturer, which is the basis of testing.

### 4.2. Reference Documents

The following documents listed in this section are referred for testing.

Reference	Title	Version
<b>ANSI C95.1</b>	IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.	<b>1999</b>
<b>IEEE 1528</b>	Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques.	<b>2013</b>
<b>KDB648474</b>	Handset SAR	<b>D04 v01r03</b>
<b>KDB648474</b>	Wireless Chargers Battery Cover	<b>D03 v01r04</b>
<b>KDB248227</b>	802 11 WiFi SAR	<b>D01 v02r02</b>
<b>KDB447498</b>	General RF Exposure Guidance	<b>D01 v06</b>
<b>KDB865664</b>	SAR Measurement 100 MHz to 6 GHz	<b>D01 v01r04</b>
<b>KDB865664</b>	RF Exposure Reporting	<b>D02 v01r02</b>
<b>KDB941225</b>	3G SAR Procedures	<b>D01 v03r01</b>
<b>KDB941225</b>	SAR for LTE Devices	<b>D05 v02r05</b>
<b>KDB941225</b>	Hotspot SAR	<b>D06 v02r01</b>
<b>KDB616217</b>	SAR for laptop and tablets	<b>D04 v01r02</b>

### 4.3. Criterion

At frequencies between 100 kHz and 6 GHz, the MPE (Maximum Permissible Exposure) in population/uncontrolled environments for electromagnetic field strengths may be exceeded if

- a) The exposure conditions can be shown by appropriate techniques to produce SARs below 0.08W/kg, as averaged over the whole body, and spatial peak SAR values not exceeding 1.6 W/kg, as averaged over any 1g of tissue (defined as a tissue volume in the shape of a cube), except for the hands, wrists, feet, and ankles where the spatial peak SAR shall not exceed 4 W/kg, as averaged over any 10g of tissue (defined as a tissue volume in the shape of a cube); and
- b) The induced currents in the body conform with the MPE in table 2, Part B in ANSI C95.1-1999.

## 5. Test Summary and Statement of Compliance

### 5.1. Test Summary

The maximum results of Specific Absorption Rate (SAR) in standalone mode are as follows.

**Table 5.1: Standalone Max. Reported SAR (1g)**

Band	SAR 1g(W/Kg)		
	Head	Body worn(10mm)	Hotspot(10mm)
GSM 850	0.248(Original)	0.607(Original)	0.607(Original)
GSM 1900	0.509(Original)	0.563(Original)	1.106(Original)
WCDMA Band2	0.313(Original)	0.478(Original)	0.526(Original)
WCDMA Band4	0.454(Original)	0.663(Original)	0.663(Original)
WCDMA Band5	0.210(Original)	0.293(Original)	0.293(Original)
CDMA BC0	0.278(Original)	0.441(Original)	0.441(Original)
CDMA BC1	0.412(Original)	0.715(Original)	<b>1.499(Original)</b>
LTE Band4	0.801(Original)	1.172(Original)	1.172(Original)
LTE Band5	0.226(Original)	0.324(Original)	0.324(Original)
LTE Band7	0.029(Original)	0.311(Original)	1.245(Original)
LTE Band12	0.165(Original)	0.225(Original)	0.225(Original)
LTE Band13	0.216(Original)	0.324(Original)	0.324(Original)
LTE Band25	0.507(Original)	0.787(Original)	1.283(Original)
LTE Band26	0.189(Original)	0.224(Original)	0.224(Original)
2.4G WiFi	0.357(Original)	0.340(Original)	0.491(Original)
5G WiFi	0.770(Original)	0.762(Original)	--

**Table 5.2: Standalone Max. Reported SAR (10g)**

Band	Position/Distance	SAR 10g (W/Kg)
GSM 850	Limb	1.851( Original )
GSM 1900	Limb	0.917( Original )
WCDMA Band2	Limb	1.063( Original )
WCDMA Band4	Limb	1.26(Original)
WCDMA Band5	Limb	0.742( Original )
CDMA BC0	Limb	1.187(Original)
CDMA BC1	Limb	1.993( Original )
LTE Band4	Limb	2.052(Original)
LTE Band5	Limb	0.732( Original )
LTE Band7	Limb	0.935( Original )
LTE Band12	Limb	0.484( Original )
LTE Band13	Limb	0.539( Original )

LTE Band25	Limb	1.647(Original)
LTE Band26	Limb	0.756( Original )
2.4G WiFi	Limb	0.964(Original)
5G WiFi	Limb	0.901(Original)

The maximum results of Specific Absorption Rate (SAR) in simultaneous mode are as follows.

**Table 5.2: Simultaneous Transmission SAR**

Highest SAR 1g(W/kg)		
Mode	Position	Highest SAR 1g(W/kg)
LTE B4&WIFI 5G	Head Side	1.548
LTE B4&WIFI 5G	Back Side (Body worn&Hotspot 10mm)	1.591
Highest SAR 10g(W/kg)		
Mode	Position	Highest SAR 10g(W/kg)
LTE B4&WIFI 2.4G	Bottom Side (Limb 0mm)	3.016

Note: The **MEMOR 10**, supporting GSM/WCDMA/LTE/WLAN, manufactured by **Datalogic S.r.l.** is a variant product for testing. According to the Product Change Description, SAR test is only required in worse case. Test data are reflected from test report **I19D00137-SAR01**, which is the test report for the initial product.

## 5.2. Statement of Compliance

The **MEMOR 10** manufactured by **Datalogic S.r.l.** is a parent model for testing.

ECIT has verified that the compliance of the tested device specified in section 3 of this test report is successfully evaluated according to the procedure and test methods as defined in type certification requirement listed in section 4 of this test report.

For body worn operation mode, this device with any accessory that contained in this report has been tested and the values meet FCC RF exposure guidelines. Use of other accessories may not ensure compliance with FCC RF exposure guidelines.

## 6. Specific Absorption Rate (SAR)

### 6.1. Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

### 6.2. SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy ( $dW$ ) absorbed by (dissipated in) an incremental mass ( $dm$ ) contained in a volume element ( $dv$ ) of a given density ( $\rho$ ). The equation description is as below:

$$SAR = \frac{d}{dt} \left( \frac{dW}{dm} \right) = \frac{d}{dt} \left( \frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be either related to the temperature elevation in tissue by

$$SAR = c \left( \frac{\delta T}{\delta t} \right)$$

Where:  $C$  is the specific heat capacity,  $\delta T$  is the temperature rise and  $\delta t$  is the exposure duration, or related to the electrical field in the tissue by

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where:

- $\sigma$  is the conductivity of the tissue
- $\rho$  is the mass density of tissue, which is normally set to  $1\text{g/cm}^3$
- $E$  is the RMS electrical field strength


However for evaluating SAR of low power transmitter, electrical field measurement is typically applied.



## 7. SAR Measurement System Introduction

### 7.1. Measurement Set-up

The DASY5 system for performing compliance tests is illustrated above graphically. This system consists of the following items:



**Picture 7-1 SAR Measurement Set-up**

- A standard high precision 6-axis robot (Stäubli TX=RX family) with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP and the DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

## 7.2. E-field Probe System

The SAR measurements were conducted with the dosimetric probe designed in the classical triangular configuration and optimized for dosimetric evaluation. The probe is constructed using the thick film technique; with printed resistive lines on ceramic substrates. The probe is equipped with an optical multi-fiber line ending at the front of the probe tip. It is connected to the EOC box on the robot arm and provides an automatic detection of the phantom surface. Half of the fibers are connected to a pulsed infrared transmitter, the other half to a synchronized receiver. As the probe approaches the surface, the reflection from the surface produces a coupling from the transmitting to the receiving fibers. This reflection increases first during the approach, reaches maximum and then decreases. If the probe is flatly touching the surface, the coupling is zero. The distance of the coupling maximum to the surface is independent of the surface reflectivity and largely independent of the surface to probe angle. The DASY5 software reads the reflection during a software approach and looks for the maximum using 2<sup>nd</sup> ord curve fitting. The approach is stopped at reaching the maximum.

Probe Specifications:	
Model:	ES3DV3,EX3DV4
Frequency Range:	10MHz — 6GHz(EX3DV4)
	10MHz — 4GHz(ES3DV3)
Calibration:	In head and body simulating tissue at frequency from 650MHz to 5900MHz
Linearity:	± 0.2 dB(30 MHz to 4 GHz) for ES3DV3 ± 0.2 dB(30 MHz to 6 GHz) for EX3DV4
Dynamic Range:	10 mW/kg — 100 W/kg
Probe Length:	330 mm
Probe Tip Length:	20 mm
Body Diameter:	12 mm
Tip Diameter:	2.5 mm (3.9 mm for ES3DV3)
Tip-Center:	1 mm (2.0mm for ES3DV3)
Application:	SAR Dosimetry Testing Compliance tests of mobile phones Dosimetry in strong gradient fields



Picture 7-2 Detail of Probe



Picture 7-3 E-field Probe

## 7.3. E-field Probe Calibration

Each E-Probe/Probe Amplifier combination has unique calibration parameters. A TEM cell calibration procedure is conducted to determine the proper amplifier settings to enter in the probe parameters. The amplifier settings are determined for a given frequency by subjecting the probe to a known E-field density (1 mW/cm<sup>2</sup>) using an RF Signal generator, TEM cell, and RF Power Meter.

The free space E-field from amplified probe outputs is determined in a test chamber. This calibration can be performed in a TEM cell if the frequency is below 1 GHz and inn a waveguide or other methodologies

above 1 GHz for free space. For the free space calibration, the probe is placed in the volumetric center of the cavity and at the proper orientation with the field. The probe is then rotated 360 degrees until the three channels show the maximum reading. The power density readings equates to 1 mW/cm<sup>2</sup>.

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate simulated brain tissue. The E-field in the medium correlates with the temperature rise in the dielectric medium. For temperature correlation calibration a RF transparent thermistor-based temperature probe is used in conjunction with the E-field probe.

$$SAR = C \frac{\Delta T}{\Delta t}$$

Where:

$\Delta t$  = Exposure time (30 seconds),

C = Heat capacity of tissue (brain or muscle),

$\Delta T$  = Temperature increase due to RF exposure.

$$SAR = \frac{|E|^2 \cdot \sigma}{\rho}$$

Where:

$\sigma$  = Simulated tissue conductivity,

$\rho$  = Tissue density (kg/m<sup>3</sup>).

## 7.4. Other Test Equipment

### 7.4.1. Data Acquisition Electronics (DAE)

The data acquisition electronics consist of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder with a control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information, as well as an optical uplink for commands and the clock.

The mechanical probe mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection.

The input impedance of the DAE is 200M Ohm; the inputs are symmetrical and floating. Common mode rejection is above 80dB.



**Picture 7-4: DAE**

### 7.4.2. Robot

The SPEAG DASY system uses the high precision robots (DASY5: TX90) type from Stäubli SA (France).

For the 6-axis controller system, the robot controller version from Stäubli is used. The Stäubli robot series have many features that are important for our application:

- High precision (repeatability 0.02mm)
- High reliability (industrial design)
- Low maintenance costs (virtually maintenance free due to direct drive gears; no belt drives)
- Jerk-free straight movements (brushless synchronal motors; no stepper motors)
- Low ELF interference (motor control fields shielded via the closed metallic construction shields)



**Picture 7-5: DASY 5**

### 7.4.3. Measurement Server

The Measurement server is based on a PC/104 CPU board with CPU (DASY5: 400 MHz, Intel Celeron), chip disk (DASY5: 128MB), RAM (DASY5: 128MB). The necessary circuits for communication with the DAE electronic box, as well as the 16 bit AD converter system for optical detection and digital I/O interface are contained on the DASY I/O board, which is directly connected to the PC/104 bus of the CPU board.



**Picture 7-6: Server for DASY 5**

The measurement server performs all real-time data evaluation of field measurements and surface detection, controls robot movements and handles safety operation. The PC operating system cannot interfere with these time critical processes. All connections are supervised by a watchdog, and disconnection of any of the cables to the measurement server will automatically disarm the robot and disable all program-controlled robot movements. Furthermore, the measurement server is equipped with an expansion port which is reserved for future applications. Please note that this expansion port does not have a standardized pinout, and therefore only devices provided by SPEAG can be connected. Devices from any other supplier could seriously damage the measurement server.

#### 7.4.4. Device Holder for Phantom

The SAR in the phantom is approximately inversely proportional to the square of the distance between the source and the liquid surface. For a source at 5mm distance, a positioning uncertainty of  $\pm 0.5\text{mm}$  would produce a SAR uncertainty of  $\pm 20\%$ . Accurate device positioning is therefore crucial for accurate and repeatable measurements. The positions in which the devices must be measured are defined by the standards.

The DASY device holder is designed to cope with the different positions given in the standard. It has two scales for device rotation (with respect to the body axis) and device inclination (with respect to the line between the ear reference points). The rotation centers for both scales is the ear reference point (ERP). Thus the device needs no repositioning when changing the angles.


The DASY device holder is constructed of low-loss POM material having the following dielectric parameters: relative permittivity  $\epsilon = 3$  and loss tangent  $\delta = 0.02$ . The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.



Picture 7-7: Device Holder

The extension is lightweight and made of POM, acrylic glass and foam. It fits easily on the upper part of the Mounting Device in place of the phone positioner. The extension is fully compatible with the Twin-SAM and ELI phantoms.

The DASY device holder is constructed of low-loss POM material having the following dielectric parameters: relative permittivity  $\epsilon = 3$  and loss tangent  $\delta = 0.02$ . The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.




Picture 7-8: Laptop Extension Kit

#### 7.4.5. Phantom

The SAM Twin Phantom V4.0 is constructed of a fiberglass shell integrated in a table. The shape of the shell is based on data from an anatomical study designed to represent the 90<sup>th</sup> percentile of the


population. The phantom enables the dissymmetric evaluation of SAR for both left and right handed handset usage, as well as body-worn usage using the flat phantom region. Reference markings on the Phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points in the robot. The shell phantom has a 2mm shell thickness (except the ear region where shell thickness increases to 6 mm).

Shell Thickness:	$2 \pm 0.2$ mm	 <p><b>Picture 7-9: SAM Twin Phantom</b></p>
Available:	Special	
Filling Volume:	Approx. 25 liters	
Dimensions:	810 x 1000 x 500 mm (H x L x W)	


## 8. Test Position in Relation to the Phantom

### 8.1. General considerations

This standard specifies two handset test positions against the head phantom – the “cheek” position and the “tilt” position.




Picture 8-1 Typical “fixed” case handset




Picture 8-2 Typical “clam-shell” case handset

$w_t$	Width of the handset at the level of the acoustic
$w_b$	Width of the bottom of the handset
A	Midpoint of the width $w_t$ of the handset at the level of the acoustic output
B	Midpoint of the width $w_b$ of the bottom of the handset




Picture 8-3 Cheek position of the wireless device on the left side of SAM



**Picture 8-4 Tilt position of the wireless device on the left side of SAM**

### 8.2. Body-worn device

A typical example of a body-worn device is a mobile phone, wireless enabled PDA (personal digital assistant) or other battery operated wireless device with the ability to transmit while mounted on a person’s body using a carry accessory approved by the wireless device manufacturer.



**Picture 8-5 Test positions for body-worn devices**


### 8.3. Desktop device

A typical example of a desktop device is a wireless enabled desktop computer placed on a table or desk when used.

The DUT shall be positioned at the distance and in the orientation to the phantom that corresponds to the intended use as specified by the manufacturer in the user instructions. For devices that employ an external antenna with variable positions.

Tests shall be performed for all antenna positions specified.

Picture 8-6 shows positions for desktop device SAR tests. If the intended use is not specified, the device shall be tested directly against the flat phantom.



**Picture 8-6 Test positions for desktop devices**



## 9. Tissue Simulating Liquids

### 9.1. Equivalent Tissues Composition

The liquid used for the frequency range of 650-6000 MHz consisted of water, sugar, salt, preventol, glycol monobutyl and Cellulose. The liquid has been previously proven to be suited for worst-case. The Table 9.1 shows the detail solution. It's satisfying the latest tissue dielectric parameters requirements proposed by the IEEE 1528 and IEC 62209.

**Table 9.1: Composition of the Head Tissue Equivalent Matter**

Frequency (MHz)	835	900	1800	1950	2300	2450	2600	5800
Ingredients (% by weight)								
Water	41.45	40.92	55.242	54.89	56.34	58.79	58.79	65.53
Sugar	56.0	56.5	/	/	/	/	/	
Salt	1.45	1.48	0.306	0.18	0.14	0.06	0.06	
Preventol	0.1	0.1	/	/	/	/	/	
Cellulose	1.0	1.0	/	/	/	/	/	
GlycolMonobutyl	/	/	44.452	44.93	43.52	41.15	41.15	
Diethylenglycol momohexylether	/	/	/	/	/	/	/	17.24
Triton X-100	/	/	/	/	/	/	/	17.23
Dielectric Parameters	$\epsilon=41.5$	$\epsilon=41.5$	$\epsilon=40.0$	$\epsilon=40.0$	$\epsilon=39.5$	$\epsilon=39.2$	$\epsilon=39.0$	$\epsilon=35.3$
Target Value	$\sigma=0.90$	$\sigma=0.97$	$\sigma=1.40$	$\sigma=1.40$	$\sigma=1.67$	$\sigma=1.80$	$\sigma=1.96$	$\sigma=5.27$

**Table 9.2: Targets for tissue simulating liquid**

Frequency(MHz)	Liquid Type	Conductivity( $\sigma$ )	$\pm 5\%$ Range	Permittivity( $\epsilon$ )	$\pm 5\%$ Range
835	Head	0.90	0.86~0.95	41.5	39.4~43.6
835	Body	0.97	0.92~1.02	55.2	52.4~58.0
1800	Head	1.40	1.33~1.47	40.0	38.0~42.0
1800	Body	1.52	1.44~1.60	53.3	50.6~56.0
1900	Head	1.40	1.33~1.47	40.0	38.0~42.0
1900	Body	1.52	1.44~1.60	53.3	50.6~56.0
2450	Head	1.80	1.71~1.89	39.2	37.2~41.2
2450	Body	1.95	1.85~2.05	52.7	50.1~55.3
2600	Head	1.96	1.86~2.06	39.0	37.1~40.9
2600	Body	2.16	2.05~2.27	52.5	59.9~55.1
5200	Head	4.66	4.43~4.89	36.0	34.2~37.8
5200	Body	5.30	5.04~5.57	49.0	46.6~51.5
5800	Head	5.27	5.01~5.53	35.3	33.5~37.1
5800	Body	6.00	5.70~6.30	48.2	45.8~50.6

Note: Effective February 19, 2019, FCC has permitted the use of single head-tissue simulating liquid specified in IEC 62209-1 for all SAR tests.

## 9.2. Dielectric Performance of TSL

**Table 9.3: Dielectric Performance of Head Tissue Simulating Liquid**

Tissue Simulating Liquid								
Frequency (MHz)	Body(Standard)		Temperature	Date	Test Result		Deviation (%)	
	Permittivity $\epsilon$	Conductivity $\sigma$			Permittivity $\epsilon$	Conductivity $\sigma$	Permittivity $\epsilon$	Conductivity $\sigma$
2000	53.30	1.52	22.6°C	2020/10/13	51.983	1.585	-2.47%	4.28%



## 10. System Validation

### 10.1. System Validation

Each DASY system is equipped with one or more system validation kits. These units, together with the predefined measurement procedures within the DASY software, enable the user to conduct the system performance check and system validation. System validation kit includes a dipole, tripod holder to fix it underneath the flat phantom and a corresponding distance holder.

### 10.2. System Setup

In the simplified setup for system evaluation, the DUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave that comes from a signal generator. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The equipment setup is shown below:



Picture 10-1 Setup for System Evaluation

Picture 10-2. Setup for Dipole

### 10.3. System Validation Result

Table 10.1: System Validation Result of SAR

SAR System Validation								
Frequency (MHz)	Average Target Value (w/kg)		Temperature	Date	Test Result (w/kg)		Deviation (%)	
	10g	1g			10g	1g	10g	1g
2000	20.6	40.2	22.6°C	2020/10/13	20.92	41.2	1.55%	2.49%

Note: The input power level is equivalent to 1w

## 11. Measurement Procedures

### 11.1. Test Steps

According to the SAR test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

#### (a) Power reference measurement

The reference and drift jobs are useful for monitoring the power drift of the device under test in the batch process. Both jobs measure the electric field strength at a specified reference position, at a selectable distance from the phantom surface. The reference position can be either the selected section's grid reference point or a user point in this section. The reference job projects the selected point onto the phantom surface, orients the probe perpendicularly to the surface, and approaches the surface using the selected detection method.

#### (b) Area scan

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a finer measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum locations even in relatively coarse grids. The scan area is defined by an editable grid. This grid is anchored at the grid reference point of the selected section in the phantom. When the area scan's property sheet is brought up, grid was at to 15mm \* 15mm and can be edited by users.

#### (c) Zoom scan

Zoom scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1g and 10g of simulated tissue. The default zoom scan measures 5 \* 5 \* 7 points within a cube whose base faces are centered around the maximum found in a preceding area scan job within the same procedure. If the preceding Area Scan job indicates more than one maximum, the number of Zoom Scans has to be enlarged accordingly.

#### (d) Power drift measurement

The drift job measures the field at the same location as the most recent reference job within the same procedure, and with the same setting. The drift measurement gives the field difference in dB from the reading conducted within the last reference measurement. Several drift measurements are possible for one reference measurement. This allows a user to monitor the power drift of the device under within a batch process. In the properties of the drift job, the user can specify a limit for the drift and have DASY software stop the measurements if this limit is exceeded. This ensures that the power drift during one measurement is within 5%.

The SAR measurement procedures for each of test conditions are as follows:

- (a) Make EUT to transmit it maximum output power
- (b) Measure conducted output power through RF cable
- (c) Place the EUT in the specific position of phantom
- (d) Measure SAR results for Middle channel or the highest power channel on each testing position
- (e) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg
- (f) Record the SAR value

## 11.2. Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the IEEE1529 standard. It can be conducted for 1g and 10g.

The DASY system allows evaluations that combine measured data and robot positions, such as:

### a) Maximum Search

During a maximum search, global and local maximum searches are automatically performed in 2D after each Area Scan measurement with at least 6 measurement points. It is based on the evaluation of the local SAR gradient calculated by the Quadratic Shepard's method. The algorithm will find the global maximum and all local maxima within -2dB of the global maxima for all SAR distributions.

### b) Extrapolation

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. Several measurements at different distances are necessary for the extrapolation. Extrapolation routines require at least 10 measurement points in 3D space. They are used in the Cube Scan to obtain SAR values between the lowest measurement points and the inner phantom surface. The routine uses the modified Quadratic Shepard's method for extrapolation. For a grid using 5\*5\*5 measurement points with 5mm resolution amounting to 343 measurement points, the uncertainty of the extrapolation routines is less than 1% for 1g and 10 cubes.

### c) Boundary effect

For measurements in the immediate vicinity of a phantom surface, the field coupling effects between the probe and the boundary influence the probe characteristics. Boundary effect errors of different dosi-metric probe types have been analyzed by measurements and using a numerical probe model. As expected, both methods showed an enhanced sensitivity in the immediate vicinity of the boundary. The effect strongly depends on the probe dimensions and disappears with increasing distance from the boundary. The sensitivity can be approximately given as:

$$S \approx S_0 + S_b * \exp\left(-\frac{z}{a}\right) * \cos\left(\pi \frac{z}{\lambda}\right)$$

Since the decay of the boundary effect dominates for small probe ( $a \ll \lambda$ ), the cos-term can be omitted. Factors  $S_b$  (parameter Alpha in the DASY software) and  $a$  (parameter Delta in the DASY software) are assessed during probe calibration and used for numerical compensation of the boundary effect. Several simulations and measurements have confirmed that the compensation is valid for different field and boundary configurations.

This simple compensation procedure can largely reduce the probe uncertainty near boundaries. It works well as long as:

- The boundary curvature is small
- The probe axis is angled less than 30° to the boundary normal
- The distance between probe and boundary is larger than 25% of the probe diameter
- The probe is symmetric (all sensors have the same offset from the probe tip)

Since all of these requirements are fulfilled in a DASY system, the correction of the probe boundary effect in the vicinity of the phantom surface is performed in a fully automated manner via the measurement data extraction during post processing.

### 11.3. General Measurement Procedure

The area and zoom scan resolutions specified in the table below must be applied to the SAR measurements and fully documented in SAR reports to qualify for TCB approval. Probe boundary effect error compensation is required for measurements with the probe tip closer than half a probe tip diameter to the phantom surface. Both the probe tip diameter and sensor offset distance must satisfy measurement protocols; to ensure probe boundary effect errors are minimized and the higher fields closest to the phantom surface can be correctly measured and extrapolated to the phantom surface for computing 1-g SAR. Tolerances of the post-processing algorithms must be verified by the test laboratory for the scan resolutions used in the SAR measurements, according to the reference distribution functions specified in IEEE Std 1528-2013. The results should be documented as part of the system validation records and may be requested to support test results when all the measurement parameters in the following table are not satisfied.

**Table 11.1: Test Resolution Requirement**

Items		≤3GHz	>3GHz
Maximum Distance		5mm ±1mm	$\frac{1}{2} * \delta * \ln(2)$ mm ±0.5mm
Maximum probe angle		30±1°	20±1°
Maximum Area Scan spatial resolution: $\Delta X_{Area}$ , $\Delta Y_{Area}$		≤2GHz: ≤15mm	3-4GHz: ≤12mm
		2-3GHz: ≤12mm	4-6GHz: ≤10mm
		when the x or y dimension of the device , in the measurement plane orientation, is smaller than the above, the measurement resolution must be ≤ the corresponding x or y dimension of the device with at least one measurement point on the device	
Maximum Zoom Scan spatial resolution: $\Delta X_{Zoom}$ , $\Delta Y_{Zoom}$		≤2GHz: ≤8mm	3-4GHz: ≤5mm
		2-3GHz: ≤5mm	4-6GHz: ≤4mm
maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta Z_{Zoom}(n)$	≤5mm	3-4GHz: ≤4mm 4-5GHz: ≤3mm 5-6GHz: ≤2mm
	graded grid $\Delta Z_{Zoom}(1)$ : between 1 <sup>st</sup> two points closest to phantom surface	≤4mm	3-4GHz: ≤3mm 4-5GHz: ≤2.5mm 5-6GHz: ≤2mm
	$\Delta Z_{Zoom}(n > 1)$ between subsequent points	≤1.5*	
minimum zoom scan volume	x, y, z	≥30mm	3-4GHz: ≥28mm 4-5GHz: ≥25mm 5-6GHz: ≥22mm
Notes: $\delta$ is the penetration depth of a plane-wave at normal incidence to the tissue medium in IEEE 1528-2013. When Zoom Scan is required and reported SAR from the Area Scan based 1-g SAR estimation procedure of KDB			

publication 447498 is  $\leq 1.4$  W/kg,  $\leq 8$ mm for 2GHz-3GHz,  $\leq 7$ mm for 3GHz-4GHz,  $\leq 5$ mm for 4GHz-6GHz Zoom Scan resolution may be applied.

#### 11.4. WCDMA Measurement Procedures

The following procedures are applicable to WCDMA handsets operating under 3GPP Release99, Release 5 and Release 6. The default test configuration is to measure SAR with an established radio link between the DUT and a communication test set using a 12.2kbps RMC (reference measurement channel) configured in Test Loop Mode 1. SAR is selectively confirmed for other physical channel configurations (DPCCH & DPDCHn), HSDPA and HSPA (HSUPA/HSDPA) modes according to output power, exposure conditions and device operating capabilities. Both uplink and downlink should be configured with the same RMC or AMR, when required. SAR for Release 5 HSDPA and Release 6 HSPA are measured using the applicable FRC (fixed reference channel) and E-DCH reference channel configurations. Maximum output power is verified according to applicable versions of 3GPP TS 34.121 and SAR must be measured according to these maximum output conditions. When Maximum Power Reduction (MPR) is not implemented according to Cubic Metric (CM) requirements for Release 6 HSPA, the following procedures do not apply.

**Table 11.2: HSDPA setting for Release 5**

Sub-test	$\beta_c$	$\beta_d$	$\beta_d$ (SF)	$\beta_c / \beta_d$	$\beta_{hs}$	CM (dB)	MPR (dB)
1	2/15	15/15	64	2/15	4/15	1.5	0.5
2	12/15	15/15	64	12/15	24/25	2.0	1
3	15/15	8/15	64	15/8	30/15	2.0	1
4	15/15	4/15	64	15/4	30/15	2.0	1

**Table 11.3: HSUPA setting for Release 6**

Sub-test	$\beta_c$	$\beta_d$	$\beta_d$ (SF)	$\beta_c / \beta_d$	$\beta_{hs}$	$\beta_{ec}$	$\beta_{ed}$	$\beta_{ed}$ (SF)	$\beta_{ed}$ (codes)	CM (dB)	MPR (dB)	AG Index	E-TFCl
1	11/15	15/15	64	11/15	22/15	209/225	1039/225	4	1	2.0	1.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	12/15	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	$\beta_{ed1}:47/15$ $\beta_{ed2}:47/15$	4	2	3.0	2.0	15	92
4	2/15	15/15	64	2/15	4/15	4/15	56/75	4	1	2.0	1.0	17	71
5	15/15	15/15	64	15/15	24/15	30/15	134/15	4	1	2.0	1.0	21	81

Note:

A KDB inquiry is required to address test and approval requirements when the maximum output power

measured in HS-DPCCH Sub-test 2 – 4 is higher than Sub-test 1.

A KDB inquiry is required to determine test and approval requirements when the maximum output power measured in E-DCH Sub-test 2 – 4 is higher than Sub-test 5.

### 11.5. LTE Measurement Procedure

SAR tests for LTE are performed with a base station simulator. Closed loop power control was used so the UE transmits with maximum output power during SAR testing.

1. Per KDB 941225 D05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.

2. 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.

3. For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are  $\leq 0.8$  W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is  $> 1.45$  W/kg, the remaining required test channels must also be tested.

4. 16QAM/64QAM output power for each RB allocation configuration is  $>$  not  $\frac{1}{2}$  dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is  $\leq 1.45$  W/kg; 16QAM/64QAM SAR testing is not required.

5. Smaller bandwidth output power for each RB allocation configuration is  $>$  not  $\frac{1}{2}$  dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is  $\leq 1.45$  W/kg; smaller bandwidth SAR testing is not required.

6. For LTE B12 / B26 the maximum bandwidth does not support three non-overlapping channels, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

7. LTE band 17 / 2 / 5 / 38 / 4 SAR test was covered by Band 12 / 25 / 26 / 41 / 66; according to TCB workshop, SAR test for overlapping LTE bands can be reduced if

a. The maximum output power, including tolerance, for the smaller band is  $\leq$  the larger band to qualify for the SAR test exclusion.

b. The channel bandwidth and other operating parameters for the smaller band are fully supported by the larger band.

#### LTE Carrier Aggregation Conducted Power (Downlink)

According to KDB941225 D05A v01r02, Uplink maximum output power measurement with downlink carrier aggregation active should be measured, using the highest output channel measured without downlink carrier aggregation, to confirm that uplink maximum output power with downlink carrier aggregation active remains within the specified tune-up tolerance limits and not more than  $\frac{1}{4}$  dB higher than the maximum output measured without downlink carrier aggregation active.

#### LTE TDD Considerations

According to KDB 941225 D05 SAR for LTE Devices, for Time-Division Duplex (TDD) systems, SAR must be tested using a fixed periodic duty factor according to the highest transmission duty factor implemented for the device and supported by the defined 3GPP LTE TDD configurations.



SAR was tested with the highest transmission duty factor (63.33%) using Uplink-downlink configuration 0 and Special sub-frame configuration 7.

LTE TDD Band 41 supports 3GPP TS 36.211 section 4.2 for Type 2 Frame Structure and Table 4.2-2 for uplink-downlink configurations and Table 4.2-1 for Special sub-frame configurations.

**Table 11.4 Calculated Duty Cycle for LTE TDD**

Uplink-Downlink Configuration		Sub-frame Number										Calculated
0	Periodicity	1	2	3	4	5	6	7	8	9	10	Duty Cycle (%)
0	5 ms	D	S	U	U	U	D	S	U	U	U	63.33
1	5 ms	D	S	U	U	D	D	S	U	U	D	43.33
2	5 ms	D	S	U	D	D	D	S	U	D	D	23.33
3	10 ms	D	S	U	U	U	D	D	D	D	D	31.67
4	10 ms	D	S	U	U	D	D	D	D	D	D	21.67
5	10 ms	D	S	U	D	D	D	D	D	D	D	11.67
6	5 ms	D	S	U	U	U	D	S	U	U	D	53.33

Example for Calculated Duty Cycle for Uplink-Downlink Configuration 0:

$$\text{Calculated Duty Cycle} = (5120 \times T_s \times 2 + 6 \text{ ms}) / 10\text{ms} = 63.33\%$$

Where

$$T_s = 1/(15000 \times 2048) \text{ seconds}$$

## 11.6. Bluetooth & WiFi Measurement Procedures

Normal network operating configurations are not suitable for measuring the SAR of 802.11 transmitters in general. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure that the results are consistent and reliable.

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in a test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters. The test frequencies should correspond to actual channel frequencies defined for domestic use. SAR for devices with switched diversity should be measured with only one antenna transmitting at a time during each SAR measurement, according to a fixed modulation and data rate. The same data pattern should be used for all measurements.

## 12. Simultaneous Transmission SAR Considerations

### 12.1. Reference Document

The following procedures adopted from “FCC SAR Considerations for Cell Phones with Multiple Transmitters” are applicable to handsets with built-in unlicensed transmitters such as 802.11 a/b/g and Bluetooth devices which may simultaneously transmit with the licensed transmitter.

### 12.2. SAR Measurement Positions

According to the KDB941225 D06 Hot Spot SAR v01, the edges with less than 2.5 cm distance to the antennas need to be tested for SAR.

**Table 12.1: SAR measurement Positions**

Antenna Mode	Front	Back	Left	Right	Top	Bottom
2/3/4G	Yes	Yes	Yes	Yes	No	Yes
BT/WiFi	Yes	Yes	No	Yes	Yes	No

### 12.3. Low Power Transmitters SAR Consideration

Standalone 1-g head or body SAR evaluation by measurement or numerical simulation for low power transmitters is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

The 1-g SAR test exclusion threshold for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$$\frac{(\text{max. power of channel, including tune-up tolerance, mW})}{(\text{min. test separation distance, mm})} * \sqrt{\text{Frequency (GHz)}} \leq 3.0$$

Where

- Frequency(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

According to the KDB447498 appendix A, the SAR test exclusion threshold for 2450MHz at 5mm test separation distances is 10mW. That means the transmitters with tune-up power below 10mW are excluded for SAR measurement.

### 12.4. Simultaneous Transmission Analysis

KDB 447498 D01 General RF Exposure Guidance introduces a new formula for calculating the SPLSR (SAR to Peak Location Ratio) between pairs of simultaneously transmitting antennas:

$$\text{SPLSR} = \sqrt{(SAR1 + SAR2)^3/R_i}$$

Where

- SAR1 is the highest measured or estimated SAR for the first of a pair of simultaneous transmitting antennas, in a specific test operating mode and exposure condition.

- SAR2 is the highest measured or estimated SAR for the second of a pair of simultaneous transmitting antennas, in the same test operating mode and exposure condition as the first.
- Ri is the separation distance between the pair of simultaneous transmitting antennas. When the SAR is measured, for both antennas in the pair, it is determined by the actual x, y and z coordinates in the 1-g SAR for each SAR peak location, based on the extrapolated and interpolated result in the zoom scan measurement, using the formula of

$$(x1 - x2)^2 + (y1 - y2)^2 + (z1 - z2)^2$$

In order for a pair of simultaneous transmitting antennas with the sum of 1-g SAR > 1.6 W/kg to qualify for exemption from Simultaneous Transmission SAR measurements, it has to satisfy the condition of:

$$\sqrt{(SAR1 + SAR2)^3/Ri} < 0.04$$

## 12.5. Simultaneous Transmission Table

**Table 12.2: Simultaneous Transmission Configurations**

Items	Capable Transmit Configurations
1	GSM/EGPRS/EDGE + BT
2	GSM/EGPRS/EDGE + WiFi
3	WCDMA + BT
4	WCDMA+ WiFi
5	LTE + BT
6	LTE + WiFi

Note: For the DUT, the WLAN and BT modules sharing a single antenna, and so these two modules can't transmit signal simultaneously. WCDMA and GSM modules sharing a single antenna, so these two modules can't transmit signal simultaneously.  
So we can get following combination that can transmit signal simultaneously.

## 13. Conducted Output Power

### 13.1. Manufacturing tolerance

**Table 13.1: GSM Speech**

GSM 850			
Channel	Channel 128	Channel 190	Channel 251
Maximum Target Value (dBm)	34.0	34.0	34.0
GSM1900			
Channel	Channel 512	Channel 661	Channel 810
Maximum Target Value (dBm)	31.5	31.5	31.5

**Table 13.2: GPRS (GMSK Modulation)**

GSM 850				
Channel		128	190	251
1 Txslots	Maximum Target Value (dBm)	34.0	34.0	34.0
2 Txslots	Maximum Target Value (dBm)	33.5	33.5	33.5
3 Txslots	Maximum Target Value (dBm)	31.5	31.5	31.5
4 Txslots	Maximum Target Value (dBm)	30.5	30.5	30.5
GSM 1900				
Channel		512	661	810
1 Txslots	Maximum Target Value (dBm)	31.5	31.5	31.5
2 Txslots	Maximum Target Value (dBm)	30.5	30.5	30.5
3 Txslots	Maximum Target Value (dBm)	29.0	29.0	29.0
4 Txslots	Maximum Target Value (dBm)	27.5	27.5	27.5

**Table 13.3: EGPRS (8-PSK Modulation)**

GSM 850				
Channel		128	190	251
1 Txslots	Maximum Target Value (dBm)	28.0	28.0	28.0
2 Txslots	Maximum Target Value (dBm)	27.0	27.0	27.0
3 Txslots	Maximum Target Value (dBm)	25.0	25.0	25.0
4 Txslots	Maximum Target Value (dBm)	24.0	24.0	24.0
GSM 1900				
Channel		512	661	810
1 Txslots	Maximum Target Value (dBm)	27.5	27.5	27.5
2 Txslots	Maximum Target Value (dBm)	26.5	26.5	26.5
3 Txslots	Maximum Target Value (dBm)	24.0	24.0	24.0
4 Txslots	Maximum Target Value (dBm)	23.5	23.5	23.5

**Table 13.4: WCDMA**

WCDMA Band II			
Channel	Channel 9262	Channel 9400	Channel 9538
Maximum Target Value (dBm)	24	24	24

WCDMA Band II HSDPA					MPR (dB)
Channel	9262	9400	9538		
1	Maximum Target Value (dBm)	23	23	23	0
2	Maximum Target Value (dBm)	23	23	23	1
3	Maximum Target Value (dBm)	23	23	23	1
4	Maximum Target Value (dBm)	23	23	23	1
WCDMA Band II HSUPA					MPR (dB)
Channel	9262	9400	9538		
1	Maximum Target Value (dBm)	22.5	22.5	22.5	1
2	Maximum Target Value (dBm)	22.5	22.5	22.5	0
3	Maximum Target Value (dBm)	22.5	22.5	22.5	1
4	Maximum Target Value (dBm)	22.5	22.5	22.5	1
5	Maximum Target Value (dBm)	22.5	22.5	22.5	1

**Table 13.5: WCDMA**

WCDMA Band IV			
Channel	1312	1413	1513
Maximum Target Value (dBm)	24	24	24

WCDMA Band IV HSDPA					MPR (dB)
Channel	1312	1413	1513		
1	Maximum Target Value (dBm)	23.5	23.5	23.5	1
2	Maximum Target Value (dBm)	23.5	23.5	23.5	1
3	Maximum Target Value (dBm)	23	23	23	1
4	Maximum Target Value (dBm)	23	23	23	1
WCDMA Band IV HSUPA					MPR (dB)
Channel	1312	1413	1513		
1	Maximum Target Value (dBm)	23	23	23	1
2	Maximum Target Value (dBm)	22	22	22	1
3	Maximum Target Value (dBm)	22	22	22	1
4	Maximum Target Value (dBm)	23	23	23	1
5	Maximum Target Value (dBm)	22.5	22.5	22.5	1

**Table 13.6: WCDMA**

WCDMA Band V			
Channel	4132	4183	4233
Maximum Target Value (dBm)	24.0	24.0	24.0

WCDMA Band V HSDPA					MPR (dB)
Channel	4132	4183	4233		
1	Maximum Target Value (dBm)	23	23	23	1
2	Maximum Target Value (dBm)	23	23	23	1
3	Maximum Target Value (dBm)	23	23	23	1
4	Maximum Target Value (dBm)	23	23	23	1
WCDMA Band V HSUPA					MPR (dB)
Channel	4132	4183	4233		
1	Maximum Target Value (dBm)	23	23	23	1
2	Maximum Target Value (dBm)	22	22	22	1
3	Maximum Target Value (dBm)	22	22	22	1
4	Maximum Target Value (dBm)	23	23	23	1
5	Maximum Target Value (dBm)	22.5	22.5	22.5	1



**Table 13.7: LTE**

LTE Band2			
RB Size	1	50%	100%
Maximum Target Value (dBm)	24	24	23.5
LTE Band4			
RB Size	1	50%	100%
Maximum Target Value (dBm)	23.5	23	22.5
LTE Band5			
RB Size	1	50%	100%
Maximum Target Value (dBm)	24.5	24	23.5
LTE Band7			
RB Size	1	50%	100%
Maximum Target Value (dBm)	23.5	23.0	22.5
LTE Band12			
RB Size	1	50%	100%
Maximum Target Value (dBm)	24	23.5	23
LTE Band13			
RB Size	1	50%	100%
Maximum Target Value (dBm)	23.5	23.0	22.5
LTE Band17			
RB Size	1	50%	100%
Maximum Target Value (dBm)	23.5	22.5	22.5
LTE Band25			
RB Size	1	50%	100%
Maximum Target Value (dBm)	24	23.5	23.5
LTE Band26			
RB Size	1	50%	100%
Maximum Target Value (dBm)	24.0	24.0	24.0

**Table 13.8: WiFi**

WiFi 802.11b 2.4G			
Channel	Channel 1	Channel 6	Channel 11
Maximum Target Value (dBm)	16.5	17.0	17.5
WiFi 802.11g 2.4G			
Channel	Channel 1	Channel 6	Channel 11
Maximum Target Value (dBm)	14.0	14.0	14.0
WiFi 802.11n 20M 2.4G			
Channel	Channel 1	Channel 6	Channel 11
Maximum Target Value (dBm)	14.0	14.0	14.0
WiFi 802.11n 40M 2.4G			
Channel	Channel 3	Channel 6	Channel 9
Maximum Target Value (dBm)	12.0	12.0	12.0

**Table 13.9: Bluetooth**

Bluetooth			
Channel	Channel 0	Channel 39	Channel 78
Maximum Target Value (dBm)	6.0	6.0	6.0

**Table 13.10: BLE**

Bluetooth			
Channel	Channel 0	Channel 19	Channel 39
Maximum Target Value (dBm)	2.5	2.5	2.5

**Table 13.11: CDMA**

Band	CDMA2000 BC0			CDMA2000 BC1		
	Channel	1013	384	777	25	600
Frequency (MHz)	824.7	836.52	848.31	1851.25	1880.00	1908.75
1xRTT RC1 SO55	25	25	25	24.5	24.5	24.5
1xRTT RC3 SO55	25	25	25	24.5	24.5	24.5
1xRTT RC3 SO32(+ F-SCH)	25	25	25	24.5	24.5	24.5
1xRTT RC3 SO32(+SCH)	25	25	25	24.5	24.5	24.5
1xEVDO RTAP 153.6Kbps	25	25	25	24.5	24.5	24.5
1xEVDO RETAP 4096Bits	24	24	24	24.5	24.5	24.5

### 13.2. GSM Measurement result

During the process of testing, the EUT was controlled via Agilent Digital Radio Communication tester (E5515C) to ensure the maximum power transmission and proper modulation. This result contains conducted output power for the EUT. In all cases, the measured peak output power should be greater and within 5% than EMI measurement.

**Table 13.12: The conducted power measurement results for GSM**

GSM 850MHZ	Conducted Power (dBm)		
	Channel 128(824.2MHz)	Channel 190(826.6MHz)	Channel 251(848.8MHz)
	33.66	33.73	33.78
GSM 1900MHZ	Conducted Power(dBm)		
	Channel 512(1850.2MHz)	Channel 661(1880 MHz)	Channel 810(1909.8MHz)
	31.04	31.15	31.02

**Table 11.13: The conducted power measurement results for GPRS/EGPRS**

GSM 850 GMSK	Measured Power (dBm)			calculation	Averaged Power (dBm)		
	128	190	251		128	190	251
1 Txslot	33.65	33.7	33.78	-9.03dB	24.62	24.67	24.75
2 Txslots	32.91	33.17	33.07	-6.02dB	26.89	27.15	27.05
3 Txslots	31.08	31.38	31.31	-4.26dB	26.82	27.12	27.05
4 Txslots	30.14	30.28	30.21	-3.01dB	27.13	27.27	27.2
GSM 1900 GMSK	Measured Power (dBm)			calculation	Averaged Power (dBm)		
	512	661	810		512	661	810
1 Txslot	31.04	31.15	31.02	-9.03dB	22.01	22.12	21.99
2 Txslots	30.22	30.15	29.71	-6.02dB	24.2	24.13	23.69
3 Txslots	28.37	28.18	27.74	-4.26dB	24.11	23.92	23.48
4 Txslots	27.23	27.02	26.56	-3.01dB	24.22	24.01	23.55

**Table 13.14: The conducted power measurement results for E-GPRS**

GSM 850 8-PSK	Measured Power (dBm)			calculation	Averaged Power (dBm)		
	128	190	251		128	190	251
1 Txslot	27.42	27.3	27.68	-9.03dB	18.39	18.27	18.65
2 Txslots	26.4	26.42	26.49	-6.02dB	20.38	20.4	20.47
3 Txslots	24.63	24.83	24.85	-4.26dB	20.37	20.57	20.59
4 Txslots	23.25	23.41	23.44	-3.01dB	20.24	20.4	20.43
GSM 1900 8-PSK	Measured Power (dBm)			calculation	Averaged Power (dBm)		
	512	661	810		512	661	810
1 Txslot	27.13	26.88	26.44	-9.03dB	18.1	17.85	17.41
2 Txslots	26.11	25.46	25.37	-6.02dB	20.09	19.44	19.35
3 Txslots	23.92	23.29	23.4	-4.26dB	19.66	19.03	19.14
4 Txslots	23.03	22.54	22.64	-3.01dB	20.02	19.53	19.63

NOTES:

#### 1) Division Factors

To average the power, the division factor is as follows:

1TX-slot = 1 transmit time slot out of 8 time slots=> conducted power divided by (8/1) => -9.03dB

2TX-slots = 2 transmit time slots out of 8 time slots=> conducted power divided by (8/2) => -6.02dB

3TX-slots = 3 transmit time slots out of 8 time slots=> conducted power divided by (8/3) => -4.26dB

4TX-slots = 4 transmit time slots out of 8 time slots=> conducted power divided by (8/4) => -3.01dB

**According to the conducted power as above, the body measurements are performed with 4Txslots for 850MHz ; 4Txslots for1900MHz;**

### 13.3. WCDMA Measurement result

Table 13.15: The conducted Power for WCDMA

Item	band	WCDMA BAND II result(dBm)		
	ARFCN	9262 (1852.4MHz)	9400 (1880.0MHz)	9538 (1907.6MHz)
WCDMA	\	23.38	23.4	23.42
HSDPA	1	22.66	22.67	22.78
	2	22.44	22.47	22.6
	3	22.11	22.17	22.31
	4	22.03	22.07	22.18
HSUPA	1	22.01	22.07	22.17
	2	21.06	21.01	21.21
	3	21.05	21.15	21.14
	4	21.86	21.85	22.05
	5	21.66	21.75	21.94
Item	band	WCDMA BAND V result(dBm)		
	ARFCN	Channel 4132 (826.4MHz)	Channel 4183 (836.6MHz)	Channel 4233 (846.6MHz)
WCDMA	\	23.71	23.59	23.24
HSDPA	1	22.96	22.85	22.52
	2	22.76	22.67	22.28
	3	22.49	22.36	22.03
	4	22.39	22.29	21.93
HSUPA	1	22.39	22.26	21.86
	2	21.36	21.27	20.87
	3	21.36	21.32	20.91
	4	22.29	22.09	21.79
	5	22	21.92	21.62
Item	band	WCDMA BAND IV result(dBm)		
	ARFCN	Channel 1312 (1712.4MHz)	Channel 1413 (1732.6MHz)	Channel 1513 (1752.6MHz)
WCDMA	\	23.7	23.6	23.94
HSDPA	1	22.98	22.87	23.2
	2	22.76	22.67	23.02
	3	22.43	22.37	22.73
	4	22.35	22.27	22.6
HSUPA	1	22.33	22.27	22.59
	2	21.38	21.21	21.63
	3	21.37	21.35	21.56
	4	22.18	22.05	22.47
	5	21.98	21.95	22.36

### 13.4. LTE Measurement result

**Table 13.16: The conducted Power for LTE BAND 2/4/5/7/12/13/17/25/26**

Band2						
Bandwidth	Mode	RB Size	RB Offset	Actual output power(dBm)		
				Channel 18625 1852.5MHz	Channel 18900 1880MHz	Channel 19175 1907.5MHz
5MHz	QPSK	1	0	22.81	22.71	22.55
		1	13	22.88	22.85	22.69
		1	24	22.75	22.70	22.55
		12	0	21.96	21.84	21.69
		12	6	21.99	21.89	21.74
		12	13	21.90	21.79	21.68
		25	0	21.98	21.87	21.72
	16QAM	1	0	21.98	21.94	21.82
		1	13	22.10	22.07	21.94
		1	24	21.98	21.93	21.77
		12	0	20.90	20.84	20.70
		12	6	20.93	20.86	20.75
		12	13	20.85	20.78	20.68
		25	0	20.91	20.80	20.69
Bandwidth	Mode	RB Size	RB Offset	Actual output power(dBm)		
				Channel 18650 1855MHz	Channel 18900 1880MHz	Channel 19150 1905MHz
10MHz	QPSK	1	0	22.95	22.87	22.72
		1	25	22.92	22.94	22.79
		1	49	22.84	22.80	22.66
		25	0	22.09	21.99	21.81
		25	13	22.05	21.93	21.81
		25	25	22.03	21.88	21.78
		50	0	22.06	21.96	21.84
	16QAM	1	0	22.05	22.00	21.89
		1	25	22.11	22.10	21.98
		1	49	22.00	21.96	21.90
		25	0	20.96	20.92	20.80
		25	13	20.89	20.86	20.72
		25	25	20.91	20.79	20.74
		50	0	20.95	20.86	20.76
Bandwidth	Mode	RB Size	RB Offset	Actual output power(dBm)		

				Channel 18675 1857.5MHz	Channel 18900 1880MHz	Channel 19125 1902.5MHz
15MHz	QPSK	1	0	22.95	22.90	22.72
		1	37	22.93	22.90	22.75
		1	74	22.77	22.76	22.65
		36	0	22.07	21.98	21.80
		36	19	22.01	21.94	21.79
		36	38	21.98	21.86	21.75
		75	0	22.06	21.96	21.82
	16QAM	1	0	22.09	22.07	21.94
		1	37	22.17	22.07	21.94
		1	74	21.98	21.96	21.86
		36	0	20.98	20.93	20.78
		36	19	20.94	20.87	20.77
		36	38	20.91	20.80	20.72
		75	0	20.96	20.86	20.75
Bandwidth	Mode	RB Size	RB Offset	Actual output power(dBm)		
				Channel 18700 1860MHz	Channel 18900 1880MHz	Channel 19100 1900MHz
20MHz	QPSK	1	0	22.93	22.88	22.75
		1	50	22.96	<b>22.98</b>	22.84
		1	99	22.70	22.66	22.59
		50	0	22.05	<b>22.10</b>	21.84
		50	25	22.02	21.98	21.85
		50	50	22.03	21.79	21.75
		100	0	22.02	21.96	21.79
	16QAM	1	0	22.10	22.09	21.99
		1	50	22.24	22.16	22.06
		1	99	21.94	21.92	21.86
		50	0	20.99	21.02	20.81
		50	25	20.95	20.92	20.79
		50	50	20.96	20.74	20.70
		100	0	20.96	20.88	20.77
Bandwidth	Mode	RB Size	RB Offset	Actual output power(dBm)		
				Channel 18615 1851.5MHz	Channel 18900 1880MHz	Channel 19185 1908.5MHz
3MHz	QPSK	1	0	22.92	22.81	22.66
		1	7	22.91	22.84	22.68
		1	14	22.87	22.83	22.66
		8	0	21.98	21.86	21.69

		8	4	21.98	21.87	21.72
		8	7	21.96	21.85	21.69
		15	0	21.97	21.83	21.70
	16QAM	1	0	22.02	22.02	21.89
		1	7	22.09	22.02	21.88
		1	14	22.04	22.00	21.85
		8	0	20.91	20.87	20.74
		8	4	20.97	20.88	20.78
		8	7	20.91	20.85	20.75
		15	0	20.88	20.82	20.70
Bandwidth	Mode	RB Size	RB Offset	Actual output power(dBm)		
				Channel 18607 1850.7MHz	Channel 18900 1880MHz	Channel 19193 1909.3MHz
1.4MHz	QPSK	1	0	22.87	22.79	22.61
		1	3	23.00	22.89	22.73
		1	5	22.86	22.80	22.62
		3	0	22.93	22.87	22.70
		3	1	23.01	22.92	22.76
		3	3	22.99	22.92	22.75
		6	0	21.99	21.89	21.72
	16QAM	1	0	21.99	21.99	21.86
		1	3	22.13	22.11	22.01
		1	5	22.03	22.01	21.84
		3	0	21.87	21.84	21.67
		3	1	21.95	21.88	21.74
		3	3	21.92	21.85	21.71
		6	0	20.96	20.92	20.78

Band4						
Bandwidth	Mode	RB Size	RB Offset	Actual output power(dBm)		
				Channel 19975 1712.5MHz	Channel 20175 1732.5MHz	Channel 20375 1752.5MHz
5MHz	QPSK	1	0	22.29	22.22	22.23
		1	13	22.35	22.31	22.32
		1	24	22.26	22.19	22.17
		12	0	21.39	21.31	21.29
		12	6	21.44	21.35	21.36
		12	13	21.35	21.28	21.30
		25	0	21.42	21.34	21.35
	16QAM	1	0	21.55	21.45	21.46



		1	13	21.57	21.54	21.51
		1	24	21.48	21.42	21.38
		12	0	20.36	20.32	20.27
		12	6	20.42	20.35	20.35
		12	13	20.36	20.27	20.29
		25	0	20.39	20.31	20.28
Bandwidth	Mode	RB Size	RB Offset	Actual output power(dBm)		
				Channel 20000 1715MHz	Channel 20175 1732.5MHz	Channel 20350 1750MHz
10MHz	QPSK	1	0	22.43	22.37	22.39
		1	25	22.49	22.47	22.45
		1	49	22.35	22.30	22.29
		25	0	21.48	21.44	21.40
		25	13	21.48	21.43	21.42
		25	25	21.49	21.38	21.45
	16QAM	50	0	21.47	21.44	21.46
		1	0	21.63	21.56	21.55
		1	25	21.65	21.62	21.62
		1	49	21.54	21.48	21.43
		25	0	20.38	20.37	20.32
		25	13	20.37	20.32	20.33
		25	25	20.38	20.30	20.34
		50	0	20.37	20.32	20.34
Bandwidth	Mode	RB Size	RB Offset	Actual output power(dBm)		
				Channel 20025 1717.5MHz	Channel 20175 1732.5MHz	Channel 20325 1747.5MHz
15MHz	QPSK	1	0	22.47	22.47	22.44
		1	38	22.50	22.46	22.47
		1	74	22.35	22.31	22.29
		36	0	21.50	21.54	21.48
		36	18	21.54	21.48	21.49
		36	39	21.51	21.43	21.48
		75	0	21.53	21.50	21.50
	16QAM	1	0	21.68	21.62	21.61
		1	38	21.70	21.65	21.64
		1	74	21.50	21.51	21.45
		36	0	20.45	20.48	20.41
		36	18	20.49	20.42	20.44
		36	39	20.43	20.37	20.40
		75	0	20.42	20.42	20.41
Bandwidth	Mode	RB Size	RB Offset	Actual output power(dBm)		

				Channel 20050 1720MHz	Channel 20175 1732.5MHz	Channel 20300 1745MHz
20MHz	QPSK	1	0	22.46	22.43	22.39
		1	50	22.55	<b>22.58</b>	22.50
		1	99	22.23	22.25	22.23
		50	0	21.50	<b>21.60</b>	21.55
		50	25	21.57	21.53	21.54
		50	50	21.45	21.45	21.51
		100	0	21.49	21.48	21.50
	16QAM	1	0	21.68	21.64	21.65
		1	50	21.81	21.75	21.76
		1	99	21.46	21.50	21.42
		50	0	20.46	20.54	20.46
		50	25	20.50	20.47	20.46
		50	50	20.40	20.39	20.45
		100	0	20.44	20.46	20.44
Bandwidth	Mode	RB Size	RB Offset	Actual output power(dBm)		
				Channel 19965 1711.5MHz	Channel 20175 1732.5MHz	Channel 20385 1753.5MHz
3MHz	QPSK	1	0	22.38	22.32	22.30
		1	8	22.35	22.29	22.29
		1	14	22.33	22.29	22.28
		8	0	21.41	21.32	21.31
		8	4	21.45	21.37	21.36
		8	7	21.41	21.30	21.29
		15	0	21.41	21.31	21.31
	16QAM	1	0	21.58	21.53	21.46
		1	8	21.55	21.52	21.47
		1	15	21.57	21.52	21.42
		8	0	20.44	20.34	20.32
		8	4	20.44	20.36	20.34
		8	7	20.42	20.35	20.32
		15	0	20.41	20.28	20.28
Bandwidth	Mode	RB Size	RB Offset	Actual output power(dBm)		
				Channel 19957 1710.7MHz	Channel 20175 1732.5MHz	Channel 20393 1754.3MHz
1.4MHz	QPSK	1	0	22.35	22.28	22.26
		1	2	22.48	22.41	22.41
		1	5	22.34	22.28	22.26
		3	0	22.43	22.36	22.37

		3	1	22.49	22.41	22.42
		3	2	22.47	22.42	22.39
		6	0	21.44	21.36	21.39
	16QAM	1	0	21.61	21.50	21.46
		1	2	21.72	21.64	21.58
		1	5	21.59	21.48	21.44
		3	0	21.41	21.34	21.32
		3	1	21.47	21.42	21.39
		3	2	21.47	21.41	21.34
		6	0	20.49	20.40	20.39

Band5						
Bandwidth	Mode	RB Size	RB Offset	Actual output power(dBm)		
				Channel 20425 826.5MHz	Channel 20525 836.5MHz	Channel 20625 846.5MHz
5MHz	QPSK	1	0	23.33	23.45	23.48
		1	12	23.50	23.62	23.65
		1	24	23.35	23.49	23.58
		12	0	22.42	22.60	22.75
		12	6	22.50	22.64	22.74
		12	13	22.49	22.58	22.69
		25	0	22.45	22.60	22.75
	16QAM	1	0	22.67	22.79	22.88
		1	12	22.83	22.96	23.08
		1	24	22.71	22.87	22.98
		12	0	21.44	21.62	21.77
		12	6	21.54	21.68	21.81
		12	13	21.49	21.61	21.73
		25	0	21.46	21.60	21.74
Bandwidth	Mode	RB Size	RB Offset	Actual output power(dBm)		
				Channel 20450 829MHz	Channel 20525 836.5MHz	Channel 20600 844MHz
10MHz	QPSK	1	0	23.40	23.52	23.62
		1	25	23.58	<b>23.67</b>	23.66
		1	49	23.50	23.54	23.66
		25	0	22.43	<b>22.69</b>	22.67
		25	13	22.55	22.64	22.67
		25	25	22.52	22.64	22.57
		50	0	22.50	22.68	22.64
	16QAM	1	0	22.77	22.87	22.99
		1	25	22.88	23.03	23.10
		1	49	22.84	22.95	23.09
		25	0	21.45	21.65	21.70
		25	13	21.52	21.62	21.71
		25	25	21.51	21.65	21.59
		50	0	21.49	21.64	21.68
Bandwidth	Mode	RB Size	RB Offset	Channel 20415	825.5MHz	Channel 20635 847.5MHz
				Channel 20415 825.5MHz	Channel 20525 836.5MHz	
3MHz	QPSK	1	0	23.45	23.56	23.59

		1	7	23.45	23.63	23.65
		1	14	23.47	23.60	23.67
		8	0	22.44	22.60	22.63
		8	4	22.53	22.67	22.69
		8	7	22.47	22.65	22.68
		15	0	22.43	22.60	22.64
	16QAM	1	0	22.75	22.82	22.96
		1	7	22.81	22.89	23.00
		1	14	22.77	22.93	23.03
		8	0	21.50	21.65	21.82
		8	4	21.58	21.74	21.88
		8	7	21.55	21.71	21.84
		15	0	21.43	21.62	21.79
Bandwidth	Mode	RB Size	RB Offset	Actual output power(dBm)		
				Channel 20407 824.7MHz	Channel 20525 836.5MHz	Channel 20643 848.3MHz
1.4MHz	QPSK	1	0	23.36	23.50	23.56
		1	2	23.47	23.61	23.60
		1	5	23.38	23.49	23.63
		3	0	23.41	23.55	23.67
		3	2	23.46	23.61	23.70
		3	3	23.45	23.58	23.71
		6	0	22.43	22.57	22.74
	16QAM	1	0	22.72	22.81	22.97
		1	2	22.84	22.95	23.12
		1	5	22.72	22.82	23.00
		3	0	22.50	22.62	22.80
		3	2	22.55	22.71	22.83
		3	3	22.52	22.66	22.87
		6	0	21.50	21.66	21.86

Band7						
Bandwidth	Mode	RB Size	RB Offset	Actual output power(dBm)		
				Channel 20775 2502.5MHz	Channel 21100 2535MHz	Channel 21425 2567.5MHz
5MHz	QPSK	1	0	22.41	22.55	22.63
		1	13	22.55	22.68	22.81
		1	24	22.45	22.58	22.68

		12	0	21.51	21.67	21.79
		12	6	21.59	21.74	21.86
		12	13	21.56	21.67	21.79
		25	0	21.58	21.73	21.84
	16QAM	1	0	21.56	21.70	21.84
		1	13	21.71	21.88	22.01
		1	24	21.61	21.74	21.87
		12	0	20.46	20.63	20.76
		12	6	20.55	20.67	20.82
		12	13	20.52	20.63	20.77
25	0	20.51	20.63	20.77		
Bandwidth	Mode	RB Size	RB Offset	Actual output power(dBm)		
				Channel 20800 2505MHz	Channel 21100 2535MHz	Channel 21400 2565MHz
10MHz	QPSK	1	0	22.48	22.62	22.73
		1	25	22.60	22.76	22.84
		1	49	22.58	22.69	22.78
		25	0	21.58	21.75	21.89
		25	13	21.64	21.75	21.85
		25	25	21.67	21.79	21.85
		50	0	21.65	21.79	21.88
	16QAM	1	0	21.63	21.77	21.90
		1	25	21.79	21.92	22.03
		1	49	21.72	21.87	21.96
		25	0	20.49	20.68	20.81
		25	13	20.54	20.66	20.76
		25	25	20.58	20.72	20.77
		50	0	20.55	20.71	20.80
Bandwidth	Mode	RB Size	RB Offset	Actual output power(dBm)		
				Channel 20825 2507.5MHz	Channel 21100 2535MHz	Channel 21375 2562.5MHz
15MHz	QPSK	1	0	22.49	22.62	22.73
		1	38	22.67	22.76	22.84
		1	74	22.63	22.75	22.81
		36	0	21.61	21.75	21.88
		36	18	21.68	21.77	21.91
		36	39	21.74	21.82	21.88
		75	0	21.68	21.82	21.92
	16QAM	1	0	21.61	21.73	21.88
		1	38	21.78	21.87	22.00
		1	74	21.75	21.85	21.96

Bandwidth	Mode	RB Size	RB Offset	Actual output power(dBm)		
				Channel 20850 2510MHz	Channel 21100 2535MHz	Channel 21350 2560MHz
20MHz	QPSK	36	0	20.50	20.67	20.79
		36	18	20.56	20.68	20.81
		36	39	20.64	20.73	20.79
		75	0	20.56	20.70	20.80
		1	0	22.44	22.54	22.69
		1	50	22.72	22.80	<b>22.93</b>
		1	99	22.59	22.74	22.80
	16QAM	50	0	21.63	21.78	21.91
		50	25	21.72	21.85	<b>21.94</b>
		50	50	21.76	21.84	21.89
		100	0	21.66	21.81	21.88
		1	0	21.60	21.73	21.89
		1	50	21.92	22.00	22.10
		1	99	21.79	21.92	21.99
	50	0	20.51	20.69	20.82	
	50	25	20.61	20.76	20.85	
	50	50	20.69	20.75	20.81	
	100	0	20.56	20.74	20.80	

Band12						
Bandwidth	Mode	RB Size	RB Offset	Actual output power(dBm)		
				Channel 23035 701.5MHz	Channel 23095 707.5MHz	Channel 23155 713.5MHz
5MHz	QPSK	1	0	22.97	22.90	22.85
		1	12	23.11	23.07	22.96
		1	24	22.94	22.95	22.83
		12	0	22.01	22.05	21.84
		12	6	22.13	22.08	21.99
		12	13	22.00	22.03	21.90
		25	0	22.02	22.04	21.91
	16QAM	1	0	22.27	22.19	22.16
		1	12	22.41	22.38	22.26
		1	24	22.21	22.22	22.09
		12	0	21.10	21.12	20.90
		12	6	21.19	21.15	21.07
		12	13	21.10	21.09	20.97

Bandwidth	Mode	RB Size	RB Offset	21.05	21.08	20.93
				Actual output power(dBm)		
				Channel 23060 704MHz	Channel 23095 707.5MHz	Channel 23130 711MHz
10MHz	QPSK	1	0	23.04	22.99	22.99
		1	25	23.14	<b>23.17</b>	23.11
		1	49	23.03	23.03	22.93
		25	0	22.06	<b>22.14</b>	22.03
		25	13	22.12	22.10	22.11
		25	25	22.08	22.12	22.12
		50	0	22.05	22.16	22.12
	16QAM	1	0	22.35	22.28	22.29
		1	25	22.43	22.45	22.38
		1	49	22.33	22.30	22.22
		25	0	21.08	21.16	21.07
		25	13	21.15	21.13	21.11
		25	25	21.07	21.21	21.17
		50	0	21.09	21.18	21.16
Bandwidth	Mode	RB Size	RB Offset	21.05	21.08	20.93
				Actual output power(dBm)		
				Channel 23025 700.5MHz	Channel 23095 707.5MHz	Channel 23165 714.5MHz
3MHz	QPSK	1	0	23.10	23.03	22.94
		1	7	23.12	23.08	22.99
		1	14	23.11	23.05	22.94
		8	0	22.10	22.06	21.95
		8	4	22.12	22.08	21.99
		8	7	22.15	22.06	21.96
		15	0	22.09	22.03	21.94
	16QAM	1	0	22.39	22.31	22.17
		1	7	22.40	22.36	22.22
		1	14	22.35	22.29	22.17
		8	0	21.23	21.17	21.03
		8	4	21.29	21.17	21.09
		8	7	21.27	21.14	21.02
		15	0	21.17	21.08	20.97
Bandwidth	Mode	RB Size	RB Offset	21.05	21.08	20.93
				Actual output power(dBm)		
				Channel 23017 699.7MHz	Channel 23095 707.5MHz	Channel 23173 715.3MHz
1.4MHz	QPSK	1	0	23.06	22.99	22.90
		1	2	23.16	23.11	22.98



		1	5	23.04	22.95	22.87
		3	0	22.35	22.25	22.13
		3	2	22.48	22.40	22.26
		3	3	22.35	22.23	22.14
		6	0	22.14	22.05	21.95
	16QAM	1	0	22.35	22.25	22.13
		1	2	22.48	22.40	22.26
		1	5	22.35	22.23	22.14
		3	0	22.16	22.09	21.94
		3	2	22.21	22.16	21.97
		3	3	22.17	22.13	21.98
		6	0	21.26	21.13	21.04

Band13						
Bandwidth	Mode	RB Size	RB Offset	Actual output power(dBm)		
				Channel 23205 779.5 MHz	Channel 23230 782 MHz	Channel 23255 784.5MHz
5MHz	QPSK	1	0	22.57	22.51	22.58
		1	12	22.64	22.68	22.71
		1	24	22.62	22.61	22.64
		12	0	21.62	21.64	21.65
		12	6	21.69	21.74	21.73
		12	13	21.70	21.77	21.69
		25	0	21.66	21.70	21.68
	16QAM	1	0	21.84	21.84	21.86
		1	12	21.91	21.98	21.95
		1	24	21.88	21.89	21.89
		12	0	20.69	20.67	20.70
		12	6	20.75	20.79	20.79
		12	13	20.76	20.81	20.74
		25	0	20.70	20.73	20.70
Bandwidth	Mode	RB Size	RB Offset	Actual output power(dBm)		
				Channel 23230 782MHz	Channel 23230 782 MHz	Channel 23230 782 MHz
10MHz	QPSK	1	0	22.64	22.65	22.64
		1	25	22.80	22.79	<b>22.80</b>
		1	49	22.75	22.74	22.73
		25	0	21.67	21.65	21.67
		25	13	21.77	21.77	21.78
		25	25	21.81	21.82	<b>21.84</b>

	16QAM	50	0	21.75	21.77	21.78
		1	0	21.93	21.90	21.93
		1	25	22.12	22.10	22.08
		1	49	22.01	22.00	22.01
		25	0	20.68	20.69	20.69
		25	13	20.80	20.78	20.79
		25	25	20.83	20.81	20.83
		50	0	20.79	20.79	20.77

Band17						
Bandwidth	Mode	RB Size	RB Offset	Actual output power(dBm)		
				Channel 23755 706.5 MHz	Channel 23790 710 MHz	Channel 23825 713.5MHz
5MHz	QPSK	1	0	23.02	22.96	22.91
		1	12	23.10	23.08	23.02
		1	24	23.02	22.99	22.94
		12	0	22.10	22.04	21.91
		12	6	22.14	22.12	22.06
		12	13	22.07	22.12	21.94
		25	0	22.12	22.12	21.97
	16QAM	1	0	22.30	22.22	22.18
		1	12	22.35	22.32	22.26
		1	24	22.25	22.21	22.16
		12	0	21.17	21.10	20.94
		12	6	21.19	21.18	21.09
		12	13	21.12	21.15	20.99
		25	0	21.14	21.14	20.99
Bandwidth	Mode	RB Size	RB Offset	Actual output power(dBm)		
				Channel 23780 709MHz	Channel 23790 710 MHz	Channel 23800 711 MHz
10MHz	QPSK	1	0	23.06	23.02	23.03
		1	25	23.16	<b>23.17</b>	23.12
		1	49	23.04	23.03	23.00
		25	0	22.18	22.15	22.10
		25	13	22.15	22.15	22.10
		25	25	22.28	<b>22.30</b>	22.22
		50	0	22.26	22.24	22.16
	16QAM	1	0	22.32	22.29	22.27
		1	25	22.44	22.42	22.36
		1	49	22.30	22.26	22.23

		25	0	21.20	21.16	21.10
		25	13	21.17	21.16	21.12
		25	25	21.30	21.30	21.23
		50	0	21.27	21.25	21.17

Band25						
Bandwidth	Mode	RB Size	RB Offset	Actual output power(dBm)		
				Channel 26065 1852.5MHz	Channel 26365 1882.5MHz	Channel 26665 1912.5MHz
5MHz	QPSK	1	0	22.89	22.77	22.69
		1	13	23.01	22.91	22.82
		1	24	22.86	22.77	22.66
		12	0	22.07	21.95	21.83
		12	6	22.09	21.99	21.86
		12	13	22.03	21.90	21.74
		25	0	22.07	21.97	21.84
	16QAM	1	0	22.06	22.04	21.94
		1	13	22.22	22.15	21.99
		1	24	22.08	22.02	21.80
		12	0	20.99	20.92	20.83
		12	6	21.03	20.96	20.85
		12	13	20.97	20.89	20.71
		25	0	21.00	20.92	20.80
Bandwidth	Mode	RB Size	RB Offset	Actual output power(dBm)		
				Channel 26090 1855MHz	Channel 26365 1882.5MHz	Channel 26640 1910MHz
10MHz	QPSK	1	0	22.99	22.87	22.74
		1	25	23.08	22.99	22.86
		1	49	22.90	22.78	22.69
		25	0	22.15	22.05	21.86
		25	13	22.14	22.02	21.85
		25	25	22.12	21.92	21.79
		50	0	22.16	22.03	21.85
	16QAM	1	0	22.11	22.08	21.95
		1	25	22.26	22.18	22.04
		1	49	22.13	22.01	21.83
		25	0	21.05	21.01	20.83
		25	13	21.03	20.93	20.80
		25	25	21.04	20.84	20.74

Bandwidth	Mode	RB Size	RB Offset	50	0	21.07	20.95	20.80	
				Actual output power(dBm)					
				Channel 26115 1857.5MHz	Channel 26365 1882.5MHz	Channel 26615 1907.5MHz			
15MHz	QPSK	1	0	23.05	22.96	22.82			
		1	38	23.05	22.96	22.85			
		1	74	22.89	22.82	22.73			
		36	0	22.16	22.11	21.92			
		36	18	22.13	22.06	21.86			
		36	39	22.13	21.95	21.82			
		75	0	22.16	22.06	21.90			
	16QAM	1	0	22.20	22.14	22.03			
		1	38	22.28	22.17	22.06			
		1	74	22.12	22.07	21.87			
		36	0	21.08	21.04	20.89			
		36	18	21.08	20.96	20.86			
		36	39	21.05	20.91	20.80			
		75	0	21.05	20.99	20.84			
Bandwidth	Mode	RB Size	RB Offset	50	0	21.07	20.95	20.80	
				Actual output power(dBm)					
				Channel 26140 1860MHz	Channel 26365 1882.5MHz	Channel 26590 1905MHz			
20MHz	QPSK	1	0	23.02	22.94	22.84			
		1	50	23.05	<b>23.13</b>	22.93			
		1	99	22.80	22.75	22.71			
		50	0	22.19	<b>22.21</b>	22.03			
		50	25	22.16	22.08	21.94			
		50	50	22.15	21.96	21.83			
		100	0	22.16	22.08	21.92			
	16QAM	1	0	22.22	22.18	22.02			
		1	50	22.39	22.28	22.13			
		1	99	22.05	22.04	21.84			
		50	0	21.10	21.14	20.97			
		50	25	21.10	21.01	20.90			
		50	50	21.09	20.94	20.81			
		100	0	21.08	21.02	20.87			
Bandwidth	Mode	RB Size	RB Offset	50	0	21.07	20.95	20.80	
				Actual output power(dBm)					
				Channel 26055 1851.5MHz	Channel 26365 1882.5MHz	Channel 26675 1913.5MHz			
3MHz	QPSK	1	0	23.01	22.90	22.81			
		1	8	23.00	22.89	22.83			

		1	14	23.00	22.90	22.78
		8	0	22.09	21.96	21.83
		8	4	22.11	22.01	21.86
		8	7	22.07	21.94	21.81
		15	0	22.06	21.97	21.84
	16QAM	1	0	22.14	22.09	22.00
		1	8	22.16	22.14	21.93
		1	15	22.16	22.13	21.88
		8	0	21.03	20.98	20.84
		8	4	21.05	20.99	20.86
		8	7	21.01	20.97	20.81
		15	0	20.99	20.93	20.79
		Bandwidth	Mode	RB Size	RB Offset	Actual output power(dBm)
Channel 26047 1850.7MHz	Channel 26365 1882.5MHz					Channel 26683 1914.3MHz
1.4MHz	QPSK	1	0	22.99	22.87	22.77
		1	2	23.11	23.03	22.90
		1	5	22.99	22.89	22.77
		3	0	22.09	21.96	21.83
		3	1	22.11	22.01	21.86
		3	2	22.07	21.94	21.81
		6	0	22.06	21.97	21.84
	16QAM	1	0	22.15	22.13	21.95
		1	2	22.32	22.29	22.08
		1	5	22.17	22.13	21.89
		3	0	21.13	20.92	20.83
		3	1	21.01	20.92	20.82
		3	2	21.03	20.92	20.80
		6	0	20.92	20.91	20.72

Band26						
Bandwidth	Mode	RB Size	RB Offset	Actual output power(dBm)		
				Channel 26715 816.5MHz	Channel 26865 831.5MHz	Channel 27015 846.5MHz
5MHz	QPSK	1	0	23.25	23.43	23.56
		1	13	23.43	23.65	23.71
		1	24	23.38	23.51	23.66
		12	0	22.36	22.56	22.82
		12	6	22.46	22.65	22.82
		12	13	22.40	22.61	22.75

	16QAM	25	0	22.43	22.61	22.85
		1	0	22.52	22.73	22.91
		1	13	22.74	22.93	23.09
		1	24	22.71	22.79	23.00
		12	0	21.42	21.59	21.90
		12	6	21.50	21.68	21.86
		12	13	21.44	21.65	21.82
		25	0	21.40	21.60	21.85
Bandwidth	Mode	RB Size	RB Offset	Actual output power(dBm)		
				Channel 26740 819MHz	Channel 26865 831.5MHz	Channel 26990 844MHz
10MHz	QPSK	1	0	23.33	23.52	23.63
		1	25	23.57	23.70	23.70
		1	49	23.53	23.60	23.69
		25	0	22.52	22.60	22.80
		25	13	22.51	22.66	22.82
		25	25	22.56	22.65	22.66
		50	0	22.56	22.64	22.76
	16QAM	1	0	22.60	22.87	23.08
		1	25	22.90	23.04	23.14
		1	49	22.89	23.00	23.10
		25	0	21.50	21.60	21.83
		25	13	21.52	21.64	21.83
		25	25	21.57	21.64	21.68
		50	0	21.56	21.62	21.76
Bandwidth	Mode	RB Size	RB Offset	Actual output power(dBm)		
				Channel 26765 821.5MHz	Channel 26865 831.5MHz	Channel 26965 841.5MHz
15MHz	QPSK	1	0	23.33	23.53	23.61
		1	38	23.67	23.77	<b>23.82</b>
		1	74	23.52	23.64	23.70
		36	0	22.51	22.56	<b>22.87</b>
		36	18	22.57	22.65	22.79
		36	39	22.63	22.66	22.70
		75	0	22.60	22.63	22.80
	16QAM	1	0	22.20	22.14	22.03
		1	38	22.28	22.17	22.06
		1	74	22.12	22.07	21.87
		36	0	21.08	21.04	20.89
		36	18	21.08	20.96	20.86
		36	39	21.05	20.91	20.80

Bandwidth	Mode	75	0	21.05	20.99	20.84
		RB Size	RB Offset	Actual output power(dBm)		
				Channel 26705 815.5MHz	Channel 26865 831.5MHz	Channel 27025 847.5MHz
3MHz	QPSK	1	0	23.35	23.61	23.66
		1	8	23.38	23.65	23.74
		1	14	23.40	23.62	23.75
		8	0	22.37	22.64	22.81
		8	4	22.44	22.70	22.85
		8	7	22.38	22.63	22.84
		15	0	22.38	22.65	22.83
	16QAM	1	0	22.61	22.91	22.99
		1	8	22.67	22.90	23.08
		1	15	22.71	22.91	23.09
		8	0	21.44	21.68	21.89
		8	4	21.47	21.75	21.96
		8	7	21.46	21.70	21.92
		15	0	21.37	21.66	21.84
Bandwidth	Mode	RB Size	RB Offset	Actual output power(dBm)		
				Channel 26697 814.7MHz	Channel 26865 831.5MHz	Channel 27033 848.3MHz
		1.4MHz	QPSK	1	0	23.31
1	2			23.42	23.71	23.82
1	5			23.34	23.57	23.72
3	0			22.37	22.64	22.81
3	1			22.44	22.70	22.85
3	2			22.38	22.63	22.84
6	0			22.40	22.64	22.87
16QAM	1		0	22.60	22.86	23.07
	1		2	22.75	23.03	23.23
	1		5	22.66	22.92	23.09
	3		0	22.39	22.65	22.88
	3		1	22.47	22.73	22.93
	3		2	22.43	22.71	22.95
	6		0	21.45	21.70	21.98

**Table 13.17: The conducted Power for LTE CA\_4C/7C**

LTE CA_4C									
PCC (UL)				SCC(DL)				Tune up	Total Tx Power
BW	Modulation	LCRB@RBstart	Channel	BW	Modulation	LCRB@RBstart	Channel		
20M	QPSK	1RB@0	20050	20M	QPSK	100RB@0	20248	23	22.67
20M	QPSK	1RB@50	20050	20M	QPSK	100RB@0	20248	23	22.72
20M	QPSK	1RB@99	20050	20M	QPSK	100RB@0	20248	23	22.53
20M	QPSK	1RB@0	20076	20M	QPSK	100RB@0	20274	23	22.53
20M	QPSK	1RB@50	20076	20M	QPSK	100RB@0	20274	23	22.88
20M	QPSK	1RB@99	20076	20M	QPSK	100RB@0	20274	23	22.70
20M	QPSK	1RB@0	20102	20M	QPSK	100RB@0	20300	23	22.65
20M	QPSK	1RB@50	20102	20M	QPSK	100RB@0	20300	23	22.9
20M	QPSK	1RB@99	20102	20M	QPSK	100RB@0	20300	23	22.67

LTE CA_7C									
PCC (UL)				SCC(DL)				Tune up	Total Tx Power
BW	Modulation	LCRB@RBstart	Channel	BW	Modulation	LCRB@RBstart	Channel		
20M	QPSK	1RB@0	20850	20M	QPSK	100RB@0	21048	23	22.47
20M	QPSK	1RB@50	20850	20M	QPSK	100RB@0	21048	23	22.67
20M	QPSK	1RB@99	20850	20M	QPSK	100RB@0	21048	23	22.33
20M	QPSK	1RB@0	21001	20M	QPSK	100RB@0	21199	23	22.41
20M	QPSK	1RB@50	21001	20M	QPSK	100RB@0	21199	23	22.63
20M	QPSK	1RB@99	21001	20M	QPSK	100RB@0	21199	23	22.31
20M	QPSK	1RB@0	21152	20M	QPSK	100RB@0	21350	23	22.37
20M	QPSK	1RB@50	21152	20M	QPSK	100RB@0	21350	23	22.76
20M	QPSK	1RB@99	21152	20M	QPSK	100RB@0	21350	23	22.36



### 13.5. WiFi and BT Measurement result

**Table 13.18: The conducted power for Bluetooth**

<b>GFSK</b>			
Channel	Ch0 (2402 MHz)	Ch39 (2441MHz)	CH78 (2480MHz)
Conducted Output Power (dBm)	3.5	3.1	3.7
<b><math>\pi/4</math> DQPSK</b>			
Channel	Ch0 (2402 MHz)	Ch39 (2441MHz)	CH78 (2480MHz)
Conducted Output Power (dBm)	2.7	2.4	2.9
<b>8DPSK</b>			
Channel	Ch0 (2402 MHz)	Ch39 (2441MHz)	CH78 (2480MHz)
Conducted Output Power (dBm)	2.6	2.4	3.0

**Table 13.19: The conducted power for BLE**

<b>GFSK</b>			
Channel	Ch0 (2402 MHz)	Ch19 (2440MHz)	CH39 (2480MHz)
Conducted Output Power (dBm)	0.92	0.45	-0.79

**NOTE:** According to KDB447498 D01 BT standalone SAR are not required, because maximum average output power is less than 10mW.

When the standalone SAR test exclusion is applied to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to the following to determine simultaneous transmission SAR test exclusion:

$(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm}) \cdot [\sqrt{f(\text{GHz})} / x]$   
 W/kg for test separation distances  $\leq 50$  mm;  
 where  $x = 7.5$  for 1-g SAR, and  $x = 18.75$  for 10-g SAR.

SAR head value of BT is 0.133 W/Kg. SAR body value of BT is 0.066 W/Kg for 1g.

SAR body value of BT is 0.053 W/Kg for 10g

**The default power measurement procedures are:**

a) Power must be measured at each transmit antenna port according to the DSSS and OFDM transmission configurations in each standalone and aggregated frequency band.


b) Power measurement is required for the transmission mode configuration with the highest maximum output power specified for production units.

1) When the same highest maximum output power specification applies to multiple transmission modes, the largest channel bandwidth configuration with the lowest order modulation and lowest data rate is measured.

2) When the same highest maximum output power is specified for multiple largest channel bandwidth configurations with the same lowest order modulation or lowest order modulation and lowest data rate, power measurement is required for all equivalent 802.11 configurations with the same maximum output power.

c) For each transmission mode configuration, power must be measured for the highest and lowest channels; and at the mid-band channel(s) when there are at least 3 channels. For configurations with multiple mid-band channels, due to an even number of channels, both channels should be measured.

During WLAN SAR testing EUT is configured with the WLAN continuous TX tool, and the transmission duty factor was monitored on the spectrum analyzer with zero-span setting, the duty cycle is 100%.



**Table 13.20: The average conducted power for WiFi**

Mode	Channel	Frequency	Average power(dBm)
802.11 b	1	2412 MHZ	16.37
	6	2437 MHZ	16.58
	11	2462 MHZ	17.14
802.11 g	1	2412 MHZ	12.81
	6	2437 MHZ	13.03
	11	2462 MHZ	13.70
802.11 n 20M	1	2412 MHZ	12,75
	6	2437 MHZ	12.96
	11	2462 MHZ	13.62
802.11 n 40M	3	2422 MHZ	11.44
	6	2437 MHZ	11.49
	9	2452 MHZ	11.67

#### **2.4 GHz 802.11g/n OFDM SAR Test Exclusion Requirements**

When SAR measurement is required for 2.4 GHz 802.11g/n OFDM configurations, the measurement and test reduction procedures for OFDM are applied. SAR is not required for the following 2.4 GHz OFDM conditions.

- a) When KDB Publication 447498 D01 SAR test exclusion applies to the OFDM configuration.
- b) When the highest *reported* SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is  $\leq 1.2$  W/kg.

### 13.6. CDMA Measurement result

**Table 13.21: The conducted Power for CDMA**

Band	CDMA2000 BC0			CDMA2000 BC1		
Channel	1013	384	777	25	600	1175
Frequency (MHz)	824.7	836.52	848.31	1851.25	1880.00	1908.75
1xRTT RC1 SO55	24.31	24.32	24.36	23.64	23.67	23.63
1xRTT RC3 SO55	24.35	24.35	24.39	23.62	23.69	23.67
1xRTT RC3 SO32(+ F-SCH)	24.28	24.31	24.32	23.57	23.53	23.54
1xRTT RC3 SO32(+SCH)	24.24	24.25	24.27	23.58	23.55	23.51
1xEVDO RTAP 153.6Kbps	24.51	24.55	24.51	23.79	23.81	23.78
1xEVDO RETAP 4096Bits	23.39	23.43	23.21	23.69	23.61	23.68

## 14.SAR Measurement Result

### 14.1. Standalone SAR Test Result for I19D00137-SAR01

Frequency		Configuration		Test Position	Spacing (mm)	Figure No.	Measured average power (dBm)	Maximum allowed Power (dBm)	Scaling factor	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Power Drift (dB)
MHz	Ch.											
836.6	190	GPRS 4TS	Class1 2	Toward Phantom	10	1	30.28	30.5	1.052	0.577	0.607	0.08
1909.8	810	GPRS 4TS	Class1 2	Toward Bottom	10	3	26.56	27.5	1.242	0.612	0.760	0.05
1880	940	Band II	12.2kpbs RMC	Toward Bottom	10	5	23.4	24	1.148	0.42	0.482	-0.03
1732.6	1413	Band IV	12.2kpbs RMC	Toward Phantom	10	7	23.6	24	1.096	0.438	0.480	0.11
836.6	4183	Band V	12.2kpbs RMC	Toward Phantom	10	9	23.59	24	1.099	0.267	0.293	0.04
1732.5	20175	QPSK_20MHz_1 RB_50 offset Middle		Toward Phantom	10	11	22.98	23.5	1.127	0.485	0.547	-0.00
836.5	20525	QPSK_10MHz_1 RB_25 offset Middle		Toward Phantom	10	13	23.67	24.5	1.211	0.25	0.303	0.03
2560	21350	QPSK_20MHz_1 RB_50 offset High		Toward Bottom	10	/	22.93	23.5	1.140	1.05	1.197	0.04
2510	20850	QPSK_20MHz_1 RB_50 offset Low		Toward Bottom	10	15	22.72	23.5	1.197	1.04	1.245	0.09
2535	21100	QPSK_20MHz_1 RB_50 offset Middle		Toward Bottom	10	/	22.80	23.5	1.175	0.918	1.079	0.02
2560	21350	QPSK_20MHz_1 00RB_0 offset High		Toward Bottom	10	/	22.93	23.5	1.140	1.01	1.152	-0.01

707.5	230 95	QPSK_10MHz_1 RB_ 25 offset Middle		Toward Ground	10	17	23.17	24	1.211	0.179	0.217	0.07
782	232 30	QPSK_10MHz_1 RB_ 25 offset Middle		Toward Ground	10	19	22.80	23.5	1.175	0.184	0.216	0.01
1882. 5	263 65	QPSK_20MHz_1 RB_ 50 offset Middle		Toward Bottom	10	21	23.17	24	1.211	0.595	0.720	0.13
841.5	269 65	QPSK_15MHz_1 RB_ 38 offset High		Toward Ground	10	23	23.82	24	1.042	0.215	0.224	0.03
836.5 2	384	CDMA BC0	1xEV-D O-0	Toward Phantom	10	25	24.55	25	1.109	0.353	0.392	0.08
1880	600	CDMA BC1	1xEV-D O-0	Toward Bottom	10	/	23.81	24.5	1.172	1.11	1.301	-0.01
1851. 25	25	CDMA BC1	1xEV-D O-0	Toward Bottom	10	/	23.79	24.5	1.178	0.964	1.135	0.03
1908. 75	1175	CDMA BC1	1xEV-D O-0	Toward Bottom	10	27	23.78	24.5	1.180	1.27	1.499	-0.02
2462	11	WiFi 2450	802.11 b	Toward Right	10	29	17.14	17.5	1.086	0.258	0.280	0.01
5530	106	WIFI 5G	802.11a c	Head Left	Cheek	33	14.57	15	1.104	0.338	0.373	0.08
5755	155	WIFI 5G	802.11a c	Toward Right	10	31	13.65	14	1.084	0.329	0.357	0.08
Repeated												
2560	213 50	QPSK_20MHz_1 RB_ 50 offset High		Toward Bottom	10	/	22.93	23.5	1.140	1.05	1.197	0.03
1908. 75	1175	CDMA BC1	1xEV-D O-0	Toward Bottom	10	/	23.78	24.5	1.180	1.2	1.416	0.02

Frequency		Configuration		Test Position	Spacing (mm)	Figure No.	Measured average power (dBm)	Maximum allowed Power (dBm)	Scaling factor	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Power Drift (dB)
MHz	Ch.											
836.6	190	GPRS 4TS	Class12	Toward Ground	0	2	30.28	30.5	1.052	1.76	1.851	-0.06
1880	661	GPRS 4TS	Class12	Toward Ground	0	4	27.02	27.5	1.117	0.821	0.917	0.05
1880	9400	Band II	12.2kbps RMC	Toward Ground	0	6	23.4	24	1.148	0.926	1.063	0.01
1732.6	1413	Band IV	12.2kbps RMC	Toward Ground	0	8	23.6	24	1.096	1.12	1.228	0.09
836.6	4175	Band V	12.2kbps RMC	Toward Ground	0	10	23.59	24	1.099	0.675	0.742	0.03
1732.5	20175	QPSK_20MHz_1R B_50 offset Middle		Toward Ground	0	12	22.58	23.5	1.236	1.08	1.335	0.01
836.5	20525	QPSK_10MHz_1R B_25 offset Middle		Toward Ground	0	14	23.67	24.5	1.211	0.605	0.732	-0.02
2560	21350	QPSK_20MHz_1R B_50 offset High		Toward Ground	0	16	22.93	23.5	1.140	0.82	0.935	0.08
707.5	23095	QPSK_10MHz_1R B_25 offset Middle		Toward Ground	0	18	23.17	24	1.211	0.4	0.484	0.02
782	23230	QPSK_10MHz_1R B_25 offset Middle		Toward Ground	0	20	22.80	23.5	1.175	0.459	0.539	-0.05
1882.5	26365	QPSK_20MHz_1R B_50 offset Middle		Toward Phantom	0	22	23.17	24	1.211	0.916	1.109	0.05
841.5	26965	QPSK_15MHz_36 RB_0 offset High		Toward Ground	0	24	22.87	24	1.297	0.583	0.756	0.01
836.52	384	CDMA BC0	1xEV-DO-0	Toward Ground	0	26	24.55	25	1.109	0.948	1.051	0.02
1880	600	CDMA BC1	1xEV-DO-0	Toward Phantom	0	28	23.81	24.5	1.172	1.7	1.993	0.05

2462	11	WiFi 2450	802.11b	Toward Ground	0	30	17.17	17.5	1.079	0.583	0.629	0.06
5530	106	WiFi 5G	802.11a c	Toward Ground	0	32	14.57	15	1.104	0.484	0.534	0.10

## 14.2. Standalone SAR Test Result for I20D00140-SAR01

Table 14.1: SAR Values CDMA BC1

Test Position	Cover Type	Mode	Channel	Frequency (MHz)	Measured power (dBm)	Tune-up (dBm)	Power Drift (dB)	Limit of 1gSAR 1.6 W/kg (mW/g)			Figure No.
								Measured SAR1g	Scaling Factor	Report SAR1g	
<b>Body SAR (HotSpot 10mm)N01</b>											
Bottom Side	Standard	1xEVDO-0	25	1851.25	23.79	24.5	0.040	0.982	1.18	1.156	/
Bottom Side	Standard	1xEVDO-0	600	1880	23.81	24.5	0.070	0.952	1.17	1.116	/
Bottom Side	Standard	1xEVDO-0	1175	1908.75	23.78	24.5	0.040	0.901	1.18	1.063	/
<b>Body SAR (HotSpot 10mm)Repeated</b>											
Bottom Side	Standard	1xEVDO-0	25	1851.25	23.79	24.5	0.110	1.020	1.18	1.201	/
<b>Body SAR (HotSpot 10mm)N02</b>											
Bottom Side	Standard	1xEVDO-0	25	1851.25	23.79	24.5	0.010	1.050	1.18	<b>1.236</b>	<b>1</b>
Bottom Side	Standard	1xEVDO-0	600	1880	23.81	24.5	0.060	1.020	1.17	1.196	/
Bottom Side	Standard	1xEVDO-0	1175	1908.75	23.78	24.5	0.040	1.010	1.18	1.192	/
<b>Body SAR (HotSpot 10mm)Repeated</b>											
Bottom Side	Standard	1xEVDO-0	25	1851.25	23.79	24.5	0.110	1.040	1.18	1.225	/



### 14.3. Simultaneous SAR Evaluation

**Table14.1 Simultaneous transmission SAR**

Standalone SAR for 2G(W/Kg)					
Test Position			GSM 850	GSM 1900	Highest SAR
Head	Left	Cheek	0.205	0.509	0.509
		Tilt 15°	0.136	0.141	0.141
	Right	Cheek	0.248	0.184	0.248
		Tilt 15°	0.151	0.093	0.151
Hotspot &Body- worn 10 mm	Phantom Side		0.607	0.563	0.607
	Ground Side		0.464	0.526	0.526
Hotspot 10 mm	Left Side		0.203	0.306	0.306
	Right Side		0.391	0.152	0.391
	Top Side		--	--	--
	Bottom Side		0.338	1.106	1.106
Limb	--		1.851	0.917	1.851

Standalone SAR for 3G(W/Kg)								
Test Position			WCDMA Band II	WCDMA Band IV	WCDMA Band V	BC0	BC1	Highest SAR
Head	Left	Cheek	0.313	0.454	0.165	0.244	0.398	0.454
		Tilt 15°	0.056	0.192	0.114	0.169	0.139	0.192
	Right	Cheek	0.133	0.261	0.210	0.278	0.412	0.412
		Tilt 15°	0.054	0.138	0.114	0.176	0.191	0.191
Hotspot &Body- worn 10 mm	Phantom Side		0.478	0.663	0.293	0.441	0.714	0.714
	Ground Side		0.361	0.454	0.170	0.378	0.715	0.715
Hotspot 10 mm	Left Side		0.217	0.418	0.087	0.243	0.291	0.418
	Right Side		0.104	0.220	0.188	0.441	0.141	0.441
	Top Side		--	--	--	--	--	--
	Bottom Side		0.526	0.371	0.135	0.297	1.499	1.499
Limb	--		1.063	1.261	0.742	1.187	1.993	1.993

Standalone SAR for 4G (W/Kg)										
Test Position		LTE	LTE Band	LTE Band7	LTE Band	LTE	LTE	LTE	Highest	
		Band 4	5		12	Band 13	Band 25	Band 26	SAR	
Head	Left	Cheek	0.801	0.167	0.029	0.165	0.188	0.507	0.151	0.801
		Tilt 15°	0.277	0.153	0.013	0.119	0.162	0.118	0.119	0.277
	Right	Cheek	0.509	0.226	0.025	0.156	0.216	0.213	0.189	0.509
		Tilt 15°	0.205	0.145	0.015	0.106	0.156	0.095	0.105	0.205
Hotspot &Body- worn 10 mm	Phantom Side		1.172	0.324	0.129	0.197	0.316	0.787	0.203	1.172
	Ground Side		0.854	0.318	0.311	0.225	0.324	0.757	0.207	0.854
Hotspot 10 mm	Left Side		0.599	0.157	0.022	0.161	0.172	0.298	0.118	0.599
	Right Side		0.363	0.269	0.012	0.179	0.314	0.136	0.166	0.363
	Top Side		--	--	--	--	--	--	--	
	Bottom Side		0.892	0.214	1.245	0.043	0.099	1.283	0.224	1.283
Limb	--		2.052	0.732	0.935	0.484	0.539	1.647	0.756	2.052

Simultaneous multi-band transmission										
Test Position			2G	3G	4G	2.4GHz		5GHz	SUM	
						BT	WiFi	WiFi	2.4GHz	5GHz
Head(1g)	Left	Cheek	0.509	0.454	0.801	0.133	0.357	0.747	1.158	1.548
		Tilt 15°	0.141	0.192	0.277	0.133	0.251	0.58	0.528	0.857
	Right	Cheek	0.248	0.412	0.509	0.133	0.155	0.737	0.664	1.246
		Tilt 15°	0.151	0.191	0.205	0.133	0.126	0.617	0.331	0.822
Hotspot &Body-worn 10 mm(1g)	Phantom Side		0.607	0.714	1.172	0.066	0.105	0.396	1.277	1.568
	Ground Side		0.526	0.715	0.854	0.066	0.340	0.737	1.194	1.591
Hotspot 10 mm(1g)	Left Side		0.306	0.418	0.599	0.066	0.007	--	0.606	0.599
	Right Side		0.391	0.441	0.363	0.066	0.491	0.762	0.932	1.203
	Top Side		--	--		0.066	0.141	0.491	0.141	0.491
	Bottom Side		1.106	1.499	1.283	0.066	--	--	1.565	1.499
Limb (10g)	--		1.851	1.993	2.052	0.027	0.964	0.901	3.016	2.953

According to the conducted power measurement result, we can draw the conclusion that: stand-alone SAR for WiFi should be performed. Then, simultaneous transmission SAR for WiFi/BT is considered with measurement results of GSM/WCDMA/LTE/CDMA and WiFi/BT. According to the above table, the sum of reported SAR values for GSM/WCDMA/LTE/CDMA and WiFi < 1.6W/kg. So the simultaneous transmission SAR is not required for WiFi/BT transmitter.

## 14.4. SAR Measurement Variability

SAR measurement variability must be assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media are required for SAR measurements in a frequency band, the variability measurement procedures should be applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium.

The following procedures are applied to determine if repeated measurements are required.

- 1) Repeated measurement is not required when the original highest measured SAR is  $< 0.80$  W/kg; steps 2) through 4) do not apply.
- 2) When the original highest measured SAR is  $\geq 0.80$  W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is  $> 1.20$  or when the original or repeated measurement is  $\geq 1.45$  W/kg ( $\sim 10\%$  from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is  $\geq 1.5$  W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is  $> 1.20$ .

**Table 14.5: SAR Measurement Variability (1g)**

Frequency		Configuration	Test Position	Original SAR (W/kg)	First Repeated SAR (W/kg)	The Ratio
MHz	Ch.					
1851.25	25	CDMA BC1 1xEV-DO-0	Bottom	0.982	1.02	1.04
1851.25	25	CDMA BC1 1xEV-DO-0	Bottom	1.05	1.04	1.01

**Note:** According to the KDB 865664 D01 repeated measurement is not required when the original highest measured SAR is  $< 0.8$  W/kg.

## 16. Test Equipment Utilized

Table 16.1 SAR Test System Equipment List

Item	Instrument Name	Type	Serial Number	Manufacturer	Cal. Date	Cal. interval
1	Network analyzer	N5242A	MY51221755	Agilent	2019-12-11	1 year
2	Power meter	NRVD	102257	RS	2020-5-10	1 year
3	Power sensor	NRV-Z5	100241			
			100644			
4	Signal Generator	E4438C	MY49072044	Agilent	2020-5-10	1 Year
5	Amplifier	NTWPA-0086010F	12023024	rflight	No Calibration Requested	
6	Coupler	778D	MY4825551	Agilent	2020-5-10	1 year
7	BTS	E5515C	MY50266468	Agilent	2019-12-11	1 year
		MT8820C	6201240338	Anritsu	2019-12-11	1 year
8	E-field Probe	EX3DV4	7401	SPEAG	2020-4-1	1 year
9	DAE	SPEAG DAE4	1581	SPEAG	2020-5-6	1 year
10	Dipole Validation Kit	SPEAG D2000V2	1051	SPEAG	2018-10-31	3 year

## 17.Measurement Uncertainty

**Table 17.1 Measurement Uncertainty Evaluation for SAR test**

Error Description	Uncert. Value	Prob. Dist.	Div.	(Ci)	(Ci)	Std. Unc.[%]	Std. Unc.[%]	(Ui) ueff
				1g	10g	(1g)	(10g)	
<b>Measurement System</b>								
Probe Calibration	13.3	N	2	1	1	6.65	6.65	∞
Axial Isotropy	4.7	R	$\sqrt{3}$	0.7	0.7	1.90	1.90	∞
Hemispherical Isotropy	9.6	R	$\sqrt{3}$	0.7	0.7	3.88	3.88	∞
Boundary effects	1	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Linearity	4.7	R	$\sqrt{3}$	1	1	2.70	2.70	∞
System Detection Limits	1	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Readout Electronics	0.7	N	1	1	1	0.70	0.70	∞
Response Time	0.8	R	$\sqrt{3}$	1	1	0.50	0.50	∞
Integration Time	2.6	R	$\sqrt{3}$	1	1	1.50	1.50	∞
RF Ambient Noise	3	R	$\sqrt{3}$	1	1	1.70	1.70	∞
RF Ambient Reflections	3	R	$\sqrt{3}$	1	1	1.70	1.70	∞
Probe Positioner	0.4	R	$\sqrt{3}$	1	1	0.20	0.20	∞
Probe Positioning	2.9	R	$\sqrt{3}$	1	1	1.70	1.70	∞
Post-processing	4	R	$\sqrt{3}$	1	1	2.30	2.30	∞
<b>Test Sample Related</b>								
Device Holder	2.55	N	1	1	1	2.55	2.55	71
Test sample Positioning	1.34	N	1	1	1	1.34	1.34	3
Power Drift	5	R	$\sqrt{3}$	1	1	2.9	2.9	∞
<b>Phantom and Setup</b>								
Phantom Uncertainty	4	R	$\sqrt{3}$	1	1	2.3	2.3	∞
Liquid Conductivity (target)	5	R	$\sqrt{3}$	0.64	0.43	2.9	2.9	∞
Liquid Conductivity (meas.)	5	N	1	0.64	0.43	5	5	∞
Liquid Permittivity (target)	5	R	$\sqrt{3}$	0.6	0.49	2.9	2.9	∞
Liquid Permittivity (meas.)	5	N	1	0.6	0.49	5	5	∞
Combined Std. Uncertainty	$U_c' = \sqrt{\sum_{i=1}^{23} C_i^2 U_i^2}$					11.23	10.70	
Expanded STD Uncertainty	$U_c = 2U_c'$					22.45	21.40	

**Table 17.2 Measurement Uncertainty Evaluation for System Validation**

Error Description	Uncert. Value	Prob. Dist.	Div.	(Ci)	(Ci)	Std. Unc. [%]	Std. Unc. [%]	(Ui) ueff	
				1g	10g	(1g)	(10g)		
<b>Measurement System</b>									
Probe Calibration	13.3	N	2	1	1	6.65	6.65	∞	
Axial Isotropy	4.7	R	$\sqrt{3}$	0.7	0.7	1.90	1.90	∞	
Hemispherical Isotropy	9.6	R	$\sqrt{3}$	0.7	0.7	3.88	3.88	∞	
Boundary effects	1	R	$\sqrt{3}$	1	1	0.58	0.58	∞	
Linearity	4.7	R	$\sqrt{3}$	1	1	2.70	2.70	∞	
System Detection Limits	1	R	$\sqrt{3}$	1	1	0.58	0.58	∞	
Readout Electronics	0.7	N	1	1	1	0.70	0.70	∞	
Response Time	0.8	R	$\sqrt{3}$	1	1	0.50	0.50	∞	
Integration Time	2.6	R	$\sqrt{3}$	1	1	1.50	1.50	∞	
RF Ambient Noise	3	R	$\sqrt{3}$	1	1	1.70	1.70	∞	
RF Ambient Reflections	3	R	$\sqrt{3}$	1	1	1.70	1.70	∞	
Probe Positioner	0.4	R	$\sqrt{3}$	1	1	0.20	0.20	∞	
Probe Positioning	2.9	R	$\sqrt{3}$	1	1	1.70	1.70	∞	
Post-processing	4	R	$\sqrt{3}$	1	1	2.30	2.30	∞	
<b>Test Sample Related</b>									
Validation Dipole Positioning	2	N	1	1	1	2	2		
Dipole Input Power	5	N	1	1	1	5	5		
Power Drift	5	R	$\sqrt{3}$	1	1	2.9	2.9	∞	
<b>Phantom and Setup</b>									
Phantom Uncertainty	4	R	$\sqrt{3}$	1	1	2.3	2.3	∞	
Liquid Conductivity (target)	5	R	$\sqrt{3}$	0.64	0.43	2.9	2.9	∞	
Liquid Conductivity (meas.)	5	N	1	0.64	0.43	5	5	∞	
Liquid Permittivity (target)	5	R	$\sqrt{3}$	0.6	0.49	2.9	2.9	∞	
Liquid Permittivity (meas.)	5	N	1	0.6	0.49	5	5	∞	
Combined Std. Uncertainty	$U_c = \sqrt{\sum_{i=1}^{23} C_i^2 U_i^2}$						12.11	11.63	
Expanded STD Uncertainty	$U_c = 2U_c'$						24.23	23.26	

\*\*\*END OF REPORT BODY\*\*\*

## ANNEX A. Graph Results

### Fig.1 CDMA BC1 1xEV-DO-0 Bottom Mode Low 10mm

Date/Time: 2020/10/13

Electronics: DAE4 Sn1581

Medium parameters used (interpolated):  $f = 1851.25$  MHz;  $\sigma = 1.527$  S/m;  $\epsilon_r = 54.77$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Ambient Temperature: 22.6°C      Liquid Temperature: 22.6°C

Communication System: CDMA 1900MHz 1900MHz; Frequency: 1851.25 MHz; Duty Cycle: 1:1

Probe: EX3DV4 - SN7401ConvF(8.11, 8.11, 8.11); Calibrated: 4/1/2020

#### CDMA BC1 1xEV-DO-0 Bottom Mode Low 10mm/Area Scan (41x71x1):

Measurement grid: dx=10 mm, dy=10 mm

Maximum value of SAR (Measurement) = 1.16 W/kg

#### CDMA BC1 1xEV-DO-0 Bottom Mode Low 10mm/Zoom Scan (7x7x7)/Cube 0:


Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 1.069 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 1.77 W/kg

SAR(1 g) = 1.05 W/kg; SAR(10 g) = 0.586 W/kg

Maximum value of SAR (measured) = 1.16 W/kg





## ANNEX B. System Validation Plot

### Body 2000MHz

Date/Time: 2020/10/13

Electronics: DAE4 Sn1581

Medium parameters used:  $f = 2000 \text{ MHz}$ ;  $\sigma = 1.585 \text{ S/m}$ ;  $\epsilon_r = 51.983$ ;  $\rho = 1000 \text{ kg/m}^3$

Ambient Temperature:  $22.6^\circ\text{C}$       Liquid Temperature:  $22.6^\circ\text{C}$

Communication System: CW 1900MHz;      Frequency: 2000 MHz; Duty Cycle: 1:1

Probe: EX3DV4 - SN7401ConvF(8.03, 8.03, 8.03); Calibrated: 4/1/2020

#### System check Validation 3 3 2/Area Scan (61x61x1):

Measurement grid:  $dx=10 \text{ mm}$ ,  $dy=10 \text{ mm}$

Maximum value of SAR (Measurement) =  $12.2 \text{ W/kg}$

#### System check Validation 3 3 2/Zoom Scan (7x7x7) (7x7x7)/Cube 0:


Measurement grid:  $dx=5\text{mm}$ ,  $dy=5\text{mm}$ ,  $dz=5\text{mm}$

Reference Value =  $74.66 \text{ V/m}$ ; Power Drift =  $0.09 \text{ dB}$

Peak SAR (extrapolated) =  $19.7 \text{ W/kg}$

SAR(1 g) =  $10.3 \text{ W/kg}$ ; SAR(10 g) =  $5.23 \text{ W/kg}$

Maximum value of SAR (measured) =  $11.7 \text{ W/kg}$



## ANNEX C. Calibration Certification



Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
 Tel: +86-10-62304633-2512 Fax: +86-10-62304633-2504  
 E-mail: cttl@chinattl.com [Http://www.chinattl.cn](http://www.chinattl.cn)



中国认可  
 国际互认  
 校准  
 CALIBRATION  
 CNAS L0570

 Client : **CTTL-SH**

 Certificate No: **Z20-60180**

### CALIBRATION CERTIFICATE

Object: **DAE4 - SN: 1581**

Calibration Procedure(s): **FF-Z11-002-01  
 Calibration Procedure for the Data Acquisition Electronics (DAEx)**

Calibration date: **May 06, 2020**

This calibration Certificate documents the traceability to national standards, which realize the physical units of measurements(SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature(22±3)°C and humidity<70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Process Calibrator 753	1971018	24-Jun-19 (CTTL, No.J19X05126)	Jun-20

	Name	Function	Signature
Calibrated by:	Yu Zongying	SAR Test Engineer	
Reviewed by:	Lin Hao	SAR Test Engineer	
Approved by:	Qi Dianyuan	SAR Project Leader	

Issued: May 08, 2020

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China  
Tel: +86-10-62304633-2512 Fax: +86-10-62304633-2504  
E-mail: cttl@chinattl.com Http://www.chinattl.cn

**Glossary:**

DAE data acquisition electronics  
Connector angle information used in DASY system to align probe sensor X to the robot coordinate system.

**Methods Applied and Interpretation of Parameters:**

- *DC Voltage Measurement:* Calibration Factor assessed for use in DASY system by comparison with a calibrated instrument traceable to national standards. The figure given corresponds to the full scale range of the voltmeter in the respective range.
- *Connector angle:* The angle of the connector is assessed measuring the angle mechanically by a tool inserted. Uncertainty is not required.
- The report provide only calibration results for DAE, it does not contain other performance test results.